

TECHNICAL DATA SHEET

Product Description

BRIGHTNER 1602 is a Polyethylene (PE) based Brightener masterbatch. It is specially designed for LDPE, LLDPE, HDPE and PP in Injection molding, Extrusion and Blow molding application, requiring excellent dispersion and optical properties.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically addition rates vary from 1% to 3% masterbatch.

Masterbatch Information

1. Product Code BRIGHTNER 1602
2. Colour Greenish Yellow
3. Carrier Polymer PE
4. Appearance Cylindrical Greenish Yellow Granules

Physical Properties:

Properties	Unit	Test Method	Specification
1. Light Fastness	--	--	NA
2. Heat Stability	°C	--	280°C
3. Moisture Content (Temp 120°C, 10Min.)	%	ASTM D6980	< 0.20
4. Bulk Density	Gm/cc	ASTM D1895	0.60 ± 0.1
5. Toxicity	--	--	NON-TOXIC
6. Dispersion	--	--	EXCELLENT
7. Active Content	%	--	1.3 ± 0.1

Regulatory

The product is food compliance as per European standard EU 10/2011. It passes heavy metal limits and hence complies with RoHS directive 2002/95/EC.

Packaging & Storage

BRIGHTNER 1602 is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place.

Recommended storage life is 1 year provided it is stored as directed.

Note: Above Report is made in identical condition. Values may be different when process on different machines and/or different processing condition, hence cannot be compare with any other same colour or product.

TECHNICAL SERVICES

Coraplast Industries

Survey No:180, Udvada Pariya Road, Village Dungri, Tal. Pardi, Dist. Valsad, Gujarat - 396185 India
T +91 98980 18180 E info@coraplast.com W coraplast.com