

TECHNICAL DATA SHEET

Product Description

Processing Aid 709 is a Polyethylene (PE) based Processing Aid masterbatch. It is specially designed for LDPE, LLDPE, HDPE and PP in Extrusion application, requiring excellent dispersion. It reduces die build up and eliminates melt fractures. It can reduce extruder torque and produce film of improved strength and quality.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically addition rates vary from 1% to 3% masterbatch.

Masterbatch Information

- | | |
|--------------------|------------------------------|
| 1. Product Code | Processing Aid 709 |
| 2. Colour | NATURAL |
| 3. Carrier Polymer | PE |
| 4. Appearance | Cylindrical Natural Granules |

Physical Properties:

Properties	Unit	Test Method	Specification
1. Light Fastness	--	--	NA
2. Heat Stability	°C	--	280°C
3. Moisture Content (Temp 120°C, 10Min.)	%	ASTM D6980	< 0.20
4. Bulk Density	Gm/cc	ASTM D1895	0.60 ± 0.1
5. Melt Flow Index at 190°C, 2.16 Kg	Gm/10 min	ASTM D1238	1 - 10
6. Specific Gravity	-	ASTM D792	0.90 ± 0.1
7. Typical Active Content	%		0.50
8. Toxicity	--	--	NON-TOXIC
9. Dispersion	--	--	EXCELLENT

Regulatory

The product is food compliance as per European standard EU 10/2011. It passes heavy metal limits and hence complies with RoHS directive 2002/95/EC.

Packaging & Storage

Processing Aid 709 is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place.

Recommended storage life is 1 year provided it is stored as directed.

Note: Above Report is made in identical condition, Values may be different when process on different machines and/or different processing condition, hence cannot be compare with any other same colour or product.

TECHNICAL SERVICES

Coraplast Industries

Survey No:180, Udvada Pariya Road, Village Dungri, Tal. Pardi, Dist. Valsad, Gujarat - 396185 India
T +91 98980 18180 E info@coraplast.com W coraplast.com