

## TECHNICAL DATA SHEET

### Product Description

SAB 1907 is a Polyethylene (PE) based Slip-Antiblock masterbatch. It is specially designed for LDPE, LLDPE, HDPE and PP in Extrusion application, requiring excellent dispersion and Slip-Antiblock properties.

### Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically addition rates vary from 2% to 4% masterbatch.

### Masterbatch Information

- |                    |                                |
|--------------------|--------------------------------|
| 1. Product Code    | SAB 1907                       |
| 2. Colour          | OFF-WHITE                      |
| 3. Carrier Polymer | PE                             |
| 4. Appearance      | Cylindrical Off-White Granules |

### Physical Properties:

| Properties                              | Unit      | Test Method | Specification |
|-----------------------------------------|-----------|-------------|---------------|
| 1. Light Fastness                       | --        | --          | NOT APLICABLE |
| 2. Heat Stability                       | °C        | --          | 280°C         |
| 3. Migration                            | --        | --          | NOT APLICABLE |
| 4. Moisture Content (Temp120°C, 10Min.) | %         | ASTM D6980  | < 0.20        |
| 5. Bulk Density                         | Gm/cc     | ASTM D1895  | 0.60 ± 0.1    |
| 6. Melt Flow Index at 190°C, 2.16 Kg    | Gm/10 min | ASTM D1238  | NO FLOW       |
| 7. Toxicity                             | --        | --          | NON-TOXIC     |
| 8. Dispersion                           | --        | --          | EXCELLENT     |
| 9. Active Content                       | %         | --          | 25 ± 1        |

### Regulatory

This product is food compliance as per EU AP 89(1).

### Packaging & Storage

Slip-Antiblock Masterbatch SAB 1907 is supplied in regular pellet form packed in 25 kg bags.

It should be stored in dry place.

Recommended storage life is 1 year provided it is stored as directed.

**Note:** Above Report is made in identical condition, Values may be different when process on different machines and/or different processing condition, hence cannot be compare with any other same colour or product.

**TECHNICAL SERVICES**

**Coraplast Industries**

Survey No:180, Udvada Pariya Road, Village Dungri, Tal. Pardi, Dist. Valsad, Gujarat - 396185 India  
**T** +91 98980 18180 **E** info@coraplast.com **W** coraplast.com