TECHNICAL DATA SHEET

Distributed by Blau Batch | Manufactured by Coraplast Industries

Product Description

SLIP 130 is a Polyethylene (PE) based Fast Slip masterbatch. It is specially designed for LDPE, LLDPE, HDPE and PP in Injection molding, Extrusion and Blow molding application, requiring excellent dispersion and slip properties.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically addition rates vary from 1% to 4% masterbatch.

Masterbatch Information

Parameter	Value
Product Code	SLIP 130
Colour	NATURAL
Carrier Polymer	PE
Appearance	Cylindrical Natural Granules

Physical Properties

Properties	Unit	Test Method	Specification
Light Fastness	--	--	NOT APPLICABLE
Heat Stability	°C	--	260°C
Moisture Content (Temp120°C, 10Min.)	%	ASTM D6980	< 0.20
Bulk Density	Gm/cc	ASTM D1895	0.60 ± 0.1
Melt Flow Index at 1900C, 2.16 Kg	Gm/10 min	ASTM D1238	10 ± 5
Specific Gravity	-	ASTM D792	0.91 ± 0.1
Toxicity	--	--	NON - TOXIC
Dispersion	--	--	EXCELLENT
Typical Active Content	%	ASTM E168	10
Pellet Count	No'S/1 Gm	--	50 - 70
Pellet Size	mm	--	2.5 - 3.5

Regulatory

The product is food compliance as per EU 10/2011.

Packaging & Storage

Slip Masterbatch SLIP 130 is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place. Recommended storage life is 1 year provided it is stored as directed.

Note: Above report is made in identical condition. Values may be different when processed on different machines and/or different processing conditions, hence cannot be compared with any other same colour or product.