

TECHNICAL DATA SHEET

Product Description

WHITE 71 FF is a Polyethylene (PE) based White Masterbatch. It is specially designed for LDPE, LLDPE, HDPE and PP in Injection molding, Extrusion and Blow molding application, requiring excellent dispersion and opacity.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application.

For Injection and Blow molding applications - Typical addition rates up to 8%

For Extrusion Film and sheet applications - Typical addition rates up to 20%

Masterbatch Information

1. Product Code WHITE 71 FF
2. Colour White
3. Carrier Polymer PE
4. Appearance Cylindrical White Granules

Physical Properties:

Properties	Unit	Test Method	Specification
1. Light Fastness	--	--	7 - 8
2. Heat Stability	°C	--	280°C
3. Moisture Content (Temp 120°C, 10Min.)	%	ASTM D6980	< 0.20
4. Bulk Density	Gm/cc	ASTM D1895	1.2 - 1.4
5. Melt Flow Index at 190°C, 2.16 Kg	Gm/10 min	ASTM D1238	15 - 25
6. Specific Gravity	-	ASTM D792	2.00 ± 0.1
7. Toxicity	--	--	NON-TOXIC
8. Dispersion	--	--	EXCELLENT
9. Titanium Dioxide (TiO ₂) Content	%	ASTM D5630	70 ± 2

Regulatory

The product is food compliance as per EU AP 89(1) and EU 10/2011.

Packaging & Storage

White Masterbatch WHITE 71 FF is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place.

Recommended storage life is 2 years provided it is stored as directed.

Note: Above Report is made in identical condition. Values may be different when process on different machines and/or different processing condition, hence cannot be compare with any other same colour or product.

TECHNICAL SERVICES

Coraplast Industries

Survey No:180, Udvada Pariya Road, Village Dungri, Tal. Pardi, Dist. Valsad, Gujarat - 396185 India
T +91 98980 18180 E info@coraplast.com W coraplast.com