

PATENT APPLICATION

INVENTOR(S)

[0001] KIMZEY, Samuel C

TITLE

[0002] Proof-of-Memory Flow Mechanism

TECHNICAL FIELD

[0003] The present invention relates to decentralized process orchestration and blockchain-based memory systems, and more particularly to theory-level methods for generating and weaving memory-flow signals from on-chain events.

BACKGROUND

[0004] Current decentralized systems often use token-based incentives or fixed schedules to coordinate processes. Such approaches overlook the intrinsic informational value in historical event logs. This invention harnesses on-chain memory events as a living substrate, where each proof contributes to an emergent flow-driven dynamic.

SUMMARY

[0005] The Proof-of-Memory Flow Mechanism encompasses:

1. Observation of atomic memory-pressure events across traditional blockchain nodes and PoM subchains.
2. Generation of cryptographic proofs for each observed event to ensure integrity.
3. Conversion of proofs into flow units and aggregation into a continuous memory-flow signal.

PATENT APPLICATION

4. Weaving of flow signals from multiple subchains to form pressure points that modulate system behavior.

DETAILED DESCRIPTION

[0006] Conceptually, each on-chain event—whether a block transaction or PoM subchain record—yields a proof. These proofs act as atomic impulses in a global memory field. As they accumulate, they shape a directional memory-flow signal. This signal is interpreted either directly or via local cognition layers to modulate reflex behavior. Interactions among multiple flow streams generate pressure points analogous to peaks in a physical medium, which can be interpreted by participants to coordinate emergent behaviors or achieve non-tokenized agreement.

METHOD FLOW

1. Event Observation – Collect on-chain events from blockchain nodes (PoS, PoA, PoW) and proof-of-memory subchains.
2. Proof Generation – For each event, create a cryptographic proof capturing event identity and context.
3. Flow Conversion – Map each proof to a flow unit; aggregate flow units over time into a continuous signal.
4. Pressure Weaving – Combine flow signals from multiple sources to identify pressure points where flow peaks occur.

NARRATIVE WORKED EXAMPLE

[0007] Imagine Domains X, Y, and Z each minting proofs. Over 30 seconds, Domain X mints at $t=0s$ and $t=10s$, Domain Y at $t=5s$, and Domain Z at $t=12s$. The clustered proofs between $t=5-12s$ form a peak in the flow signal, naturally defining a pressure point at $t \approx 10s$, prompting participants to initiate coordinated actions.

PATENT APPLICATION

ALGORITHMIC WORKED EXAMPLE

[0008] In an alternative embodiment, flow units F are computed via $F = w_p * 1 + w_r / \Delta t$, where $w_p=1.0$ and $w_r=0.5$.

For events at $t=0s$ ($F_0=1.0$) and $t=5s$ ($F_1=1.0 + 0.5/5 = 1.1$), a simple moving average B with window 2 yields $B_1=(1.0+1.1)/2=1.05$. Since $F_1 > B_1$, a pressure point is recorded at $t=5s$.

POTENTIAL EMBODIMENTS

[0009] Embodiments using moving averages, EMA, or percentile-based filters to illustrate controlled flow dynamics.

[00010] Embodiments where natural proof inter-arrival patterns alone yield observable pressure points.

[00011] Embodiments combining privacy-preserving proofs (e.g., ZKPs) with flow generation.

[00012] Embodiments leveraging hierarchical subchain layers to modulate flow per chain level.

IMPLEMENTATION NOTES

[00013] Proofs are recorded directly on-chain via one-action-one-mint transactions; no external scripts or endpoints are required. All proofs persist permanently, contributing to the memory-flow substrate. Flow interpretation may occur on-device, within VM-executed rule engines, or via pressure-triggered cognition layers.

CLAIMS

PATENT APPLICATION

1. A method for generating an emergent memory-flow signal from atomic memory-pressure events, the method comprising:
 - a. observing, by a processor, a plurality of on-chain events across at least one base chain and one memory-anchored subchain;
 - b. generating, by the processor, a cryptographic proof for each observed event;
 - c. converting, by the processor, each proof into one or more flow units and aggregating said units into a continuous signal;
 - d. weaving, by the processor, continuous flow signals from multiple sources to generate pressure points;
 - e. interpreting, by participants, the pressure points to coordinate emergent system behaviors.
2. The method of claim 1, wherein converting proofs and aggregating flow units occurs without reliance on token-based triggers.
3. The method of claim 1, wherein proofs are recorded via on-chain mint transactions following a one-action-one-mint paradigm.
4. The method of claim 1, further comprising applying privacy-preserving proofs to event attestations.
5. The method of claim 1, wherein pressure points arise from temporal clustering, absence of expected proofs, or divergence from established memory flow rhythms.
6. The method of claim 1, wherein continuous flow signals are interpreted locally by embedded systems or cognitive agents without reliance on global thresholds.
7. The method of claim 1, wherein flow dynamics are rendered as structured formats selected from the group consisting of:
 - a. narrative sequences,
 - b. temporal visualizations,
 - c. tabular signal logs, or
 - d. decision support prompts.
8. The method of claim 1, wherein flow signals persist permanently in a multi-layered memory mesh comprising at least one private and one public chain.

PATENT APPLICATION

ABSTRACT

[00014] A method for deriving cryptographic proofs from atomic memory-pressure events and converting those proofs into an intangible memory-flow signal that dynamically drives emergent system behaviors without reliance on token-based mechanisms.