

Clinic Computer and Local Network Manual

Simple installation, daily operation, backup, and recovery instructions

WHO THIS IS FOR	Clinic administrators and the person responsible for the main clinic computer
SYSTEM VERSION	1.0
SUPPORT NOTE	Keep this guide beside the clinic host computer or server records.

1. What this package does

One Windows computer becomes the clinic host. Staff, doctors, and authorized users open the system in a web browser using the host computer's local network address. Patient and clinic data stays on the clinic host unless the clinic creates an external backup.

STEP 1 Prepare	STEP 2 Install	STEP 3 Open	STEP 4 Back up
----------------	----------------	-------------	----------------

2. Before you begin

- A Windows 10 or Windows 11 computer that can remain switched on during clinic hours.
- At least 8 GB RAM, 20 GB free disk space, and a stable clinic router or Wi-Fi network.
- Docker Desktop installed and running on the host computer.
- The clinic computer's LAN address, such as 192.168.1.20.
- A strong administrator password stored privately by the clinic owner or manager.

3. First installation

1. **Extract the package.** Place the extracted folder in a permanent location such as C:\ClinicSystem. Do not run it from a USB drive
2. **Start Docker Desktop.** Wait until Docker Desktop reports that the engine is running
3. **Run guided installation.** Open deploy\local and double-click INSTALL-CLINIC.cmd. Enter the administrator name, email, phone, and a private password when requested
4. **Keep settings private.** Database and security secrets are generated automatically. Do not share the deploy\local\.env file
5. **Open the application.** On the host computer open <http://localhost:8080>. On another clinic device open the LAN address followed by :8080
6. **Sign in.** Use the administrator email and password entered in the .env file, then immediately store them in the clinic's secure password record

4. Normal daily operation

Start and stop

- Start Docker Desktop, then double-click START-CLINIC.cmd or OPEN-CLINIC.cmd.
- Check the system with: .\clinic.ps1 status.
- At the end of the day, double-click STOP-CLINIC.cmd before shutting down the host computer.

Role workflow

- Administrator/staff: manage departments, assign doctor accounts, register walk-ins, monitor queues, confirm admission, and view reports.
- Doctor: set availability, call the next patient, start consultation, record findings, and complete the visit.
- Patient: register, book an available appointment, mark arrival near the appointment time, follow queue updates, and view visit history.

5. Create a backup

1. **Keep the clinic system running.** Docker Desktop and the database must be available
2. **Run the backup command.** In PowerShell run: `.\clinic.ps1 backup`
3. **Copy the backup elsewhere.** Copy the new SQL file from the backups folder to an encrypted USB drive or other clinic-approved secure location
4. **Record the date.** Write the backup date in the clinic's backup register

6. Restore after a problem

1. **Protect the current files.** Do not delete the current system folder. Make an extra copy before restoring
2. **Choose the correct backup.** Use the newest known-good SQL backup
3. **Run restore.** Run: `.\clinic.ps1 restore -BackupFile C:\Path\To\hospital-queue-backup.sql`
4. **Verify.** Sign in and confirm that departments, users, appointments, queues, and reports are present

7. Update the system

- Create and copy a backup before every update.
- Replace the application files only with the approved new release package. Keep the existing `deploy\local\env` file.
- Run `.\clinic.ps1 update` and wait for the services to become healthy.
- Sign in and test one administrator page, one doctor page, and one patient page.

8. Troubleshooting

- Page does not open: confirm Docker Desktop is running and run `.\clinic.ps1 status`.
- Other devices cannot connect: confirm they are on the same network, use the correct LAN address, and allow port 8080 through Windows Firewall.
- Login fails: check the exact email, password, and Caps Lock. Do not edit database files manually.

- Service is unhealthy: run `.\clinic.ps1 stop`, restart Docker Desktop manually, then run `.\clinic.ps1 start`.
- Data appears missing: stop work and contact the technical maintainer before restoring or deleting anything.

9. Security and emergency rules

- Never send the `.env` file, database backup, or administrator password through ordinary chat or email.
- Do not expose port 8080 directly to the public internet.
- Keep Windows, Docker Desktop, and browsers updated.
- If the host computer is stolen or infected, disconnect it from the network and contact the clinic's technical maintainer.
- Keep at least one recent encrypted backup away from the clinic computer.