

Challenge-4

Phua Zong Yao

2023-09-04

Questions

Load the “CommQuest2023.csv” dataset using the `read_csv()` command and assign it to a variable named “comm_data.”

```
# Enter code here
```

```
library(tidyverse)
```

```
## — Attaching core tidyverse packages — tidyverse 2.0.0 —
## ✓ dplyr      1.1.2      ✓ readr      2.1.4
## ✓ forcats    1.0.0      ✓ stringr    1.5.0
## ✓ ggplot2    3.4.3      ✓ tibble     3.2.1
## ✓ lubridate  1.9.2      ✓ tidyr      1.3.0
## ✓ purrr      1.0.2
## — Conflicts — tidyverse_conflicts() —
## ✗ dplyr::filter() masks stats::filter()
## ✗ dplyr::lag()     masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to be
come errors
```

```
read_csv('CommQuest2023_Larger.csv')
```

```
## Rows: 1000 Columns: 5
## — Column specification —
## Delimiter: ","
## chr  (3): channel, sender, message
## dbl  (1): sentiment
## date (1): date
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

```
## # A tibble: 1,000 × 5
##   date      channel sender      message      sentiment
##   <date>    <chr>   <chr>    <chr>        <dbl>
## 1 2023-08-11 Twitter dave@example Fun weekend!    0.824
## 2 2023-08-11 Email   @bob_tweets Hello everyone! 0.662
## 3 2023-08-11 Slack   @frank_chat Hello everyone! -0.143
## 4 2023-08-18 Email   @frank_chat Fun weekend!    0.380
## 5 2023-08-14 Slack   @frank_chat Need assistance 0.188
## 6 2023-08-04 Email   @erin_tweets Need assistance -0.108
## 7 2023-08-10 Twitter @frank_chat Hello everyone! -0.741
## 8 2023-08-04 Slack   alice@example Hello everyone! -0.188
## 9 2023-08-20 Email   dave@example Team meeting    0.618
## 10 2023-08-09 Slack   @erin_tweets Hello everyone! -0.933
## # i 990 more rows
```

```
comm_data <- read_csv('CommQuest2023_Larger.csv')
```

```
## Rows: 1000 Columns: 5
## — Column specification —————
## Delimiter: ","
## chr   (3): channel, sender, message
## dbl   (1): sentiment
## date  (1): date
##
## i Use `spec()` to retrieve the full column specification for this data.
## i Specify the column types or set `show_col_types = FALSE` to quiet this message.
```

Question-1: Communication Chronicles

Using the select command, create a new dataframe containing only the “date,” “channel,” and “message” columns from the “comm_data” dataset.

Solution:

```
# Enter code here

select(comm_data,date,channel,message)
```

```
## # A tibble: 1,000 × 3
##   date      channel message
##   <date>    <chr>   <chr>
## 1 2023-08-11 Twitter Fun weekend!
## 2 2023-08-11 Email   Hello everyone!
## 3 2023-08-11 Slack   Hello everyone!
## 4 2023-08-18 Email   Fun weekend!
## 5 2023-08-14 Slack   Need assistance
## 6 2023-08-04 Email   Need assistance
## 7 2023-08-10 Twitter Hello everyone!
## 8 2023-08-04 Slack   Hello everyone!
## 9 2023-08-20 Email   Team meeting
## 10 2023-08-09 Slack   Hello everyone!
## # i 990 more rows
```

Question-2: Channel Selection

Use the filter command to create a new dataframe that includes messages sent through the “Twitter” channel on August 2nd.

Solution:

Enter code here

```
comm_data %>%
  filter(channel == 'Twitter', date == "2023-08-02")
```

```
## # A tibble: 15 × 5
##   date      channel sender      message      sentiment
##   <date>    <chr>   <chr>    <chr>        <dbl>
## 1 2023-08-02 Twitter alice@example Team meeting    0.210
## 2 2023-08-02 Twitter @erin_tweets Exciting news!  0.750
## 3 2023-08-02 Twitter dave@example Exciting news!  0.817
## 4 2023-08-02 Twitter @erin_tweets Exciting news!  0.582
## 5 2023-08-02 Twitter @erin_tweets Exciting news! -0.525
## 6 2023-08-02 Twitter alice@example Team meeting    0.965
## 7 2023-08-02 Twitter dave@example Great work!     0.516
## 8 2023-08-02 Twitter carol_slack Hello everyone! 0.451
## 9 2023-08-02 Twitter carol_slack Hello everyone! 0.174
## 10 2023-08-02 Twitter carol_slack Need assistance 0.216
## 11 2023-08-02 Twitter @frank_chat Need assistance -0.115
## 12 2023-08-02 Twitter alice@example Need assistance 0.158
## 13 2023-08-02 Twitter carol_slack Exciting news! -0.693
## 14 2023-08-02 Twitter @bob_tweets Need assistance -0.282
## 15 2023-08-02 Twitter @erin_tweets Need assistance 0.821
```

Question-3: Chronological Order

Utilizing the arrange command, arrange the “comm_data” dataframe in ascending order based on the “date” column.

Solution:

Enter code here

```
arrange(comm_data, date)
```

```
## # A tibble: 1,000 × 5
##   date      channel sender      message      sentiment
##   <date>    <chr>   <chr>    <chr>        <dbl>
## 1 2023-08-01 Twitter alice@example Need assistance 0.677
## 2 2023-08-01 Twitter @bob_tweets  Need assistance 0.148
## 3 2023-08-01 Twitter @frank_chat  Need assistance 0.599
## 4 2023-08-01 Twitter @frank_chat  Exciting news! -0.823
## 5 2023-08-01 Slack  @frank_chat  Team meeting  -0.202
## 6 2023-08-01 Slack  @bob_tweets  Exciting news! 0.146
## 7 2023-08-01 Slack  @erin_tweets Great work!    0.244
## 8 2023-08-01 Twitter @frank_chat  Team meeting  -0.526
## 9 2023-08-01 Twitter @frank_chat  Exciting news! -0.399
## 10 2023-08-01 Slack  @frank_chat  Need assistance 0.602
## # i 990 more rows
```

Question-4: Distinct Discovery

Apply the distinct command to find the unique senders in the “comm_data” dataframe.

Solution:

```
# Enter code here
```

```
distinct(comm_data,sender)
```

```
## # A tibble: 6 × 1
##   sender
##   <chr>
## 1 dave@example
## 2 @bob_tweets
## 3 @frank_chat
## 4 @erin_tweets
## 5 alice@example
## 6 carol_slack
```

Question-5: Sender Stats

Employ the count and group_by commands to generate a summary table that shows the count of messages sent by each sender in the “comm_data” dataframe.

Solution:

```
# Enter code here
```

```
comm_data %>%
  count(sender,message)
```

```
## # A tibble: 36 × 3
##   sender      message      n
##   <chr>      <chr>    <int>
## 1 @bob_tweets Exciting news!    30
## 2 @bob_tweets Fun weekend!    29
## 3 @bob_tweets Great work!    29
## 4 @bob_tweets Hello everyone! 29
## 5 @bob_tweets Need assistance 30
## 6 @bob_tweets Team meeting   32
## 7 @erin_tweets Exciting news! 27
## 8 @erin_tweets Fun weekend!    27
## 9 @erin_tweets Great work!    29
## 10 @erin_tweets Hello everyone! 27
## # i 26 more rows
```

Question-6: Channel Chatter Insights

Using the `group_by` and `count` commands, create a summary table that displays the count of messages sent through each communication channel in the “comm_data” dataframe.

Solution:

```
# Enter code here
```

```
comm_data %>%
  group_by(channel) %>%
  count()
```

```
## # A tibble: 3 × 2
## # Groups:   channel [3]
##   channel      n
##   <chr>    <int>
## 1 Email    331
## 2 Slack    320
## 3 Twitter  349
```

Question-7: Positive Pioneers

Utilize the `filter`, `select`, and `arrange` commands to identify the top three senders with the highest average positive sentiment scores. Display their usernames and corresponding sentiment averages.

Solution:

```
# Enter code here
```

```
comm_data %>%
  filter(sentiment>0) %>%
  group_by(sender) %>%
  summarise(average_psentiment=mean(sentiment)) %>%
  arrange(-average_psentiment) %>%
  slice(1:3) %>%
  select(sender,average_psentiment)
```

```
## # A tibble: 3 × 2
##   sender      average_psentiment
##   <chr>          <dbl>
## 1 dave@example    0.541
## 2 @frank_chat     0.528
## 3 alice@example   0.493
```

Question-8: Message Mood Over Time

With the `group_by`, `summarise`, and `arrange` commands, calculate the average sentiment score for each day in the “comm_data” dataframe.

Solution:

```
# Enter code here

comm_data %>%
  group_by(date) %>%
  summarise(mean_sentiment = mean(sentiment)) %>%
  arrange(date)
```

```
## # A tibble: 20 × 2
##   date      mean_sentiment
##   <date>          <dbl>
## 1 2023-08-01    -0.0616
## 2 2023-08-02     0.136
## 3 2023-08-03     0.107
## 4 2023-08-04    -0.0510
## 5 2023-08-05     0.193
## 6 2023-08-06    -0.0144
## 7 2023-08-07     0.0364
## 8 2023-08-08     0.0666
## 9 2023-08-09     0.0997
## 10 2023-08-10    -0.0254
## 11 2023-08-11    -0.0340
## 12 2023-08-12     0.0668
## 13 2023-08-13    -0.0604
## 14 2023-08-14    -0.0692
## 15 2023-08-15     0.0617
## 16 2023-08-16    -0.0220
## 17 2023-08-17    -0.0191
## 18 2023-08-18    -0.0760
## 19 2023-08-19     0.0551
## 20 2023-08-20     0.0608
```

Question-9: Selective Sentiments

Use the `filter` and `select` commands to extract messages with a negative sentiment score (less than 0) and create a new dataframe.

Solution:

```
# Enter code here
```

```
data_frame(comm_data %>%  
  filter(sentiment <= 0) %>%  
  select(sentiment))
```

```
## Warning: `data_frame()` was deprecated in tibble 1.1.0.  
## i Please use `tibble()` instead.  
## This warning is displayed once every 8 hours.  
## Call `lifecycle::last_lifecycle_warnings()` to see where this warning was  
## generated.
```

```
## # A tibble: 487 × 1  
##   sentiment  
##   <dbl>  
## 1    -0.143  
## 2    -0.108  
## 3    -0.741  
## 4    -0.188  
## 5    -0.933  
## 6    -0.879  
## 7    -0.752  
## 8    -0.787  
## 9    -0.539  
## 10   -0.142  
## # i 477 more rows
```

Question-10: Enhancing Engagement

Apply the mutate command to add a new column to the “comm_data” dataframe, representing a sentiment label: “Positive,” “Neutral,” or “Negative,” based on the sentiment score.

Solution:

```
# Enter code here
```

```
comm_data %>%  
  mutate(label = case_when(sentiment>0 ~ 'positive', sentiment==0 ~ 'neutral', sentiment<0 ~ 'negative'))
```

```
## # A tibble: 1,000 × 6
##   date      channel sender      message      sentiment label
##   <date>    <chr>  <chr>      <chr>      <dbl> <chr>
## 1 2023-08-11 Twitter dave@example Fun weekend!    0.824 positive
## 2 2023-08-11 Email  @bob_tweets Hello everyone! 0.662 positive
## 3 2023-08-11 Slack  @frank_chat Hello everyone! -0.143 negative
## 4 2023-08-18 Email  @frank_chat Fun weekend!    0.380 positive
## 5 2023-08-14 Slack  @frank_chat Need assistance 0.188 positive
## 6 2023-08-04 Email  @erin_tweets Need assistance -0.108 negative
## 7 2023-08-10 Twitter @frank_chat Hello everyone! -0.741 negative
## 8 2023-08-04 Slack  alice@example Hello everyone! -0.188 negative
## 9 2023-08-20 Email  dave@example Team meeting    0.618 positive
## 10 2023-08-09 Slack  @erin_tweets Hello everyone! -0.933 negative
## # i 990 more rows
```

Question-11: Message Impact

Create a new dataframe using the mutate and arrange commands that calculates the product of the sentiment score and the length of each message. Arrange the results in descending order.

Solution:

```
# Enter code here

data_new <- data_frame(comm_data %>%
  mutate(product=sentiment*nchar(message)) %>%
  arrange(desc(product)))

data_new
```

```
## # A tibble: 1,000 × 6
##   date      channel sender      message      sentiment product
##   <date>    <chr>  <chr>      <chr>      <dbl> <dbl>
## 1 2023-08-16 Email  @frank_chat Hello everyone!    0.998    15.0
## 2 2023-08-14 Slack  @erin_tweets Hello everyone!    0.988    14.8
## 3 2023-08-18 Email  dave@example Hello everyone!    0.978    14.7
## 4 2023-08-17 Email  dave@example Hello everyone!    0.977    14.7
## 5 2023-08-07 Slack  carol_slack Hello everyone!    0.973    14.6
## 6 2023-08-06 Slack  dave@example Hello everyone!    0.968    14.5
## 7 2023-08-08 Slack  @frank_chat Need assistance    0.964    14.5
## 8 2023-08-09 Email  @erin_tweets Need assistance    0.953    14.3
## 9 2023-08-17 Twitter @frank_chat Hello everyone!    0.952    14.3
## 10 2023-08-12 Email  carol_slack Need assistance    0.938    14.1
## # i 990 more rows
```

Question-12: Daily Message Challenge

Use the group_by, summarise, and arrange commands to find the day with the highest total number of characters sent across all messages in the “comm_data” dataframe.

Solution:

Enter code here

```
comm_data %>%
  group_by(date) %>%
  summarise(total_characters = sum(nchar(message))) %>%
  arrange(desc(total_characters))
```

```
## # A tibble: 20 × 2
##   date      total_characters
##   <date>          <int>
## 1 2023-08-10           875
## 2 2023-08-14           850
## 3 2023-08-07           790
## 4 2023-08-12           764
## 5 2023-08-18           743
## 6 2023-08-15           694
## 7 2023-08-13           680
## 8 2023-08-08           679
## 9 2023-08-20           669
## 10 2023-08-16           659
## 11 2023-08-06           643
## 12 2023-08-11           635
## 13 2023-08-01           597
## 14 2023-08-03           593
## 15 2023-08-19           593
## 16 2023-08-04           587
## 17 2023-08-05           584
## 18 2023-08-09           568
## 19 2023-08-17           561
## 20 2023-08-02           422
```

Question-13: Untidy data

Can you list at least two reasons why the dataset illustrated in slide 10 is non-tidy? How can it be made Tidy?

Solution:

In the percentage column, there is a combination of both percentages and population values. Also in the subject column, there are multiple variables included, which should not be the case as there should only be 1 variable in each column.

To make it Tidy, more columns should be created such as gender, employment status and age group should be created for the subject column. Also, avoid combining percentages and population values within the same column for the percentage column.