UNIT 4 · TOPIC 4.4

Endpoint Threat Auditing

Assignment

Instructions: 18 practice questions + 3 coding assignment(s), 33 points total. Show your work for short-answer items. Coding assignments may be completed here or in the interactive auto-graded environment on the course site (same problem, same points).

Name: **Date:** **Class:**

Practice Questions

4.4.a · Endpoint detection and response (EDR)

1. What distinguishes EDR from traditional antivirus software? (1 pt)

- ○ A. EDR only checks files against known signatures at rest
- ○ B. EDR monitors continuous runtime behavior and can respond by isolating or killing processes
- ○ C. EDR runs only at the network perimeter, not on individual devices
- ○ D. EDR requires internet access to query a cloud threat database

2. Which of the following are telemetry streams that an EDR agent typically collects? Select ALL that apply. (3 pts)

- □ A. Process creation and termination events
- □ B. File system changes (writes, renames, deletes)
- □ C. Physical room temperature from HVAC sensors
- □ D. Network connections opened by each process

(Select ALL that apply.)

3. An attacker uses PowerShell (a legitimate Windows tool) to download and run malware. Which EDR capability is MOST likely to catch this, and why? (1 pt)

- ○ A. Signature matching, because PowerShell is on the known-bad list
- ○ B. Endpoint isolation, because PowerShell always triggers isolation
- ○ C. File quarantine, because the PowerShell binary itself is quarantined
- ○ D. Behavioral detection, because the unusual parent-child process relationship and outbound connection deviate from the baseline

4. When an EDR platform 'isolates' an endpoint, what does that mean? (1 pt)

- ○ A. The device's hard drive is wiped immediately
- ○ B. All network connections are cut except the EDR management channel, stopping lateral movement
- ○ C. The user is logged out and their account is disabled permanently
- ○ D. The device is powered off remotely

5. Name the attacker technique where legitimate operating-system tools like PowerShell or WMI are misused to carry out malicious actions. (1 pt)

6. Why is it incorrect to assume a device is clean just because no EDR alert has fired? (1 pt)

- ○ A. EDR only scans files when they are first downloaded
- ○ B. EDR alerts are hidden from analysts until they are confirmed
- ○ C. EDR detection relies on signatures and baselines that may not cover every possible attack
- ○ D. EDR stops monitoring a device once it has been scanned clean

4.4.b · Log analysis

7. Why is a single failed login log entry usually NOT enough evidence of an attack? (1 pt)

- ○ A. Failed logins are only logged when the account is locked
- ○ B. Attackers never fail more than once because they use stolen passwords
- ○ C. A single failure is ordinary human error; attacks are recognized through correlated patterns across multiple entries
- ○ D. Single entries are compressed and cannot be read until more arrive

8. What does 'correlation' mean in the context of log analysis? (1 pt)

- ○ A. Comparing a log entry to a list of known-bad IP addresses
- ○ B. Linking multiple log entries together (by user, IP, or time) to reveal a pattern invisible in any single entry
- ○ C. Calculating the average number of log entries per hour
- ○ D. Sorting log entries by severity so the worst appear first

9. Select ALL statements that are TRUE about SIEM platforms. (3 pts)

- □ A. They ingest logs from many systems across an organization
- □ B. They apply correlation rules automatically at scale to raise alerts
- □ C. They eliminate the need for any human security analyst
- □ D. They can generate false positives if detection thresholds are set too sensitively

(Select ALL that apply.)

10. An authentication log shows 6 failed logins for the same user within 45 seconds, followed immediately by a success from the same IP. What does this pattern most likely indicate? (1 pt)

- ○ A. The user simply forgot their password and does not need investigation
- ○ B. A brute-force attack that guessed the password after repeated attempts
- ○ C. A hardware failure on the authentication server
- ○ D. Normal end-of-day login behavior

11. Name the phenomenon where overly sensitive detection thresholds cause so many false alarms that analysts start ignoring alerts, potentially missing real attacks. (1 pt)

12. Why are logs valuable even after an attacker has already left a compromised system? (1 pt)

- ○ A. Logs let the team reverse the attacker's changes automatically
- ○ B. Logs are the record used for forensic reconstruction of what the attacker did
- ○ C. Logs prove the attacker's identity in court on their own
- ○ D. Logs show which antivirus product failed

4.4.c · Identifying compromised devices (indicators of compromise)

13. What is an indicator of compromise (IOC)? (1 pt)

- ○ A. Any alert raised by antivirus software
- ○ B. A known vulnerability on a device that has not been patched
- ○ C. Forensic evidence (a file, connection, account, or behavior) suggesting a device has been breached
- ○ D. A list of the attacker's names and locations

14. Why is a single IOC usually not enough to confidently declare a device compromised? (1 pt)

- ○ A. IOCs expire after 24 hours and must be re-collected
- ○ B. Attackers always leave at least three IOCs, so one means a false alarm
- ○ C. IOCs only count once they appear in a threat-intelligence feed
- ○ D. A single artifact often has an innocent explanation; confident verdicts come from combining multiple independent IOCs

15. Select ALL examples of host-based indicators of compromise. (Choose all that apply.) (3 pts)

- □ A. A new administrator account nobody remembers creating
- □ B. A registry run-key added for persistence
- □ C. Antivirus/EDR protection silently disabled
- □ D. A DNS lookup for an algorithmically generated domain name

(Select ALL that apply.)

16. Using weight table: disabled AV = 5, new admin account = 4, thresholds clean<4, suspicious 4-7, compromised>=8. A device shows BOTH IOCs. What is the verdict? (1 pt)

- ○ A. Clean, because neither IOC alone reaches 8
- ○ B. Suspicious, because two IOCs together should never be scored as fully compromised
- ○ C. Cannot be determined without more information
- ○ D. Compromised, because the combined score (9) is at or above the compromised threshold

17. Name the attacker technique of maintaining access to a compromised system even after the initial foothold is discovered or the system is rebooted. (1 pt)

18. How does an indicator of attack (IOA) differ from an indicator of compromise (IOC)? (1 pt)

- ○ A. IOAs come from antivirus, while IOCs come from firewalls
- ○ B. IOAs are used only by governments, while IOCs are used by companies
- ○ C. An IOA focuses on catching attacker technique/intent while an attack is in progress; an IOC is typically after-the-fact evidence
- ○ D. IOAs describe vulnerabilities, while IOCs describe patches

Coding Assignments (Python 3)

4.4.a · Endpoint detection and response (EDR)

3 pts · auto-graded on the site

Coding problem 4.4.a: EDR telemetry analyzer

Skill: Detect Attacks · **Maps to:** 4.4.A · **Language:** Python 3 (pytest)

Problem

An EDR agent streams process-event telemetry from an endpoint. Each event records a process, its parent process, whether it opened an external network connection, and how many bytes it transferred. Build the analyzer that flags processes exhibiting either of the two classic red flags an EDR platform's behavioral detection looks for: a "living off the land" parent-child relationship, or unusual outbound data transfer.

Function contract

Implement `def solve(events: list) -> list` in `starter.py` (see `interface.md` / `blackbox.yaml`).

Input

A list of dicts, each with keys `pid` (int), `process` (str), `parent_process` (str), `external_connection` (bool), `bytes_transferred` (int).

Output

A sorted list of `pid` (int) for every event that is flagged.

Detection rules (a process is flagged if EITHER rule fires)

1. **Living-off-the-land parent-child pair:** `process` (case-insensitive) is one of the script interpreters {`"powershell.exe"`, `"cmd.exe"`, `"wscript.exe"`, `"cscript.exe"`, `"mshta.exe"`} AND `parent_process` (case-insensitive) is **not** `"explorer.exe"` (the only parent considered a normal, user-initiated launch of an interpreter). Any other parent, including `winword.exe`, `outlook.exe`, `svchost.exe`, or a browser, is treated as suspicious, matching the living-off-the-land pattern where a document or script silently spawns a shell. 2. **Unusual outbound transfer:** `external_connection` is `True` AND `bytes_transferred > 1000000` (strictly greater than 1,000,000 bytes).

Examples

```
[{"pid": 501, "process": "powershell.exe", "parent_process": "winword.exe",
  "external_connection": True, "bytes_transferred": 500},
 {"pid": 502, "process": "chrome.exe", "parent_process": "explorer.exe",
  "external_connection": True, "bytes_transferred": 200000},
 {"pid": 503, "process": "backup.exe", "parent_process": "explorer.exe",
  "external_connection": True, "bytes_transferred": 5000000}]
    -> [501, 503]
```

(pid 501 flagged for the living-off-the-land parent; pid 503 flagged for excessive outbound transfer; pid 502 is a normal browser launch under the transfer threshold.)

Constraints

- Deterministic, offline, standard library only.
- Case-insensitive matching of process/parent names.
- Return a de-duplicated, ascending-sorted list of pids (each pid appears at most once even if both rules fire).
- Must pass all cases in `tests.py` (visible + hidden).

How to run

```
cd problem && python -m pytest tests.py -q
```

Starter code:

```
"""Starter code for 4.4.a. Student completes the TODO.
This file intentionally FAILS the tests until implemented."""


def solve(events: list) -> list:
    """Flag EDR process events showing a living-off-the-land parent-child pair or an
    unusually large outbound data transfer.

    Args:
        events: list of dicts with keys pid (int), process (str), parent_process (str),
            external_connection (bool), bytes_transferred (int).

    Returns:
        Sorted list of unique pids (int) flagged by either detection rule.
    """
    # TODO: implement per prompt.md
    raise NotImplementedError("implement solve() — see prompt.md")
```

4.4.b · Log analysis

3 pts · auto-graded on the site

Coding problem 4.4.b: Brute-force log correlator

Skill: Detect Attacks · **Maps to:** 4.4.B, 4.4.D · **Language:** Python 3 (pytest)

Problem

An authentication log records every login attempt as an event with a username, a timestamp (in seconds), and a result (`"SUCCESS"` or `"FAILED"`). A brute-force attack shows up as a cluster of failed attempts for the same user, tightly packed in time. Build the correlator that scans the log and flags every username showing this pattern.

Function contract

Implement `def solve(entries: list) -> list` in `starter.py` (see `interface.md` / `blackbox.yaml`).

Input

A list of dicts, each with keys `ts` (int, seconds since some reference point), `user` (str), `result` (str, `"SUCCESS"` or `"FAILED"`). Entries are not guaranteed to already be sorted by timestamp.

Output

A sorted list of usernames (str) flagged for a brute-force pattern.

Detection rule

A user is flagged if there exist **5 or more `"FAILED"` entries for that user** where the time span from the earliest to the latest of those 5 (or more) entries is **at most 60 seconds** (inclusive). In other words: sort that user's failed-attempt timestamps ascending; if any 5 consecutive failed timestamps (in that sorted order) span 60 seconds or less (`timestamps[i+4] - timestamps[i] <= 60`), the user is flagged. SUCCESS entries do not count toward the failure count and do not reset or break a streak of failures, only FAILED entries matter for this rule.

Examples

```
[{"ts": 0, "user": "jsmith", "result": "FAILED"},
 {"ts": 13, "user": "jsmith", "result": "FAILED"},
 {"ts": 21, "user": "jsmith", "result": "FAILED"},
 {"ts": 30, "user": "jsmith", "result": "FAILED"},
 {"ts": 38, "user": "jsmith", "result": "FAILED"},
```

```
 {"ts": 46, "user": "jsmith", "result": "SUCCESS"},
 {"ts": 100, "user": "agarcia", "result": "FAILED"},
 {"ts": 1662, "user": "agarcia", "result": "FAILED"}]
    -> ["jsmith"]
```

(jsmith has 5 failures spanning 0-38s = 38s <= 60s -> flagged. agarcia has only 2 failures, 1562s apart -> not flagged.)

Constraints

- Deterministic, offline, standard library only.
- Input entries may arrive out of timestamp order; sort within your implementation.
- Return a de-duplicated, alphabetically sorted list of usernames.
- Must pass all cases in `tests.py` (visible + hidden).

How to run

```
cd problem && python -m pytest tests.py -q
```

Starter code:

```
"""Starter code for 4.4.b. Student completes the TODO.
This file intentionally FAILS the tests until implemented."""


def solve(entries: list) -> list:
    """Flag usernames showing a brute-force pattern: 5+ FAILED attempts within any
    60-second window.

    Args:
        entries: list of dicts with keys ts (int), user (str), result ("SUCCESS"/"FAILED").
            Not guaranteed sorted by timestamp.

    Returns:
        Alphabetically sorted list of unique usernames flagged for brute-force.
    """
    # TODO: implement per prompt.md
    raise NotImplementedError("implement solve() — see prompt.md")
```

4.4.c · Identifying compromised devices (indicators of compromise)

3 pts · auto-graded on the site

Coding problem 4.4.c: Weighted IOC-scoring engine

Skill: Detect Attacks · **Maps to:** 4.4.B, 4.4.C · **Language:** Python 3 (pytest)

Problem

Each device under investigation reports a set of observed indicators of compromise (IOCs). Each IOC type carries a fixed severity weight. Build the scoring engine that sums the weights of the IOCs observed on a device and returns an overall compromise verdict.

Function contract

Implement `def solve(iocs: list) -> str` in `starter.py` (see `interface.md` / `blackbox.yaml`).

Input

A list of strings, each an IOC type observed on one device. Duplicate entries in the list count only once (an IOC type either is or is not present on the device).

IOC weight table

| IOC type string | weight | |---|---| | "known_malicious_hash" | 6 | | "av_disabled" | 5 | | "new_admin_account" | 4 | | "unusual_outbound_traffic" | 3 | | "unexpected_scheduled_task" | 3 | | "registry_run_key_added" | 2 | | "failed_login_cluster" | 1 |

Any IOC type string not in this table contributes a weight of 0 (it is ignored, not an error).

Output

One of the strings: "clean" (total score < 4), "suspicious" (4 <= total score < 8), "compromised" (total score >= 8).

Examples

```
["av_disabled", "new_admin_account"]
    -> "compromised"   # 5 + 4 = 9 >= 8

["failed_login_cluster"]
    -> "clean"          # 1 < 4

["new_admin_account", "failed_login_cluster"]
    -> "suspicious"      # 4 + 1 = 5, in [4, 8)
```

Constraints

- Deterministic, offline, standard library only.
- Duplicate IOC types in the input list must not be double-counted.
- Unknown/unrecognized IOC type strings contribute 0 and must not raise an error.
- Thresholds are: < 4 clean, 4 <= score < 8 suspicious, >= 8 compromised.
- Must pass all cases in tests.py (visible + hidden).

How to run

```
cd problem && python -m pytest tests.py -q
```

Starter code:

```
"""Starter code for 4.4.c. Student completes the TODO.
This file intentionally FAILS the tests until implemented."""


def solve(iocs: list) -> str:
    """Sum the weights of unique observed IOCs and classify a compromise verdict.

    Args:
        iocs: list of str IOC type identifiers observed on one device.

    Returns:
        "clean" (score < 4), "suspicious" (4 <= score < 8), or "compromised" (score >= 8).
    """
    # TODO: implement per prompt.md
    raise NotImplementedError("implement solve() — see prompt.md")
```