UNIT 4 · TOPIC 4.2

Device Authentication Hardening

Assignment, Answer Key

Teacher answer key, 39 points total.

Practice Questions

4.2.a · Passwords and password policies

1. According to NIST SP 800-63B, which practice is recommended when a user creates a new password? (1 pt)

- ○ A. Require at least one uppercase letter, one digit, and one symbol
- ○ B. Force the user to change the password every 90 days
- **● C. Check the candidate against a list of known-compromised passwords and reject matches**
- ○ D. Block copy-paste to prevent shoulder surfing

Why: NIST 800-63B dropped mandatory complexity rules and periodic rotation, but does require checking new passwords against known-breach lists.

2. Which of the following are valid reasons an organization enforces an account lockout policy? (Select ALL that apply.) (2 pts)

- **■ A. Prevents automated online guessing attacks**
- □ B. Eliminates the need for password hashing
- **■ C. Forces attackers to slow down their credential testing**
- **■ D. Makes brute-force infeasible in an interactive login scenario**

Why: Lockout blocks fast online guessing and slows credential testing. It does not replace hashing, which protects the stored credential database offline.

3. An attacker obtains a copy of a site's password database. The passwords are stored with bcrypt. Why does this algorithm make cracking harder than MD5? (1 pt)

- ○ A. Bcrypt produces longer hashes, so there are more possible values to try
- ○ B. Bcrypt hashes are encrypted with a server key the attacker does not have
- ○ C. Bcrypt changes each user's hash every time they log in
- **● D. Bcrypt is intentionally slow, making each guess computationally expensive**

Why: Cracking means hashing guesses and comparing. MD5 is built for speed, so a GPU tries billions of guesses per second; bcrypt has a tunable work factor that makes each hash deliberately slow, cutting that to thousands. Bcrypt also salts every hash. It is a one-way hash, not encryption, and the stored hash only changes when the password changes.

4. What is the primary purpose of a cryptographic salt in password storage? (1 pt)

- ○ A. To make the password longer before the user sees it
- ○ B. To encrypt the password so it can be decrypted later
- **● C. To ensure two users with the same password have different stored hashes**
- ○ D. To enforce complexity rules automatically

Why: A salt is a unique random value per user. Two users with identical passwords produce different hashes, defeating precomputed rainbow-table attacks.

5. Name the two attack types that increasing password LENGTH most directly defends against. (1 pt)

Acceptable answers: brute-force; brute force; dictionary; dictionary attack; brute-force and dictionary

Why: Length exponentially expands the search space for brute-force attacks and reduces overlap with dictionary word lists.

4.2.b · Multi-factor authentication

6. A user logs in with a password, then enters a memorized answer to a security question. Is this true multi-factor authentication? (1 pt)

- **● A. No, both credentials are 'something you know', the same factor category**
- ○ B. Yes, two credentials were entered
- ○ C. Yes, because a security question is a possession factor
- ○ D. No, security questions are never allowed in authentication

Why: A password and a security-question answer are both knowledge factors. True MFA requires two DIFFERENT factor categories, not just two credentials.

7. Which factor category does a hardware security key (like a FIDO2/YubiKey device) belong to? (1 pt)

- ○ A. Something you know
- **● B. Something you have (possession)**
- ○ C. Something you are (inherence)
- ○ D. It is not a factor at all

Why: A hardware key is a physical object the user possesses, the possession factor category.

8. Select ALL statements that are TRUE about SMS-based one-time codes used for MFA. (2 pts)

- **■ A. They are vulnerable to SIM-swapping attacks**
- □ B. They are immune to phishing because the code changes every time
- **■ C. They can be intercepted or relayed by an adversary-in-the-middle phishing kit**
- **■ D. They still combine a knowledge factor (password) with a possession factor (phone)**

Why: SMS codes are possession-factor evidence but are vulnerable to SIM swapping and real-time phishing relay; a changing code does not prevent an attacker from relaying it live to the real site.

9. An attacker who already has a victim's password sends them ten push-approval MFA prompts in a row until the victim taps Approve just to stop the notifications. What is this attack called? (1 pt)

- ○ A. SIM swapping
- **● B. MFA fatigue (push bombing)**
- ○ C. TOTP replay
- ○ D. Credential stuffing

Why: Repeatedly sending push prompts until an annoyed or confused user approves one is MFA fatigue, also called push bombing.

10. Why is FIDO2/WebAuthn considered phishing-resistant compared to a typed authenticator-app code? (1 pt)

- **● A. It cryptographically binds the response to the legitimate site's exact domain, so a fake login page cannot obtain a valid response**
- ○ B. It never requires a second device
- ○ C. It does not require a password at all, ever
- ○ D. It uses a longer numeric code than TOTP

Why: FIDO2/WebAuthn performs a domain-bound cryptographic challenge-response, so even a convincing fake site cannot capture a usable credential, unlike a typed code, which a user can be tricked into entering anywhere.

11. Name the attack in which an adversary tricks or bribes a mobile carrier into porting a victim's phone number to an attacker-controlled SIM card, in order to intercept SMS-based MFA codes. (1 pt)

Acceptable answers: sim swap; sim swapping; sim-swap; sim swap attack; simjacking

Why: SIM swapping transfers the victim's phone number to a SIM the attacker controls, letting the attacker receive SMS MFA codes intended for the victim.

4.2.c · Session security

12. An attacker sends a victim a link containing a session ID the attacker already knows. The victim logs in and the server keeps using that same ID. Which attack is this? (1 pt)

- ○ A. Session hijacking
- ○ B. SQL injection
- **● C. Session fixation**
- ○ D. Brute force

Why: The attacker supplied the session ID BEFORE the victim authenticated; this is session fixation, distinct from hijacking a token that was already live.

13. Which cookie attribute prevents JavaScript (including injected XSS scripts) from reading the session cookie? (1 pt)

- **● A. HttpOnly**
- ○ B. Secure
- ○ C. SameSite
- ○ D. Max-Age

Why: The HttpOnly flag hides the cookie from JavaScript entirely, so even a successful XSS injection cannot read and exfiltrate it.

14. Select ALL statements that are TRUE about session timeouts. (2 pts)

- **■ A. An idle timeout ends a session after a period of no activity**
- **■ B. An absolute timeout ends a session after a fixed total duration regardless of activity**
- □ C. A session with no timeout configured poses no additional risk
- **■ D. Timeouts limit how long a stolen or fixated token remains useful**

Why: Idle and absolute timeouts are distinct expiration mechanisms, and both limit the damage a leaked token can do. A session with no timeout at all is a real risk, not a neutral choice.

15. A user clicks 'Log Out' and their browser cookie is deleted, but the server never marks the session record as invalid. What is the consequence? (1 pt)

- ○ A. No consequence; deleting the cookie is sufficient
- ○ B. The user's password is exposed
- **● C. A token captured earlier by an attacker remains valid and usable**
- ○ D. The session is automatically regenerated

Why: Logout must invalidate the session server-side. If it does not, any copy of the token an attacker already captured continues to work, regardless of the client-side cookie deletion.

16. Name the defensive technique of issuing a brand-new session ID at login (and at privilege change) that specifically defeats session fixation. (1 pt)

Acceptable answers: session regeneration; regenerate session id; session id regeneration; regenerating the session id

Why: Session regeneration discards any attacker-planted ID at the moment of login, so fixation fails even if the attacker set an ID on the victim's browser beforehand.

17. A session cookie is sent only over HTTPS due to one cookie flag, but is still readable by page JavaScript because a different flag is missing. Which flag is MISSING? (1 pt)

- ● **A. HttpOnly**
- ○ B. Secure
- ○ C. Domain
- ○ D. Path

Why: Secure restricts transmission to HTTPS; HttpOnly is the separate flag that hides the cookie from JavaScript. HTTPS alone does not stop an XSS-based cookie read.

4.2.d · Least privilege and access control models

18. What does the principle of least privilege (PoLP) require? (1 pt)

- ● **A. A subject should be granted only the minimum access needed for its job function**
- ○ B. Every user should have the same access, so no one is treated unfairly
- ○ C. Access should be granted generously at first, then reduced if problems appear
- ○ D. Only administrators need access controls; regular users are low risk

Why: Least privilege grants exactly what the job needs and nothing more, so a compromised or careless account can do limited damage. Starting broad and trimming later rarely happens in practice (that is privilege creep), and regular users are the most common phishing targets.

19. A file's owner directly decides who else may read or write it, without any central authority involved. Which access control model is this? (1 pt)

- ○ A. MAC
- ○ B. RBAC
- ○ C. ABAC
- ● **D. DAC**

Why: Discretionary Access Control (DAC) lets the resource owner grant or revoke access directly; classic Unix file permissions are the standard example.

20. A system grants access dynamically based on the user's department, the sensitivity label of the resource, and whether the request happens during business hours. Which model is this? (1 pt)

- ● **A. ABAC**
- ○ B. MAC
- ○ C. RBAC
- ○ D. DAC

Why: Attribute-Based Access Control (ABAC) evaluates attributes of the user, resource, and environment at request time to make a dynamic access decision.

21. Select ALL statements that are TRUE about over-privileged accounts. (2 pts)

- ■ **A. They increase the blast radius if the account is compromised**
- □ B. They eliminate insider-threat risk because trusted employees hold them
- ■ **C. Malware executed under an over-privileged session inherits that account's broad access**
- ■ **D. They make ransomware propagation to additional systems more likely**

Why: Over-provisioning expands blast radius, lets malware inherit broader privileges, and increases ransomware spread risk. Trust does not eliminate insider-threat or compromise risk.

22. Name the term for the silent accumulation of unnecessary access rights over time as an employee's role changes. (1 pt)

Acceptable answers: privilege creep; access creep; permission creep

Why: Privilege creep is the accumulation of unneeded access over time; it is mitigated by periodic access reviews/recertification.

23. Which statement correctly distinguishes RBAC from ABAC? (1 pt)

○ A. RBAC lets owners share files, while ABAC uses security labels

● **B. RBAC assigns static permissions via roles; ABAC evaluates dynamic attributes at request time**

○ C. RBAC is used for networks, while ABAC is used for physical doors

○ D. RBAC checks the user only, while ABAC checks the user's password strength

Why: RBAC asks "what role does this person hold?" and grants that role's fixed permissions. ABAC evaluates many attributes when the request happens: department, data sensitivity, time of day, device health, location. Owner-controlled sharing is DAC, and security labels are MAC.

Coding Assignments (Python 3)

4.2.a · Passwords and password policies

3 pts · auto-graded on the site

Coding problem 4.2.a: Passwords and password policies

Skill: Mitigate Risk · **Maps to:** 4.2.A, 4.2.D · **Language:** Python 3 (pytest)

Problem

A system administrator has defined a password policy (minimum length, complexity requirements, a banned/breached-password list, and a history of previously used passwords). Build the checker that evaluates a candidate password against that policy and reports every rule it violates, so the login form can show the user exactly what to fix.

Function contract

Implement `validate_password(password: str, policy: dict) -> list[str]` in `starter.py` (see `interface.md` / `blackbox.yaml`).

Input

- `password`: a string, the candidate password.

- `policy`: a dict. Example: ``python policy = { "min_length": 12, "require_upper": True, "require_lower": True, "require_digit": True, "require_symbol": True, "banned_list": ["password123", "letmein", "qwerty123456"], "history": ["OldPass2023!", "OldPass2024!"], } Any key may be omitted; a missing key means that rule is not enforced (see interface.md` for exact defaults).

Output

A `list[str]` of violated rule names, in the fixed order defined in `interface.md`: `too_short`, `no_upper`, `no_lower`, `no_digit`, `no_symbol`, `in_banned_list`, `reused_password`. An empty list `[]` means the password is fully compliant.

Examples

```
validate_password("abc", {"min_length": 12, "require_upper": True, "require_digit": True})
    -> ["too_short", "no_upper", "no_digit"]
```

```
validate_password("Password123", {"banned_list": ["password123"]})
    -> ["in_banned_list"]

validate_password(
    "Tr0ub4dor&3xtra!",
    {"min_length": 12, "require_upper": True, "require_lower": True,
     "require_digit": True, "require_symbol": True,
     "banned_list": ["password123"], "history": ["OldPass2023!"]},
) -> []
```

Constraints

- Deterministic, offline, standard library only.
- Missing policy keys are treated as "not required" (see `interface.md` for exact defaults).
- Violated rule names must be returned in the fixed order given above, even when several rules are violated at once.
- Must pass all cases in `tests.py` (visible + hidden).

How to run

```
cd problem && python -m pytest tests.py -q
```

Reference solution:

```
def validate_password(password: str, policy: dict) -> list:
    min_length = policy.get("min_length", 0)
    require_upper = policy.get("require_upper", False)
    require_lower = policy.get("require_lower", False)
    require_digit = policy.get("require_digit", False)
    require_symbol = policy.get("require_symbol", False)
    banned_list = policy.get("banned_list", [])
    history = policy.get("history", [])

    violations = []

    if len(password) < min_length:
        violations.append("too_short")

    if require_upper and not any(c.isupper() for c in password):
        violations.append("no_upper")

    if require_lower and not any(c.islower() for c in password):
        violations.append("no_lower")

    if require_digit and not any(c.isdigit() for c in password):
        violations.append("no_digit")

    if require_symbol and not any(not c.isalnum() for c in password):
        violations.append("no_symbol")

    if any(password.lower() == banned.lower() for banned in banned_list):
        violations.append("in_banned_list")

    if any(password == prior for prior in history):
        violations.append("reused_password")

    return violations
```

4.2.b · Multi-factor authentication

3 pts · auto-graded on the site

Coding problem 4.2.b: Classify a login attempt's MFA strength

Skill: Mitigate Risk · **Maps to:** 4.2.A, 4.2.B · **Language:** Python 3 (pytest)

Problem

A security analyst receives, for each login attempt, the list of authentication factors that were presented (e.g. `["password", "sms_code"]`). Build the classifier that determines whether the attempt satisfies true multi-factor authentication, and if so, whether it relies on a phishing-resistant possession factor or a phishable one.

Categories of result:

- `"single_factor"`: the presented factors, once mapped to their factor category (knowledge / possession / inherence), cover fewer than two distinct categories. This includes presenting only one factor, presenting several factors from the *same* category (e.g. two passwords), an empty list, or a list of only unrecognized factor strings.
- `"mfa_phishing_resistant"`: two or more distinct factor categories are present, and at least one of the presented factors is a phishing-resistant possession factor (`hardware_key` or `fido2`).
- `"mfa_phishable"`: two or more distinct factor categories are present, but no phishing-resistant possession factor was used (e.g. it relies on `sms_code`, `totp_code`, `authenticator_app`, `push_approved`, or `backup_code` for the possession factor).

The exact factor-to-category mapping and full rule set are defined in `interface.md`, implementations must follow it precisely.

Function contract

Implement `solve(factors: list[str]) -> str` in `starter.py` (see `interface.md` / `blackbox.yaml`).

Input

A list of strings, each a recognized or unrecognized factor name. May be empty.

Output

One of: `"single_factor"`, `"mfa_phishable"`, `"mfa_phishing_resistant"`.

Examples

```
["password"]                          -> "single_factor"
["password", "password"]              -> "single_factor"
["password", "security_question"]     -> "single_factor"
["password", "sms_code"]              -> "mfa_phishable"
["password", "push_approved"]         -> "mfa_phishable"
["password", "hardware_key"]          -> "mfa_phishing_resistant"
["password", "sms_code", "hardware_key"] -> "mfa_phishing_resistant"
["biometric", "password"]             -> "mfa_phishable"
[]                                     -> "single_factor"
```

Constraints

- Deterministic, offline, standard library only.
- Follow the exact factor -> category mapping in `interface.md`.
- Unrecognized factor strings must not raise an error; they are simply ignored.

- Must pass all cases in `tests.py` (visible + hidden).

How to run

```
cd problem && python -m pytest tests.py -q
```

Reference solution:

```
from typing import List, Optional

_CATEGORY = {
    "password": "knowledge",
    "pin": "knowledge",
    "security_question": "knowledge",
    "sms_code": "possession",
    "totp_code": "possession",
    "authenticator_app": "possession",
    "push_approved": "possession",
    "backup_code": "possession",
    "hardware_key": "possession",
    "fido2": "possession",
    "biometric": "inherence",
}

_PHISHING_RESISTANT = {"hardware_key", "fido2"}


def _category_of(factor: str) -> Optional[str]:
    return _CATEGORY.get(factor)


def solve(factors: List[str]) -> str:
    if not factors:
        return "single_factor"

    distinct_categories = set()
    has_phishing_resistant = False

    for factor in factors:
        category = _category_of(factor)
        if category is None:
            continue
        distinct_categories.add(category)
        if factor in _PHISHING_RESISTANT:
            has_phishing_resistant = True

    if len(distinct_categories) < 2:
        return "single_factor"

    if has_phishing_resistant:
        return "mfa_phishing_resistant"

    return "mfa_phishable"
```

4.2.c · Session security

3 pts · auto-graded on the site

Coding problem 4.2.c: Classify session-security incidents

Skill: Mitigate Risk · **Maps to:** 4.2.B · **Language:** Python 3 (pytest)

Problem

A security analyst receives short incident-report strings describing observed session behavior. Build the classifier that maps each description to the correct session-security category.

Categories:

- `"hijacking"`: an already-authenticated session token is stolen (XSS read, network sniffing, malware) and reused by an attacker
- `"fixation"`: an attacker supplies a session ID to the victim before login, then reuses that same ID after the victim authenticates
- `"insecure_cookie"`: the session cookie is missing a secure attribute (HttpOnly, Secure, or SameSite) that would have prevented exposure or misuse
- `"timeout_issue"`: a session remains valid far longer than it should because of a missing or misconfigured idle/absolute timeout
- `"secure"`: the report describes a session that is properly protected (regeneration, secure flags, timeouts all present) with no vulnerability
- `"unknown"`: nothing in the report matches any category

A report may match exactly one category. If no category matches, return `"unknown"`.

Function contract

Implement `solve(report: str) -> str` in `starter.py` (see `interface.md` / `blackbox.yaml`). Return the single category label string. Matching is case-insensitive substring detection using the indicator sets defined in `interface.md`.

Input

A single string describing observed session behavior on a device, browser, or server.

Output

One of: `"hijacking"`, `"fixation"`, `"insecure_cookie"`, `"timeout_issue"`, `"secure"`, `"unknown"`.

Examples

```
"Session token was sniffed over unencrypted HTTP and replayed by an attacker"        -> "hijacking"
"Attacker sent a link with a pre-set session id; victim logged in and id unchanged"  -> "fixation"
"Session cookie has no HttpOnly flag configured; automated scan flagged the issue"    -> "insecure_cookie"
"Logged-in kiosk left unattended for hours with no idle timeout configured"          -> "timeout_issue"
"Session id regenerated at login; cookie set Secure, HttpOnly, SameSite=Strict"      -> "secure"
"User changed their display name in account settings"                                -> "unknown"
```

Constraints

- Deterministic, offline, standard library only.
- Detection by case-insensitive substring match against indicator sets in `interface.md`.
- Exactly one label returned (string, not list).
- Must pass all cases in `tests.py` (visible + hidden).

How to run

```
cd problem && python -m pytest tests.py -q
```

Reference solution:

```
def solve(report: str) -> str:
    if not isinstance(report, str):
        return "unknown"

    report_lower = report.lower()


    fixation_indicators = [
        "fixation", "pre-set session", "attacker-supplied session",
        "session id unchanged after login", "id unchanged", "session id before",
        "known session id", "id was already set"
    ]
    if any(ind in report_lower for ind in fixation_indicators):
        return "fixation"

    hijacking_indicators = [
        "sniffed", "sniffing", "intercepted", "stolen session", "stole the session",
        "replayed", "captured token", "plain http", "plaintext",
        "read by an injected script", "read via injected", "malware read the",
        "xss", "reused by an attacker"
    ]
    if any(ind in report_lower for ind in hijacking_indicators):
        return "hijacking"

    insecure_cookie_indicators = [
        "missing httponly", "no httponly", "httponly flag", "missing secure flag",
        "no secure flag", "missing samesite", "no samesite", "cookie has no",
        "cookie is missing", "readable from client-side javascript",
        "not set to httponly"
    ]
    if any(ind in report_lower for ind in insecure_cookie_indicators):
        return "insecure_cookie"

    timeout_indicators = [
        "no idle timeout", "no timeout", "without a timeout", "left unattended",
        "no absolute timeout", "never expires", "does not expire",
        "session never times out", "unattended for", "abandoned", "kiosk"
    ]
    if any(ind in report_lower for ind in timeout_indicators):
        return "timeout_issue"

    secure_indicators = [
        "regenerated at login", "session id regenerated", "secure, httponly",
        "all secure flags", "properly secured", "secure flags set",
        "set secure", "set httponly", "samesite=strict",
        "session expired automatically"
    ]
    if any(ind in report_lower for ind in secure_indicators):
        return "secure"

    return "unknown"
```

4.2.d · Least privilege and access control models

3 pts · auto-graded on the site

Coding problem 4.2.d: Access-request auditor

Skill: Mitigate Risk · **Maps to:** 4.2.B, 4.2.C · **Language:** Python 3 (pytest)

Problem

A security team reviews access requests before granting them. Each request either has a business justification attached or it does not; the requester's access may or may not have been reviewed recently; and the requested access may be scoped to a temporary time window or be standing (permanent). Build the auditor function that applies the least-privilege triage rules to a single request and returns the decision.

Function contract

Implement `def solve(request: dict) -> str` in `starter.py` (see `interface.md` / `blackbox.yaml`).

Input

A dict with keys `current_role` (str), `requested_access` (str), `justification_present` (bool), `time_bound` (bool or None), `last_reviewed_days_ago` (int). Optional keys default as documented in `interface.md` (missing `justification_present` defaults to `False`; missing `time_bound` defaults to `False`; missing `last_reviewed_days_ago` defaults to `0`).

Output

One of the strings: `"approve"`, `"deny_no_justification"`, `"flag_privilege_creep"`, `"approve_time_bound"`.

Decision rule (apply in this exact order, first match wins)

1. No justification (`justification_present` is `False`) → `"deny_no_justification"`. 2. Else, stale review (`last_reviewed_days_ago > 365`) → `"flag_privilege_creep"`. 3. Else, time-bound request (`time_bound` is `True`) → `"approve_time_bound"`. 4. Else → `"approve"`.

Rule 1 is checked before rule 2, a request with no justification is denied even if it is also years overdue for review or time-bound. The staleness threshold is 365 days, strictly greater than (365 itself is still considered current).

Examples

```
{"current_role": "Marketing Intern", "requested_access": "prod-db-write",
 "justification_present": False, "time_bound": False, "last_reviewed_days_ago": 10}
    -> "deny_no_justification"

{"current_role": "HR Analyst", "requested_access": "payroll-admin",
 "justification_present": True, "time_bound": False, "last_reviewed_days_ago": 800}
    -> "flag_privilege_creep"

{"current_role": "On-call Engineer", "requested_access": "prod-ssh",
 "justification_present": True, "time_bound": True, "last_reviewed_days_ago": 5}
    -> "approve_time_bound"

{"current_role": "Analyst", "requested_access": "reporting-read",
 "justification_present": True, "time_bound": False, "last_reviewed_days_ago": 30}
    -> "approve"
```

Constraints

- Deterministic, offline, standard library only.
- Missing optional keys must not raise, use the documented defaults.
- Exactly one label returned (string, not list).

- Must pass all cases in `tests.py` (visible + hidden).

How to run

```
cd problem && python -m pytest tests.py -q
```

Reference solution:

```
def solve(request: dict) -> str:
    justification_present = bool(request.get("justification_present", False))
    time_bound = request.get("time_bound", False)
    last_reviewed_days_ago = request.get("last_reviewed_days_ago", 0)

    if not justification_present:
        return "deny_no_justification"

    if last_reviewed_days_ago > 365:
        return "flag_privilege_creep"

    if time_bound is True:
        return "approve_time_bound"

    return "approve"
```