UNIT 3 · TOPIC 3.2

Wireless Network Security

Assignment, Answer Key

Teacher answer key, 31 points total.

Practice Questions

3.2.a · Wi-Fi basics and wireless security protocols (WPA2/WPA3)

1. Which cipher suite does WPA2 use to provide both confidentiality and data integrity? (1 pt)

- ○ A. RC4-TKIP
- **● B. AES-CCMP**
- ○ C. DES-CBC
- ○ D. 3DES-ECB

Why: WPA2 uses AES in Counter Mode with CBC-MAC (CCMP), replacing the broken RC4-based WEP and TKIP.

2. What is the primary security advantage of WPA3-SAE over WPA2-PSK? (1 pt)

- **● A. WPA3-SAE prevents offline dictionary attacks against captured handshakes**
- ○ B. WPA3 requires passwords of at least 20 characters
- ○ C. WPA3 hides the network name from scanners
- ○ D. WPA3 encrypts traffic with WEP for backward compatibility

Why: With WPA2-PSK, an attacker who captures the 4-way handshake can guess passwords offline, as fast as their hardware allows. WPA3's SAE (Dragonfly) handshake forces every guess to be an interactive attempt against the access point, so offline cracking does not work. It does not change password length rules or hide the SSID, and WEP is long broken.

3. A student says 'I hid my SSID so attackers cannot find my network.' What is wrong with this reasoning? (1 pt)

- ○ A. Nothing; a hidden SSID is a strong control on its own
- ○ B. Hidden networks are illegal to operate in most countries
- **● C. Hidden SSIDs still appear in probe responses and any passive scanner reveals them**
- ○ D. Hiding the SSID turns off WPA2 encryption

Why: A hidden network still transmits; devices that know it shout its name in probe requests wherever they go, and the access point answers. Any passive scanner recovers the name within seconds. It is obscurity, not security, and can even make client devices leak the name in public. Encryption is unaffected.

4. Select ALL configuration choices that represent best practice for a school Wi-Fi network. (3 pts)

- **■ A. Use WPA2-AES or WPA3 for the student SSID**
- □ B. Use WEP for legacy device compatibility
- **■ C. Isolate guest devices on a separate VLAN**
- **■ D. Keep AP firmware updated to patch protocol vulnerabilities**

Why: WPA2-AES/WPA3, VLAN isolation, and firmware updates are best practice. WEP is completely broken and must not be used.

5. Which WPA2 mode requires individual credentials via a RADIUS server and is preferred for corporate environments? (1 pt)

- ○ A. WPA2-PSK (Personal)

○ B. WPA2-OWE

○ C. WPA2-TKIP

● D. WPA2-EAP (Enterprise)

Why: WPA2-Enterprise uses 802.1X and a RADIUS server so each user or device has individual credentials and accountability.

6. Name the WPA3 property that ensures compromising today's session key cannot decrypt previously captured sessions. (1 pt)

Acceptable answers: forward secrecy; perfect forward secrecy; pfs; forward secret

Why: Forward secrecy ensures each session derives fresh keys; past captured sessions remain protected even if the current key is exposed.

3.2.b · Managerial controls and security policies

7. What distinguishes a managerial (administrative) control from a technical control? (1 pt)

● A. Managerial controls are policies/procedures enforced through training and process, not automatically by hardware or software

○ B. Managerial controls are written by managers, while technical controls are written by IT staff

○ C. Managerial controls only apply after an incident, while technical controls apply before

○ D. Managerial controls protect data, while technical controls protect networks

Why: The category comes from HOW the control works: a policy, training, review process or hiring check works through people following rules, while a technical control (firewall, encryption, MFA) is enforced by technology. Who writes it, when it applies, and what it protects do not decide the category.

8. An organization requires new employees to sign a document defining permitted and prohibited use of company systems. What is this document called? (1 pt)

○ A. Firewall configuration

● B. Acceptable Use Policy (AUP)

○ C. Access control list

○ D. Badge access log

Why: An Acceptable Use Policy (AUP) defines what employees are and are not permitted to do with organizational systems and data.

9. Which of the following are examples of managerial controls? Select ALL that apply. (2 pts)

■ A. A documented least-privilege access review process

□ B. A locked server room door

■ C. Annual security awareness training

□ D. A firewall rule blocking a malicious IP

Why: A documented access-review process and awareness training are both policy/process-driven managerial controls. The locked door is a physical control, and the firewall rule is a technical control.

10. Why is 'privilege creep' a problem that a least-privilege policy specifically addresses? (1 pt)

● A. It refers to accounts gradually accumulating unnecessary access rights over time without review

○ B. It refers to attackers slowly escalating privileges with exploits

○ C. It refers to administrators sharing one admin account

○ D. It refers to new employees being given too little access at first

Why: When people change roles, they often gain new access but never lose the old access, so over years an account can open far more than the job needs. Least privilege, enforced through periodic access reviews, removes the leftovers. Attacker privilege escalation is a related but different idea: it is an exploit, not an administrative drift.

11. Name the recurring managerial control that teaches employees to recognize social engineering and follow security policy, often including simulated phishing emails. (1 pt)

Acceptable answers: security awareness training; awareness training; security training

Why: Security awareness training is a recurring program (often annual, with phishing simulations) that changes employee behavior through education and reinforcement.

12. A badge reader that requires a PIN and physical badge to open a data center door, is this a technical or physical control? (1 pt)

● **A. Physical, it restricts physical access to a space, regardless of using electronic components**

○ B. Technical, anything involving electronics is automatically technical

○ C. Managerial, it requires an employee to remember a PIN

○ D. None of the above

Why: Classification depends on what the control restricts (physical access to a space), not on whether it involves electronic components, this is a physical control.

3.2.c · Layered network defense overview

13. What is the core justification for defense in depth (layered defense)? (1 pt)

○ A. Using many vendors means at least one product will be good

○ B. Layers let each control be configured more loosely, since others will catch mistakes

● **C. Every individual control has weaknesses or can be misconfigured, so no single control should be relied on alone**

○ D. Attackers give up after the first layer, so layering mostly adds deterrence

Why: Any single control can fail, be bypassed, or be misconfigured, so independent layers mean one failure does not lead straight to a breach. Layering is not an excuse to weaken each layer, and determined attackers do not stop at the first one. Vendor diversity can help but is not the core idea.

14. Endpoint antivirus/EDR software installed on individual employee laptops belongs to which defense-in-depth layer? (1 pt)

○ A. Perimeter

○ B. Human

○ C. Data

● **D. Host**

Why: Host-layer controls protect the individual device itself, assuming outer layers (perimeter, network) may fail.

15. Which of the following are examples of network-layer controls (as distinct from perimeter or host)? Select ALL that apply. (2 pts)

■ **A. VLAN segmentation separating departments**

■ **B. WPA3 wireless security protocol**

□ C. A border firewall at the internet gateway

□ D. Full-disk encryption on a laptop

Why: VLAN segmentation and WPA3 both operate inside the internal network to limit lateral movement and secure the wireless segment. The border firewall is perimeter-layer, and full-disk encryption is data-layer.

16. Why does the human/managerial layer 'span' all the other layers rather than sitting at one specific point? (1 pt)

○ A. Because training is the cheapest layer, so it is applied everywhere

○ B. Because only humans can make policy, so it sits above the technical layers

○ C. Because human error only happens at the perimeter

● D. It keeps every technical layer correctly configured, monitored, and improved, and catches what automated controls miss

Why: Every technical layer is configured, reviewed and responded to by people, and people also face attacks directly (phishing). So policies, training and procedures affect the perimeter, network, host and data layers alike. Human error can happen at any layer, not just the edge.

17. Name the layer that protects data itself (e.g., via encryption) regardless of which device or network segment it is currently on. (1 pt)

Acceptable answers: data layer; data

Why: The data layer is the innermost layer, even if every outer layer fails, strong data-layer controls like encryption can still prevent stolen data from being usable.

18. An organization deploys only a single, very strong perimeter firewall and no other controls. What is the main risk of this approach? (1 pt)

○ A. Internal traffic is slower when it passes through a strong firewall

○ B. Strong firewalls generate too many false positives to be useful

● C. Different attack vectors (e.g., ARP spoofing on the internal network, phishing) bypass the perimeter entirely, so a single control leaves other layers completely unprotected

○ D. A single firewall cannot inspect encrypted traffic, so it blocks nothing

Why: A perimeter firewall only sees traffic crossing the perimeter. Phishing delivered through allowed email, a malicious insider, or an attacker already inside doing ARP spoofing never meets it. Without host, network and human layers, one bypass leaves everything exposed. Firewalls do block plenty; the issue is coverage, not strength.

Coding Assignments (Python 3)

3.2.a · Wi-Fi basics and wireless security protocols (WPA2/WPA3)

3 pts · auto-graded on the site

Coding problem 3.2.a: Wi-Fi configuration security evaluator

Skill: Mitigate Risk · **Maps to:** 3.2.A · **Language:** Python 3 (pytest)

Problem

You are building an automated Wi-Fi configuration checker for Crestfield Analytics, mirroring what enterprise wireless assessment tools do. Given a dictionary describing one access point's configuration, return the sorted list of security gap codes that configuration has, based on the criteria from the lesson (protocol strength, PSK password length, guest network isolation, admin interface password strength, and firmware currency).

Function contract

Implement `evaluate_wifi_config(cfg)` in `starter.py` (see `interface.md` / `blackbox.yaml`).

Input

- `cfg`: `dict` with: - `"protocol"`: `str`, one of `"WPA3"`, `"WPA2-AES"`, `"WPA2-TKIP"`, `"WEP"`, `"OPEN"` - `"mode"`: `str`, `"personal"` or `"enterprise"` - `"psk_length"`: `int`, length of the pre-shared key/password (only meaningful when `mode == "personal"`) - `"guest_network_isolated"`: `bool`, whether guest devices are on a separate, isolated SSID/VLAN - `"admin_password_strong"`: `bool`, whether the AP's management interface has a strong unique password - `"firmware_current"`: `bool`, whether the AP is running current (patched) firmware

Output

A sorted `list[str]` of gap codes present in the configuration (empty list if there are no gaps). Possible gap codes:

- `"insecure_protocol"`: protocol is `"WEP"`, `"WPA2-TKIP"`, or `"OPEN"`
- `"weak_psk"`, `mode == "personal"` and `psk_length < 20`
- `"no_guest_isolation"`, `guest_network_isolated` is `False`
- `"weak_admin_password"`, `admin_password_strong` is `False`
- `"outdated_firmware"`, `firmware_current` is `False`

Examples

```
cfg = {
    "protocol": "WPA2-TKIP", "mode": "personal", "psk_length": 12,
    "guest_network_isolated": True, "admin_password_strong": True, "firmware_current": True,
}
evaluate_wifi_config(cfg)
# -> ["insecure_protocol", "weak_psk"]

cfg2 = {
    "protocol": "WPA3", "mode": "enterprise", "psk_length": 0,
    "guest_network_isolated": True, "admin_password_strong": True, "firmware_current": True,
}
evaluate_wifi_config(cfg2)
# -> []
```

Constraints

- Deterministic, offline, standard library only.
- `psk_length` is only checked when `mode == "personal"`; ignore it entirely for `"enterprise"` mode (enterprise mode uses per-user 802.1X credentials, not a shared PSK).
- Gap codes in the output list must be sorted alphabetically and contain no duplicates.
- Must pass all cases in `tests.py` (visible + hidden).

How to run

```
cd problem && python -m pytest tests.py -q
```

Reference solution:

```
from typing import Dict, List

_INSECURE_PROTOCOLS = {"WEP", "WPA2-TKIP", "OPEN"}
```

```
def evaluate_wifi_config(cfg: Dict) -> List[str]:
    gaps = []

    if cfg["protocol"] in _INSECURE_PROTOCOLS:
        gaps.append("insecure_protocol")

    if cfg["mode"] == "personal" and cfg["psk_length"] < 20:
        gaps.append("weak_psk")

    if not cfg["guest_network_isolated"]:
        gaps.append("no_guest_isolation")

    if not cfg["admin_password_strong"]:
        gaps.append("weak_admin_password")

    if not cfg["firmware_current"]:
        gaps.append("outdated_firmware")

    return sorted(gaps)
```

3.2.b · Managerial controls and security policies

3 pts · auto-graded on the site

Coding problem 3.2.b: Control-type classifier

Skill: Mitigate Risk · **Maps to:** 3.2.A, 3.2.B · **Language:** Python 3 (pytest)

Problem

You are building a control matrix tool for Crestfield Analytics' security program. Given a list of implemented security scenarios, classify each one by control family: `"managerial"`, `"technical"`, or `"physical"`, based on how the control is actually implemented (its `"mechanism"`), not on what risk it happens to address.

Function contract

Implement `classify_controls(scenarios)` in `starter.py` (see `interface.md` / `blackbox.yaml`).

Input

- `scenarios`: `list[dict]`, each with: - `"id"`: `str`, a scenario identifier - `"description"`: `str`, flavor text describing the scenario (not used for classification) - `"mechanism"`: `str`, one of `"policy_document"`, `"training_program"`, `"access_review_process"`, `"software_or_hardware_enforcement"`, `"physical_barrier"`

Output

A `list[str]` of classifications, **one per input scenario, in the same order as the input**. Each entry is one of `"managerial"`, `"technical"`, `"physical"`.

Examples

```
scenarios = [
    {"id": "s1", "description": "New hires sign a document listing allowed and prohibited use of company
laptops.",
     "mechanism": "policy_document"},
    {"id": "s2", "description": "The office network blocks known-malicious IP ranges automatically.",
     "mechanism": "software_or_hardware_enforcement"},
    {"id": "s3", "description": "The server room door requires a badge to open.",
     "mechanism": "physical_barrier"},
]
classify_controls(scenarios)  ->  ["managerial", "technical", "physical"]
```

Constraints

- Deterministic, offline, standard library only.
- Classification depends only on `"mechanism"`, never on `"description"` text.
- Mapping: `"policy_document"`, `"training_program"`, and `"access_review_process"` are all `"managerial"`; `"software_or_hardware_enforcement"` is `"technical"`; `"physical_barrier"` is `"physical"`.
- Must pass all cases in `tests.py` (visible + hidden).

How to run

```
cd problem && python -m pytest tests.py -q
```

Reference solution:

```
from typing import Dict, List

_MANAGERIAL = {"policy_document", "training_program", "access_review_process"}
_TECHNICAL = {"software_or_hardware_enforcement"}
_PHYSICAL = {"physical_barrier"}


def classify_controls(scenarios: List[Dict]) -> List[str]:
    result = []
    for s in scenarios:
        mech = s["mechanism"]
        if mech in _MANAGERIAL:
            result.append("managerial")
        elif mech in _TECHNICAL:
            result.append("technical")
        elif mech in _PHYSICAL:
            result.append("physical")
        else:
            raise ValueError(f"unknown mechanism: {mech}")
    return result
```

3.2.c · Layered network defense overview

3 pts · auto-graded on the site

Coding problem 3.2.c: Defense-in-depth layer classifier

Skill: Mitigate Risk · **Maps to:** 3.2.B, 3.2.C · **Language:** Python 3 (pytest)

Problem

You are building a defense-in-depth mapping tool for Crestfield Analytics' security architecture review. Given a list of deployed controls, assign each one to its correct layer in the layered defense model taught in the lesson: `"perimeter"`, `"network"`, `"host"`, `"application"`, `"data"`, or `"human"`.

Function contract

Implement `classify_layer(controls)` in `starter.py` (see `interface.md` / `blackbox.yaml`).

Input

- `controls`: `list[dict]`, each with: - `"name"`: `str`, a human-readable control name (not used for classification) - `"category"`: `str`, one of the following exact values: - Perimeter: `"firewall"`, `"ips"`, `"dns_filter"` - Network: `"vlan_segmentation"`, `"internal_firewall"`, `"wifi_protocol"` - Host: `"endpoint_av"`, `"host_firewall"`,

`"os_patching"` - Application: `"input_validation"`, `"waf"`, `"app_auth"` - Data: `"encryption_at_rest"`, `"dlp"`, `"data_classification"` - Human: `"awareness_training"`, `"aup"`, `"access_review"`, `"incident_response_policy"`

Output

A `list[str]` of layer assignments, **one per input control, in the same order as the input**. Each entry is one of `"perimeter"`, `"network"`, `"host"`, `"application"`, `"data"`, `"human"`.

Examples

```
controls = [
    {"name": "Border firewall", "category": "firewall"},
    {"name": "WPA3 wireless", "category": "wifi_protocol"},
    {"name": "Annual phishing training", "category": "awareness_training"},
]
classify_layer(controls)  ->  ["perimeter", "network", "human"]
```

Constraints

- Deterministic, offline, standard library only.
- Classification depends only on `"category"`, never on `"name"` text.
- `"category"` always contains one of the 16 listed values in test data (no invalid values).
- Must pass all cases in `tests.py` (visible + hidden).

How to run

```
cd problem && python -m pytest tests.py -q
```

Reference solution:

```
from typing import Dict, List

_LAYER_MAP = {
    "firewall": "perimeter",
    "ips": "perimeter",
    "dns_filter": "perimeter",
    "vlan_segmentation": "network",
    "internal_firewall": "network",
    "wifi_protocol": "network",
    "endpoint_av": "host",
    "host_firewall": "host",
    "os_patching": "host",
    "input_validation": "application",
    "waf": "application",
    "app_auth": "application",
    "encryption_at_rest": "data",
    "dlp": "data",
    "data_classification": "data",
    "awareness_training": "human",
    "aup": "human",
    "access_review": "human",
    "incident_response_policy": "human",
}


def classify_layer(controls: List[Dict]) -> List[str]:
    result = []
    for c in controls:
```

```
    category = c["category"]
    if category not in _LAYER_MAP:
        raise ValueError(f"unknown category: {category}")
    result.append(_LAYER_MAP[category])
return result
```