UNIT 5 · TOPIC 5.6

Application Threat Auditing

Assignment, Answer Key

Teacher answer key, 30 points total.

Practice Questions

5.6.a · Application monitoring and logging

1. A single failed login for one user is unremarkable. Fifty failed logins from one IP across twenty usernames in two minutes is a signal. What does this illustrate? (1 pt)

- **● A. The pattern, not the individual event, is the signal**
- ○ B. Failed logins should never be logged because they are too common
- ○ C. Alerts should fire on every single failed login
- ○ D. Only successful logins indicate an attack

Why: One failure is noise; fifty from one source against twenty accounts is a password-spraying signal. Detection rules look for patterns across events (count, spread, timing) rather than single entries. Failures must be logged, or the pattern cannot be seen.

2. Select ALL fields a well-designed security log line typically includes. (3 pts)

- **■ A. Timestamp**
- **■ B. Requesting IP address**
- **■ C. Result/status code**
- □ D. The victim's home address

Why: Standard log fields are timestamp, source IP, user identity, resource accessed, and result code, never unrelated personal data like a home address.

3. What is a SIEM? (1 pt)

- ○ A. A firewall that inspects application traffic
- ○ B. A tool that scans source code for vulnerabilities
- ○ C. An endpoint agent that blocks malware on laptops
- **● D. A platform that centralizes logs from many sources and applies detection rules to raise alerts**

Why: SIEM (Security Information and Event Management) collects logs from servers, firewalls, apps and endpoints in one place, correlates them, and raises alerts. A web firewall, a code scanner (SAST) and an endpoint agent (EDR/antivirus) are different tools that often SEND logs to a SIEM.

4. Name the log severity level at which security-relevant events (like authentication attempts) should be recorded so they are not silently dropped in production. (1 pt)

Acceptable answers: INFO; info level; info or higher

Why: Security-relevant events should be logged at INFO or higher, since DEBUG is typically disabled in production.

5. Why do defenders stream logs to a remote aggregator in real time rather than only storing them locally on the application server? (1 pt)

- ○ A. Remote storage compresses logs so more history can be kept
- **● B. An attacker who compromises the server can delete local logs to cover their tracks; a remote copy preserves the forensic record**

○ C. Local logs cannot include timestamps

○ D. Remote aggregators automatically block attackers

Why: Clearing logs is a standard attacker step after gaining access. Shipping each line off the server as it is written means the evidence already exists elsewhere before the attacker can erase it, and a central store also lets analysts correlate across systems.

5.6.b · Data loss detection (DLP)

6. Which DLP detection strategy inspects the actual data leaving the organization for patterns like credit-card numbers or SSNs? (1 pt)

○ A. Volume/behavior-based detection

○ B. Endpoint detection and response

● C. Content-based detection

○ D. Least privilege

Why: Content-based detection scans the data itself for recognizable sensitive patterns.

7. Select ALL statements that correctly describe volume/behavior-based DLP detection. (3 pts)

■ A. It can catch exfiltration of encrypted or compressed data that has no recognizable content pattern

■ B. It relies on comparing an account's current activity against its normal baseline

□ C. It requires reading and understanding the literal content of every file transferred

■ D. A sudden large transfer to an unfamiliar destination is a classic signal it looks for

Why: Behavior-based detection watches how much/when/where data moves, not what it contains, which is exactly why it catches encrypted exfiltration content inspection would miss.

8. Why do effective DLP programs maintain an approved-destination allowlist? (1 pt)

○ A. Allowlisted destinations do not need to be monitored at all

○ B. Allowlists stop attackers from using approved destinations

● C. So legitimate large transfers (backups, sanctioned partners) don't drown out real alerts with false positives

○ D. Allowlists encrypt the data sent to those destinations

Why: Backups and partner integrations move huge amounts of data every day. Without an allowlist, they would fire constantly and bury real exfiltration alerts. The trade-off: an attacker who abuses an approved destination may slip by, so allowlisted traffic still deserves some monitoring.

9. Name the DLP deployment point that runs on individual laptops/workstations and can block a USB copy of a flagged file, which network DLP alone would never see. (1 pt)

Acceptable answers: endpoint dlp; endpoint

Why: Endpoint DLP instruments the device itself, catching exfiltration paths (USB, local print) that never touch the network.

10. How does DLP differ from a purely forensic control like log review? (1 pt)

○ A. DLP only reviews data after it has been stored in logs

○ B. DLP can only see data on servers, not on laptops

○ C. DLP replaces log review, so logs are no longer needed

● D. A well-integrated DLP system can act preventively in real time, blocking or quarantining a transfer before it completes

Why: Log review reconstructs what happened afterward. DLP can sit in the path of email, web uploads, USB copies and cloud sync and stop a transfer as it happens. DLP runs on endpoints and networks alike, and it still produces logs that investigators rely on.

5.6.c · Digital evidence analysis and attack classification

11. A single failed-login spike is observed. What is the analyst's correct next step before declaring it a brute-force attack? (1 pt)

- **● A. Check the underlying evidence, e.g. is it one source targeting many usernames, or many sources targeting one username?**
- ○ B. Block the source IP immediately and close the case
- ○ C. Reset every user's password as a precaution
- ○ D. Wait for a second spike before doing anything

Why: A spike could be brute force, password spraying, a misconfigured service retrying an old password, or users locked out after a change. Looking at the shape (one source vs many, one account vs many, any successes) decides both the classification and the right response. Blocking or mass resets before you understand it can cause outages and miss the real problem.

12. Select ALL statements that correctly describe an indicator of compromise (IOC). (3 pts)

- **■ A. A single IOC is rarely conclusive proof of a specific attack type by itself**
- **■ B. Examples include a suspicious IP, a known-malware file hash, or a credential-harvesting URL**
- **■ C. Attack classification typically requires reasoning about multiple IOCs together**
- □ D. An IOC always proves the attacker's exact identity

Why: IOCs are individually weak signals; classification comes from weighing multiple IOCs together, and none of them reveal an attacker's identity by themselves.

13. Why does chain of custody matter for evidence even outside a courtroom? (1 pt)

- ○ A. Chain of custody is only needed when police are involved
- ○ B. It makes evidence files smaller and easier to store
- ○ C. It replaces the need to keep original copies
- **● D. An internal investigation's credibility also depends on being able to show evidence wasn't tampered with**

Why: Internal investigations lead to firings, insurance claims and lawsuits that may come later. If you cannot show who handled the evidence and that it was not altered (hashes, logs of access), conclusions can be challenged. Investigators always preserve originals and analyze copies.

14. Name the widely-used framework that gives analysts a shared vocabulary for attack techniques so classifications are consistent across teams. (1 pt)

Acceptable answers: MITRE ATT&CK; ATT&CK; MITRE ATTACK

Why: MITRE ATT&CK provides a common, consistent vocabulary for classifying attack techniques across analysts and teams.

15. An evidence bundle contains a known-malware file hash AND a suspicious email attachment. Which best describes correct classification reasoning? (1 pt)

- ○ A. Classify it as malware, since a file hash is stronger evidence than an email
- **● B. Score how many known indicators support each category and communicate which is best-supported, noting remaining uncertainty if any**
- ○ C. Classify it as phishing, since the attachment arrived first
- ○ D. Report both categories equally and let management decide

Why: Good classification weighs all the evidence: here both malware and phishing have support (phishing delivered it, the hash says it ran or was present). The analyst reports which is best supported, why, and what is still uncertain, rather than picking one indicator or passing the decision up.

Coding Assignments (Python 3)

5.6.a · Application monitoring and logging

3 pts · auto-graded on the site

Coding problem 5.6.a: Brute-force detector (SIEM alert rule)

Skill: Detect Attacks · **Maps to:** 5.6.A · **Language:** Python 3 (pytest)

Problem

Implement the SIEM alert rule described in the lesson: given a list of parsed application log entries, return every IP address whose failed-login (`401`) count exceeds a threshold within a rolling time window, a classic brute-force signal.

Function contract

Implement `solve(entries: list, threshold: int, window_seconds: int) -> list` in `starter.py` (see `interface.md` / `blackbox.yaml`).

Input

- `entries`: `list[dict]`, each `{"ip": str, "ts": int, "status": int}` (`ts` = seconds since start of log, not necessarily sorted).
- `threshold`: `int`, minimum number of `401` events within the window to flag the IP.
- `window_seconds`: `int`, rolling window size, in seconds (inclusive on both ends).

Output

A **sorted, de-duplicated** `list[str]` of flagged IP addresses.

Examples

```
entries = [
  {"ip":"10.0.0.1","ts":0,"status":401},
  {"ip":"10.0.0.1","ts":10,"status":401},
  {"ip":"10.0.0.1","ts":20,"status":401},
]
solve(entries, threshold=3, window_seconds=60) -> ["10.0.0.1"]
```

```
entries = [{"ip":"10.0.0.2","ts":0,"status":200}]
solve(entries, threshold=1, window_seconds=60) -> []   # success responses never count
```

Constraints

- Deterministic, offline, standard library only.
- Only `status == 401` entries count toward the brute-force count; other codes are ignored.
- Must pass all cases in `tests.py` (visible + hidden).

How to run

```
cd problem && python -m pytest tests.py -q
```

Reference solution:

```
from collections import defaultdict
from typing import Dict, List


def solve(entries: List[Dict[str, object]], threshold: int, window_seconds: int) -> List[str]:
    by_ip: Dict[str, List[int]] = defaultdict(list)
    for e in entries:
        if e.get("status") == 401:
            by_ip[e["ip"]].append(e["ts"])

    flagged = set()
    for ip, times in by_ip.items():
        times = sorted(times)
        for start in times:
            count = sum(1 for t in times if start <= t <= start + window_seconds)
            if count >= threshold:
                flagged.add(ip)
                break

    return sorted(flagged)
```

5.6.b · Data loss detection (DLP)

3 pts · auto-graded on the site

Coding problem 5.6.b: DLP egress rule

Skill: Detect Attacks · **Maps to:** 5.6.B · **Language:** Python 3 (pytest)

Problem

Implement the volume/behavior-based DLP rule described in the lesson: given a list of outbound transfer events, flag the ones that exceed a size threshold AND go to a destination that is not on the organization's approved-destination list, a classic egress-monitoring rule.

Function contract

Implement `solve(transfers: list, approved_destinations: list, volume_threshold_mb: int) -> list` in `starter.py` (see `interface.md` / `blackbox.yaml`).

Input

- `transfers`: `list[dict]`, each `{"id": str, "bytes_mb": int, "destination": str}`.
- `approved_destinations`: `list[str]` of known-good destination names.
- `volume_threshold_mb`: `int`, transfer must exceed this size to be eligible for flagging.

Output

Sorted `list[str]` of flagged transfer ids.

Examples

```
transfers = [{"id":"t1","bytes_mb":500,"destination":"unknown-cloud.example"}]
solve(transfers, ["corp-backup.internal"], volume_threshold_mb=100) -> ["t1"]
```

```
transfers = [{"id":"t2","bytes_mb":500,"destination":"corp-backup.internal"}]
solve(transfers, ["corp-backup.internal"], volume_threshold_mb=100) -> []   # approved destination
```

Constraints

- Deterministic, offline, standard library only.
- The size comparison is strict (`bytes_mb > volume_threshold_mb`).
- Must pass all cases in `tests.py` (visible + hidden).

How to run

```
cd problem && python -m pytest tests.py -q
```

Reference solution:

```
from typing import Dict, List


def solve(
    transfers: List[Dict[str, object]],
    approved_destinations: List[str],
    volume_threshold_mb: int,
) -> List[str]:
    approved = set(approved_destinations)
    flagged = [
        t["id"]
        for t in transfers
        if t["bytes_mb"] > volume_threshold_mb and t["destination"] not in approved
    ]
    return sorted(flagged)
```

5.6.c · Digital evidence analysis and attack classification

3 pts · auto-graded on the site

Coding problem 5.6.c: Attack classifier (evidence -> category)

Skill: Detect Attacks, Collaborate · **Maps to:** 5.6.B, 5.6.C · **Language:** Python 3 (pytest)

Problem

Formalize the analyst reasoning process from the lesson: given a bundle of evidence indicators collected during an investigation, score each known attack category by how many of its indicators are present, and return the best-supported classification.

Function contract

Implement `solve(indicators: list) -> str` in `starter.py` (see `interface.md` / `blackbox.yaml`).

Input

`indicators`: `list[str]` of evidence tags (may contain duplicates).

Known indicator-to-category mapping

- `"brute-force"`: `multiple_401_responses`, `single_source_ip`, `many_usernames_targeted`, `credential_guessing_pattern`
- `"sql-injection"`: `sql_meta_characters_in_request`, `database_error_in_response`, `union_select_pattern`, `unexpected_query_result_size`
- `"malware"`: `known_malware_file_hash`, `unexpected_process_spawned`, `outbound_c2_connection`, `persistence_mechanism_installed`

- "phishing": suspicious_email_attachment, credential_harvesting_url, spoofed_sender_domain, user_reported_suspicious_email

Output

str, the category with the most matching indicators (as a set; duplicates don't add extra weight). Ties go to the alphabetically first tied category. "unknown" if nothing matches.

Examples

```
["multiple_401_responses", "single_source_ip"]  ->  "brute-force"
["server_restarted"]                             ->  "unknown"
```

Constraints

- Deterministic, offline, standard library only.
- Must pass all cases in tests.py (visible + hidden).

How to run

```
cd problem && python -m pytest tests.py -q
```

Reference solution:

```
from typing import List

_CATEGORY_INDICATORS = {
    "brute-force": {
        "multiple_401_responses",
        "single_source_ip",
        "many_usernames_targeted",
        "credential_guessing_pattern",
    },
    "sql-injection": {
        "sql_meta_characters_in_request",
        "database_error_in_response",
        "union_select_pattern",
        "unexpected_query_result_size",
    },
    "malware": {
        "known_malware_file_hash",
        "unexpected_process_spawned",
        "outbound_c2_connection",
        "persistence_mechanism_installed",
    },
    "phishing": {
        "suspicious_email_attachment",
        "credential_harvesting_url",
        "spoofed_sender_domain",
        "user_reported_suspicious_email",
    },
}


def solve(indicators: List[str]) -> str:
    evidence = set(indicators)
    scores = {
        category: len(evidence & known_indicators)
        for category, known_indicators in _CATEGORY_INDICATORS.items()
    }
    best_score = max(scores.values())
    if best_score == 0:
```

```
    return "unknown"
winners = sorted(cat for cat, score in scores.items() if score == best_score)
return winners[0]
```