UNIT 2 · TOPIC 2.2

Physical Vulnerabilities and Attacks

Assignment, Answer Key

Teacher answer key, 29 points total.

Practice Questions

2.2.a · Unauthorized physical access (tailgating, piggybacking, lock bypass)

1. An attacker carries boxes to appear busy and follows an employee through a badge-reader door without swiping. This is BEST described as: (1 pt)

- ○ A. Piggybacking
- ● **B. Tailgating**
- ○ C. RFID cloning
- ○ D. Bump keying

Why: Tailgating = following an authorized person through a secured entry without the authorized person's knowledge or consent. The employee did not knowingly allow entry.

2. Which physical attack leaves evidence in a badge-access log that looks identical to a legitimate single entry? (1 pt)

- ○ A. Lock picking
- ○ B. Bump keying
- ● **C. Tailgating**
- ○ D. RFID jamming

Why: Both tailgating and piggybacking produce only one badge-swipe event in the log even though two people passed through. Lock picking and bump keying bypass the reader entirely.

3. Select ALL techniques that can grant physical access WITHOUT the correct badge credential. (3 pts)

- ■ **A. Tailgating**
- ■ **B. RFID badge cloning**
- □ C. Multi-factor authentication
- ■ **D. Lock picking**

Why: Tailgating bypasses the reader socially; RFID cloning replays a copied credential; lock picking bypasses the lock mechanically. MFA is a defensive control, not an attack.

4. A building access log shows badge ID 1042 swiping door D1 at 09:00:02 and door D2 (40 meters away) at 09:00:05. Why is this record suspicious? (1 pt)

Acceptable answers: impossible; too fast; three seconds; cannot walk; physically impossible; speed

Why: Three seconds is insufficient to walk 40 meters; this suggests the badge was passed to a second person, a replay attack, or a log integrity issue.

5. Older 125 kHz HID proximity cards are especially vulnerable to which attack? (1 pt)

- ○ A. Bump keying
- ● **B. RFID cloning**
- ○ C. Lock shimming
- ○ D. Tailgating

Why: 125 kHz proximity cards broadcast their ID without cryptographic protection; a hidden reader can capture and clone them in seconds.

6. Name the physical security control that uses two interlocked doors to prevent a second person from following through a secured entry. (1 pt)

Acceptable answers: mantrap; man trap; airlock; sally port

Why: A mantrap (also called an airlock or sally port) keeps one door locked until the first closes, eliminating the physical opportunity for tailgating.

2.2.b · Environmental vulnerabilities (power, HVAC, fire, water)

7. Why do data centers use clean-agent fire suppression (e.g., FM-200, inert gas) instead of water sprinklers? (1 pt)

- ● **A. Water sprinklers would themselves destroy the electronics they are meant to protect**
- ○ B. Clean-agent systems are cheaper to install
- ○ C. Clean-agent systems put out fires faster than water in all cases
- ○ D. Fire codes prohibit water sprinklers in any commercial building

Why: Water-based sprinklers short-circuit and corrode electronics, so they would cause the same loss the fire threatens. Clean-agent systems suppress fire by removing oxygen or interrupting combustion without wetting equipment.

8. A server room's temperature sensor and humidity sensor both cross their warning thresholds at the same time. What does this combined pattern most likely indicate? (1 pt)

- ○ A. A single faulty sensor
- ○ B. A tailgating attempt
- ● **C. A failing or overloaded HVAC (cooling) system**
- ○ D. A power surge

Why: Rising temperature together with drifting humidity is the classic signature of an HVAC failure, since the same cooling system regulates both.

9. Which TWO controls directly address power-related environmental risk? Select all that apply. (2 pts)

- ■ **A. Uninterruptible power supply (UPS)**
- □ B. Clean-agent fire suppression
- ■ **C. Backup generator with N+1 redundancy**
- □ D. Raised flooring

Why: A UPS bridges short outages/dips, and a redundant generator covers longer outages. Fire suppression addresses fire risk; raised flooring addresses water/flood risk.

10. Why is raised flooring used as a control against water/flood risk in a data center? (1 pt)

Acceptable answers: elevate; elevates equipment; above the slab; keeps equipment off the floor; raises equipment above water level; above floor level

Why: Raised flooring physically elevates equipment above the slab, so a shallow flood or leak does not immediately reach the hardware.

11. Why should environmental risks (power, HVAC, fire, water) be analyzed with the same rigor as a targeted cyberattack? (1 pt)

- ○ A. They are legally required to be reported the same way
- ● **B. They can produce the same availability or integrity loss as a targeted attack, even without an adversary**
- ○ C. They are actually more common than cyberattacks in every organization

○ D. Insurance companies require it

Why: The CIA triad does not care whether the cause was malicious; a power failure, fire, or flood can take systems offline or corrupt data just as effectively as an attacker would.

2.2.c · Device theft and tampering

12. What is the single most effective control against data exposure from a STOLEN laptop? (1 pt)

○ A. A strong login password

● **B. Full-disk encryption**

○ C. A Kensington cable lock

○ D. An asset tag

Why: A login password only protects the normal OS boot path; an attacker with physical possession can often boot from external media and read the disk directly. Full-disk encryption makes the drive's contents unreadable without the key even if removed.

13. What distinguishes an evil-maid attack from ordinary device theft? (1 pt)

● **A. The device is covertly tampered with and returned, so the owner does not know anything happened**

○ B. The attacker copies the data and keeps the device, so the owner notices it is gone

○ C. The attacker uses a stolen password instead of physical access

○ D. The device is damaged so it cannot be used, which is an availability attack

Why: The defining trait is covert access followed by return: the attacker (a "maid" in a hotel room, but it can be anyone) installs something like a hardware keylogger or modified boot loader, then leaves the device so the owner keeps using it. Theft is noticed; an evil-maid attack is designed not to be. Full-disk encryption plus secure boot and tamper-evident seals are the defenses.

14. Which TWO of the following are physical/behavioral signs that a device tampering incident may have occurred? Select all that apply. (2 pts)

■ **A. A tamper-evident seal shows a torn or VOID pattern**

□ B. The device's login password was recently changed by the owner

■ **C. An unfamiliar dongle is found plugged into the keyboard port**

□ D. The device was rebooted after a routine software update

Why: A broken tamper-evident seal is direct physical evidence of tampering, and an unfamiliar USB implant (like a keylogger dongle) is a classic hardware-tampering sign. A user-initiated password change or a routine update reboot are normal, expected activity.

15. Why can a tampering incident still be a risk even if the tamper-evident seal is intact? (1 pt)

Acceptable answers: usb implant; does not require opening; external device; peripheral; doesn't require opening the case; rogue usb; without opening the enclosure

Why: Some tampering, such as plugging in a rogue USB keylogger or malicious peripheral, does not require opening the device's enclosure at all, so an intact seal does not rule out tampering.

16. A stolen laptop was encrypted, contained sensitive data, and was not reported missing for 60 hours. Per this atom's triage rules, what risk level should this incident receive? (1 pt)

○ A. LOW

○ B. HIGH

● **C. MEDIUM**

○ D. Cannot be determined

Why: Encrypted (not HIGH), but sensitive data plus more than 48 hours since the last check triggers the MEDIUM rule, the long detection delay raises risk even though the disk itself is protected.

Coding Assignments (Python 3)

2.2.a · Unauthorized physical access (tailgating, piggybacking, lock bypass)

3 pts · auto-graded on the site

Coding problem 2.2.a: Detect unauthorized physical access in a badge log

Skill: Analyze Risk · **Maps to:** 2.2.A, 2.2.B · **Language:** Python 3 (pytest)

Problem

A building security system writes one log record per door event. Your job is to implement the analyst's first-pass filter: given a list of log records, return the event IDs of all records that indicate a likely unauthorized physical access attempt, based on two detection rules:

Rule 1, Impossible speed (tailgating / badge pass-back indicator). If the same badge ID appears at two different doors and the time between events is less than the minimum walk time (distance_meters / MAX_WALK_SPEED), the second event is suspicious. `MAX_WALK_SPEED = 2.0` meters per second.

Rule 2, Sensor mismatch (tailgating indicator). If an event has `"sensor_count": 2` (or higher) but only one badge swipe was recorded (i.e., the event itself has `"badge": <a badge id>` and no second badge event at the same door within 1 second), that event is suspicious.

Return the list of flagged event IDs (strings), sorted ascending. An event may match both rules but should appear only once.

Function contract

Implement `solve(records: list[dict]) -> list[str]` in `starter.py` (see `interface.md` / `blackbox.yaml`).

Input

`records`, a list of dicts, each with keys:

- `"id"` (str): unique event identifier, e.g. `"E001"`
- `"time"` (int): Unix timestamp in seconds (integer)
- `"badge"` (str | None): badge ID that was swiped, or None if no swipe
- `"door"` (str): door identifier, e.g. `"D1"`
- `"distance_from_prev"` (int | None): meters from the previous door this badge was seen at, or None if this is the badge's first appearance or badge is None
- `"sensor_count"` (int): number of bodies the door sensor detected crossing (1 = normal)

Records are provided in chronological order (ascending `"time"`).

Output

A sorted `list[str]` of flagged event IDs. Empty list if no violations found.

Examples

```
[
  {"id":"E001","time":1000,"badge":"B-204","door":"D1","distance_from_prev":None,"sensor_count":1},
  {"id":"E002","time":1003,"badge":"B-204","door":"D2","distance_from_prev":50,"sensor_count":1},
```

```
  {"id":"E003","time":2000,"badge":"B-117","door":"D1","distance_from_prev":None,"sensor_count":2},
]
-> ["E002", "E003"]

E002: B-204 covers 50 m in 3 s = 16.7 m/s > 2.0 m/s  (Rule 1)
E003: sensor_count=2 with one swipe                   (Rule 2)
```

Constraints

- Deterministic, offline, standard library only.
- MAX_WALK_SPEED = 2.0 m/s (defined in interface.md).
- Must pass all cases in `tests.py` (visible + hidden).

How to run

```
cd problem && python -m pytest tests.py -q
```

Reference solution:

```
from typing import List, Dict, Any

MAX_WALK_SPEED = 2.0


def solve(records: List[Dict[str, Any]]) -> List[str]:
    flagged = set()
    last_time: Dict[str, int] = {}

    for rec in records:
        eid = rec["id"]
        badge = rec["badge"]
        t = rec["time"]
        dist = rec["distance_from_prev"]
        sensor = rec["sensor_count"]

        if badge is not None and dist is not None:
            if badge in last_time:
                elapsed = t - last_time[badge]
                if elapsed == 0 or dist / elapsed > MAX_WALK_SPEED:
                    flagged.add(eid)
            last_time[badge] = t
        elif badge is not None:
            last_time[badge] = t

        if badge is not None and sensor >= 2:
            flagged.add(eid)

    return sorted(flagged)
```

2.2.b · Environmental vulnerabilities (power, HVAC, fire, water)

3 pts · auto-graded on the site

Coding problem 2.2.b: Environmental sensor triage

Skill: Analyze Risk · **Maps to:** 2.2.A · **Language:** Python 3 (pytest)

Problem

A data center streams readings from environmental sensors placed around each server room: power (voltage as a percent of nominal), temperature (Celsius), humidity (percent relative humidity), smoke detectors, and water/flood detectors. Facilities staff need every reading automatically triaged into a severity level so a human only has to look at what matters.

Your task is to write a function `solve(data)` that takes a list of sensor readings and returns a dictionary mapping each reading's `id` to a severity string: `"NORMAL"`, `"WARNING"`, or `"CRITICAL"`.

Per-reading thresholds (by `type`)

`power` (`value` = supply voltage as a percent of nominal, 100 = nominal):

- `CRITICAL` if `value == 0` (total outage) or `value < 90` or `value > 110`
- `WARNING` if `90 <= value < 95` or `105 < value <= 110`
- `NORMAL` otherwise (`95 <= value <= 105`)

`temperature` (`value` = degrees Celsius):

- `CRITICAL` if `value > 30`
- `WARNING` if `27 < value <= 30` or `value < 15`
- `NORMAL` otherwise (`15 <= value <= 27`)

`humidity` (`value` = percent relative humidity):

- `CRITICAL` if `value > 70` or `value < 20`
- `WARNING` if `60 < value <= 70` or `20 <= value < 40`
- `NORMAL` otherwise (`40 <= value <= 60`)

`smoke` (`value` = detector reading, `0` = clear, any positive value = smoke detected):

- `CRITICAL` if `value > 0`
- `NORMAL` otherwise

`water` (`value` = detector reading, `0` = dry, any positive value = moisture detected):

- `CRITICAL` if `value > 0`
- `NORMAL` otherwise

Combined-signal escalation (cooling-failure pattern) After computing each reading's per-reading severity above, apply one escalation rule: for readings that share the same `room`, if there is **both** a `temperature` reading rated `WARNING` or `CRITICAL` **and** a `humidity` reading rated `WARNING` or `CRITICAL` in that same room, escalate *both* of those specific readings (temperature and humidity only) to `CRITICAL`. This models a failing HVAC unit, where rising temperature and drifting humidity together are a stronger signal than either alone. Other reading types in the room (power, smoke, water) are not affected by this rule, and a room where only one of the two (temperature or humidity) is elevated is not escalated.

Function contract

Implement `solve(data: list[dict]) -> dict[str, str]` in `starter.py`.

Input

A list of dictionaries, each representing one sensor reading:

```
[
    {"id": "s1", "room": "server-room-a", "type": "temperature", "value": 29},
    {"id": "s2", "room": "server-room-a", "type": "humidity", "value": 65},
    {"id": "s3", "room": "server-room-b", "type": "power", "value": 100},
]
```

Output

A dictionary mapping each reading's `"id"` to its severity string:

```
{
    "s1": "CRITICAL",   # escalated: room also had a humidity WARNING/CRITICAL
    "s2": "CRITICAL",   # escalated: room also had a temperature WARNING/CRITICAL
    "s3": "NORMAL",
}
```

Constraints

- `type` is one of `"power"`, `"temperature"`, `"humidity"`, `"smoke"`, `"water"`.
- `value` is a non-negative number (float or int) except `power`, which may be `0` (outage).
- Pure function, deterministic, standard library only.

How to run

```
cd problem && python -m pytest tests.py -q
```

Reference solution:

```
def _power_severity(value: float) -> str:
    if value == 0 or value < 90 or value > 110:
        return "CRITICAL"
    if (90 <= value < 95) or (105 < value <= 110):
        return "WARNING"
    return "NORMAL"


def _temperature_severity(value: float) -> str:
    if value > 30:
        return "CRITICAL"
    if (27 < value <= 30) or value < 15:
        return "WARNING"
    return "NORMAL"


def _humidity_severity(value: float) -> str:
    if value > 70 or value < 20:
        return "CRITICAL"
    if (60 < value <= 70) or (20 <= value < 40):
        return "WARNING"
    return "NORMAL"


def _binary_severity(value: float) -> str:
    return "CRITICAL" if value > 0 else "NORMAL"


_RANK = {"NORMAL": 0, "WARNING": 1, "CRITICAL": 2}


def solve(data: list[dict]) -> dict[str, str]:
    severities: dict[str, str] = {}
```

```
    for reading in data:
        rid = reading["id"]
        rtype = reading["type"]
        value = reading["value"]

        if rtype == "power":
            severities[rid] = _power_severity(value)
        elif rtype == "temperature":
            severities[rid] = _temperature_severity(value)
        elif rtype == "humidity":
            severities[rid] = _humidity_severity(value)
        elif rtype in ("smoke", "water"):
            severities[rid] = _binary_severity(value)
        else:
            severities[rid] = "NORMAL"

    rooms: dict[str, dict[str, list[str]]] = {}
    for reading in data:
        room = reading["room"]
        rtype = reading["type"]
        if rtype in ("temperature", "humidity"):
            rooms.setdefault(room, {}).setdefault(rtype, []).append(reading["id"])

    for room, by_type in rooms.items():
        temp_ids = by_type.get("temperature", [])
        hum_ids = by_type.get("humidity", [])
        temp_elevated = any(_RANK[severities[i]] >= _RANK["WARNING"] for i in temp_ids)
        hum_elevated = any(_RANK[severities[i]] >= _RANK["WARNING"] for i in hum_ids)
        if temp_elevated and hum_elevated:
            for i in temp_ids:
                if _RANK[severities[i]] >= _RANK["WARNING"]:
                    severities[i] = "CRITICAL"
            for i in hum_ids:
                if _RANK[severities[i]] >= _RANK["WARNING"]:
                    severities[i] = "CRITICAL"

    return severities
```

2.2.c · Device theft and tampering

3 pts · auto-graded on the site

Coding problem 2.2.c: Device theft/tampering incident triage

Skill: Analyze Risk · **Maps to:** 2.2.B, 2.2.C · **Language:** Python 3 (pytest)

Problem

The IT security team receives reports whenever a device is reported stolen or found to show signs of tampering. Each report needs to be triaged into a risk level so the team knows what needs an immediate incident response versus what can be logged and monitored.

Your task is to write a function `solve(data)` that takes a list of incident reports and returns a dictionary mapping each incident's `id` to a risk level: `"LOW"`, `"MEDIUM"`, or `"HIGH"`.

Rules, by incident `type`

`type == "theft"` (a device was physically taken): 1. `"HIGH"` if the device was **not** encrypted (`encrypted` is `False`), an unencrypted stolen device exposes its data with no cryptographic barrier. 2. `"MEDIUM"` if the device **was** encrypted, but `contains_sensitive_data` is `True` **and** `hours_since_check` is greater than 48, encryption protects the data, but a long detection delay on a sensitive device still raises risk (e.g., the device may have been unlocked and in active use when taken). 3. `"LOW"` otherwise.

`type == "tampering"` (a device was found to show signs of covert alteration): 1. `"HIGH"` if the tamper-evident seal was **not** intact (`seal_intact` is `False`), physical evidence the enclosure was opened. 2. `"MEDIUM"` if the seal **was** intact but `hours_since_check` is greater than 48, a long window since the last inventory check means tampering that does not require opening the enclosure (e.g., a rogue USB implant) could have gone unnoticed even with an intact seal. 3. `"LOW"` otherwise.

Any other `type` value should be treated as `"LOW"`.

Function contract

Implement `solve(data: list[dict]) -> dict[str, str]` in `starter.py`.

Input

A list of dictionaries, each representing one incident report:

```
[
    {
        "id": "inc-1",
        "type": "theft",
        "encrypted": False,
        "seal_intact": True,
        "contains_sensitive_data": True,
        "hours_since_check": 10,
    },
    {
        "id": "inc-2",
        "type": "tampering",
        "encrypted": True,
        "seal_intact": False,
        "contains_sensitive_data": False,
        "hours_since_check": 5,
    },
]
```

Every report includes all five fields (`type`, `encrypted`, `seal_intact`, `contains_sensitive_data`, `hours_since_check`), even if a field is not relevant to that report's `type` (e.g., `seal_intact` is present but ignored for `type == "theft"`).

Output

A dictionary mapping each incident's `"id"` to its risk level string:

```
{
    "inc-1": "HIGH",
    "inc-2": "HIGH",
}
```

Constraints

- `type` is `"theft"` or `"tampering"` (or, in hidden tests, possibly another string that must default to `"LOW"`).
- `encrypted`, `seal_intact`, `contains_sensitive_data` are booleans.
- `hours_since_check` is a non-negative number (int or float).
- Pure function, deterministic, standard library only.

How to run

```
cd problem && python -m pytest tests.py -q
```

Reference solution:

```
def _theft_risk(incident: dict) -> str:
    if not incident["encrypted"]:
        return "HIGH"
    if incident["contains_sensitive_data"] and incident["hours_since_check"] > 48:
        return "MEDIUM"
    return "LOW"


def _tampering_risk(incident: dict) -> str:
    if not incident["seal_intact"]:
        return "HIGH"
    if incident["hours_since_check"] > 48:
        return "MEDIUM"
    return "LOW"


def solve(data: list[dict]) -> dict[str, str]:
    results = {}
    for incident in data:
        rid = incident["id"]
        itype = incident["type"]
        if itype == "theft":
            results[rid] = _theft_risk(incident)
        elif itype == "tampering":
            results[rid] = _tampering_risk(incident)
        else:
            results[rid] = "LOW"
    return results
```