

Technologies and Web Programming

Web Application Architectures

Overview



- Data Independence in Databases
- N-Tier Architectures
- Design Patterns
 - The MVC Design Pattern




Web Application Architectures


Data Independence in Databases

Database Architecture and Views





Logical and Physical Independence



Each level is independent of the levels below

Data Independence



Physical Independence

- The ability to change the internal schema without changing the conceptual schema
 - Storage space can change
 - Type of some data can change for reasons of optimization

Logical Independence

- The ability to change the conceptual schema without changing the views or application programs
 - Can add new fields, new tables without changing views
 - Can change structure of tables without changing view

Data Independence



- Main Lesson to Learn
 - Keep the VIEW
 - what the user sees
 - Independent from
 - The MODEL
 - domain knowledge



Web Application Architectures

N-Tier Architectures


Significance of "Tiers"



- N-Tier architectures have the same layers
 - Presentation
 - Business/Logic
 - Data
- N-Tier architectures try to separate the layers into different tiers
 - Layer: logical separation
 - Tier: physical separation

1-Tier Architecture






- All 3 layers are on the same machine
 - All code and processing kept on a single machine
- Presentation, Logic, Data layers are tightly connected
 - Scalability: Single processor means hard to increase volume of processing
 - Portability: Moving to a new machine may mean rewriting everything
 - Maintenance: Changing one layer requires changing other layer

2-Tier Architecture






- Database runs on Server
 - Separated from client
 - Easy to switch to a different database
- Presentation and logic layers still tightly connected
 - Heavy load on server
 - Potential congestion on network
- Presentation still tied to business logic

3-Tier Architecture






- Each layer can potentially run on a different machine
- Presentation, logic, and data layers are disconnected

A Typical 3-tier Architecture






Architecture Principles

- Client-server architecture
- Each layer (Presentation, Logic, Data) should be independent and should not expose dependencies related to the implementation
- Unconnected layers should not communicate
- Changes in a platform affects only the layer running on that particular platform

A Typical 3-tier Architecture (ii)






Presentation Layer

- Provides user interface
- Handles the interaction with the user
- Sometimes called the GUI, client view or front-end
- Should not contain business logic or data access code

A Typical 3-tier Architecture (iii)






Logic Layer

- The set of rules for processing information
- Can accommodate many users
- Sometimes called middleware/back-end
- Should not contain presentation or data access code

A Typical 3-tier Architecture (iv)





Data Layer

- The physical storage layer for data persistence
- Manages access to DB or file system
- Sometimes called back-end
- Should not contain presentation or business logic code

The 3-Tier Architecture for Web Apps



- Presentation Layer
 - Static or dynamically generated content rendered by the browser (front-end)
- Logic Layer
 - A dynamic content processing and generation level application server, e.g., Java EE, ASP.NET, Python Django Framework (middleware)
- Data Layer
 - A database, comprising both data sets and the database management system or RDBMS software that manages and provides access to the data (back-end)

3-Tier Architecture – Advantages



Independence of Layers

- Easier to maintain
- Components are reusable
- Faster development (division of work)
 - Web designer does presentation
 - Software engineer does logic
 - DB admin does data model



Web Application Architectures

Design Patterns

Design Problems & Decisions



- Construction and testing
 - how do we build a web application?
 - what technology should we choose?
- Re-use
 - can we use standard components?
- Scalability
 - how will our web application cope with large numbers of requests?
- Security
 - how do we protect against attack, viruses, malicious data access, denial of service?
- Different data views
 - user types, individual accounts, data protection

Need for general and reusable solution: **Design Patterns**.

What is a Design Pattern?




- A general and reusable solution to a commonly occurring problem in the design of software
- A template for how to solve a problem that has been used in many different situations
- NOT a finished design
 - The pattern must be adapted to the application
 - Cannot simply translate into code

Origin of Design Pattern?



- Architectural concept by Christopher Alexander (1977/79)
- Adapted to OO Programming by Beck and Cunningham (1987)
- Popularity in CS after the book:

 "Design Patterns: Elements of Re-useable
 Object Oriented Software", 1994.
 Erich Gamma, Richard Helm,
 Ralph Johnson, John Vlissides
- Now widely-used in software engineering





Web Application Architectures

The MVC Design Pattern

Design Problem



- Need to change the look-and-feel without changing the core/logic
- Need to present data under different contexts (e.g., powerful desktop, web, mobile device).
- Need to interact with/access data under different contexts (e.g., touch screen on a mobile device, keyboard on a computer)
- Need to maintain multiple views of the same data (list, thumbnails, detailed, etc.)


Design Solution



- Separate core functionality from the presentation and control logic that uses this functionality
- Allow multiple views to share the same data model
- Make supporting multiple clients easier to implement, test, and maintain

The Model-View-Controller Pattern

- Design pattern for graphical systems that promotes separation between model and view
- With this pattern the logic required for data maintenance (database, text file) is separated from how the data is viewed (graph, numerical) and how the data can be interacted with (GUI, command line, touch)



The MVC Pattern



Model


- manages the behavior and data of the application domain
- responds to requests for information about its state (usually from the view) follows instructions to change state (usually from the controller)

View

 renders the model into a form suitable for interaction, typically a user interface (multiple views can exist for a single model for different purposes)

Controller

- receives user input and initiates a response by making calls on model objects
- accepts input from the user and instructs the model and viewport to perform actions based on that input



The MVC Pattern (in practice)



Model

- Contains domain-specific knowledge
- Records the state of the application
 - E.g., what items are in a shopping cart
- Often linked to a database
- Independent of view
 - One model can link to different views

View

- Presents data to the user
- Allows user interaction
- Does no processing

Controller

- defines how user interface reacts to user input (events)
- receives messages from view (where events come from)
- sends messages to model (tells what data to display TPW

The MVC for Web Applications



Model

- database tables (persistent data)
- session information (current system state data)
- rules governing transactions

View

- (X)HTML
- CSS style sheets
- server-side templates

Controller

- client-side scripting
- http request processing
- business logic/preprocessing

MVC Advantages



- Clarity of Design
 - model methods give an API for data and state
 - view and controller design is easier
- Efficient Modularity
 - any of the components can be easily replaced
- Multiple Views
 - many views can be developed as appropriate
 - each uses the same API for the model
- Easier to Construct and Maintain
 - simple (text-based) views while constructing
 - more views and controllers can be added
 - stable interfaces ease development
- Distributable

3-Tier Architecture vs. MVC Pattern

Communication

- 3-Tier: The presentation layer never communicates directly with the data layer – but, only through the logic layer (linear topology)
- MVC: All layers communicate directly (triangle topology)

Usage

- 3-Tier: Is used in web applications where the client, middleware and data tiers ran on physically separate platforms
- MVC: Historically used on applications that run on a single graphical workstation
 - In a Web Application context, however, its logical components can be decoupled to comply with a true 3-tier architecture