

Large Kernel Spectral and Spatial Attention Networks for Hyperspectral Image Classification

Genyun Sun^{1b}, Senior Member, IEEE, Zhaojie Pan, Aizhu Zhang^{2b}, Member, IEEE, Xiuping Jia^{3b}, Fellow, IEEE, Jinchang Ren^{4b}, Senior Member, IEEE, Hang Fu, and Kai Yan

Abstract—Currently, long-range spectral and spatial dependencies have been widely demonstrated to be essential for hyperspectral image (HSI) classification. Due to the transformer superior ability to exploit long-range representations, the transformer-based methods have exhibited enormous potential. However, existing transformer-based approaches still face two crucial issues that hinder the further performance promotion of HSI classification: 1) treating HSI as 1-D sequences neglects spatial properties of HSI and 2) the dependence between spectral and spatial information is not fully considered. To tackle the above problems, a large kernel spectral–spatial attention network (LKSSAN) is proposed to capture the long-range 3-D properties of HSI, which is inspired by the visual attention network (VAN). Specifically, a spectral–spatial attention module (SSAM) is first proposed to effectively exploit discriminative 3-D spectral–spatial features while keeping the 3-D structure of HSI. This module introduces the large kernel attention (LKA) and convolutional feed-forward (CFF) to flexibly emphasize, model, and exploit the long-range 3-D feature dependencies with lower computational pressure. Finally, the features from the SSAM are fed into the classification module for the optimization of 3-D spectral–spatial representation. To verify the effectiveness of the proposed classification method, experiments are executed on four widely used HSI datasets. The experiments demonstrate that LKSSAN is indeed an effective way for long-range 3-D feature extraction of HSI.

Index Terms—Convolutional feed-forward (CFF), deep learning (DL), hyperspectral image (HSI) classification, large kernel attention (LKA), long-range 3-D spectral–spatial feature extraction, spectral–spatial attention.

Manuscript received 30 May 2022; revised 29 May 2023; accepted 25 June 2023. Date of publication 10 July 2023; date of current version 29 August 2023. This work was supported in part by the National Natural Science Foundation of China under Grant 42371350, Grant 41971292, and Grant 42271347; and in part by the National Key Research and Development Program under Grant 2019YFE0126700. (Corresponding author: Kai Yan.)

Genyun Sun is with the College of Oceanography and Space Informatics, China University of Petroleum (East China), Qingdao 266580, China, and also with the Laboratory for Marine Mineral Resources, Qingdao National Laboratory for Marine Science and Technology, Qingdao 266237, China (e-mail: genyunsun@163.com).

Zhaojie Pan and Hang Fu are with the College of Oceanography and Space Informatics, China University of Petroleum (East China), Qingdao 266580, China (e-mail: panzhj99@163.com; hangf_upc@163.com).

Aizhu Zhang is with the College of Oceanography and Space Informatics, China University of Petroleum (East China), Qingdao 266580, China, and also with the Key Laboratory of Poyang Lake Wetland and Watershed Research, Jiangxi Normal University, Ministry of Education, Nanchang 330022, China (e-mail: zhangaizhu789@163.com).

Xiuping Jia is with the School of Engineering and Information Technology, The University of New South Wales at Canberra, Canberra, ACT 2600, Australia (e-mail: x.jia@adfa.edu.au).

Jinchang Ren is with the National Subsea Centre, Robert Gordon University, AB21 0BH Aberdeen, U.K. (e-mail: jinchang.ren@ieee.org).

Kai Yan is with the Faculty of Geographical Science, Beijing Normal University, Beijing 100875, China (e-mail: kaiyan.earthscience@gmail.com). Digital Object Identifier 10.1109/TGRS.2023.3292065

I. INTRODUCTION

HYPERSPECTRAL images (HSIs) contain hundreds of continuous and narrow spectral bands. Such valuable information can precisely characterize the physical properties and bring great convenience for land object recognition [1]. These characteristics have enabled HSI to be widely applied in environmental protection [2], land-cover mapping [3], and urban development monitoring [4]. HSI classification is one of the most critical tasks in these applications.

Over the few years, various methods have been developed for HSI classification. The earlier classification methods mainly focus on spectral features, i.e., support vector machine (SVM) [5], multiple regression (MLR) [6], and k-nearest neighbors [7]. However, the high dimensionality with a small number of labeled samples may lead to the Hughes phenomenon [8], which usually causes overfitting [9]. Feature selection [10] and feature extraction [11] are persuasive to alleviate these problems. Nevertheless, an increasing number of studies have demonstrated that it is challenging to distinguish confusing objects only utilizing spectral information [12], [13]. Meanwhile, the spatial context of HSI provides complementary features to their abundant spectral correlations for precise recognition [14]. Thus, effectively exploiting spatial and spectral information is essential for HSI classification. The traditional spectral and spatial feature extraction methods are partitioned into two categories [15]: spectral plus spatial feature extraction methods and spectral–spatial feature extraction methods. For spectral plus spatial feature extraction, numerous spatial algorithms, such as morphological operators [16], Gabor filters [17], hypergraph structure [18], and Markov random fields (MRFs) [19], were employed to extract spatial features. However, the feature-stacking-based methods lead to information redundancy, causing overfitting of classification models [20]. For spectral–spatial feature extraction, spectral and spatial information are jointly exploited to keep the most discriminative features for HSI classification. The typical methods include 3-D discrete wavelets [21], 3-D scattering wavelets [22], and 3-D Gabor filters [23]. Nevertheless, these traditional methods extract the features of the original data in a shallow manner, which is hard to dig deep nonlinear spectral–spatial correlation information [24].

Compared with the traditional feature extraction, deep learning (DL) can extract more abstract and discriminative features and has been widely used in HSI classification. Recurrent neural networks (RNNs) [25], autoencoders (AEs) [26],

deep belief networks (DBNs) [27], fully convolutional networks (FCNs) [28], [29], and convolutional neural networks (CNNs) [30] are the mainstream DL architectures. Among these methods, patch-based CNN is the most popular framework, mainly because it elegantly integrates spectral features with spatial-contextual information from HSI data in its unique local connection. Note that patch-based methods may face problems such as multiple computations and insufficient global information mining. Fortunately, their advantages in the following three aspects allow them to remain in the mainstream.

- 1) Local feature mining is more convenient. The features related to classification performance mainly exist locally, and spatial partitioning helps to reduce the interference of redundant information.
- 2) Sample production is more convenient. The model can be optimized based on point samples, which considerably reduces the sample production time in practical applications.
- 3) The model is more flexible. The end-to-end model is not suitable for the problems of scale diversity and high spatial heterogeneity, while the patch-based method can improve the migration of the model in different geographical environments with different patch sizes.

In recent decades, numerous CNN-based methods have made prosperous progress in HSI classification. In [31], CNNs were used to extract hierarchical deep spatial features. Lee and Kwon [32] introduced a 3-D convolutional network (3DCNN) to explore local spectral-spatial contextual interactions simultaneously. While the CNNs enhanced the performance of methods, the extraction of spatial and spectral features is still insufficient. Hence, Xu et al. [33] designed a dual-tunnel CNN in which 1-D convolutional network (1DCNN) was employed to exploit the spectral features, and 2-D convolutional network (2DCNN) was comprised to highlight the spatial characteristic. Li et al. [34] proposed an automatic clustering-based two-branch network to extract spectral and spatial features. However, the methods based on dual-tunnel or two-branch do not meet the characteristics of HSI spectral-spatial integration and thus inherently overlook the ample spectral-spatial correlation information. To resolve these issues, 3-D spectral-spatial feature extraction is required to reveal the 3-D inherent structure of HSI [35]. Zhong et al. [36] designed an end-to-end spectral-spatial residual network (SSRN) that takes raw 3-D cubes as input data and introduced residual connections [37] for HSI classification. Sellami et al. [38] combined band clustering based on spectral clustering with 3DCNN to find informative and distinctive spectral-spatial features. Jia et al. [39] adopted spectral-spatial Schrodinger eigenmaps (SSSE) and dual-scale convolution to obtain the joint spatial-spectral correlation information.

However, the aforementioned-based CNN methods treat local features equally, which is easy to cause the loss of crucial information. Fortunately, the attention mechanism can alleviate this issue since it can adaptively capture salient parts through constructing the weight map. In [40], a squeeze-and-excitation network (SEnet) was constructed to recalibrate channelwise

feature responses. Based on this structure, spectral attention classification networks were developed and obtained favorable applications [41], [42]. In [43], a convolutional block attention module (CBAM) was proposed, which can learn channel dependencies and spatial connections by spectral and spatial weights. Inspired by CBAM, Ma et al. [44] proposed the double-branch multiattention mechanism network (DBMA) to excavate the spectral and spatial information. Pu et al. [45] developed a learnable spectral-spatial attention module (SSAM) to focus on spectral-spatial correlations. Nevertheless, SENet and CBAM do not fully consider the long-range correlation over local spectral and spatial features. Therefore, a dual attention network (DAN) [46] was proposed, which can effectively mitigate the problem through channel and spatial self-attention modules. Subsequently, [47], [48], and [49] introduced self-attention to set various weights for extracted long-range spectral-spatial features.

Transformer [50] is a new self-attention-based network and further enhances performance with its remarkable capability of exploiting long-range features. In [51], a transformer was applied for the first time in the HSI classification task. Xue et al. [52] proposed a local transformer with a spatial partition restore network (SPRLT-Net) to model locally detailed spatial discrepancies. Similarly, Sun et al. [53] constructed a spectral-spatial feature tokenization transformer (SSFTT) method to capture spectral-spatial features and high-level semantic features. More recently, Yang et al. [54] developed an interactive learning framework to achieve multiscale, detail-aware, and space-interactive classification based on different transformer structures. Although the abovementioned transformer-based approaches have made many efforts for long-range spectral-spatial features extraction and gain better performance, there are still two crucial obstacles that can be summarized: 1) treating HSI as 1-D sequences inevitably neglects 3-D properties of HSI and 2) the dependence between spectral and spatial information is not fully considered.

To address these two limitations, we propose the following three strategies.

- 1) We use large kernel 3-D convolution to extract spectral and spatial features while maintaining the HSI 3-D structure. Compared with the transformer-based methods, the method is more facilitated to exploit the spectral-spatial correlation characterization and can still effectively leverage long-range dependencies.
- 2) Large kernel convolution causes a massive computational burden. Therefore, we introduce convolutional decomposition to alleviate this problem.
- 3) The transformer-based methods can adaptively extract salient features by attention mechanism. Hence, we design an attention structure to enhance vital information. Unlike the existing attention mechanism, this structure is encapsulated in a large kernel 3DCNN and can more effectively exploit the long-range spectral-spatial dependencies, which is more in line with HSI.

Based on the above strategies, we proposed a patch-based large kernel spectral-spatial attention network (LKSSAN) to capture long-range 3-D spectral-spatial features, which is

inspired by a visual attention network (VAN) [55]. LKSSAN first uses principal component analysis (PCA) to reduce the HSI spectral dimension, followed by image segmentation to generate 3-D patches as the input of the model. Then, the SSAM and classification module are designed to exploit long-range 3-D features and generate labels for patch center pixels, respectively. The SSAM follows a modular design, and the basic module is composed of a scale expansion block, several hybrid blocks, and a layer normalization. The hybrid block is the main feature processing structure of LKSSAN and contains two core operations, large kernel attention (LKA) and convolutional feed-forward (CFF). LKA captures long-range spectral-spatial characters by large kernel convolution with a 3-D spectral-spatial attention mechanism. The CFF integrates the 3-D features along the spatial and spectral dimensions by employing multilayer perceptron (MLP) and depthwise convolution. Both LKA and CFF take the 3-D patch as input, which makes the SSAM easy to exploit 3-D spectral-spatial feature associations, thus improving the performance of the feature extraction. The classification module is a specially designed simple MLP (SMLP), which can take advantage of the features extracted by the SSAM to complete high-precision HSI classification. The three major contributions of this article are listed as follows.

- 1) An LKSSAN is proposed to extract the long-range 3-D properties of HSI. In this model, the SSAM and classification module are adopted to emphasize, exploit, and distinguish the long-range spectral-spatial features with lightweight structures, thus relieving the problems of the 3-D feature utilization.
- 2) Inspired by VAN, the SSAM integrates the attention mechanism and convolutional decomposition into large kernel 3DCNN to exploit long-range dependencies. To further explore the 3-D characterization, the module simultaneously introduces the CFF. With this structure, 3-D properties can be fully identified with a lower computational burden, which is more suitable for high spatial and spectral resolution 3-D HSI.
- 3) To promote SSAM performance, a patch-based sampling strategy and a classification module are designed to generate 3-D image patches and the labels of land cover. The patch-based sampling strategy helps excavate local spatial and spectral information. The classification module can be perfectly integrated with the SSAM and thus effectively aggregate and classify features.

The remainder of this article is organized as follows. The related works of the proposed method are presented in Section II. In Section III, we describe the proposed method in detail. The experiments and results are presented and discussed in Section IV. Finally, concluding remarks are provided in Section V.

II. RELATED WORKS

In this section, we will provide a brief introduction to patch-based CNN, attention mechanism, and the VAN, which are also the crucial techniques of the proposed methods.




Fig. 1. Patch-based CNN and pixel-based CNN.




Fig. 2. Overview of currently well-recognized attention models for the HSI classification task, such as: (a) SENet [40]; (b) CBAM [43]; (c) DAN [46]; and (d) transformer [50].

A. Patch-Based CNN

Based on the input method of HSI data, CNNs mainly have two structures: patch-based CNNs and pixel-based CNNs. The comparison of the patch-based and pixel-based methods is shown in Fig. 1. Patch-based CNNs handle images as a multidimensional input, instead of a single vector and consider the spatial contexts of image pixels explicitly. To facilitate the utilization of spatial information, it uses HSI patches to assist pixel classification.

Specifically, let $F \in R^{H \times W \times C}$ as the HSI for classification, where H , W , and C denote the length, the width, and the number of bands of F , respectively. Denote the patch size is w , then F is decomposed into some image patches, which number is $H \times W$, and the data patch can be represented as $X \in R^{w \times w \times c}$, where $w \times w$ denotes the size of patch and c denotes the number of bands. After that, the data cube is input into the CNN model for extracting spectral and spatial information and classification. Finally, the model output tensor $T \in R^{1 \times s}$, $T = [t_1, t_2, \dots, t_i, \dots, t_{s-1}, t_s]$, where s represents the total number of categories in the dataset. If the index corresponds to the largest data in the T is i , the classification of the label of center pixel of the patch is i .

B. Attention Mechanism

The attention mechanism originated in computer vision, embedding it into the network can promote the representation capacity of the critical features, and Fig. 2 exhibits the existing mainstream attention structure. Attention models can be divided into spectral attention models and spatial attention models. SENet [40] is the typical representative of the spectral attention model, which can enhance crucial

information on spectral dimension through spectral weight maps. The spatial attention models are often combined with spectral attention structures, and the typical models include a CBAM [43] and DAN [46]. CBAM first uses spectral attention to enhance the critical HSI spectral information and then uses spatial attention to exploit the spatial correlation. DAN is a two-branch structure, including a channel attention module (CAM) and position attention module (PAM), which can complete spectral attention and spatial attention, respectively. The association between long-range spectral features helps improve the classification effect, and transformer [50] is better at processing the features than the state-of-the-art attention networks.

The attention models mentioned above have been widely applied in HSI classification [54], but they cannot achieve 3-D spectral-spatial attention. The main reason for this situation is that the existing attention structures have a series of deficiencies as follows.

1) *Spectral Attention Models*: As an early attention architecture, spectral attention can describe long-range dependencies and boost the discriminability of spectral features, which can enhance the critical spectral information for classification. However, these models have not taken full consideration of the discriminative spatial features, which limits their further development in HSI classification.

2) *Spectral-Spatial Attention Models*: Unlike spectral attention models, these models combining spectral and spatial attention can facilitate methods to exploit spectral and spatial information. Nevertheless, none of these models can achieve 3-D spectral-spatial attention information. For instance, CBAM processes the spectral and spatial features in turn, and DAN exploits spectral and spatial contextual through parallel subnetworks. They all ignore the inherent spectral-spatial correlation information in HSI, which does not meet the characteristics of HSI spectral-spatial integration.

3) *Transformer-Based Models*: These methods can excavate the associated information in long-range data and have an advantage in processing HSI data. However, because the transformer originated from NLP, its block idea destroys the spatial structure of HSI.

In summary, none of the mainstream attention-based networks for HSI classification are compatible with the spectral-spatial unity while extracting image features. Therefore, they inherently overlook long-range 3-D dependencies regardless of how to combine the spectral and spatial attention structures or what structures of the transformer are employed to mine the image features.

C. Attention Mechanism

VAN is a novel attention-based model that can simultaneously enhance spatial and channel information through a 3-D attention map built by large kernel convolution in visual tasks. VAN has a simple hierarchical structure, as overviewed of VAN, as shown in Fig. 3. The basic block of VAN first performs downsampling, then, feature extraction is completed through LKA and CFF [56], and the last step is layer normalization. LKA and CFF are the core modules of VAN. Large kernel convolution means that the computational burden of




Fig. 3. Original VAN consists of four stages, the scale of the feature map is compressed at each step, and finally uses the multitask head to complete different downstream tasks.

image classification will be larger. To address this problem, VAN designs a large convolution kernel decomposition method to generate spectral-spatial attention maps. VAN divides a large kernel convolution into three components: a spatial local convolution (depthwise convolution), a spatial long-range convolution (depthwise dilation convolution), and a channel convolution (1×1 convolution).

Suppose F is the input feature map, the operation of using a large convolution kernel to complete the attention can be expressed as

$$\text{Attention} = \text{conv}_{(1 \times 1, 1)}(\text{DW}_d(\text{DW}(F))) \quad (1)$$

$$F^{\text{LKA}} = \text{Attention} \otimes F \quad (2)$$

where Attention is the spectral-spatial attention map, $\text{con}(k \times k, g)$ denotes the 2-D convolution function with a kernel size of k and a group value of g , $\text{DW}_d(\cdot)$ is the depthwise dilation convolution, $\text{DW}(\cdot)$ is the depthwise convolution, and $\otimes$ denotes the elementwise product.

After the LKA, the feature map is processed by CFF. The difference between CFF and feed-forward is that a depthwise convolution is added between the 1×1 convolution and activation function, which can enhance spatial information in different channels. The processing result of the CFF can be expressed by

$$F^{\text{CFF}} = \text{conv}_{(1 \times 1, 1)}(\text{GELU}(\text{DW}(\text{conv}_{(1 \times 1, 1)}(F^{\text{LKA}})))) \quad (3)$$

where $\text{GELU}(\cdot)$ denotes an activation function called Gaussian error linear units (GELUs), and the functions that have been introduced above will not be repeated.

Nonetheless, there are still some problems in VAN that hinder its development.

- 1) For the input scale, although VAN performs outstandingly in solving the problem of natural image, it is not suitable for HSI.
- 2) For feature utilization, VAN can extract high-quality features but cannot achieve classification.

However, it is challenging to build a classifier that can fully integrate with feature extraction [57]. Hence, we introduced VAN into the patch-based model, which not only solves the scale problem but also promotes the mining of local spectral




Fig. 4. Overview illustration of the proposed LKSSAN for the HSI classification task. LKSSAN consists of two modules, i.e., SSAM and classification module, and SSAM has two core components: LKA and CFF.

and spatial information. In addition, we specially designed an SMLP classifier to directly establish the relationship between the obtained features and the classification of the center pixel of the patch.

III. LKSSAN FOR HSI CLASSIFICATION

The proposed LKSSAN is a patch-based attention HSI classification network, as shown in Fig. 4, which includes data preparation with spatial patching, SSAM, and classification module. The challenges of DL for HSI classification are: 1) it is difficult to exploit long-range 3-D features and 2) these methods that are employed to capture long-range information impose a huge computational burden on the facility. Spatial patching is introduced for generating a large number of 3-D patches to be the input of the model, which is more favorable for the model to use the local features indispensable for classification. In the SSAM, the LKA and CFF are introduced to guide the network to be more focused on the most informative long-range 3-D features of the input data, which is achieved by adaptively weighting different pixel blocks. LKA is used to emphasize spectral-spatial cohesion features with lightweight structures by progressively learning 3-D feature embedding. CFF is then introduced to adaptively aggregate the spatial and spectral dimensional features. Differing from the feed-forward in the transformer, the CFF can flexibly recover the spatial information of the semantic features. In the classification module, the 3-D feature maps with long-range spectral and spatial dependencies extracted by the SSAM are further refined and reinforced through SMLP to generate class probability maps. Apart from that, to facilitate the utilization of the spectral-spatial connections in the multilevel feature maps, a scale expansion block is used to refine the spatial and channel sizes of feature maps in the SSAM.

A. Spectral-Spatial Attention Module

It is essential to explore discriminant 3-D spectral-spatial features for more effective HSI classification. Although previous studies have applied spatial contextual information and long-range spectral correlation features for HSI classification, the correlation information between spectral and spatial features is ignored. Fortunately, 3-D spectral-spatial feature extraction can reveal the 3-D inherent structure of HSI. Hence,




Fig. 5. Flowchart of the proposed scale expansion block.

we design an SSAM that follows a modular design and can effectively extract 3-D spectral-spatial features by a scale expansion block, L_i hybrid blocks, and layer normalization, where i is the number of hybrid blocks of the i th basic block. Let $F_{in} \in R^{(2r+1) \times (2r+1) \times P}$ be the input 3-D patch, where r is the number of pixels separating the central pixel from the edge and P denotes the number of the first several principal components (PCs) selected by PCA. Each component of the basic block is described in the following.

1) *Scale Expansion Block*: To excavate spatial and spectral correlation features, we first feed the feature map into a scale expansion block to increase the number of channels and the spatial scale of patch, as shown in Fig. 5. We can see that the scale expansion block first expands the spatial scale of the patch by using the spatial depth convolution with a convolution kernel of size 2, and then, the channel convolution is used to expand the channel features of the patch. The process can be expressed vividly as follows:

$$A_i = \text{con}_{(1 \times 1, 1)}(\text{con}_{(2 \times 2, c_{i-1})}(F_{i-1})) \quad (4)$$

where $A_i \in R^{(2r+1+i) \times (2r+1+i) \times c_i}$ is the feature map after scale expansion, F_{i-1} is the output of $i-1$ th basic block, and c_{i-1} is the number of channels of F_{i-1} . When i is 1, the F_{i-1} is F_{in} . According to the above description, we can learn that the scale expansion module is simple and provides a larger feature space for subsequent feature mining. Note that although the convolution can only affect the edge features of 3Dpatch during the scale expansion, the influence range of this edge feature will be effectively expanded after the base block processing.




Fig. 6. LKA for spectral-spatial feature learning: (a) detailed structure of LKA in LKSSAN and (b) changes of feature map when using LKA.

2) *LKA for Exploiting 3-D Features*: After the scale expansion block, the A_i is used as the input of hybrid blocks, and large kernel convolution is employed to realize the spectral-spatial attention operation. Fig. 6 shows the structure of the LKA.

Specifically, the LKA first uses 1×1 convolution to improve the flexibility of the model. Next, GELU is adopted to model the nonlinear features. And then, large kernel convolution decomposition is used to obtain a 3-D spectral-spatial attention weight map $W_i \in R^{(2r+1+i) \times (2r+1+i) \times c_i}$ by calculating the spectral and spatial correlation between pixels. This process can be expressed as

$$B_i^j = \text{GELU}\left(\text{conv}_{(1 \times 1, 1)}\left(E_i^{j-1}\right)\right) \quad (5)$$

$$W_i^j = \text{conv}_{(1 \times 1, 1)}\left(\text{DW}_d\left(\text{DW}\left(B_i^j\right)\right)\right) \quad (6)$$

where E_i^{j-1} is the output of CFF of $j-1$ th hybrid block. When j is 1, the E_i^{j-1} is A_i . It can be deduced from (6) that the pixel block in each position of $B_i^j \in R^{(2r+1+i) \times (2r+1+i) \times c_i}$ has a corresponding weight value at the same position in W_i^j , and the pixel block of W_i^j can effectively establish dependencies with long-range features by adaptive weighted aggregation of convolution. Then, a weighted matrix is obtained by

$$C_i^j = B_i^j \otimes W_i^j \quad (7)$$

where $\otimes$ denotes the elementwise product, and $C_i^j \in R^{(2r+1+i) \times (2r+1+i) \times c_i}$ is the 3-D attention. According to (7), we can speculate that each pixel block of C_i^j has been fused with neighborhood features based on the same local statistical properties of convolutional modeling by weighting, which will effectively suppress high-frequency noise and reinforce the crucial long-range dependencies.

Finally, a residual connection and 1×1 convolution is performed to obtain the output of LKA $D_i^j \in R^{(2r+1+i) \times (2r+1+i) \times c_i}$. It can be expressed by

$$D_i^j = A_i^j + \text{conv}_{(1 \times 1, 1)}\left(C_i^j\right). \quad (8)$$

LKA can capture long-range relationship with slight computational cost and parameters through the decomposition of large kernel convolution. After obtaining a long-range relationship, LKA can estimate the importance of a pixel block




Fig. 7. Structures of feed-forward and convolution feed-forward: (a) feed-forward; (b) convolution feed-forward; and (c) exploded view of convolution feed-forward.

and generate a spectral-spatial attention map. As shown in Fig. 6, LKA combines the advantages of convolution and self-attention, which enable it to take the local contextual spatial information, and large receptive field into consideration and realize 3-D spectral-spatial attention. The architecture of LKA is shown in Fig. 6. It consists of two 1×1 convolution, an activation function, and a spectral-spatial attention. The output spectral-spatial features of this subnetwork are fed into CFF for further information fusion and extraction.

3) *CFF for Spectral and Spatial Features Fusion*: The mechanism of combining attention with feed-forward has been proven to be an effective strategy in transformer, which can enhance information exchange between long-range information. Unlike the transformer, the SSAM replaces feed-forward with CFF, as shown in Fig. 7.

The difference between CFF and FF is that CFF encodes the spatial information of each channel by adding depthwise convolution, which is zero-padding convolution. Therefore, the CFF operation can be expressed as

$$E_i^j = \text{con}_{(1 \times 1, 1)}\left(\text{GELU}\left(\text{DW}\left(\text{con}_{(1 \times 1, 1)}\left(D_i^j\right)\right)\right)\right) + D_i^j \quad (9)$$

where $E_i^j \in R^{(2r+1+i) \times (2r+1+i) \times c_i}$ is the output of CFF. It can be inferred from (9) that CFF realizes the weight fusion of spectral and spatial information of each pixel and capture the local continuity of the input tensor spatial dimension, by combining depthwise convolution and 1×1 convolution.

Finally, the output of the i th basic block F_i is generated by

$$F_i = \text{LN}\left(E_i^{L_i}\right) \quad (10)$$

where $\text{LN}(\cdot)$ is the layer normalization function.

B. Classification Module

After SSAM has performed sufficiently spectral-spatial feature extraction and fusion. To take full advantage of the information, we design an SMLP classifier. The SMLP consists of global average pooling and MLP, as shown in Fig. 4. The SMLP consists of global average pooling (GAP) and fully connected (FC), as shown in Fig. 4. The SMLP only contains three layers, the hidden layer is GAP, and the output layer is FC. The operation process of the SMLP can be expressed as

$$p = \text{FC}(\text{Avg}(F_4)) \quad (11)$$

$$Y = \arg \max(p) \quad (12)$$

where $F_4 \in R^{(2r+5) \times (2r+5) \times c_4}$ is the output of the SSAM, and $FC(\cdot)$ and $Avg(\cdot)$ denote the fully connected and global average pooling, respectively. The $\arg\max(\cdot)$ is the argmax function, and $p = [p_0, p_1, \dots, p_k, \dots, p_K]$, where K is the number of classes in the dataset, and p_k is the probability that the central pixel of the 3-D-patch belongs to the category k . After that, $Y \in \{0, 1, 2, \dots, K-1\}$ represents the class of the center pixel. Such a simple classifier can preserve the integrity of the acquired features, which is more helpful for the optimization of the SSAM.

During the model training, we introduce focal loss [58] to suppress the effect of sample imbalance on model training. The focal loss for multiclassification can be calculated using the following formula:

$$t_{ki} = \begin{cases} 1, & k = \hat{y}_i \\ 0, & k \neq \hat{y}_i \end{cases} \quad (13)$$

$$L = -\frac{1}{B} \sum_{i=1}^B \sum_{k=0}^{K-1} (\alpha_k \times (1 - p_k)^\gamma \times \log(p_k) \times t_{ki}) \quad (14)$$

where α_k denotes the weighting factor that is used to balance the sample distribution, γ is the focus parameter that smoothly adjusts the weight reduction rate of the simple example, and B is the batch size. The $\hat{y}_i$ denotes the truth label of the center pixel. By means of the loss function L and backpropagation algorithm [59], the model is optimized and the predicted class of each pixel is output.

IV. EXPERIMENT AND DISCUSSION

In this section, we first introduce the four HSI datasets and then describe the experimental evaluation indicators and hardware configuration. To analyze the performance of LKSSAN, we test the influence of related parameters and key modules on the accuracy of the algorithm, and finally, we will qualitatively and quantitatively analyze the performance of the proposed LKSSAN and state-of-the-art methods on the HSI datasets.

A. Datasets Description

1) *University of Houston 2018 Dataset (UH2018)*: The UH2018 is captured by the ITRES CASI 1500 sensor over the University of Houston, Houston, TX, USA, and contains 501015 labeling pixels with 20 ground-truth (GT) classes. This database consists of 601×2385 pixels, 1-m ground sampling distance (GSD), and 48 spectral bands with wavelengths ranging from 380 to 1050 nm. Table I reports the detailed pixel distributions in each class. The specific ground features of the UH2018 dataset are shown in Fig. 8.

2) *Yellow River Estuary Coastal Wetland (YRE)*: The second hyperspectral dataset was acquired by using the Gaofen-5 satellite over the Yellow River Estuary coastal wetland between Bohai Bay and Laizhou Bay. The whole image contains 740×761 pixels with 30 m per pixel resolution. The YRE coastal wetland image has eight classes with 296 spectral bands. The specific ground features of the YRE dataset are shown in Fig. 9, and the fixed number of training and testing samples is detailed in Table II.




Fig. 8. (a) False-color image. (b) Spatial distribution of GT.

TABLE I

NUMBERS OF TRAINING AND TEST SAMPLES USED IN UH2018 DATASET

No.	Land Cover Type	Train	Test	Total
1	Healthy grass	100	9395	9495
2	Stressed grass	100	31830	31930
3	Synthetic grass	100	544	644
4	Evergreen grass	100	13310	13410
5	Deciduous grass	100	4828	4928
6	Soil	100	4383	4483
7	Water	100	138	238
8	Residential	100	39405	39505
9	Commercial	100	223896	223996
10	Road	100	44844	44944
11	Sidewalk	100	32033	32133
12	Crosswalk	100	1417	1517
13	Major Thoroughfares	100	46683	46783
14	Highway	100	9782	9882
15	Railway	100	6827	6927
16	Paved Parking Lot	100	11337	11437
17	Gravel Parking Lot	100	39	139
18	Cars	100	6505	6605
19	Trains	100	5129	5229
20	Seats	100	6690	6790
Total		2000	499015	501015




Fig. 9. (a) True-color image of YRE. (b) Spatial distribution of ground truth of YRE.

TABLE II

NUMBERS OF TRAINING AND TEST SAMPLES USED IN YRE DATASET

No.	Land Cover Type	Train	Test	Total
1	Reed Marsh	45	44394	44439
2	Spartina Alterniflora	31	30687	30718
3	Water	215	214194	214409
4	Tamarix	17	16294	16311
5	Tidal Flat Reed	13	12233	12246
6	Suaeda Salsa	30	29559	29589
7	Bare Lake Beach	47	46044	46091
8	Bare Land	22	21276	21298
Total		420	414681	415101

3) *Pavia Centre Dataset (PC)*: The image was gathered by the reflective optics system imaging spectrometer (ROSIS) sensor, which covers the area of Pavia, northern Italy. The HSI cube comprises 1096×715 pixels with 102 wavelength bands in the range of 430–860 nm. As shown in Fig. 10, there exist nine different classes of land covers with a resolution of 1.3 m




Fig. 10. (a) True-color image of PC. (b) Spatial distribution of GT of PC.

TABLE III

NUMBERS OF TRAINING AND TEST SAMPLES USED IN PC DATASET

No.	Land Cover Type	Train	Test	Total
1	Water	66	65905	65971
2	Trees	8	7590	7598
3	Asphalt	4	3086	3090
4	Self-blocking bricks	3	2682	2685
5	Bitumen	7	6577	6584
6	Tiles	10	9238	9248
7	Shadows	8	7279	7287
8	Meadows	43	42783	42826
9	Bare soil	3	2860	2863
Total		152	148000	148152




Fig. 11. (a) True-color image of WH. (b) Spatial distribution of GT of WH.

per pixel. Meanwhile, the training set with few samples and test set is listed in Table III.

4) *WHU-Hi-HongHu Dataset (WH)*: The WH dataset was recorded by the Headwall Nano-Hyperspec sensor with fragmented plots and various crops. The image size in pixels is 940×475 , with a spatial resolution of 0.043 m, composed of 270 bands ranging from 400 to 1000 nm. The GT of this scene consists of 22 classes, and 0.1% samples per class were selected to train the networks, and the remaining were used for testing, as listed in Table IV. A three-band true-color composite image and the GT map are shown in Fig. 11.

B. Experimental Setup

1) *Evaluation Metrics*: To quantify the classification performance of LKSSAN, the overall accuracy (OA), average accuracy (AA), kappa coefficient (kappa), producer's accuracies (PAs) of each land-cover category, and time taken by the model to train (T) are employed as evaluation measures.

TABLE IV

NUMBERS OF TRAINING AND TEST SAMPLES USED IN WH DATASET

No.	Land Cover Type	Train	Test	Total
1	Red roof	15	14026	14041
2	Road	4	3508	3512
3	Bare soil	22	21799	21821
4	Cotton	164	163121	163285
5	Cotton firewood	7	6211	6218
6	Rape	45	44512	44557
7	Chinese cabbage	25	24078	24103
8	Pakchoi	5	4049	4054
9	Cabbage	11	10808	10819
10	Tuber mustard	13	12381	12394
11	Brassica parachinensis	12	11003	11015
12	Brassica chinensis	9	8945	8954
13	Small Brassica chinensis	23	22484	22507
14	Lactuca sativa	8	7348	7356
15	Celtuce	2	1000	1002
16	Film covered lettuce	8	7254	7262
17	Romaine lettuce	4	3006	3010
18	Carrot	4	3213	3217
19	White radish	9	8703	8712
20	Garlic sprout	4	3482	3486
21	Broad bean	2	1326	1328
22	Tree	5	4035	4040
Total		401	386292	386693

Moreover, the classification maps obtained by different models are visualized to make a qualitative comparison.

2) Comparison With State-of-the-Art Backbone Networks:

To analyze the effectiveness of LKSSAN and the performance of long-range 3-D spectral-spatial information for HSI classification, we compare LKSSAN with other existing state-of-the-art methods of various types and structures. The comparison algorithm is divided into three categories, 3-D spectral-spatial extraction, two-branch, and transformer-based structures. For the 3-D spectral-spatial extraction, we choose SSRN, multi-scale dense networks (MSDNs) [60], spectral-spatial unified networks (SSUNs) [61], and residual spectral-spatial attention network (RSSAN) [62] for comparison. For the two branches, we choose adaptive spectral-spatial multiscale network (ASSMN) [63], double-branch dual-attention mechanism network (DBDA) [49], and attention-based adaptive spectral-spatial kernel ResNet (A2S2K) [64] to analyze the effectiveness of the LKSSAN SSAM. For the transformer-based models, we use spectral-spatial transformer network (SSTN) [57] and SSFTT [53] to evaluate the performance of LKSSAN in HSI spectral-spatial features processing capability.

3) *Implementation Details*: All the experiments were implemented on Windows 10 and an 8-GB GPU of Nvidia GeForce GTX 1080. The proposed networks were carried out using the PyTorch platform as the backend. We trained the network for 200 epochs to adopt the Adam optimizer [65] with a batch size of 28 and a learning rate of 0.005. To avoid biased estimation, all experiments were conducted with five independent tests, and the average values were reported for all the evaluation metrics.

C. Model Analysis

1) *Parameter Sensitivity Analysis*: For CNN-based models, the settings of hyperparameters often have a greater impact on model accuracy. Therefore, we analyze the effect of hyperparameters on LKSSAN in this section. LKSSAN has a simple structure and does not perform complex processing on HSI. The number of PCs, the radius of the patch, the number of




Fig. 12. Effect of: (a) number of PCs; (b) size of patch; and (c) number of training samples on the classification accuracies in the four datasets.

training samples, and the combination of the value of kernel-padding-dilation on LKA are critical to the performance of LKSSAN. Note that in this article, except for the UH2018 dataset, the training sample size of each category of training samples selected in the rest of the datasets is taken as 0.1% of the total number of samples in the respective category. In different parameter sensitivity analysis experiments, we set the default values of the above parameters to 10, 4, 0.1%/100, and (7, 9, 3) when we do not specifically mention parameter settings. Next, we will analyze them in detail.

a) Effect of the number of PCs: To reduce the redundancy of the spectral information, we perform PCA on the HSI at the initial stage and select a certain number of PCs for subsequent processing. Hence, the number of PCs selected influences the performance of the model to a large extent. Fig. 12(a) displays the OA versus the number of PCs in different datasets. We can observe that except for the YRE dataset, all other datasets show a rise and then stabilization with the rise in the number of PCs. For this reason, we can simply speculate that only a small number of PCs have an impact on the model performance. In addition, the variation of OA on the YRE dataset is relatively stable which indicates that when the number of PCs is set in the range of {5, 10, 15, 20, 25, 30, 35, 40}, the impact on its performance is rather small. According to the above analysis, we finally set the number of PCs to 10 to balance the performance of the model on each dataset and reduce the operational burden.

b) Effect of the size of the patch: LKSSAN is a patch-based CNN model, which is essential for the analysis of patch size. Fig. 12(b) shows the effect of the spatial size of the patch on the OA of the proposed network. A large patch block can contain more spatial contextual information, but a too-large patch size also contains more noise, which adversely affects the spatial features analysis of the center pixel. The

key spectral-spatial information of remote sensing images mainly exists locally. Therefore, after the patch size increases to a critical value, if the patch size continues to increase, the effective information will not increase, and the accuracy will be reduced due to excessive redundant information. Note that the variation of OA in the PC dataset does not conform to the trend of OA in other datasets; instead, it gradually decreases with the increase of patch size in the higher accuracy range. This result further confirms that the perceptual field of the model is not as large as possible, and the images with different resolutions and different scenes are suitable for different patch scales. In Fig. 12(b), it is clear that the 12, 10, 2, and 16 patch sizes lead to the best results on UH2018, YRE, PC, and WH datasets, respectively. After that, the network performance starts to decrease on these four datasets. Therefore, in the following experiments, the patch size is set to 12, 10, 2, and 16 for UH2018, YRE, PC, and WH datasets, respectively.

c) Effect of the training percent: Few shot is an important problem for HSI classification models, and the change in the number of training samples often has a huge impact on the model. Therefore, we analyzed the LKSSAN accuracy under different number of training samples. In this article, 100 training samples were taken for each category in the UH2018 dataset in the quantitative analysis phase, and the training samples used in the other datasets were all obtained proportionally based on the total number of samples. Therefore, in order to keep the same sample distribution for different experiments on the same dataset, in this part, the variation range of samples for each category on the UH2018 dataset is {20, 40, 60, 80, 100, 120}, while the variation range of training samples on the other datasets is {0.05%, 0.1%, 0.2%, 0.5%, 1%, 2%}. Fig. 12(c) shows the performance on different number of training samples. According to the experimental results, we can know that in the simple scenario of the PC dataset, the OA of the model can be better than 95% by relying on 0.05% of the training percent. In YRE and PC datasets, if the accuracy is better than 95%, only 1% of the training samples are needed. In addition, the model can achieve better than 70% performance in the UH2018 dataset when only 40 samples of each type are taken, which indicates that the model has a vigorous ability to resist the imbalance of sample distribution. However, the performance on the UH2018 dataset with a training set of 80 is worse than that of 60, which demonstrates that the performance of the model in the small sample dataset with unbalanced sample distribution needs to be improved.

d) Effect of the kernel-padding-dilation: In LKSSAN, we introduce a convolutional decomposition, which uses depthwise convolution, depthwise dilation convolution, and 1×1 convolution instead of large kernel 3-D convolution to construct image 3-D weights. The kernel size and dilation size of the atrous convolution will directly affect the spatial perceptual field size of LKA. Therefore, in this section, we analyze the effect of different combinations of kernel, padding, and dilation on the experimental results. Table V shows the experimental results on different datasets when the kernel-padding-dilation is set to the parameters in {(5, 4, 2), (7, 6, 2), (7, 9, 3), (9, 8, 2), (9, 12, 3)}.

TABLE V

EFFECTS OF KERNEL-PADDING-DILATION ON LKA. THE BEST ONE IS SHOWN IN BOLD

Kernel-padding-dilation		5-4-2	7-6-2	7-9-3	9-8-2	9-12-3
Houston 2018 dataset	OA/%	84.07	84.80	84.06	83.64	83.85
	AA/%	74.30	85.71	73.11	72.99	74.73
	Kappa	0.7967	0.8053	0.7911	0.7926	0.7973
YRE coastal wetland dataset	OA/%	93.64	93.23	93.72	93.09	93.11
	AA/%	90.48	88.89	90.15	89.80	89.55
	Kappa	0.9085	0.9025	0.9091	0.9004	0.9004
Pavia Centre dataset	OA/%	94.93	95.70	95.61	96.26	96.43
	AA/%	87.73	90.73	88.10	92.05	90.78
	Kappa	92.79	0.9389	0.9375	0.9470	0.9494
WHU-Hi-HongHu dataset	OA/%	92.59	90.19	92.03	92.36	90.94
	AA/%	84.45	83.12	82.56	84.20	80.30
	Kappa	0.9060	0.9012	0.8991	90.34	0.8854

In this section, we set the radius of the patch to 14 to ensure the reasonableness of the experiment. According to Table V, we can intuitively see that different datasets are adapted to different parameters. The convolutional kernels corresponding to the parameters adapted to different datasets are PC, YRE, UH2018, and WH in descending order, and this order is the same as the order from small to large based on the optimal patch size of each dataset, i.e., the smaller the patch size is, the farther the long-range information is needed. This phenomenon may occur because the feature distribution presents an overall dispersion and a local aggregation in this hypothesis space; meanwhile, the larger the optimal patch size of the image, the larger the dispersion value of its spatial feature set distribution, and the smaller the dispersion value between the elements within different spatial feature sets. Although the optimal values are obtained for different scenes and data with different spatial resolutions under different combinations of kernel and dilation, the discrepancies between the results obtained in different combinations of the same dataset are relatively small. Therefore, there is no harm in eventually setting the kernel-padding-dilation to (7, 9, 3).

2) *Ablation Study*: This article proposes the LKSSAN method, and the technical contributions include: the scale expansion block to expand both spatial and spectral scales of 3-D patch; the LKA for long-range 3-D representation learning; and the CFF to assist LKA to further exploit spatial and spectral information. In this section, we investigate how these structures in the LKSSAN affect the classification performance in YRE and PC datasets. For that, we conduct extensive ablation experiments on the datasets to verify the effectiveness of these components in LKSSAN for HSI classification, and the detailed classification results with different structures are shown in Table VI. Note that data input and classification are the basic modules of LKSSAN, and the good performance of the model is the best proof for them, so we do not analyze the performance of these two modules in detail in this article.

Table VI indicates that the spatial expansion increases accuracy significantly by 1.01% of OA on the YRE dataset and by 0.5% of OA on the PC dataset. Furthermore, we can observe that the spectral expansion can improve higher accuracy compared to the spatial expansion. The aforementioned results show that although the scale expansion structure is simple, it can facilitate the model to extract spectral and spatial

TABLE VI

ABLATION ANALYSIS OF THE PROPOSED LKSSAN WITH A COMBINATION OF DIFFERENT MODULES ON THE YRE AND PC DATASETS. THE BEST ONE IS SHOWN IN BOLD

Framework	No scale expansion	No spatial expansion	No-LKA	No-CFF	3D-LKSSAN	LKSSAN
YRE coastal wetland dataset	OA/%	90.40	91.52	90.83	90.89	92.82
	AA/%	85.50	85.32	85.61	84.11	86.97
	Kappa	0.8705	0.8822	0.8812	0.8688	0.8964
Pavia Centre dataset	OA/%	94.91	97.26	96.96	96.98	97.64
	AA/%	76.51	91.10	90.58	90.74	91.58
	Kappa	0.9277	0.9653	0.9611	0.9514	0.9680
Parameter size	—	—	—	—	21.57M	0.74M

information by expanding the spectral and spatial scales of the data. Moreover, when the LKA is removed, the OA of the model is reduced by 1.7% and 0.8% on the YRE and PC datasets, respectively, which reflects the importance of joint extraction of spectral and spatial information. Meanwhile, we can notice that when LKA loses the assistance of CFF, the OA values will drop to 90.89% and 96.98%, respectively, while CFF without LKA also fails to obtain excellent performance. This indicates that LKA and CFF can achieve mutual reinforcement, which consequently justifies the combination of these two structures.

In addition, to verify the effect of convolutional decomposition on the performance of LKSSAN, we replace the weight construction part of LKA with the corresponding 3-D convolution. Since the default kernel and dilation of depthwise dilation convolution are 7 and 3, respectively, the spatial and channel kernels of the corresponding 3-D convolution are set to 19 and c_i , respectively, where c_i denotes the dimension of the feature map in the i th base module. Obviously, in the YRE dataset, the OA of LKSSAN is inferior to that of 3D-LKSSAN OA, while in the PC dataset, the OA of LKSSAN is better than that of 3D-LKSSAN. Although LKSSAN and 3D-LKSSAN have their advantages in different datasets, the mutual advantages are small or even negligible, which indicates that the convolutional decomposition can effectively replace the large kernel 3-D convolution to exploit the long-range 3-D spectral-spatial features. Moreover, Table VI presents the size of parameters required by the model when the two models take the same size of input for the PC dataset. It can be found that the size of the parameters of LKSSAN is much smaller than that of 3D-LKSSAN, which reflects that convolutional decomposition can effectively reduce the model parameters. In summary, although large kernel 3-D convolution is effective in extracting long-range 3-D features, it has high computational pressure, and the convolutional decomposition approach can maintain the model performance to the maximum while significantly reducing the number of model parameters.

D. Comparison With State-of-the-Art Methods

In this section, to evaluate the performance of LKSSAN, we qualitatively and quantitatively compare LKSSAN with other existing state-of-the-art methods. All these methods are implemented using open-source code with optimal parameters, as described in the corresponding references. Furthermore, for a fair comparison, all methods are trained and tested on the same sample number, as listed in Tables I-IV.

TABLE VII

QUANTITATIVE PERFORMANCE OF DIFFERENT CLASSIFICATION METHODS IN TERMS OF OA, AA, AND KAPPA, AS WELL AS THE ACCURACY FOR EACH CLASS ON THE UH2018 DATASET. THE BEST ONE IS SHOWN IN BOLD

Class No.	3D spectral-spatial extraction				two-branch			Transformer		LKSSAN
	SSRN	MSDN	SSUN	RSSAN	ASSMN	DBDA	A2S2K	SSTN	SSFTT	
1	79.18±2.567	71.89±2.464	93.91±0.96	62.94±0.409	92.43±1.174	79.94±2.266	81.02±2.55	67.42±7.085	63.14±6.018	61.63±2.229
2	94.83±0.594	88.3±0.653	87.22±2.251	85.81±0.637	89.29±2.616	85.52±0.818	93.45±0.629	91.35±2.005	90.91±1.589	90.13±1.129
3	97.16±1.414	58.76±9.709	100±0	48.08±16.183	100±0	81.02±18.519	83.36±5.229	79.4±13.883	63.22±25.202	94.38±6.295
4	81.77±0.983	86.34±3.719	94.85±1.117	83.31±1.972	98.48±0.643	88.16±1.596	87.52±0.658	82.32±4.016	83.94±3.309	74.31±0.854
5	49.89±8.858	34.8±4.405	90.09±2.431	32.34±3.192	98.63±1.907	91.6±2.367	49.05±5.729	17.41±1.603	56.26±7.416	59.59±2.442
6	78.92±5.524	45.53±12.531	99.13±0.515	49.92±12.102	99.84±0.204	98.61±1.177	84.84±4.002	51.72±16.541	87.56±1.583	96.56±1.513
7	88.32±4.842	26.29±16.331	100±0	6.23±2.111	100±0	100±0	64.25±4.194	26.61±22.381	84.11±17.466	57.11±9.181
8	62.32±2.147	62.26±4.683	80.41±3.85	64.57±3.429	92.79±1.28	69.78±1.321	73.24±0.76	63.93±4.406	71.99±3.934	82.65±1.111
9	98.15±0.153	97.05±0.522	60.13±1.851	95.39±0.726	73.13±1.512	94.7±0.265	98.11±0.135	97.17±0.205	98.09±0.532	98.66±0.118
10	63.03±2.675	53.99±2.406	52.48±5.741	36.83±0.82	53.63±2.645	64.22±2.213	54.51±3.031	50.75±2.945	70.91±2.992	75.54±0.486
11	56.52±0.762	47.98±3.237	46.98±7.761	40.61±1.732	55.42±2.834	54.46±1.368	54.03±2.418	55.42±1.916	50.36±4.688	47.22±0.406
12	8.48±0.989	5.1±0.485	60.21±9.503	3.1±0.389	90.48±2.075	0±0	7.82±1.039	5.08±1.276	9.11±0.643	12.25±1.169
13	76.51±1.835	59.14±3.153	45.87±7.223	50.21±1.781	64.57±1.292	61.02±0.714	70.73±2.683	67.13±3.312	81.29±1.957	83.85±0.691
14	58.7±4.663	47.91±6.60	80.86±2.639	47.51±4.296	95.4±0.734	87.22±4.398	58.8±3.514	57.24±6.068	67.08±5.603	82.3±1.457
15	91.28±2.756	59.68±17.733	98.04±1.119	53.04±2.907	99.23±0.532	83.47±2.513	83.84±3.021	46.86±5.147	96.04±1.555	97.07±2.999
16	78.2±2.591	58.6±7.044	91.07±2.74	49.28±4.069	95.62±1.964	64.66±1.022	77.93±1.914	57.41±10.165	88.16±1.959	88.33±2.599
17	54.09±18.569	2.82±1.911	100±0	2.51±1.282	100±0	0±0	12.35±6.303	4.22±2.635	29.46±10.013	17.39±7.359
18	58.67±2.086	26.89±9.566	91.28±0.856	27.02±2.374	97.52±0.804	83.11±22.554	51.33±2.142	42.72±7.004	57.24±3.686	92.38±2.962
19	69±9.934	39.16±15.726	97.71±1.538	50.06±4.857	99.86±0.114	95.40±2.059	74.96±6.851	48.47±8.473	70.77±8.519	96.96±1.592
20	75.61±3.934	51.96±9.037	97.47±1.687	55.1±5.9	100±0.007	96.69±0.924	67.07±3.784	73.6±6.085	75.67±3.616	87.48±6.53
OA (%)	78.06±0.391	58.09±1.966	65.94±0.895	61.22±1.333	72.34±1.18	81.36±0.284	77.63±0.593	67.32±2.269	80.42±1.238	84.85±0.311
AA (%)	71.03±0.579	64.52±2.028	83.89±0.267	47.12±1.746	75±0.379	73.94±0.616	65.55±0.734	54.31±1.843	69.77±2.165	74.86±0.816
kappa	0.2777±0.004	0.5131±0.014	0.5991±0.009	0.5401±0.013	0.7399±0.137	0.7592±0.168	0.7256±0.007	0.6089±0.023	0.7343±0.014	0.8085±0.004
Time/s	3203.58	1827.27	76.19	4785.74	2969.93	732.48	3983.24	3258.96	425.37	3802.39

1) *Results on the UH2018 Dataset:* The UH2018 dataset shows urban scenes with more feature classes and is mainly used to verify the performance of the model for refined classification in urban scenarios. Table VII shows the mean and standard deviation of each accuracy metric obtained by each algorithm after five experiments on the UH2018 dataset. As shown in Table VII, LKSSAN produces the best OA and kappa. Specifically, the two-branch algorithms obtain the best result among the compared algorithms, while the 3-D algorithms obtain the worst performance. In the two-branch networks, ASSMN yields the lowest OA value, but it has the highest number of optimal PAs. This phenomenon may occur because the UH2018 dataset has the same number of training samples for all types of features, which leads to it hard for ASSMN to adequately explore the characteristics of land cover with more validation samples. Among the compared algorithms, DBDA and SSFTT have higher OA values of 81.36% and 80.42%, respectively. By contrast, LKSSAN obtained the finest OA with 84.55%, which is superior to them by 3.19% and 4.13%, respectively. The three algorithms that obtain the highest AA are ASSMN, SSUN, and LKSSAN, but the OA and kappa of ASSMN and SSUN are lower, which indicates that they extracted fewer representative features. In addition, the kappa of LKSSAN is 0.8035, which achieves significant improvements ranging from 0.0473 to 0.2914. Moreover, although LKSSAN has an absolute advantage in accuracy metrics, its training time is longer, which indirectly reflects the necessity of convolutional decomposition.

Fig. 13 displays the classification maps of all methods for visual performance estimation. It can be seen that the results of MSDN, RSSAN, and A2S2K are seriously affected by noise, and the commercial misclassification phenomenon is more serious in the images of SSRN, SSUN, ASSMN, SSTN, and SSFTT. Although DBDA performs best in the comparison algorithms, its classification map shows serious confusion between paved parking lot and car. Compared with the comparison algorithms, LKSSAN obtains a smooth classification map with optimal visualization.

2) *Results on the YRE Dataset:* Among all experimental datasets, the YRE dataset has the widest spectral coverage, the




Fig. 13. Classification maps of different methods on UH2018 dataset: (a) false-color image of UH2018; (b) GT; (c) SSRN; (d) MSDN; (e) SSUN; (f) RSSAN; (g) ASSMN; (h) DBDA; (i) A2S2K; (j) SSTN; (k) SSFTT; and (l) LKSSAN.

TABLE VIII

QUANTITATIVE PERFORMANCE OF DIFFERENT CLASSIFICATION METHODS IN TERMS OF OA, AA, AND KAPPA, AS WELL AS THE ACCURACY FOR EACH CLASS ON THE YRE DATASET. THE BEST ONE IS SHOWN IN BOLD

Class No.	3D spectral-spatial extraction				two-branch			Transformer		LKSSAN
	SSRN	MSDN	SSUN	RSSAN	ASSMN	DBDA	A2S2K	SSTN	SSFTT	
1	91.41±1.721	82.43±6.428	92.95±1.966	85.08±1.356	91.14±2.788	92.64±1.027	93.39±0.906	90.84±1.801	92.89±0.408	90.57±0.375
2	95.77±1.094	91.07±2.016	94.67±1.721	91.68±3.86	94.46±2.057	91.80±0.355	95.42±1.15	97.14±1.226	95.22±1.062	97.14±0.379
3	98.61±0.397	98.2±0.957	98.78±0.367	98.41±0.341	98.72±0.285	99.61±0.044	99.34±0.142	98.95±0.2	97.97±0.219	99.29±0.061
4	81.22±4.456	62.23±7.295	73.71±2.831	67.51±4.78	68.47±9.776	89.10±1.618	84.6±0.629	81.38±9.339	74.25±3.042	84.73±0.878
5	80.85±2.467	53.22±13.759	71.8±4.818	78.8±6.463	69.53±6.337	68.16±1.2	88.83±2.728	86.93±6.308	76.54±3.201	89.49±1.806
6	79.17±2.052	55.2±7.631	72.64±5.787	71.55±2.918	77.56±5.42	84.44±1.853	77.14±1.601	71.94±9.313	77.61±0.595	85.73±1.686
7	85.4±1.342	76.69±5.844	90.83±2.417	79.11±3.554	88.14±5.595	86.89±1.669	84.91±1.285	84.03±4.437	87.37±1.03	81.58±0.959
8	94.49±2.106	81.12±5.557	93.11±2.095	86.71±3.781	88.6±6.146	96.49±0.298	95.09±1.715	96.34±1.469	91.1±0.551	90.87±0.795
OA (%)	89.36±0.004	80.29±1.792	93.03±0.216	90.04±0.591	92.34±1.237	94.04±0.002	92.97±0.302	92.67±0.817	92.64±0.276	94.39±0.240
AA (%)	88.36±0.009	86.34±1.243	86.06±0.933	82.36±1.020	84.58±3.157	86.6±0.002	89.83±0.51	88.44±1.534	86.62±0.628	90.97±0.503
kappa	0.9040±0.006	0.7527±0.014	0.8995±0.003	0.8561±0.008	0.8896±	0.9143±0.003	0.9031±0.004	0.8942±0.012	0.8951±0.408	0.9191±0.003
Time/s	4211.08	1212.23	22.54	739.81	649.45	288.20	6879.30	756.46	89.15	682.41

highest number of spectra, and the lowest spatial resolution, and is mainly used to verify the performance of the model for coastal wetland classification based on satellite images.

Table VIII shows the experimental results of each algorithm on the YRE dataset. According to Table VIII, we can find that all the algorithms obtain excellent performance on this dataset. The SSUN requires the shortest training time and its OA is 93.03%. The OA of SSRN exceeds the OA of SSUN by 0.33%, but its training time is about 200 times longer than the training time of SSUN. In the two-branch algorithms, DBDA obtains the best performance with the least training time and the best accuracy. In the transformer-based algorithms, the difference in OA between SSTN and SSFTT is smaller, but SSTN takes more training time. Although the dominant algorithms in different categories all obtain good performance, their results have large variance values and the differences in each accuracy are large. By contrast, LKSSAN obtains the optimal OA and the best kappa, which directly proves that LKSSAN can alleviate the imbalanced training data problems and indirectly reflects the advantages of the




Fig. 14. Classification maps of different methods on YRE dataset: (a) true-color image of YRE; (b) GT; (c) SSRN; (d) MSDN; (e) SSUN; (f) RSSAN; (g) ASSMN; (h) DBDA; (i) A2S2K; (j) SSTN; (k) SSFTT; and (l) LKSSAN.

TABLE IX

QUANTITATIVE PERFORMANCE OF DIFFERENT CLASSIFICATION METHODS IN TERMS OF OA, AA, AND KAPPA, AS WELL AS THE ACCURACY FOR EACH CLASS ON THE PC DATASET. THE BEST ONE IS SHOWN IN BOLD

Class No.	3D spectral-spatial extraction				two-branch			Transformer		LKSSAN
	SSRN	MSDN	SSUN	RSSAN	ASSMN	DBDA	A2S2K	SSTN	SSFTT	
1	99.99±0.006	97.81±0.514	99.85±0.162	89.31±7.058	99.91±0.083	99.98±0.05	99.98±0.026	99.94±0.062	99.79±0.14	100±0.004
2	97.3±1.128	90.91±3.082	91.41±4.852	58.4±20.017	86.71±5.263	94.81±1.356	92.52±3.73	97.98±1.468	97.23±1.451	95.08±0.49
3	71.89±9.848	68.35±7.191	49.16±19.044	42.49±21.271	61.26±10.668	89.21±1.111	86.28±4.31	75.55±13.574	64.01±4.313	82.29±1.873
4	65.04±5.289	64.53±12.599	84.24±26.843	16.35±13.682	75.47±8.393	77.5±3.113	69.93±5.336	70.55±7.703	77.06±8.312	87.63±1.066
5	95.24±3.515	54.59±8.153	63.27±12.26	22.56±4.326	76.86±5.544	98.8±0.677	92.4±2.762	94.12±4.226	93.4±4.318	86.51±0.674
6	93.59±1.223	79.07±3.843	92.26±2.523	36.28±10.047	92.54±2.718	93.11±0.638	98.12±1.081	91.76±1.496	86.47±1.913	96.05±0.368
7	99.96±0.05	75.85±6.693	80.8±2.274	38.58±12.917	84.39±3.555	98.59±1.722	93.78±1.023	99.15±0.878	99.15±0.803	98.69±0.172
8	99.94±0.076	84.52±2.698	97.06±1.298	62.07±5.042	89.39±0.732	99.06±0.173	99.08±0.2	99.29±0.6	99.33±0.159	99.97±0.007
9	99.51±0.475	98.76±0.619	93.48±10.166	33.25±18.694	81.06±3.726	99.81±0.273	99.36±0.825	99.7±0.392	99.09±1.496	98.37±0.06
OA (%)	97.72±0.376	83.67±0.895	93.01±1.141	74.57±1.291	94.94±0.297	98.1±0.202	97.77±0.306	97.34±0.680	96.75±0.026	98.13±0.043
AA (%)	92.05±1.376	88.71±0.628	76.84±4.862	44.48±6.899	84.07±0.85	94.54±0.665	92.45±0.899	92.00±1.695	90.28±1.137	93.61±0.277
kappa	0.9678±0.005	0.7938±0.020	0.9005±0.017	0.6048±0.024	0.9280±0.004	0.9736±0.022	0.9684±0.004	0.9624±0.010	0.9539±0.004	0.9735±0.001
Time s	253.43	688.33	13.94	182.27	228.55	423.16	380.52	259.49	40.11	202.00

3-D spectral-spatial extraction method in remote sensing target recognition based on satellite images.

Fig. 14 shows the experimental maps of each algorithm on the YRE dataset. The results demonstrate that SSRN, MSDN, DBDA, A2S2K, and SSFTT are severely affected by strip noise, while RSSAN, ASSMN, and SSTN maintain details well, but the tamarix in their upper left of classification maps is more severely affected by noise. The 3-D feature extraction-based model SSUN has good detail retention, but the suaeda salsa at the bottom is misclassified, and LKSSAN is more balanced for all kinds of feature recognition, but there is still a weak banding phenomenon. In summary, SSUN and LKSSAN obtain the best visualization results.

3) *Results on the PC Dataset:* The PC dataset shows urban scenes with fewer categories and stitched areas and is mainly used to verify the model's classification effect in multiscale coarse-grained cases. Table IX shows the results of all the algorithms on the PC dataset. The results show that OAs of all the algorithms except RSSAN and MSDN obtained better than 93%, which may indicate the high spectral quality of the image and low classification difficulty. The PA of LKSSAN was better than 80%, which speculates that the model can resist sample imbalance. In addition, although DBDA obtained the highest AA and kappa, the differences with LKSSAN are smaller. Fortunately, the training speed of LKSSAN is better




Fig. 15. Classification maps of different methods on PC dataset: (a) true-color image of PC; (b) GT; (c) SSRN; (d) MSDN; (e) SSUN; (f) RSSAN; (g) ASSMN; (h) DBDA; (i) A2S2K; (j) SSTN; (k) SSFTT; and (l) LKSSAN.

than that of DBDA, so LKSSAN produces the best quantitative metrics based on the overall performance.

Fig. 15 shows the classification map of each algorithm. To facilitate the qualitative evaluation, we enlarge the white box area in the classification graphs. The classification maps of MSDN, RSSAN, ASSMN, DBDA, and SSFTT cannot effectively reflect the spatial distribution of vegetation in this region. According to Fig. 15(a), it can be found that the nonresidential area contains a large amount of meadows and bare soil except for trees, but SSRN and SSUN have a serious phenomenon of misclassifying these two classes as trees. Based on the visualization results of the white box field, we can deduce that joint mining of long-range spectral and spatial information helps to alleviate the scenarios with poor spatial regularity of feature distribution. Moreover, compared with LKSSAN, A2S2K misclassifies asphalt and shadows into tiles in the left splicing area. Additionally, LKSSAN can still obtain smooth images in the region without labels indicating that the algorithm can effectively alleviate the spatial autocorrelation issue. In summary, LKSSAN has optimal visualization results.

4) *Results on the WH Dataset:* The WH dataset is ultrahigh spatial resolution hyperspectral data acquired by UAV with numerous agricultural classes, and each type of class provides only 0.1% of its all label for model training. In this section, we use the WH dataset to validate the performance of the models for fine-grained agricultural classification using high spatial and spectral resolution in the small sample case. The experimental results of all models on the WH dataset are shown in Table X. Obviously, LKSSAN has a tremendous advantage with an OA that is 31.77%–2.68% higher than the comparison algorithm. Specifically, the transformer-based algorithm obtains the best performance, which indicates the

TABLE X

QUANTITATIVE PERFORMANCE OF DIFFERENT CLASSIFICATION METHODS IN TERMS OF OA, AA, AND KAPPA, AS WELL AS THE ACCURACY FOR EACH CLASS ON THE WH DATASET. THE BEST ONE IS SHOWN IN BOLD

Class	3D spectral-spatial extraction				two-branch		Transformer		LKSSAN
	SSRN	MSDN	SSUN	RSSAN	ASSMN	A2S2K	SSTN	SSFTT	
No.									
1	93.83±1.723	91.17±3.903	86.92±7.856	80.98±5.284	87.15±4.95	97.59±0.486	93.73±2.435	90.57±3.339	94.78±1.422
2	75.95±7.203	78.97±8.667	72.62±9.972	56.34±13.385	64.29±7.652	87.16±2.122	66.49±6.412	67.33±3.887	63.86±15.786
3	78.59±2.919	72.38±12.025	89.78±0.729	72.25±1.808	90.5±2.083	85.19±0.45	82.21±2.419	84.71±0.019	81.15±6.114
4	94.02±1.095	76.5±11.302	99.73±0.078	93.36±2.56	97.5±2.407	96.53±0.247	95.9±0.862	97.54±0.271	97.05±1.665
5	70.89±9.009	49.36±27.614	51.61±16.081	31.73±16.984	67.13±15.722	84.78±4.607	59.17±10.152	97.48±0.809	74.15±9.827
6	85.87±0.999	76.75±2.483	91.4±0.284	74.71±5.528	90.3±3.06	93.76±0.69	91.33±1.399	93.31±2.534	85.58±6.266
7	65.08±4.729	51.32±2.776	71.93±4.448	50.63±1.859	73.29±3.868	80.42±0.96	74.74±5.757	77.41±2.367	86.16±8.214
8	57±6.913	35.92±12.482	15.02±1.989	12.76±7.097	5.91±1.848	77.34±9.535	29.76±7.363	50.52±1.481	86.57±8.799
9	93.32±1.847	82.83±3.207	87.71±5.262	77.67±10.555	78.4±7.923	99.18±0.275	96.56±1.517	97.36±5.055	97.69±0.907
10	80.33±2.961	61.95±10.02	60.21±10.479	38.62±8.398	49.8±7.753	69.98±4.702	79.57±2.291	79.8±8.987	83.42±8.63
11	62.47±7.179	27.51±3.535	26.82±8.199	25.61±8.752	19.7±7.582	79.71±2.278	67.15±7.005	75.65±7.039	63.12±11.362
12	54.18±9.036	60.03±8.138	39.29±15.083	32.46±5.452	37.43±12.866	66.45±2.092	55.74±5.087	67.78±5.529	67.42±18.05
13	68.07±4.086	87.73±6.576	80.76±4.211	51.74±2.578	69.22±3.468	69.84±2.266	70.14±3.146	80.1±4.622	68.55±4.342
14	78.19±4.089	51.98±5.541	44.65±7.521	40.75±11.466	52.16±8.378	90.32±6.218	90.3±3.143	84.17±3.083	61.87±16.061
15	81.78±21.791	60±48.99	36.12±29.922	18.54±17.105	14.96±15.01	99.65±0.383	70.08±23.264	97.81±3.39	79.01±10.654
16	74.47±3.905	71.32±5.11	79.32±11.421	59.17±1.126	74.22±6.055	92.02±1.802	82.56±3.151	98.96±2.231	87.98±4.939
17	49.53±6.147	55.12±8.468	34±17.60	27.45±2.261	37.29±18.412	93.53±1.692	66.81±11.972	69.32±9.268	86.67±4.537
18	72.3±4.283	39.63±22.022	28.42±10.436	14.11±3.86	15.91±10.599	96.66±1.08	61.14±10.433	69.78±8.043	76.54±21.816
19	68.94±10.23	58.39±11.919	50.09±10.615	53.32±17.232	40.1±6.391	84.47±1.65	91.34±3.668	94.81±1.889	82.54±7.38
20	64±0.052	73.18±18.604	34.23±9.471	28.44±10.011	37.51±21.193	90.1±2.443	77.67±12.665	78.38±9.814	65.57±13.196
21	45±7.408	16.49±19.3	1.7±1.687	6.75±2.08	6.58±6.593	10.16±16.472	23.6±7.067	11.14±6.764	64.65±19.741
22	47.1±14.285	41.11±24.764	50.46±13.127	49.09±20.742	21.48±7.01	88.51±2.007	58.63±7.936	74.07±6.546	70.14±14.34
OA (%)	83.69±0.337	60.75±11.07	82.34±0.664	74.22±2.227	79.69±2.131	89.84±0.297	86.30±0.416	89.36±0.345	86.32±1.610
AA (%)	70.87±2.355	73.33±6.097	55.16±1.819	45.29±6.047	51.39±1.745	83.33±1.514	72.11±0.202	79.09±0.627	77.38±1.687
kappa	0.7909±0.004	0.5702±0.060	0.7733±0.009	0.6666±0.030	0.7420±0.275	0.8704±0.004	0.8254±0.006	0.8649±0.440	0.8260±1.239
Time/s	3444.91	1533.66	22.99	746.24	611.83	1954.41	5593.38	683.05	88.19




Fig. 16. Classification maps of different methods on WH dataset: (a) false-color image of WH; (b) GT; (c) SSRN; (d) MSDN; (e) SSUN; (f) RSSAN; (g) ASSMN; (h) DBDA; (i) A2S2K; (j) SSTN; (k) SSFTT; and (l) LKSSAN.

advantage of long-range information in refined classification. DBDA and A2S2K have higher OA and longer training times than the 3-D spectral-spatial extraction-based algorithms. In contrast, LKSSAN achieves optimal performance with the highest number of optimal PAs, the best OA, AA, and kappa.

Fig. 16 shows the classification maps of each model for model qualitative analysis. Based on Fig. 16, we can see that MSDN, RSSAN, ASSMN, and A2S2K are most affected by noise, and SSRN, SSUN, SSTN, and SSFTT have severe feature confusion in the upper left region of their classification maps. Although the classification map of DBDA has the best visualization, with the ground truth (GT) map as the benchmark, we can identify the best image quality obtained by LKSSAN. By comparing the 3-D extraction models as SSRN, SSUN, and RSSAN with the two-branch models such as DBDA and A2S2K, we can find that although the 3-D extraction models perform poorly overall, the edges between local objects in the classification map are better maintained. Together with the performance of LKSSAN on the WH dataset, we can infer that 3-D feature extraction is essential for the fine classification of agriculture.

TABLE XI

TRAINABLE PARAMETERS OF DIFFERENT DL-BASED METHODS ON YRE DATASETS. THE BEST ONE IS SHOWN IN BOLD

Patch size	3D spectral-spatial extraction				two-branch			Transformer		LKSSAN
	SSRN	MSDN	SSUN	RSSAN	ASSMN	DBDA	A2S2K	SSTN	SSFTT	
Parameters	0.5114M	1.5374M	0.3117M	0.0234M	3.0245M	0.5565M	0.5205M	0.0257M	0.1527M	0.7427M

5) *Model Complexity Analysis*: To evaluate the complexity of the proposed LKSSAN method, we list the trainable parameters of different DL-based methods with the same patch size on YRE datasets in Table XI. According to Table XI, we can notice that RSSAN has the least parameters, but the lightweight structure causes performance loss. In the two-branch networks, A2S2K and DBDA have fewer parameters. The transformer-based methods have fewer parameters and poorer performance than the two-branch models. In addition, LKSSAN has the best performance on each dataset, but it requires more parameters compared to the other methods. Fortunately, it is small that the difference between the parameters of LKSSAN and the state-of-the-art algorithm. The result confirms the feasibility and value of LKSSAN in practical applications to some extent.

V. CONCLUSION

In this article, we have proposed an LKSSAN to exploit the long-range 3-D dependence. Instead of the transformer, the proposed method can excavate the long-range features by large kernel 3-D convolution, which can effectively address the challenges in the field of HSI classification. To emphasize and model the critical 3-D features, we are inspired by VAN and design an SSAM that contains two crucial structures (i.e., LKA and CFF). The LKA extracts long-range 3-D dependencies from the 3-D patch expanded by scale expansion block through attention and convolution decomposition, and the CFF facilitates the LKA and exploits the more abstract 3-D semantic representation. Moreover, to adequately utilize the long-range 3-D information, the classification module fuses the information and obtains the final classification map by SMLP.

Experiments with SSRN, MSDN, SSUN, RSSAN, ASSMN, DBDA, A2S2K, SSTN, and SSFTT on UH2018, YRE, PC, and WH datasets demonstrate the superior performance of LKSSAN. The reasons are that the SSAM can effectively excavate the long-range 3-D spectral-spatial features, and the well-designed SMLP can perfectly match the SSAM to realize the efficient integration and utilization of information. However, it should be mentioned that, although the LKSSAN can obtain high classification accuracies with various complex scenes, its ability in addressing insufficient training data problems and reducing computational burden still needs to be improved. In the future, we will introduce more lightweight structures to optimize HSI classification speed and build a semisupervised model to alleviate the insufficient training data issue.

REFERENCES

- [1] L. He, J. Li, C. Liu, and S. Li, "Recent advances on spectral-spatial hyperspectral image classification: An overview and new guidelines," *IEEE Trans. Geosci. Remote Sens.*, vol. 56, no. 3, pp. 1579–1597, Mar. 2018.

- [2] B. Zhang, D. Wu, L. Zhang, Q. Jiao, and Q. Li, "Application of hyperspectral remote sensing for environment monitoring in mining areas," *Environ. Earth Sci.*, vol. 65, no. 3, pp. 649–658, Feb. 2012.
- [3] J. Li, P. R. Marpu, A. Plaza, J. M. Bioucas-Dias, and J. A. Benediktsson, "Generalized composite kernel framework for hyperspectral image classification," *IEEE Trans. Geosci. Remote Sens.*, vol. 51, no. 9, pp. 4816–4829, Sep. 2013.
- [4] Z. Wu, J. Sun, Y. Zhang, Z. Wei, and J. Chanussot, "Recent developments in parallel and distributed computing for remotely sensed big data processing," *Proc. IEEE*, vol. 109, no. 8, pp. 1282–1305, Aug. 2021.
- [5] S. Chen, Y. Ouyang, C. Lin, and C. Chang, "Iterative support vector machine for hyperspectral image classification," in *Proc. IEEE Int. Geosci. Remote Sens. Symp.*, Jul. 2011, pp. 1712–1715.
- [6] M. Pal, "Multinomial logistic regression-based feature selection for hyperspectral data," *Int. J. Appl. Earth Observ. Geoinf.*, vol. 14, no. 1, pp. 214–220, Feb. 2012.
- [7] B. Tu, J. Wang, X. Kang, G. Zhang, X. Ou, and L. Guo, "KNN-based representation of superpixels for hyperspectral image classification," *IEEE J. Sel. Topics Appl. Earth Observ. Remote Sens.*, vol. 11, no. 11, pp. 4032–4047, Nov. 2018.
- [8] G. Hughes, "On the mean accuracy of statistical pattern recognizers," *IEEE Trans. Inf. Theory*, vol. IT-14, no. 1, pp. 55–63, Jan. 1968.
- [9] D. Donoho, "High-dimensional data analysis: The curses and blessings of dimensionality," *AMS Math. Challenges Lect.*, pp. 1–32, Jan. 2000.
- [10] C. Rodarmel and J. Shan, "Principal component analysis for hyperspectral image classification," *Surv. Land Inf. Syst.*, vol. 62, Jan. 2002.
- [11] X. Jia, B. Kuo, and M. M. Crawford, "Feature mining for hyperspectral image classification," *Proc. IEEE*, vol. 101, no. 3, pp. 676–697, Mar. 2013.
- [12] J. Li, X. Huang, and L. Tu, "WHU-OHS: A benchmark dataset for large-scale hyperspectral image classification," *Int. J. Appl. Earth Observ. Geoinf.*, vol. 113, Sep. 2022, Art. no. 103022.
- [13] F. Luo, L. Zhang, X. Zhou, T. Guo, Y. Cheng, and T. Yin, "Sparse-adaptive hypergraph discriminant analysis for hyperspectral image classification," *IEEE Geosci. Remote Sens. Lett.*, vol. 17, no. 6, pp. 1082–1086, Jun. 2020.
- [14] L. Fang, S. Li, X. Kang, and J. A. Benediktsson, "Spectral-spatial classification of hyperspectral images with a superpixel-based discriminative sparse model," *IEEE Trans. Geosci. Remote Sens.*, vol. 53, no. 8, pp. 4186–4201, Aug. 2015.
- [15] H. Liu, W. Li, X. Xia, M. Zhang, C. Gao, and R. Tao, "Central attention network for hyperspectral imagery classification," *IEEE Trans. Neural Netw. Learn. Syst.*, early access, Mar. 10, 2022, doi: 10.1109/TNNLS.2022.3155114.
- [16] J. Plaza, A. Plaza, and C. Barra, "Multi-channel morphological profiles for classification of hyperspectral images using support vector machines," *Sensors*, vol. 9, no. 1, pp. 196–218, Jan. 2009.
- [17] M. Shi and G. Healey, "Hyperspectral texture recognition using a multiscale opponent representation," *IEEE Trans. Geosci. Remote Sens.*, vol. 41, no. 5, pp. 1090–1095, May 2003.
- [18] R. Ji, Y. Gao, R. Hong, Q. Liu, D. Tao, and X. Li, "Spectral-spatial constraint hyperspectral image classification," *IEEE Trans. Geosci. Remote Sens.*, vol. 52, no. 3, pp. 1811–1824, Mar. 2014.
- [19] B. Zhang, S. Li, X. Jia, L. Gao, and M. Peng, "Adaptive Markov random field approach for classification of hyperspectral imagery," *IEEE Geosci. Remote Sens. Lett.*, vol. 8, no. 5, pp. 973–977, Sep. 2011.
- [20] X. Kang, S. Li, L. Fang, and J. A. Benediktsson, "Intrinsic image decomposition for feature extraction of hyperspectral images," *IEEE Trans. Geosci. Remote Sens.*, vol. 53, no. 4, pp. 2241–2253, Apr. 2015.
- [21] Y. Qian, M. Ye, and J. Zhou, "Hyperspectral image classification based on structured sparse logistic regression and three-dimensional wavelet texture features," *IEEE Trans. Geosci. Remote Sens.*, vol. 51, no. 4, pp. 2276–2291, Apr. 2013.
- [22] Y. Y. Tang, Y. Lu, and H. Yuan, "Hyperspectral image classification based on three-dimensional scattering wavelet transform," *IEEE Trans. Geosci. Remote Sens.*, vol. 53, no. 5, pp. 2467–2480, May 2015.
- [23] Z. Zhu, S. Jia, S. He, Y. Sun, Z. Ji, and L. Shen, "Three-dimensional Gabor feature extraction for hyperspectral imagery classification using a memetic framework," *Inf. Sci.*, vol. 298, pp. 274–287, Mar. 2015.
- [24] Y. Xu, B. Du, F. Zhang, and L. Zhang, "Hyperspectral image classification via a random patches network," *ISPRS J. Photogramm. Remote Sens.*, vol. 142, pp. 344–357, Aug. 2018.
- [25] R. Hang, Q. Liu, D. Hong, and P. Ghamisi, "Cascaded recurrent neural networks for hyperspectral image classification," *IEEE Trans. Geosci. Remote Sens.*, vol. 57, no. 8, pp. 5384–5394, Aug. 2019.
- [26] Y. Chen, Z. Lin, X. Zhao, G. Wang, and Y. Gu, "Deep learning-based classification of hyperspectral data," *IEEE J. Sel. Topics Appl. Earth Observ. Remote Sens.*, vol. 7, no. 6, pp. 2094–2107, Jun. 2014.
- [27] Y. Chen, X. Zhao, and X. Jia, "Spectral-spatial classification of hyperspectral data based on deep belief network," *IEEE J. Sel. Topics Appl. Earth Observ. Remote Sens.*, vol. 8, no. 6, pp. 2381–2392, Jun. 2015.
- [28] X. Hu et al., "SPNet: Spectral patching end-to-end classification network for UAV-borne hyperspectral imagery with high spatial and spectral resolutions," *IEEE Trans. Geosci. Remote Sens.*, vol. 60, 2022, Art. no. 5503417.
- [29] Z. Zheng, Y. Zhong, A. Ma, and L. Zhang, "FPGA: Fast patch-free global learning framework for fully end-to-end hyperspectral image classification," *IEEE Trans. Geosci. Remote Sens.*, vol. 58, no. 8, pp. 5612–5626, Aug. 2020.
- [30] A. Romero, C. Gatta, and G. Camps-Valls, "Unsupervised deep feature extraction for remote sensing image classification," *IEEE Trans. Geosci. Remote Sens.*, vol. 54, no. 3, pp. 1349–1362, Mar. 2016.
- [31] G. Cheng, Z. Li, J. Han, X. Yao, and L. Guo, "Exploring hierarchical convolutional features for hyperspectral image classification," *IEEE Trans. Geosci. Remote Sens.*, vol. 56, no. 11, pp. 6712–6722, Nov. 2018.
- [32] H. Lee and H. Kwon, "Going deeper with contextual CNN for hyperspectral image classification," *IEEE Trans. Image Process.*, vol. 26, no. 10, pp. 4843–4855, Oct. 2017.
- [33] X. Xu, W. Li, Q. Ran, Q. Du, L. Gao, and B. Zhang, "Multisource remote sensing data classification based on convolutional neural network," *IEEE Trans. Geosci. Remote Sens.*, vol. 56, no. 2, pp. 937–949, Feb. 2018.
- [34] Y. Li, Q. Xu, W. Li, and J. Nie, "Automatic clustering-based two-branch CNN for hyperspectral image classification," *IEEE Trans. Geosci. Remote Sens.*, vol. 59, no. 9, pp. 7803–7816, Sep. 2021.
- [35] M. Imani and H. Ghassemian, "An overview on spectral and spatial information fusion for hyperspectral image classification: Current trends and challenges," *Inf. Fusion*, vol. 59, pp. 59–83, Jul. 2020.
- [36] Z. Zhong, J. Li, Z. Luo, and M. Chapman, "Spectral-spatial residual network for hyperspectral image classification: A 3-D deep learning framework," *IEEE Trans. Geosci. Remote Sens.*, vol. 56, no. 2, pp. 847–858, Feb. 2018.
- [37] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, Jun. 2016, pp. 770–778.
- [38] A. Sellami, A. Ben Abbes, V. Barra, and I. R. Farah, "Fused 3-D spectral-spatial deep neural networks and spectral clustering for hyperspectral image classification," *Pattern Recognit. Lett.*, vol. 138, pp. 594–600, Oct. 2020.
- [39] S. Jia et al., "A lightweight convolutional neural network for hyperspectral image classification," *IEEE Trans. Geosci. Remote Sens.*, vol. 59, no. 5, pp. 4150–4163, May 2021.
- [40] J. Hu, L. Shen, S. Albanie, G. Sun, and E. Wu, "Squeeze-and-excitation networks," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 42, no. 8, pp. 2011–2023, Aug. 2020.
- [41] L. Mou and X. X. Zhu, "Learning to pay attention on spectral domain: A spectral attention module-based convolutional network for hyperspectral image classification," *IEEE Trans. Geosci. Remote Sens.*, vol. 58, no. 1, pp. 110–122, Jan. 2020.
- [42] J. Li et al., "Hyperspectral image super-resolution by band attention through adversarial learning," *IEEE Trans. Geosci. Remote Sens.*, vol. 58, no. 6, pp. 4304–4318, Jun. 2020.
- [43] S. Woo, J. Park, J.-Y. Lee, and I. S. Kweon, "CBAM: Convolutional block attention module," in *Proc. Eur. Conf. Comput. Vis. (ECCV)*, 2018, pp. 3–19.
- [44] W. Ma, Q. Yang, Y. Wu, W. Zhao, and X. Zhang, "Double-branch multi-attention mechanism network for hyperspectral image classification," *Remote Sens.*, vol. 11, no. 11, p. 1307, Jun. 2019.
- [45] C. Pu, H. Huang, and L. Yang, "An attention-driven convolutional neural network-based multi-level spectral-spatial feature learning for hyperspectral image classification," *Expert Syst. Appl.*, vol. 185, Dec. 2021, Art. no. 115663.
- [46] J. Fu et al., "Dual attention network for scene segmentation," in *Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR)*, Jun. 2019, pp. 3141–3149.
- [47] H. Sun, X. Zheng, X. Lu, and S. Wu, "Spectral-spatial attention network for hyperspectral image classification," *IEEE Trans. Geosci. Remote Sens.*, vol. 58, no. 5, pp. 3232–3245, May 2020.
- [48] X. Zhang et al., "Spectral-spatial self-attention networks for hyperspectral image classification," *IEEE Trans. Geosci. Remote Sens.*, vol. 60, 2022, Art. no. 5512115.

- [49] R. Li, S. Zheng, C. Duan, Y. Yang, and X. Wang, "Classification of hyperspectral image based on double-branch dual-attention mechanism network," *Remote Sens.*, vol. 12, no. 3, p. 582, Feb. 2020.
- [50] A. Dosovitskiy et al., "An image is worth 16×16 words: Transformers for image recognition at scale," 2020, *arXiv:2010.11929*.
- [51] D. Hong et al., "SpectralFormer: Rethinking hyperspectral image classification with transformers," *IEEE Trans. Geosci. Remote Sens.*, vol. 60, 2022, Art. no. 5518615.
- [52] Z. Xue, Q. Xu, and M. Zhang, "Local transformer with spatial partition restore for hyperspectral image classification," *IEEE J. Sel. Topics Appl. Earth Observ. Remote Sens.*, vol. 15, pp. 4307–4325, 2022.
- [53] L. Sun, G. Zhao, Y. Zheng, and Z. Wu, "Spectral-spatial feature tokenization transformer for hyperspectral image classification," *IEEE Trans. Geosci. Remote Sens.*, vol. 60, 2022, Art. no. 5522214.
- [54] J. Yang, B. Du, and L. Zhang, "From center to surrounding: An interactive learning framework for hyperspectral image classification," *ISPRS J. Photogramm. Remote Sens.*, vol. 197, pp. 145–166, Mar. 2023.
- [55] M.-H. Guo, C. Lu, Z.-N. Liu, M.-M. Cheng, and S. Hu, "Visual attention network," 2022, *arXiv:2202.09741*.
- [56] W. Wang et al., "PVT v2: Improved baselines with pyramid vision transformer," *Comput. Vis. Media*, vol. 8, no. 3, pp. 415–424, Sep. 2022.
- [57] Z. Zhong, Y. Li, L. Ma, J. Li, and W. Zheng, "Spectral-spatial transformer network for hyperspectral image classification: A factorized architecture search framework," *IEEE Trans. Geosci. Remote Sens.*, vol. 60, 2022, Art. no. 5514715.
- [58] T. Lin, P. Goyal, R. Girshick, K. He, and P. Dollár, "Focal loss for dense object detection," in *Proc. IEEE Int. Conf. Comput. Vis. (ICCV)*, Oct. 2017, pp. 2999–3007.
- [59] D. E. Rumelhart, G. E. Hinton, and R. J. Williams, "Learning representations by back-propagating errors," *Nature*, vol. 323, no. 6088, pp. 533–536, Oct. 1986.
- [60] C. Zhang, G. Li, and S. Du, "Multi-scale dense networks for hyperspectral remote sensing image classification," *IEEE Trans. Geosci. Remote Sens.*, vol. 57, no. 11, pp. 9201–9222, Nov. 2019.
- [61] Y. Xu, L. Zhang, B. Du, and F. Zhang, "Spectral-spatial unified networks for hyperspectral image classification," *IEEE Trans. Geosci. Remote Sens.*, vol. 56, no. 10, pp. 5893–5909, Oct. 2018.
- [62] M. Zhu, L. Jiao, F. Liu, S. Yang, and J. Wang, "Residual spectral-spatial attention network for hyperspectral image classification," *IEEE Trans. Geosci. Remote Sens.*, vol. 59, no. 1, pp. 449–462, Jan. 2021.
- [63] D. Wang, B. Du, L. Zhang, and Y. Xu, "Adaptive spectral-spatial multiscale contextual feature extraction for hyperspectral image classification," *IEEE Trans. Geosci. Remote Sens.*, vol. 59, no. 3, pp. 2461–2477, Mar. 2021.
- [64] S. K. Roy, S. Manna, T. Song, and L. Bruzzone, "Attention-based adaptive spectral-spatial kernel ResNet for hyperspectral image classification," *IEEE Trans. Geosci. Remote Sens.*, vol. 59, no. 9, pp. 7831–7843, Sep. 2021.
- [65] D. P. Kingma and J. Ba, "Adam: A method for stochastic optimization," 2014, *arXiv:1412.6980*.



Genyun Sun (Senior Member, IEEE) received the B.Sc. degree from Wuhan University, Wuhan, China, in 2003, and the Ph.D. degree from the Institute of Remote Sensing Applications, Chinese Academy of Sciences, Beijing, China, in 2008.


He is currently a Professor with the China University of Petroleum (East China), Qingdao, China. He is also with the Laboratory for Marine Mineral Resources, Qingdao National Laboratory for Marine Science and Technology, Qingdao. His research interests cover remote sensing image processing, and high-resolution remote sensing, and intelligent

including hyperspectral optimization.



Zhaojie Pan received the B.Sc. degree in geomatics engineering from the China University of Petroleum (East China), Qingdao, China, in 2021, where he is currently pursuing the M.Sc. degree.

His research interests include hyperspectral classification and deep learning.



Aizhu Zhang (Member, IEEE) received the B.Sc., M.Sc., and Ph.D. degrees from the China University of Petroleum (East China), Qingdao, China, in 2011, 2014, and 2017, respectively.

She is currently an Associate Professor with the China University of Petroleum (East China). She is also with the Key Laboratory of Poyang Lake Wetland and Watershed Research, Jiangxi Normal University, Ministry of Education, Nanchang, China. Her research interests are in multisource remote sensing processing, wetland remote sensing, and city environment remote sensing.



Xiuping Jia (Fellow, IEEE) received the B.Eng. degree from the Beijing University of Posts and Telecommunications, Beijing, China, in 1982, and the Ph.D. degree in electrical engineering from The University of New South Wales, Australia, in 1996.

Since 1988, she has been with the School of Engineering and Information Technology, The University of New South Wales at Canberra, Canberra, ACT, Australia, where she is currently an Associate Professor. She has authored or coauthored more than 270 refereed articles, including over 160 journal articles,

addressing various topics including data correction, feature reduction, and image classification using machine learning techniques. She has coauthored the remote sensing textbook titled *Remote Sensing Digital Image Analysis* [Springer-Verlag, 3rd (1999) and 4th eds. (2006)]. Her research interests include remote sensing, hyperspectral image processing, and spatial data analysis.

Dr. Jia is a Subject Editor of the *Journal of Soils and Sediments* and the Associate Editor-in-Chief of the *IEEE TRANSACTIONS ON GEOSCIENCE AND REMOTE SENSING*.



Jinchang Ren (Senior Member, IEEE) received the B.Eng., M.Eng., and D.Eng. degrees from Northwestern Polytechnical University, Xi'an, China, in 1992, 1997, and 2000, respectively, and the Ph.D. degree from the University of Bradford, Bradford, U.K., in 2019.

He is currently a Professor with the National Subsea Centre, Robert Gordon University, Aberdeen, U.K. His research interests include image processing, computer vision, machine learning, and big data analytics.

Dr. Ren served as an Associate Editor for several international journals, including the *IEEE TRANSACTIONS ON GEOSCIENCE AND REMOTE SENSING (TGRS)* and *Journal of the Franklin Institute*.



Hang Fu received the B.Sc. degree in geomatics engineering from the China University of Petroleum (East China), Qingdao, China, in 2019, where he is currently pursuing the Ph.D. degree in computer technology and resource information engineering.

His research interests are related to hyperspectral image (HSI) feature extraction and classification.



Kai Yan received the B.S. degree in mapping and surveying from the Beijing University of Civil Engineering and Architecture, Beijing, China, in 2011, and the Ph.D. degree in geographic information system (GIS)/remote sensing (RS) from Beijing Normal University, Beijing, in 2018.

He was a Visiting Scholar with the Department of Earth and Environment, Boston University, Boston, MA, USA, from 2014 to 2016, and an Assistant Professor with the School of Land Science and Techniques, China University of Geosciences, Beijing.

He is currently an Associate Professor with the Faculty of Geographical Science, Beijing Normal University. He has been involved in the generation and assessment of official MODIS/VIIRS global leaf area index (LAI) and the fraction of photosynthetically active radiation absorbed by vegetation (FPAR) products. His research interests include vegetation bidirectional reflectance distribution function (BRDF) modeling, RS big data and artificial intelligence, and LAI and FPAR mapping.