

# **Zowe Documentation**

## **Version 1.4.0**



# Contents

<b>Chapter 1: Getting Started.....</b>	<b>7</b>
Zowe overview.....	8
Zowe overview.....	8
Zowe architecture.....	12
Release notes.....	14
Version 1.4.0 (August 2019).....	14
Version 1.3.0 (June 2019).....	16
Version 1.2.0 (May 2019).....	17
Version 1.1.0 (April 2019).....	19
Version 1.0.1 (March 2019).....	20
Version 1.0.0 (February 2019).....	21
Zowe CLI quick start.....	22
Installing.....	22
Issuing your first commands.....	23
Using profiles.....	23
Writing scripts.....	24
Next Steps.....	24
Frequently Asked Questions.....	24
Zowe FAQ.....	24
Zowe CLI FAQ.....	26
<b>Chapter 2: User Guide.....</b>	<b>29</b>
Installing Zowe.....	30
Planning the installation.....	30
System requirements.....	31
Installing Node.js on z/OS.....	32
Configuring z/OSMF.....	33
Configuring z/OSMF Lite (for non-production use).....	36
Installing Zowe on z/OS.....	53
Installing Zowe CLI.....	73
Updating Zowe CLI.....	75
Uninstalling Zowe.....	75
Configuring Zowe.....	77
Zowe Application Framework configuration.....	77
Configuring Zowe CLI.....	88
Using Zowe.....	93
Getting started tutorial.....	93
Using the Zowe Desktop.....	112
API Catalog.....	117
Zowe CLI extensions and plug-ins.....	120
Extending Zowe CLI.....	120
Software requirements for Zowe CLI plug-ins.....	120
Installing plug-ins.....	120
IBM® CICS® Plug-in for Zowe CLI.....	123
Zowe CLI Plug-in for IBM Db2 Database.....	124
VSCode Extension for Zowe.....	127

## **Chapter 3: Extending.....129**

Developing for API Mediation Layer.....	130
Onboarding Overview.....	130
Java REST APIs with Spring Boot.....	133
Java REST APIs service without Spring Boot.....	146
Prerequisites.....	147
Java Jersey REST APIs.....	156
REST APIs without code changes required.....	169
Developing for Zowe CLI.....	176
Developing for Zowe CLI.....	176
Setting up your development environment.....	177
Installing the sample plug-in.....	178
Extending a plug-in.....	180
Developing a new plug-in.....	183
Implementing profiles in a plug-in.....	188
Developing for Zowe Application Framework.....	189
Overview.....	189
Creating application plug-ins.....	191
Plug-ins definition and structure.....	192
Dataservices.....	195
Internationalizing applications.....	198
Zowe Desktop and window management.....	202
Configuration Dataservice.....	206
URI Broker.....	211
Application-to-application communication.....	212
Error reporting UI.....	216
Logging utility.....	219
Tutorial: Stand up a local version of the Example Zowe Application Server.....	221
Tutorial: User Browser Workshop App.....	226
Zowe Conformance Program.....	241
Introduction.....	241
How to participate.....	241

## **Chapter 4: Troubleshooting.....243**

Troubleshooting.....	244
Troubleshooting API ML.....	244
Enable API ML Debug Mode.....	244
Change the Log Level of Individual Code Components.....	244
Known Issues.....	246
Zowe Application Framework.....	246
Troubleshooting Zowe Application Framework.....	246
Gathering information to troubleshoot Zowe Application Framework.....	247
Known Zowe Application Framework issues.....	249
Raising a Zowe Application Framework issue on GitHub.....	251
Troubleshooting z/OS Services.....	252
z/OS Services are unavailable.....	252
Troubleshooting Zowe CLI.....	253
Troubleshooting Zowe CLI.....	253
Gathering information to troubleshoot Zowe CLI.....	253
z/OSMF troubleshooting.....	256
Known Zowe CLI issues.....	256
Raising a CLI issue on GitHub.....	258
Troubleshooting Zowe through Zowe Open Community.....	258

Contact Zowe Open Community to Troubleshoot Zowe.....	259
<<<<< HEAD Community members start to troubleshoot your issue.....	259

## Chapter 5: Contributing..... 261

Code guidelines.....	262
Code categories.....	262
General code style guidelines.....	262
Pull requests guidelines.....	263
Documentation Guidelines.....	263
UI guidelines.....	264
Introduction.....	264
Colors.....	265
Typography.....	269
Grid.....	271
Iconography.....	273
Application icon.....	274
How to contribute.....	277
Before you get started.....	277
Contributing to documentation.....	277
Documentation Style guide .....	278
Word usage.....	283



---

# Chapter

# 1

---

## Getting Started

---

**Topics:**

- Zowe overview
  - Release notes
  - Zowe CLI quick start
  - Frequently Asked Questions
- 

## Zowe overview

---

### Zowe overview

Zowe is an open source project created to host technologies that benefit the IBM Z platform for all members of the Z community, including Integrated Software Vendors (ISVs), System Integrators, and z/OS consumers. Zowe, like Mac or Windows, comes with a set of APIs and OS capabilities that applications build on and also includes some applications out of the box. Zowe offers modern interfaces to interact with z/OS and allows you to work with z/OS in a way that is similar to what you experience on cloud platforms today. You can use these interfaces as delivered or through plug-ins and extensions that are created by clients or third-party vendors.

### Zowe Demo Video

### Component Overview

Zowe consists of the following components:

#### Zowe Application Framework

A web user interface (UI) that provides a virtual desktop containing a number of apps allowing access to z/OS function. Base Zowe includes apps for traditional access such as a 3270 terminal and a VT Terminal, as well as an editor and explorers for working with JES, MVS Data Sets and Unix System Services.

[Click for more information](#)

The Zowe Application Framework modernizes and simplifies working on the mainframe. With the Zowe Application Framework, you can create applications to suit your specific needs. The Zowe Application Framework contains a web UI that has the following features:

- The web UI works with the underlying REST APIs for data, jobs, and subsystem, but presents the information in a full screen mode as compared to the command line interface.
- The web UI makes use of leading-edge web presentation technology and is also extensible through web UI plug-ins to capture and present a wide variety of information.
- The web UI facilitates common z/OS developer or system programmer tasks by providing an editor for common text-based files like REXX or JCL along with general purpose data set actions for both Unix System Services (USS) and Partitioned Data Sets (PDS) plus Job Entry System (JES) logs.

The Zowe Application Framework consists of the following components:

- **Zowe Desktop**

The desktop, accessed through a browser.

- **Zowe Application Server**

The Zowe Application Server runs the Zowe Application Framework. It consists of the Node.js server plus the Express.js as a webservices framework, and the proxy applications that communicate with the z/OS services and components.

- **ZSS Server**

The ZSS Server provides secure REST services to support the Zowe Application Server.

- **Application plug-ins**

Several application-type plug-ins are provided. For more information, see [Zowe Desktop application plug-ins](#) on page 112.

### z/OS Services

Provides a range of APIs for the management of z/OS JES jobs and MVS data set services.

[Click for more information](#)

Zowe provides a z/OS® RESTful web service and deployment architecture for z/OS microservices. Zowe contains the following core z/OS services:

- **z/OS Datasets services**

Get a list of data sets, retrieve content from a member, create a data set, and more.

- **z/OS Jobs services**

Get a list of jobs, get content from a job file output, submit a job from a data set, and more.

You can view the full list of capabilities of the RESTful APIs from the API catalog that displays the Open API Specification for their capabilities.

- These APIs are described by the Open API Specification allowing them to be incorporated to any standard-based REST API developer tool or API management process.
- These APIs can be exploited by off-platform applications with proper security controls.

As a deployment architecture, the z/OS Services are running as microservices with a Springboot embedded Tomcat stack.

## Zowe CLI

Zowe CLI is a command-line interface that lets application developers interact with the mainframe in a familiar, off-platform format. Zowe CLI helps to increase overall productivity, reduce the learning curve for developing mainframe applications, and exploit the ease-of-use of off-platform tools. Zowe CLI lets application developers use common tools such as Integrated Development Environments (IDEs), shell commands, bash scripts, and build tools for mainframe development. It provides a set of utilities and services for application developers that want to become efficient in supporting and building z/OS applications quickly.

[Click for more information](#)

Zowe CLI provides the following benefits:

- Enables and encourages developers with limited z/OS expertise to build, modify, and debug z/OS applications.
- Fosters the development of new and innovative tools from a computer that can interact with z/OS. Some Zowe extensions are powered by Zowe CLI, for example the [VSCode Extension for Zowe](#) on page 127.
- Ensure that business critical applications running on z/OS can be maintained and supported by existing and generally available software development resources.
- Provides a more streamlined way to build software that integrates with z/OS.

**Note:** For information about software requirements, installing, and upgrading Zowe CLI, see [Planning the installation](#) on page 30.

### Zowe CLI capabilities

With Zowe CLI, you can interact with z/OS remotely in the following ways:

- **Interact with mainframe files:** Create, edit, download, and upload mainframe files (data sets) directly from Zowe CLI.
- **Submit jobs:** Submit JCL from data sets or local storage, monitor the status, and view and download the output automatically.
- **Issue TSO and z/OS console commands:** Issue TSO and console commands to the mainframe directly from Zowe CLI.
- **Integrate z/OS actions into scripts:** Build local scripts that accomplish both mainframe and local tasks.
- **Produce responses as JSON documents:** Return data in JSON format on request for consumption in other programming languages.

For detailed information about the available functionality in Zowe CLI, see [Zowe CLI Command Groups](#).

For information about extending the functionality of Zowe CLI by installing plug-ins, see [Extending Zowe CLI](#) on page 120.

### More Information:

- [System requirements](#) on page 31
- [Installing Zowe CLI](#) on page 73

## API Mediation Layer

Provides a gateway that acts as a reverse proxy for z/OS services, together with a catalog of REST APIs and a dynamic discovery capability. Base Zowe provides core services for working with MVS Data Sets, JES, as well as working with z/OSMF REST APIs. The API Mediation Layer also provides a framework for Single Sign On (SSO).

[Click for more information](#)

The API Mediation Layer provides a single point of access for mainframe service REST APIs. The layer offers enterprise, cloud-like features such as high-availability, scalability, dynamic API discovery, consistent security, a single sign-on experience, and documentation. The API Mediation Layer facilitates secure communication across loosely coupled microservices through the API Gateway. The API Mediation Layer consists of three components: the Gateway, the Discovery Service, and the Catalog. The Gateway provides secure communication across loosely coupled API services. The Discovery Service enables you to determine the location and status of service instances running inside the API ML ecosystem. The Catalog provides an easy-to-use interface to view all discovered services, their associated APIs, and Swagger documentation in a user-friendly manner.

### *Key features*

- **Consistent Access:** API routing and standardization of API service URLs through the Gateway component provides users with a consistent way to access mainframe APIs at a predefined address.
- **Dynamic Discovery:** The Discovery Service automatically determines the location and status of API services.
- **High-Availability:** API Mediation Layer is designed with high-availability of services and scalability in mind.
- **Redundancy and Scalability:** API service throughput is easily increased by starting multiple API service instances without the need to change configuration.
- **Presentation of Services:** The API Catalog component provides easy access to discovered API services and their associated documentation in a user-friendly manner. Access to the contents of the API Catalog is controlled through a z/OS security facility.
- **Encrypted Communication:** API ML facilitates secure and trusted communication across both internal components and discovered API services.

### *API Mediation Layer architecture*

The following diagram illustrates the single point of access through the Gateway, and the interactions between API ML components and services:



### Components

The API Layer consists of the following key components:

#### API Gateway

Services that comprise the API ML service ecosystem are located behind a gateway (reverse proxy). All end users and API client applications interact through the Gateway. Each service is assigned a unique service ID that is used in the access URL. Based on the service ID, the Gateway forwards incoming API requests to the appropriate service. Multiple Gateway instances can be started to achieve high-availability. The Gateway access URL remains unchanged. The Gateway is built using Netflix Zuul and Spring Boot technologies.

## **Discovery Service**

The Discovery Service is the central repository of active services in the API ML ecosystem. The Discovery Service continuously collects and aggregates service information and serves as a repository of active services. When a service is started, it sends its metadata, such as the original URL, assigned serviceId, and status information to the Discovery Service. Back-end microservices register with this service either directly or by using a Eureka client. Multiple enablers are available to help with service on-boarding of various application architectures including plain Java applications and Java applications that use the Spring Boot framework. The Discovery Service is built on Eureka and Spring Boot technology.

## **Discovery Service TLS/SSL**

HTTPS protocol can be enabled during API ML configuration and is highly recommended. Beyond encrypting communication, the HTTPS configuration for the Discovery Service enables heightened security for service registration. Without HTTPS, services provide a username and password to register in the API ML ecosystem. When using HTTPS, only trusted services that provide HTTPS certificates signed by a trusted certificate authority can be registered.

## **API Catalog**

The API Catalog is the catalog of published API services and their associated documentation. The Catalog provides both the REST APIs and a web user interface (UI) to access them. The web UI follows the industry standard Swagger UI component to visualize API documentation in OpenAPI JSON format for each service. A service can be implemented by one or more service instances, which provide exactly the same service for high-availability or scalability.

## **Catalog Security**

Access to the API Catalog can be protected with an Enterprise z/OS Security Manager such as IBM RACF, CA ACF2, or CA Top Secret. Only users who provide proper mainframe credentials can access the Catalog. Client authentication is implemented through the z/OSMF API.

## *Onboarding APIs*

Essential to the API Mediation Layer ecosystem is the API services that expose their useful APIs. Use the following topics to discover more about adding new APIs to the API Mediation Layer and using the API Catalog:

- [Onboarding Overview](#) on page 130
- [Java REST APIs with Spring Boot](#) on page 133
- [API Catalog](#) on page 117


## **Zowe Third-Party Software Requirements and Bill of Materials**

- [Third-Party Software Requirements \(TPSR\)](#)
- [Bill of Materials \(BOM\)](#)

## **Zowe architecture**

Zowe is a collection of components that together form a framework that allows Z based functionality to be accessible across an organization. This includes exposing Z based components such as z/OSMF as Rest APIs. The framework provides an environment where other components can be included and exposed to a broader non-Z based audience.

The following diagram depicts the high level Zowe architecture.



## Release notes

---

Learn about what is new, changed, removed, and known issues in Zowe.

Zowe Version 1.4.0 and later releases include the following enhancements, release by release.

- [Version 1.4.0 \(August 2019\)](#)
- [Version 1.3.0 \(June 2019\)](#)
- [Version 1.2.0 \(May 2019\)](#)
- [Version 1.1.0 \(April 2019\)](#)
- [Version 1.0.1 \(March 2019\)](#)
- [Version 1.0.0 \(February 2019\)](#)

### Version 1.4.0 (August 2019)

#### What's new in API Mediation Layer

This release of Zowe API ML contains the following improvements:

- JWT token configuration
  - RS256 is used as a token encryption algorithm
  - JWT secret string is generated at the time of installation and exported as a .pem file for use by other services
  - JWT secret string is stored in a key store in PKCS 11 format under "jwtsecret" name
- SonarQube problems fixed
  - Various fixes from SonarQube scan
- API Mediation Layer log format aligned with other Zowe services:

```
%d{yyyy-MM-dd HH:mm:ss.SSS,UTC} %clr(<${logbackService:-${logbackServiceName}}:>${thread:$PID:- }){magenta} %X{userid:-}
%clr(%-5level) %clr(\(%logger{15},%file:%line\)){cyan} %msg%n
```

- Added an NPM command to register certificates on Windows. The following command installs the certificate to trusted root certification authorities:
 

```
npm run register-certificates-win
```
- Cookie persistence changed
  - Changed the API Mediation Layer cookie from persistent to session. The cookie gets cleared between browser sessions.
- Fixed high CPU usage occurrence replicated in Broadcom ([#282](#))
  - Changed configuration of LatencyUtils to decrease idle CPU consumption by API ML services
- API Mediation layer now builds using OpenJDK with OpenJ9 JVM

#### What's new in the Zowe App Server

Made the following fixes and enhancements:

- Added the ability for the App Server Framework to defer to managers for dataservices that are not written in NodeJS or C. The first implementation is a manager of Java servlet type dataservices, where the App Server manages Tomcat instances when Tomcat is present. ([#158](#))
- Added a tomcat xml configuration file with substitutions for values (ports, keys, certificates) necessary for the App Server to manage one or more instances of Tomcat for hosting servlet dataservices. Also added a new section to the zluxserver.json file to describe dataservice providers such as the aforementioned Tomcat Java Servlet one. (#49)
- Added Swagger API documentation support. Application developers can include a Swagger 2.0 JSON or YAML file in the app's /doc/swagger directory for each REST data service. Each file must have the same name as the data

service. Developers can then reference the files at runtime using a new app route: /ZLUX/plugins/PLUGINID/catalogs/swagger. They can reference individual services at: /ZLUX/plugins/PLUGINID/catalogs/swagger/SERVICENAME. If swagger documents are not present, the server will use contextual knowledge to show some default values. (#159)

- The following new REST and cross-memory services have been added (#32):
  - Extract RACF user profiles
  - Define/delete/permit general RACF resource profiles (limited to a single class)
  - Add/remove RACF groups
  - Connect users to RACF groups (for a limited set of group prefixes)
  - Check RACF user access levels (limited to a single class)
- Fixed multiple issues in the File Editor App. (#88)
- Fixed multiple ZSS file and dataset API issues (#49 #42 #40 #44 #45)
- Remove several CSS styles from the Desktop to prevent bleed-in of styles to Apps (#117)
- Fixed incorrect count of open Apps upon logging in more than once per browser session (#123) Add OMVS information API to uribroker (#116)
- Enhanced auth plugin structure for application framework that lists auth capabilities (#118 #14 #19)
- Improved searching for node libraries for dataservices within an plugin (#114)
- Editor & File Explorer Widget Changes
  - Unix directory listing now starts in the user's home directory (#16)
  - JCL syntax coloring revision (#73)
  - Cursor, scroll position and text selection is now kept while switching tabs in editor (#71)
  - Editor now scrolls tab bar to newest tab when opening, and tab scrolling improved when closing tabs (#69)
  - Tab name, tooltip, and scroll fixes (#55 #60 #63)
  - Change in double and single click behavior of file explorer widget (#21)
  - Fix to show language menu on new file (#62)
  - Fix to keep language menu within the bounds of app window (#59)
  - Fix to the delete file prompt (#61)
  - Fix to allow closing of multiple editor instances (#22)
  - Fix to query datasets correctly by making queries uppercase (#65)
- Fixed issue where the cascading position of new windows were wrong when that application was maximized. (#102)
- Fixed issue where the file tabs in File Editor app were vertically scrollable, and where the close button would not be accessible for long file names. (#170)
- Updated the package lock files in all repositories to fix vulnerable dependencies. (#163)
- Fixed an issue where the Desktop used the roboto-latin-regular font for all text, which would not display well with non-latin languages. Now the fallback font is sans-serif. (#118)

## What's new in Zowe CLI and Plug-ins

You can now explore the Zowe CLI command help in an interactive online format. See [Zowe CLI Web Help](#).

The following new commands and enhancements are added:

- The [VSCode Extension for Zowe](#) now supports manipulation of USS files. (#32)
- You can now archive z/OS workflows using a wildcard. (#435)
- The z/OS Workflows functionality is now exported to an API. Developers can leverage the exported APIs to create applications and scripts without going through the CLI layer. (#482)
- The CLI now exploits all "z/OS data set and file REST interface" options that are provided in z/OSMF v2.3. (#491)

The following bugs are fixed:

- Fixed an issue where examples for `zowe files list uss-files` were slightly incorrect. (#440)
- Improved error message for `zowe db2 call procedure` command. (#22)

## Version 1.3.0 (June 2019)

### What's new in API Mediation Layer

This release of Zowe API ML contains the following user experience improvements:

- Added authentication endpoints (/login, /query) to the API Gateway
- Added the Gateway API Swagger document ([#305](#))
  - Fixed the bug that causes JSON response to set incorrectly when unauthenticated
  - Fixed error messages shown when a home page cannot be modified
- Added a new e2e test for GW, and update the detail service tile ([#309](#))
- Removed a dependency of integration-enabler-java on the gateway-common ([#302](#))
- Removed access to the Discovery service UI with basic authentication ([#313](#))
- Fixed the issue with the connection logic on headers to pass in the websocket ([#275](#))
- Fixed the bug 264: Bypass the API Gateway when the server returns 302 ([#276](#))
- Fixed the issue that causes the API ML Services display as UP, and makes the API doc available in the Catalog regardless whether the API ML Services stop ([#287](#))
- Fixed the issue that prevents the API Catalog to load under zLux 9 ([#314](#))

### What's new in the Zowe App Server

Made the following fixes and enhancements:

- Added internationalization to the Angular and React sample applications. ([#133](#))
- Made the following enhancements to the ZSS server:
  - Added support for Zowe on z/OS version 2.4. ([#15](#))
  - Updated documentation for query parameter to file API. ([#48](#))
- Made the following enhancements to security:
  - App Server session cookie is now a browser session cookie rather than having an expiration date. Expiration is now tracked on the server side. ([#132](#), [#97](#), [#81](#))
  - Added a "mode=base64" option to the unixfile API. ([#127](#))
- Added a port to the cookie name to differentiate multiple servers on same domain. ([#95](#))
- Made the following fixes and enhancements to the Code Editor application:
  - Added a menu framework to provide options specific to the current file/data set type. ([#131](#))
  - Added ISPF-like syntax highlighting for JCL. ([#48](#))
  - Fixed an issue by notifying users if the editor cannot open a file or data set. ([#148](#))
  - Fixed an issue with event behavior when a tab is closed. ([#135](#))
  - Fixed an issue with not showing the content of files in Chrome and Safari. ([#100](#))
  - Fixed an issue with files shown without alphabetical sorting. ([#85](#))
- Made the following fixes and enhancements to the TN3270 application ([#96](#)):
  - Fixed an issue where the application could not be configured to default to a TLS connection.
  - Fixed an issue where it could not handle a TN3270 connection, only TN3270E. Improved preference saving. Administrators can now store default values for terminal mod type, codepage, and screen dimensions.
- Made the following fixes and enhancements for App2App for IFrames ([#24](#), [#107](#)):
  - Fixed an issue with an exception when handling App2App communication with IFrames.
  - Added experimental support for App2App communication with an IFrame application as destination.
- Made the following enhancements to support TopSecret:
  - Added a user-profiles endpoint. ([#113](#))
  - Added an endpoint extraction for groups. ([#129](#))
- Fixed an issue with app names not being internationalized when translations were present. ([#85](#))
- Fixed Russian language errors in translation files. ([#100](#))

- Fixed several issues with using the Application Server as a proxy. ([#93](#))
- Fixed an issue with the App Server throwing exceptions when authorization plugins were installed but not requested. ([#94](#))
- Fixed an issue with ZSS consuming excessive CPU during download. ([#147](#))
- Fixed documentation issue by replacing "zLUX" with "Zowe Application Framework" and "MVD" with "Zowe Desktop." ([#214](#))
- Fixed an issue with an incorrect translation for word "Japanese" in Japanese. ([#108](#))

### **What's new in Zowe CLI and Plug-ins**

The following new commands and enhancements are added:

- Return a list of archived z/OSMF workflows with the `zowe zos-workflows list arw` command. ([#391](#))
- Return a list of systems that are defined to a z/OSMF instance with the `zowe zosmf list systems` command. ([#348](#))
- The `zowe uss issue ssh` command now returns the exit code of the shell command that you issued. ([#359](#))
- The `zowe files upload dtu` command now supports the metadata file named `.zosattributes`. ([#366](#))

The following bugs are fixed:

- Fixed an issue where `zowe workflow ls aw` commands with the `--wn` option failed if there was a space in the workflow name. ([#356](#))
- Fixed an issue where `zowe zowe-files delete uss` command could fail when resource URL includes a leading forward-slash. ([#343](#)).

## **Version 1.2.0 (May 2019)**

Version 1.2.0 contains the following changes since Version 1.1.0.

### **What's new in the Zowe installer**

- Made the following installer improvements:
  - Check whether ICSF is configured before checking Node version to avoid runaway CPU.
  - Warn if the host name that is determined by the installer is not a valid IP address.
  - Fixed a bug where a numeric value is specified in `ZOWE_HOST_NAME` causing errors generating the Zowe certificate.
- Made the following improvements to the `zowe-check-prereqs.sh` script:
  - Improvements for checking and validating the telnet and ssh port required by the Zowe Desktop applications.

### **What's new in API Mediation Layer**

This release of Zowe API ML contains the following user experience improvements:

- Prevented the Swagger UI container on the service detail page from spilling.
- Added a check for the availability of the z/OSMF URL contained in the configuration. z/OSMF is used to verify users logging into the Catalog.
- Made `PageNotFound` error visible only in the debug log level.
- Added zD&T-compatible ciphers and the TLS protocol restricted to 1.2.
- Introduced support for VSCode development.
- Introduced a common cipher configuration property.
- Fixed URL transformation defects.
- Fixed reporting that the Catalog is down when it is started before the Discovery Service.
- Removed the bean overriding error message from the log.
- Fixed the state manipulation mechanism in the Catalog. As a result, no restoring of the application state is performed.
- Fixed the Catalog routing mechanism for a users who is already loggedin so that the user is not prompted to log in again.

- A timeout has been set for Catalog login when z/OSMF is not responding.
- A tile change in the Catalog is now propagated to the UI.
- Fixed a problem with an incorrect service homepage link in the Catalog.
- The Catalog Login button has been disabled when the login request is in progress.

### **What's new in the Zowe App Server**

- Improved security by adding support for RBAC (Role Based Access Control) to enable Zowe to determine whether a user is authorized to access a dataservice.
- Added Zowe Desktop settings feature for specifying the Zowe desktop language.
- Added German language files.
- Fixed a bug by adding missing language files.
- Enabled faster load times by adding support for serving the Zowe Application Framework core components, such as the Desktop, as compressed files in gzip format.
- Added support for application plug-ins to serve static content, such as HTML, JavaScript, and images, to browsers in gzip and brotli compressed files.
- Fixed a Code Editor bug by separating browsing of files and data sets.

### **What's new in Zowe CLI and Plug-ins**

The Zowe CLI core component contains the following improvements and fixes:

- The `zos-uss` command group is added to the core CLI. The commands let you issue Unix System Services shell commands by establishing an SSH connection to an SSH server. For more information, see [#unique\\_48](#).
- The `zowe zos-workflows` command group now contains the following `active-workflow-details` options:
  - `--steps-summary-only` | `--sso` (boolean): An optional parameter that lets you list (only) the steps summary.
  - `--skip-workflow-summary` | `--sws` (boolean): An optional parameter that lets you skip the default workflow summary.
- Zowe CLI was updated to correct an issue where the `zowe zos-workflows start` command ignored the `-- workflow-name` argument.
- Updated and clarified the description the `-- overwrite` option for the `zowe zos-workflows create workflow-from-data-set` command and the Zowe `zos-workflows create workflow-from-uss-file` command.
- The [CLI Reference Guide](#) is featured on the Zowe Docs home page. The document is a comprehensive guide to commands and options in Zowe CLI.
- You can now click the links on the Welcome to Zowe help section and open the URL in a browser window. Note that the shell application must support the capability to display and click hyperlinks.

### **What's new in Zowe USS API**

Made the following enhancements:

- Chtag detection and ascii/ebcdic conversion on GET & PUT requests. For details, see [this issue](#).
- New optional header on GET Unix file content request to force conversion from ebcdic to ascii. For details, see [this issue](#).
- New response header on GET Unix file content requests: E-Tag for overwrite detection and validation. For details, see [this issue](#).
- Reintroduced PUT (update) Unix file content endpoint. For details, see [this issue](#).
- Reintroduced DELETE Unix file content endpoint. For details, see [this issue](#).
- Reintroduced POST (create) Unix file or directory endpoint. For details, see [this issue](#).
- Fixed a problem with incorrect return error when the user requests to view contents of a USS folder they do not have permission to. Now it returns a 403 (Forbidden) error. For details, see [this issue](#).

## Version 1.1.0 (April 2019)

Version 1.1.0 contains the following changes since the last 1.0.x version.

### What's new in Zowe system requirements

z/OSMF Lite is now available for non-production use such as development, proof-of-concept, demo and so on. It simplifies the setup of z/OSMF with only a minimal amount of z/OS customization, but provides key functions that are required. For more information, see [Configuring z/OSMF Lite \(for non-production use\)](#) on page 36.

### What's new in the Zowe App Server

- Made the following user experience improvements:
  - Enabled the Desktop to react to session expiration information from the Zowe Application Server. If a user is active the Desktop renews their session before it expires. If a user appears inactive they are prompted and can click to renew the session. If they don't click, they are logged out with a session expired message.
  - Added the ability to programmatically dismiss popups created with the "zlux-widgets" popup manager.
- Made the following security improvements:
  - Encoded URIs shown in the App Server 404 handler, which prevents some browsers from loading malicious scripts.
  - Documented and support configuring HTTPS on ZSS.
  - For ZSS API callers, added HTTP response headers to instruct clients not to cache HTTPS responses from potentially sensitive APIs.
- Improved the Zowe Editor App by adding app2app communication support that allows the application to open requested directories, dataset listings, and files.
- Improved the Zowe App API by allowing subscription to close events on viewports instead of windows, which allows applications to better support Single App Mode.
- Fixed a bug that generated an extraneous RACF audit message when you started ZSS.
- Fixed a bug that would sometimes move application windows when you attempted to resized them.
- Fixed a bug in the "Getting started with the ZOWE WebUi" tutorial documentation.
- Fixed a bug that caused applications that made ZSS service requests to fail with an HTTP 401 error because of dropped session cookies.

### What's new in the Zowe CLI and Plug-ins

This release of Zowe CLI contains the following new and improved capabilities:

- Added APIs to allow the definition of workflows
- Added the option `max-concurrent-requests` to the `zowe zos-files upload dir-to-uss` command
- Added the option `overwrite` to the `zowe zos-workflows create` commands
- Added the option `workflow-name` to the `zowe zos-workflows` commands
- Added the following commands along with their APIs:
  - `zowe zos-workflows archive active-workflow`
  - `zowe zos-workflows create workflow-from-data-set`
  - `zowe zos-workflows create workflow-from-uss-file`
  - `zowe zos-workflows delete active-workflow`
  - `zowe zos-files list uss-files`

This release of the Plug-in for IBM DB2 Database contains the following new and improved capabilities:

- Implemented command line precedence, which lets users issue commands without the need of a DB2 profile.
- The DB2 plug-in can now be influenced by the `ZOWE_OPT_` environment variables.

## What's new in API Mediation Layer

- Made the following user experience improvements:
  - Documented the procedure for changing the log level of individual code components in *Troubleshooting API ML*.
  - Documented a known issue when the API ML stops accepting connections after z/OS TCP/IP is recycled in the *Troubleshooting API ML*.

## Version 1.0.1 (March 2019)

Version 1.0.1 contains the following changes since the last version.

### What's new in Zowe installation on z/OS

During product operation of the Zowe Cross Memory Server which was introduced in V1.0.0, the z/OSMF user ID IZUSVR or its equivalent must have UPDATE access to the BPX.SERVER and BPX.DAEMON FACILITY classes. The install script will do this automatically if the installing user has enough authority, or provide the commands to be issued manually if not. For more information, see [Installing the Zowe Cross Memory Server on z/OS](#)

### What's new in the Zowe App Server

- Made the following improvements to security:
  - Removed the insecure SHA1 cipher from the Zowe App Server's supported ciphers list.
  - Added instructions to REST APIs to not cache potentially sensitive response contents.
  - Set secure attributes to desktop and z/OSMF session cookies.
- Fixed a bug that caused the configuration data service to mishandle PUT operations with bodies that were not JSON.
- Fixed a bug that prevented IFrame applications from being selected by clicking on their contents.
- Fixed various bugs in the File Explorer and updated it to use newer API changes.
- Fixed a bug in which App2App Communication Actions could be duplicated upon logging in a second time on the same desktop.

### What's new in Zowe CLI

- Create and Manage z/OSMF Workflows using the new `zos-workflows` command group. For more information, see [Zowe CLI command groups](#).
- Use the `@lts-incremental` tag when you install and update Zowe CLI core or plug-ins. The tag ensures that you don't consume breaking changes that affect your existing scripts. Installation procedures are updated to reflect this change.
- A [Zowe CLI quick start](#) on page 22 is now available for users who are familiar with command-line tools and want to get up and running quickly.
- IBM CICS Plug-in for Zowe CLI was updated to support communication over HTTPS. Users can enable https by specifying `--protocol https` when creating a profile or issuing a command. For backwards compatibility, HTTP remains the default protocol.

### What's new in the Zowe REST APIs

Introduced new Unix files APIs that reside in the renamed API catalog tile `z/OS Datasets and Unix files service` (previously named `z/OS Datasets service`). You can use these APIs to:

- List the children of a Unix directory
- Get the contents of a Unix file

## What's changed

- **Zowe explorer apps**
  - JES Explorer: Enhanced Info/Error messages to better help users diagnose problems.
  - MVS Explorer: Fixed an issue where Info/Error messages were not displayed when loading a Dataset/ Members contents.

## Version 1.0.0 (February 2019)

Version 1.0.0 contains the following changes since the Open Beta release.

### What's new in API Mediation Layer

- HTTPs is now supported on all Java enablers for onboarding API microservices with the API ML.
- SSO authentication using z/OSMF has been implemented for the API Catalog login. Mainframe credentials are required for access.

### What's new in Zowe CLI

- **Breaking change to Zowe CLI:** The `--pass` command option is changed to `--password` for all core Zowe CLI commands for clarity and to be consistent with plug-ins. If you have zosmf profiles that you created prior to January 11, 2019, you must recreate them to use the `--password` option. The aliases `--pw` and `--pass` still function when you issue commands as they did prior to this breaking change. You do not need to modify scripts that use `--pass`.
- The `@next` npm tag used to install Zowe CLI is deprecated. Use the `@latest` npm tag to install the product with the online registry method.

### What's new in the Zowe Desktop

- You can now obtain information about an application by right-clicking on an application icon and then clicking **Properties**.
- To view version information for the desktop, click the avatar in the lower right corner of the desktop.
- Additional information was added for the Workflow application.
- The titlebar of the active window is now colored to give an at-a-glance indication of which window is in the foreground.
- Window titlebar maximize button now changes style to indicate whether a window is maximized.
- Windows now have a slight border around them to help see boundaries and determine which window is active.
- Multiple instances of the same application can be opened and tracked from the launchbar. To open multiple instances, right-click and choose **Open New**. Once multiple instances are open, you can click the application icon to select which application to bring to the foreground. The number of orbs below the application icon relates to the number of instances of the application that is open.
- Desktop framework logging trimmed and formalized to the Zowe App Logger. For more information, see <https://github.com/zowe/zlux/wiki/Logging>.
- The UriBroker was updated to support dataservice versioning and UNIX file API updates.
- Removed error messages about missing components .js by making this optional component explicitly declared within an application. By using the property "webContent.hasComponents = true/false".
- Set the maximum username and password length for login to 100 characters each.
- Applications can now list webContent.framework = "angular" as an alias for "angular2".
- Fixed a bug where the desktop might not load on high latency networks.

### What's new in the Zowe App Server

- HTTP support was disabled in favor of HTTPS-only hosting.
- The server can be configured to bind to specific IPs or to hostnames. Previously, the server would listen on all interfaces. For more information, see <https://github.com/zowe/zlux-app-server/pull/30>.
- The core logger prefixes for the Zowe App Server were changed from "\_unp" to "\_zsf".

- Dataservices are now versioned, and dataservices can depend on specific versions of other dataservices. A plug-in can include more than one version of a datasource for compatibility. For more information, see <https://github.com/zowe/zlux/wiki/ZLUX-Dataservices>.
- Support to communicate with the API Mediation Layer with the use of keys and certificates was added.
- Trimmed and corrected error messages regarding unconfigured proxies for clarity and understanding. For more information, see <https://github.com/zowe/zlux-server-framework/pull/33>.
- Fixed the `nodeCluster.sh` script to have its logging and environment variable behavior consistent with `nodeServer.sh`.
- Removed the "swaggerui" plug-in in favor of the API Catalog.
- Bugfix for `/plugins` API to not show the installation location of the plug-in.
- Bugfix to print a warning if the server finds two plug-ins with the same name.
- Added the ability to conditionally add HTTP headers for secure services to instruct the browser not to cache the responses. For more information, see <https://github.com/zowe/zlux-server-framework/issues/36>.
- Added a startup check to confirm that ZSS is running as a prerequisite of the Zowe App Server.
- Bugfix for sending HTTP 404 response when content is missing, instead of a request hanging.
- Added tracing of login, logout, and HTTP routing so that administrators can track access.

## What's changed

- Previously, APIs for z/OS Jobs services and z/OS Data Set services are provided using an IBM WebSphere Liberty web application server. In this release, they are provided using a Tomcat web application server. You can view the associated API documentation corresponding to the z/OS services through the API Catalog.
- References to `zlux-example-server` were changed to `zlux-app-server` and references to `zlux-proxy-server` were changed to `zlux-server-framework`.

## Known issues

### Paste operations from the Zowe Desktop TN3270 and VT Terminal applications

**TN3270 App** - If you are using Firefox, the option to use Ctrl+V to paste is not available. Instead, press Shift + right-click to access the paste option through the context menu.

Pressing Ctrl+V will perform paste for the TN3270 App on other browsers.

**VT Terminal App** - In the VT Terminal App, Ctrl+V will not perform a paste operation for any browser.

**Note:** In both terminals, press Shift + right-click to access copy and paste options through the context menu.

**z/OS Subsystems App** - The z/OS Subsystems application is being removed temporarily for the 1.0 release. The reason is that as the ZSS has transitioned from closed to open source some APIs needed to be re-worked and are not complete yet. Look for the return of the application in a future update.

---

## Zowe CLI quick start

Get started with Zowe CLI quickly and easily.

**Note:** This section assumes some prerequisite knowledge of command-line tools and writing scripts. If you prefer more detailed instructions, see [Installing Zowe CLI](#) on page 73

[]

## Installing

Before you install Zowe CLI, download and install [Node.js](#) and [npm](#).

## Installing Zowe CLI core

```
npm config set @brightside:registry https://api.bintray.com/npm/ca/brightside
```

```
npm install @brightside/core@lts-incremental -g
```

## Installing CLI plug-ins

```
zowe plugins install @brightside/cics@lts-incremental
```

The command installs the IBM CICS plug-in, but the IBM Db2 plug-in requires [Installing](#) on page 125.

For more information, see [Installing plug-ins](#) on page 120.

## Issuing your first commands

Issue zowe --help to display full command help. Append --help (alias -h) to any command to see available command actions and options.

To interact with the mainframe, type zowe followed by a command group, action, and object. Use options to specify your connection details such as password and system name.

### Listing all data sets under a high-level qualifier (HLQ)

```
zowe zos-files list data-set "MY.DATASET.*" --host my.company.com --port 123  
--user myusername123 --pass mypassword123
```

### Downloading a partitioned data-set (PDS) member to local file

```
zowe zos-files download data-set "MY.DATA.SET(member)" -f "mylocalfile.txt"  
--host my.company.com --port 123 --user myusername123 --pass mypassword123
```

See [Command Groups](#) for a list of available functionality.

## Using profiles

Zowe profiles let you store configuration details such as username, password, host, and port for a mainframe system. Switch between profiles to quickly target different subsystems and avoid typing connection details on every command.

### Profile types

Most command groups require a `zosmf-profile`, but some plug-ins add their own profile types. For example, the CICS plug-in has a `cics-profile`. The profile type that a command requires is defined in the PROFILE OPTIONS section of the help response.

**Tip:** The first `zosmf` profile that you create becomes your default profile. If you don't specify any options on a command, the default profile is used. Issue `zowe profiles -h` to learn about listing profiles and setting defaults.

### Creating a zosmf profile

```
zowe profiles create zosmf-profile myprofile123 --host my.company.com --port  
123 --user myusername123 --password mypassword123
```

**Note:** The port defaults to 443 if you omit the `--port` option. Specify a different port if your host system does not use port 443.

## Using a zosmf profile

```
zowe zos-files download data-set "MY.DATA.SET(member)" -f "mylocalfile.txt"
--zosmf-profile myprofile123
```

For detailed information about issuing commands, using profiles, and storing variables as environment variables, see [Defining Zowe CLI connection details](#) on page 88

## Writing scripts

You can write Zowe CLI scripts to streamline your daily development processes or conduct mainframe actions from an off-platform automation tool such as Jenkins or TravisCI.

### Example:

You want to delete a list of temporary datasets. Use Zowe CLI to download the list, loop through the list, and delete each data set using the `zowe zos-files delete` command.

```
#!/bin/bash

set -e

# Obtain the list of temporary project data sets
dslist=$(zowe zos-files list dataset "my.project.ds*")

# Delete each data set in the list
IFS=$'\n'
for ds in $dslist
do
    echo "Deleting Temporary Project Dataset: $ds"
    zowe files delete ds "$ds" -f
done
```

For more information, see [Writing scripts to automate mainframe actions](#).

## Next Steps

You successfully installed Zowe CLI, issued your first commands, and wrote a simple script! Next, you might want to:

- Review [Command Groups](#) to learn what functionality is available, and explore the in-product help.
- Learn about [Defining Environment Variables](#) on page 90 to store configuration options.
- Integrate your scripts with an automation server like Jenkins.
- See what [Extending Zowe CLI](#) on page 120 for the CLI.
- Learn about [Developing a new plug-in](#) on page 183 (contributing to core and developing plug-ins).

## Frequently Asked Questions

---

Check out the following FAQs to learn more about the purpose and function of Zowe.

- [Zowe FAQ](#) on page 24
- [Zowe CLI FAQ](#) on page 26

## Zowe FAQ

### What is Zowe?

Click to show answer

Zowe is an open source project within the [Open Mainframe Project](#) that is part of [The Linux Foundation](#). The Zowe project provides modern software interfaces on IBM z/OS to address the needs of a variety of modern users. These interfaces include a new web graphical user interface, a scriptable command-line interface, extensions to existing REST APIs, and new REST APIs on z/OS.

### **Who is the target audience for using Zowe?**

Click to show answer

Zowe technology can be used by a variety of mainframe IT and non-IT professionals. The target audience is primarily application developers and system programmers, but the Zowe Application Framework is the basis for developing web browser interactions with z/OS that can be used by anyone.

### **What language is Zowe written in?**

Click to show answer

Zowe consists of several components. The primary languages are Java and JavaScript. Zowe CLI is written in TypeScript.

### **What is the licensing for Zowe?**

Click to show answer

Zowe source code is licensed under EPL2.0. For license text click [here](#) and for additional information click [here](#).

In the simplest terms (taken from the FAQs above) - "...if you have modified EPL-2.0 licensed source code and you distribute that code or binaries built from that code outside your company, you must make the source code available under the EPL-2.0."

### **Why is Zowe licensed using EPL2.0?**

Click to show answer

The Open Mainframe Project wants to encourage adoption and innovation, and also let the community share new source code across the Zowe ecosystem. The open source code can be used by anyone, provided that they adhere to the licensing terms.

### **What are some examples of how Zowe technology might be used by z/OS products and applications?**

Click to show answer

The Zowe Desktop (web user interface) can be used in many ways, such as to provide custom graphical dashboards that monitor data for z/OS products and applications.

Zowe CLI can also be used in many ways, such as for simple job submission, data set manipulation, or for writing complex scripts for use in mainframe-based DevOps pipelines.

The increased capabilities of RESTful APIs on z/OS allows APIs to be used in programmable ways to interact with z/OS services.

### **What is the best way to get started with Zowe?**

Click to show answer

Zowe provides a convenience build that includes the components released-to-date, as well as IP being considered for contribution, in an easy to install package on [Zowe.org](#). The convenience build can be easily installed and the Zowe capabilities seen in action.

To install the complete Zowe solution, see [Planning the installation](#) on page 30.

To get up and running with the Zowe CLI component quickly, see [Zowe CLI quick start](#) on page 22.

### **What are the prerequisites for Zowe?**

Click to show answer

The primary prerequisites is Java on z/OS and the z/OS Management Facility enabled and configured. For a complete list of software requirements listed by component, see [System requirements](#) on page 31.

**How is access security managed on z/OS?**

Click to show answer

Zowe components use typical z/OS System authorization facility (SAF) calls for security.

**How is access to the Zowe open source managed?**

Click to show answer

The source code for Zowe is maintained on an Open Mainframe Project GitHub server. Everyone has read access. "Committers" on the project have authority to alter the source code to make fixes or enhancements. A list of Committers is documented in [Committers to the Zowe project](#).

**How do I get involved in the open source development?**

Click to show answer

The best way to get started is to join a [Zowe Slack channel](#) and/or email distribution list and begin learning about the current capabilities, then contribute to future development.

For more information about emailing lists, community calendar, meeting minutes, and more, see the [Zowe Community](#) GitHub repo.

For information and tutorials about extending Zowe with a new plug-in or application, see [Onboarding Overview](#) on page 130 on Zowe Docs.

**When will Zowe be completed?**

Click to show answer

Zowe will continue to evolve in the coming years based on new ideas and new contributions from a growing community.

**Can I try Zowe without a z/OS instance?**

Click to show answer

IBM has contributed a free hands-on tutorial for Zowe. Visit the [Zowe Tutorial page](#) to learn about adding new applications to the Zowe Desktop and how to enable communication with other Zowe components.

The Zowe community is also currently working to provide a vendor-neutral site for an open z/OS build and sandbox environment.

Zowe is also compatible with IBM z/OSMF Lite for non-production use. For more information, see [Configuring z/OSMF Lite \(for non-production use\)](#) on page 36 on Zowe Docs.

## Zowe CLI FAQ

**Why might I use Zowe CLI versus a traditional ISPF interface to perform mainframe tasks?**

Click to show answer

For developers new to the mainframe, command-line interfaces might be more familiar than an ISPF interface. Zowe CLI lets developers be productive from day-one by using familiar tools. Zowe CLI also lets developers write scripts that automate a sequence of mainframe actions. The scripts can then be executed from off-platform automation tools such as Jenkins automation server, or manually during development.

**With what tools is Zowe CLI compatible?**

Click to show answer

Zowe CLI is very flexible; developers can integrate with modern tools that work best for them. It can work in conjunction with popular build and testing tools such as Gulp, Gradle, Mocha, and Junit. Zowe CLI runs on a variety of operating systems, including Windows, macOS, and Linux. Zowe CLI scripts can be abstracted into automation tools such as Jenkins and TravisCI.

**Where can I use the CLI?**

Click to show answer

Usage Scenario	Example
Interactive use, in a command prompt or bash terminal.	Perform one-off tasks such as submitting a batch job.
Interactive use, in an IDE terminal	Download a data set, make local changes in your editor, then upload the changed dataset back to the mainframe.
Scripting, to simplify repetitive tasks	Write a shell script that submits a job, waits for the job to complete, then returns the output.
Scripting, for use in automated pipelines	Add a script to your Jenkins (or other automation tool) pipeline to move artifacts from a mainframe development system to a test system.

### Which method should I use to install Zowe CLI?

Click to show answer

You can install Zowe CLI using the following methods:

- **Local package installation:** The local package method lets you install Zowe CLI from a zipped file that contains the core application and all plug-ins. When you use the local package method, you can install Zowe CLI in an offline environment. We recommend that you download the package and distribute it internally if your site does not have internet access.
- **Online NPM registry:** The online NPM (Node Package Manager) registry method unpacks all of the files that are necessary to install Zowe CLI using the command line. When you use the online registry method, you need an internet connection to install Zowe CLI

### How can I get help with using Zowe CLI?

Click to show answer

- You can get help for any command, action, or option in Zowe CLI by issuing the command 'zowe --help'.
- For information about the available commands in Zowe CLI, see [Command Groups](#).
- If you have questions, the [Zowe Slack space](#) is the place to ask our community!

### How can I use Zowe CLI to automate mainframe actions?

Click to show answer

- You can automate a sequence of Zowe CLI commands by writing bash scripts. You can then run your scripts in an automation server such as Jenkins. For example, you might write a script that moves your Cobol code to a mainframe test system before another script runs the automated tests.
- Zowe CLI lets you manipulate data sets, submit jobs, provision test environments, and interact with mainframe systems and source control management, all of which can help you develop robust continuous integration/delivery.

### How can I contribute to Zowe CLI?

Click to show answer

As a developer, you can extend Zowe CLI in the following ways:

- Build a plug-in for Zowe CLI
- Contribute code to the core Zowe CLI
- Fix bugs in Zowe CLI or plug-in code, submit enhancement requests via GitHub issues, and raise your ideas with the community in Slack.

**Note:** For more information, see [How can I contribute?](#) on page 176.



---

# Chapter 2

---

## User Guide

---

### Topics:

- [Installing Zowe](#)
  - [Configuring Zowe](#)
  - [Using Zowe](#)
  - [Zowe CLI extensions and plug-ins](#)
- 

# Installing Zowe

---


## Planning the installation

The installation of Zowe consists of two independent processes: installing Zowe runtime on z/OS and installing Zowe CLI on your computer.

When you install Zowe runtime on z/OS, there are two parts:

- The first part is to install the Zowe Application Framework, the API Mediation Layer, and a number of micro services that provide capability to both.
- The second part is to install the Zowe Cross Memory Server. This is an authorized server application that provides privileged services to Zowe in a secure manner.

The Zowe CLI is not installed on z/OS and runs on a personal computer. The following diagram shows the installation location of Zowe components.



## Installation roadmap

Installing Zowe involves several steps that you must complete in the order listed. Review the following table that presents the task-flow for preparing your environment and installing and configuring Zowe before you begin the installation process.

1. Review the pre-installation planning information and prepare your environment to meet the installation prerequisites. | See [Planning the installation of Zowe z/OS components](#) and [System requirements](#) on page 31.
2. Allocate enough space for the installation. | The installation process requires approximately 1 GB of available space. Once installed on z/OS, API Mediation Layer requires approximately 150MB of space, and the Zowe Application Framework requires approximately 50 MB of space before configuration. Zowe CLI requires approximately 200 MB of space on your computer.
3. Download the installation files and install components of Zowe. | To install Zowe runtime on z/OS, see [Installing Zowe on z/OS](#) on page 53. To install Zowe CLI on a computer, see [Installing Zowe CLI](#) on page 73.
4. (Optional) Troubleshoot problems that occur during installation. | See [Troubleshooting](#) on page 244. To uninstall Zowe, see [Uninstalling Zowe](#) on page 75.

## Planning the installation of Zowe z/OS components

The following information is required during the installation process of API Mediation Layer and Zowe Application Framework. Make the decisions before the installation.

- The HFS directory where you install Zowe.
- The HFS directory that contains a 64-bit Java™ 8 JRE.
- The z/OSMF installation directory, for example, /usr/lpp/zosmf/lib.
- The API Mediation Layer HTTP and HTTPS port numbers. You will be asked for 3 unique port numbers.

- The user ID that runs the Zowe started task.
- Tip:** Use the same user ID that runs the z/OSMF IZUSVR1 task, or a user ID with equivalent authorizations.
- The mainframe account under which the ZSS server runs must have UPDATE permission on the BPX.DAEMON and BPX.SERVER facility class profiles.

## System requirements

Before installing Zowe, ensure that your environment meets the prerequisites.

- [Common system requirements](#) on page 31
- [Zowe Application Framework requirements](#) on page 31
- [Zowe CLI requirements](#) on page 31

### Common system requirements

- z/OS Version 2.2 or later.
- IBM z/OS Management Facility (z/OSMF) Version 2.2 or Version 2.3

z/OSMF is a prerequisite for the Zowe microservices, Zowe Desktop applications, and Zowe CLI. z/OSMF must be installed and running before you use Zowe.

::: tip

- For non-production use of Zowe (such as development, proof-of-concept, demo), you can customize the configuration of z/OSMF to create what is known as "z/OS MF Lite" that simplifies the setup of z/OSMF. As z/OS MF Lite only supports selected REST services (JES, DataSet/File, TSO and Workflow), you will observe considerable improvements in start up time as well as a reduction in the efforts involved in setting up z/OSMF. For information about how to set up z/OSMF Lite, see [Configuring z/OSMF Lite \(for non-production use\)](#) on page 36
- For production use of Zowe, see [Configuring z/OSMF](#) on page 33. :::

### Zowe Application Framework requirements

- Node.js version 6.14.4.1 or later *on the z/OS host* where you install the Zowe Application Server. To install Node.js on z/OS, follow the instructions in [Installing Node.js on z/OS](#) on page 32.
- IBM SDK for Java Technology Edition V8 or later
- 833 MB of HFS file space
- Supported browsers:
  - Google Chrome V66 or later
  - Mozilla Firefox V60 or later
  - Safari V11.1 or later
  - Microsoft Edge 17 (Windows 10)

### Zowe CLI requirements

Zowe CLI is supported on platforms where Node.js 8.0 or 10 is available, including Windows, Linux, and Mac operating systems.

- [Node.js V8.0 or later](#) on your computer

**Tip:** You might need to restart the command prompt after installing Node.js. Issue the command `node --version` to verify that Node.js is installed. As a best practice, we recommend that you update Node.js regularly to the latest Long Term Support (LTS) version.

- [Node Package Manager V5.0 or later](#) on your computer.

npm is included with the Node.js installation. Issue the command `npm --version` to verify that npm is installed.

## Free disk space

Zowe CLI requires approximately **100 MB** of free disk space. The actual quantity of free disk space consumed might vary depending on the operating system where you install Zowe CLI.

## Installing Node.js on z/OS

Installing Zowe requires Node.js version 6.14.4.1 or later to be installed on the z/OS host where you install the Zowe Application Server.

### How to obtain IBM SDK for Node.js - z/OS

IBM SDK for Node.js - z/OS, V6.0 (5655-SDK) is available at no license charge, as [announced in October 2018](#). You can obtain the free SDK for IBM Z Mainframe in one of several ways, depending on your requirements. For details, see the blog "[How to obtain IBM SDK for Node.js - z/OS, at no charge](#)".

To satisfy Zowe's prerequisite for Node.js - z/OS, you can choose one of the following ways:

- Order the SMP/E version through your IBM representative for production use
- Use the pax evaluation for non-production deployments

### Hardware and software requirements

#### Hardware:

IBM zEnterprise® 196 (z196) or newer

#### Software:

- Node.js version 6 (see [IBM Knowledge Center](#) for all prerequisites):
  - z/OS V2R2 with PTF UI46658 or z/OS V2R3
- Node.js v8 (see [IBM Knowledge Center](#) for all prerequisites):
  - z/OS 2.2: PTFs UI62788, UI46658, UI62416 (APARs PH10606, PI79959, PH10740)
  - z/OS 2.3: PTFs UI61308, UI61376 and UI61747 (APARs PH07107, PH08353 and PH09543)
- z/OS UNIX System Services enabled
- Integrated Cryptographic Service Facility (ICSF) configured and started.

## Installing Node.js

The following section summarizes the required configuration steps for **installing the pax evaluation version of Node.js - z/OS** to run Zowe.

1. Download the pax.Z file from the [Download](#) section to a z/OS machine.
2. Extract the pax.Z file inside an installation directory of your choice. For example:

```
pax -rf <path_to_pax.Z_file> -x pax
```

3. Add the full path of your installation directory to your PATH environment variable:

```
export PATH=<installation_directory>/bin/:$PATH
```

4. Run the following command from the command line to verify the installation.

```
node --version
```

If Node.js is installed, the version of Node.js is displayed.

5. After you install Node.js, set the *NODE\_HOME* environment variable to the directory where Node.js is installed. For example, *NODE\_HOME=/proj/mvd/node/install/node-v6.14.4-os390-s390x*.

To troubleshoot or read more information, see the [documentation for IBM SDK for Node.js - z/OS](#).

## Configuring z/OSMF

The following information contains procedures and tips for meeting z/OSMF requirements. For complete information, go to [IBM Knowledge Center](#) and read the following documents.

- [IBM z/OS Management Facility Configuration Guide](#)
- [IBM z/OS Management Facility Help](#)

### z/OS requirements

Ensure that the z/OS system meets the following requirements:

Requirements	Description	Resources in IBM Knowledge Center
Integrated Cryptographic Service Facility (ICSF)	On z/OS, Node requires ICSF to be installed, configured and started.	N/A
AXR (System REXX)	z/OS uses AXR (System REXX) component to perform Incident Log tasks. The component enables REXX executable files to run outside of conventional TSO and batch environments.	<a href="#">System REXX</a>
Common Event Adapter (CEA) server	The CEA server, which is a co-requisite of the Common Information Model (CIM) server, enables the ability for z/OSMF to deliver z/OS events to C-language clients.	<a href="#">Customizing for CEA</a>
Common Information Model (CIM) server	z/OSMF uses the CIM server to perform capacity-provisioning and workload-management tasks. Start the CIM server before you start z/OSMF (the IZU* started tasks).	<a href="#">Reviewing your CIM server setup</a>
CONSOLE and CONSPROF commands	The CONSOLE and CONSPROF commands must exist in the authorized command table.	<a href="#">Customizing the CONSOLE and CONSPROF commands</a>
Java level	IBM® 64-bit SDK for z/OS®, Java Technology Edition V8 or later is required.	<a href="#">Software prerequisites for z/OSMF</a>
TSO region size	To prevent <b>exceeds maximum region size</b> errors, verify that the TSO maximum region size is a minimum of 65536 KB for the z/OS system.	N/A
User IDs	User IDs require a TSO segment (access) and an OMVS segment. During workflow processing and REST API requests, z/OSMF might start one or more TSO address spaces under the following job names: userid; substr(userid, 1, 6) CN (Console).	N/A

## Configuring z/OSMF

### Follow these steps:

- From the console, issue the following command to verify the version of z/OS:

```
/D IPLINFO
```

Part of the output contains the release, for example,

```
RELEASE z/OS 02.02.00.
```

- Configure z/OSMF.

z/OSMF is a base element of z/OS V2.2 and V2.3, so it is already installed. But it might not be configured and running on every z/OS V2.2 and V2.3 system.

In short, to configure an instance of z/OSMF, run the IBM-supplied jobs IZUSEC and IZUMKFS, and then start the z/OSMF server. The z/OSMF configuration process occurs in three stages, and in the following order:

- Stage 1 - Security setup
- Stage 2 - Configuration
- Stage 3 - Server initialization

This stage sequence is critical to a successful configuration. For complete information about how to configure z/OSMF, see [Configuring z/OSMF](#) if you use z/OS V2.2 or [Setting up z/OSMF for the first time](#) if V2.3.

**Note:** In z/OS V2.3, the base element z/OSMF is started by default at system initial program load (IPL). Therefore, z/OSMF is available for use as soon as you set up the system. If you prefer not to start z/OSMF automatically, disable the autostart function by checking for START commands for the z/OSMF started procedures in the *COMMNDxx parmlib* member.

The z/OS Operator Consoles task is new in Version 2.3. Applications that depend on access to the operator console such as Zowe CLI's RestConsoles API require Version 2.3.

- Verify that the z/OSMF server and angel processes are running. From the command line, issue the following command:

```
/D A,IZU*
```

If jobs IZUANG1 and IZUSVR1 are not active, issue the following command to start the angel process:

```
/S IZUANG1
```

After you see the message ""CWWKB0056I INITIALIZATION COMPLETE FOR ANGEL"", issue the following command to start the server:

```
/S IZUSVR1
```

The server might take a few minutes to initialize. The z/OSMF server is available when the message ""CWWKF0011I: The server zosmfServer is ready to run a smarter planet."" is displayed.

- Issue the following command to find the startup messages in the SDSF log of the z/OSMF server:

```
f IZUG349I
```

You could see a message similar to the following message, which indicates the port number:

```
IZUG349I: The z/OSMF STANDALONE Server home page can be accessed at  
https://mvs.hursley.ibm.com:443/zosmf after the z/OSMF server is started  
on your system.
```

In this example, the port number is 443. You will need this port number later.

Point your browser at the nominated z/OSMF STANDALONE Server home page and you should see its Welcome Page where you can log in.

**Note:** If your implementation uses an external security manager other than RACF (for example, CA Top Secret for z/OS or CA ACF2 for z/OS), you provide equivalent commands for your environment. For more information, see the following product documentation:

- Configure z/OS Management Facility for CA Top Secret
- Configure z/OS Management Facility for CA ACF2

### **z/OSMF REST services for the Zowe CLI**

The Zowe CLI uses z/OSMF Representational State Transfer (REST) APIs to work with system resources and extract system data. Ensure that the following REST services are configured and available.

<b>z/OSMF REST services</b>	<b>Requirements</b>	<b>Resources in IBM knowledge Center</b>
Cloud provisioning services	Cloud provisioning services are required for the Zowe CLI CICS and Db2 command groups. Endpoints begin with /zosmf/provisioning/	<a href="#">Cloud provisioning services</a>
TSO/E address space services	TSO/E address space services are required to issue TSO commands in the Zowe CLI. Endpoints begin with /zosmf/tsoApp	<a href="#">TSO/E address space services</a>
z/OS console services	z/OS console services are required to issue console commands in the Zowe CLI. Endpoints begin with /zosmf/restconsoles/	<a href="#">z/OS console</a>
z/OS data set and file REST interface	z/OS data set and file REST interface is required to work with mainframe data sets and UNIX System Services files in the Zowe CLI. Endpoints begin with /zosmf/restfiles/	<a href="#">z/OS data set and file interface</a>
z/OS jobs REST interface	z/OS jobs REST interface is required to use the zos-jobs command group in the Zowe CLI. Endpoints begin with /zosmf/restjobs/	<a href="#">z/OS jobs interface</a>

z/OSMF REST services	Requirements	Resources in IBM knowledge Center
z/OSMF workflow services	z/OSMF workflow services is required to create and manage z/OSMF workflows on a z/OS system. Endpoints begin with /zosmf/workflow/	<a href="#">z/OSMF workflow services</a>

Zowe uses symbolic links to the `zosmf.bootstrap.properties`, `jvm.security.override.properties`, and `ltpa.keys` files. Zowe reuses SAF, SSL, and LTPA configurations; therefore, they must be valid and complete.

For more information, see [Using the z/OSMF REST services](#) in IBM z/OSMF documentation.

To verify that z/OSMF REST services are configured correctly in your environment, enter the REST endpoint into your browser. For example: <https://mvs.ibm.com:443/zosmf/restjobs/jobs>

#### Notes:

- Browsing z/OSMF endpoints requests your user ID and password for defaultRealm; these are your TSO user credentials.
- The browser returns the status code 200 and a list of all jobs on the z/OS system. The list is in raw JSON format.

## Configuring z/OSMF Lite (for non-production use)

This section provides information about requirements for z/OSMF Lite configuration.

**Disclaimer:** z/OSMF Lite can be used in a non-production environment such as development, proof-of-concept, demo and so on. It is not for use in a production environment. To use z/OSMF in a production environment, see [Configuring z/OSMF](#) on page 33.

1. [Introduction](#) on page 37
2. [Assumptions](#) on page 37
3. [Software Requirements](#) on page 37
  - a. [Minimum Java level](#) on page 37
  - b. [WebSphere® Liberty profile \(z/OSMF V2R3 and later\)](#)
  - c. [System settings](#) on page 38
  - d. [Web browser](#) on page 38
4. [Creating a z/OSMF nucleus on your system](#)
  - a. [Running job IZUNUSEC to create security](#) on page 39
  - b. [Running job IZUMKFS to create the z/OSMF user file system](#)
  - c. [Copying the IBM procedures into JES PROCLIB](#) on page 42
  - d. [Starting the z/OSMF server](#)
  - e. [Accessing the z/OSMF Welcome page](#)
  - f. [Mounting the z/OSMF user file system at IPL time](#)
5. [Adding the required REST services](#) on page 47
  - a. [Enabling the z/OSMF JOB REST services](#)
  - b. [Enabling the TSO REST services](#) on page 48
  - c. [Enabling the z/OSMF data set and file REST services](#)
  - d. [Enabling the z/OSMF Workflow REST services and Workflows task UI](#)
6. [Troubleshooting problems](#) on page 50
  - a. [Common problems and scenarios](#) on page 50
  - b. [Tools and techniques for troubleshooting](#) on page 51
- [Appendix A. Creating an IZUPRMxx parmlib member](#) on page 51

- [Appendix B. Modifying IZUSVR1 settings](#) on page 53
- [Appendix C. Adding more users to z/OSMF](#)

## Introduction

IBM® z/OS® Management Facility (z/OSMF) provides extensive system management functions in a task-oriented, web browser-based user interface with integrated user assistance, so that you can more easily manage the day-to-day operations and administration of your mainframe z/OS systems.

By following the steps in this guide, you can quickly enable z/OSMF on your z/OS system. This simplified approach to set-up, known as "z/OSMF Lite", requires only a minimal amount of z/OS customization, but provides the key functions that are required by many exploiters, such as the open mainframe project (Zowe).

A z/OSMF Lite configuration is applicable to any future expansions you make to z/OSMF, such as adding more optional services and plug-ins.

It takes 2-3 hours to set up z/OSMF Lite. Some steps might require the assistance of your security administrator.

For detailed information about various aspects of z/OSMF configuration such as enabling the optional plug-ins and services, see the IBM publication [z/OSMF Configuration Guide](#).

## Assumptions

This document is intended for a first time z/OSMF setup. If z/OSMF is already configured on your system, you do not need to create a z/OSMF Lite configuration.

This document is designed for use with a single z/OS system, not a z/OS sysplex. If you plan to run z/OSMF in a sysplex, see [z/OSMF Configuration Guide](#) for multi-system considerations.

It is assumed that a basic level of security for z/OSMF is sufficient on the z/OS system. IBM provides a program, IZUNUSEC, to help you set up basic security for a z/OSMF Lite configuration.

System defaults are used for the z/OSMF environmental settings. Wherever possible, it is recommended that you use the default values. If necessary, however, you can override the defaults by supplying an IZUPRMxx member, as described in [Appendix A. Creating an IZUPRMxx parmlib member](#) on page 51.

It is recommended that you use the following procedures as provided by IBM:

- Started procedures IZUSVR1 and IZUANG1
- Logon procedure IZUFPROC

Information about installing these procedures is provided in [Copying the IBM procedures into JES PROCLIB](#) on page 42.

## Software Requirements

Setting up z/OSMF Lite requires that you have access to a z/OS V2R2 system or later. Also, your z/OS system must meet the following minimum software requirements:

- [Minimum Java level](#) on page 37
- [WebSphere® Liberty profile \(z/OSMF V2R3 and later\)](#)
- [System settings](#) on page 38
- [Web browser](#) on page 38

### Minimum Java level

Java™ must be installed and operational on your z/OS system, at the required minimum level. See the table that follows for the minimum level and default location. If you installed Java in another location, you must specify the JAVA\_HOME statement in your IZUPRMxx parmlib member, as described in [Appendix A. Creating an IZUPRMxx parmlib member](#) on page 51.

<b>z/OS Version</b>	<b>Minimum level of Java™</b>	<b>Recommended level of Java</b>	<b>Default location</b>
z/OS V2R2	IBM® 64-bit SDK for z/OS®, Java Technology Edition V7.1 (SR3), with the PTFs for APAR PI71018 and APAR PI71019 applied <b>OR</b> IBM® 64-bit SDK for z/OS®, Java Technology Edition V8, with the PTF for APAR PI72601 applied.	IBM® 64-bit SDK for z/OS®, Java™ Technology Edition, V8 SR6 (5655-DGH)	/usr/lpp/java/J7.1_64
z/OS V2R3	IBM® 64-bit SDK for z/OS®, Java™ Technology Edition, V8 SR4 FP10 (5655-DGH)	IBM® 64-bit SDK for z/OS®, Java™ Technology Edition, V8 SR6 (5655-DGH)	/usr/lpp/java/J8.0_64

### WebSphere® Liberty profile (z/OSMF V2R3 and later)

z/OSMF V2R3 uses the Liberty Profile that is supplied with z/OS, rather than its own copy of Liberty. The WebSphere Liberty profile must be mounted on your z/OS system. The default mount point is: /usr/lpp/liberty\_zos. To determine whether WebSphere® Liberty profile is mounted, check for the existence of the mount point directory on your z/OS system.

If WebSphere® Liberty profile is mounted at a non-default location, you need to specify the location in the IZUSVR1 started procedure on the keyword **WLPDIR=**. For details, see [Appendix B. Modifying IZUSVR1 settings](#) on page 53.

Note: Whenever you apply PTFs for z/OSMF, you might be prompted to install outstanding WebSphere Liberty service. It is recommended that you do so to maintain z/OSMF functionality.

### System settings

Ensure that the z/OS host system meets the following requirements:

- Port 443 (default port) is available for use.
- The system host name is unique and maps to the system on which z/OSMF Lite will be configured.

Otherwise, you might encounter errors later in the process. If you encounter errors, see [Troubleshooting problems](#) on page 50 for the corrective actions to take.

### Web browser

For the best results with z/OSMF, use one of the following web browsers on your workstation:

- Microsoft Internet Explorer Version 11 or later
- Microsoft Edge (Windows 10)
- Mozilla Firefox ESR Version 52 or later.

To check your web browser's level, click **About** in the web browser.

### Creating a z/OSMF nucleus on your system

The following system changes are described in this chapter:

- [Running job IZUNUSEC to create security](#) on page 39
- [Running job IZUMKFS to create the z/OSMF user file system](#)
- [Copying the IBM procedures into JES PROCLIB](#) on page 42
- [Starting the z/OSMF server](#)
- [Accessing the z/OSMF Welcome page](#)

- [Mounting the z/OSMF user file system at IPL time](#)

The following sample jobs that you might use are included in the package and available for download:

- IZUAUTH
- IZUICSEC
- IZUNUSEC\_V2R2
- IZUNUSEC\_V2R3
- IZUPRM00
- IZURFSEC
- IZUTSSEC
- IZUWFSEC

#### [Download sample jobs](#)

Check out the video for a demo of the process:

#### **Running job IZUNUSEC to create security**

The security job IZUNUSEC contains a minimal set of RACF® commands for creating security profiles for the z/OSMF nucleus. The profiles are used to protect the resources that are used by the z/OSMF server, and to grant users access to the z/OSMF core functions. IZUNUSEC is a simplified version of the sample job IZUSEC, which is intended for a more complete installation of z/OSMF.

**Note:** If your implementation uses an external security manager other than RACF (for example, CA Top Secret or CA ACF2), provide equivalent commands for your environment. For more information, see the following CA Technologies product documentation:

- [Configure z/OS Management Facility for CA Top Secret](#)
- [Configure z/OS Management Facility for CA ACF2](#)

#### *Before you begin*

In most cases, you can run the IZUNUSEC security job without modification. To verify that the job is okay to run as is, ask your security administrator to review the job and modify it as necessary for your security environment. If security is not a concern for the host system, you can run the job without modification.

#### *Procedure*

1. If you run z/OS V2R2 or V2R3, download job IZUNUSEC in the [sample jobs package](#) and upload this job to z/OS. If you run z/OS V2R4, locate job IZUNUSEC at SYS1.SAMPLIB.
2. Review and edit the job, if necessary.
3. Submit IZUNUSEC as a batch job on your z/OS system.
4. Connect your user ID to IZUADMIN group.
  - a. Download job IZUAUTH in the [sample jobs package](#) and customize it.
  - b. Replace the 'userid' with your z/OSMF user ID.
  - c. Submit the job on your z/OS system.

#### *Results*

Ensure the IZUNUSEC job completes with return code 0000.

To verify, check the results of the job execution in the job log. For example, you can use SDSF to examine the job log:

1. In the SDSF primary option menu, select Option ST.
2. On the SDSF Status Display, enter S next to the job that you submitted.
3. Check the return code of the job. The job succeeds if '0000' is returned.

#### *Common errors*

Review the following messages and the corresponding resolutions as needed:

Symptom	Cause	Resolution
Message IKJ56702I: INVALID data is issued	The job is submitted more than once.	You can ignore this message.
Job fails with an authorization error.	Your user ID lacks superuser authority.	Contact your security admin to run IZUNUSEC. If you are using RACF®, select a user ID with SPECIAL attribute which can issue all RACF® commands.
Job fails with an authorization error.	Your installation uses the RACF PROTECT-ALL option.	See <a href="#">Troubleshooting problems</a> on page 50.
ADDGROUP and ADDUSER commands are not executed.	The automatic GID and UID assignment is required.	Define SHARED.IDS and BPX.NEXT.USER profiles to enable the use of AUTOUID and AUTOgid.

### Running job IZUMKFS to create the z/OSMF user file system

The job IZUMKFS initializes the z/OSMF user file system, which contains configuration settings and persistence information for z/OSMF.

The job mounts the file system. On a z/OS V2R3 system with the PTF for APAR PI92211 installed, the job uses mount point /global/zosmf. Otherwise, for an earlier system, the job mounts the file system at mount point /var/zosmf.

#### *Before you begin*

To perform this step, you need a user ID with "superuser" authority on the z/OS host system. For more information about how to define a user with superuser authority, see the publication [z/OS UNIX System Services](#).

#### *Procedure*

1. In the system library SYS1.SAMPLIB, locate job IZUMKFS.
2. Copy the job.
3. Review and edit the job:
  - Modify the job information so that the job can run on your system.
  - You must specify a volume serial (VOLSER) to be used for allocating a data set for the z/OSMF data directory.
4. Submit IZUMKFS as a batch job on your z/OS system.

#### *Results*

The z/OSMF file system is allocated, formatted, and mounted, and the necessary directories are created.

To verify if the file system is allocated, formatted, locate the following messages in IZUMKFS job output.

```
IDC0002I IDCAMS PROCESSING COMPLETE. MAX CONDITION CODE WAS 0.
IOEZ00077I HFS-compatibility aggregate izu.sizuusrd has been successfully
created.
```

Sample output:

Session A - - POKVMTI4 62x160.ws - [24 x 80]  
File Edit View Communication Actions Window Help

```

Display Filter View Print Options Search Help
-----
SDSF OUTPUT DISPLAY IZUMKFS JOB000028 DSID      2 LINE 0      COLUMNS 02- 81
COMMAND INPUT ===> _                               SCROLL ==> PAGE
***** TOP OF DATA *****
J E S 2 J O B L O G -- S Y S T E M S Y 1   - - N O D E

01.35.00 JOB000028 ---- TUESDAY, 25 SEP 2018 ----
01.35.00 JOB000028 IRR0101 USERID IBMUSER IS ASSIGNED TO THIS JOB.
01.35.00 JOB000028 ICH700011 IBMUSER LAST ACCESS AT 01:27:32 ON TUESDAY, SEPTEMBER 25, 2018
01.35.00 JOB000028 SHASP373 IZUMKFS STARTED - INIT 1 - CLASS A - SYS
01.35.00 JOB000028 IEF403I IZUMKFS - STARTED - TIME=01.35.00
01.35.02 JOB000028 IEF404I IZUMKFS - ENDED - TIME=01.35.02
01.35.02 JOB000028 SHASP395 IZUMKFS ENDED - RC=0000
----- JES2 JOB STATISTICS -----
25 SEP 2018 JOB EXECUTION DATE
    77 CARDS READ
    168 SYSOUT PRINT RECORDS
        0 SYSOUT PUNCH RECORDS
        18 SYSOUT SPOOL KBYTES
    0.03 MINUTES EXECUTION TIME
F1=HELP      F2=SPLIT      F3=END      F4=RETURN      F5=IFIND      F6=BOOK
F7=UP        F8=DOWN       F9=SWAP     F10=LEFT      F11=RIGHT     F12=RETRIEVE

```

Connected to remote server/host pokvmti4.pok.ibm.com using port 23

Session A - - POKVMTI4 62x160.ws - [24 x 80]  
File Edit View Communication Actions Window Help

```

Display Filter View Print Options Search Help
-----
SDSF OUTPUT DISPLAY IZUMKFS JOB000028 DSID      4 LINE 53      COLUMNS 02- 81
COMMAND INPUT ===> _                               SCROLL ==> PAGE
IEF033I JOB/IZUMKFS /STOP 2018268.0135
CPU:      0 HR 00 MIN 00.03 SEC      SRB:      0 HR 00 MIN 00.00 SEC
IDCAMS SYSTEM SERVICES                           TIME: 01:35:00

DEFINE      -
CLUSTER      -
( NAME(IZU.SIZUUSRD) -
VOLUMES(IZUV01) -
LINEAR      -
CYL(200 20) -
SHAREOPTIONS(3 3))
IDC0508I DATA ALLOCATION STATUS FOR VOLUME IZUV01 IS 0
IDC0512I NAME GENERATED-(D) IZU.SIZUUSRD.DATA
IDC0001I FUNCTION COMPLETED, HIGHEST CONDITION CODE WAS 0
IDC0002I IDCAMS PROCESSING COMPLETE. MAXIMUM CONDITION CODE WAS 0
IOEZ00077I HFS-compatibility aggregate IZU.SIZUUSRD has been successfully created

```

Connected to remote server/host pokvmti4.pok.ibm.com using port 23

### Common errors

Review the following messages and the corresponding resolutions as needed

Symptom	Cause	Resolution
Job fails with FSM error.	Your user ID lacks superuser authority.	For more information about how to define a user with superuser authority, see the publication <a href="#">z/OS UNIX System Services</a> .
Job fails with an authorization error.	Job statement errors.	See <a href="#">Troubleshooting problems</a> on page 50.

### Copying the IBM procedures into JES PROCLIB

Copy the z/OSMF started procedures and logon procedure from SYS1.PROCLIB into your JES concatenation. Use \$D PROCLIB command to display your JES2 PROCLIB definitions.

#### Before you begin

Locate the IBM procedures. IBM supplies procedures for z/OSMF in your z/OS order:

- ServerPac and CustomPac orders: IBM supplies the z/OSMF procedures in the SMP/E managed proclib data set. In ServerPac and SystemPac, the default name for the data set is SYS1.IBM.PROCLIB.
- CBPDO orders: For a CBPDO order, the SMP/E-managed proclib data set is named as SYS1.PROCLIB.
- Application Development CD.

#### Procedure

Use ISPF option 3.3 or 3.4 to copy the procedures from SYS1.PROCLIB into your JES concatenation.

- IZUSVR1
- IZUANG1
- IZUFPROC

#### Results

The procedures now reside in your JES PROCLIB.

## Common errors

Review the following messages and the corresponding resolutions as needed

Symptom	Cause	Resolution
Not authorized to copy into PROCLIB.	Your user ID doesn't have the permission to modify PROCLIB.	Contact your security administrator.
Abend code B37 or E37.	The data set runs out of space.	Use IEBCOPY utility to compress PROCLIB dataset before you copy it.

## Starting the z/OSMF server

z/OSMF processing is managed through the z/OSMF server, which runs as the started tasks IZUANG1 and IZUSVR1. z/OSMF is started with the START command.

### *Before you begin*

Ensure that you have access to the operations console and can enter the START command.

### *Procedure*

In the operations console, enter the START commands sequentially:

```
S IZUANG1
S IZUSVR1
```

Note: The z/OSMF angel (IZUANG1) must be started before the z/OSMF server (IZUSVR1).

You must enter these commands manually at subsequent IPLs. If necessary, you can stop z/OSMF processing by entering the STOP command for each of the started tasks IZUANG1 and IZUSVR1.

Note: z/OSMF offers an autostart function, which you can configure to have the z/OSMF server started automatically. For more information about the autostart capability, see [z/OSMF Configuration Guide](#).

### *Results*

When the z/OSMF server is initialized, you can see the following messages displayed in the operations console:

```
CWWKB0069I: INITIALIZATION IS COMPLETE FOR THE IZUANG1 ANGEL PROCESS.
IZUG400I: The z/OSMF Web application services are initialized.
CWWKF0011I: The server zosmfServer is ready to run a smarter planet.
```

## Accessing the z/OSMF Welcome page

At the end of the z/OSMF configuration process, you can verify the results of your work by opening a web browser to the Welcome page.

### *Before you begin*

To find the URL of the Welcome page, look for message IZUG349I in the z/OSMF server job log.

```

Session A - - POKVMTI4 62x160.ws - [24 x 80]
File Edit View Communication Actions Window Help
Display Filter View Print Options Search Help
-----
SDSF OUTPUT DISPLAY IZUSVR1 STC00036 DSID 107 LINE 31 COLS 02- 81
COMMAND INPUT ===> SCROLL ==> CSR
: was saved to a backup file
: /global/zosmf/configuration/backup_configuration.09.25.18.06.06.13.
IZUG227I: The z/OSMF Cloud Provisioning and Management automatic security
configuration REXX exec location properties file already exists.
No changes will be made.

The current contents are:
security-configuration-rexx-location=/usr/lpp/zosmf/workflow/izu.provi
IZUG210I: The z/OSMF Configuration Utility has completed successfully at Tue Sep
IZUG349I: The z/OSMF AUTOSTART Server home page can be accessed at
: https://ALPS4099.POK.IBM.COM/zosmf
: after the z/OSMF server is started on your system.

IZUG350I: The z/OSMF server on this system will attempt to connect to the named
Launching zosmfServer (z/OSMF 2.3.0/wlp-1.0.20.c1180120180309-2209) on IBM J9 VM
YAUDIT " CWNKE0001I: The server zosmfServer has been launched.
YAUDIT " CWNKZ0058I: Monitoring dropins for applications.
IZUG019I: User Feature Application State Listener has started.
F1=HELP F2=SPLIT F3=END F4=RETURN F5=IFIND F6=BOOK
F7=UP F8=DOWN F9=SWAP F10=LEFT F11=RIGHT F12=RETRIEVE
-----
```

Connected to remote server/host pokvmti4.pok.ibm.com using port 23

### Procedure

1. Open a web browser to the z/OSMF Welcome page. The URL for the Welcome page has the following format:  
<https://hostname:port/zosmf/>
- Where:
  - *hostname* is the host name or IP address of the system in which z/OSMF is installed.
  - *port* is the secure port for the z/OSMF configuration. If you specified a secure port for SSL encrypted traffic during the configuration process through parmlib statement HTTP\_SSL\_PORT, *port* is required to log in. Otherwise, it is assumed that you use the default port 443.
2. In the z/OS USER ID field on the Welcome page, enter the z/OS user ID that you use to configure z/OSMF.
3. In the z/OS PASSWORD field, enter the password or pass phrase that is associated with the z/OS user ID.
4. Select the style of UI for z/OSMF. To use the desktop interface, select this option. Otherwise, leave this option unselected to use the tree view UI.
5. Click **Log In**.

### Results

If the user ID and password or pass phrase are valid, you are authenticated to z/OSMF. The Welcome page of IBM z/OS Management Facility tab opens in the main area. At the top right of the screen, Welcome <*your\_user\_ID*> is displayed. In the UI, only the options you are allowed to use are displayed.

The screenshot shows a web browser window for the IBM z/OS Management Facility. The title bar reads "IBM z/OS Management Facility". The address bar shows a warning: "Not Secure" and the URL "https://pev157.pok.ibm.com/zosmf". The main content area features the IBM z/OS logo and the title "IBM z/OS Management Facility". On the left, there's a sidebar with a navigation menu:

- Welcome
- Notifications

A "Refresh" button is also present in this sidebar.

The main panel has a "Welcome" header and a large "Welcome to" message. Below it, there are several links:

- IBM® z/OS® Management Facility
- To learn more about z/OSMF
- To start managing your system
- Learn More:
  - What's New
  - z/OSMF tasks at a glance
  - Getting started with z/OSMF

You have successfully configured the z/OSMF nucleus.

#### *Common errors*

The following errors might occur during this step:

Symptom	Cause	Resolution
z/OSMF welcome page does not load in your web browser.	The SSL handshake was not successful. This problem can be related to the browser certificate.	See <a href="#">Certificate error in the Mozilla Firefox browser</a> .
To log into z/OSMF, enter a valid z/OS user ID and password. Your account might be locked after too many incorrect log-in attempts.	The user ID is not connected to the IZUADMIN group.	Connect your user ID to the IZUADMIN group.
To log into z/OSMF, enter a valid z/OS user ID and password. Your account might be locked after too many incorrect log-in attempts.	The password is expired.	Log on to TSO using your z/OS User ID and password, you will be asked to change your password if it's expired.

#### **Mounting the z/OSMF user file system at IPL time**

Previously, in [Running job IZUMKFS to create the z/OSMF user file system](#), you ran job IZUMKFS to create and mount the z/OSMF user file system. Now you should ensure that the z/OSMF user file system is mounted automatically for subsequent IPLs. To do so, update the BPXPRMxx parmlib member on your z/OS system.

#### *Before you begin*

By default, the z/OSMF file system uses the name IZU.SIZUUSRD, and is mounted in read/write mode. It is recommended that this file system is mounted automatically at IPL time.

If you do not know which BPXPRMxx member is active, follow these steps to find out:

1. In the operations console, enter the following command to see which parmlib members are included in the parmlib concatenation on your system:  
D PARMLIB
2. Make a note of the BPXPRMxx member suffixes that you see.
3. To determine which BPXPRMxx member takes precedence, enter the following command:  
D OMVS

The output of this command should be similar to the following:

```
BPXO042I 04.01.03 DISPLAY OMVS 391
OMVS 000F ACTIVE OMVS=(ST,3T)
```

In this example, the member BPXPRMST takes precedence. If BPXPRMST is not present in the concatenation, member BPXPRM3T is used.

#### *Procedure*

Add a MOUNT command for the z/OSMF user file system to your currently active BPXPRMxx parmlib member. For example:

On a z/OS V2R3 system with the PTF for APAR PI92211 installed:

```
MOUNT FILESYSTEM('IZU.SIZUUSRD') TYPE(ZFS) MODE(RDWR)
MOUNTPOINT('/global/zosmf') PARM('AGGRGROW') UNMOUNT
```

On a z/OS V2R2 or V2R3 system without PTF for APAR PI92211 installed:

```
MOUNT FILESYSTEM('IZU.SIZUUSRD') TYPE(ZFS) MODE(RDWR)
MOUNTPOINT('/var/zosmf') PARM('AGGRGROW') UNMOUNT
```

### Results

The BPXPRMxx member is updated. At the next system IPL, the following message is issued to indicate that the z/OSMF file system is mounted automatically.

```
BPXF013I FILE SYSTEM IZU.SIZUUSRD WAS SUCCESSFULLY MOUNTED.
```

## Adding the required REST services

You must enable a set of z/OSMF REST services for the Zowe framework.

The following system changes are described in this topic:

- [Enabling the z/OSMF JOB REST services](#)
- [Enabling the TSO REST services](#) on page 48
- [Enabling the z/OSMF data set and file REST services](#)
- [Enabling the z/OSMF Workflow REST services and Workflows task UI](#)

### Enabling the z/OSMF JOB REST services

The Zowe framework requires that you enable the z/OSMF JOB REST services, as described in this topic.

#### Procedure

None

#### Results

To verify if the z/OSMF JOB REST services are enabled, open a web browser to our z/OS system (host name and port) and add the following REST call to the URL:

```
GET /zosmf/rest/jobs/jobs
```

The result is a list of the jobs that are owned by your user ID. For more information about the z/OSMF JOB REST services, see [z/OSMF Programming Guide](#).

#### Common errors

Review the following messages and the corresponding resolutions as needed:

Symptom	Cause	Resolution
401 Unauthorized	The user ID is not connected to IZUADMIN or IZUUSER.	Connect your user ID to IZUADMIN or IZUUSER.
HTTP/1.1 500 Internal Server Error CATEGORY_CIM rc=16 reason=-1 IZUG911I: Connection to \"http://null:5988\" cannot be established, or was lost and cannot be re-established using protocol \"CIM\".....Caused by: WBEMException: CIM_ERR_FAILED (JNI Exception type CannotConnectException: \nCannot connect to local CIM server. Connection failed.)	For JES2, you may have performed {"rc":16,"reason":-1,"stack":"JesException:of the following "Modify" operations: Hold a job, Release a job, cause=com.ibm.zosmf.util.eis.EisConnectionException, Cancel a job, Delete a job (Cancel a job and purge its output), or you are running JES3 without configuring CIM Server.	If you are running JES2, you can use <a href="#">synchronous support for job modify operations</a> which does not require CIM. If you are running JES3, follow the <a href="#">CIM setup instructions</a> to configure CIM on your system.

## Enabling the TSO REST services

The Zowe framework requires that you enable the TSO REST services, as described in this topic.

### *Before you begin*

Ensure that the common event adapter component (CEA) of z/OS is running in full function mode.

1. To check if the CEA address space is active, enter the following command:

```
D A,CEA
```

1. If not, start CEA in full function mode. For detailed instructions, see [System prerequisites for the CEA TSO/E address space services](#).
2. To verify that CEA is running in full function mode, enter the following command:

```
F CEA,D
```

The output should look like the following:

```
CEA0004I COMMON EVENT ADAPTER 399
STATUS: **ACTIVE-FULL** CLIENTS: 0 INTERNAL: 0
EVENTS BY TYPE: \#WTO: 0 \#ENF: 0 \#PGM: 0
TSOASMGR: ALLOWED: 50 IN USE: 0 HIGHCNT: 0
```

### *Procedure*

1. If you run z/OS V2R2 and V2R3, download job IZUTSSEC in the [sample jobs package](#) and upload this Job to z/OS. If you run z/OS V2R4, locate job IZUTSSEC at SYS1.SAMPLIB.
2. Review and edit job IZUTSSEC before you submit. You can review the IZUTSSEC section below for more details.
3. Submit IZUTSSEC as a batch job on your z/OS system.

### **IZUTSSEC**

IBM provides a set of jobs in SYS1.SAMPLIB with sample RACF commands to help with your z/OSMF configuration and its prerequisites. The IZUTSSEC job represents the authorizations that are needed for the z/OSMF TSO/E address space service. Your security administrator can edit and run the job. Generally, your z/OSMF user ID requires the same authorizations for using the TSO/E address space services as when you perform these operations through a TSO/E session on the z/OS system. For example, to start an application in a TSO/E address space requires that your user ID be authorized to operate that application. In addition, to use TSO/E address space services, you must have:

- READ access to the account resource in class ACCTNUM, where account is the value specified in the COMMON\_TSO\_ACCT option in parmlib.
- READ access to the CEA.CEATSO.TSOREQUEST resource in class SERVAUTH.
- READ access to the proc resource in class TSOPROC, where proc is the value specified with the COMMON\_TSO\_PROC option in parmlib.
- READ access to the <SAF\_PREFIX>.\*.izuUsers profile in the EJBROLE class. Or, at a minimum, READ access to the <SAF\_PREFIX>.IzuManagementFacilityTsoServicesizuUsers resource name in the EJBROLE class. You must also ensure that the z/OSMF started task user ID, which is IZUSVR by default, has READ access to the CEA.CEATSO.TSOREQUEST resource in class SERVAUTH. To create a TSO/E address space on a remote system, you require the following authorizations:
- You must be authorized to the SAF resource profile that controls the ability to send data to the remote system (systemname), as indicated: CEA.CEATSO.FLOW.systemname
- To flow data between different systems in the sysplex, you must be authorized to do so by your external security manager, such as a RACF database with sysplex-wide scope. For example, to flow data between System A and System B, you must be permitted to the following resource profiles:
  - CEA.CEATSO.FLOW.SYSTEMA
  - CEA.CEATSO.FLOW.SYSTEMB

## Results

The IZUTSSEC job should complete with return code 0000.

## Enabling the z/OSMF data set and file REST services

The Zowe framework requires that you enable the z/OSMF data set and file REST services.

### Before you begin

1. Ensure that the message queue size is set to a large enough value. It is recommended that you specify an IPCMSGQBYTES value of at least 20971520 (20M) in BPXPRMxx.

Issue command D OMVS,O to see the current value of IPCMSGQBYTES, if it is not large enough, use the SETOMVS command to set a large value. To set this value dynamically, you can enter the following operator command:

```
SETOMVS IPCMSGQBYTES=20971520
```

2. Ensure that the TSO REST services are enabled.
3. Ensure that IZUFPROC is in your JES concatenation.
4. Ensure that your user ID has a TSO segment defined. To do so, enter the following command from TSO/E command prompt:

```
LU userid TSO
```

Where *userid* is your z/OS user ID.

The output from this command must include the section called **TSO information**, as shown in the following example:

```
TSO LU ZOSMFAD TSO NORACF
4:57:17 AM: USER=ZOSMFAD
TSO INFORMATION
-----
ACCTNUM= 123412345
PROC= OMVSPROC
SIZE= 02096128
MAXSIZE= 00000000
USERDATA= 0000
***
```

## Procedure

1. If you run z/OS V2R2 and V2R3, download job IZURFSEC in the [sample jobs package](#) and upload it to z/OS. If you run z/OS V2R4, locate job IZURFSEC at SYS1.SAMPLIB.
2. Copy the job.
3. Examine the contents of the job.
4. Modify the contents as needed so that the job will run on your system.
5. From the TSO/E command line, run the IZURFSEC job.

## Results

Ensure that the IZURFSEC job completes with return code 0000.

To verify if this setup is complete, try issuing a REST service. See the example in [List data sets](#) in the z/OSMF programming guide.

#### **Common errors**

Review the following messages and the corresponding resolutions as needed:

Symptom	Cause	Resolution
REST API doesn't return expected data with rc=12, rsn=3, message: message queue size "SIZE" is less than minimum: 20M	The message queue size for CEA is too small.	Ensure that the message queue size is set to a large enough value. It is recommended that you specify an IPCMSGQBYTES value of at least 20971520 (20M) in BPXPRMx.

### **Enabling the z/OSMF Workflow REST services and Workflows task UI**

The Zowe framework requires that you enable the z/OSMF Workflow REST services and Workflows task UI.

#### *Before you begin*

1. Ensure that the JOB REST services are enabled.
2. Ensure that the TSO REST services are enabled.
3. Ensure that the dataset and file REST services are enabled.

#### *Procedure*

1. If you run z/OS V2R2 and V2R3, download job IZUWFSEC in the [sample jobs package](#) and upload this job to z/OS. If you run z/OS V2R4, locate job IZUWFSEC at SYS1.SAMPLIB.
2. Copy the job.
3. Examine the contents of the job.
4. Modify the contents as needed so that the job will run on your system.
5. From the TSO/E command line, run the IZUWFSEC job.

#### *Results*

Ensure the IZUWFSEC job completes with return code 0000.

To verify, log on to z/OSMF (or refresh it) and verify that the Workflows task appears in the z/OSMF UI.

At this point, you have completed the setup of z/OSMF Lite.

Optionally, you can add more users to z/OSMF, as described in [Appendix C. Adding more users to z/OSMF](#).

### **Troubleshooting problems**

This section provides tips and techniques for troubleshooting problems you might encounter when creating a z/OSMF Lite configuration. For other types of problems that might occur, see [z/OSMF Configuration Guide](#).

#### **Common problems and scenarios**

This section discusses troubleshooting topics, procedures, and tools for recovering from a set of known issues.

##### *System setup requirements not met*

This document assumes that the following is true of the z/OS host system:

- Port 443 is available for use. To check this, issue either TSO command NETSTAT SOCKET or TSO command NETSTAT BYTE to determine if the port is being used.
- The system host name is unique and maps to the system on which z/OSMF Lite is being installed. To retrieve this value, enter either "hostname" z/OS UNIX command or TSO command "HOMETEST". If your system uses another method of assigning the system name, such as a multi-home stack, dynamic VIPA, or System Director, see [z/OSMF Configuration Guide](#).
- The global mount point exists. On a z/OS 2.3 system, the system includes this directory by default. On a z/OS 2.2 system, you must create the global directory at the following location: /global/zosmf/.

If you find that a different value is used on your z/OS system, you can edit the IZUPRMxx parmlib member to specify the correct setting. For details, see [Appendix A. Creating an IZUPRMxx parmlib member](#) on page 51.

## Tools and techniques for troubleshooting

For information about working with z/OSMF log files, see [z/OSMF Configuration Guide](#).

### Common messages

```
ICH420I PROGRAM CELQLIB FROM LIBRARY CEE.SCEERUN2 CAUSED THE ENVIRONMENT  
TO BECOME UNCONTROLLED.
```

```
BXP014I ENVIRONMENT MUST BE CONTROLLED FOR DAEMON (BPX.DAEMON)  
PROCESSING.
```

If you see above error messages, check if your IZUANG0 procedure is up to date.

For descriptions of all the z/OSMF messages, see [z/OSMF messages](#) in IBM Knowledge Center.

## Appendix A. Creating an IZUPRMxx parmlib member

If z/OSMF requires customization, you can modify the applicable settings by using the IZUPRMxx parmlib member. To see a sample member, locate the IZUPRM00 member in the SYS1.SAMPLIB data set. IZUPRM00 contains settings that match the z/OSMF defaults.

Using IZUPRM00 as a model, you can create a customized IZUPRMxx parmlib member for your environment and copy it to SYS1.PARMLIB to override the defaults.

The following IZUPRMxx settings are required for the z/OSMF nucleus:

- HOSTNAME
- HTTP\_SSL\_PORT
- JAVA\_HOME.

The following setting is needed for the TSO/E REST services:

- COMMON\_TSO ACCT(IZUACCT) REGION(50000) PROC(IZUFPROC)

Descriptions of these settings are provided in the table below. For complete details about the IZUPRMxx settings and the proper syntax for updating the member, see [z/OSMF Configuration Guide](#).

If you change values in the IZUPRMxx member, you might need to customize the started procedure IZUSVR1, accordingly. For details, see [Appendix B. Modifying IZUSVR1 settings](#) on page 53.

To create an IZUPRMxx parmlib member, follow these steps:

1. Copy the sample parmlib member into the desired parmlib data set with the desired suffix.
2. Update the parmlib member as needed.
3. Specify the IZUPRMxx parmlib member or members that you want the system to use on the IZU parameter of IEASYSxx. Or, code a value for IZUPRM= in the IZUSVR1 started procedure. If you specify both IZU= in IEASYSxx and IZUPARM= in IZUSVR1, the system uses the IZUPRM= value you specify in the started procedure.

Setting	Purpose	Rules	Default
HOSTNAME( <i>hostname</i> )	Specifies the host name, as defined by DNS, where the z/OSMF server is located. To use the local host name, enter asterisk (*), which is equivalent to \@HOSTNAME from previous releases. If you plan to use z/OSMF in a multisystem sysplex, IBM recommends using a dynamic virtual IP address (DVIPA) that resolves to the correct IP address if the z/OSMF server is moved to a different system.	Must be a valid TCP/IP HOSTNAME or an asterisk (*).	Default: \*
HTTP_SSL_PORT(nnn)	Identifies the port number that is associated with the z/OSMF server. This port is used for SSL encrypted traffic from your z/OSMF configuration. The default value, 443, follows the Internet Engineering Task Force (IETF) standard. <b>Note:</b> By default, the z/OSMF server uses the SSL protocol SSL_TLSv2 for secure TCP/IP communications. As a result, the server can accept incoming connections that use SSL V3.0 and the TLS 1.0, 1.1 and 1.2 protocols.	Must be a valid TCP/IP port number. Value range: 1 - 65535 (up to 5 digits)	Default: 443
COMMON_TSO ACCT( <i>account-number</i> ) REGION( <i>region-size</i> ) PROC( <i>proc-name</i> )	Specifies values for the TSO/E logon procedure that is used internally for various z/OSMF activities and by the Workflows task.	The valid ranges for each value are described in <a href="#">z/OSMF Configuration Guide</a> .	Default: 443 ACCT(IZUACCT) REGION(50000) PROC(IZUFPROC)
USER_DIR= <i>filepath</i>	z/OSMF data directory path. By default, the z/OSMF data directory is located in /global/zosmf. If you want to use a different path for the z/OSMF data directory, specify that value here, for example: USER_DIR=/the/new/config/dir.	Must be a valid z/OS UNIX path name.	Default: /global/zosmf/

## Appendix B. Modifying IZUSVR1 settings

You might need to customize the started procedure IZUSVR1 for z/OSMF Lite.

To modify the IZUSVR1 settings, follow these steps:

1. Make a copy
2. Apply your changes
3. Store your copy in PROCLIB.

Setting	Purpose	Rules	Default
WLPDIR='directory-path'	WebSphere Liberty server code path.	The directory path must: Be a valid z/OS UNIX path name Be a full or absolute path name Be enclosed in quotation marks Begin with a forward slash ('/').	Default: /usr/lpp/zosmf/liberty
USER_DIR= <i>filepath</i>	z/OSMF data directory path. By default, the z/OSMF data directory is located in /global/zosmf. If you want to use a different path for the z/OSMF data directory, specify that value here, for example: USER_DIR=/the/new/config/dir.	Must be a valid z/OS UNIX path name.	Default: /global/zosmf/

## Appendix C. Adding more users to z/OSMF

Your security administrator can authorize more users to z/OSMF. Simply connect the required user IDs to the z/OSMF administrator group (IZUADMIN). This group is permitted to a default set of z/OSMF resources (tasks and services). For the specific group permissions, see Appendix A in [z/OSMF Configuration Guide](#).

You can create more user groups as needed, for example, one group per z/OSMF task.

### Before you Begin

Collect the z/OS user IDs that you want to add.

### Procedure

1. On an RACF system, enter the CONNECT command for the user IDs to be granted authorization to z/OSMF resources:

```
CONNECT userid GROUP(IZUADMIN)
```

### Results

The user IDs can now access z/OSMF.

## Installing Zowe on z/OS

To install Zowe on z/OS, there are two parts. The first part is the Zowe runtime that consists of three components: Zowe Application Framework, z/OS Explorer Services, and Zowe API Mediation Layer. The second part is the Zowe Cross Memory Server. This is an authorized server application that provides privileged services to Zowe in a secure manner.

Follow the instructions in this topic to obtain the installation file for z/OS runtime components and run the installation scripts.

1. [Obtaining and preparing the installation file](#) on page 54

2. [Prerequisites](#) on page 56
3. [Installing the Zowe runtime on z/OS](#)
  - [How the install script `zowe-install.sh` works](#)
4. [Starting and stopping the Zowe runtime on z/OS](#)
  - [Starting the ZOWESVR PROC](#) on page 64
  - [Stopping the ZOWESVR PROC](#) on page 65
5. [Installing the Zowe Cross Memory Server on z/OS](#)
  - [Manually installing the Zowe Cross Memory Server](#) on page 66
  - [Scripted install of the Zowe Cross Memory Server](#) on page 70
6. [Starting and stopping the Zowe Cross Memory Server on z/OS](#)
7. [Verifying installation](#) on page 71
8. [Looking for troubleshooting help?](#) on page 73

### **Obtaining and preparing the installation file**

The Zowe installation file for Zowe z/OS components are distributed as a PAX file that contains the runtimes and the scripts to install and launch the z/OS runtime. For each release, there is a PAX file named `zowe-v.r.m.pax`, where

- v indicates the version
- r indicates the release number
- m indicates the modification number

The numbers are incremented each time a release is created so the higher the numbers, the later the release.

To download the PAX file, open your web browser and click the *Zowe z/OS Components* button on the [Zowe Download](#) website to save it to a folder on your desktop. After you obtain the PAX file, follow the procedures below to verify the PAX file and prepare it to install the Zowe runtime.

**Follow these steps:**

1. Verify the integrity of the PAX file to ensure that the file you download is officially distributed by the Zowe project.

**Notes:**

- The commands in the following steps are tested on both Mac OS X V10.13.6 and Ubuntu V16.04 and V17.10.
- Ensure that you have GPG installed. Click [here](#) to download and install GPG.
- The v.r.m in the commands of this step is a variable. You must replace it with the actual PAX file version, for example, 0.9.0.

**Step 1: Verify the hash code.**

Download the hash code file zowe-v.r.m.pax.sha512 from the [Zowe website](#). Then, run the following commands to check:

```
(gpg --print-md SHA512 zowe-v.r.m.pax > zowe-v.r.m.pax.sha512.my) && diff
zowe-v.r.m.pax.sha512.my zowe-v.r.m.pax.sha512 && echo matched || echo
"not match"
```

When you see "matched", it means the PAX file that you download is the same one that is officially distributed by the Zowe project. You can delete the temporary zowe-v.r.m.pax.sha512.my file.

You can also use other commands such as sha512, sha512sum, or openssl dgst -sha512 to generate SHA512 hash code. These hash code results are in a different format from what Zowe provides but the values are the same.

**Step 2. Verify with signature file.**

In addition to the SHA512 hash, the hash is also verifiable. This is done by digitally signing the hash text file with a KEY from one of the Zowe developers.

**Follow these steps:**

- a. Download the signature file zowe-v.r.m.pax.asc from [https://zowe.org/Downloads/post\\_download.html](https://zowe.org/Downloads/post_download.html), and download the public key KEYS from <https://github.com/zowe/release-management/>.
- b. Import the public key with the gpg --import KEYS command.
- c. If you have never used gpg before, generate keys with the gpg --gen-key command.
- d. Sign the downloaded public key with the gpg --sign-key DC8633F77D1253C3 command.
- e. Verify the file with the gpg --verify zowe-v.r.m.pax.asc zowe-v.r.m.pax command.
- f. Optional: You can remove the imported key with the gpg --delete-key DC8633F77D1253C3 command.

When you see output similar to the following one, it means the PAX file that you download is the same one that is officially distributed by the Zowe project.

```
gpg: Signature made Tue 14 Aug 2018 08:29:46 AM EDT
gpg: using RSA key DC8633F77D1253C3
gpg: Good signature from "Matt Hogstrom (CODE SIGNING KEY) " [full]
```

**2.** Transfer the PAX file to z/OS.

**Follow these steps:**

a. Open a terminal in Mac OS/Linux, or command prompt in Windows OS, and navigate to the directory where you downloaded the Zowe PAX file.

b. Connect to z/OS using SFTP. Issue the following command:

```
sftp <userID@ip.of.zos.box>
```

If SFTP is not available or if you prefer to use FTP, you can issue the following command instead:

```
ftp <userID@ip.of.zos.box>
```

**Note:** When you use FTP, switch to binary file transfer mode by issuing the following command:

```
bin
```

c. Navigate to the target directory that you wish to transfer the Zowe PAX file into on z/OS.

**Note:** After you connect to z/OS and enter your password, you enter into the Unix file system. The following commands are useful:

- To see what directory you are in, type `pwd`.
- To switch directory, type `cd`.
- To list the contents of a directory, type `ls`.
- To create a directory, type `mkdir`.

d. When you are in the directory you want to transfer the Zowe PAX file into, issue the following command:

```
put <zowe-v.r.m>.pax
```

Where `zowe-v.r.m` is a variable that indicates the name of the PAX file you downloaded.

**Note:** When your terminal is connected to z/OS through FTP or SFTP, you can prepend commands with `l` to have them issued against your desktop. To list the contents of a directory on your desktop, type `l ls` where `ls` lists contents of a directory on z/OS.

**3.** When the PAX file is transferred, expand the PAX file by issuing the following command in an SSH session:

```
pax -ppx -rf <zowe-v.r.m>.pax
```

Where `zowe-v.r.m` is a variable that indicates the name of the PAX file you downloaded.

This will expand to a file structure.

```
/files  
/install  
/scripts  
...
```

**Note:** The PAX file will expand into the current directory. A good practice is to keep the installation directory apart from the directory that contains the PAX file. To do this, you can create a directory such as `/zowe/paxes` that contains the PAX files, and another such as `/zowe/builds`. Use SFTP to transfer the Zowe PAX file into the `/zowe/paxes` directory, use the `cd` command to switch into `/zowe/builds` and issue the command `pax -ppx -rf .. /paxes/<zowe-v.r.m>.pax`. The `/install` folder will be created inside the `zowe/builds` directory from where the installation can be launched.

## Prerequisites

Ensure that you meet the following software requirements before you install Zowe on z/OS:

- Your environment meets the necessary prerequisites that are described in [System requirements](#) on page 31.
- The user ID that is used to perform the installation must have authority to read the z/OSMF keyring. For how to check the name of the keyring and grant read access to the keyring, see the [Trust z/OSMF certificate](#) topic.
- The user ID that is used to perform the installation must have READ permission for the BPX.JOBNAME FACILITY class. To display who is authorized to the FACILITY class, issue the following command:

```
RLIST FACILITY BPX.JOBNAME AUTHUSER
```

Additionally, you need to activate facility class, permit BPX.JOBNAME, and refresh facility class:

```
SETROPTS CLASSACT(FACILITY) RACLST(FACILITY)
PERMIT BPX.JOBNAME CLASS(FACILITY) ID(&useridToAuthorizeHere) ACCESS(READ)
SETROPTS RACLST(FACILITY) REFRESH
```

For more information, see [Setting up the UNIX-related FACILITY and SURROGAT class profiles](#).

## Installing the Zowe runtime on z/OS

To install Zowe API Mediation Layer, Zowe Application Framework, and z/OS Services, you install the Zowe runtime on z/OS.

### Follow these steps:

1. Navigate to the directory where the installation archive is extracted. Locate the /install directory.

```
/install
/zowe-install.sh
/zowe-install.yaml
```

2. Review the zowe-install.yaml file which contains the following properties:

- `install:rootDir` is the directory that Zowe installs to create a Zowe runtime. The default directory is `~/zowe/v.r.m` where *v* is the Zowe version number, *r* is the release number and *m* is the modification number, for example, 1.0.0 or 1.2.11. The user's home directory is the default value. This ensures that the user who performs the installation has permission to create the directories that are required for the installation. If the Zowe runtime will be maintained by multiple users, it is recommended to use another directory based on your site's conventions. You can run the installation process multiple times with different values in the `zowe-install.yaml` file to create separate installations of the Zowe runtime. Ensure that the directory where

Zowe will be installed is empty. The install script exits if the directory is not empty and creates the directory if it does not exist.

- `install:prefix` defines a prefix for Zowe address space STC name associated with USS processes. STC names have certain components and use the following format:

```
pfxCssN
```

where:

- `pfx` - prefix that contains up to four characters, for example, `ZOWE`.
- `C` - a component character that is similar to ones that are used for message IDs. The following list contains the component characters:
  - **A** - API Mediation Layer
  - **D** - Zowe Desktop
  - **E** - Zowe Explorer
  - **S** - Zowe System Services
  - **Z** - ZSS process
  - **X** - Cross Memory Server
- `ss` - a subcomponent that consists of 1 or 2 characters:
  - **GW** - API ML Gateway
  - **DS** - API ML Discovery Service
  - **AC** - API ML Catalog
  - **AJ** - Explorer API Jobs
  - **AD** - Explorer API Data Sets
  - **UD** - Explorer UI Data Sets
  - **UJ** - Explorer UI Jobs
  - **UU** - Explorer UI USS
  - **S** - Zowe Desktop Application Server
- `N` - instance number

You should use the prefix for the main started task (+ number).

#### **Example: 1st instance of Zowe API ML Gateway identifier**

```
ZOWEAGW1
```

- Zowe API Mediation Layer has three HTTPS ports, one for each micro-service.
- z/OS Services has HTTPS ports for the jobs and the data sets microservices.
- z/OS desktop apps has three ports for each of its explorer apps
- The Zowe App Server has two ports: the HTTPS port used by the Zowe Application Server, and an HTTP port that is used by the ZSS Server.

#### **Example:**

```
install:
  rootDir=/tmp/zowe/1.4.0
  prefix=ZOWE

api-mediation:
  catalogPort=7552
  discoveryPort=7553
  gatewayPort=7554
  externalCertificate=
  externalCertificateAlias=
  externalCertificateAuthorities=
  verifyCertificatesOfServices=true
```

```

enableSso=false
zosmfKeyring=IZUKeyring.IZUDFLT
zosmfUser=IZUSVR

zos-services:
  jobsAPIPort=8545
  mvsAPIPort=8547

zowe-desktop-apps:
  jobsExplorerPort=8546
  mvsExplorerPort=8548
  ussExplorerPort=8550

zlux-server:
  httpsPort=8544
  zssPort=8542

```

**Notes:**

- If all of the default port values are acceptable, the ports do not need to be changed. To allocate ports, ensure that the ports are not in use for the Zowe runtime servers.
- Comments are not supported in the YAML file, apart from lines starting with '#' in column one.

**3. Determine which ports are not available.**

- a. Display a list of ports that are in use with the following command:

```
TSO NETSTAT
```

- b. Display a list of reserved ports with the following command:

```
TSO NETSTAT PORTLIST
```

The `zowe-install.yaml` also contains the telnet and SSH port with defaults of 23 and 22. If your z/OS LPAR is using different ports, edit the values. This allows the TN3270 terminal desktop application to connect as well as the VT terminal desktop application.

**Note:** Unlike the ports needed by the Zowe runtime for its Zowe Application Framework and z/OS Services which must be unused, the terminal ports are expected to be in use.

```

# Ports for the TN3270 and the VT terminal to connect to
terminals:
  sshPort=22
  telnetPort=23

```

**4. Select the ZOWESVR PROCLIB member.**

The `zowe-install.yaml` file contains the dataset name and member name of the ZOWESVR JCL to be used to run Zowe.

**Example:**

```

# started task JCL member for Zowe job
zowe-server-proclib:
  # dsName=SYS1.PROCLIB
  dsName=auto

```

```
memberName=ZOWESVR
```

**Follow these steps:**

- Specify the dataset name of the PROCLIB member you want to use with the `dsName` tag. For example,

```
dsName=user.proclib
```

The following guidelines apply.

- Do not enclose the dataset name in quotes.
- The dataset name is not case-sensitive, but the `dsName` tag is case-sensitive and must be written exactly as shown.
- The dataset name must be an existing z/OS dataset in the PROCLIB concatenation. The user who installs Zowe must have update access to this dataset.
- If you omit the `dsName` tag or specify `dsName=auto`, the install script scans the available PROCLIB datasets and places the JCL member in the first dataset where the installing user has write access. For further details, see [How the install script zowe-install.sh works](#).

- Specify the member name of the PROCLIB member you want to use with the `memberName` tag. For example,

```
memberName=ZOWEABC
```

The following guidelines apply.

- Do not enclose the member name in quotes.
- The member name is not case-sensitive, but the `memberName` tag is case-sensitive and must be written exactly as shown.
- The member name must be a valid PDS member name in z/OS. If the member already exists, it will be overwritten.
- If you omit the `memberName` tag or specify `memberName=`, the install script uses ZOWESVR.

- (Optional) Use existing certificate signed by an external CA for HTTPS ports in API Mediation Layer and Zowe Application Framework.

If you skip this step, then certificates generated by the local API Mediation CA are used. These certificates are generated automatically during the installation. The server certificate needs to be imported to your browser. See [Import the local CA certificate to your browser](#).

You can use an existing server certificate that is signed by an external CA such as a CA managed by the IT department of your company. The benefit of such certificate is that it will be trusted by browsers in your company. You can even use a public certificate authority such as Symantec, Comodo, or GoDaddy. Such certificate are trusted by all browsers and most REST API clients. This is, however, a manual process of requesting a certificate. As such, we recommend to start with the local API Mediation Layer CA for an initial evaluation.

You can use an existing certificate with the following procedure.

**Follow these steps:**

- Update the value of `externalCertificate` in the `api-mediation` section of the YAML file. The value needs to point to a keystore in PKCS12 format that contains the certificate with its private key. The file needs to be transferred as a binary to the z/OS system. Currently only the PKCS12 keystore with the password set to `password` are supported.
- Update the value of `externalCertificateAlias` to the alias of the server certificate in the keystore.
- Update the value of `externalCertificateAuthorities` to the path of the public certificate of the certificate authority that has signed the certificate. You can add additional certificate authorities separated by commas.

spaces. This can be used for certificate authorities that have signed the certificates of the services that you want to access via the API Mediation Layer.

d. (Optional) If you have trouble getting the certificates and you want only to evaluate Zowe, you can switch off the certificate validation by setting `verifyCertificatesOfServices=false`. The HTTPS will still be used but the API Mediation Layer will not validate any certificate.

**Important!** Switching off certificate evaluation is a non-secure setup.

**Example:**

```
api-mediation:
  externalCertificate=/path/to/keystore.p12
  externalCertificateAlias=servercert
  externalCertificateAuthorities=/path/to/cacert.cer
  verifyCertificatesOfServices=true
```

6. (Optional) Check the install condition of the required prerequisites. To do this, issue the following command with the current directory being the `/install` directory.

```
zowe-check-prereqs.sh
```

The script writes messages to your terminal window. The results are marked `OK`, `Info`, `Warning` or `Error`. Correct any reported errors and rerun the command to ensure that no errors exist before you run the `zowe-install.sh` script to install the Zowe runtime. The `zowe-check-prereqs.sh` script does not change any settings. You can run it as often as required before you run the install script.

1. Execute the `zowe-install.sh` script.

With the current directory being the `/install` directory, execute the script `zowe-install.sh` by issuing the following command:

```
zowe-install.sh
```

You might receive the following error that the file cannot be executed:

```
zowe-install.sh: cannot execute
```

The error occurs when the install script does not have execute permission. To add execute permission, issue the following command:

```
chmod u+x zowe-install.sh
```

When the script runs, it echos its progress to the shell and attempts to determine and validate the location of the prerequisites including z/OSMF, Java, and Node. When the script cannot determine the location of these prerequisites, you will be prompted for their location.

Each time the install script runs it creates a log file that contains more information. This file is stored in the `/log` directory and is created with a date and time stamp name, for example `/log/2019-02-05-18-08-35.log`. This file is copied across into the runtime folder into which Zowe is installed, and contains useful information to help diagnose problems that may occur during an install.

You may also receive the following message:

```
apiml_cm.sh --action trust-zosmf has failed.
WARNING: z/OSMF is not trusted by the API Mediation Layer. Follow
instructions in Zowe documentation about manual steps to trust z/OSMF
```

This error does not interfere with installation progress and can be remediated after the install completes. See [Trust z/OSMF Certificate](#) for more details.

## 2. Configure Zowe as a started task.

The ZOWESVR must be configured as a started task (STC) under the IZUSVR user ID. You can do this after the zowe-install.sh script has completed by running the script zowe-config-stc.sh. To run this script, use the cd command to switch to the scripts directory that is created by the pax command. For example:

```
cd /zowe/builds/scripts
zowe-config-stc.sh
```

Alternatively, you can issue the commands manually:

**Note:** You must replace ZOWESVR in the commands below with the name of your server that you specified as memberName=ZOWESVR in the zowe-install.yaml file.

- If you use RACF, issue the following commands:

```
RDEFINE STARTED ZOWESVR.* UACC(NONE) STDATA(USER(IZUSVR) GROUP(IZUADMIN)
      PRIVILEGED(NO) TRUSTED(NO) TRACE(YES))
      SETROPTS REFRESH RACLIST(STARTED)
```

- If you use CA ACF2, issue the following commands:

```
SET CONTROL(GSO)
INSERT STC.ZOWESVR LOGONID(IZUSVR) GROUP(IZUADMIN) STCID(ZOWESVR)
F ACF2,REFRESH(STC)
```

- If you use CA Top Secret, issue the following commands:

```
TSS ADDTO(STC) PROCNAME(ZOWESVR) ACID(IZUSVR)
```

## 3. Add the users to the required groups, IZUADMIN for administrators, and IZUUSER for standard users.

- If you use RACF, issue the following command:

```
CONNECT (userid) GROUP(IZUADMIN)
```

- If you use CA ACF2, issue the following commands:

```
ACFNRULE TYPE(TGR) KEY(IZUADMIN) ADD(UID(<uid string of user>) ALLOW)
F ACF2,REBUILD(TGR)
```

- If you use CA Top Secret, issue the following commands:

```
TSS ADD(userid) PROFILE(IZUADMIN)
TSS ADD(userid) GROUP(IZUADMGP)
```

## How the install script zowe-install.sh works

When the zowe-install.sh script runs, it performs a number of steps broken down into the following sections. Review the sections to help you understand messages and issues that might occur when you run the script and actions you can take to resolve the issues.

## 1. Environment variables

To prepare the environment for the Zowe runtime, a number of ZFS folders need to be located for prerequisites on the platform that Zowe needs to operate. These can be set as environment variables before the script is run. If the environment variables are not set, the install script will attempt to locate default values.

- `ZOWE_ZOSMF_PATH`: The path where z/OSMF is installed. Defaults to `/usr/lpp/zosmf/lib/default_servers/zosmfServer`.
- `ZOWE_JAVA_HOME`: The path where 64 bit Java 8 or later is installed. Defaults to `/usr/lpp/java/J8.0_64`.
- `ZOWE_EXPLORER_HOST`: The hostname of where the explorer servers are launched from. Defaults to running `hostname -c`.

When you run the install script for the first time, the script attempts to locate environment variables. The install script creates a file named `.zowe_profile` that resides in the current user's home directory and adds lines that specify the values of the environment variables to the file. The next time you run the install script, it uses the same values in this file.

Each time you run the install script, it retrieves environment variable settings in the following ways.

- When the `.zowe-profile` file exists in the home directory, the install script uses the values in this file to set the environment variables.
- When the `.zowe-profile` file does not exist, the install script checks if the `.profile` file exists in the home directory. If it does exist, the install script uses the values in this file to set the environment variables. The install script does not update or execute the `.profile` file.

You can create, edit, or delete the `.zowe_profile` file (as needed) before each install to set the variables to the values that you want. We recommend that you *do not* add commands to the `.zowe_profile` file, with the exception of the `export` command and shell variable assignments.

### Notes:

- If you wish to set the environment variables for all users, add the lines to assign the variables and their values to the file `/etc/profile`.
- If the environment variables for `ZOWE_ZOSMF_PATH`, `ZOWE_JAVA_HOME` are not set and the install script cannot determine a default location, the install script will prompt for their location. The install script will not continue unless valid locations are provided.
- Ensure that the value of the `ZOWE_EXPLORER_HOST` variable is accessible from a machine external to the z/OS environment thus users can log in to Zowe from their desktops. When there is no environment variable set and there is no `.zowe_profile` file with the variable set, the install script will default to the value of `hostname -c`. In this case, ensure that the value of `hostname -c` is externally accessible from clients who want to use Zowe as well as internally accessible from z/OS itself. If not accessible, then set an environment variable with `ZOWE_EXPLORER_HOST` set to the correct host name, or create and update the `zowe_profile` file in the current user's home directory.

## 2. Expanding the PAX files

The install script will create the Zowe runtime directory structure using the `install:rootDir` value in the `zowe-install.yaml` file. The runtime components of the Zowe server are then unpaxed into the directory that contains a number of directories and files that make up the Zowe runtime.

If the expand of the PAX files is successful, the install script will report that it ran its install step to completion.

## 3. Changing Unix permissions

After the install script lays down the contents of the Zowe runtime into the `rootDir`, the next step is to set the file and directory permissions correctly to allow the Zowe runtime servers to start and operate successfully.

The install process will execute the file `scripts/zowe-runtime-authorize.sh` in the Zowe runtime directory. If the script is successful, the result is reported. If for any reason the script fails to run because of insufficient authority by the user running the install, the install process reports the errors. A user with sufficient authority should then run the `zowe-runtime-authorize.sh`. If you attempt to start the Zowe runtime

servers without the `zowe-runtime-authorize.sh` having successfully completed, the results are unpredictable and Zowe runtime startup or runtime errors will occur.

#### 4. Creating the PROCLIB member to run the Zowe runtime

**Note:** The name of the PROCLIB member might vary depending on the standards in place at each z/OS site, however for this documentation, the PROCLIB member is called `ZOWESVR`.

At the end of the installation, a Unix file `ZOWESVR.jcl` is created under the directory where the runtime is installed into, `$INSTALL_DIR/files/templates`. The contents of this file need to be tailored and placed in a JCL member of the PROCLIB concatenation for the Zowe runtime to be executed as a started task. The install script does this automatically. If the user specifies `dsName=auto`, or omits the `dsName` tag, or sets it to null by coding `dsName=`, the install script proceeds as follows and stops after the first successful write to the destination PROCLIB.

- a. Try JES2 PROCLIB concatenation.
- b. Try master JES2 JCL.
- c. Try `SYS1.PROCLIB`.

If this succeeds, you will see a message like the following one:

```
PROC ZOWESVR placed in USER.PROCLIB
```

Otherwise you will see messages beginning with the following information:

```
Failed to put ZOWESVR.JCL in a PROCLIB dataset.
```

In this case, you need to copy the PROC manually. Issue the TSO `oget` command to copy the `ZOWESVR.jcl` file to the preferred PROCLIB:

```
oget '$INSTALL_DIR/files/templates/ZOWESVR.jcl' 'MY.USER.PROCLIB(ZOWESVR)'
```

You can place the PROC in any PROCLIB data set in the PROCLIB concatenation, but some data sets such as `SYS1.PROCLIB` might be restricted, depending on the permission of the user.

You can tailor the JCL at this line

```
/ZOWESVR PROC SRVRPATH='{{root_dir}}'
```

to replace the `{{root_dir}}` with the location of the Zowe runtime directory that contains the z/OS Services. The install process inserts the expanded `install:rootDir` value from the `zowe-install.yaml` file into the SRVRPATH for you by default. Otherwise you must specify that path on the START command when you start Zowe in SDSF:

```
/S ZOWESVR,SRVRPATH='$ZOWE_ROOT_DIR'
```

### Starting and stopping the Zowe runtime on z/OS

Zowe has a number of runtimes on z/OS: the z/OS Service microservice server, the Zowe Application Server, and the Zowe API Mediation Layer microservices. When you run the `ZOWESVR` PROC, all of these components start. The Zowe Application Server startup script also starts the zSS server, so starting the `ZOWESVR` PROC starts all the required servers. Stopping `ZOWESVR` PROC stops all of the servers that run as independent Unix processes.

#### Starting the ZOWESVR PROC

To start the `ZOWESVR` PROC, run the `zowe-start.sh` script at the Unix Systems Services command prompt:

```
cd $ZOWE_ROOT_DIR/scripts
./zowe-start.sh
```

where:

`$ZOWE_ROOT_DIR` is the directory where you installed the Zowe runtime. This script starts the ZOWESVR PROC for you so you do not have to log on to TSO and use SDSF.

**Note:** The default startup allows self-signed and expired certificates from the Zowe Application Framework proxy data services.

If you prefer to use SDSF to start Zowe, start ZOWESVR by issuing the following operator command in SDSF:

```
/S ZOWESVR
```

By default, Zowe uses the runtime version that you most recently installed. To start a different runtime, specify its server path on the START command:

```
/S ZOWESVR,SRVRPATH=' $ZOWE_ROOT_DIR '
```

To test whether the API Mediation Layer is active, open the URL: `https://<hostname>:7554`.

The port number 7554 is the default API Gateway port. You can overwrite this port in the `zowe-install.yaml` file before the `zowe-install.sh` script is run. See Step 2 in [Installing the Zowe runtime on z/OS](#).

### Stopping the ZOWESVR PROC

To stop the ZOWESVR PROC, run the `zowe-stop.sh` script at the Unix Systems Services command prompt:

```
cd $ZOWE_ROOT_DIR/scripts
./zowe-stop.sh
```

If you prefer to use SDSF to stop Zowe, stop ZOWESVR by issuing the following operator command in SDSF:

```
/C ZOWESVR
```

Either method will stop the z/OS Service microservice server, the Zowe Application Server, and the zSS server.

When you stop the ZOWESVR, you might get the following error message:

```
IEE842I ZOWESVR DUPLICATE NAME FOUND- REENTER COMMAND WITH 'A='
```

This error results when there is more than one started task named ZOWESVR. To resolve the issue, stop the required ZOWESVR instance by issuing the following commands:

```
/C ZOWESVR,A=asid
```

You can obtain the `asid` from the value of `A=asid` when you issue the following commands:

```
/D A,ZOWESVR
```

### Installing the Zowe Cross Memory Server on z/OS

The Zowe Cross Memory Service is a started task angel that runs an authorized server application providing privileged cross-memory services to Zowe.

The server runs as a started task and requires an APF authorized load library, a program properties table (PPT) entry, and a parmlib. You can create these by using one of the following methods. The two methods achieve the same end result.

- Manually
- Use the script `/install/zowe-install-apf-server.sh` that reads configuration parameters from the file `/install/zowe-install-apf-server.yaml`

You can choose which method to use depending on your familiarity with z/OS configuration steps that are required for the manual path, together with the authority and privileges of your user ID if you choose to run the automated path.

Once the cross memory server is installed and started, there will be started task ZWESIS01 that runs the load library ZWESIS01. The ZWESIS01 started task serves the ZOWESVR started task and provides secure services that require running in an APF-authorized state.

### **Manually installing the Zowe Cross Memory Server**

A number of files are included in the USS directory \$INSTALL\_DIR/files/zss. If this directory is not present, you must create it by expanding the file \$INSTALL\_DIR/files/zss.pax. To do this, first create the folder zss beneath files using the command `mkdir zss` and navigate into the zss folder using the command `cd zss`. Then, expand the zss.pax file using the command `pax -ppx -rf .../zss.pax`.

The manual installation consists of the following steps.

#### **1. ZWESIS01 load module and proclib**

Zowe Cross Memory Server consists of a single load module with the name ZWESIS01. The load module is supplied in the files\zss\LOADLIB\ZWESIS01 file. This must be copied to a user-defined data set zwes\_loadlib, for example, ZWES.SISLOAD.

You can copy the ZWESIS01 file to your zwes\_loadlib data set by using the command `cp -X ZWESIS01 " // 'zwes_loadlib(ZWESIS01)' "`. The zwes\_loadlib must be a PDSE due to language requirements.

Do not add the zwes\_loadlib data set to the system LNKLST or LPALST concatenations. You must execute it by using a started task that uses a STEPLIB DD statement so that the appropriate version of the software is loaded correctly. A sample JCL for the PROCLIB is provided in files/zss/SAMPLIB/ZWESIS01. Copy this to your system PROCLIB, such as SYS1.PROCLIB, or any other PROCLIB in the JES2 Concatenation PROCLIB Path.

**Note:** The user that is assigned to the started task must have an OMVS segment. The cross memory server loads the module to LPA for its PC-cp services.

#### **2. PPT Entry**

The Zowe cross memory server must run in key 4 and be non-swappable. For the server to start in this environment, you must add a corresponding PPT entry to the SCHEDEX member of the system PARMLIB. For example, add the following PPT entry to the SCHEDEX member:

```
PPT PGMNAME(ZWESIS01) KEY(4) NOSWAP
```

After you edit the PARMLIB, issue the following command to make the SCHEDEX changes effective:

```
/SET SCH=xx
```

#### **3. APF-authorization**

Due to the nature of the services the Zowe cross memory server provides, its load library requires APF-authorization. It is possible to check whether a load library is APF-authorized by using the following TSO command:

```
D PROG,APF,DSNAME=ZWES.SISLOAD
```

where the value of DSNAME is the name of the data set that contains the ZWESIS01 load module.

To dynamically add the load library to the APF list, run one of the following TSO commands:

```
SETPROG APF,ADD,DSNAME=ZWES.SISLOAD,VOLUME=volser  

(If the load library resides on Non SMS-Managed Volume)  

Or  

SETPROG APF,ADD,DSNAME=ZWES.SISLOAD,SMS  

(If the load library is SMS-Managed library)
```

where the value of DSNAME is the name of the data set that contains the ZWESIS01 load module.

#### 4. PARMLIB member

The Zowe cross memory server started task requires a valid ZWESISPxx PARMLIB member to be found at startup. The file \$INSTALL\_DIR/files/zss/SAMPLIB/ZWESIP00 contains the default configuration values. You can copy this member to your system PARMLIB data set, or allocate the default PDS data set ZWES.SISAMP that is specified in the ZWESIS01 started task JCL.

#### 5. Security requirements for the cross memory server

The Zowe cross memory server performs a sequence of SAF checks to protect its services from unauthorized callers. This is done by using the FACILITY class and an entry for ZWES.IS. Valid callers must have READ access to the ZWES.IS class. The following examples assume that you will be running the ZOWESVR STC under the IZUSVR user.

- If you use RACF, issue the following commands:
  - To see the current class settings, issue:

```
SETROPTS LIST
```

- To activate the FACILITY class, issue:

```
SETROPTS CLASSACT(FACILITY)
```

- To RACLIST the FACILITY class, issue:

```
SETROPTS RACLIST(FACILITY)
```

- To define the ZWES.IS profile in the FACILITY class and grant IZUSVR READ access, issue the following commands:

```
RDEFINE FACILITY ZWES.IS UACC(NONE)
PERMIT ZWES.IS CLASS(FACILITY) ID(IZUSVR) ACCESS(READ)
SETROPTS RACLIST(FACILITY) REFRESH
```

- To check whether the permission has been successfully granted, issue the following command:

```
RLIST FACILITY ZWES.IS AUTHUSER
```

This shows the user IDs who have access to the ZWES.IS class, which should include IZUSVR with READ access.

- If you use CA ACF2, issue the following commands:

```
SET RESOURCE(FAC)
RECKEY ZWES ADD(IS ROLE(IZUSVR) SERVICE(READ) ALLOW)
F ACF2,REBUILD(FAC)
```

- If you use CA Top Secret, issue the following commands, where owner-acid may be IZUSVR or a different ACID:

```
TSS ADD(`owner-acid`) IBMFAC(ZWES.)
TSS PERMIT(IZUSVR) IBMFAC(ZWES.IS) ACCESS(READ)
```

## 6. ICSF cryptographic services

The user IZUSVR who runs ZOWESVR will need READ access to CSFRNGL in the CSFSERV class in order to generate symmetric keys.

When using ICSF services, you need to define or check the following configurations depending on whether ICSF is already installed.

- The ICSF or CSF job that runs on your z/OS system.
- Configuration of ICSF options in SYS1.PARMLIB(CSFPRM00), SYS1.SAMPLIB, SYS1.PROCLIB.
- Create CKDS, PKDS, TKDS VSAM data sets.
- Define and activate the CSFSERV class:
  - If you use RACF, issue the following commands:

```
RDEFINE CSFSERV profile-name UACC(NONE)
PERMIT profile-name CLASS(CSFSERV) ID(tcpip-stackname) ACCESS(READ)
PERMIT profile-name CLASS(CSFSERV) ID(userid-list) ... [for userids
IKED, NSSD, and Policy Agent]
SETROPTS CLASSACT(CSFSERV)
SETROPTS RACLIST(CSFSERV) REFRESH
```

- If you use CA ACF2, issue the following commands. Note that **profile-prefix** and **profile-suffix** are user defined.

```
SET CONTROL(GSO)
INSERT CLASMAP.CSFSERV RESOURCE(CSFSERV) RSRCTYPE(CSF)
F ACF2,REFRESH(CLASMAP)
SET RESOURCE(CSF)
RECKEY profile-prefix ADD(profile-suffix uid(UID string for tcpip-
stackname) SERVICE(READ) ALLOW)
RECKEY profile-prefix ADD(profile-suffix uid(UID string for IZUSVR)
SERVICE(READ) ALLOW) ... [repeat for userids IKED, NSSD, and Policy
Agent]
F ACF2,REBUILD(CSF)
```

- If you use CA Top Secret, issue the following commands. Note that **profile-prefix** and **profile-suffix** are user defined.

```
TSS ADDTO(owner-acid) RESCLASS(CSFSERV)

TSS ADD(owner-acid) CSFSERV(profile-prefix.)
TSS PERMIT(tcpip-stackname) CSFSERV(profile-prefix.profile-suffix)
ACCESS(READ)
TSS PERMIT(user-acid) CSFSERV(profile-prefix.profile-suffix)
ACCESS(READ) ... [repeat for user-acids IKED, NSSD,
and Policy Agent]
```

- The user under which zssServer runs will need READ access to CSFRNGL in the CSFSERV class.
- Determine whether you want SAF authorization checks against CSFSERV and set CSF.CSFSERV.AUTH.CSFRNG.DISABLE accordingly.
- Refer to the [z/OS 2.3.0 z/OS Cryptographic Services ICSF System Programmer's Guide: Installation, initialization, and customization](#).
- CCA and/or PKCS #11 coprocessor for random number generation.
- Enable FACILITY IRR.PROGRAM.SIGNATURE.VERIFICATION and RDEFINE CSFINPV2 if required.

## 7. Security environment switching

The node zssServer running under USS needs the ability to change the security environment of its process in order to associate itself with the security context of the logged in user when responding to API requests, also known

as impersonation. To switch the security environment, the user ID associated with the ZOWESVR started task IZUSVR must have UPDATE access to the BPX.SERVER and BPX.DAEMON FACILITY classes.

You can issue the following commands first to check if you already have the BPX facilities defined as part of another server configuration, such as the FTPD daemon. Review the output to confirm that the two BPX facilities exist and the user who runs the ZWESIS01 started task (IZUSVR by default) has UPDATE access to both facilities.

- If you use RACF, issue the following commands:

```
RLIST FACILITY BPX.SERVER AUTHUSER
RLIST FACILITY BPX.DAEMON AUTHUSER
```

- If you use CA Top Secret, issue the following commands:

```
TSS WHOHAS IBMFAC(BPX.SERVER)
TSS WHOHAS IBMFAC(BPX.DAEMON)
```

- If you use CA ACF2, issue the following commands:

```
SET RESOURCE(FAC)
LIST BPX
```

If the user who runs the ZWESIS01 started task does not have UPDATE access to both facilities, follow the instructions below.

- If you use RACF, complete the following steps:

[Click to Expand](#)

- Activate and RACLIST the FACILITY class. This may have already been done on the z/OS environment if another z/OS server has been previously configured to take advantage of the ability to change its security environment, such as the FTPD daemon that is included with z/OS Communications Server TCP/IP services.

```
SETROPTS CLASSACT(FACILITY)
SETROPTS RACLIST(FACILITY)
```

- Define the BPX facilities. This may have already been done on behalf of another server such as the FTPD daemon.

```
RDEFINE FACILITY BPX.SERVER UACC(NONE)
RDEFINE FACILITY BPX.DAEMON UACC(NONE)
```

- Having activated and RACLIST the FACILITY class, the user ID who runs the ZWESIS01 started task (by default IZUSVR) must be given update access to the BPX.SERVER and BPX.DAEMON profiles in the FACILITY class.

```
PERMIT BPX.SERVER CLASS(FACILITY) ID(IZUSVR) ACCESS(UPDATE)
PERMIT BPX.DAEMON CLASS(FACILITY) ID(IZUSVR) ACCESS(UPDATE)
/* Activate these changes */
SETROPTS RACLIST(FACILITY) REFRESH
```

- Issue the following commands to check whether permission has been successfully granted:

```
RLIST FACILITY BPX.SERVER AUTHUSER
```

```
RLIST FACILITY BPX.DAEMON AUTHUSER
```

- If you use CA Top Secret, complete the following steps:

Click to Expand

- Define the BPX Resource and access for IZUSVR.

```
TSS ADD(`owner-acid`) IBMFAC(BPX.)
TSS PERMIT(IZUSVR) IBMFAC(BPX.SERVER) ACCESS(UPDATE)
TSS PERMIT(IZUSVR) IBMFAC(BPX.DAEMON) ACCESS(UPDATE)
```

- Issue the following commands and review the output to check whether permission has been successfully granted:

```
TSS WHOHAS IBMFAC(BPX.SERVER)
TSS WHOHAS IBMFAC(BPX.DAEMON)
```

- If you use CA ACF2, complete the following steps:

Click to Expand

- Define the BPX Resource and access for IZUSVR.

```
SET RESOURCE(FAC)
RECKEY BPX ADD(SERVER ROLE(IZUSVR) SERVICE(UPDATE) ALLOW)
RECKEY BPX ADD(DAEMON ROLE(IZUSVR) SERVICE(UPDATE) ALLOW)
F ACF2,REBUILD(FAC)
```

- Issue the following commands and review the output to check whether permission has been successfully granted:

```
SET RESOURCE(FAC)
LIST BPX
```

### Scripted install of the Zowe Cross Memory Server

For users who have sufficient authority under their user ID on the z/OS instance where they are installing the Zowe cross memory server, a convenience script is provided in `$INSTALL_DIR/install/zowe-install-apf-server.sh`.

- The script will create the APF authorized load library, copy the load module, create the PROCLIB, define the `ZWES.IS` FACILITY class and give READ access to the `ZOWESVR` user ID.
- The script will not create the PPT entry which must be done manually. This is done using the steps described in step "5. Security requirements for the cross memory server" in [Manually installing the Zowe Cross Memory Server](#) on page 66.
- The script will not create anything for the ICSF cryptographic services. These are described in step "6. ICSF cryptographic services" in [Manually installing the Zowe Cross Memory Server](#) on page 66.

Because the parameters that are used to control the script are contained in the file `$INSTALL_DIR/install/zowe-install-apf-server.yaml`, you must edit this file before running the `zowe-install-apf-server.sh` script with appropriate values.

```
# Datasets that APF server will be installed into
install:
  # PROCLIB dataset name (required, no default values)
  proclib=
  # PARMLIB dataset name (${USER}.PARMLIB by default)
  parmlib=
  # LOADLIB dataset name (${USER}.LOADLIB by default)
  loadlib=
```

where,

- *install:proclib* is the data set name that the ZWESIS01 JCL member that is used to start the ZWESIS01 started task will be copied into, for example, USER.PROCLIB.
- *install:parmlib* is the data set name that the ZWESIP00 PARMLIB member will be copied into and used by the ZWESIS01 PROCLIB. Choose a value such as IZUSVR.PARMLIB.
- *install:loadlib* is the data set name where the ZWESIS01 load module will be copied into. This data set will be created as a PDSE and be APF authorized by the script. Choose a value such as USER.LOADLIB.

```
# APF server users
users:
  # User to run Zowe server (required, no default values)
  zoweUser=
  # APF server STC user (ZWESISTC by default)
  stcUser=
  # APF server STC user UID (required if STC user doesn't exist)
  stcUserUid=
  # STC user group (required if either STC user or profile doesn't exist)
  stcGroup=
```

where,

- *users:zoweUser* is the TSO user ID that the ZOWESVR started task runs under. For the majority of installs, this will be IZUSVR, so enter IZUSVR as the value, and the script will give this user access to the READ ZWES.FACILITY class that allows Zowe to use the cross memory server.
- *users:stcUser* is the user ID that the ZWESIS01 started task will be run under. Enter the same value as the user ID that is running ZOWESVR, so choose IZUSVR.
- *users:stcUserUid*. This is the Unix user ID of the TSO user ID used to run the ZWESIS01 started task. If the user ID is IZUSVR to see the Unix user ID enter the command `id IZUSVR` which will return the stcUserUid in the uid result. In the example below IZUSVR has a uid of 210, so *users:stcUserUid=210* should be entered.

```
/:>id IZUSVR
uid=210(IZUSVR) gid=202(IZUADMIN) groups=205(IZUSECAD)
```

- *users:stcGroup* is the user group that the ZWESIS01 started task will be run under. Enter the same values as the user group that is running ZOWESVR, so choose IZUADMIN.

After you edit the `zowe-install-apf-server.yaml` file with values, add a PPT entry before you run `zowe-install-apf-server.sh`.

## Starting and stopping the Zowe Cross Memory Server on z/OS

The Zowe Cross Memory server is run as a started task from the JCL in the PROCLIB member ZWESIS01. To start this, issue the operator start command through SDSF:

```
/S ZWESIS01
```

To end the Zowe APF Angel process, issue the operator stop command through SDSF:

```
/P ZWESIS01
```

**Note:** The starting and stopping of the ZOWESVR for the main Zowe servers is independent of the ZWESIS01 angel process. If you are running more than one ZOWESVR instance on the same LPAR, then these will be sharing the same ZWESIS01 cross memory server. Stopping ZWESIS01 will affect the behavior of all Zowe servers on the same LPAR. The Zowe Cross Memory Server is designed to be a long-lived address space. There is no requirement to recycle on a regular basis. When the cross-memory server is started with a new version of the ZWESIS01 load module, it will abandon its current load module instance in LPA and will load the updated version.

## Verifying installation

Once Zowe is running and the startup sequence is complete, you can check the configuration files and jobs for Zowe on your z/OS system to ensure that the installation process is successful. To do this, follow these steps.

1. Navigate to the runtime `$ZOWE_ROOT_DIR/scripts` directory, where `$ZOWE_ROOT_DIR` is the location of the Zowe runtime directory that contains the explorer server.
2. Run the `zowe-verify.sh` script by issuing the following command:

```
zowe-verify.sh
```

The script writes its messages to your terminal window. The results are marked OK, Info, Warning or Error. Correct any reported errors and restart the Zowe server. The `zowe-verify.sh` script does not change any settings, so you can run it as often as required.

### Next steps

Follow the instructions in the following sections to verify that the components are installed correctly and are functional.

- [Verifying Zowe Application Framework installation](#) on page 72
- [Verifying z/OS Services installation](#)
- [Verifying API Mediation installation](#) on page 72

### Verifying Zowe Application Framework installation

If the Zowe Application Framework is installed correctly, you can open the Zowe Desktop from a supported browser.

From a supported browser, open the Zowe Desktop at `https://myhost:httpsPort/ZLUX/plugins/org.zowe.zlux.bootstrap/web/index.html`

where:

- *myHost* is the host on which you installed the Zowe Application Server.
- *httpPort* is the port number that is assigned to `node.http.port` in `zluxserver.json`.
- *httpsPort* is the port number that is assigned to `node.https.port` in `zluxserver.json`.

For example, if the Zowe Application Server runs on host *myhost* and the port number that is assigned to `node.https.port` is 12345, you specify `https://myhost:12345/ZLUX/plugins/org.zowe.zlux.bootstrap/web/index.html`.

### Verifying z/OS Services installation

After the ZOWESVR procedure is started, you can verify the installation of z/OS Services from an internet browser by entering the following case-sensitive URL:

```
https://hostName:<_gatewayPort_>/api/v1/jobs?prefix=*
```

where, *gatewayPort* is the port number that is assigned to `api:mediation:gatewayPort` in `zowe-install.yaml`.

### Verifying API Mediation installation

Use your preferred REST API client to review the value of the `status` variable of the API Catalog service that is routed through the API Gateway using the following URL:

```
https://hostName:basePort/api/v1/apicatalog/application/health
```

The `hostName` is set during install, and `basePort` is set as the `gatewayPort` parameter.

#### Example:

The following example illustrates how to use the `curl` utility to invoke API Mediation Layer endpoint and the `grep` utility to parse out the response status variable value

```
$ curl -v -k --silent https://hostName:basePort/api/v1/apicatalog/application/health 2>&1 | grep -Po '(?=<\"status\"\\:\\")[^\\"]+'  
UP
```

The response UP confirms that API Mediation Layer is installed and is running properly.

### **Looking for troubleshooting help?**

If you encounter unexpected behavior when installing or verifying Zowe runtime, see the [Troubleshooting](#) on page 244 section for troubleshooting tips.

## **Installing Zowe CLI**

Install Zowe CLI on your computer. You can learn about new CLI features in the [Release notes](#) on page 14 or read about overall CLI functionality in the [Zowe overview](#) on page 8.

**Tip:** If you are familiar with command-line tools and want to get started using Zowe CLI quickly, see [Zowe CLI quick start](#) on page 22

### **Methods to install Zowe CLI**

Use one of the following methods to install Zowe CLI.

- [Installing Zowe CLI from a local package](#) on page 73
- [Installing Zowe CLI from an online registry](#) on page 74

If you encounter problems when you attempt to install Zowe CLI, see [Troubleshooting Zowe CLI](#) on page 253.

### **Installing Zowe CLI from a local package**

If you do not have internet access at your site, use the following method to install Zowe CLI from a local package.

#### **Follow these steps:**

1. Ensure that the following prerequisite software is installed on your computer:

- [Node.js V8.0 or later](#)

**Tip:** You might need to restart the command prompt after installing Node.js. Issue the command `node --version` to verify that Node.js is installed.

- [Node Package Manager V5.0 or later](#)

`npm` is included with the Node.js installation. Issue the command `npm --version` to verify that `npm` is installed.

2. Obtain the installation files. From the Zowe [Download](#) website, click [Zowe Command Line Interface](#) to download the Zowe CLI installation package named `zowe-cli-package-*v*.r.*m*.zip` to your computer.

#### **Note:**

- `v` indicates the version
- `r` indicates the release number
- `m` indicates the modification number

3. Open a command line window such as Windows Command Prompt. Browse to the directory where you downloaded the Zowe CLI installation package (.zip file). Issue the following command to unzip the files:

```
unzip zowe-cli-package-v.r.m.zip
```

#### **Example:**

```
unzip zowe-cli-package-1.0.1.zip
```

By default, the `unzip` command extracts the contents of the zip file to the directory where you downloaded the .zip file. You can extract the contents of the zip file to your preferred location.

**Optional:** Double-click the Zowe CLI installation package to extract its contents into the directory where you downloaded the package. (Windows and Mac computers contain built-in software that lets you extract .zip files into a preferred location.)

- Issue the following command against the extracted directory to install Zowe CLI on your computer:

```
npm install -g zowe-cli.tgz
```

**Note:** On Linux, you might need to prepend `sudo` to your `npm` commands so that you can issue the install and uninstall commands. For more information, see [Troubleshooting Zowe CLI](#) on page 253.

Zowe CLI is installed on your computer. See [Installing plug-ins](#) on page 120 for information about the commands for installing plug-ins from the package.

- (Optional) Create a `zosmf` profile so that you can issue commands that communicate with z/OSMF. For information about how to create a profile, see [Creating Zowe CLI profiles](#) on page 89.

**Tip:** Profiles are a Zowe CLI feature that let you store configuration information for use on multiple commands. You can create a profile that contains your username, password, and connection details for a particular mainframe system, then reuse that profile to avoid typing it again on every command.

After you install and configure Zowe CLI, you can issue the `zowe --help` command to view a list of available commands. For information about how to connect the CLI to the mainframe (using command-line options, user profiles, or environment variables), see [Defining Zowe CLI connection details](#) on page 88. You can also [test your connection to z/OSMF](#) with or without a profile.

### Installing Zowe CLI from an online registry

If your computer is connected to the Internet, you can use the following method to install Zowe CLI from an npm registry.

#### Follow these steps:

- Ensure that the following required software is installed on your computer:

- Node.js V8.0 or later**

**Tip:** You might need to restart the command prompt after installing Node.js. Issue the command `node --version` to verify that Node.js is installed.

- Node Package Manager V5.0 or later**

`npm` is included with the Node.js installation. Issue the command `npm --version` to verify that `npm` is installed.

- Issue the following command to set the registry to the Zowe CLI scoped package. In addition to setting the scoped registry, your default registry must be set to an npm registry that includes all of the dependencies for Zowe CLI, such as the global npm registry:

```
npm config set @brightside:registry https://api.bintray.com/npm/ca/brightside
```

- Issue the following command to install Zowe CLI from the registry:

```
npm install -g @brightside/core@lts-incremental
```

- (Optional) To install all available plug-ins to Zowe CLI, issue the following command:

```
zowe plugins install @brightside/cics@lts-incremental
```

**Note:** The IBM Db2 plug-in requires additional configuration. For more information about how to install multiple plug-ins, update to a specific version of a plug-in, and install from specific registries, see [Installing plug-ins](#) on page 120.

After you install and configure Zowe CLI, you can issue the `zowe --help` command to view a list of available commands. For information about how to connect the CLI to the mainframe (using command-line options, user profiles, or environment variables), see [Defining Zowe CLI connection details](#) on page 88. You can also [test your connection to z/OSMF](#) with or without a profile.

## Updating Zowe CLI

Zowe CLI is updated continuously. You can update Zowe CLI to a more recent version using online registry method or the local package method. However, you can only update Zowe CLI using the method that you used to install Zowe CLI.

- [\(Optional\) Identify the currently installed version of Zowe CLI](#) on page 75
- [\(Optional\) Identify the currently installed versions of Zowe CLI plug-ins](#) on page 75
- [Update Zowe CLI from the online registry](#) on page 75
- [Update or revert Zowe CLI to a specific version](#) on page 75
- [Update Zowe CLI from a local package](#) on page 75

### (Optional) Identify the currently installed version of Zowe CLI

Issue the following command:

```
zowe -V
```

### (Optional) Identify the currently installed versions of Zowe CLI plug-ins

Issue the following command:

```
zowe plugins list
```

### Update Zowe CLI from the online registry

You can update Zowe CLI to the latest version from the online registry on Windows, Mac, and Linux computers.

**Note:** The following steps assume that you set the npm registries for the @brightside scopes as described in [Installing Zowe CLI from an online registry](#) on page 74.

#### Follow these steps:

1. Issue the following command to update Zowe CLI to the most recent @lts-incremental version:

```
npm install -g @brightside/core@lts-incremental
```

2. Reinstall the plug-ins and update existing plug-ins using the following command:

```
zowe plugins install @brightside/cics@lts-incremental @brightside/db2@lts-incremental
```

3. Recreate any user profiles that you created before you updated to the latest version of Zowe CLI.

### Update or revert Zowe CLI to a specific version

Optionally, you can update Zowe CLI (or revert) to a known version. The following example illustrates the syntax to update Zowe CLI to version 3.3.1:

```
npm install -g @brightside/core@3.3.1
```

### Update Zowe CLI from a local package

To update Zowe CLI from an offline (.tgz), local package, uninstall your current package then reinstall from a new package using the Install CA Brightside from a Local Package instructions. For more information, see [Uninstalling Zowe CLI from the desktop](#) on page 76 and [Installing Zowe CLI from a local package](#) on page 73.

**Important!** Recreate any user profiles that you created before the update.

## Uninstalling Zowe

You can uninstall Zowe if you no longer need to use it. Follow these procedures to uninstall each Zowe component.

- [Uninstalling Zowe from z/OS](#)
- [Uninstalling Zowe CLI from the desktop](#) on page 76

## Uninstalling Zowe from z/OS

**Follow these steps on z/OS:**

1. Stop the Zowe started task which stops all of its microservices by using the following command:

```
C ZOWESVR
```

2. Delete the ZOWESVR member from your system PROCLIB data set.

To do this, you can issue the following TSO DELETE command from the TSO READY prompt or from ISPF option 6:

```
delete 'your.zowe.proclib(zowesvr)'
```

Alternatively, you can issue the TSO DELETE command at any ISPF command line by prefixing the command with TSO:

```
tso delete 'your.zowe.proclib(zowesvr)'
```

To query which PROCLIB data set that ZOWESVR is put in, you can view the SDSF JOB log of ZOWESVR and look for the following message:

```
IEFC001I PROCEDURE ZOWESVR WAS EXPANDED USING SYSTEM LIBRARY  
your.zowe.proclib
```

If no ZOWESVR JOB log is available, issue the /\$D PROCLIB command at the SDSF COMMAND INPUT line and BROWSE each of the DSNAME=some.jes.proclib output lines in turn with ISPF option 1, until you find the first data set that contains member ZOWESVR. Then issue the DELETE command as shown above.

3. Remove RACF® (or equivalent) definitions using the following command:

```
RDELETE STARTED (ZOWESVR.*)
SETR RACLIST(STARTED) REFRESH
REMOVE (userid) GROUP(IZUUSER)
```

where *userid* indicates the user ID that is used to install Zowe.

## Uninstalling Zowe CLI from the desktop

**Important!** The uninstall process does not delete the profiles and credentials that you created when using the product from your computer. To delete the profiles from your computer, delete them before you uninstall Zowe CLI.

The following steps describe how to list the profiles that you created, delete the profiles, and uninstall Zowe CLI.

**Follow these steps:**

1. Open a command line window.

**Note:** If you do not want to delete the Zowe CLI profiles from your computer, go to Step 5.

2. List all profiles that you created for a [Command Group](#) by issuing the following command:

```
zowe profiles list <profileType>
```

**Example:**

```
$ zowe profiles list zosmf
The following profiles were found for the module zosmf:
'SMITH-123' (DEFAULT)
smith-123@SMITH-123-W7 C:\Users\SMITH-123
```

```
$
```

3. Delete all of the profiles that are listed for the command group by issuing the following command:

**Tip:** For this command, use the results of the `list` command.

**Note:** When you issue the `delete` command, it deletes the specified profile and its credentials from the credential vault in your computer's operating system.

```
zowe profiles delete <profileType> <profileName> --force
```

#### Example:

```
zowe profiles delete zosmf SMITH-123 --force
```

4. Repeat Steps 2 and 3 for all Zowe CLI command groups and profiles.

5. Uninstall Zowe CLI by issuing one of the following commands:

- If you installed Zowe CLI from the package, issue the following command

```
npm uninstall --global @brightside/core
```

- If you installed Zowe CLI from the online registry, issue the following command:

```
npm uninstall --global brightside
```

The uninstall process removes all Zowe CLI installation directories and files from your computer.

6. Delete the `C:\Users\<user_name>\.brightside` directory on your computer. The directory contains the Zowe CLI log files and other miscellaneous files that were generated when you used the product.

**Tip:** Deleting the directory does not harm your computer.

7. If you installed Zowe CLI from the online registry, issue the following command to clear your scoped npm registry:

```
npm config set @brightside:registry
```

---

## Configuring Zowe

### Zowe Application Framework configuration

After you install Zowe, you can optionally configure the Zowe Application Framework as a Mediation Layer client, configure connections for the terminal application plug-ins, or modify the Zowe Application Server and Zowe System Services (ZSS) configuration, as needed.

#### Configuring the framework as a Mediation Layer client

For simpler Zowe administration and better security, you can install an instance of the Zowe Application Framework as an API Mediation Layer client.

This configuration is simpler to administer because the framework servers are accessible externally through a single port. It is more secure because you can implement stricter browser security policies for accessing cross-origin content.

You must use SSL certificates to configure the Zowe Application Server to communicate with the SSL-enabled Mediation Layer. Those certificates were created during the Zowe installation process, and are located in the `zlux-app-server/deploy/instance/ZLUX/serverConfig` directory.

#### Enabling the Application Server to register with the Mediation Layer

1. Open the Application Server configuration file: `zlux-app-server/deploy/instance/ZLUX/serverConfig/zluxserver.json`. The file might be in the `zlux-app-server/config` directory.

If so, navigate to the `zlux-build` folder and run the `ant deploy` command to deploy the file to the correct location.

## 2. Specify the following values:

- `mediationLayer`: If this object is not there, create it. It contains all of the key-value pairs.
- `server`: Container for most of the key-value pairs.
- `hostname` (string): Specify the hostname that the Application Server can use to access the Mediation Layer servers. The Mediation Layer servers must be on a single system.
- `port` (number): Specify the Mediation Layer discovery server TCP port.
- `gatewayPort` (number): Specify the gateway TCP port (used for single sign-on).
- `isHttps` (boolean): Specify `true` to use HTTPS (recommended).
- `enabled` (boolean): Specify `true` to enable the Application Server to use the Mediation Layer.

For example:

```
"mediationLayer": {
  "server": {
    "hostname": "localhost",
    "port": 10011,
    "gatewayPort": 10012,
    "isHttps": true
  },
  "enabled": true
}
```

To verify that the server registered correctly, open the log file in the `zlux/zlux-app-server/log` directory. The following line should be at the bottom (with the current date and time):

```
[20xx-xx-xx xx:xx:xx.xxx _zsf.apiml INFO] - Eureka Client Registered
```

The registration process might take a few minutes. If the line is not there, make sure that the Mediation Layer values you enabled in the `zluxserver.json` file are correct.

## Accessing the Application Server

To access the Application Server through the Mediation Layer, use the Mediation Layer gateway server hostname and port. For example, when accessed directly, this is Zowe Desktop URL: `https://<appservername_port>/ZLUX/plugins/org.zowe.zlux.bootstrap/web/index.html`

When accessed through the Mediation Layer, this is the Zowe Desktop URL: `https://<gwsname_port>/ui/v1/zlux/ZLUX/plugins/org.zowe.zlux.bootstrap/web/index.html`

## Setting up terminal application plug-ins

Follow these optional steps to configure the default connection to open for the terminal application plug-ins.

### Setting up the TN3270 mainframe terminal application plug-in

`_defaultTN3270.json` is a file in `tn3270-ng2/`, which is deployed during setup. Within this file, you can specify the following parameters to configure the terminal connection:

```
"host": <hostname>
"port": <port>
"security": {
  type: "<telnet" or "tls">
}
```

### Setting up the VT Terminal application plug-in

`_defaultVT.json` is a file in `vt-ng2/`, which is deployed during setup. Within this file, you can specify the following parameters to configure the terminal connection:

```
"host": <hostname>
```

```

    "port": <port>
    "security": {
        type: <"telnet" or "ssh">
    }
}

```

## Configuration file

The Zowe Application Server and ZSS rely on many parameters to run, which includes setting up networking, deployment directories, plug-in locations, and more.

For convenience, the Zowe Application Server and ZSS read from a JSON file with a common structure. ZSS reads this file directly as a startup argument, while the Zowe Application Server (as defined in the `zlux-server-framework` repository) accepts several parameters, which are intended to be read from a JSON file through an implementer of the server, such as the example in the `zlux-app-server` repository, the `js/zluxServer.js` file. This file accepts a JSON file that specifies most, if not all, of the parameters needed. Other parameters can be provided through flags, if needed.

An example of a JSON file (`zluxserver.json`) can be found in the `zlux-app-server` repository, in the `config` directory.

**Note:** All examples are based on the `zlux-app-server` repository.

## Network configuration

**Note:** The following attributes are to be defined in the server's JSON configuration file.

The Zowe Application Server can be accessed over HTTP, HTTPS, or both, provided it has been configured for either (or both).

### HTTP

To configure the server for HTTP, complete these steps:

1. Define an attribute `http` within the top-level `node` attribute.
2. Define `port` within `http`. Where `port` is an integer parameter for the TCP port on which the server will listen. Specify 80 or a value between 1024-65535.

### HTTPS

For HTTPS, specify the following parameters:

1. Define an attribute `https` within the top-level `node` attribute.
2. Define the following within `https`:
  - `port`: An integer parameter for the TCP port on which the server will listen. Specify 443 or a value between 1024-65535.
  - `certificates`: An array of strings, which are paths to PEM format HTTPS certificate files.
  - `keys`: An array of strings, which are paths to PEM format HTTPS key files.
  - `pfx`: A string, which is a path to a PFX file which must contain certificates, keys, and optionally Certificate Authorities.
  - `certificateAuthorities` (Optional): An array of strings, which are paths to certificate authorities files.
  - `certificateRevocationLists` (Optional): An array of strings, which are paths to certificate revocation list (CRL) files.

**Note:** When using HTTPS, you must specify `pfx`, or both `certificates` and `keys`.

## Network example

In the example configuration, both HTTP and HTTPS are specified:

```

"node": {
    "https": [
        "port": 8544,

```

```
//pfx (string), keys, certificates, certificateAuthorities, and
certificateRevocationLists are all valid here.
  "keys": [ "../deploy/product/ZLUX/serverConfig/server.key" ],
  "certificates": [ "../deploy/product/ZLUX/serverConfig/server.cert" ]
},
  "http": {
    "port": 8543
  }
}
```

## Deploy configuration

When the Zowe Application Server is running, it accesses the server's settings and reads or modifies the contents of its resource storage. All of this data is stored within the Deploy folder hierarchy, which is spread out into a several scopes:

- **Product:** The contents of this folder are not meant to be modified, but used as defaults for a product.
- **Site:** The contents of this folder are intended to be shared across multiple Zowe Application Server instances, perhaps on a network drive.
- **Instance:** This folder represents the broadest scope of data within the given Zowe Application Server instance.
- **Group:** Multiple users can be associated into one group, so that settings are shared among them.
- **User:** When authenticated, users have their own settings and storage for the application plug-ins that they use.

These directories dictate where the [Configuration Dataservice](#) on page 206 stores content.

## Deploy example

```
// All paths relative to zlux-app-server/js or zlux-app-server/bin
// In real installations, these values will be configured during the
installation process.
  "rootDir": "../deploy",
  "productDir": "../deploy/product",
  "siteDir": "../deploy/site",
  "instanceDir": "../deploy/instance",
  "groupsDir": "../deploy/instance/groups",
  "usersDir": "../deploy/instance/users"
```

## Application plug-in configuration

This topic describes application plug-ins that are defined in advance.

In the configuration file, you can specify a directory that contains JSON files, which tell the server what application plug-in to include and where to find it on disk. The backend of these application plug-ins use the server's plug-in structure, so much of the server-side references to application plug-ins use the term *plug-in*.

To include application plug-ins, define the location of the plug-ins directory in the configuration file, through the top-level attribute **pluginsDir**.

**Note:** In this example, the directory for these JSON files is /plugins. Yet, to separate configuration files from runtime files, the zlux-app-server repository copies the contents of this folder into /deploy/instance/ZLUX/plugins. So, the example configuration file uses the latter directory.

## Plug-ins directory example

```
// All paths relative to zlux-app-server/js or zlux-app-server/bin
// In real installations, these values will be configured during the install
process.
//...
  "pluginsDir": "../deploy/instance/ZLUX/plugins",
```

## Logging configuration

For more information, see [Logging utility](#) on page 219.

## ZSS configuration

Running ZSS requires a JSON configuration file that is similar or the same as the one used for the Zowe Application Server. The attributes that are needed for ZSS, at minimum, are: *rootDir*, *productDir*, *siteDir*, *instanceDir*, *groupsDir*, *usersDir*, *pluginsDir* and *zssPort*. All of these attributes have the same meaning as described above for the server, but if the Zowe Application Server and ZSS are not run from the same location, then these directories can be different.

The *zssPort* attribute is specific to ZSS. This is the TCP port on which ZSS listens in order to be contacted by the Zowe Application Server. Define this port in the configuration file as a value between 1024-65535.

## Connecting the Zowe Application Server to ZSS

When you run the Zowe Application Server, specify the following flags to declare which ZSS instance the Zowe Application Framework will proxy ZSS requests to:

- *-h*: Declares the host where ZSS can be found. Use as "*-h <hostname>*"
- *-P*: Declares the port at which ZSS is listening. Use as "*-P <port>*"

## Configuring ZSS for HTTPS

To secure ZSS, you can use Application Transparent Transport Layer Security (AT-TLS) to enable Hyper Text Transfer Protocol Secure (HTTPS) on communication with ZSS.

Before you begin, you must have a basic knowledge of RACF and AT-TLS, and you must have Policy Agent configured. For more information on [AT-TLS](#) and [Policy Agent](#), see the [z/OS Knowledge Center](#).

To configure ZSS for HTTPS, you create a certificate authority (CA) certificate and a personal certificate, and add the personal certificate to a key ring. Then you define an AT-TLS rule. Then you copy the certificate to the Zowe App Server and specify values in the Zowe App Server configuration file.

By default, the Zowe App Server is the only client that communicates with the ZSS server. In these steps, you configure HTTPS between them by creating a CA certificate and using it to sign a personal certificate. If you want to configure other clients to communicate with ZSS, best practice is to sign their certificates using a recognized certificate authority, such as Symantec. For more information, see documentation for that client.

**Note:** Bracketed values below (including the brackets) are variables. Replace them with values relevant to your organization.

### Creating certificates and a key ring

Use the IBM Resource Access Control Facility (RACF) to create a CA certificate and a personal certificate, and sign the personal certificate with the CA certificate. Then create a key ring with the personal certificate attached.

1. Enter the following command to generate a RACF (CA) certificate:

```
RACDCERT CERTAUTH GENCERT +
 SUBJECTSDN(CN(' [common_name] ') +
 OU(' [organizational_unit] ') +
 O(' [organization_name] ') +
 L(' [locality] ') SP(' [state_or_province] ') C(' [country] ') ) +
 KEYUSAGE(HANDSHAKE DATAENCRYPT DOCSIGN CERTSIGN) +
 WITHLABEL(' [ca_label] ') +
 NOTAFTER(DATE(' [xxxx/xx/xx] ') ) +
 SIZE(2048)
```

**Note:** `[common_name]` must be the ZSS server host name.

1. Enter the follow command to generate a RACF personal certificate signed by the CA certificate:

```
RACDCERT ID(' [cert_owner] ') GENCERT +
 SUBJECTSDN(CN(' [common_name] ') +
```

```

OU(''[organizational_unit]'') +
O(''[organization_name]'') +
L(''[locality]'') SP(''[state_or_province]'') C(''[country]'') +
KEYUSAGE(HANDSHAKE DATAENCRYPT DOCSIGN CERTSIGN) +
WITHLABEL(''[personal_label]'') +
NOTAFTER(DATE([xxxx/xx/xx])) +
SIZE(2048) +
SIGNWITH(CERTAUTH LABEL(''[ca_label]''))

```

1. Enter the following command to create a RACF key ring and connect the personal certificate to the key ring:

```

RACDCERT ID([cert_owner]) ADDRING([ring_name])
RACDCERT CONNECT(ID([cert_owner]) LABEL(''[cert_label]'') RING([ring_name]))

```

1. Enter the following command to refresh the DIGTRING and DIGTCERT classes to activate your changes:

```

SETROPTS RACLIST(DIGTRING,DIGTCERT) REFRESH

```

1. Enter the following command to verify your changes:

```

RACDCERT LISTRING([ring_name]) ID([cert_owner])

```

1. Enter the following command to export the RACF CA certificate to a dataset:

```

RACDCERT EXPORT(LABEL(''[ca_label]'')) CERTAUTH DSN(''[output_dataset_name]'')
FORMAT(CERTB64)

```

#### *Defining the AT-TLS rule*

To define the AT-TLS rule, use the sample below to specify values in your AT-TLS Policy Agent Configuration file:

TTLSRule	ATTLS1~ZSS
{	
LocalAddr	All
RemoteAddr	All
LocalPortRange	[zss_port]
Jobname	*
Userid	*
Direction	Inbound
Priority	255
TTLSGroupActionRef	gAct1~ZSS
TTLSEnvironmentActionRef	eAct1~ZSS
TTLSCreationActionRef	cAct1~ZSS
}	
TTLSGroupAction	gAct1~ZSS
{	
TTLSEnabled	On
Trace	1
}	
TTLSEnvironmentAction	eAct1~ZSS
{	
HandshakeRole	Server
EnvironmentUserInstance	0
TTLSCKeyringParmsRef	key~ZSS
Trace	1
}	
TTLSCreationAction	cAct1~ZSS
{	
HandshakeRole	Server
TTLSCipherParmsRef	cipherZSS
TTLSCreationAdvancedParmsRef	cAdvl~ZSS
Trace	1

```

}
TTLSCConnectionAdvancedParms      cAdvl~ZSS
{
  SSLv3                         Off
  TLSv1                          Off
  TLSv1.1                        Off
  TLSv1.2                        On
  CertificateLabel                [personal_label]
}
TTLSSKeyringParms               key~ZSS
{
  Keyring                        [ring_name]
}
TTLSCipherParms                 cipher~ZSS
{
  V3CipherSuites                  TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA256
  V3CipherSuites                  TLS_ECDHE_ECDSA_WITH_AES_256_CBC_SHA384
  V3CipherSuites                  TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256
  V3CipherSuites                  TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384
  V3CipherSuites                  TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256
  V3CipherSuites                  TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384
  V3CipherSuites                  TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256
  V3CipherSuites                  TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
}

```

### *Configuring the Zowe App Server for HTTPS communication with ZSS*

Copy the CA certificate to the ZSS server. Then in the Zowe App Server configuration file, specify the location of the certificate, and add a parameter to specify that ZSS uses AT-TLS.

1. Enter the following command to copy the CA certificate to the correct location in UNIX System Services (USS):

```
cp "/*'[output_dataset_name]'" 'zlux-app-server/deploy/instance/ZLUX/
serverConfig/[ca_cert]'
```

1. In the `zlux-app-server/deploy/instance/ZLUX/serverConfig` directory, open the `zluxserver.json` file.
2. In the `node.https.certificateAuthorities` object, add the CA certificate file path, for example:

```
"certificateAuthorities": ["../deploy/instance/ZLUX/serverConfig/[ca_cert]"]
```

1. In the `agent.http` object add the key-value pair `"attls": true`, for example:

```

"agent": {
  "host": "localhost",
  "http": {
    "ipAddresses": ["127.0.0.1"],
    "port": 8542,
    "attls": true
  }
}
```

### **Installing additional ZSS instances**

After you install Zowe, you can install and configure additional instances of ZSS on the same z/OS server. You might want to do this to test different ZSS versions.

The following steps assume you have installed a Zowe runtime instance (which includes ZSS), and that you are installing a second runtime instance to install an additional ZSS.

- To stop the installed Zowe runtime, in SDSF enter the following command:

```
/C ZOWESVR
```

- Install a new Zowe runtime by following steps in [Obtaining and preparing the installation file](#) on page 54.

**Note:** In the `zowe-install.yaml` configuration file, specify ports that are not used by the first Zowe runtime.

- To restart the first Zowe runtime, in SDSF enter the following command:

```
/S ZOWESVR,SRVRPATH='$ZOWE_ROOT_DIR'
```

Where '`$ZOWE_ROOT_DIR`' is the first Zowe runtime root directory. By default the command starts the most recently installed runtime unless you specify the root directory of the runtime that you want to start.

- To specify a name for the new ZSS instance, follow these steps:

- Copy the PROCLIB member JCL named `ZWESIS01` that was installed with the new runtime.
- Rename the copy to uniquely identify it as the JCL that starts the new ZSS, for example `ZWESIS02`.
- Edit the JCL, and in the `NAME` parameter specify a unique name for the cross-memory server, for example:

```
//ZWESIS02 PROC NAME='ZWESIS_MYSRV', MEM=00, RGN=0M
```

Where `ZWESIS_MYSRV` is the unique name of the new ZSS.

- To start the new ZSS, in SDSF enter the following command:

```
/S ZWESIS02
```

- Make sure that the TSO user ID that runs the first ZSS started task also runs the new ZSS started task. The default ID is `IZUSVR`.
- In the new ZSS `zluxserver.json` configuration file, add a `"privilegedServerName"` parameter and specify the new ZSS name, for example:

```
"rootDir": ".../deploy",
"productDir": ".../deploy/product",
"siteDir": ".../deploy/site",
"instanceDir": ".../deploy/instance",
"groupsDir": ".../deploy/instance/groups",
"usersDir": ".../deploy/instance/users",
"pluginsDir": ".../deploy/instance/ZLUX/plugins",
"privilegedServerName": "ZWESIS_MYSRV",
"dataserviceAuthentication": { ... }
```

**Note:** The default location of `zluxserver.json` is `$ZOWE_ROOT_DIR/zlux-app-server/deploy/instance/ZLUX/serverConfig/zluxserver.json`

- Run the `zlux-build/deploy.sh` command redeploy and make the `zluxserver.json` change take effect.
- To start the new Zowe runtime, in SDSF enter the following command:

```
/S ZOWESVR
```

- To verify that the new cross-memory server is being used, check for the following messages in the `ZOWESVR` server job log:

```
ZIS status - Ok (name='ZWESIS_MYSRV', cmsRC=0, description='Ok',
clientVersion=2)
```

### Applying role-based access control to dataservices

To use role-based access control (RBAC) for Zowe dataservice endpoints, enable RBAC for Zowe, and then use a z/OS security product such as RACF to map roles and authorities to the endpoints.

After you configure RBAC, Zowe checks users' authority to access dataservices.

## How it works

Most Zowe functionality is available as dataservices. For example, Zowe Application Framework plug-in services provide the infrastructure for creating web applications, and application plug-in dataservices provide data and services from that application.

Plug-ins can also use [Configuration Dataservice](#) on page 206. These endpoints have scope at the product, site, instance, and user level, and the data is stored and retrieved by path name.

Dataservice endpoints are identified by URLs that are formatted like this:

```
/<product>/plugins/<plugin id>/services/<service>/<version>/<path>
```

For example:

```
/ZLUX/plugins/org.zowe.foo/services/baz/_current/users/fred
```

Where product is ZLUX, plugin id is org.zowe.foo, service is baz, version is \_current, and path is /users/fred.

To access dataservice endpoints when RBAC is enabled, users must have READ access to a corresponding System Authorization Facility (SAF) profile in the ZOWE class. SAF profiles have this format:

```
<product>. <instance id>. SVC. <pluginid_with_underscores>. <service>. <HTTP method>. <url with forward slashes '/' replaced by periods '.'>
```

For example, to issue a POST request to the dataservice endpoint documented above, users must have READ access to the following profile:

```
ZLUX.DEFAULT.SVC.ORG_ZOWE_FOO.BAZ.POST.USERS.FRED
```

Configuration endpoints have profiles with this format:

```
<product>. <instance id>. CFG. <pluginid_with_underscores>. <service>. <HTTP method>. <url with forward slashes '/' replaced by periods '.'>
```

For example, users must have READ access to the following profile to access the instance-scoped configuration element "files":

```
ZLUX.DEFAULT.CFG.ORG_ZOWE_FOO.GET.INSTANCE.FILES
```

## Enabling RBAC

By default, RBAC is disabled and all authenticated Zowe users can access all dataservices. To enable RBAC, follow these steps:

1. Open the Zowe Application Server configuration JSON file. In the default server instance, the configuration file is `/zlux-app-server/config/zluxserver.json`.
2. In the `dataserviceAuthentication` object, add `"rbac": true`.

## Creating generic authorization profiles

Some endpoints can generate an unlimited number of URLs. For example, an endpoint that performs a DELETE action on any file would generate a different URL for each file, and users can create an unlimited number of files. To apply RBAC to this type of endpoint you must create a generic profile, for example:

```
ZLUX.DEFAULT.SVC.ORG_ZOWE_FOO.BAZ.DELETE.**
```

You can create generic profile names using wildcards, such as asterisks (\*). For information on generic profile naming, see [IBM documentation](#).

## Configuring basic authorization

We recommend configuring the following basic authorization:

- To give administrators access to everything in Zowe, create a `ZLUX.**` profile and give them UPDATE access to it.

- To give non-administrators basic access to the site and product, create a ZLUX.\*.ORG\_ZOWE\_\* profile and give them READ access to it.
- To prevent non-administrators from configuring endpoints at the product and instance levels, create a ZLUX.DEFAULT.CFG.\*\* profile and do not give them access to it.
- To give non-administrators all access to user, create a ZLUX.DEFAULT.CFG.\*.\*.USER.\*\* profile and give them UPDATE access to it.

## Endpoint URL length limitations

SAF profiles cannot contain more than 246 characters. If the path section of an endpoint URL is long enough that the profile name exceeds the limit, the path is trimmed to only include elements that do not exceed the limit. To avoid this issue, we recommend that application developers maintain relatively short endpoint URL paths.

For information on endpoint URLs, see [Limiting the length of dataservice paths for RBAC](#) on page 196

## Enabling tracing

To obtain more information about how a server is working, you can enable tracing within the `zluxserver.json` file.

For example:

```
"logLevels": {
  "_zsf.routing": 0,
  "_zsf.install": 0,
  "_zss.traceLevel": 0,
  "_zss.fileTrace": 1
}
```

Specify the following settings inside the **logLevels** object.

All settings are optional.

## Zowe Application Server tracing

To determine how the Zowe Application Server (`zlux-app-server`) is working, you can assign a logging level to one or more of the pre-defined logger names in the `zluxserver.json` file.

The log prefix for the Zowe Application Server is `_zsf`, which is used by the server framework. (Applications and plug-ins that are attached to the server do not use the `_zsf` prefix.)

The following are the logger names that you can specify:

**\_zsf.bootstrap** Logging that pertains to the startup of the server.

**\_zsf.auth** Logging for network calls that must be checked for authentication and authorization purposes.

**\_zsf.static** Logging of the serving of static files (such as images) from an application's /web folder.

**\_zsf.child** Logging of child processes, if any.

**\_zsf.utils** Logging for miscellaneous utilities that the server relies upon.

**\_zsf.proxy** Logging for proxies that are set up in the server.

**\_zsf.install** Logging for the installation of plug-ins.

**\_zsf.apimpl** Logging for communication with the api mediation layer.

**\_zsf.routing** Logging for dispatching network requests to plug-in dataservices.

**\_zsf.network** Logging for the HTTPS server status (connection, ports, IP, and so on)

## Log levels

The log levels are:

- SEVERE = 0,

- WARNING = 1,
- INFO = 2,
- FINE = 3,
- FINER = 4,
- FINEST = 5

FINE, FINER, and FINEST are log levels for debugging, with increasing verbosity.

### **Enabling tracing for ZSS**

To increase logging for ZSS, you can assign a logging level (an integer value greater than zero) to one or more of the pre-defined logger names in the `zluxserver.json` file.

A higher value specifies greater verbosity.

The log prefix for ZSS is `_zss`. The following are the logger names that you can specify:

- \_zss.traceLevel:** Controls general server logging verbosity.
- \_zss.fileTrace:** Logs file serving behavior (if file serving is enabled).
- \_zss.socketTrace:** Logs general TCP Socket behavior.
- \_zss.httpParseTrace:** Logs parsing of HTTP messages.
- \_zss.httpDispatchTrace:** Logs dispatching of HTTP messages to dataservices.
- \_zss.httpHeadersTrace:** Logs parsing and setting of HTTP headers.
- \_zss.httpSocketTrace:** Logs TCP socket behavior for HTTP.
- \_zss.httpCloseConversationTrace:** Logs HTTP behavior for when an HTTP conversation ends.
- \_zss.httpAuthTrace:** Logs behavior for session security.

When you are finished specifying the settings, save the `zluxserver.json` file.

### **Zowe Application Framework logging**

The Zowe Application Framework log files contain processing messages and statistics. The log files are generated in the following default locations:

- Zowe Application Server: `zlux-app-server/log/nodeServer-yyyy-mm-dd-hh-mm.log`
- ZSS: `zlux-app-server/log/zssServer-yyyy-mm-dd-hh-mm.log`

The logs are timestamped in the format `yyyy-mm-dd-hh-mm` and older logs are deleted when a new log is created at server startup.

### **Controlling the logging location**

The log information is written to a file and to the screen. (On Windows, logs are written to a file only.)

#### ***ZLUX\_NODE\_LOG\_DIR and ZSS\_LOG\_DIR environment variables***

To control where the information is logged, use the environment variable `ZLUX_NODE_LOG_DIR`, for the Zowe Application Server, and `ZSS_LOG_DIR`, for ZSS. While these variables are intended to specify a directory, if you specify a location that is a file name, Zowe will write the logs to the specified file instead (for example: `/dev/null` to disable logging).

When you specify the environment variables `ZLUX_NODE_LOG_DIR` and `ZSS_LOG_DIR` and you specify directories rather than files, Zowe will timestamp the logs and delete the older logs that exceed the `ZLUX_NODE_LOGS_TO_KEEP` threshold.

#### ***ZLUX\_NODE\_LOG\_FILE and ZSS\_LOG\_FILE environment variables***

If you set the log file name for the Zowe Application Server by setting the `ZLUX_NODE_LOG_FILE` environment variable, or if you set the log file for ZSS by setting the `ZSS_LOG_FILE` environment variable, there will only be one log file, and it will be overwritten each time the server is launched.

**Note:** When you set the `ZLUX_NODE_LOG_FILE` or `ZSS_LOG_FILE` environment variables, Zowe will not override the log names, set a timestamp, or delete the logs.

If the directory or file cannot be created, the server will run (but it might not perform logging properly).

## Retaining logs

By default, the last five logs are retained. To specify a different number of logs to retain, set `ZLUX_NODE_LOGS_TO_KEEP` (Zowe Application Server logs) or `ZSS_LOGS_TO_KEEP` (ZSS logs) to the number of logs that you want to keep. For example, if you set `ZLUX_NODE_LOGS_TO_KEEP` to 10, when the eleventh log is created, the first log is deleted.

## Configuring Zowe CLI

This section explains how to define and verify your connection to the mainframe through the CLI. You can also configure CLI settings, such as the level of detail produced in logs and the location of the home directory on your computer.

**Note** The configuration for the CLI is stored on your computer in a directory such as `C:\Users\user01\.zowe`. The configuration includes log files, your profile information, and CLI plug-ins that are installed. When you troubleshoot an issue with the CLI, the log files in the imperative and zowe folders contain valuable information.

- [Defining Zowe CLI connection details](#) on page 88
- [Testing Zowe CLI connection to z/OSMF](#)
- [Setting Zowe CLI log levels](#) on page 93
- [Setting the Zowe CLI home directory](#) on page 93

### Defining Zowe CLI connection details

Zowe CLI has a *command option order of precedence* that lets you define arguments and options for commands in multiple ways (command-line, environment variables, and profiles). This provides flexibility when you issue commands and write automation scripts. This topic explains order of precedence and different methods for specifying your mainframe connection details.

- [Understanding command option order of precedence](#) on page 88
- [Creating Zowe CLI profiles](#) on page 89
- [Defining Environment Variables](#) on page 90
- [Integrating with API Mediation Layer](#) on page 91

### Understanding command option order of precedence

Before you issue commands, it is helpful to understand the command option order of precedence. The following is the order in which Zowe CLI *searches for* your command arguments and options when you issue a command:

1. Arguments and options that you specify directly on the command line.
2. Environment variables that you define in the computer's operating system. For more information, see [Defining Environment Variables](#) on page 90
3. User profiles that you create.
4. The default value for the argument or option.

The affect of the order is that if you omit an argument/option from the command line, Zowe CLI searches for an environment variable that contains a value that you defined for the argument/option. If Zowe CLI does not find a value for the argument/option in an environment variable, Zowe CLI searches your user profiles for the value that you defined for the option/argument. If Zowe CLI does not find a value for the argument/option in your profiles, Zowe CLI executes the command using the default value for the argument/option.

**Note:** If a required option or argument value is not located, you receive a syntax error message that states `Missing Positional Argument` or `Missing Option`.

## **Creating Zowe CLI profiles**

Profiles let you store configuration details for use on multiple commands. You can create a profile that contains your username, password, and connection details for a particular mainframe system, then reuse that profile to avoid typing it again on every command. Switch between profiles to quickly target different mainframe subsystems.

### **Notes:**

- Profile values are stored on your computer in plaintext in the C:\Users\<yourUsername>\.zowe\profiles folder.
- Profiles are **not** required to use the CLI. You can choose to specify all connection details in options on every command.
- For information about securely connecting to the server when you issue commands, see [Certificate security](#) on page 92.

### *Displaying profiles help*

To learn about the options available for creating zosmf profiles, issue the following command:

```
zowe profiles create zosmf-profile --help
```

### *Creating and Using a profile*

Create a profile, then use the profile when you issue a command. For example, substitute your connection details and issue the following command to create a profile with the name myprofile123:

```
zowe profiles create zosmf-profile myprofile123 --host host123 --port port123 --user ibmuser --password pass123
```

Issue the following command to list all data sets under the username ibmuser on the system specified in myprofile123:

```
zowe zos-files list data-set "ibmuser.*" --zosmf-profile myprofile123
```

After you create a profile, you can verify that it can communicate with z/OSMF. For more information, see [Testing Connection to z/OSMF](#).

### *Creating a profile that accesses API Mediation Layer*

You can create profiles that access either an exposed API or API Mediation Layer (API ML) in the following ways:

- When you create a profile, specify the host and port of the API that you want to access. When you only provide the host and port configuration, Zowe CLI connects to the exposed endpoints of a specific API.
- When you create a profile, specify the host, port, and the base path of API ML instance that you want to access. Using the base path to API ML, Zowe CLI routes your requests to an appropriate instance of the API based on the system load and the available instances of the API.

For more information, see [Integrating with API Mediation Layer](#) on page 91.

### **Example:**

The following example illustrates the command to create a profile that connects to z/OSMF through API ML with the base path my/api/layer:

```
zowe profiles create zosmf myprofile -H <myhost> -P <mypor> -u <myuser> --pw <mypass> --base-path <my/api/layer>
```

After you create a profile, verify that it can communicate with z/OSMF. For more information, see [Testing Zowe CLI connection to z/OSMF](#).

## Defining Environment Variables

You can define environment variables in your environment to execute commands more efficiently. You can store a value, such as your password, in an environment variable, then issue commands without specifying your password every time. The term environment refers to your operating system, but it can also refer to an automation server, such as Jenkins or a Docker container. In this section we explain how to transform arguments and options from Zowe CLI commands into environment variables and define them with a value.

- **Assigning an environment variable for a value that is commonly used.**

For example, you might want to specify your mainframe user name as an environment variable on your computer. When you issue a command and omit the `--username` argument, Zowe CLI automatically uses the value that you defined in the environment variable. You can now issue a command or create any profile type without specifying your user name repeatedly.

- **Overriding a value that is used in existing profiles.**

For example, you might want to override a value that you previously set on multiple profiles to avoid recreating each profile. This reduces the number of profiles that you need to maintain and lets you avoid specifying every option on command line for one-off commands.

- **Specifying environment variables in a Jenkins environment (or other automation server) to store credentials securely.**

You can set values in Jenkins environment variables for use in scripts that run in your CI/CD pipeline. You can define Jenkins environment variables in the same manner that you can on your computer. You can also define sensitive information in the Jenkins secure credential store. For example, you might need to define your mainframe password in the secure credential store so that it is not available in plain text.

### *Transforming arguments/options to environment variable format*

Transform the option/argument into the correct format for a Zowe CLI environment variable, then define values to the new variable. The following rules apply to this transformation:

- Prefix environment variables with `ZOWE_OPT_`
- Convert lowercase letters in arguments/options to uppercase letters
- Convert hyphens in arguments/options to underscores

**Tip:** See your operating system documentation for information about how to set and get environment variables. The procedure for setting environment variables varies between Windows, Mac, and various versions of Linux operating systems.

### **Examples:**

The following table shows command line options that you might want to transform and the resulting environment variable to which you should define the value. Use the appropriate procedure for your operating system to define the variables.

Command Option	Environment Variable	Use Case
<code>--user</code>	<code>ZOWE_OPT_USER</code>	Define your mainframe user name to an environment variable to avoid specifying it on all commands or profiles.
<code>--reject-unauthorized</code>	<code>ZOWE_OPT_REJECT_UNAUTHORIZED</code>	Define a value of <code>true</code> to the <code>--reject-unauthorized</code> flag when you always require the flag and do not want to specify it on all commands or profiles.

### *Setting environment variables in an automation server*

You can use environment variables in an automation server, such as Jenkins, to write more efficient scripts and make use of secure credential storage.

You can either set environment variables using the SET command within your scripts, or navigate to **Manage Jenkins** > **Configure System** > **Global Properties** and define an environment variable in the Jenkins GUI. For example:

Name	TEST_VARIABLE
Value	test-value

### *Using secure credential storage*

Automation tools such as Jenkins automation server usually provide a mechanism for securely storing configuration (for example, credentials). In Jenkins, you can use `withCredentials` to expose credentials as an environment variable (ENV) or Groovy variable.

**Note:** For more information about using this feature in Jenkins, see [Credentials Binding Plugin](#) in the Jenkins documentation.

### **Integrating with API Mediation Layer**

The API Mediation Layer provides a single point of access to a defined set of microservices. The API Mediation Layer provides cloud-like features such as high-availability, scalability, dynamic API discovery, consistent security, a single sign-on experience, and API documentation.

When Zowe CLI executes commands that connect to a service through the API Mediation Layer, the layer routes the command execution requests to an appropriate instance of the API. The routing path is based on the system load and available instances of the API.

Use the `--base-path` option on commands to let all of your Zowe CLI core command groups (excludes plug-in groups) access REST APIs through an API Mediation Layer. To access API Mediation Layers, you specify the base path, or URL, to the API gateway as you execute your commands. Optionally, you can define the base path URL as an environment variable or in a profile that you create.

#### **Examples:**

The following example illustrates the base path for a REST request that is not connecting through an API Mediation Layer to one system where an instance of z/OSMF is running:

```
https://mymainframehost:port/zosmf/restjobs/jobs
```

The following example illustrates the base path (named `api/v1/zosmf1`) for a REST request to an API mediation layer:

```
https://myapilayerhost:port/api/v1/zosmf1/zosmf/restjobs/jobs
```

The following example illustrates the command to verify that you can connect to z/OSMF through an API Mediation Layer that contains the base path `my/api/layer`:

```
zowe zosmf check status -H <myhost> -P <myport> -u <myuser> --pw <mypass> --base-path <my/api/layer>
```

## More Information:

- [Zowe overview](#) on page 8
- [Creating a profile that accesses API Mediation Layer](#) on page 89

## Testing Zowe CLI connection to z/OSMF

You can issue a command at any time to receive diagnostic information from the server and confirm that Zowe CLI can communicate with z/OSMF or other mainframe APIs.

**Important!** By default, the server certificate is verified against a list of Certificate Authorities (CAs) trusted by Mozilla. This handshake ensures that the CLI can trust the server. You can append the flag `--ru false` to any of the following commands to bypass the certificate verification against CAs. If you use the `--ru false` flag, ensure that you understand the potential security risks of bypassing the certificate requirement at your site. For the most secure environment, system administrators configure a server keyring with a server certificate signed by a Certificate Authority (CA). For more information, see [Certificate security](#) on page 92.

### Without a Profile

Verify that your CLI instance can communicate with z/OSMF.

```
zowe zosmf check status --host <host> --port <port> --user <username> --pass
<password>
```

### Default profile

After you [Creating Zowe CLI profiles](#) on page 89, verify that you can use your *default profile* to communicate with z/OSMF:

```
zowe zosmf check status
```

### Specific profile

After you [Creating Zowe CLI profiles](#) on page 89, verify that you can use a *specific profile* to communicate with z/OSMF:

```
zowe zosmf check status --zosmf-profile <profile_name>
```

The commands return a success or failure message and display information about your z/OSMF server, such as the z/OSMF version number. Report any failure to your systems administrator and use the information for diagnostic purposes.

## Certificate security

Certificates authorize communication between a server and client, such as z/OSMF and Zowe CLI. The client CLI must "trust" the server to successfully issue commands. Use one of the following methods to let the CLI communicate with the server:

- [Configure certificates signed by a Certificate Authority \(CA\)](#) on page 92
- [Extend trusted certificates on client](#) on page 93
- [Bypass certificate requirement with CLI flag](#) on page 93

### Configure certificates signed by a Certificate Authority (CA)

System Administrators can configure the server with a certificate signed by a Certificate Authority (CA) trusted by Mozilla. When a CA trusted by Mozilla exists in the certificate chain, the CLI automatically recognizes the server and authorizes the connection.

### Related information:

- [Using certificates with z/OS client/server applications](#) in the IBM Knowledge Center.
- [Configuring the z/OSMF key ring and certificate](#) in the IBM Knowledge Center.
- [Certificate management in Zowe API Mediation Layer](#)

- [Mozilla Included CA Certificate List](#)

### Extend trusted certificates on client

If your organization uses self-signed certificates in the certificate chain (rather than a CA trusted by Mozilla), you can download the certificate to your computer add it to the local list of trusted certificates. Provide the certificate locally using the `NODE_EXTRA_CERTS` environment variable. Organizations might want to configure all client computers to trust the self-signed certificate.

[This blog post](#) outlines the process for using environment variables to trust the self-signed certificate.

### Bypass certificate requirement with CLI flag

If you do not have server certificates configured at your site, or you want to trust a known self-signed certificate, you can append the `--reject-unauthorized false` flag to your CLI commands. Setting the `--reject-unauthorized` flag to `false` rejects self-signed certificates and essentially bypasses the certificate requirement.

**Important!** Understand the security implications of accepting self-signed certificates at your site before you use this command.

#### Example:

```
zowe zosmf check status --host <host> --port <port> --user <username> --pass
<password> --reject-unauthorized false
```

### Setting Zowe CLI log levels

You can set the log level to adjust the level of detail that is written to log files:

**Important!** Setting the log level to TRACE or ALL might result in "sensitive" data being logged. For example, command line arguments will be logged when TRACE is set.

Environment Variable	Description	Values	Default
<code>ZOWE\_APP\_LOG\_LEVEL</code>	Zowe CLI logging level	Log4JS log levels (OFF, TRACE, DEBUG, INFO, WARN, ERROR, FATAL)	DEBUG
<code>ZOWE\_IMPERATIVE\_LOG\_LEVEL</code>	Imperative CLI Framework logging level	Log4JS log levels (OFF, TRACE, DEBUG, INFO, WARN, ERROR, FATAL)	DEBUG

### Setting the Zowe CLI home directory

You can set the location on your computer where Zowe CLI creates the `.zowe` directory, which contains log files, profiles, and plug-ins for the product:

Environment Variable	Description	Values	Default
<code>ZOWE\_CLI\_HOME</code>	Zowe CLI home directory location	Any valid path on your computer	Your computer default home directory

## Using Zowe

---

### Getting started tutorial

[ ]

#### Learning objectives

This tutorial walks you through the Zowe interfaces, including the Zowe Desktop and Zowe CLI, with several simple tasks to help you get familiar with Zowe.

- If you are new to Zowe, start with this tutorial to explore the base Zowe features and functions.
- If you are already familiar with Zowe interfaces and capabilities, you might want to visit the **Extending** section which guides you to extend Zowe by creating your own APIs or applications.
  - [Onboarding Overview](#) on page 130
  - [Overview](#) on page 189
  - [Developing for Zowe CLI](#) on page 176

By the end of the session, you'll know how to:

- Log in to the Zowe Desktop
- Query jobs with filters and view the related status by using the JES Explorer
- View jobs by using TN3270 in the Zowe Desktop
- View and edit data sets by using the MVS Explorer
- Edit a data set and upload it to the mainframe by using Zowe Command-Line Interface (CLI)

As an introductory scenario, no previous knowledge of Zowe is needed.

### **Estimated time**

This tutorial guides you through the steps in roughly 20 minutes. If you explore other concepts related to this tutorial, it can take longer to complete.

### **Prerequisites and assumptions**

Before you begin, it is assumed that you have already successfully installed Zowe. You are ready to launch Zowe Desktop and Zowe CLI.

For information about how to install Zowe, see [Planning the installation](#) on page 30.

### **Important!**

- In this tutorial, the following parameters are used as an example. Replace them with your own settings when you follow the tutorial in your environment.
  - URL to access the Zowe Desktop: `https://s0w1:8544/ZLUX/plugins/org.zowe.zlux.bootstrap/web/index.html`
  - Mainframe credentials:
    - Username: `ibmuser`
    - Password: `sys1`
- It is assumed that you perform the tasks in a Windows environment and that you have Visual Studio Code (VS Code) installed.

### **Logging in to the Zowe Desktop**

Access and navigate the Zowe Desktop to view the Zowe applications. In this tutorial, you will use the Firefox browser to log in to the Zowe Desktop.

The URL to access the Zowe Desktop is `https://myhost:httpsPort/ZLUX/plugins/org.zowe.zlux.bootstrap/web/index.html` in your own environment, where:

- *myHost* is the host on which you are running the Zowe Application Server.
- *httpsPort* is the value that was assigned to *node.https.port* in *zluxserver.json*. For example, if you run the Zowe Application Server on host *myhost* and the value that is assigned to *node.https.port* in *zluxserver.json* is 12345, you would specify `https://myhost:12345/ZLUX/plugins/org.zowe.zlux.bootstrap/web/index.html`.

### **Follow these steps:**


1. In the address field, enter the URL to access the Zowe Desktop. In this tutorial, the following URL is used as an example:

<https://s0w1:8544/ZLUX/plugins/org.zowe.zlux.bootstrap/web/index.html>



2. On the login page of the Zowe Desktop, enter your mainframe credentials. In this tutorial, the following ID is used as an example:
  - Username: ibmuser
  - Password: sys1
3. Press Enter.

Upon authentication of your user name and password, the Zowe Desktop opens. Several applications are pinned to the taskbar. Click the Start menu to see a list of applications that are installed by default. You can pin other applications to the taskbar by right-clicking the application icon and selecting **Pin to taskbar**.



Next, you will use the JES Explorer application to query the jobs with filters and view the related status.

### Querying JES jobs and viewing related status in JES Explorer

Use the Job Entry Subsystem (JES) Explorer to query JES jobs with filters and view the related status.

**Follow these steps:**

1. Click the Start menu in the Zowe Desktop.



2. Scroll down to find the JES Explorer icon and click to open it. The JES Explorer is displayed. If prompted to provide credentials for authentication, enter your mainframe credentials.

3. Click the **Job Filters** column to expand the filter criteria. You can filter jobs on various criteria by Owner, Prefix, Job ID, and Status. By default, the jobs are filtered by Owner. In this tutorial, the example owner is IBMUSER.

The screenshot shows a 'Job Filters' dialog box. At the top, there are two input fields: 'Owner= IBMUSER' and 'Prefix= \*'. Below this, the 'Job Filters' section is expanded, showing two rows of filters:

Owner	Prefix
IBMUSER	*

Below this, another row of filters is shown:

Job ID	Status
*	*

At the bottom of the dialog box are two buttons: 'APPLY' (dark blue) and 'RESET' (light blue).

4. To query the jobs starting with SDSF and in an active status, clear the field of **Owner**, then enter SDSF\* in the **Prefix** field and select **ACTIVE** from the **Status** drop-down list, and click **APPLY**.

**Note:** Wildcard is supported. Valid wildcard characters are asterisk (\*), percent sign (%), and question mark (?).

The screenshot shows the same 'Job Filters' dialog box as before, but with different filter settings. The 'Owner' field now contains 'IBMUSER' (with the cursor inside). The 'Prefix' field contains 'SDSF\*'. The 'Status' dropdown menu is open, showing options like 'ACTIVE', 'INACTIVE', and 'PENDING'. The 'Job ID' field contains '\*'.

- From the job filter results, click the job named **SDSF**. The data sets for this job are listed.



- Click **JESJCL** to open the JESJCL data set. The contents of this data set are displayed. You can also select other data sets to view their contents.

**Tip:** You can hover over the text in purple color to display a hover help window.

A screenshot of the JES Explorer interface showing a tooltip for the word 'JOB' in the JCL code. The tooltip content is: 'The JOB Operation Field' and 'The first control statement. Marks the beginning of a job; This assigns a name to the job.' The JCL code itself includes lines like //SDSF, //STARTING, and various JOB and XX\* entries.

```

1 //SDSF      JOB MSGLEVEL=1
2 //STARTING   JOB
3 XXDSF       XX
4          XX*   The JOB Operation Field
5          XX*   The first control statement. Marks the beginning of a job;
6          XX*   This assigns a name to the job.
7          XX*   The SDSFPARM DD Statement is optional. If it is not
8          XX*   present, SYS1.PARMLIB will be assumed.
9 XXDSF       CALL PGM=ISPFHELP,REGION=32M,TIME=1440,PARM=-M(EM),OR
10         XX*
11         XX*   The SDSFPARM DD Statement is optional. If it is not
12         XX*   present, SYS1.PARMLIB will be assumed.

```

You used the JES Explorer to query the JES jobs with filters and viewed the related steps, files, and status.

Close the JES Explorer window. Next, you'll use the TN3270 application plug-in in the Zowe Desktop to view the same job that you viewed in this task.

### Using TN3270 in Zowe Desktop to view the job

Use the TN3270 application plug-in to view the same job that you filtered out in the previous task.

Zowe not only provides new modern applications to interact with z/OS®, but also integrates the traditional TN3270 tool that you are familiar with. This TN3270 application plug-in provides a 3270 connection to the mainframe on which the Zowe Application Server runs.

**Follow these steps:**

- From the taskbar at the bottom of the Zowe Desktop, click the TN3270 icon to open the TN3270 application plugin.



The TN3270 panel is displayed, which offers selections to access various mainframe services.

A screenshot of the TN3270 application window. The title bar says "TN3270". The window displays a mainframe session with the following text:

```
z/OS V2R3 LVLI PUT1803/RSU1803          IP Address = 127.0.0.1  
VTAM Terminal = SC0TCP04  
  
Application Developer System  
  
zzzzzz // 0000000 SSSSS  
zzzzzz // 00 00 SS  
zzzzzz // 00 00 SS  
zzzzzz // 00 00 SSSS  
zzzzzz // 00 00 SS  
zzzzzz // 0000000 SSSSS  
  
System Customization - ADCD.Z23B.*  
  
==> Enter "LOGON" followed by the TSO userid. Example "LOGON IBMUSER" or  
==> Enter L followed by the APPLID  
==> Examples: "L TSO", "L CICSTS53", "L CICSTS54", "L IMS14", "L IMS15"
```

The bottom of the window shows a status bar with "MA A" on the left and "24/1" on the right.


2. Enter the following command and press Enter to log on to TSO:

```
LOGON ibmuser
```

The terminal window shows the following text:

```
X - □ TN3270  
z/OS V2R3 LVL1 PUT1803/RSUI803 IP Address = 127.0.0.1  
VTAM Terminal = SC0TCP02  
Application Developer System  
zzzzzz // 0000000 SSSSS  
zzzzzz // 00 00 SS  
zz // 00 00 SSSS  
zz // 00 00 SS  
zzzzzz // 0000000 SSSS  
System Customization - ADCD.Z238.*  
==> Enter "LOGON" followed by the TSO userid. Example "LOGON IBMUSER" or  
==> Enter L followed by the APPLID  
==> Examples: "L TSO", "L CICSTS53", "L CICSTS54", "L IMS14", "L IMS15"  
LOGON ibmuser  
MA A 24/14
```

3. On the TSO/E LOGON panel, enter the password sys1 in the **Password** field and press Enter.



You successfully log on to TSO.

- When you see the following screen, press Enter. The **ISPF Primary Option Menu** is displayed.


The screenshot shows a terminal window titled "TN3270". The window displays several system messages at the top, including logon information and broadcast message notices. Below these messages is a table showing user authentication details. The table has three columns: "USERID", "PASSWORD", and "COMMENT". The data in the table is as follows:

USERID	PASSWORD	COMMENT
IBMUSER	- SYS1/IBMUSER	FULL AUTHORITY
ADCDMST	- ADCDMST	FULL AUTHORITY
ADCD A THRU ADCDZ	- TEST	LIMITED AUTHORITY(NO OMVS)*
OPEN1 THRU OPEN3	- SYS1	UID(0) (NO TSO)

At the bottom of the window, the text "ISPF \*\*\*" is visible. The bottom status bar shows the characters "MA" and "A" on the left, and the page number "23/10" on the right.

5. Access SDSF to view output from a job. To do this,

- a. Type M at the **Option** prompt and press Enter.




- b. Type 5 and press Enter.




MA A

22/15

- To view the jobs in an active status, type DA at the command input prompt and press Enter. The jobs that are running are displayed.



7. To query the jobs that start with SDSF, type prefix sdsf; owner \* at the command input prompt and press Enter.




The screenshot shows a TN3270 terminal window titled "TN3270". The menu bar includes "Display", "Filter", "View", "Print", "Options", "Search", and "Help". The main area displays a list of jobs. The command input field at the bottom left contains "COMMAND INPUT ==> prefix sdsf; owner \*". The F12 key is highlighted in red. The terminal window has a standard Windows-style border with close, minimize, and maximize buttons.

NP	JOBNAME	StepName	ProcStep	JobID	Owner	C	Pos	DP	Real	Paging	SIO
	IZUANG1	IZUANG1	STEP1	STC00033	IZUSVR	LO	FF	404	0.00	0.00	
	ZOWESVR3	STEP1		STC00039	IZUSVR	LO	FF	455	0.00	0.00	
	ZOWESVR	ZOWESTEP		STC00037	IZUSVR	LO	FF	324	0.00	0.00	
	ZOWESVR8	STEP1		STC00040	IZUSVR	LO	FF	2457	0.00	0.00	
	ZOWESVR1	STEP1		STC00038	IZUSVR	LO	FF	415	0.00	0.00	
	IZUSVR1	IZUSVR1	ZOSMF	STC00034	IZUSVR	IN	C8	113T	0.00	0.00	
	ZWESIS01	ZWESIS01	ZWESIS01	STC00036	IZUSVR	NS	C8	516	0.00	0.00	
	ZOWESVR6	*OMVSEX		STC00041	IZUSVR	IN	F6	64T	0.00	0.00	
	ZOWESVR9	*OMVSEX		STC00042	IZUSVR	IN	F6	71T	0.00	0.00	
	ZOWESVR9	*OMVSEX		STC00043	IZUSVR	IN	F6	85T	0.00	0.00	
	ZOWESVR7	STEP1		STC00044	IZUSVR	IN	F6	31T	0.00	0.00	
	ZOWESVR3	*OMVSEX		STC00045	IZUSVR	IN	F6	62T	0.00	0.00	
	ZOWESVR6	*OMVSEX		STC00046	IZUSVR	IN	F6	63T	0.00	0.00	
	ZOWESVR8	*OMVSEX		STC00047	IZUSVR	LO	FF	2354	0.00	0.00	
	ZOWESVR7	*OMVSEX		STC00048	IZUSVR	LO	FF	24T	0.00	0.00	
	ZOWESVR5	STEP1		STC00049	IZUSVR	LO	FF	2444	0.00	0.00	

COMMAND INPUT ==> **prefix sdsf; owner \*** SCROLL ==> PAGE

F1=HELP F2=SPL11 F3=END F4=RETURN F5=IFIND F6=BOOK  
 F7=UP F8=DOWN F9=SWAP F10=LEFT F11=RIGHT F12=RETRIEVE

- To view the contents of the job, type S next to the job name SDSF and press Enter.



The contents of the job are displayed.

```

TN3270

Display Filter View Print Options Search Help
SDSF OUTPUT DISPLAY SDSF      STC00018  DSID      2 LINE 0      COLUMNS 02- 81
COMMAND INPUT ==>          SCROLL ==> PAGE
***** TOP OF DATA *****
J E S 2 J O B L O G -- S Y S T E M S 0 W 1 -- N O

07.22.31 STC00018 ---- MONDAY,    01 APR 2019 ----
07.22.31 STC00018 IEF695I START SDSF      WITH JOBNAMESDSF      IS ASSIGNED TO U
07.22.31 STC00018 $HASP373 SDSF      STARTED
07.22.32 STC00018 ISF724I SDSF level HQX77B0 initialization complete for server
07.22.33 STC00018 IEE252I MEMBER ISFPRM00 FOUND IN ACD.Z23B.PARMLIB
07.22.33 STC00018 ISF739I SDSF parameters being read from member ISFPRM00 of da
07.22.46 STC00018 ISF728I SDSF parameters have been activated.
07.22.47 STC00018 ISF450I Server SDSF starting SDSFAUX.
  1 //SDSF      JOB MSGLEVEL=1
  2 //STARTING EXEC SDSF
  3 XXSDSF      PROC M=00,          /* Suffix for ISFPRMxx */
     XX           P='LC(A)'        /* USE SySout class A for SDSFLOG */
     XX*
     XX*
     XX*      This is a Sample procedure to Start the SDSF Server.
F1=HELP      F2=SPLIT      F3=END      F4=RETURN      F5=IFIND      F6=BOOK
F7=UP        F8=DOWN       F9=SWAP      F10=LEFT       F11=RIGHT      F12=RETRIEVE

```

MA A 4 /21


Close the TN3270 window. In the next step, you will use the MVS Explorer to make changes to a data set.

### Editing a data set in MVS Explorer


Use the MVS Explorer to create and edit a data set member and save the changes. The MVS Explorer view lets you to browse the MVS file system by creating filters against data set names.

#### Follow these steps:

1. Click the Start menu on Zowe Desktop.
2. Scroll down to find the MVS Explorer icon and pin this application to the desktop for later use.
3. Click the **MVS Explorer** icon on the task bar. The MVS Explorer opens. The **Filter** field is pre-filled with the user name. In this tutorial, the filter string is **IBMUSER**. All the data sets matching this filter are displayed. You can expand a data set name and see the members in it.




4. Enter USER.Z23B.PARMLIB in the **Filter** field to locate this data set and then click to expand it. Ensure that there is no extra space before the data set member name that you enter.
5. Right-click the USER.Z23B.PARMLIB data set and select **New Dataset Member**.



6. Enter **ZTRIAL** as the data set member name and click **OK** to create the data set member.




7. Click the data set member you just created and edit it by adding a new sentence, for example, **First change to Zowe zTrial**.



8. Click **SAVE** to save your edits.

The following message **Save success for USER.Z23B.PARMLIB(ZTRIAL)** pops up quickly at the bottom of the MVS Explorer window, which indicates that your edits are successfully saved.



Leave the MVS Explorer window open; we will look at the contents of the data set in a later step. If asked to leave the page, choose **Stay on Page**. Next, you will use Zowe CLI to view and add another change to the same data set.

### Using the Zowe CLI to edit a data set

Use Zowe CLI to download the same data set that you edited by using MVS Explorer in the previous step, edit it, and upload the changes to the mainframe.

Zowe CLI is a command-line interface that lets you interact with z/OS from various other platforms, such as cloud or distributed systems, to submit jobs, issue TSO and z/OS console commands, integrate z/OS actions into scripts, produce responses as JSON documents, and more. With this extensible and scriptable interface, you can tie in mainframes to distributed DevOps pipelines and build automation.

## Follow these steps:

1. Start the Command Prompt or a terminal in your local desktop. In this tutorial, it's assumed that you use Windows Command Prompt.



2. (Optional) Issue the following command to view the top-level help descriptions.

```
zowe --help
```

**Tip:** The command zowe initiates the product on a command line. All Zowe CLI commands begin with zowe.

3. To list the data sets of USER, enter the following command:

```
zowe zos-files list data-set "USER.*"
```

The following data sets are listed.

```
C:\Users\Administrator>zowe zos-files list data-set "USER.*"
USER.ADCD.SMPLELIST
USER.Z23B.CIDTABL
USER.Z23B.CLIST
USER.Z23B.HELP
USER.Z23B.ISPMLIB
USER.Z23B.ISPMLIB
USER.Z23B.ISPPLIB
USER.Z23B.ISPSLIB
USER.Z23B.ISPTLIB
USER.Z23B.LINKLIB
USER.Z23B.LOADLIB
USER.Z23B.LPALIB
USER.Z23B.MSGENU
USER.Z23B.PARMLIB
USER.Z23B.PROCLIB
USER.Z23B.STCJOBS
USER.Z23B.SVSEEXEC
USER.Z23B.TCPPARMS
USER.Z23B.UTAMLIB
USER.Z23B.UTAMLST
```

4. To download all the data set members of USER.Z23B.PARMLIB, enter the following command:

```
zowe zos-files download all-members "USER.Z23B.PARMLIB"
```

The message "Data set downloaded successfully" indicates that the data set members are downloaded. A file hierarchy is added to your current directory.

```
C:\Users\Administrator>zowe zos-files download all-members "USER.Z23B.PARMLIB"
Data set downloaded successfully.
Destination: user/z23b/parmlib
```


5. To open the data set member named ZTRIAL in Visual Studio Code, issue the following command against the same directory where you issued the download command:

```
code USER/Z23B/PARMLIB/ZTRIAL.txt
```

Alternatively, navigate to the PARMLIB directory and issue code ZTRIAL.txt.

The file opens in a text editor (in this example, VS Code). You will see the changes you made in the previous step by using the MVS Explorer.

6. Add the text Second change to Zowe zTrial to the file and then use Ctrl+S to save your edits.



7. Open the Command Prompt again and upload your changes to the mainframe by entering the following command:

```
zowe zos-files upload file-to-data-set USER/Z23B/PARMLIB/ZTRIAL.txt
"USER.Z23B.PARMLIB"
```

The following message indicates that you successfully uploaded your changes:

```
C:\Users\Administrator>zowe zos-files upload file-to-data-set USER/Z23B/PARMLIB/
ZTRIAL.txt "USER.Z23B.PARMLIB"
success: true
from: C:\Users\Administrator\USER\Z23B\PARMLIB\ZTRIAL.txt
to: USER.Z23B.PARMLIB(ZTRIAL)

file_to_upload: 1
success: 1
error: 0
skipped: 0

Data set uploaded successfully.
```

Congratulations! You used Zowe CLI to edit a data set member and upload the changes to mainframe.


Close the Command Prompt window. In the next step, you will open the MVS Explorer again to view the updates that you made to the data set in this procedure.

### **Viewing the data set changes in MVS Explorer**

Use the MVS Explorer to view the data set changes from the previous step.

#### **Procedure**

1. Return to the Zowe Desktop and open the MVS Explorer application.
2. Locate the data set member **USER.Z23B.PARMLIB > ZTRIAL** and click the refresh icon. You will see the changes you just made by using Zowe CLI.



Congratulations! You explored several applications on the Zowe Desktop and learned how to work with them.

#### **Next steps**

Here are some next steps.

#### **Go deeper with Zowe**

In roughly 20 minutes, you used the MVS™ Explorer and Zowe CLI to edit the same data set member, and used the JES Explorer and TN3270 to query the same JES job with filters, all without leaving Zowe. Now that you're familiar with Zowe components, you can continue to learn more about the project. Zowe also offers many more plug-ins for both Zowe Desktop and Zowe CLI.

For more information, see the [Using the Zowe Desktop](#) on page 112.

For a complete list of available CLI commands, explore the Zowe CLI [Command Reference Guide](#).

#### **Try the Extending Zowe scenarios**

You can add your own application plug-ins to Zowe. See how easy it is to extend Zowe to create your own APIs and applications by reading the [Onboarding Overview](#) on page 130 section.

#### **Give feedback**

Did you find this tutorial useful? You can tell us what you think about this tutorial via an [online survey](#).

If you encounter any problems or have an idea for improving this tutorial, you can create a GitHub issue [here](#).

## Using the Zowe Desktop

You can use the Zowe Application Framework to create application plug-ins for the Zowe Desktop. For more information, see [Overview](#) on page 189.

### Navigating the Zowe Desktop

From the Zowe Desktop, you can access Zowe applications.

### Accessing the Zowe Desktop

From a supported browser, open the Zowe Desktop at `https://myhost:httpsPort/ZLUX/plugins/org.zowe.zlux.bootstrap/web/index.html`

where:

- *myHost* is the host on which you are running the Zowe Application Server.
- *httpsPort* is the value that was assigned to `node.https.port` in `zluxserver.json`. For example, if you run the Zowe Application Server on host *myhost* and the value that is assigned to `node.https.port` in `zluxserver.json` is 12345, you would specify `https://myhost:12345/ZLUX/plugins/org.zowe.zlux.bootstrap/web/index.html`.

### Logging in and out of the Zowe Desktop

1. To log in, enter your mainframe credentials in the **Username** and **Password** fields.
2. Press Enter. Upon authentication of your user name and password, the desktop opens.

To log out, click the the avatar in the lower right corner and click **Sign Out**.

### Pinning applications to the task bar

1. Click the Start menu.
2. Locate the application you want to pin.
3. Right-click the on the application icon and select **Pin to taskbar**.

### Changing the desktop language

Use the Languages setting in the personalization panel to change the desktop language. After you change the language and restart Zowe, desktop menus and text display in the specified language. Applications that support the specified desktop language also display in that language.

1. Click the personalization icon in the lower right corner.
2. Click **Languages**.
3. In the **Languages** dialog, click a language, and then click **Apply**.
4. When you are prompted, restart Zowe.

### Zowe Desktop application plug-ins

Application plug-ins are applications that you can use to access the mainframe and to perform various tasks. Developers can create application plug-ins using a sample application as a guide. The following application plug-ins are installed by default:

#### Hello World Sample

The Hello World sample application plug-in for developers demonstrates how to create a dataservice and how to create an application plug-in using Angular.

#### IFrame Sample

The IFrame sample application plug-in for developers demonstrates how to embed pre-made webpages within the desktop as an application and how an application can request an action of another application (see the source code for more information).

## **z/OS Subsystems**

The z/OS Subsystems plug-in helps you find information about the important services on the mainframe, such as CICS, Db2, and IMS.

### **TN3270**

This TN3270 plug-in provides a 3270 connection to the mainframe on which the Zowe Application Server runs.

### **VT Terminal**

The VT Terminal plug-in provides a connection to UNIX System Services and UNIX.

### **API Catalog**

The API Catalog plug-in lets you view API services that have been discovered by the API Mediation Layer. For more information about the API Mediation Layer, Discovery Service, and API Catalog, see [Zowe overview](#) on page 8.

### **Editor**

With the Zowe Editor you can create and edit files on the system that Zowe serves.

### **Workflows**

From the Workflows application plug-in you can create, manage, and use z/OSMF workflows to manage your system.

### **JES Explorer**

Use this application to query JES jobs with filters, and view the related steps, files, and status. You can also purge jobs from this view.

### **MVS Explorer**

Use this application to browse the MVS™ file system by using a high-level qualifier filter. With the MVS Explorer, you can complete the following tasks:

- List the members of partitioned data sets.
- Create new data sets using attributes or the attributes of an existing data set ("Allocate Like").
- Submit data sets that contain JCL to Job Entry Subsystem (JES).
- Edit sequential data sets and partitioned data set members with basic syntax highlighting and content assist for JCL and REXX.
- Conduct basic validation of record length when editing JCL.
- Delete data sets and members.
- Open data sets in full screen editor mode, which gives you a fully qualified link to that file. The link is then reusable for example in help tickets.

### **USS Explorer**

Use this application to browse the USS files by using a path. With the USS Explorer, you can complete the following tasks:

- List files and folders.
- Create new files and folders.
- Edit files with basic syntax highlighting and content assist for JCL and REXX.
- Delete files and folders.

### **Using the Editor**

With the Zowe Editor, you can create and edit the many types of files.

### **Specifying a language server**

To specify a language server, complete these steps:

1. From the **Language Server** menu, select **URL\***.
2. From the **Language Server Setting, Put your config here** area, paste your configuration.

3. Ensure that the **Enable Language Server** check box is selected.
4. Click **Save**.

### **Specifying a language**

From the **Language** menu, select the language you want to use.

### **Opening a directory**

To open a directory on the system, complete these steps:

1. From the **File** menu, select **Open Directory**. (Alternatively, you can click **Open Directory** in the File Explorer.)
2. From the **Open Directory, Input Your Directory** field, type the name of the directory you want to open. For example: /u/zs1234
3. Click **Open**.

The File Explorer on the left side of the window lists the folders and files in the specified directory. Clicking on a folder expands the tree. Clicking on a file opens a tab that displays the file contents.

### **Creating a new file**

To create a new file, complete these steps:

1. From the **File** menu, select **New File**. The **New File** tab opens.
2. From the **New File, File Name** field, type the name of the file.
3. Click **Create**.

### **Saving a file**

To save a file, click **File > Save**.

**Note:** To save all files, click **File > Save All** (or Ctrl+S).

### **Using the Workflows application plug-in**

The Workflows application plug-in is available from the Zowe Desktop Start menu. To launch Workflows, click the Start menu in the lower-left corner of the desktop and click the Workflows application plug-in icon. The **Users/Tasks Workflows** window opens.

### **Logging on to the system**

If you are prompted to log on to the system, complete these steps:

1. Enter your user ID and password.
2. Click **Sign in**.

### **Updating the data display**

To refresh the data on any tab, click  in the upper right corner of the window.

### **Configuration**

From the **Configuration** tab, you can view, add, and remove servers.

#### **Adding a z/OSMF server**

Complete these steps to add a new z/OSMF server:

1. Click the **Configuration** tab.
2. Click the plus sign (+) on the left side of the window.
3. In the **Host** field, type the name of the host.
4. In the **Port** field, type the port number.
5. Click **OK**.

## Testing a server connection

To test the connection, click **Test**. When the server is online the **Online** indicator next to the server **Host** and **Port** is green.

## Setting a server as the default z/OSMF server

Complete these steps to set a default z/OSMF server:

1. Click **Set as default**.
2. Enter your user ID and password.
3. Click **Sign in**.

**Note:** You must specify a default server.

## Removing a server

To remove a server, click **x** next to the server that you want to remove.

## Reload a server configuration

To reload a server configuration, click **Reload**.

## Save a server configuration

To save a server configuration, click **Save**.

## Workflows

To display all workflows on the system, click the **Workflows** tab.

You can sort the workflows based on the following information:

### Workflow

The name of the workflow.

### Description

The description of the workflow.

### Version

The version number.

### Owner

The user ID of the workflow owner.

### System

The system identifier.

### Status

The status of the workflow (**In progress** or **Completed**).

### Progress

Indicates how much of the workflow has been completed based on the number of tasks completed.

## Searching workflows

To locate a specific workflow, type a search string in the search box in the upper right corner of the window.

## Defining a workflow

To define a workflow, complete these steps:

1. From the **Workflows** tab, click **Actions > New workflow**. (By default, the **Advanced Mode** check box is selected.)
2. In the **Name** field, specify a descriptive name for the workflow.

3. In the **Workflow definition file** field, specify the primary XML file for this workflow.
4. In the **System** field, specify a system.
5. In the **Owner** field, specify the user ID of the person that is responsible for assigning the tasks in the workflow.  
(To set the owner to the current user, select the **Set owner to current user** check box.)
6. Click **OK**.

### **Viewing tasks**

To view the tasks associated with a workflow, click the **My Tasks** tab. Workflows that have assigned tasks are shown on the left side of the window. The task work area is on the right side of the window.

You can choose to view workflows that have **Pending** or **Completed** tasks or you can choose to view all workflows (**Pending** and **Completed**) and their tasks, regardless of the task status.

For each workflow, you can click the arrow to expand or collapse the task list. Assigned tasks display below each workflow. Hovering over each task displays more information about the task, such as the status and the owner.

Each task has a indicator of **PERFORM** (a step to be performed) or **CHECK** (Check the step that was performed). Clicking **CHECK** or **PERFORM** opens a work area on the right side of the window. When a task is complete, a green clipboard icon with a checkmark is displayed.

**Note:** If you are viewing tasks on a **Pending** or **Completed** tab, only those workflows that have tasks with a corresponding status, are displayed.

### **Task work area**

When you click **CHECK** or **PERFORM**, a work area on the right side of the window opens to display the steps to complete the task. Expand or collapse the work area by clicking .

**Tip:** Hovering over the task description in the title bar of the work area window on the right side displays more information about the corresponding workflow and the step description.

### **Performing a task**

1. To perform a task that has steps that are assigned to you, click **PERFORM**.
2. Use the work area to perform the steps associated with the selected task. Depending on the task, you might use an embedded tool (such as another application) or you might complete a series of steps to complete the task.
3. If there are multiple steps to perform, click **Next** to advance to the next step for the task.
4. Click **Finish**.

**Note:** When a task is complete, a green clipboard icon with a checkmark is displayed next to the task.

### **Checking a task**

1. To check a task, click **CHECK**.
2. In the task work area, view the JESMSGGLG, JESJCL, JESYSMSG, or SYSTSPRT output that is associated with the selected task.

### **Managing tasks**

To manage a task in the **PERFORM** status, click  to the right of the task status. Choose from the following options:

#### **Properties**

Display the title and description of the task.

#### **Perform**

Perform the first step.

#### **Skip**

Skip this step.

#### **Override Complete**

Override the completion of the step. The selected step will be bypassed and will not be performed for this workflow. You must ensure that the step is performed manually.

### **Assignment**

Opens the Manage Assignees window where authorized users can add or remove the user ID of the person that is assigned to the step.

### **Return**

Remove ownership of the step.

### **Viewing warnings**

To view any warning messages that were encountered, click the **Warnings** tab. A message is listed in this tab each time it is encountered.

To locate a specific message, type a search string in the search box in the upper right corner of the window.

You can sort the warning messages based on the following information.

#### **Message Code**

The message code that is associated with the warning.

#### **Description**

A description of the warning.

#### **Date**

The date of the warning.

#### **Corresponding Workflow**

The workflow that is associated with the warning.

## **API Catalog**

As an application developer, use the API Catalog to view what services are running in the API Mediation Layer. Through the API Catalog, you can also view the associated API documentation corresponding to a service, descriptive information about the service, and the current state of the service. The tiles in the API Catalog can be customized by changing values in the mfaas.catalog-ui-tile section defined in the application.yml of a service. A microservice that is onboarded with the API Mediation Layer and configured appropriately, registers automatically with the API Catalog and a tile for that service is added to the Catalog.

**Note:** For more information about how to configure the API Catalog in the application.yml, see: [Java REST APIs with Spring Boot](#) on page 133.

### **View Service Information and API Documentation in the API Catalog**

Use the API Catalog to view services, API documentation, descriptive information about the service, the current state of the service, service endpoints, and detailed descriptions of these endpoints.

**Note:** Verify that your service is running. At least one started and registered instance with the Discovery Service is needed for your service to be visible in the API Catalog.

#### **Follow these steps:**

1. Use the search bar to find the service that you are looking for. Services that belong to the same product family are displayed on the same tile.

**Example:** Sample Applications, Endevor, SDK Application

- Click the tile to view header information, the registered services under that family ID, and API documentation for that service.

**Notes:**

- The state of the service is indicated in the service tile on the dashboard page. If no instances of the service are currently running, the tile displays a message displays that no services are running.
- At least one instance of a service must be started and registered with the discovery service for it to be visible in the API Catalog. If the service that you are onboarding is running, and the corresponding API documentation is displayed, this API documentation is cached and remains visible even when the service and all service instances stop.
- Descriptive information about the service and a link to the home page of the service is displayed.

**Example:**

The screenshot shows the API Catalog interface. At the top, there's a blue header bar with the 'API Catalog' logo and a 'Back' button. Below the header, the title 'Sample API Mediation Layer Applications' is displayed in large, bold, dark blue font. A subtitle below it reads 'Applications which demonstrate how to make a service integrated to the API Mediation Layer ecosystem'. Underneath the title, there's a navigation bar with three tabs: 'discoverableclient' (which is highlighted in blue), 'sampleservice', and 'enablerv1sampleapp'. The main content area for the 'discoverableclient' tab shows the following details:

## Service Integration Enabler V2 Sample

API Doc Version: 1.0.0

[ Base URL: <https://ca3x.ca.com:10010> ]  
</api/v1/apicatalog/apidoc/discoverableclient/v1>

Sample service showing how to integrate a Spring Boot v2.x application

**Other Operations** General Operations

**GET** </ui/v1/discoverableclient/api/v1/instance/gateway-url> What is the URI of the Gateway

3. Expand the endpoint panel to see a detailed summary with responses and parameters of each endpoint, the endpoint description, and the full structure of the endpoint.

**Example:**

## Service Integration Enabler V1 Sample App (spring boot 1.x)

API Doc Version: 1.0.0

[ Base URL: <https://ca3x.ca.com:10010> ]  
</api/v1/apicatalog/apidoc/enablerv1sampleapp/v1>

Sample micro-service showing how to enable a Spring Boot v1.x application

**V1EnablerSampleApp** Sample Controller

**GET** /api/v1/enablerv1sampleapp/samples Retrieve all samples

Simple method to demonstrate how to expose an API endpoint with Open API information

### Parameters

No parameters

### Responses

200

**ok**

[Example Value](#) | [Model](#)

```
[
  {
    "details": "string",
    "index": 0,
    "name": "string"
  }
]
```

401

**Unauthorized**

403

**Forbidden**

404

**URI not found**

500

**Internal Error**

### Notes:

- If a lock icon is visible on the right side of the endpoint panel, the endpoint requires authentication.
- The structure of the endpoint is displayed relative to the base URL.
- The URL path of the abbreviated endpoint relative to the base URL is displayed in the following format:

**Example:**

```
/api/v1/{yourServiceId}/{endpointName}
```

The path of the full URL that includes the base URL is also displayed in the following format:

```
https://hostName:basePort/api/v1/{yourServiceId}/{endpointName}
```

Both links target the same endpoint location.

## Zowe CLI extensions and plug-ins

---

### Extending Zowe CLI

You can install plug-ins to extend the capabilities of Zowe CLI. Plug-ins CLI to third-party applications are also available, such as Visual Studio Code Extension for Zowe (powered by Zowe CLI). Plug-ins add functionality to the product in the form of new command groups, actions, objects, and options.

**Important!** Plug-ins can gain control of your CLI application legitimately during the execution of every command. Install third-party plug-ins at your own risk. We make no warranties regarding the use of third-party plug-ins.

- [Installing plug-ins](#) on page 120
- [IBM® CICS® Plug-in for Zowe CLI](#) on page 123
- [Zowe CLI Plug-in for IBM Db2 Database](#) on page 124
- [VSCode Extension for Zowe](#) on page 127

### Software requirements for Zowe CLI plug-ins

Before you use Zowe CLI plug-ins, complete the following steps:

1. Install [Installing Zowe CLI](#) on page 73 on your computer.
2. Complete the following configurations:

Plug-in	Required Configurations
<a href="#">IBM® CICS® Plug-in for Zowe CLI</a> on page 123	<ul style="list-style-type: none"> <li>• Ensure that <a href="#">IBM CICS Transaction Server v5.2 or later</a> is installed and running in your mainframe environment</li> <li>• <a href="#">IBM CICS Management Client Interface (CMCI)</a> is configured and running in your CICS region.</li> </ul>
<a href="#">Zowe CLI Plug-in for IBM Db2 Database</a> on page 124	<ul style="list-style-type: none"> <li>• Download and prepare the ODBC driver (required for only package installations) and address the licensing requirements.</li> </ul>

**Important!** You can perform the required configurations for the plug-ins that you want to use *before* or *after* you install the plug-ins. However, if you do not perform the required configurations, the plug-ins will not function as designed.

### Installing plug-ins

Use commands in the `plugins` command group to install and manage plug-ins for Zowe CLI.

**Important!** Plug-ins can gain control of your CLI application legitimately during the execution of every command. Install third-party plug-ins at your own risk. We make no warranties regarding the use of third-party plug-ins.

You can install the following plug-ins:

- **IBM CICS Plug-in for Zowe CLI**

Use `@brightside/cics@lts-incremental` in your command syntax to install, update, and validate the plug-in.

- **IBM Db2 Database for Zowe CLI**

Use `@brightside/db2@lts-incremental` in your command syntax to install, update, and validate the plug-in.

### Setting the registry

If you installed Zowe CLI from the bundle distributed with the Zowe PAX media, proceed to the [Installing plug-ins](#) on page 120.

If you installed Zowe CLI from an online registry, confirm that NPM is set to target the registry by issuing the following command:

```
npm config set @brightside:registry https://api.bintray.com/npm/ca/brightside
```

### Meeting the software requirements

Ensure that you meet the software requirements for a plug-in before you install the plug-in to Zowe CLI. For information related to each plug-in, see [Software requirements for Zowe CLI plug-ins](#) on page 120.

### Installing plug-ins

Issue an `install` command to install plug-ins to Zowe CLI. The `install` command contains the following syntax:

```
zowe plugins install [plugin...] [--registry <registry>]
```

- **[`plugin...`]**(Optional) Specifies the name of a plug-in, an npm package, or a pointer to a (local or remote) URL. When you do not specify a plug-in version, the command installs the latest plug-in version and specifies the prefix that is stored in npm save-prefix. For more information, see [npm save prefix](#). For more information about npm semantic versioning, see [npm semver](#). Optionally, you can specify a specific version of a plug-in to install. For example, `zowe plugins install pluginName@^1.0.0`.

**Tip:** You can install multiple plug-ins with one command. For example, issue `zowe plugins install plugin1 plugin2 plugin3`

- **[`--registry <registry>`]**(Optional) Specifies a registry URL from which to install a plug-in when you do not use `npm config set` to set the registry initially.

### Examples: Install plug-ins

- The following example illustrates the syntax to use to install a plug-in that is distributed with the `zowe-cli-bundle.zip`. If you are using `zowe-cli-bundle.zip`, issue the following command for each plug-in `.tgz` file:

```
zowe plugins install ./zowe-cli-cics.tgz
```

- The following example illustrates the syntax to use to install a plug-in that is named "my-plugin" from a specified registry:

```
zowe plugins install @brightside/my-plugin@lts-incremental
```

- The following example illustrates the syntax to use to install a specific version of "my-plugins"

```
zowe plugins install @brightside/my-plugin@"^1.2.3"
```

## Validating plug-ins

Issue the plug-in validation command to run tests against all plug-ins (or against a plug-in that you specify) to verify that the plug-ins integrate properly with Zowe CLI. The tests confirm that the plug-in does not conflict with existing command groups in the base application. The command response provides you with details or error messages about how the plug-ins integrate with Zowe CLI.

Perform validation after you install the plug-ins to help ensure that it integrates with Zowe CLI.

The validate command has the following syntax:

```
zowe plugins validate [plugin]
```

- **[plugin]**(Optional) Specifies the name of the plug-in that you want to validate. If you do not specify a plug-in name, the command validates all installed plug-ins. The name of the plug-in is not always the same as the name of the NPM package.

### Examples: Validate plug-ins

- The following example illustrates the syntax to use to validate a specified installed plug-in:

```
zowe plugins validate @brightside/my-plugin
```

- The following example illustrates the syntax to use to validate all installed plug-ins:

```
zowe plugins validate
```

## Updating plug-ins

Issue the update command to install the latest version or a specific version of a plug-in that you installed previously. The update command has the following syntax:

```
zowe plugins update [plugin...] [--registry <registry>]
```

- **[plugin...]**

Specifies the name of an installed plug-in that you want to update. The name of the plug-in is not always the same as the name of the NPM package. You can use npm semantic versioning to specify a plug-in version to which to update. For more information, see [npm semver](#).

- **--registry <registry>**

(Optional) Specifies a registry URL that is different from the registry URL of the original installation.

### Examples: Update plug-ins

- The following example illustrates the syntax to use to update an installed plug-in to the latest version:

```
zowe plugins update @brightside/my-plugin@lts-incremental
```

- The following example illustrates the syntax to use to update a plug-in to a specific version:

```
zowe plugins update @brightside/my-plugin@"^1.2.3"
```

## Uninstalling plug-ins

Issue the uninstall command to uninstall plug-ins from a base application. After the uninstall process completes successfully, the product no longer contains the plug-in configuration.

**Tip:** The command is equivalent to using [npm uninstall](#) to uninstall a package.

The uninstall command contains the following syntax:

```
zowe plugins uninstall [plugin]
```

- **[plugin]**Specifies the plug-in name to uninstall.

#### **Example: Uninstall plug-ins**

- The following example illustrates the syntax to use to uninstall a plug-in:

```
zowe plugins uninstall @brightside/my-plugin
```

## **IBM® CICS® Plug-in for Zowe CLI**

The IBM® CICS® Plug-in for Zowe CLI lets you extend Zowe CLI to interact with CICS programs and transactions. The plug-in uses the IBM CICS® Management Client Interface (CMCI) API to achieve the interaction with CICS. For more information, see [CICS management client interface](#) on the IBM Knowledge Center.

- [Use cases](#) on page 123
- [Commands](#) on page 123
- [Software requirements](#) on page 123
- [Installing](#) on page 123
- [Creating a user profile](#) on page 124

### **Use cases**

As an application developer, you can use the plug-in to perform the following tasks:

- Deploy code changes to CICS applications that were developed with COBOL.
- Deploy changes to CICS regions for testing or delivery. See the [Commands](#) on page 123 for an example of how you can define programs to CICS to assist with testing and delivery.
- Automate CICS interaction steps in your CI/CD pipeline with Jenkins Automation Server or TravisCI.
- Deploy build artifacts to CICS regions.
- Alter, copy, define, delete, discard, and install CICS resources and resource definitions.

### **Commands**

For detailed documentation on commands, actions, and options available in this plug-in, see our Web Help. It is available for download in three formats: a PDF document, an interactive online version, and a ZIP file containing the HTML for the online version.

- [Browse Online](#)
- [Download \(ZIP\)](#)
- [Download \(PDF\)](#)

### **Software requirements**

Before you install the plug-in, meet the software requirements in [Software requirements for Zowe CLI plug-ins](#) on page 120.

### **Installing**

Use one of the following methods to install the plug-in:

- [Installing from an online registry](#) on page 123
- [Installing from a local package](#) on page 124

**Note:** For more information about how to install multiple plug-ins, update to a specific version of a plug-ins, and install from specific registries, see [Installing plug-ins](#) on page 120.

#### **Installing from an online registry**

To install Zowe CLI from an online registry, complete the following steps:

- Set your npm registry if you did not already do so when you installed Zowe CLI. Issue the following command:

```
npm config set @brightside:registry https://api.bintray.com/npm/ca/brightside
```

- Open a command line window and issue the following command:

```
zowe plugins install @brightside/cics@lts-incremental
```

- (Optional) After the command execution completes, issue the following command to validate that the installation completed successfully.

```
zowe plugins validate @brightside/cics
```

Successful validation of the IBM CICS plug-in returns the response: Successfully validated.

### **Installing from a local package**

If you downloaded the Zowe PAX file and extracted the `zowe-cli-bundle.zip` package, complete the following steps to install the Zowe CLI Plug-in for CICS:

- Open a command line window and change the local directory where you extracted the `zowe-cli-bundle.zip` file. If you do not have the `zowe-cli-bundle.zip` file, see the topic [Installing Zowe CLI from a local package](#) on page 73 for information about how to obtain and extract it.
- Issue the following command to install the plug-in:

```
zowe plugins install zowe-cli-cics.tgz
```

- (Optional) After the command execution completes, issue the following command to validate that the installation completed successfully.

```
zowe plugins validate @brightside/cics
```

Successful validation of the CICS plug-in returns the response: Successfully validated. You can safely ignore \*\*\* Warning: messages related to Imperative CLI Framework.

### **Creating a user profile**

You can set up a CICS profile to avoid typing your connection details on every command. The profile contains your host, port, username, and password for the CMCI instance of your choice. You can create multiple profiles and switch between them if necessary. Issue the following command to create a cics profile:

```
zowe profiles create cics <profile name> -H <host> -P <port> -u <user> -p <password>
```

**Note:** For more information, issue the command `zowe profiles create cis --help`

## **Zowe CLI Plug-in for IBM Db2 Database**

The Zowe CLI plug-in for IBM® Db2® Database lets you interact with Db2 for z/OS to perform tasks through Zowe CLI and integrate with modern development tools. The plug-in also lets you interact with Db2 to advance continuous integration and to validate product quality and stability.

Zowe CLI Plug-in for IBM Db2 Database lets you execute SQL statements against a Db2 region, export a Db2 table, and call a stored procedure. The plug-in also exposes its API so that the plug-in can be used directly in other products.

[]

### **Use cases**

As an application developer, you can use Zowe CLI Plug-in for IBM DB2 Database to perform the following tasks:

- Execute SQL and interact with databases.

- Execute a file with SQL statements.
- Export tables to a local file on your computer in SQL format.
- Call a stored procedure and pass parameters.

## Commands

For detailed documentation on commands, actions, and options available in this plug-in, see our Web Help. It is available for download in three formats: a PDF document, an interactive online version, and a ZIP file containing the HTML for the online version.

- [Browse Online](#)
- [Download \(ZIP\)](#)
- [Download \(PDF\)](#)

## Software requirements

Before you install the plug-in, meet the software requirements in [Software requirements for Zowe CLI plug-ins](#) on page 120.

## Installing

Use one of the following methods to install the the Zowe CLI Plug-in for IBM Db2 Database:

- [Installing from an online registry](#) on page 125
- [Installing from a local package](#) on page 125

### Installing from an online registry

If you installed Zowe CLI from **online registry**, complete the following steps:

1. Open a command line window and issue the following command:

```
zowe plugins install @brightside/db2@lts-incremental
```

2. [Addressing the license requirement](#) on page 126 to begin using the plug-in.

### Installing from a local package

Follow these procedures if you downloaded the Zowe installation package:

#### *Downloading the ODBC driver*

Download the ODBC driver before you install the Db2 plug-in.

#### **Follow these steps:**

1. [Download the ODBC CLI Driver](#). Use the table within the download URL to select the correct CLI Driver for your platform and architecture.
2. Create a new directory named `odbc_cli` on your computer. Remember the path to the new directory. You will need to provide the full path to this directory immediately before you install the Db2 plug-in.
3. Place the ODBC driver in the `odbc_cli` folder. **Do not extract the ODBC driver.**

You downloaded and prepared to use the ODBC driver successfully. Proceed to install the plug-in to Zowe CLI.

#### *Installing the plug-in*

Now that the Db2 ODBC CLI driver is downloaded, set the `IBM_DB_INSTALLER_URL` environment variable and install the Db2 plug-in to Zowe CLI.

#### **Follow these steps:**

1. Open a command line window and change the directory to the location where you extracted the `zowe-cli-bundle.zip` file. If you do not have the `zowe-cli-bundle.zip` file, see the topic [Install Zowe CLI from local package](#) in [Installing Zowe CLI](#) on page 73 for information about how to obtain and extract it.

2. From a command line window, set the IBM\_DB\_INSTALLER\_URL environment variable by issuing the following command:
  - Windows operating systems:

```
set IBM_DB_INSTALLER_URL=<path_to_your_odbc_folder>/odbc_cli
```

- Linux and Mac operating systems:

```
export IBM_DB_INSTALLER_URL=<path_to_your_odbc_folder>/odbc_cli
```

For example, if you downloaded the Windows x64 driver (ntx64\_odbc\_cli.zip) to C:\odbc\_cli, you would issue the following command:

```
set IBM_DB_INSTALLER_URL=C:\odbc_cli
```

3. Issue the following command to install the plug-in:

```
zowe plugins install zowe-db2.tgz
```

4. [Addressing the license requirement](#) on page 126 to begin using the plug-in.

### **Addressing the license requirement**

The following steps are required for both the registry and offline package installation methods:

1. Locate your client copy of the Db2 license. You must have a properly licensed and configured Db2 instance for the Db2 plugin to successfully connect to Db2 on z/OS.

**Note:** The license must be of version 11.1 if the Db2 server is not db2connectactivated. You can buy a db2connect license from IBM. The connectivity can be enabled either on server using db2connectactivate utility or on client using client side license file. To know more about DB2 license and purchasing cost, please contact IBM Customer Support.

2. Copy your Db2 license file and place it in the following directory.

- **Windows:**

```
<zowe_home>\plugins\installed\node_modules\@brightside\db2\node_modules
\ibm_db\installer\clidriver\license
```

- **Linux:**

```
<zowe_home>/plugins/installed/lib/node_modules/@brightside/db2/
node_modules/ibm_db/installer/clidriver/license
```

**Tip:** By default, <zowe\_home> is set to ~/.zowe on /\*NIX systems, and C:\Users\<Your\_User>\.zowe on Windows systems.

After the license is copied, you can use the Db2 plugin functionality.

### **Creating a user profile**

Before you start using the IBM Db2 plug-in, create a profile.

Issue the command **-DISPLAY DDF** in the SPUFI or ask your DBA for the following information:

- The Db2 server host name
- The Db2 server port number
- The database name (you can also use the location)
- The user name
- The password
- If your Db2 systems use a secure connection, you can also provide an SSL/TSL certificate file.

To create a db2 profile in Zowe CLI, issue the following command with your connection details for the Db2 instance:

```
zowe profiles create db2 <profile name> -H <host> -P <port> -d <database> -u
<user> -p <password>
```

**Note** For more information, issue the command `zowe profiles create db2-profile --help`

## VSCODE Extension for Zowe

The Visual Studio Code (VSCODE) Extension for Zowe lets you interact with data sets that are stored on IBM z/OS mainframe. Install the extension directly to [VSCode](#) to enable the extension within the GUI. You can explore data sets, view their contents, make changes, and upload the changes to the mainframe. For some users, it can be more convenient to interact with data sets through a GUI rather than using command-line interfaces or 3270 emulators. The extension is powered by Zowe CLI.

**Note:** The primary documentation, for this plug-in is available on the [Visual Studio Code Marketplace](#). This topic is intended to be an overview of the extension.

- [Software requirements](#) on page 127
- [Installing](#) on page 127
- [Use-Cases](#) on page 127

### Software requirements

Before you use the VSCODE extension, meet the following software requirements on your computer:

- Install [VSCode](#).
- [Installing Zowe CLI](#) on page 73.
- Create at least one Zowe CLI 'zosmf' profile so that the extension can communicate with the mainframe. See [Creating Zowe CLI profiles](#) on page 89.

### Installing

1. Address [Software requirements](#) on page 127.
2. Open VSCode. Navigate to the **Extensions** tab on the left side of the UI.
3. Click the green **Install** button to install the plug-in.
4. Restart VSCode. The plug-in is now installed and available for use.

**Tip:** For information about how to install the extension from a VSIX file and run system tests on the extension, see the Developer README file in the Zowe VSCODE extension GitHub repository.

You can also watch the following video to learn how to install and use the Zowe VSCODE Extension. If you read this doc in PDF format, you can click [here](#) to watch the video.

### Use-Cases

As an developer, you can use VSCODE Extension for Zowe to perform the following tasks.

- View and filter mainframe data sets.
- Create download, edit, upload, and delete PDS and PDS members.
- Use "safe save" to safely resolve conflicts when a data set is changed during local editing.
- Switch between Zowe CLI profiles to quickly target different mainframe systems.

**Note:** For detailed step-by-step instructions for using the plug-in and more information about each feature, see [Zowe on the Visual Studio Code Marketplace](#).



---

# Chapter

# 3

---

---

## Extending

---

**Topics:**

- Developing for API Mediation Layer
- Developing for Zowe CLI
- Developing for Zowe Application Framework
- Zowe Conformance Program

# Developing for API Mediation Layer

---

## Onboarding Overview


### Overview of APIs

Before identifying the API you want to expose in the API Mediation Layer, it is useful to consider the structure of APIs. An application programming interface (API) is a set of rules that allow programs to talk to each other. A developer creates an API on a server and allows a client to talk to the API. Representational State Transfer (REST) determines the look of an API and is a set of rules that developers follow when creating an API. One of these rules states that a user should be able to get a piece of data (resource) through URL endpoints using HTTP. These resources are usually represented in the form of JSON or XML documents. The preferred documentation type in Zowe is in the JSON format.

A REST API service can provide one or more REST APIs and usually provides the latest version of each API. A REST service is hosted on a web server which can host one or more services, often referred to as *applications*. A web server that hosts multiple services or applications is referred to as a *web application server*. Examples of *web application servers* are [Apache Tomcat](#) or [WebSphere Liberty](#).

**Note:** Definitions used in this procedure follow the [OpenAPI specification](#). Each API has its own title, description, and version (versioned using [Semantic Versioning 2.0.0](#)).

The following diagram shows the relations between various types of services, their APIs, REST API endpoints, and the API gateway:



### Sample REST API Service

In microservice architecture, a web server usually provides a single service. A typical example of a single service implementation is a Spring Boot web application.

To demonstrate the concepts that apply to REST API services, we use the following example of a Spring Boot REST API service: <https://github.com/swagger-api/swagger-samples/tree/master/java/java-spring-boot>. This example is used in the REST API onboarding guide: **REST API without code changes required**.

You can build this service using instructions in the source code of the Spring Boot REST API service example (<https://github.com/swagger-api/swagger-samples/blob/master/java/java-spring-boot/README.md>).

The Sample REST API Service has a base URL. When you start this service on your computer, the *service base URL* is: `http://localhost:8080`.

**Note:** If a service is deployed to a web application server, the base URL of the service (application) has the following format: `https://application-server-hostname:port/application-name`.

This sample service provides one API that has the base path /v2, which is represented in the base URL of the API as <http://localhost:8080/v2>. In this base URL, /v2 is a qualifier of the base path that was chosen by the developer of this API. Each API has a base path depending on the particular implementation of the service.

This sample API has only one single endpoint:

- `/pets/{id}` - *Find pet by ID.*


This endpoint in the sample service returns information about a pet when the `{id}` is between 0 and 10. If `{id}` is greater than 0 or a non-integer then it returns an error. These are conditions set in the sample service.

**Tip:** Access <http://localhost:8080/v2/pets/1> to see what this REST API endpoint does. You should get the following response:

```
{
  "category": {
    "id": 2,
    "name": "Cats"
  },
  "id": 1,
  "name": "Cat 1",
  "photoUrls": [
    "url1",
    "url2"
  ],
  "status": "available",
  "tags": [
    {
      "id": 1,
      "name": "tag1"
    },
    {
      "id": 2,
      "name": "tag2"
    }
  ]
}
```

**Note:** The onboarding guides demonstrate how to add the Sample REST API Service to the API Mediation Layer to make the service available through the `petstore` service ID.

The following diagram shows the relations between the Sample REST API Service and its corresponding API, REST API endpoint, and API gateway:



This sample service provides a Swagger document in JSON format at the following URL:

```
http://localhost:8080/v2/swagger.json
```

The Swagger document is used by the API Catalog to display the API documentation.

### API Service Types

The process of onboarding depends on the method that is used to develop the API service.

While any REST API service can be added to the API Mediation Layer, this documentation focuses on following types of REST APIs:

- Services that can be updated to support the API Mediation Layer natively by updating the service code:
  - [Java REST APIs with Spring Boot](#) on page 133
  - [Java Jersey REST APIs](#) on page 156
  - [Java REST APIs service without Spring Boot](#) on page 146
  - [REST APIs without code changes required](#) on page 169

**Tip:** When developing a new service, we recommend that you update the code to support the API Mediation Layer natively. Use the previously listed onboarding guides for services that can be updated to support the API Mediation Layer natively. The benefit of supporting the API Mediation Layer natively is that it requires less configuration for the system administrator. Such service can be moved to different systems, can be listened to on a different port, or additional instances can be started without the need to change configuration of the API Mediation Layer.

### Java REST APIs with Spring Boot

Zowe API Mediation Layer (API ML) provides a single point of access for mainframe service REST APIs. For a high-level overview of this component, see [API Mediation Layer](#) on page 10.

**Note:** Spring is a Java-based framework that lets you build web and enterprise applications. For more information, see the [Spring website](#).

As an API developer, use this guide to onboard your REST API service into the Zowe API Mediation Layer. This article outlines a step-by-step process to make your API service available in the API Mediation Layer.

1. [Add Zowe API enablers to your service](#) on page 134
2. [Add API ML onboarding configuration](#) on page 136
3. [Externalize API ML configuration parameters](#) on page 145
4. [Test your service](#) on page 146
5. [Review the configuration examples of the discoverable client](#) on page 146

### Add Zowe API enablers to your service

In order to onboard a REST API with the Zowe ecosystem, you add the Zowe Artifactory repository definition to the list of repositories, then add the Spring enabler to the list of your dependencies, and finally add enabler annotations to your service code. Enablers prepare your service for discovery and swagger documentation retrieval.

#### Follow these steps:

1. Add the Zowe Artifactory repository definition to the list of repositories in Gradle or Maven build systems. Use the code block that corresponds to your build system.
  - In a Gradle build system, add the following code to the `build.gradle` file into the `repositories` block.

**Note:** Ensure that you are using valid Zowe Artifactory credentials.

```
maven {
    url 'https://gizaartifactory.jfrog.io/gizaartifactory/libs-release'
    credentials {
        username 'apilayer-build'
        password 'lHj7sjJmAxL5k7obuf800f+tCLQYZPMVpDob5oJG1NI='
    }
}
```

**Note:** You can define the `gradle.properties` file where you can set your username, password, and the read-only repo URL for access to the Zowe Artifactory. By defining the `gradle.properties`, you do not need to hardcode the username, password, and read-only repo URL in your `gradle.build` file.

#### Example:

```
# Artifactory repositories for builds
artifactoryMavenRepo=https://gizaartifactory.jfrog.io/
gizaartifactory/libs-release

# Artifactory credentials for builds (not publishing):
mavenUser=apilayer-build
mavenPassword=lHj7sjJmAxL5k7obuf800f+tCLQYZPMVpDob5oJG1NI=
```

- In a Maven build system, follow these steps:

a) Add the following code to the `pom.xml` file:

```
<repository>
    <id>Gizaartificatory</id>
    <url>https://gizaartifactory.jfrog.io/gizaartifactory/libs-
release</url>
</repository>
```

b) Create a `settings.xml` file and copy the following XML code block which defines the login credentials for the Zowe Artifactory. Use valid credentials.

```
<?xml version="1.0" encoding="UTF-8"?>
```

```

<settings xmlns="http://maven.apache.org/SETTINGS/1.0.0"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://maven.apache.org/SETTINGS/1.0.0
        https://maven.apache.org/xsd/settings-1.0.0.xsd">

    <servers>
        <server>
            <id>Gizaartificatory</id>
            <username>apilayer-build</username>
            <password>lHj7sjJmAxL5k7obuf800f+tCLQYZPMVpDob5oJG1NI=</password>
        </server>
    </servers>
</settings>

```

c) Copy the `settings.xml` file inside the  `${user.home} / .m2/` directory.

2. Add a JAR package to the list of dependencies in Gradle or Maven build systems. Zowe API Mediation Layer supports Spring Boot versions 1.5.9 and 2.0.4.

- If you use Spring Boot release 1.5.x in a Gradle build system, add the following code to the `build.gradle` file into the `dependencies` block:

```

compile group: 'com.ca.mfaas.sdk', name: 'mfaas-integration-enabler-
spring-v1-springboot-1.5.9.RELEASE', version: '1.1.0'

```

- If you use Spring Boot release 1.5.x in a Maven build system, add the following code to the `pom.xml` file:

```

<dependency>
    <groupId>com.ca.mfaas.sdk</groupId>
    <artifactId>mfaas-integration-enabler-spring-v1-
springboot-1.5.9.RELEASE</artifactId>
    <version>1.1.0</version>
</dependency>

```

- If you use the Spring Boot release 2.0.x in a Gradle build system, add the following code to the `build.gradle` file into the `dependencies` block:

```

compile group: 'com.ca.mfaas.sdk', name: 'mfaas-integration-enabler-
spring-v2-springboot-2.0.4.RELEASE', version: '1.1.0'

```

- If you use the Spring Boot release 2.0.x in a Maven build system, add the following code to the `pom.xml` file:

```

<dependency>
    <groupId>com.ca.mfaas.sdk</groupId>
    <artifactId>mfaas-integration-enabler-spring-v2-
springboot-2.0.4.RELEASE</artifactId>
    <version>1.1.0</version>
</dependency>

```

3. Add the following annotations to the main class of your Spring Boot, or add these annotations to an extra Spring configuration class:

- `@ComponentScan({ "com.ca.mfaas.enable", "com.ca.mfaas.product" })`

Makes an API documentation endpoint visible within the Spring context.

- `@EnableApiDiscovery`

Exposes your Swagger (OpenAPI) documentation in the Zowe ecosystem to make your micro service discoverable in the Zowe ecosystem.

**Note:** The `@EnableApiDiscovery` annotation uses the Spring Fox library. If your service uses the library already, some fine tuning may be necessary.

#### Example:

```
package com.ca.mfaas.DiscoverableClientSampleApplication;
...
import com.ca.mfaas.enable.EnableApiDiscovery;
import org.springframework.context.annotation.ComponentScan;
...
@EnableApiDiscovery
@ComponentScan({ "com.ca.mfaas.enable", "com.ca.mfaas.product" })
...
public class DiscoverableClientSampleApplication { ... }
```

You are now ready to build your service to include the code pieces that make it discoverable in the API Mediation Layer and to add Swagger documentation.

#### Add API ML onboarding configuration

As an API service developer, you set multiple configuration settings in your application.yml that correspond to the API ML. These settings enable an API to be discoverable and included in the API catalog. Some of the settings in the application.yml are internal and are set by the API service developer. Some settings are externalized and set by the customer system administrator. Those external settings are service parameters and are in the format:  `${environment.*}` .

**Important!** Spring Boot configuration can be externalized in multiple ways. For more information see: [Externalized configuration](#). This Zowe onboarding documentation applies to API services that use an application.yml file for configuration. If your service uses a different configuration option, transform the provided configuration sample to the format that your API service uses.

**Tip:** For information about how to set your configuration when running a Spring Boot application under an external servlet container (TomCat), see the following short stackoverflow article: [External configuration for spring-boot application](#).

#### Follow these steps:

1. Add the following #MFAAS configuration section in your application.yml:

```
#####
# MFAAS configuration section
#####
mfaas:
  discovery:
    serviceId: ${environment.serviceId}
    locations: ${environment.discoveryLocations}
    enabled: ${environment.discoveryEnabled:true}
    endpoints:
      statusPage: ${mfaas.server.scheme}://${mfaas.service.hostname}:${mfaas.server.port}${mfaas.server.contextPath}/application/info
```

```

        healthPage: ${mfaas.server.scheme}://${mfaas.service.hostname}:${mfaas.server.port}${mfaas.server.contextPath}/application/health
        homepage: ${mfaas.server.scheme}://${mfaas.service.hostname}:${mfaas.server.port}${mfaas.server.contextPath}/info:
            serviceTitle: ${environment.serviceTitle}
            description: ${environment.serviceDescription}
            # swaggerLocation:
resource_location_of_your_static_swagger_doc.json
    fetchRegistry: false
    region: default
service:
    hostname: ${environment.hostname}
    ipAddress: ${environment.ipAddress}
catalog-ui-tile:
    id: yourProductFamilyId
    title: Your API service product family title in the API catalog dashboard tile
    description: Your API service product family description in the API catalog dashboard tile
    version: 1.0.0
server:
    scheme: http
    port: ${environment.port}
    contextPath: /yourServiceUrlPrefix
security:
    sslEnabled: true
    protocol: TLSv1.2
    ciphers:
        TLS_RSA_WITH_AES_128_CBC_SHA, TLS_DHE_RSA_WITH_AES_256_CBC_SHA, TLS_ECDH_RSA_WITH_AES_
        keyAlias: localhost
        keyPassword: password
        keyStore: keystore/ssl_local/localhost.keystore.p12
        keyStoreType: PKCS12
        keyStorePassword: password
        trustStore: keystore/ssl_local/localhost.truststore.p12
        trustStoreType: PKCS12
        trustStorePassword: password

eureka:
    instance:
        appname: ${mfaas.discovery.serviceId}
        hostname: ${mfaas.service.hostname}
        statusPageUrlPath: ${mfaas.discovery.endpoints.statusPage}
        healthCheckUrl: ${mfaas.discovery.endpoints.healthPage}
        homePageUrl: ${mfaas.discovery.endpoints.homePage}
        metadata-map:
            routed-services:
                api_v1:
                    gateway-url: "api/v1"
                    service-url: ${mfaas.server.contextPath}
    apiml:
        apiInfo:
            - apiId: ${mfaas.discovery.serviceId}
              gatewayUrl: api/v1
              swaggerUrl: ${mfaas.server.scheme}://${mfaas.service.hostname}:${mfaas.server.port}${mfaas.server.contextPath}/api-doc
              documentationUrl: https://www.zowe.org
    mfaas:
        api-info:
            apiVersionProperties:
                v1:

```

```

                title: Your API title for swagger JSON which
is displayed in API Catalog / service / API Information
                description: Your API description for
swagger JSON
                version: 1.0.0
                basePackage:
your.service.base.package.for.swagger.annotated.controllers
                # apiPattern: /v1/.+ # alternative to
basePackage for exposing endpoints which match the regex pattern to
swagger JSON
                discovery:
                    catalogUiTile:
                        id: ${mfaas.catalog-ui-tile.id}
                        title: ${mfaas.catalog-ui-tile.title}
                        description: ${mfaas.catalog-ui-
tile.description}
                        version: ${mfaas.catalog-ui-tile.version}
                        enableApiDoc:
${mfaas.discovery.info.enableApiDoc:true}
                    service:
                        title: ${mfaas.discovery.info.serviceTitle}
                        description: ${mfaas.discovery.info.description}
client:
    enabled: ${mfaas.discovery.enabled}
    healthcheck:
        enabled: true
    serviceUrl:
        defaultZone: ${mfaas.discovery.locations}
        fetchRegistry: ${mfaas.discovery.fetchRegistry}
        region: ${mfaas.discovery.region}

#####
# Application configuration section

#####
server:
    # address: ${mfaas.service.ipAddress}
    port: ${mfaas.server.port}
    servlet:
        contextPath: ${mfaas.server.contextPath}
    ssl:
        enabled: ${mfaas.security.sslEnabled}
        protocol: ${mfaas.security.protocol}
        ciphers: ${mfaas.security.ciphers}
        keyStore: ${mfaas.security.keyStore}
        keyAlias: ${mfaas.security.keyAlias}
        keyPassword: ${mfaas.security.keyPassword}
        keyStorePassword: ${mfaas.security.keyStorePassword}
        keyStoreType: ${mfaas.security.keyStoreType}
        trustStore: ${mfaas.security.trustStore}
        trustStoreType: ${mfaas.security.trustStoreType}
        trustStorePassword: ${mfaas.security.trustStorePassword}

spring:
    application:
        name: ${mfaas.discovery.serviceId}

```

In order to run your application locally, you need to define variables used under the environment group.

```

#####
# Local configuration section
#####

```

```
environment:  
    serviceId: Your service id  
    serviceTitle: Your service title  
    serviceDescription: Your service description  
    discoveryEnabled: true  
    hostname: localhost  
    port: Your service port  
    discoveryLocations: https://localhost:10011/eureka/  
    ipAddress: 127.0.0.1
```

**Important:** Add this configuration also to the `application.yml` used for testing. Failure to add this configuration to the `application.yml` will cause your tests to fail.

- Change the MFaaS parameters to correspond with your API service specifications. Most of these internal parameters contain "your service" text.

**Note:** \${mfaas.\*} variables are used throughout the application.yml sample to reduce the number of required changes.

**Tip:** When existing parameters set by the system administrator are already present in your configuration file (for example, hostname, address, contextPath, and port), we recommend that you replace them with the corresponding MFaaS properties.

#### a. Discovery Parameters

- mfaas.discovery.serviceId**

Specifies the service instance identifier to register in the API ML installation. The service ID is used in the URL for routing to the API service through the gateway. The service ID uniquely identifies instances of a microservice in the API ML. The system administrator at the customer site defines this parameter.

**Important!** Ensure that the service ID is set properly with the following considerations:

- When two API services use the same service ID, the API Gateway considers the services to be clones. An incoming API request can be routed to either of them.
- The same service ID should be set for only multiple API service instances for API scalability.
- The service ID value must contain only lowercase alphanumeric characters.
- The service ID cannot contain more than 40 characters.
- The service ID is linked to security resources. Changes to the service ID require an update of security resources.
- The service ID must match the spring.application.name parameter.

#### Examples:

- If the customer system administrator sets the service ID to sysviewlpr1, the API URL in the API Gateway appears as the following URL:

```
https://gateway:port/api/v1/sysviewlpr1/endpoint1/...
```

- If the customer system administrator sets the service ID to vantageprod1, the API URL in the API Gateway appears as the following URL:

```
http://gateway:port/api/v1/vantageprod1/endpoint1/...
```

- mfaas.discovery.locations**

Specifies the public URL of the Discovery Service. The system administrator at the customer site defines this parameter.

#### Example:

```
http://eureka:password@141.202.65.33:10311/eureka/
```

- mfaas.discovery.enabled**

Specifies whether the API service instance is to be discovered in the API ML. The system administrator at the customer site defines this parameter. Set this parameter to true if the API ML is installed and configured. Otherwise, you can set this parameter to false to exclude an API service instances from the API ML.

- mfaas.discovery.fetchRegistry**

Specifies whether the API service is to receive regular update notifications from the discovery service. Under most circumstances, you can accept the default value of false for the parameter.

- mfaas.discovery.region**

Specifies the geographical region. This parameter is required by the Discovery client. Under most circumstances you can accept the value default for the parameter.

## b. Service and Server Parameters

- **mfaas.service.hostname**

Specifies the hostname of the system where the API service instance runs. This parameter is externalized and is set by the customer system administrator. The administrator ensures the hostname can be resolved by DSN to the IP address that is accessible by applications running on their z/OS systems.

- **mfaas.service.ipAddress**

Specifies the local IP address of the system where the API service instance runs. This IP address may or may not be a public IP address. This parameter is externalized and set by the customer system administrator.

- **mfaas.server.scheme**

Specifies whether the API service is using the HTTPS protocol. This value can be set to https or http depending on whether your service is using SSL.

- **mfaas.server.port**

Specifies the port that is used by the API service instance. This parameter is externalized and set by the customer system administrator.

- **mfaas.server.contextPath**

Specifies the prefix that is used within your API service URL path.

**Examples:**

- If your API service does not use an extra prefix in the URL (for example, http://host:port/endpoint1/), set this value to /.
- If your API service uses an extra URL prefix set the parameter to that prefix value. For the URL: http://host:port/filemaster/endpoint1/, set this parameter to /filemaster.
- In both examples, the API service URL appears as the following URL when routed through the Gateway:

```
http://gateway:port/serviceId/endpoint1/
```

## c. API Catalog Parameters

These parameters are used to populate the API Catalog. The API Catalog contains information about every registered API service. The Catalog also groups related APIs. Each API group has its own name and description.

Catalog groups are constructed in real-time based on information that is provided by the API services. Each group is displayed as a tile in the API Catalog UI dashboard.

- **mfaas.catalog-ui-tile.id**

Specifies the unique identifier for the API services product family. This is the grouping value used by the API ML to group multiple API services together into "tiles". Each unique identifier represents a single API Catalog UI dashboard tile. Specify a value that does not interfere with API services from other products.

- **mfaas.catalog-ui-tile.title**

Specifies the title of the API services product family. This value is displayed in the API Catalog UI dashboard as the tile title

- **mfaas.catalog-ui-tile.description**

Specifies the detailed description of the API services product family. This value is displayed in the API Catalog UI dashboard as the tile description

- **mfaas.catalog-ui-tile.version**

Specifies the semantic version of this API Catalog tile. Increase the version when you introduce new changes to the API services product family details (title and description).

- **mfaas.discovery.info.serviceTitle**

Specifies the human readable name of the API service instance (for example, "Endevor Prod" or "Sysview LPAR1"). This value is displayed in the API Catalog when a specific API service instance is selected. This parameter is externalized and set by the customer system administrator.

## API Catalog - Available

MFaaS Microservice to locate and display API documentation for MFaaS discovered microservices

**Tip:** We recommend that you provide a good default value or give good naming examples to the customers.

- **mfaas.discovery.info.description**

Specifies a short description of the API service.

**Example:** "CA Endevor SCM - Production Instance" or "CA SYSVIEW running on LPAR1". This value is displayed in the API Catalog when a specific API service instance is selected. This parameter is externalized and set by the customer system administrator.

**Tip:** We recommend that you provide a good default value or give good naming examples to the customers. Describe the service so that the end user knows the function of the service.

- **mfaas.discovery.info.swaggerLocation**

Specifies the location of a static swagger document. The JSON document contained in this file is displayed instead of the automatically generated API documentation. The JSON file must contain a valid OpenAPI 2.x Specification document. This value is optional and commented out by default.

**Note:** Specifying a `swaggerLocation` value disables the automated JSON API documentation generation with the SpringFox library. By disabling auto-generation, you need to keep the contents of the manual swagger

definition consistent with your endpoints. We recommend to use auto-generation to prevent incorrect endpoint definitions in the static swagger documentation.

#### d. Metadata Parameters

The routing rules can be modified with parameters in the metadata configuration code block.

**Note:** If your REST API does not conform to Zowe API Mediation layer REST API Building codes, configure routing to transform your actual endpoints (serviceUrl) to gatewayUrl format. For more information see: [REST API Building Codes](#)

- `eureka.instance.metadata-map.routed-services.<prefix>`

Specifies a name for routing rules group. This parameter is only for logical grouping of further parameters. You can specify an arbitrary value but it is a good development practice to mention the group purpose in the name.

#### Examples:

```
api_v1
api_v2
```

- `eureka.instance.metadata-map.routed-services.<prefix>.gatewayUrl`

Both gateway-url and service-url parameters specify how the API service endpoints are mapped to the API gateway endpoints. The gateway-url parameter sets the target endpoint on the gateway.

- `metadata-map.routed-services.<prefix>.serviceUrl`

Both gateway-url and service-url parameters specify how the API service endpoints are mapped to the API gateway endpoints. The service-url parameter points to the target endpoint on the gateway.

- `eureka.instance.metadata-map.apiml.apiInfo.apiId`

Specifies the API identifier that is registered in the API Mediation Layer installation. The API ID uniquely identifies the API in the API Mediation Layer. The same API can be provided by multiple services. The API ID can be used to locate the same APIs that are provided by different services. The creator of the API defines this ID. The API ID needs to be a string of up to 64 characters that uses lowercase alphanumeric characters and a dot: ... We recommend that you use your organization as the prefix.

- `eureka.instance.metadata-map.apiml.apiInfo.gatewayUrl`

The base path at the API gateway where the API is available. Ensure that it is the same path as the *gatewayUrl* value in the *routes* sections.

- `eureka.instance.metadata-map.apiml.apiInfo.documentationUrl`

(Optional) Link to external documentation, if needed. The link to the external documentation can be included along with the Swagger documentation.

- `eureka.instance.metadata-map.apiml.apiInfo.swaggerUrl`

(Optional) Specifies the HTTP or HTTPS address where the Swagger JSON document is available. **Important!** Ensure that each of the values for gatewayUrl parameter are unique in the configuration. Duplicate gatewayUrl values may cause requests to be routed to the wrong service URL.

**Note:** The endpoint /api-doc returns the API service Swagger JSON. This endpoint is introduced by the `@EnableMfaasInfo` annotation and is utilized by the API Catalog.

#### e. Swagger Api-Doc Parameters

Configures API Version Header Information, specifically the [InfoObject](#) section, and adjusts Swagger documentation that your API service returns. Use the following format:

```
api-info:
  apiVersionProperties:
    v1:
      title: Your API title for swagger JSON which is displayed in API Catalog / service / API Information
```

```

description: Your API description for swagger JSON
version: 1.0.0
basePackage:
your.service.base.package.for.swagger.annotated.controllers
# apiPattern: /v1/.* # alternative to basePackage for exposing
endpoints which match the regex pattern to swagger JSON

```

The following parameters describe the function of the specific version of an API. This information is included in the swagger JSON and displayed in the API Catalog:

#### **Title** API Catalog

**Description** This is the REST API for the API Catalog microservice. The API Catalog is one of the API Mediation Layer components. It provides documentation corresponding to a service, service descriptive information, and the current state of the service.

#### **Version** 1.0.0

- **v1**

Specifies the major version of your service API: v1, v2, etc.

- **title**

Specifies the title of your service API.

- **description**

Specifies the high-level function description of your service API.

- **version**

Specifies the actual version of the API in semantic format.

- **basePackage**

Specifies the package where the API is located. This option only exposes endpoints that are defined in a specified java package. The parameters `basePackage` and `apiPattern` are mutually exclusive. Specify only one of them and remove or comment out the second one.

- **apiPattern**

This option exposes any endpoints that match a specified regular expression. The parameters `basePackage` and `apiPattern` are mutually exclusive. Specify just one of them and remove or comment out the second one.

**Tip:** You have three options to make your endpoints discoverable and exposed: `basePackage`, `apiPattern`, or none (if you do not specify a parameter). If `basePackage` or `apiPattern` are not defined, all endpoints in the Spring Boot app are exposed.

### Setup keystore with the service certificate

To register with the API Mediation Layer, a service is required to have a certificate that is trusted by API Mediation Layer.

#### Follow these steps:

1. Follow instructions at [Generating certificate for a new service on localhost](#)

When a service is running on localhost, the command can have the following format:

```

<api-layer-repository>/scripts/apiml_cm.sh --action new-service --service-
alias localhost --service-ext SAN=dns:localhost.localdomain,dns:localhost
--service-keystore keystore/localhost.keystore.p12 --service-truststore
keystore/localhost.truststore.p12 --service-dname "CN=Sample REST API
Service, OU=Mainframe, O=Zowe, L=Prague, S=Prague, C=Czechia" --service-

```

```
password password --service-validity 365 --local-ca-filename <api-layer-repository>/keystore/local_ca/localca
```

Alternatively, for the purpose of local development, copy or use the <api-layer-repository>/keystore/localhost.truststore.p12 in your service without generating a new certificate.

2. Update the configuration of your service application.yml to contain the HTTPS configuration by adding the following code:

```
server:
  ssl:
    protocol: TLSv1.2
    ciphers:
      TLS_RSA_WITH_AES_128_CBC_SHA,TLS_DHE_RSA_WITH_AES_256_CBC_SHA,TLS_ECDH_RSA_WITH_AES_
      keyAlias: localhost
      keyPassword: password
      keyStore: keystore/localhost.keystore.p12
      keyStoreType: PKCS12
      keyStorePassword: password
      trustStore: keystore/localhost.truststore.p12
      trustStoreType: PKCS12
      trustStorePassword: password
eureka:
  instance:
    nonSecurePortEnabled: false
    securePortEnabled: true
```

**Note:** You need to define both keystore and truststore even if your server is not using HTTPS port.

### Externalize API ML configuration parameters

The following list summarizes the API ML parameters that are set by the customer system administrator:

- mfaas.discovery.enabled: \${environment.discoveryEnabled:true}
- mfaas.discovery.locations: \${environment.discoveryLocations}
- mfaas.discovery.serviceID: \${environment.serviceId}
- mfaas.discovery.info.serviceTitle: \${environment.serviceTitle}
- mfaas.discovery.info.description: \${environment.serviceDescription}
- mfaas.service.hostname: \${environment.hostname}
- mfaas.service.ipAddress: \${environment.ipAddress}
- mfaas.server.port: \${environment.port}

**Tip:** Spring Boot applications are configured in the application.yml and bootstrap.yml files that are located in the USS file system. However, system administrators prefer to provide configuration through the mainframe sequential data set (or PDS member). To override Java values, use Spring Boot with an external YML file, environment variables, and Java System properties. For Zowe API Mediation Layer applications, we recommend that you use Java System properties.

Java System properties are defined using -D options for Java. Java System properties can override any configuration. Those properties that are likely to change are defined as \${environment.variableName} :

```
IJO="$IJO -Denvironment.discoveryEnabled=.."
IJO="$IJO -Denvironment.discoveryLocations=.."

IJO="$IJO -Denvironment.serviceId=.."
IJO="$IJO -Denvironment.serviceTitle=.."
IJO="$IJO -Denvironment.serviceDescription=.."
IJO="$IJO -Denvironment.hostname=.."
IJO="$IJO -Denvironment.ipAddress=.."
IJO="$IJO -Denvironment.port=.."
```

The `discoveryLocations` (public URL of the discovery service) value is found in the API Meditation Layer configuration, in the `*.PARMLIB(MASxPRM)` member and assigned to the `MFS_EUREKA` variable.

#### **Example:**

```
MFS_EUREKA="http://eureka:password@141.202.65.33:10011/eureka/" )
```

#### **Test your service**

To test that your API instance is working and is discoverable, use the following validation tests:

##### **Validate that your API instance is still working**

###### **Follow these steps:**

1. Disable discovery by setting `discoveryEnabled=false` in your API service instance configuration.
2. Run your tests to check that they are working as before.

##### **Validate that your API instance is discoverable**

###### **Follow these steps:**

1. Point your configuration of API instance to use the following Discovery Service:

```
http://eureka:password@localhost:10011/eureka
```

2. Start up the API service instance.
3. Check that your API service instance and each of its endpoints are displayed in the API Catalog

```
https://localhost:10010/ui/v1/caapicatalog/
```

4. Check that you can access your API service endpoints through the Gateway.

###### **Example:**

```
https://localhost:10010/api/v1/
```

5. Check that you can still access your API service endpoints directly outside of the Gateway.

#### **Review the configuration examples of the discoverable client**

Refer to the [Discoverable Client API Sample Service](#) in the API ML git repository.

## **Java REST APIs service without Spring Boot**

As an API developer, use this guide to onboard a Java REST API service that is built without Spring Boot with the Zowe API Mediation Layer. This article outlines a step-by-step process to onboard a Java REST API application with the API Mediation Layer. More detail about each of these steps is described later in this article.

###### **Follow these steps:**

1. [Get enablers from the Artifactory](#) on page 147
  - [Gradle guide](#) on page 147
  - [Maven guide](#) on page 148
2. [\(Optional\) Add Swagger API documentation to your project](#) on page 148
3. [Add endpoints to your API for API Mediation Layer integration](#) on page 150
4. [Add configuration for Discovery client](#) on page 150
5. [Add a context listener](#) on page 154
  - a. [Add a context listener class](#) on page 154
  - b. [Register a context listener](#) on page 155
6. [Run your service](#) on page 156
7. [\(Optional\) Validate discovery of the API service by the Discovery Service](#) on page 156

## Notes:

- This onboarding procedure uses the Spring framework for implementation of a REST API service, and describes how to generate Swagger API documentation using a Springfox library.
- If you use another framework that is based on a Servlet API, you can use `ServletContextListener` that is described later in this article.
- If you use a framework that does not have a `ServletContextListener` class, see the [Add a context listener](#) on page 154 section in this article for details about how to register and unregister your service with the API Mediation Layer.

## Prerequisites

- Ensure that your REST API service that is written in Java.
- Ensure that your service has an endpoint that generates Swagger documentation.

### Get enablers from the Artifactory

The first step to onboard a Java REST API into the Zowe ecosystem is to get enabler annotations from the Artifactory. Enablers prepare your service for discovery in the API Mediation Layer and for the retrieval of Swagger documentation.

You can use either Gradle or Maven build automation systems.

#### Gradle guide

Use the following procedure if you use Gradle as your build automation system.

##### Follow these steps:

1. Create a `gradle.properties` file in the root of your project.
2. In the `gradle.properties` file, set the following URL of the repository. Use the values provided in the following code block for user credentials to access the Artifactory:

```
# Repository URL for getting the enabler-java artifact
artifactoryMavenRepo=https://gizaartifactory.jfrog.io/gizaartifactory/
libs-release

# Artifactory credentials for builds:
mavenUser=apilayer-build
mavenPassword=lHj7sjJmAxL5k7obuf800f+tCLQYZPMVpDob5oJG1NI=
```

This file specifies the URL of the repository of the Artifactory. The enabler-java artifacts are downloaded from this repository.

3. Add the following Gradle code block to the `build.gradle` file:

```
ext.mavenRepository = {
    maven {
        url artifactoryMavenSnapshotRepo
        credentials {
            username mavenUser
            password mavenPassword
        }
    }
}

repositories mavenRepositories
```

The `ext` object declares the `mavenRepository` property. This property is used as the project repository.

- In the same `build.gradle` file, add the following code to the dependencies code block to add the enabler-java artifact as a dependency of your project:

```
compile(group: 'com.ca.mfaas.sdk', name: 'mfaas-integration-enabler-java', version: '1.1.2')
```

- In your project directory, run the `gradle build` command to build your project.

## Maven guide

Use the following procedure if you use Maven as your build automation system.

### Follow these steps:

- Add the following `xml` tags within the newly created `pom.xml` file:

```
<repositories>
  <repository>
    <id>libs-release</id>
    <name>libs-release</name>
    <url>https://gizaartifactory.jfrog.io/gizaartifactory/libs-release</url>
    <snapshots>
      <enabled>false</enabled>
    </snapshots>
  </repository>
</repositories>
```

This file specifies the URL of the repository of the Artifactory where you download the enabler-java artifacts.

- In the same `pom.xml` file, copy the following `xml` tags to add the enabler-java artifact as a dependency of your project:

```
<dependency>
  <groupId>com.ca.mfaas.sdk</groupId>
  <artifactId>mfaas-integration-enabler-java</artifactId>
  <version>1.1.2</version>
</dependency>
```

- Create a `settings.xml` file and copy the following `xml` code block which defines the credentials for the Artifactory:

```
<?xml version="1.0" encoding="UTF-8"?>

<settings xmlns="http://maven.apache.org/SETTINGS/1.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/SETTINGS/1.0.0
    https://maven.apache.org/xsd/settings-1.0.0.xsd">
  <servers>
    <server>
      <id>libs-release</id>
      <username>apilayer-build</username>
      <password>1Hj7sjJmAxL5k7obuf800f+tCLQYZPMVpDob5oJG1NI=</password>
    </server>
  </servers>
</settings>
```

- Copy the `settings.xml` file inside the `~/.m2/` directory.
- In the directory of your project, run the `mvn package` command to build the project.

## (Optional) Add Swagger API documentation to your project

If your application already has Swagger API documentation enabled, skip this step. Use the following procedure if your application does not have Swagger API documentation.

## Follow these steps:

### 1. Add a Springfox Swagger dependency.

- For Gradle add the following dependency in build.gradle:

```
compile "io.springfox:springfox-swagger2:2.8.0"
```

- For Maven add the following dependency in pom.xml:

```
<dependency>
    <groupId>io.springfox</groupId>
    <artifactId>springfox-swagger2</artifactId>
    <version>2.8.0</version>
</dependency>
```

### 2. Add a Spring configuration class to your project:

```
package com.ca.mfaas.hellospring.configuration;

import org.springframework.context.annotation.Bean;
import org.springframework.context.annotation.Configuration;
import org.springframework.web.servlet.config.annotation.EnableWebMvc;
import
org.springframework.web.servlet.config.annotation.WebMvcConfigurerAdapter;
import springfox.documentation.builders.PathSelectors;
import springfox.documentation.builders.RequestHandlerSelectors;
import springfox.documentation.service.ApiInfo;
import springfox.documentation.service.Contact;
import springfox.documentation.spi.DocumentationType;
import springfox.documentation.spring.web.plugins.Docket;
import springfox.documentation.swagger2.annotations.EnableSwagger2;

import java.util.ArrayList;

@Configuration
@EnableSwagger2
@EnableWebMvc
public class SwaggerConfiguration extends WebMvcConfigurerAdapter {
    @Bean
    public Docket api() {
        return new Docket(DocumentationType.SWAGGER_2)
            .select()
            .apis(RequestHandlerSelectors.any())
            .paths(PathSelectors.any())
            .build()
            .apiInfo(new ApiInfo(
                "Spring REST API",
                "Example of REST API",
                "1.0.0",
                null,
                null,
                null,
                new ArrayList<>()
            ));
    }
}
```

### 3. Customize this configuration according to your specifications. For more information about customization properties, see [Springfox documentation](#).

## Add endpoints to your API for API Mediation Layer integration

To integrate your service with the API Mediation Layer, add the following endpoints to your application:

- **Swagger documentation endpoint**

The endpoint for the Swagger documentation.

- **Health endpoint**

The endpoint used for health checks by the Discovery Service.

- **Info endpoint**

The endpoint to get information about the service.

The following java code is an example of these endpoints added to the Spring Controller:

**Example:**

```
package com.ca.mfaas.hellospring.controller;

import com.ca.mfaas.eurekaservice.model.*;
import org.springframework.stereotype.Controller;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.ResponseBody;
import springfox.documentation.annotations.ApiIgnore;

@Controller
@ApiIgnore
public class MfaasController {

    @GetMapping("/api-doc")
    public String apiDoc() {
        return "forward:/v2/api-docs";
    }

    @GetMapping("/application/health")
    public @ResponseBody Health getHealth() {
        return new Health("UP");
    }

    @GetMapping("/application/info")
    public @ResponseBody ResponseEntity<EmptyJsonResponse>
    getDiscoveryInfo() {
        HttpHeaders headers = new HttpHeaders();
        headers.add("Content-Type", "application/json");
        return new ResponseEntity(new EmptyJsonResponse(), headers,
        HttpStatus.OK);
    }
}
```

## Add configuration for Discovery client

After you add API Mediation Layer integration endpoints, you are ready to add service configuration for Discovery client.

**Follow these steps:**

1. Create the file `service-configuration.yml` in your resources directory.
2. Add the following configuration to your `service-configuration.yml`:

```
serviceId: hellospring
title: HelloWorld Spring REST API
description: POC for exposing a Spring REST API
baseUrl: http://localhost:10020/hellospring
homePageRelativeUrl:
```

```

statusPageRelativeUrl: /application/info
healthCheckRelativeUrl: /application/health
discoveryServiceUrls:
  - http://eureka:password@localhost:10011/eureka
routes:
  - gatewayUrl: api/v1
    serviceUrl: /hellospring/api/v1
apiInfo:
  - apiId: ${mfaas.discovery.serviceId}
    gatewayUrl: api/v1
    swaggerUrl: ${mfaas.server.scheme}://${mfaas.service.hostname}:
${mfaas.server.port}${mfaas.server.contextPath}/api-doc
    documentationUrl: https://docs.zowe.org
catalogUiTile:
  id: helloworld-spring
  title: Hello World Spring REST API
  description: Proof of Concept application to demonstrate exposing a
REST API in the MFaaS ecosystem
  version: 1.0.0

```

### 3. Customize your configuration parameters to correspond with your API service specifications.

The following list describes the configuration parameters:

- **serviceId**

Specifies the service instance identifier that is registered in the API Mediation Layer installation. The service ID is used in the URL for routing to the API service through the gateway. The service ID uniquely identifies

instances of a microservice in the API Mediation Layer. The system administrator at the customer site defines this parameter.

**Important!** Ensure that the service ID is set properly with the following considerations:

- When two API services use the same service ID, the API Gateway considers the services to be clones. An incoming API request can be routed to either of them.
- The same service ID should be set only for multiple API service instances for API scalability.
- The service ID value must contain only lowercase alphanumeric characters.
- The service ID cannot contain more than 40 characters.
- The service ID is linked to security resources. Changes to the service ID require an update of security resources.

**Examples:**

- If the customer system administrator sets the service ID to `sysviewlpr1`, the API URL in the API Gateway appears as the following URL:

```
https://gateway:port/api/v1/sysviewlpr1/endpoint1/...
```

- If a customer system administrator sets the service ID to `vantageprod1`, the API URL in the API Gateway appears as the following URL:

```
http://gateway:port/api/v1/vantageprod1/endpoint1/...
```

- **title**

Specifies the human readable name of the API service instance (for example, "Endevor Prod" or "Sysview LPAR1"). This value is displayed in the API Catalog when a specific API service instance is selected. This parameter is externalized and set by the customer system administrator.

**Tip:** We recommend that you provide a specific default value of the `title`. Use a title that describes the service instance so that the end user knows the specific purpose of the service instance.

- **description**

Specifies a short description of the API service.

**Example:** "CA Endevor SCM - Production Instance" or "CA SYSVIEW running on LPAR1".

This value is displayed in the API Catalog when a specific API service instance is selected. This parameter is externalized and set by the customer system administrator.

**Tip:** Describe the service so that the end user knows the function of the service.

- **baseUrl**

Specifies the URL to your service to the REST resource. It will be the prefix for the following URLs:

- `homePageRelativeUrl`
- `statusPageRelativeUrl`
- `healthCheckRelativeUrl`.

**Examples:**

- `http://host:port/servicename` for HTTP service
- `https://host:port/servicename` for HTTPS service

- **homePageRelativeUrl**

Specifies the relative path to the home page of your service. The path should start with `/`. If your service has no home page, leave this parameter blank.

**Examples:**

- `homePageRelativeUrl: The service has no home page`
- `homePageRelativeUrl: / The service has home page with URL ${baseUrl} /`

- **statusPageRelativeUrl**

Specifies the relative path to the status page of your service. This is the endpoint that you defined in the `MfaasController` controller in the `getDiscoveryInfo` method. Start this path with `/`.

**Example:**

- `statusPageRelativeUrl: /application/info` the result URL will be  `${baseUrl} /application/info`

- **healthCheckRelativeUrl**

Specifies the relative path to the health check endpoint of your service. This is the endpoint that you defined in the `MfaasController` controller in the `getHealth` method. Start this URL with `/`.

**Example:**

- `healthCheckRelativeUrl: /application/health`. This results in the URL:  `${baseUrl} /application/health`

- **discoveryServiceUrls**

Specifies the public URL of the Discovery Service. The system administrator at the customer site defines this parameter.

**Example:**

- `http://eureka:password@141.202.65.33:10311/eureka/`

- **routedServices**

The routing rules between the gateway service and your service.

- **routedServices.gatewayUrl**

Both gateway-url and service-url parameters specify how the API service endpoints are mapped to the API gateway endpoints. The gateway-url parameter sets the target endpoint on the gateway.

- **routedServices.serviceUrl**

Both gateway-url and service-url parameters specify how the API service endpoints are mapped to the API gateway endpoints. The service-url parameter points to the target endpoint on the gateway.

- **apiInfo.apiId**

Specifies the API identifier that is registered in the API Mediation Layer installation. The API ID uniquely identifies the API in the API Mediation Layer. The same API can be provided by multiple services. The API ID can be used to locate the same APIs that are provided by different services. The creator of the API defines

this ID. The API ID needs to be a string of up to 64 characters that uses lowercase alphanumeric characters and a dot: ... We recommend that you use your organization as the prefix.

- **apiInfo.gatewayUrl**

The base path at the API Gateway where the API is available. Ensure that this is the same path as the *gatewayUrl* value in the *routes* sections.

- **apiInfo.swaggerUrl**

(Optional) Specifies the HTTP or HTTPS address where the Swagger JSON document is available.

- **apiInfo.documentationUrl**

(Optional) Link to external documentation, if needed. The link to the external documentation can be included along with the Swagger documentation.

- **catalogUiTile.id**

Specifies the unique identifier for the API services product family. This is the grouping value used by the API Mediation Layer to group multiple API services together into "tiles". Each unique identifier represents a single API Catalog UI dashboard tile. Specify a value that does not interfere with API services from other products.

- **catalogUiTile.title**

Specifies the title of the API services product family. This value is displayed in the API catalog UI dashboard as the tile title.

- **catalogUiTile.description**

Specifies the detailed description of the API services product family. This value is displayed in the API catalog UI dashboard as the tile description.

- **catalogUiTile.version**

Specifies the semantic version of this API Catalog tile. Increase the number of the version when you introduce new changes to the product family details of the API services including the title and description.

## Add a context listener

The context listener invokes the `apiMediationClient.register(config)` method to register the application with the API Mediation Layer when the application starts. The context listener also invokes the `apiMediationClient.unregister()` method before the application shuts down to unregister the application in API Mediation Layer.

**Note:** If you do not use a Java Servlet API based framework, you can still call the same methods for `apiMediationClient` to register and unregister your application.

## Add a context listener class

Add the following code block to add a context listener class:

```
package com.ca.mfaas.hellospring.listener;

import com.ca.mfaas.eurekaservice.client.ApiMediationClient;
import com.ca.mfaas.eurekaservice.client.config.ApiMediationServiceConfig;
import com.ca.mfaas.eurekaservice.client.impl.ApiMediationClientImpl;
import
com.ca.mfaas.eurekaservice.client.util.ApiMediationServiceConfigReader;

import javax.servlet.ServletContextEvent;
import javax.servlet.ServletContextListener;

public class ApiDiscoveryListener implements ServletContextListener {
    private ApiMediationClient apiMediationClient;

    @Override
    public void contextInitialized(ServletContextEvent sce) {
        apiMediationClient = new ApiMediationClientImpl();
```

```

        String configurationFile = "/service-configuration.yml";
        ApiMediationServiceConfig config = new
        ApiMediationServiceConfigReader(configurationFile).readConfiguration();
        apiMediationClient.register(config);
    }

    @Override
    public void contextDestroyed(ServletContextEvent sce) {
        apiMediationClient.unregister();
    }
}

```

## Register a context listener

Register a context listener to start Discovery client. Add the following code block to the deployment descriptor web.xml to register a context listener:

```

<listener>
    <listener-class>com.ca.mfaas.hellospring.listener.ApiDiscoveryListener</
    listener-class>
</listener>

```

## Setup key store with the service certificate

All API services require a certificate that is trusted by API Mediation Layer in order to register with it.

### Follow these steps:

1. Follow instructions at [Generating certificate for a new service on localhost](#)

If the service runs on localhost, the command uses the following format:

```

<api-layer-repository>/scripts/apiml_cm.sh --action new-service --service-
alias localhost --service-ext SAN=dns:localhost.localdomain,dns:localhost
--service-keystore keystore/localhost.keystore.p12 --service-truststore
keystore/localhost.truststore.p12 --service-dname "CN=Sample REST API
Service, OU=Mainframe, O=Zowe, L=Prague, S=Prague, C=Czechia" --service-
password password --service-validity 365 --local-ca-filename <api-layer-
repository>/keystore/local_ca/localca

```

Alternatively, copy or use the <api-layer-repository>/keystore/localhost.truststore.p12 in your service without generating a new certificate, for local development.

2. Update the configuration of your service service-configuration.yml to contain the HTTPS configuration by adding the following code:

```

ssl:
    protocol: TLSv1.2
    ciphers:
        TLS_RSA_WITH_AES_128_CBC_SHA,TLS_DHE_RSA_WITH_AES_256_CBC_SHA,TLS_ECDH_RSA_WITH_AES_
        keyAlias: localhost
        keyPassword: password
        keyStore: keystore/localhost.keystore.p12
        keyStoreType: PKCS12
        keyStorePassword: password
        trustStore: keystore/localhost.truststore.p12
        trustStoreType: PKCS12
        trustStorePassword: password
eureka:
    instance:
        nonSecurePortEnabled: false
        securePortEnabled: true

```

**Note:** You need to define both key store and trust store even if your server is not using HTTPS port.

## Run your service

After you add all configurations and controllers, you are ready to run your service in the API Mediation Layer ecosystem.

### Follow these steps:

1. Run the following services to onboard your application:

- Gateway Service
- Discovery Service
- API Catalog Service

**Tip:** For more information about how to run the API Mediation Layer locally,

see [Running the API Mediation Layer on Local Machine](#).

2. Run your Java application.

**Tip:** Wait for the Discovery Service to discover your service. This process may take a few minutes.

3. Go to the following URL to reach the API Catalog through the Gateway (port 10010):

```
https://localhost:10010/ui/v1/apicatalog/
```

You successfully onboarded your Java application with the API Mediation Layer if your service is running and you can access the API documentation.

### (Optional) Validate discovery of the API service by the Discovery Service

If your service is not visible in the API Catalog, you can check if your service is discovered by the Discovery Service.

### Follow these steps:

1. Go to `http://localhost:10011`.
2. Enter `eureka` as a username and `password` as a password.
3. Check if your application appears in the Discovery Service UI.

If your service appears in the Discovery Service UI but is not visible in the API Catalog, check to ensure that your configuration settings are correct.

## Java Jersey REST APIs

As an API developer, use this guide to onboard your Java Jersey REST API service into the Zowe API Mediation Layer. This article outlines a step-by-step process to make your API service available in the API Mediation Layer.

The following procedure is an overview of steps to onboard a Java Jersey REST API application with the API Mediation Layer.

### Follow these steps:

1. [Get enablers from the Artifactory](#) on page 156
2. [Add API ML Onboarding Configuration](#) on page 158
3. [Externalize parameters](#) on page 166
4. [Download Apache Tomcat and enable SSL](#) on page 168
5. [Run your service](#) on page 168

### Get enablers from the Artifactory

The first step to onboard a Java Jersey REST API into the Zowe ecosystem is to get enabler annotations from the Artifactory. Enablers prepare your service for discovery and for the retrieval of Swagger documentation.

You can use either Gradle or Maven build automation systems.

#### Gradle guide

Use the following procedure if you use Gradle as your build automation system.

**Tip:** To migrate from Maven to Gradle, go to your project directory and run `gradle init`. This converts the Maven build to a Gradle build by generating a `setting.gradle` file and a `build.gradle` file.

#### Follow these steps:

1. Create a `gradle.properties` file in the root of your project.
2. In the `gradle.properties` file, set the following URL of the repository and customize the values of your credentials to access the repository.

```
# Repository URL for getting the enabler-jersey artifact (`integration-enabler-java`)
artifactoryMavenRepo=https://gizaartifactory.jfrog.io/gizaartifactory/libs-release

# Artifactory credentials for builds:
mavenUser=apilayer-build
mavenPassword=lHj7sjJmAxL5k7obuf80Of+tCLQYZPMVpDob5oJG1NI=
```

This file specifies the URL for the repository of the Artifactory. The enabler-jersey artifact is downloaded from this repository.

3. Add the following Gradle code block to the `build.gradle` file:

```
ext.mavenRepository = {
    maven {
        url artifactoryMavenSnapshotRepo
        credentials {
            username mavenUser
            password mavenPassword
        }
    }
}

repositories mavenRepositories
```

The `ext` object declares the `mavenRepository` property. This property is used as the project repository.

4. In the same `build.gradle` file, add the following code to the dependencies code block to add the enabler-jersey artifact as a dependency of your project:

```
compile(group: 'com.ca.mfaas.sdk', name: 'mfaas-integration-enabler-java', version: '1.1.0')
```

5. In your project directory, run the `gradle build` command to build your project.

#### Maven guide

Use the following procedure if you use Maven as your build automation system.

**Tip:** To migrate from Gradle to Maven, go to your project directory and run `gradle install`. This command automatically generates a `pom-default.xml` inside the `build/poms` subfolder where all of the dependencies are contained.

#### Follow these steps:

1. Add the following `xml` tags within the newly created `pom.xml` file:

```
<repositories>
    <repository>
        <id>libs-release</id>
        <name>libs-release</name>
        <url>https://gizaartifactory.jfrog.io/gizaartifactory/libs-release</url>
        <snapshots>
            <enabled>false</enabled>
```

```

    </snapshots>
  </repository>
</repositories>
```

This file specifies the URL for the repository of the Artifactory where you download the enabler-jersey artifact.

2. In the same file, copy the following *xml* tags to add the enabler-jersey artifact as a dependency of your project:

```

<dependency>
  <groupId>com.ca.mfaas.sdk</groupId>
  <artifactId>mfaas-integration-enabler-java</artifactId>
  <version>1.1.0</version>
</dependency>
```

3. Create a *settings.xml* file and copy the following *xml* code block which defines the credentials for the Artifactory:

```

<?xml version="1.0" encoding="UTF-8"?>

<settings xmlns="http://maven.apache.org/SETTINGS/1.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/SETTINGS/1.0.0
                      https://maven.apache.org/xsd/settings-1.0.0.xsd">
  <servers>
    <server>
      <id>libs-release</id>
      <username>apilayer-build</username>
      <password>lHj7sjJmAxL5k7obuf800f+tCLQYZPMVpDob5oJG1NI=</password>
    </server>
  </servers>
</settings>
```

4. Copy the *settings.xml* file inside  `${user.home} / .m2/` directory.
5. In the directory of your project, run the mvn package command to build the project.

## Add API ML Onboarding Configuration

As an API service developer, you set multiple configuration settings in your application.yml that correspond to the API ML. These settings enable an API to be discoverable and included in the API catalog. Some of the settings in the application.yml are internal and are set by the API service developer. Some settings are externalized and set by the customer system administrator. Those external settings are service parameters and are in the format:  `${environment.*}`.

**Important!** Spring Boot configuration can be externalized in multiple ways. For more information see: [Externalized configuration](#). This Zowe onboarding documentation applies to API services that use an application.yml file for configuration. If your service uses a different configuration option, transform the provided configuration sample to the format that your API service uses.

**Tip:** For information about how to set your configuration when running a Spring Boot application under an external servlet container (TomCat), see the following short stackoverflow article: [External configuration for spring-boot application](#).

### Follow these steps:

1. Add the following #MFAAS configuration section in your application.yml:

```

#####
# MFAAS configuration section
#####
mfaas:
  discovery:
    serviceId: ${environment.serviceId}
    locations: ${environment.discoveryLocations}
```

```

        enabled: ${environment.discoveryEnabled:true}
        endpoints:
            statusPage: ${mfaas.server.scheme}://${mfaas.service.hostname}:${mfaas.server.port}${mfaas.server.contextPath}/application/info
            healthPage: ${mfaas.server.scheme}://${mfaas.service.hostname}:${mfaas.server.port}${mfaas.server.contextPath}/application/health
            homepage: ${mfaas.server.scheme}://${mfaas.service.hostname}:${mfaas.server.port}${mfaas.server.contextPath}/info:
                serviceTitle: ${environment.serviceTitle}
                description: ${environment.serviceDescription}
                # swaggerLocation:
resource_location_of_your_static_swagger_doc.json
    fetchRegistry: false
    region: default
    service:
        hostname: ${environment.hostname}
        ipAddress: ${environment.ipAddress}
    catalog-ui-tile:
        id: yourProductFamilyId
        title: Your API service product family title in the API catalog dashboard tile
        description: Your API service product family description in the API catalog dashboard tile
        version: 1.0.0
    server:
        scheme: http
        port: ${environment.port}
        contextPath: /yourServiceUrlPrefix

eureka:
    instance:
        appname: ${mfaas.discovery.serviceId}
        hostname: ${mfaas.service.hostname}
        statusPageUrlPath: ${mfaas.discovery.endpoints.statusPage}
        healthCheckUrl: ${mfaas.discovery.endpoints.healthPage}
        homePageUrl: ${mfaas.discovery.endpoints.homePage}
        metadata-map:
            routed-services:
                api_v1:
                    gateway-url: "api/v1"
                    service-url: ${mfaas.server.contextPath}
            apiml:
                apiInfo:
                    - apiId: ${mfaas.discovery.serviceId}
                      gatewayUrl: api/v1
                      swaggerUrl: ${mfaas.server.scheme}://${mfaas.service.hostname}:${mfaas.server.port}${mfaas.server.contextPath}/api-doc
                        documentationUrl: https://www.zowe.org
            mfaas:
                api-info:
                    apiVersionProperties:
                        v1:
                            title: Your API title for swagger JSON which is displayed in API Catalog / service / API Information
                            description: Your API description for swagger JSON
                            version: 1.0.0
                            basePackage:
                                your.service.base.package.for.swagger.annotated.controllers

```

```

# apiPattern: /v1/.* # alternative to
basePackage for exposing endpoints which match the regex pattern to
swagger JSON
discovery:
    catalogUiTile:
        id: ${mfaas.catalog-ui-tile.id}
        title: ${mfaas.catalog-ui-tile.title}
        description: ${mfaas.catalog-ui-
tile.description}
        version: ${mfaas.catalog-ui-tile.version}
enableApiDoc:
${mfaas.discovery.info.enableApiDoc:true}
service:
    title: ${mfaas.discovery.info.serviceTitle}
    description: ${mfaas.discovery.info.description}
client:
    enabled: ${mfaas.discovery.enabled}
    healthcheck:
        enabled: true
    serviceUrl:
        defaultZone: ${mfaas.discovery.locations}
        fetchRegistry: ${mfaas.discovery.fetchRegistry}
        region: ${mfaas.discovery.region}

#####
# Application configuration section
#####
server:
    # address: ${mfaas.service.ipAddress}
    port: ${mfaas.server.port}
    servlet:
        contextPath: ${mfaas.server.contextPath}

spring:
    application:
        name: ${mfaas.discovery.serviceId}

```

In order to run your application locally, you need to define variables used under the environment group.

```

#####
# Local configuration section
#####
environment:
    serviceId: Your service id
    serviceTitle: Your service title
    serviceDescription: Your service description
    discoveryEnabled: true
    hostname: localhost
    port: Your service port
    discoveryLocations: https://localhost:10011/eureka/
    ipAddress: 127.0.0.1

```

**Important:** Add this configuration also to the `application.yml` used for testing. Failure to add this configuration to the `application.yml` will cause your tests to fail.

2. Change the MFaaS parameters to correspond with your API service specifications. Most of these internal parameters contain "your service" text.

**Note:** \${mfaas.\*} variables are used throughout the application.yml sample to reduce the number of required changes.

**Tip:** When existing parameters set by the system administrator are already present in your configuration file (for example, hostname, address, contextPath, and port), we recommend that you replace them with the corresponding MFaaS properties.

#### a. Discovery Parameters

- **mfaas.discovery.serviceId**

Specifies the service instance identifier to register in the API ML installation. The service ID is used in the URL for routing to the API service through the gateway. The service ID uniquely identifies instances of a microservice in the API ML. The system administrator at the customer site defines this parameter.

**Important!** Ensure that the service ID is set properly with the following considerations:

- When two API services use the same service ID, the API Gateway considers the services to be clones. An incoming API request can be routed to either of them.
- The same service ID should be set for only multiple API service instances for API scalability.
- The service ID value must contain only lowercase alphanumeric characters.
- The service ID cannot contain more than 40 characters.
- The service ID is linked to security resources. Changes to the service ID require an update of security resources.
- The service ID must match the spring.application.name parameter.

#### Examples:

- If the customer system administrator sets the service ID to sysviewlpr1, the API URL in the API Gateway appears as the following URL:

```
https://gateway:port/api/v1/sysviewlpr1/endpoint1/...
```

- If the customer system administrator sets the service ID to vantageprod1, the API URL in the API Gateway appears as the following URL:

```
http://gateway:port/api/v1/vantageprod1/endpoint1/...
```

- **mfaas.discovery.locations**

Specifies the public URL of the Discovery Service. The system administrator at the customer site defines this parameter.

#### Example:

```
http://eureka:password@141.202.65.33:10311/eureka/
```

- **mfaas.discovery.enabled**

Specifies whether the API service instance is to be discovered in the API ML. The system administrator at the customer site defines this parameter. Set this parameter to true if the API ML is installed and configured. Otherwise, you can set this parameter to false to exclude an API service instances from the API ML.

- **mfaas.discovery.fetchRegistry**

Specifies whether the API service is to receive regular update notifications from the discovery service. Under most circumstances, you can accept the default value of false for the parameter.

- **mfaas.discovery.region**

Specifies the geographical region. This parameter is required by the Discovery client. Under most circumstances you can accept the value default for the parameter.

## b. Service and Server Parameters

- **mfaas.service.hostname**

Specifies the hostname of the system where the API service instance runs. This parameter is externalized and is set by the customer system administrator. The administrator ensures the hostname can be resolved by DSN to the IP address that is accessible by applications running on their z/OS systems.

- **mfaas.service.ipAddress**

Specifies the local IP address of the system where the API service instance runs. This IP address may or may not be a public IP address. This parameter is externalized and set by the customer system administrator.

- **mfaas.server.scheme**

Specifies whether the API service is using the HTTPS protocol. This value can be set to https or http depending on whether your service is using SSL.

- **mfaas.server.port**

Specifies the port that is used by the API service instance. This parameter is externalized and set by the customer system administrator.

- **mfaas.server.contextPath**

Specifies the prefix that is used within your API service URL path.

**Examples:**

- If your API service does not use an extra prefix in the URL (for example, http://host:port/endpoint1/), set this value to /.
- If your API service uses an extra URL prefix set the parameter to that prefix value. For the URL: http://host:port/filemaster/endpoint1/, set this parameter to /filemaster.
- In both examples, the API service URL appears as the following URL when routed through the Gateway:

```
http://gateway:port/serviceId/endpoint1/
```

## c. API Catalog Parameters

These parameters are used to populate the API Catalog. The API Catalog contains information about every registered API service. The Catalog also groups related APIs. Each API group has its own name and description.

Catalog groups are constructed in real-time based on information that is provided by the API services. Each group is displayed as a tile in the API Catalog UI dashboard.

- **mfaas.catalog-ui-tile.id**

Specifies the unique identifier for the API services product family. This is the grouping value used by the API ML to group multiple API services together into "tiles". Each unique identifier represents a single API Catalog UI dashboard tile. Specify a value that does not interfere with API services from other products.

- **mfaas.catalog-ui-tile.title**

Specifies the title of the API services product family. This value is displayed in the API Catalog UI dashboard as the tile title

- **mfaas.catalog-ui-tile.description**

Specifies the detailed description of the API services product family. This value is displayed in the API Catalog UI dashboard as the tile description

- **mfaas.catalog-ui-tile.version**

Specifies the semantic version of this API Catalog tile. Increase the version when you introduce new changes to the API services product family details (title and description).

- **mfaas.discovery.info.serviceTitle**

Specifies the human readable name of the API service instance (for example, "Endevor Prod" or "Sysview LPAR1"). This value is displayed in the API Catalog when a specific API service instance is selected. This parameter is externalized and set by the customer system administrator.

## API Catalog - Available

MFaaS Microservice to locate and display API documentation for MFaaS discovered microservices

**Tip:** We recommend that you provide a good default value or give good naming examples to the customers.

- **mfaas.discovery.info.description**

Specifies a short description of the API service.

**Example:** "CA Endevor SCM - Production Instance" or "CA SYSVIEW running on LPAR1". This value is displayed in the API Catalog when a specific API service instance is selected. This parameter is externalized and set by the customer system administrator.

**Tip:** We recommend that you provide a good default value or give good naming examples to the customers. Describe the service so that the end user knows the function of the service.

- **mfaas.discovery.info.swaggerLocation**

Specifies the location of a static swagger document. The JSON document contained in this file is displayed instead of the automatically generated API documentation. The JSON file must contain a valid OpenAPI 2.x Specification document. This value is optional and commented out by default.

**Note:** Specifying a `swaggerLocation` value disables the automated JSON API documentation generation with the SpringFox library. By disabling auto-generation, you need to keep the contents of the manual swagger

definition consistent with your endpoints. We recommend to use auto-generation to prevent incorrect endpoint definitions in the static swagger documentation.

#### d. Metadata Parameters

The routing rules can be modified with parameters in the metadata configuration code block.

**Note:** If your REST API does not conform to Zowe API Mediation layer REST API Building codes, configure routing to transform your actual endpoints (serviceUrl) to gatewayUrl format. For more information see: [REST API Building Codes](#)

- `eureka.instance.metadata-map.routed-services.<prefix>`

Specifies a name for routing rules group. This parameter is only for logical grouping of further parameters. You can specify an arbitrary value but it is a good development practice to mention the group purpose in the name.

#### Examples:

```
api_v1
api_v2
```

- `eureka.instance.metadata-map.routed-services.<prefix>.gatewayUrl`

Both gateway-url and service-url parameters specify how the API service endpoints are mapped to the API gateway endpoints. The gateway-url parameter sets the target endpoint on the gateway.

- `metadata-map.routed-services.<prefix>.serviceUrl`

Both gateway-url and service-url parameters specify how the API service endpoints are mapped to the API gateway endpoints. The service-url parameter points to the target endpoint on the gateway.

- `eureka.instance.metadata-map.apiml.apiInfo.apiId`

Specifies the API identifier that is registered in the API Mediation Layer installation. The API ID uniquely identifies the API in the API Mediation Layer. The same API can be provided by multiple services. The API ID can be used to locate the same APIs that are provided by different services. The creator of the API defines this ID. The API ID needs to be a string of up to 64 characters that uses lowercase alphanumeric characters and a dot: ... We recommend that you use your organization as the prefix.

- `eureka.instance.metadata-map.apiml.apiInfo.gatewayUrl`

The base path at the API gateway where the API is available. Ensure that it is the same path as the *gatewayUrl* value in the *routes* sections.

- `eureka.instance.metadata-map.apiml.apiInfo.documentationUrl`

(Optional) Link to external documentation, if needed. The link to the external documentation can be included along with the Swagger documentation.

- `eureka.instance.metadata-map.apiml.apiInfo.swaggerUrl`

(Optional) Specifies the HTTP or HTTPS address where the Swagger JSON document is available. **Important!** Ensure that each of the values for gatewayUrl parameter are unique in the configuration. Duplicate gatewayUrl values may cause requests to be routed to the wrong service URL.

**Note:** The endpoint /api-doc returns the API service Swagger JSON. This endpoint is introduced by the `@EnableMfaasInfo` annotation and is utilized by the API Catalog.

#### e. Swagger Api-Doc Parameters

Configures API Version Header Information, specifically the [InfoObject](#) section, and adjusts Swagger documentation that your API service returns. Use the following format:

```
api-info:
  apiVersionProperties:
    v1:
      title: Your API title for swagger JSON which is displayed in API Catalog / service / API Information
```

```

description: Your API description for swagger JSON
version: 1.0.0
basePackage:
your.service.base.package.for.swagger.annotated.controllers
# apiPattern: /v1/.* # alternative to basePackage for exposing
endpoints which match the regex pattern to swagger JSON

```

The following parameters describe the function of the specific version of an API. This information is included in the swagger JSON and displayed in the API Catalog:

#### **Title** API Catalog

**Description** This is the REST API for the API Catalog microservice. The API Catalog is one of the API Mediation Layer components. It provides documentation corresponding to a service, service descriptive information, and the current state of the service.

#### **Version** 1.0.0

- **v1**

Specifies the major version of your service API: v1, v2, etc.

- **title**

Specifies the title of your service API.

- **description**

Specifies the high-level function description of your service API.

- **version**

Specifies the actual version of the API in semantic format.

- **basePackage**

Specifies the package where the API is located. This option only exposes endpoints that are defined in a specified java package. The parameters `basePackage` and `apiPattern` are mutually exclusive. Specify only one of them and remove or comment out the second one.

- **apiPattern**

This option exposes any endpoints that match a specified regular expression. The parameters `basePackage` and `apiPattern` are mutually exclusive. Specify just one of them and remove or comment out the second one.

**Tip:** You have three options to make your endpoints discoverable and exposed: `basePackage`, `apiPattern`, or none (if you do not specify a parameter). If `basePackage` or `apiPattern` are not defined, all endpoints in the Spring Boot app are exposed.

### Setup keystore with the service certificate

To register with the API Mediation Layer, a service is required to have a certificate that is trusted by API Mediation Layer.

#### Follow these steps:

1. Follow instructions at [Generating certificate for a new service on localhost](#)

When a service is running on localhost, the command can have the following format:

```

<api-layer-repository>/scripts/apiml_cm.sh --action new-service --service-
alias localhost --service-ext SAN=dns:localhost.localdomain,dns:localhost
--service-keystore keystore/localhost.keystore.p12 --service-truststore
keystore/localhost.truststore.p12 --service-dname "CN=Sample REST API
Service, OU=Mainframe, O=Zowe, L=Prague, S=Prague, C=Czechia" --service-

```

```
password password --service-validity 365 --local-ca-filename <api-layer-repository>/keystore/local_ca/localca
```

Alternatively, for the purpose of local development, copy or use the <api-layer-repository>/keystore/localhost.truststore.p12 in your service without generating a new certificate.

2. Update the configuration of your service application.yml to contain the HTTPS configuration by adding the following code:

```
server:
  ssl:
    protocol: TLSv1.2
    ciphers:
      TLS_RSA_WITH_AES_128_CBC_SHA,TLS_DHE_RSA_WITH_AES_256_CBC_SHA,TLS_ECDH_RSA_WITH_AES_
      keyAlias: localhost
      keyPassword: password
      keyStore: keystore/localhost.keystore.p12
      keyStoreType: PKCS12
      keyStorePassword: password
      trustStore: keystore/localhost.truststore.p12
      trustStoreType: PKCS12
      trustStorePassword: password
eureka:
  instance:
    nonSecurePortEnabled: false
    securePortEnabled: true
```

**Note:** You need to define both keystore and truststore even if your server is not using HTTPS port.

### Externalize parameters

In order to externalize parameters, you have to create a ServletContextListener. To create your own ServletContextListener, register a ServletContextListener and enable it to read all the properties defined inside the .yml file.

#### Follow these steps:

1. Define parameters that you want to externalize in a .yml file. Ensure that this file is placed in the WEB-INF folder located in the module of your service. Check the ApiMediationServiceConfig.java class inside com.ca.mfaas.eurekaservice.client.config package in the integration-enabler-java to see the mapped parameters and make sure that the yml file follows the correct structure. The following example shows the structure of the 'yml' file:

#### Example:

```
serviceId:
eureka:
  hostname:
  ipAddress:
  port:
title:
description:
defaultZone:
baseUrl:
homePageRelativeUrl:
statusPageRelativeUrl:
healthCheckRelativeUrl:
discoveryServiceUrls:

ssl:
  verifySslCertificatesOfServices: true
  protocol: TLSv1.2
  keyAlias: localhost
  keyPassword: password
```

```

keyStore: ./keystore/localhost/localhost.keystore.p12
keyStorePassword: password
keyStoreType: PKCS12
trustStore: ./keystore/localhost/localhost.truststore.p12
trustStorePassword: password
trustStoreType: PKCS12
routes:
  - gatewayUrl:
      serviceUrl:
  - gatewayUrl:
      serviceUrl:
  - gatewayUrl:
      serviceUrl:
  - gatewayUrl:
      serviceUrl:
  - gatewayUrl:
      serviceUrl:
apiInfo:
  - apiId:
      gatewayUrl:
      swaggerUrl:
      documentationUrl:
catalogUiTile:
  id:
  title:
  description:
  version:

```

- Before the web application is started (Tomcat), create a `ServletContextListener` to run the defined code.

**Example:**

```

package com.ca.hwsjersey.listener;

import com.ca.mfaas.eurekaservice.client.ApiMediationClient;
import com.ca.mfaas.eurekaservice.client.config.ApiMediationServiceConfig;
import com.ca.mfaas.eurekaservice.client.impl.ApiMediationClientImpl;
import com.ca.mfaas.eurekaservice.client.util.ApiMediationServiceConfigReader;

import javax.servlet.ServletContextEvent;
import javax.servlet.ServletContextListener;

public class ApiDiscoveryListener implements
ServletContextListener {
    private ApiMediationClient apiMediationClient;

    @Override
    public void contextInitialized(ServletContextEvent sce) {
        apiMediationClient = new ApiMediationClientImpl();
        String configurationFile = "/service-
configuration.yml";
        ApiMediationServiceConfig config = new
        ApiMediationServiceConfigReader(configurationFile).readConfiguration();
        apiMediationClient.register(config);
    }

    @Override
    public void contextDestroyed(ServletContextEvent sce) {
        apiMediationClient.unregister();
    }
}

```

3. Register the listener. Use one of the following two options:

- Add the @WebListener annotation to the servlet.
- Reference the listener by adding the following code block to the deployment descriptor *web.xml*.

**Example:**

```
<listener>
  <listener-class>your.class.package.path</listener-class>
</listener>
```

### Download Apache Tomcat and enable SSL

To run Helloworld Jersey, requires the installation of Apache Tomcat. As the service uses HTTPS, configure Tomcat to use the SSL/TLS protocol.

**Follow these steps:**

1. Download Apache Tomcat 8.0.39 and install it.
2. Build Helloworld Jersey through IntelliJ or by running `gradlew helloworld-jersey:build` in the terminal.
3. Enable HTTPS for Apache Tomcat with the following steps:

a) Go to the `apache-tomcat-8.0.39-windows-x64\conf` directory.

**Note:** The full path depends on where you decided to install Tomcat.

b) Open the `server.xml` file with a text editor as Administrator and add the following xml block: `xml`  
`<Connector port="8080" protocol="org.apache.coyote.http11.Http11NioProtocol" maxThreads="150" SSLEnabled="true" scheme="https" secure="true" clientAuth="false" sslProtocol="TLS" keystoreFile="{your-project-directory}\api-layer\keystore\localhost\localhost.keystore.p12" keystorePass="password" />` Ensure to comment the HTTP connector which uses the same port. c) Navigate to the `WEB-INF/` located in `helloworld-jersey` module and add the following xml block to the `web.xml` file. This should be added right below the `<servlet-mapping>` tag:

```
<security-constraint>
  <web-resource-collection>
    <web-resource-name>Protected resource</web-resource-name>
    <url-pattern>/*</url-pattern>
    <http-method>GET</http-method>
    <http-method>POST</http-method>
  </web-resource-collection>
  <user-data-constraint>
    <transport-guarantee>CONFIDENTIAL</transport-guarantee>
  </user-data-constraint>
</security-constraint>
```

### Run your service

After you externalize the parameters to make them readable through Tomcat and enable SSL, you are ready to run your service in the APIM Ecosystem.

**Note:** The following procedure uses `localhost` testing.

**Follow these steps:**

- Run the following services to onboard your application:

**Tip:** For more information about how to run the API Mediation Layer locally, see [Running the API Mediation Layer on Local Machine](#).

- Gateway Service
- Discovery Service
- API Catalog Service

- Run `gradlew tomcatRun` with these additional parameters: –

```
Djavax.net.ssl.trustStore="

```

`Djavax.net.ssl.trustStorePassword="password".` If you need some more information about SSL configuration status while deploying, use this parameter `-Djavax.net.debug=SSL`.

**Tip:** Wait for the services to be ready. This process may take a few minutes.

- Navigate to the following URL:

```
https://localhost:10011
```

Enter *eureka* as a username and *password* as a password and check if the service is registered to the discovery service.

Go to the following URL to reach the API Catalog through the Gateway (port 10010) and check if the API documentation of the service is retrieved:

```
https://localhost:10010/ui/v1/apicatalog/#/dashboard
```

You successfully onboarded your Java Jersey application if see your service running and can access the API documentation.

## REST APIs without code changes required

As a user of Zowe API Mediation Layer, onboard a REST API service with the Zowe API Mediation Layer without changing the code of the API service. The following procedure is an overview of steps to onboard an API service through the API Gateway in the API Mediation Layer.

### Follow these steps:

- [Identify the API that you want to expose](#) on page 169
- [Route your API](#) on page 170
- [Define your service and API in YAML format](#) on page 170
- [Configuration parameters](#) on page 171
- [Add and validate the definition in the API Mediation Layer running on your machine](#) on page 174
- [Add a definition in the API Mediation Layer in the Zowe runtime](#) on page 175
- [\(Optional\) Check the log of the API Mediation Layer](#) on page 175
- [\(Optional\) Reload the services definition after the update when the API Mediation Layer is already started](#) on page 175

### Identify the API that you want to expose

Onboard an API service through the API Gateway without making code changes.

**Tip:** For more information about the structure of APIs and which APIs to expose in the Zowe API Mediation Layer, see [Onboarding Overview](#) on page 130.

### Follow these steps:

- Identify the following parameters of your API service:

- Hostname
- Port
- (Optional) base path where the service is available. This URL is called base URL of the service.

**Example:**

In the sample service described earlier, the URL of the service is: `http://localhost:8080`.

- Identify all APIs that this service provides that you want to expose through the API Gateway.

**Example:**

In the sample service, this REST API is the one available at the path `/v2` relative to base URL of the service. This API is version 2 of the Pet Store API.

- Choose the *service ID* of your service. The *service ID* identifies the service in the API Gateway. The service ID is an alphanumeric string in lowercase ASCII.

**Example:**

In the sample service, the *service ID* is `petstore`.

- Decide which URL to use to make this API available in the API Gateway. This URL is referred to as the gateway URL and is composed of the API type and the major version.

**Example:**

In the sample service, we provide a REST API. The first segment is `/api`. To indicate that this is version 2, the second segment is `/v2`.

## Route your API

After you identify the APIs you want to expose, define the *routing* of your API. Routing is the process of sending requests from the API gateway to a specific API service. Route your API by using the same format as in the following `petstore` example.

**Note:** The API Gateway differentiates major versions of an API.

**Example:**

To access version 2 of the `petstore` API use the following gateway URL:

`https://gateway-host:port/api/v2/petstore`

The base URL of the version 2 of the `petstore` API is:

`http://localhost:8080/v2`

The API Gateway routes REST API requests from the gateway URL `https://gateway:port/api/v2/petstore` to the service `http://localhost:8080/v2`. This method provides access to the service in the API Gateway through the gateway URL.

**Note:** This method enables you to access the service through a stable URL and move the service to another machine without changing the gateway URL. Accessing a service through the API Gateway also enables you to have multiple instances of the service running on different machines to achieve high-availability.

## Define your service and API in YAML format

Define your service and API in YAML format in the same way as presented in the following sample `petstore` service example.

**Example:**

To define your service in YAML format, provide the following definition in a YAML file as in the following sample `petstore` service:

```
services:
  - serviceId: petstore
```

```

catalogUiTileId: static
title: Petstore Sample Service
description: This is a sample server Petstore service
instanceBaseUrls:
  - http://localhost:8080
routes:
  - gatewayUrl: api/v2
    serviceRelativeUrl: /v2
apiInfo:
  - apiId: io.swagger.petstore
    gatewayUrl: api/v2
    swaggerUrl: http://localhost:8080/v2/swagger.json
    documentationUrl: https://petstore.swagger.io/
    version: 2.0.0

catalogUiTiles:
  static:
    title: Static API services
    description: Services which demonstrate how to make an API service
discoverable in the APIML ecosystem using YAML definitions

```

In this example, a suitable name for the file is `petstore.yml`.

#### **Notes:**

- The filename does not need to follow specific naming conventions but it requires the `.yml` extension.
- The file can contain one or more services defined under the `services`: node.
- Each service has a service ID. In this example, the service ID is `petstore`. The service can have one or more instances. In this case, only one instance `http://localhost:8080` is used.
- A service can provide multiple APIs that are routed by the API Gateway. In this case, requests with the relative base path `api/v2` at the API Gateway (full gateway URL: `https://gateway:port/api/v2/...`) are routed to the relative base path `/v2` at the full URL of the service (`http://localhost:8080/v2/...`).

#### **Tips:**

- There are more examples of API definitions at this [link](#).
- For more details about how to use YAML format, see this [link](#)

#### **Configuration parameters**

The following list describes the configuration parameters:

- **serviceId**

Specifies the service instance identifier that is registered in the API Mediation Layer installation. The service ID is used in the URL for routing to the API service through the gateway. The service ID uniquely identifies the service in the API Mediation Layer. The system administrator at the customer site defines this parameter.

**Important!** Ensure that the service ID is set properly with the following considerations:

- When two API services use the same service ID, the API gateway considers the services to be clones (two instances for the same service). An incoming API request can be routed to either of them.
- The same service ID should be set only for multiple API service instances for API scalability.
- The service ID value must contain only lowercase alphanumeric characters.
- The service ID cannot contain more than 40 characters.
- The service ID is linked to security resources. Changes to the service ID require an update of security resources.

**Examples:**

- If the customer system administrator sets the service ID to sysviewlpr1, the API URL in the API Gateway appears as the following URL:

`https://gateway:port/api/v1/sysviewlpr1/...`

- If customer system administrator sets the service ID to vantageprod1, the API URL in the API Gateway appears as the following URL:

`http://gateway:port/api/v1/vantageprod1/...`

- **title**

Specifies the human readable name of the API service instance (for example, "Endevor Prod" or "Sysview LPAR1"). This value is displayed in the API catalog when a specific API service instance is selected. This parameter is externalized and set by the customer system administrator.

**Tip:** We recommend that you provide a specific default value of the `title`. Use a title that describes the service instance so that the end user knows the specific purpose of the service instance.

- **description**

Specifies a short description of the API service.

**Example:** "CA Endevor SCM - Production Instance" or "CA SYSVIEW running on LPAR1".

This value is displayed in the API Catalog when a specific API service instance is selected. This parameter is externalized and set by the customer system administrator.

**Tip:** Describe the service so that the end user knows the function of the service.

- **instanceBaseUrls**

Specifies a list of base URLs to your service to the REST resource. It will be the prefix for the following URLs:

- **homePageRelativeUrl**
- **statusPageRelativeUrl**
- **healthCheckRelativeUrl**

**Examples:**

- – `http://host:port/filemasterplus` for an HTTP service
- – `https://host:port/endeavor` for an HTTPS service

You can provide one URL if your service has one instance. If your service provides multiple instances for the high-availability then you can provide URLs to these instances.

```
- https://host1:port1/endeavor
  https://host2:port2/endeavor
```

- **homePageRelativeUrl**

Specifies the relative path to the homepage of your service. The path should start with /. If your service has no homepage, omit this parameter.

**Examples:**

- `homePageRelativeUrl: /` The service has homepage with URL \${baseUrl} /
- `homePageRelativeUrl: /ui/` The service has homepage with URL \${baseUrl} /ui /
- `homePageRelativeUrl:`  The service has homepage with URL \${baseUrl}

- **statusPageRelativeUrl**

Specifies the relative path to the status page of your service. Start this path with /. If your service has not a status page, omit this parameter.

**Example:**

- `statusPageRelativeUrl: /application/info` the result URL will be \${baseUrl} / application / info

- **healthCheckRelativeUrl**

Specifies the relative path to the health check endpoint of your service. Start this URL with /. If your service does not have a health check endpoint, omit this parameter.

**Example:**

- `healthCheckRelativeUrl: /application/health`. This results in the URL: \${baseUrl} / application / health

- **routes**

The routing rules between the gateway service and your service.

- **routes.gatewayUrl**

Both *gatewayUrl* and *serviceUrl* parameters specify how the API service endpoints are mapped to the API gateway endpoints. The *gatewayUrl* parameter sets the target endpoint on the gateway.

- **routes.serviceUrl**

Both *gatewayUrl* and *serviceUrl* parameters specify how the API service endpoints are mapped to the API gateway endpoints. The *serviceUrl* parameter points to the target endpoint on the gateway.

- **apiInfo**

This section defines APIs that are provided by the service. Currently, only one API is supported.

- **apiInfo.apiId**

Specifies the API identifier that is registered in the API Mediation Layer installation. The API ID uniquely identifies the API in the API Mediation Layer. The same API can be provided by multiple services. The API ID can be used to locate the same APIs that are provided by different services. The creator of the API defines this ID. The API ID needs to be a string of up to 64 characters that uses lowercase alphanumeric characters and a dot: .. We recommend that you use your organization as the prefix.

**Examples:**

- `org.zowe.file`
- `com.ca.sysview`
- `com.ibm.zosmf`

- **apiInfo.gatewayUrl**

The base path at the API gateway where the API is available. Ensure that this path is the same as the *gatewayUrl* value in the *routes* sections.

- **apiInfo.swaggerUrl**

(Optional) Specifies the HTTP or HTTPS address where the Swagger JSON document is available.

- **apiInfo.documentationUrl**

(Optional) Specifies a URL to a website where external documentation is provided. This can be used when *swaggerUrl* is not provided.

- **apiInfo.version**

(Optional) Specifies the actual version of the API in [semantic versioning](#) format. This can be used when *swaggerUrl* is not provided.

- **catalogUiTileId**

Specifies the unique identifier for the API services group. This is the grouping value used by the API Mediation Layer to group multiple API services together into "tiles". Each unique identifier represents a single API Catalog UI dashboard tile. Specify the value based on the ID of the defined tile.

- **catalogUiTile**

This section contains definitions of tiles. Each tile is defined in a section that has its tile ID as a key. A tile can be used by multiple services.

```
catalogUiTiles:
  tile1:
    title: Tile 1
    description: This is the first tile with ID tile1
  tile2:
    title: Tile 2
    description: This is the second tile with ID tile2
```

- **catalogUiTile.{tileId}.title**

Specifies the title of the API services product family. This value is displayed in the API catalog UI dashboard as the tile title.

- **catalogUiTile.{tileId}.description**

Specifies the detailed description of the API Catalog UI dashboard tile. This value is displayed in the API catalog UI dashboard as the tile description.

### Add and validate the definition in the API Mediation Layer running on your machine

After you define the service in YAML format, you are ready to add your service definition to the API Mediation Layer ecosystem.

The following procedure describes how to add your service to the API Mediation Layer on your local machine.

**Follow these steps:**

1. Copy or move your YAML file to the config/local/api-defs directory in the directory with API Mediation layer.
2. Start the API Mediation Layer services.

**Tip:** For more information about how to run the API Mediation Layer locally, see [Running the API Mediation Layer on Local Machine](#).

3. Run your Java application.

**Tip:** Wait for the services to be ready. This process may take a few minutes.

4. Go to the following URL to reach the API Gateway (port 10010) and see the paths that are routed by the API Gateway:

```
https://localhost:10010/application/routes
```

The following line should appear:

```
/api/v2/petstore/**: "petstore"
```

This line indicates that requests to relative gateway paths that start with `/api/v2/petstore/` are routed to the service with the service ID `petstore`.

You successfully defined your Java application if your service is running and you can access the service endpoints. The following example is the service endpoint for the sample application:

```
https://localhost:10010/api/v2/petstore/pets/1
```

### Add a definition in the API Mediation Layer in the Zowe runtime

After you define and validate the service in YAML format, you are ready to add your service definition to the API Mediation Layer running as part of the Zowe runtime installation.

#### Follow these steps:

1. Locate the Zowe runtime directory. The Zowe runtime directory is chosen during Zowe installation. The location of the directory is in the `zowe-install.yaml` file in the variable `install:rootDir`.
- Note:** We use the  `${zoweRuntime}` symbol in following instructions.
2. Copy your YAML file to the  `${zoweRuntime}/api-mediation/api-defs` directory.
3. Run your application.
4. Restart Zowe runtime or follow steps in section [\(Optional\) Reload the services definition after the update when the API Mediation Layer is already started](#) on page 175.
5. Go to the following URL to reach the API Gateway (default port 7554) and see the paths that are routed by the API Gateway: `https://${zoweHostname}:${gatewayHttpsPort}/application/routes`

The following line should appear:

```
/api/v2/petstore/**: "petstore"
```

This line indicates that requests to the relative gateway paths that start with `/api/v2/petstore/` are routed to the service with service ID `petstore`.

You successfully defined your Java application if your service is running and you can access its endpoints. The endpoint displayed for the sample application is: `https://1${zoweHostname}: ${gatewayHttpsPort}/api/v2/petstore/pets/1`

### (Optional) Check the log of the API Mediation Layer

The API Mediation Layer prints the following messages to its log when the API definitions are processed:

```
Scanning directory with static services definition: config/local/api-defs
Static API definition file: /Users/plape03/workspace/api-layer/config/local/
api-defs/petstore.yml
Adding static instance STATIC-localhost:petstore:8080 for service ID
petstore mapped to URL http://localhost:8080
```

### (Optional) Reload the services definition after the update when the API Mediation Layer is already started

The following procedure enables you to refresh the API definitions after you change the definitions when the API Mediation Layer is already running.

#### Follow these steps:

1. Use a REST API client to issue a POST request to the Discovery Service (port 10011):

```
http://localhost:10011/discovery/api/v1/staticApi
```

The Discovery Service requires authentication by a client certificate. If the API Mediation Layer is running on your local machine, the certificate is stored at `keystore/localhost/localhost.pem`.

This example uses the [HTTPie command-line HTTP client](#):

```
http --cert=keystore/localhost/localhost.pem --verify=keystore/local_ca/localca.cer -j POST https://localhost:10011/discovery/api/v1/staticApi
```

2. Check if your updated definition is effective.

#### Notes:

- It can take up to 30 seconds for the API Gateway to pick up the new routing.
- The basic authentication will be replaced by client certificates when the Discovery Service is updated to use HTTPS.

## Developing for Zowe CLI

---

### Developing for Zowe CLI

You can extend Zowe CLI by developing plug-ins and contributing code to the base Zowe CLI or existing plug-ins.

#### How can I contribute?

You can contribute to Zowe CLI in the following ways:

1. Add new commands, options, or other improvements to the base CLI.
2. Develop a plug-in that users can install to Zowe CLI.

You might want to contribute to Zowe CLI to accomplish the following:

- Provide new scriptable functionality for yourself, your organization, or to a broader community.
- Make use of Zowe CLI infrastructure (profiles and programmatic APIs).
- Participate in the Zowe CLI community space.

#### Getting started

If you want to start working with the code immediately, check out the [Zowe CLI core repository](#) and the [contribution guidelines](#). The [zowe-cli-sample-plugin GitHub repository](#) is a sample plug-in that adheres to the guidelines for contributing to Zowe CLI projects.

#### Tutorials

Follow these tutorials to get started working with the sample plug-in:

1. [Setting up your development environment on page 177](#) - Clone the project and prepare your local environment.
2. [Installing the sample plug-in on page 178](#) - Install the sample plug-in to Zowe CLI and run as-is.
3. [Extending a plug-in on page 180](#) - Extend the sample plug-in with a new by creating a programmatic API, definition, and handler.
4. [Developing a new plug-in on page 183](#) - Create a new CLI plug-in that uses Zowe CLI programmatic APIs and a diff package to compare two data sets.
5. [Implementing profiles in a plug-in on page 188](#) - Implement user profiles with the plug-in.

#### Plug-in Development Overview

At a high level, a plug-in must have `imperative-framework` configuration ([sample here](#)). This configuration is discovered by `imperative-framework` through the `package.json` `imperative` key.

A Zowe CLI plug-in will minimally contain the following:

- 1. Programmatic API** - Node.js programmatic APIs to be called by your handler or other Node.js applications.
- 2. Command definition** - The syntax definition for your command.
- 3. Handler implementation** - To invoke your programmatic API to display information in the format that you defined in the definition.

The following guidelines and documentation will assist you during development:

### Imperative CLI Framework Documentation

[Imperative CLI Framework documentation](#) is a key source of information to learn about the features of Imperative CLI Framework (the code framework that you use to build plug-ins for Zowe CLI). Refer to these supplementary documents during development to learn about specific features such as:

- Auto-generated help
- JSON responses
- User profiles
- Logging, progress bars, experimental commands, and more!

### Contribution Guidelines

The Zowe CLI contribution guidelines contain standards and conventions for developing Zowe CLI plug-ins.

The guidelines contain critical information about working with the code, running/writing/maintaining automated tests, developing consistent syntax in your plug-in, and ensuring that your plug-in integrates with Zowe CLI properly:

For more information about ...	See:
General guidelines that apply to contributing to Zowe CLI and Plug-ins	<a href="#">Contribution Guidelines</a>
Conventions and best practices for creating packages and plug-ins for Zowe CLI	<a href="#">Package and Plug-in Guidelines</a>
Guidelines for running tests on Zowe CLI	<a href="#">Testing Guidelines</a>
Guidelines for running tests on the plug-ins that you build	<a href="#">Plug-in Testing Guidelines</a>
Versioning conventions for Zowe CLI and Plug-ins	<a href="#">Versioning Guidelines</a>

## Setting up your development environment

Before you follow the development tutorials for creating a Zowe CLI plug-in, follow these steps to set up your environment.

### Prerequisites

[Methods to install Zowe CLI](#) on page 73.

### Initial setup

To create your development space, you will clone and build [zowe-cli-sample-plugin](#) from source.

Before you clone the repository, create a local development folder named `zowe-tutorial`. You will clone and build all projects in this folder.

### Clone zowe-cli-sample-plugin and build from source

Clone the repository into your development folder to match the following structure:

```
zowe-tutorial
### zowe-cli-sample-plugin
```

Follow these steps:

1. cd to your zowe-tutorial folder.
2. git clone <https://github.com/zowe/zowe-cli-sample-plugin>
3. cd to your zowe-cli-sample-plugin folder.
4. npm install
5. npm run build

The first time that you build, the script will interactively ask you for the location of your Zowe CLI directory. Subsequent builds will not ask again.

The build script creates symbolic links. On Windows, you might need to have Administrator privileges to create those symbolic links.

### (Optional) Run the automated tests

We recommend running automated tests on all code changes. Follow these steps:

1. cd to the \_\_tests\_\_/\_\_resources\_\_/properties folder.
2. Copy example\_properties.yaml to custom\_properties.yaml.
3. Edit the properties within custom\_properties.yaml to contain valid system information for your site.
4. cd to your zowe-cli-sample-plugin folder
5. npm run test

### Next steps

After you complete your setup, follow the [Installing the sample plug-in](#) on page 178 tutorial to install this sample plug-in to Zowe CLI.

## Installing the sample plug-in

Before you begin, [Setting up your development environment](#) on page 177 your local environment to install a plug-in.

### Overview

This tutorial covers installing and running this bundled Zowe CLI plugin as-is (without modification), which will display your current directory contents.

The plug-in adds a command to the CLI that lists the contents of a directory on your computer.

### Installing the sample plug-in to Zowe CLI

To begin, cd into your zowe-tutorial folder.

Issue the following commands to install the sample plug-in to Zowe CLI:

```
zowe plugins install ./zowe-cli-sample-plugin
```

### Viewing the installed plug-in

Issue zowe --help in the command line to return information for the installed zowe-cli-sample command group:

```
$ zowe

DESCRIPTION
-----
Welcome to Zowe CLI!

Zowe CLI is a command line interface (CLI) that provides a simple and
streamlined way to interact with IBM z/OS.

For additional Zowe CLI documentation, visit https://zowe.github.io/zowe-cli-docs/

For Zowe CLI support, visit https://zowe.org.
```

```
USAGE
-----
zowe [group]

GROUPS
-----
diagnostics          Run diagnostics
plugins              Install and manage plug-ins
profiles             Create and manage configuration profiles
provisioning | pv    Perform z/OSMF provisioning tasks on P
                      Templates in the Service Catalog and P
                      Instances in the Service Registry.
zos-console | console Issue z/OS console commands and collect
zos-files | files    Manage z/OS data sets
zos-jobs | jobs      Manage z/OS jobs
zos-tso | tso         Issue TSO commands and interact with T
zosmf                Interact with z/OSMF
zowe-cli-sample | zcsp Zowe CLI sample plug-in
```

Figure 1: Installed Sample Plugin

#### Using the installed plug-in

To use the plug-in functionality, issue: `zowe zowe-cli-sample list directory-contents`:

```
$ zowe zowe-cli-sample list directory-contents
We just got a valid z/OSMF status response from system = [REDACTED]

mode size birthed
16822      Thu Sep 20 2018 09:52:20 GMT-0400 (Eastern Daylight
33206 297   Thu Sep 20 2018 09:40:07 GMT-0400 (Eastern Daylight
16822      Thu Sep 20 2018 09:54:20 GMT-0400 (Eastern Daylight
33206      Thu Sep 20 2018 09:40:07 GMT-0400 (Eastern Daylight
33206 211   Thu Sep 20 2018 09:40:07 GMT-0400 (Eastern Daylight
33206 6855  Thu Sep 20 2018 09:40:07 GMT-0400 (Eastern Daylight
33206 1609  Thu Sep 20 2018 09:40:07 GMT-0400 (Eastern Daylight
16822      Thu Sep 20 2018 09:40:07 GMT-0400 (Eastern Daylight
16822      Thu Sep 20 2018 09:40:07 GMT-0400 (Eastern Daylight
33206 36028 Thu Sep 20 2018 09:40:07 GMT-0400 (Eastern Daylight
16822      Thu Sep 20 2018 10:06:27 GMT-0400 (Eastern Daylight
33206 14109 Thu Sep 20 2018 09:40:07 GMT-0400 (Eastern Daylight
[REDACTED]
```

**Figure 2: Sample Plugin Output**

### Testing the installed plug-in

To run automated tests against the plug-in, cd into your `zowe-tutorial/zowe-cli-sample-plugin` folder.

Issue the following command:

- `npm run test`

### Next steps

You successfully installed a plug-in to Zowe CLI! Next, try the [Extending a plug-in](#) on page 180 tutorial to learn about developing new commands for this plug-in.

## Extending a plug-in

Before you begin, be sure to complete the [Installing the sample plug-in](#) on page 178 tutorial.

### Overview

This tutorial demonstrates how to extend the plug-in that is bundled with this sample by:

1. Creating a new programmatic API
2. Creating a new command definition
3. Creating a new handler

We'll do this by using `@brightside/imperative` infrastructure to surface REST API data on our Zowe CLI plug-in.

Specifically, we're going to show data from [this URI](#) by [Typicode](#). Typicode serves sample REST JSON data for testing purposes.

At the end of this tutorial, you will be able to use a new command from the Zowe CLI interface: `zowe zowe-cli-sample list typicode-todos`

Completed source for this tutorial can be found on the `typicode-todos` branch of the `zowe-cli-sample-plugin` repository.

## Creating a Typescript interface for the Typicode response data

First, we'll create a Typescript interface to map the response data from a server.

Within `zowe-cli-sample-plugin/src/api`, create a folder named `doc` to contain our interface (sometimes referred to as a "document" or "doc"). Within the `doc` folder, create a file named `ITodo.ts`.

The `ITodo.ts` file will contain the following:

```
export interface ITodo {
  userId: number;
  id: number;
  title: string;
  completed: boolean;
}
```

## Creating a programmatic API

Next, we'll create a Node.js API that our command handler uses. This API can also be used in any Node.js application, because these Node.js APIs make use of REST APIs, Node.js APIs, other NPM packages, or custom logic to provide higher level functions than are served by any single API.

Adjacent to the existing file named `zowe-cli-sample-plugin/src/api/Files.ts`, create a file `Typicode.ts`.

`Typicode.ts` should contain the following:

```
import { ITodo } from "./doc/ITodo";
import { RestClient, AbstractSession, ImperativeExpect, Logger } from
  "@brightside/imperative";

export class Typicode {

  public static readonly TODO_URI = "/todos";

  public static getTodos(session: AbstractSession): Promise<ITodo[]> {
    Logger.getAppLogger().trace("Typicode.getTodos() called");
    return RestClient.getExpectJSON<ITodo[]>(session,
      Typicode.TODO_URI);
  }

  public static getTodo(session: AbstractSession, id: number): Promise<ITodo> {
    Logger.getAppLogger().trace("Typicode.getTodos() called with id " + id);
    ImperativeExpect.toNotBeNullOrUndefined(id, "id must be provided");
    const resource = Typicode.TODO_URI + "/" + id;
    return RestClient.getExpectJSON<ITodo>(session, resource);
  }
}
```

The `Typicode` class provides two programmatic APIs, `getTodos` and `getTodo`, to get an array of `ITodo` objects or a specific `ITodo` respectively. The Node.js APIs use `@brightside/imperative` infrastructure to provide logging, parameter validation, and to call a REST API. See the [Imperative CLI Framework documentation](#) for more information.

## Exporting interface and programmatic API for other Node.js applications

Update `zowe-cli-sample-plugin/src/index.ts` to contain the following:

```
export * from "./api/doc/ITodo";
export * from "./api/Typicode";
```

A sample invocation of your API might look similar to the following, if it were used by a separate, standalone Node.js application:

```
import { Typicode } from "@brightside/zowe-cli-sample-plugin";
import { Session, Imperative } from "@brightside/imperative";
import { inspect } from "util";

const session = new Session({ hostname: "jsonplaceholder.typicode.com" });
(async () => {
    const firstTodo = await Typicode.getTodo(session, 1);
    Imperative.console.debug("First todo was: " + inspect(firstTodo));
})();
```

## Checkpoint

Issue `npm run build` to verify a clean compilation and confirm that no lint errors are present. At this point in this tutorial, you have a programmatic API that will be used by your handler or another Node.js application. Next you'll define the command syntax for the command that will use your programmatic Node.js APIs.

### Defining command syntax

Within Zowe CLI, the full command that we want to create is `zowe zowe-cli-sample list typicode-todos`. Navigate to `zowe-cli-sample-plugin/src/cli/list` and create a folder `typicode-todos`. Within this folder, create `TypicodeTodos.definition.ts`. Its content should be as follows:

```
import { ICommandDefinition } from "@brightside/imperative";
export const TypicodeTodosDefinition: ICommandDefinition = {
    name: "typicode-todos",
    aliases: ["td"],
    summary: "Lists typicode todos",
    description: "List typicode REST sample data",
    type: "command",
    handler: __dirname + "/TypicodeTodos.handler",
    options: [
        {
            name: "id",
            description: "The todo to list",
            type: "number"
        }
    ]
};
```

This describes the syntax of your command.

### Defining command handler

Also within the `typicode-todos` folder, create `TypicodeTodos.handler.ts`. Add the following code to the new file:

```
import { ICommandHandler, IHandlerParameters, TextUtils, Session } from
    "@brightside/imperative";
import { Typicode } from "../../api/Typicode";
export default class TypicodeTodosHandler implements ICommandHandler {

    public static readonly TYPICODE_HOST = "jsonplaceholder.typicode.com";
    public async process(params: IHandlerParameters): Promise<void> {

        const session = new Session({ hostname:
            TypicodeTodosHandler.TYPICODE_HOST });
        if (params.arguments.id) {
            const todo = await Typicode.getTodo(session,
                params.arguments.id);
            params.response.data.setObj(todo);
        }
    }
}
```

```

        params.response.console.log(TextUtils.prettyJson(todo));
    } else {
        const todos = await Typicode.getTodos(session);
        params.response.data.setObj(todos);
        params.response.console.log(TextUtils.prettyJson(todos));
    }
}
}

```

The if statement checks if a user provides an --id flag. If yes, we call getTodo. Otherwise, we call getTodos. If the Typicode API throws an error, the @brightside/imperative infrastructure will automatically surface this.

### Defining command to list group

Within the file zowe-cli-sample-plugin/src/cli/list/List.definition.ts, add the following code below other import statements near the top of the file:

```

import { TypicodeTodosDefinition } from "./typicode-todos/
TypicodeTodos.definition";

```

Then add TypicodeTodosDefinition to the children array. For example:

```

children: [DirectoryContentsDefinition, TypicodeTodosDefinition]

```

### Checkpoint

Issue npm run build to verify a clean compilation and confirm that no lint errors are present. You now have a handler, definition, and your command has been defined to the list group of the command.

### Using the installed plug-in

Issue the command: zowe zowe-cli-sample list typicode-todos

Refer to zowe zowe-cli-sample list typicode-todos --help for more information about your command and to see how text in the command definition is presented to the end user. You can also see how to use your optional --id flag:

```
$ zowe zowe-cli-sample list typicode-todos --id 4
userId: 1
id: 4
title: et porro tempora
completed: true
```

### Summary

You extended an existing Zowe CLI plug-in by introducing a Node.js programmatic API, and you created a command definition with a handler. For an official plugin, you would also add [JSDoc](#) to your code and create automated tests.

### Next steps

Try the [Developing a new plug-in](#) on page 183 tutorial next to create a new plug-in for Zowe CLI.

## Developing a new plug-in

Before you begin this tutorial, make sure that you completed the [Extending a plug-in](#) on page 180 tutorial.

## Overview

This tutorial demonstrates how to create a brand new Zowe CLI plug-in that uses Zowe CLI Node.js programmatic APIs.

At the end of this tutorial, you will have created a data set diff utility plug-in for Zowe CLI, from which you can pipe your plugin's output to a third-party utility for a side-by-side diff of data set member contents.

## Files changed (1) [show](#)

		@@ -1,2 +1,2 @@
1	1	//SWAWI03\$ JOB 105300000
2	-	//EXEC EXEC PGM=IEFBR14
	2	+ //EXEC EXEC PGM=IEFBR15

Completed source for this tutorial can be found on the `develop-a-plugin` branch of the `zowe-cli-sample-plugin` repository.

## Cloning the sample plug-in source

Clone the sample repo, delete the irrelevant source, and create a brand new plug-in. Follow these steps:

1. cd into your `zowe-tutorial` folder
2. git clone <https://github.com/zowe/zowe-cli-sample-plugin files-util>
3. cd `files-util`
4. Delete the `.git` (hidden) folder.
5. Delete all content within the `src/api`, `src/cli`, and `docs` folders.
6. Delete all content within the `__tests__/__system__/api`, `__tests__/__system__/cli`, `__tests__/api`, and `__tests__/cli` folders
7. git init
8. git add .
9. git commit -m "initial"

## Changing package.json

Use a unique npm name for your plugin. Change `package.json` name field as follows:

```
"name": "@brightside/files-util",
```

Issue the command `npm install` against the local repository.

## Adjusting Imperative CLI Framework configuration

Change `imperative.ts` to contain the following:

```
import { IImparativeConfig } from "@brightside/imperative";

const config: IImparativeConfig = {
  commandModuleGlobs: ["**/cli/**/*definition!(.d).*s"],
  rootCommandDescription: "Files utility plugin for Zowe CLI",
  envVariablePrefix: "FILES_UTIL_PLUGIN",
```

```

    defaultHome: "~/.files_util_plugin",
    productDisplayName: "Files Util Plugin",
    name: "files-util"
};

export = config;

```

Here we adjusted the description and other fields in the imperative JSON configuration to be relevant to this plug-in.

### Adding third-party packages

We'll use the following packages to create a programmatic API:

- npm install --save diff
- npm install -D @types/diff

### Creating a Node.js programmatic API

In `files-util/src/api`, create a file named `DataSetDiff.ts`. The content of `DataSetDiff.ts` should be the following:

```

import { AbstractSession } from "@brightside/imperative";
import { Download, IDownloadOptions, IZosFilesResponse } from "@brightside/core";
import * as diff from "diff";
import { readFileSync } from "fs";

export class DataSetDiff {

    public static async diff(session: AbstractSession, oldDataSet: string,
    newDataSet: string) {

        let error;
        let response: IZosFilesResponse;

        const options: IDownloadOptions = {
            extension: "dat",
        };

        try {
            response = await Download.dataSet(session, oldDataSet, options);
        } catch (err) {
            error = `oldDataSet: ${err}`;
            throw error;
        }

        try {
            response = await Download.dataSet(session, newDataSet, options);
        } catch (err) {
            error = `newDataSet: ${err}`;
            throw error;
        }

        const regex = /\./gi; // Replace . and ( with /
        const regex2 = /\)/gi; // Replace ) with .

        // convert the old data set name to use as a path/file
        let file = oldDataSet.replace(regex, "/");
        file = file.replace(regex2, ".") + "dat";
        // Load the downloaded contents of 'oldDataSet'
        const oldContent = readFileSync(`$file`).toString();

        // convert the new data set name to use as a path/file

```

```

        file = newDataSet.replace(regex, "/");
        file = file.replace(regex2, ".") + "dat";
        // Load the downloaded contents of 'oldDataSet'
        const newContent = readFileSync(` ${file}`).toString();

        return diff.createTwoFilesPatch(oldDataSet, newDataSet, oldContent,
newContent, "Old", "New");
    }
}

```

## Exporting your API

In `files-util/src`, change `index.ts` to contain the following:

```
export * from "./api/DataSetDiff";
```

## Checkpoint

At this point, you should be able to rebuild the plug-in without errors via `npm run build`. You included third party dependencies, created a programmatic API, and customized this new plug-in project. Next, you'll define the command to invoke your programmatic API.

## Defining commands

In `files-util/src/cli`, create a folder named `diff`. Within the `diff` folder, create a file `Diff.definition.ts`. Its content should be as follows:

```

import { ICommandDefinition } from "@brightside/imperative";
import { DataSetsDefinition } from "./data-sets/DataSets.definition";
const IssueDefinition: ICommandDefinition = {
    name: "diff",
    summary: "Diff two data sets content",
    description: "Uses open source diff packages to diff two data sets
content",
    type: "group",
    children: [DataSetsDefinition]
};

export = IssueDefinition;

```

Also within the `diff` folder, create a folder named `data-sets`. Within the `data-sets` folder create `DataSets.definition.ts` and `DataSets.handler.ts`.

`DataSets.definition.ts` should contain:

```

import { ICommandDefinition } from "@brightside/imperative";

export const DataSetsDefinition: ICommandDefinition = {
    name: "data-sets",
    aliases: ["ds"],
    summary: "data sets to diff",
    description: "diff the first data set with the second",
    type: "command",
    handler: __dirname + "/DataSets.handler",
    positionals: [
        {
            name: "oldDataSet",
            description: "The old data set",
            type: "string"
        },
        {
            name: "newDataSet",
            description: "The new data set",
            type: "string"
        }
    ]
};

```

```

        type: "string"
    }
],
profile: {
    required: [ "zosmf" ]
}
};

```

`DataSets.handler.ts` should contain the following:

```

import { ICommandHandler, IHandlerParameters, TextUtils, Session } from
    "@brightside/imperative";
import { DataSetDiff } from "../../api/DataSetDiff";

export default class DataSetsDiffHandler implements ICommandHandler {
    public async process(params: IHandlerParameters): Promise<void> {

        const profile = params.profiles.get("zosmf");
        const session = new Session({
            type: "basic",
            hostname: profile.host,
            port: profile.port,
            user: profile.user,
            password: profile.pass,
            base64EncodedAuth: profile.auth,
            rejectUnauthorized: profile.rejectUnauthorized,
        });
        const resp = await DataSetDiff.diff(session,
            params.arguments.oldDataSet, params.arguments.newDataSet);
        params.response.console.log(resp);
    }
}

```

### Trying your command

Be sure to build your plug-in via `npm run build`.

Install your plug-in into Zowe CLI via `zowe plugins install`.

Issue the following command. Replace the data set names with valid mainframe data set names on your system:

```
$ zowe files-util diff data-sets "████████.cntl(iefbr14)" "████████.cntl(iefbr15)"
```

The raw diff output is displayed as a command response:

```

$ zowe files-util diff data-sets "████████.cntl(iefbr14)" "████████.cntl(iefbr15)"
=====
--- ████████.cntl(iefbr14)          Old
+++ ████████.cntl(iefbr15)          New
@@ -1,2 +1,2 @@
 // $ JOB 105300000
-//EXEC      EXEC PGM=IEFBR14
+//EXEC      EXEC PGM=IEFBR15

```

## Bringing together new tools!

The advantage of Zowe CLI and of the CLI approach in mainframe development is that it allows for combining different developer tools for new and interesting uses.

[diff2html](#) is a free tool to generate HTML side-by-side diffs to help see actual differences in diff output.

Install the `diff2html` CLI via `npm install -g diff2html-cli`. Then, pipe your Zowe CL plugin's output into `diff2html` to generate diff HTML and launch a web browser that contains the content in the screen shot at the [Overview](#) on page 184.

- `zowe files-util diff data-sets "kelda16.work.jcl(iefbr14)" "kelda16.work.jcl(iefbr15)" | diff2html -i stdin`

## Next steps

Try the [Implementing profiles in a plug-in](#) on page 188 tutorial to learn about using profiles with your plug-in.

## Implementing profiles in a plug-in

You can use this profile template to create a profile for your product.

The profile definition is placed in the `imperative.ts` file.

`someproduct` will be the profile name that you might require on various commands to have credentials loaded from a secure credential manager and retain host/port information (so that you can easily swap to different servers) from the CLI).

By default, if your plug-in is installed into Zowe CLI that contains a profile definition like this, commands will automatically be created under `zowe profiles ...` to create, validate, set default, list, etc... for your profile.

```
profiles: [
  {
    type: "someproduct",
    schema: {
      type: "object",
      title: "Configuration profile for SOME PRODUCT",
      description: "Configuration profile for SOME PRODUCT",
      properties: {
        host: {
          type: "string",
          optionDefinition: {
            type: "string",
            name: "host",
            alias: ["H"],
            required: true,
            description: "Host name of your SOME PRODUCT REST API server"
          }
        },
        port: {
          type: "number",
          optionDefinition: {
            type: "number",
            name: "port",
            alias: ["P"],
            required: true,
            description: "Port number of your SOME PRODUCT REST API
server"
          }
        },
        user: {
          type: "string",
          optionDefinition: {
            type: "string",
            description: "User name for your SOME PRODUCT REST API
server"
          }
        }
      }
    }
  }
]
```

```

        name: "user",
        alias:[ "u" ],
        required: true,
        description: "User name to authenticate to your SOME PRODUCT
REST API server"
    },
    secure: true
},
password: {
    type: "string",
    optionDefinition: {
        type: "string",
        name: "password",
        alias:[ "p" ],
        required: true,
        description: "Password to authenticate to your SOME PRODUCT
REST API server"
    },
    secure: true
},
required: [ "host", "port", "user", "password" ],
},
createProfileExamples: [
{
    options: "spprofile --host zos123 --port 1234 --user ibmuser --
password myp4ss",
    description: "Create a SOME PRODUCT profile named 'spprofile' to
connect to SOME PRODUCT at host zos123 and port 1234"
}
]
}
]

```

## Next steps

If you completed all previous tutorials, you now understand the basics of extending and developing plug-ins for Zowe CLI. Next, we recommend reviewing the project [Contribution Guidelines](#) on page 177 and [Imperative CLI Framework Documentation](#) on page 177 to learn more.

---

# Developing for Zowe Application Framework

## Overview

You can create application plug-ins to extend the capabilities of the Zowe Application Framework. An application plug-in is an installable set of files that present resources in a web-based user interface, as a set of RESTful services, or in a web-based user interface and as a set of RESTful services.

Read the following topics to get started with extending the Zowe Application Framework.

### How Zowe Application Framework works

Read the following topics to learn how Zowe Application Framework works:

- [Creating application plug-ins](#) on page 191
- [Plug-ins definition and structure](#) on page 192
- [Dataservices](#) on page 195
- [Zowe Desktop and window management](#) on page 202
- [Configuration Dataservice](#) on page 206
- [URI Broker](#) on page 211

- Application-to-application communication on page 212
- Error reporting UI on page 216
- Logging utility on page 219

## Tutorials

Follow these tutorials to get started working with the sample application plug-in:

1. **[Tutorial: Stand up a local version of the Example Zowe Application Server on page 221](#)**

The `zlux-app-server` repository is an example of a server built upon the application framework. Within the repository, you will find a collection of build, deploy, and run scripts and configuration files that will help you to configure a simple Zowe Application Server with a few applications included.

2. **[Tutorial: User Browser Workshop App on page 226](#)**

This tutorial contains code snippets and descriptions that you can combine to build a complete application.

The following tutorials are available in Github.

- **Internationalization in Angular Templates in Zowe Application Server**  
:::tip Github Sample Repo: [sample-angular-app \(Internationalization\)](#) :::
- **App to app communication**  
:::tip Github Sample Repo : [sample-angular-app \(App to app communication\)](#) :::
- **Using the Widgets Library**  
:::tip Github Sample Repo: [sample-angular-app \(Widgets\)](#) :::
- **Configuring user preferences (configuration dataservice)**  
:::tip Github Sample Repo: [sample-angular-app \(configuration dataservice\)](#) :::

## Samples

Zowe allows extensions to be written in any UI framework through the use of an Iframe, or Angular and React natively. In this section, code samples of various use-cases will be provided with install instructions.

::: warning Troubleshooting Suggestions: If you are running into issues, try these suggestions:

- Restart the Zowe Server/ VM.
- Double check that the name in the plugins folder matches your identifier in `pluginsDefinition.json` located in the Zowe root.
- After logging into the Zowe desktop, use the Chrome or Firefox developer tools and navigate to the "network" tab to see what errors you are getting.
- Check each file with `cat <filename>` to be sure it wasn't corrupted while uploading. If files were corrupted, try uploading using a different method like SCP or SFTP. :::

### Sample Iframe App

:::tip Github Sample Repo: [sample-iframe-app](#) :::

### Sample Angular App

:::tip Github Sample Repo: [sample-angular-app](#) :::

### Sample React App

:::tip Github Sample Repo: [sample-react-app](#) :::

### User Browser Workshop Starter App

:::tip Github Sample Repo: [workshop-starter-app](#) :::

*This sample is included as the first part of a tutorial detailing communication between separate Zowe apps.*

**It should be installed on your system before starting the [Tutorial: User Browser Workshop App on page 226](#)**

The App's scenario is that it has been opened to submit a task report to a set of users who can handle the task. In this case, it is a bug report. We want to find engineers who can fix this bug, but this App does not contain a directory listing for engineers in the company, so we need to communicate with some App that does provide this information. In this tutorial, you must build an App which is called by this App in order to list engineers, is able to be filtered by the office that they work from, and is able to submit a list of engineers which would be able to handle the task.

After installing this app on your system, follow directions in the [Tutorial: User Browser Workshop App](#) on page 226 to enable app-to-app communication.

## Creating application plug-ins

An application plug-in is an installable set of files that present resources in a web-based user interface, as a set of RESTful services, or in a web-based user interface and as a set of RESTful services.

Before you build an application plug-in, you must set the UNIX environment variables that support the plug-in environment.

### Setting the environment variables for plug-in development

To set up the environment, the node must be accessible on the PATH. To determine if the node is already on the PATH, issue the following command from the command line:

```
node --version
```

If the version is returned, the node is already on the PATH.

If nothing is returned from the command, you can set the PATH using the *NODE\_HOME* variable. The *NODE\_HOME* variable must be set to the directory of the node install. You can use the `export` command to set the directory. For example:

```
export NODE_HOME=node_installation_directory
```

Using this directory, the node will be included on the PATH in `nodeCluster.sh`. (`nodeCluster.sh` is located in `zlux-app-server/bin`).

### Using the sample application plug-in

You can experiment with the sample application plug-in called `sample-app` that is provided.

To build the sample application plug-in, node and npm must be included in the PATH. You can use the `npm run build` or `npm start` command to build the sample application plug-in. These commands are configured in `package.json`.

#### Note:

- If you change the source code for the sample application, you must rebuild it.
- If you want to modify `sample-app`, you must run `npm install` in the Zowe Desktop and the `sample-app/webClient`. Then, you can run `npm run build` in `sample-app/webClient`.
- Ensure that you set the `MVD_DESKTOP_DIR` system variable to the Zowe Desktop plug-in location. For example: `<ZLUX_CAP>/zlux-app-manager/virtual-desktop`.

1. Add an item to `sample-app`. The following figure shows an excerpt from `app.component.ts`:

```
export class AppComponent {
  items = ['a', 'b', 'c', 'd']
  title = 'app';
  helloText: string;
  serverResponseMessage: string;
```

2. Save the changes to `app.component.ts`.

**3.** Issue one of the following commands:

- To rebuild the application plug-in, issue the following command:

```
npm run build
```

- To rebuild the application plug-in and wait for additional changes to `app.component.ts`, issue the following command:

```
npm start
```

**4.** Reload the web page.

**5.** If you make changes to the sample application source code, follow these steps to rebuild the application:

- a. Navigate to the `sample-app` subdirectory where you made the source code changes.
- b. Issue the following command:

```
npm run build
```

- c. Reload the web page.

## Plug-ins definition and structure

The Zowe Application Server (`zlux-server-framework`) enables extensibility with application plug-ins. Application plug-ins are a subcategory of the unit of extensibility in the server called a *plug-in*.

The files that define a plug-in are located in the `pluginsDir` directory.

### Application plug-in filesystem structure

An application plug-in can be loaded from a filesystem that is accessible to the Zowe Application Server, or it can be loaded dynamically at runtime. When accessed from a filesystem, there are important considerations for the developer and the user as to where to place the files for proper build, packaging, and operation.

#### Root files and directories

The root of an application plug-in directory contains the following files and directories.

##### `pluginDefinition.json`

This file describes an application plug-in to the Zowe Application Server. (A plug-in is the unit of extensibility for the Zowe Application Server. An application plug-in is a plug-in of the type "Application", the most common and visible type of plug-in.) A definition file informs the server whether the application plug-in has server-side dataservices, client-side web content, or both.

#### Dev and source content

Aside from demonstration or open source application plug-ins, the following directories should not be visible on a deployed server because the directories are used to build content and are not read by the server.

##### `nodeServer`

When an application plug-in has router-type dataservices, they are interpreted by the Zowe Application Server by attaching them as ExpressJS routers. It is recommended that you write application plug-ins using Typescript, because it facilitates well-structured code. Use of Typescript results in build steps because the pre-transpilation Typescript content is not to be consumed by NodeJS. Therefore, keep server-side source code in the `nodeServer` directory. At runtime, the server loads router dataservices from the `lib` directory.

##### `webClient`

When an application plug-in has the `webContent` attribute in its definition, the server serves static content for a client. To optimize loading of the application plug-in to the user, use Typescript to write the application plug-in and then package it using Webpack. Use of Typescript and Webpack result in build steps because the pre-transpilation

TypeScript and the pre-webpack content are not to be consumed by the browser. Therefore, separate the source code from the served content by placing source code in the `webClient` directory.

## Runtime content

At runtime, the following set of directories are used by the server and client.

### `lib`

The `lib` directory is where router-type dataservices are loaded by use in the Zowe Application Server. If the JS files that are loaded from the `lib` directory require NodeJS modules, which are not provided by the server base (the modules `zlux-server-framework` requires are added to `NODE_PATH` at runtime), then you must include these modules in `lib/node_modules` for local directory lookup or ensure that they are found on the `NODE_PATH` environment variable. `nodeServer/node_modules` is not automatically accessed at runtime because it is a dev and build directory.

### `web`

The `web` directory is where the server serves static content for an application plug-in that includes the `webContent` attribute in its definition. Typically, this directory contains the output of a webpack build. Anything you place in this directory can be accessed by a client, so only include content that is intended to be consumed by clients.

## Packaging applications as compressed files

Application plug-in files can be served to browsers as compressed files in brotli (.br) or gzip (.gz) format. The file must be below the application's `/web` directory, and the browser must support the compression method. If there are multiple compressed files in the `/web` directory, the Zowe Application Server and browser perform runtime negotiation to decide which file to use.

## Location of plug-in files

The files that define a plug-in are located in the `plugins` directory.

### `pluginsDir` directory

At startup, the server reads from the `plugins` directory. The server loads the valid plug-ins that are found by the information that is provided in the JSON files.

Within the `pluginsDir` directory are a collection of JSON files. Each file has two attributes, which serve to locate a plug-in on disk:

**location:** This is a directory path that is relative to the server's executable (such as `zlux-app-server/bin/nodeServer.sh`) at which a `pluginDefinition.json` file is expected to be found.

**identifier:** The unique string (commonly styled as a Java resource) of a plug-in, which must match what is in the `pluginDefinition.json` file.

### Plug-in definition file

`pluginDefinition.json` is a file that describes a plug-in. Each plug-in requires this file, because it defines how the server will register and use the backend of an application plug-in (called a *plug-in* in the terminology of the proxy server). The attributes in each file are dependent upon the `pluginType` attribute. Consider the following `pluginDefinition.json` file from `sample-app`:

```
{
  "identifier": "com.rs.mvd.myplugin",
  "apiVersion": "1.0",
  "pluginVersion": "1.0",
  "pluginType": "application",
  "webContent": {
    "framework": "angular2",
    "launchDefinition": {
      "pluginShortNameKey": "helloWorldTitle",
      "pluginShortNameDefault": "Hello World",
      "imageSrc": "assets/icon.png"
    }
  }
}
```

```

    },
    "descriptionKey": "MyPluginDescription",
    "descriptionDefault": "Base MVD plugin template",
    "isSingleWindowApp": true,
    "defaultWindowState": {
        "width": 400,
        "height": 300
    }
},
"dataServices": [
{
    "type": "router",
    "name": "hello",
    "serviceLookupMethod": "external",
    "fileName": "helloWorld.js",
    "routerFactory": "helloWorldRouter",
    "dependenciesIncluded": true
}
]
}

```

## Plug-in attributes

There are two categories of attributes: General and Application.

### General attributes

#### **identifier**

Every application plug-in must have a unique string ID that associates it with a URL space on the server.

#### **apiVersion**

The version number for the pluginDefinition scheme and application plug-in or dataservice requirements. The default is 1.0.0.

#### **pluginVersion**

The version number of the individual plug-in.

#### **pluginType**

A string that specifies the type of plug-in. The type of plug-in determines the other attributes that are valid in the definition.

- **application:** Defines the plug-in as an application plug-in. Application plug-ins are composed of a collection of web content for presentation in the Zowe web component (such as the Zowe Desktop), or a collection of dataservices (REST and websocket), or both.
- **library:** Defines the plug-in as a library that serves static content at a known URL space.
- **node authentication:** Authentication and Authorization handlers for the Zowe Application Server.

### Application attributes

When a plug-in is of *pluginType* application, the following attributes are valid:

#### **webContent**

An object that defines several attributes about the content that is shown in a web UI.

#### **dataServices**

An array of objects that describe REST or websocket dataservices.

#### **configurationData**

An object that describes the resource structure that the application plug-in uses for storing user, group, and server data.

## Application web content attributes

An application that has the *webContent* attribute defined provides content that is displayed in a Zowe web UI.

The following attributes determine some of this behavior:

### framework

States the type of web framework that is used, which determines the other attributes that are valid in *webContent*.

- **angular2**: Defines the application as having an Angular (2+) web framework component. This is the standard for a "native" framework Zowe application.
- **iframe**: Defines the application as being external to the native Zowe web application environment, but instead embedded in an iframe wrapper.

### launchDefinition

An object that details several attributes for presenting the application in a web UI.

- **pluginShortNameDefault**: A string that gives a name to the application when i18n is not present. When i18n is present, i18n is applied by using the *pluginShortNameKey*.
- **descriptionDefault**: A longer string that specifies a description of the application within a UI. The description is seen when i18n is not present. When i18n is present, i18n is applied by using the *descriptionKey*.
- **imageSrc**: The relative path (from /web) to a small image file that represents the application icon.

### defaultWindowStyle

An object that details the placement of a default window for the application in a web UI.

- **width**: The default width of the application plug-in window, in pixels.
- **height**: The default height of the application plug-in window, in pixels.

## Iframe application web content

In addition to the general web content attributes, when the framework of an application is "iframe", you must specify the page that is being embedded in the iframe. To do so, include the attribute *startingPage* within *webContent*. *startingPage* is relative to the application's /web directory.

Specify *startingPage* as a relative path rather than an absolute path because the *pluginDefinition.json* file is intended to be read-only, and therefore would not work well when the hostname of a page changes.

Within an IFrame, the application plug-in still has access to the globals that are used by Zowe for application-to-application communication; simply access *window.parent.ZoweZLUX*.

## Dataservices

Dataservices are a dynamic component of the backend of a Zowe application. Dataservices are optional, because the proxy server might only serve static content for a particular application. However, when included in an application, a dataservice defines a URL space for which the server will run the extensible code from the application. Dataservices are primarily intended to be used to create REST APIs and Websocket channels.

### Defining a dataservice

Within the sample-app repository, in the top directory, you will find a *pluginDefinition.json* file. Each application requires this file, because it defines how the server registers and uses the backend of an application (called a plug-in in the terminology of the proxy server).

Within the JSON file, there is a top level attribute, *dataServices*:

```
"dataServices": [
  {
    "type": "router",
    "name": "hello",
    "serviceLookupMethod": "external",
    "fileName": "helloWorld.js",
```

```

        "routerFactory": "helloWorldRouter",
        "dependenciesIncluded": true
    }
]

```

## Dataservices defined in pluginDefinition

The following attributes are valid for each dataservice in the *dataServices* array:

### **type**

Specify one of the following values:

- **router**: Router dataservices that run under the proxy server, and use ExpressJS Routers for attaching actions to URLs and methods.
- **service**: Service dataservices that run under ZSS, and utilize the API of ZSS dataservices for attaching actions to URLs and methods.

### **name**

The name of the service that must be unique for each `pluginDefinition.json` file. The name is used to reference the dataservice during logging and it is also used in the construction of the URL space that the dataservice occupies.

### **serviceLookupMethod**

Specify `external` unless otherwise instructed.

### **fileName**

The name of the file that is the entry point for construction of the dataservice, relative to the application's `/lib` directory. In the case of `sample-app`, upon transpilation of the typescript code, javascript files are placed into the `/lib` directory.

### **routerFactory (Optional)**

When you use a router dataservice, the dataservice is included in the proxy server through a `require()` statement. If the dataservice's exports are defined such that the router is provided through a factory of a specific name, you must state the name of the exported factory using this attribute.

### **dependenciesIncluded**

Must be `true` for anything in the `pluginDefinition.json` file. (This setting is `false` only when adding dataservices to the server dynamically.)

## **Limiting the length of datasource paths for RBAC**

If your administrator configures the Zowe Application Framework to use role-based access control (RBAC), then when you create a datasource you must consider the length of its paths.

To control access to dataservices, administrators can enable RBAC, then use a z/OS security product such as RACF to map roles and authorities to a System Authorization Facility (SAF) profile. For information on RBAC, see [Applying role-based access control to dataservices](#) on page 84.

SAF profiles have the following format:

```
<product>.<instance id>.SVC.<pluginid_with_underscores>.<service>.<HTTP method>.<dataservice path with forward slashes '/' replaced by periods '.'>
```

For example, to access this datasource endpoint:

```
/ZLUX/plugins/org.zowe.foo/services/baz/_current/users/fred
```

Users must have READ access to the following profile:

```
ZLUX.DEFAULT.SVC.ORG_ZOWE_FOO.BAZ.POST.USERS.FRED
```

Profiles cannot contain more than 246 characters. If the path section of an endpoint URL makes the profile name exceed limit, the path is trimmed to only include elements that do not exceed the limit. For example, imagine that each path section in this endpoint URL contains 64 characters:

```
/ZLUX/plugins/org.zowe.zosssystem.subsystems/services/data/_current/aa..a/
bb..b/cc..c/dd..d
```

So aa..a is 64 "a" characters, bb..b is 64 "b" characters, and so on. The URL could then map to the following example profile:

```
ZLUX.DEFAULT.SVC.ORG_ZOWE_ZOSSYSTEM_SUBSYSTEMS.DATA.GET.AA..A.BB..B
```

The profile ends at the BB..B section because adding CC..C would put it over 246 characters. So in this example, all dataservice endpoints with paths that start with AA..A.BB..B are controlled by this one profile.

To avoid this issue, we recommend that you maintain relatively short endpoint URL paths.

## Dataservice API

The API for a dataservice can be categorized as Router-based or ZSS-based, and Websocket or not.

**Note:** Each Router dataservice can safely import express, express-ws, and bluebird without requiring the modules to be present, because these modules exist in the proxy server's directory and the *NODE\_MODULES* environment variable can include this directory.

### Router-based dataservices

#### *HTTP/REST router dataservices*

Router-based dataservices must return a (bluebird) Promise that resolves to an ExpressJS router upon success. For more information, see the ExpressJS guide on use of Router middleware: [Using Router Middleware](#).

Because of the nature of Router middleware, the dataservice need only specify URLs that stem from a root '/' path, as the paths specified in the router are later prepended with the unique URL space of the dataservice.

The Promise for the Router can be within a Factory export function, as mentioned in the *pluginDefinition* specification for *routerFactory* above, or by the module constructor.

An example is available in `sample-app/nodeServer/ts/helloWorld.ts`

#### *Websocket router dataservices*

ExpressJS routers are fairly flexible, so the contract to create the Router for Websockets is not significantly different.

Here, the express-ws package is used, which adds websockets through the ws package to ExpressJS.

The two changes between a websocket-based router and a normal router are that the method is 'ws', as in `router.ws(<url>, <callback>)`, and the callback provides the websocket on which you must define event listeners.

See the ws and express-ws topics on [www.npmjs.com](http://www.npmjs.com) for more information about how they work, as the API for websocket router dataservices is primarily provided in these packages.

An example is available in `zlux-server-framework/plugins/terminal-proxy/lib/terminalProxy.js`

#### *Router dataservice context*

Every router-based dataservice is provided with a *Context* object upon creation that provides definitions of its surroundings and the functions that are helpful. The following items are present in the *Context* object:

##### **serviceDefinition**

The dataservice definition, originally from the *pluginDefinition.json* file within a plug-in.

##### **serviceConfiguration**

An object that contains the contents of configuration files, if present.

##### **logger**

An instance of a Zowe Logger, which has its component name as the unique name of the dataservice within a plug-in.

#### **makeSublogger**

A function to create a Zowe Logger with a new name, which is appended to the unique name of the dataservice.

#### **addBodyParseMiddleware**

A function that provides common body parsers for HTTP bodies, such as JSON and plaintext.

#### **plugin**

An object that contains more context from the plug-in scope, including:

- **pluginDef**: The contents of the `pluginDefinition.json` file that contains this dataservice.
- **server**: An object that contains information about the server's configuration such as:
  - **app**: Information about the product, which includes the *productCode* (for example: `ZLUX`).
  - **user**: Configuration information of the server, such as the port on which it is listening.

## Internationalizing applications

You can internationalize Zowe application plug-ins using Angular and React frameworks. Internationalized applications display in translated languages and include structures for ongoing translation updates.

The steps below use the [Zowe Sample Angular Application](#) and [Zowe Sample React Application](#) as examples. Your applications might have slightly different requirements, for example the React Sample Application requires the `react-i18next` library, but your application might require a different React library.

For detailed information on Angular or React, see their documentation. For detailed information on specific internationalization libraries, see their documentation. You can also reference the [Sample Angular Application internationalization tutorial](#).

After you internationalize your application, you can view it by following steps in [Changing the desktop language](#) on page 112.

### Internationalizing Angular applications

Zowe applications that use the Angular framework depend on `.xlf` formatted files to store static translated content and `.json` files to store dynamic translated content. These files must be in the application's `web/assets/i18n` folder at runtime. Each translated language will have its own file.

To internationalize an application, you must install Angular-compatible internationalization libraries. Be aware that libraries can be better suited to either static or dynamic HTML elements. The examples in this task use the `ngx-i18nsupport` library for static content and `angular-i110n` for dynamic content.

To internationalize Zowe Angular applications, take the following steps:

1. To install internationalization libraries, use the `npm` command, for example:

```
npm install --save-dev ngx-i18nsupport
npm install --save-dev angular-i110n
```

**Note** `--save-dev` commits the library to the application's required libraries list for future use.

2. To support the CLI tools and to control output, create a `webClient/tsconfig.i18n.json` typescript file and add the following content:

```
{
  "extends": "../../zlux-app-manager/virtual-desktop/plugin-config/
tsconfig.ngx-i18n.json",
  "include": [
    "./src"
  ],
}
```

```

    "compilerOptions": {
      "outDir": "./src/assets/i18n",
      "skipLibCheck": true
    }
}

```

For example, see this file in the [Sample Angular Application](#).

3. In the static elements in your HTML files, tag translatable content with the i18n attribute within an Angular template, for example:

```

<div>
  <p i18n="welcome message@@welcome">Welcome</p>
</div>

```

The attribute should include a message ID, for example the @@welcome above.

4. To configure static translation builds, take the following steps:

- a. In the `webClient/package.json` script, add the following line:

```

"i18n": "ng-xi18n -p tsconfig.i18n.json --i18nFormat=xlf --
outfile=messages.xlf && xliffmerge -p xliffmerge.json",

```

- b. In the `in webClient` directory, create a `xliffmerge.json` file, add the following content, and specify the codes for each language you will translate in the `languages` parameter:

```

{
  "xliffmergeOptions": {
    "srcDir": "src/assets/i18n",
    "genDir": "src/assets/i18n",
    "i18nFile": "messages.xlf",
    "i18nBaseFile": "messages",
    "i18nFormat": "xlf",
    "encoding": "UTF-8",
    "defaultLanguage": "en",
    "languages": ["fr", "ru"],
    "useSourceAsTarget": true
  }
}

```

When you run the `i18n` script, it reads this file and generates a `messages.[lang].xlf` file in the `src/assets/i18n` directory for each language specified in the `languages` parameter. Each file contains the untranslated text from the `i18n`-tagged HTML elements.

5. Run the following command to run the `i18n` script and extract `i18n` tagged HTML elements to `.xlf` files:

```
npm run i18n
```

**Note** If you change static translated content, you must run the `npm run build` command to build the application, and then re-run the `npm run i18n` command to extract the tagged content again.

6. In each `.xlf` file, replace `target` element strings with translated versions of the `source` element strings. For example:

```

<source>App Request Test</source>
<target>Test de Demande à l'App</target>

```

7. Run the following command to rebuild the application:

```
npm run build
```

When you [Changing the desktop language](#) on page 112 to one of the application's translated languages, the application displays the translated strings.

**8.** For dynamic translated content, follow these steps:

- a. Import and utilize angular-i10n objects within an Angular component, for example:

```
import { LocaleService, TranslationService, Language } from 'angular-i10n';
@Component({
  selector: 'app-root',
  templateUrl: './app.component.html',
  styleUrls: ['./app.component.css'],
  providers: [HelloService]
})

export class AppComponent {
  @Language() lang: string;

  public myDynamicMessage:string = '';

  constructor(
    public locale: LocaleService,
    public translation: TranslationService) { }

  sayHello() {
    this.myDynamicMessage =
      `${this.translation.translate('my_message')}`;
  }
}
```

- b. In the related Angular template, you can implement `myDynamicMessage` as an ordinary substitutable string, for example:

```
<div>
  <textarea class="response" placeholder="Response" i18n-placeholder="@@myStaticPlaceholder">{{myDynamicMessage}}</textarea>
</div>
```

**9.** Create logic to copy the translation files to the `web/assets` directory during the webpack process, for example in the sample application, the following JavaScript in the `copy-webpack-plugin` file copies the files:

```
var config = {
  'entry': [
    path.resolve(__dirname, './src/plugin.ts')
  ],
  'output': {
    'path': path.resolve(__dirname, '../web'),
    'filename': 'main.js',
  },
  'plugins': [
    new CopyWebpackPlugin([
      {
        from: path.resolve(__dirname, './src/assets'),
        to: path.resolve('../web/assets')
      }
    ])
  ]
};
```

**Note:** Do not edit files in the `web/assets/i18n` directory. They are overwritten by each build.

### Internationalizing React applications

To internationalize Zowe applications using the React framework, take the following steps:

**Note:** These examples use the recommended react-i18next library, which does not differentiate between dynamic and static content, and unlike the Angular steps above does not require a separate build process.

1. To install the React library, run the following command:

```
npm install --save-dev react-i18next
```

2. In the directory that contains your `index.js` file, create an `i18n.js` file and add the translated content, for example:

```
import i18n from "i18next";
import { initReactI18next } from "react-i18next";

// the translations
// (tip move them in a JSON file and import them)
const resources = {
  en: {
    translation: {
      "Welcome to React": "Welcome to React and react-i18next"
    }
  }
};

i18n
  .use(initReactI18next) // passes i18n down to react-i18next
  .init({
    resources,
    lng: "en",

    keySeparator: false, // we do not use keys in form messages.welcome

    interpolation: {
      escapeValue: false // react already safes from xss
    }
  });

export default i18n;
```

3. Import the `i18n` file from the previous step into `index.js` file so that you can use it elsewhere, for example:

```
import React, { Component } from "react";
import ReactDOM from "react-dom";
import './i18n';
import App from './App';

// append app to dom
ReactDOM.render(
  <App />,
  document.getElementById("root")
);
```

4. To internationalize a component, include the `useTranslation` hook and reference it to substitute translation keys with their translated values. For example:

```
import React from 'react';

// the hook
import { useTranslation } from 'react-i18next';

function MyComponent () {
  const { t, i18n } = useTranslation(); // use
  return <h1>{t('Welcome to React')}</h1>
}
```

## Internationalizing application desktop titles

To display the translated application name and description in the Desktop, take the following steps:

1. For each language, create a `pluginDefinition.i18n.<lang_code>.json` file. For example, for German create a `pluginDefinition.i18n.de.json` file.
2. Place the `.json` files in the `web/assets/i18n` directory.
3. Translate the `pluginShortNameKey` and `descriptionKey` values in the application's `pluginDefinition.json` file. For example, for the file below you would translate the values `"sampleangular"` and `"sampleangulardescription"`:

```
{
  "identifier": "org.zowe.zlux.sample.angular",
  "apiVersion": "1.0.0",
  "pluginVersion": "1.1.0",
  "pluginType": "application",
  "webContent": {
    "framework": "angular2",
    "launchDefinition": {
      "pluginShortNameKey": "sampleangular",
      "pluginShortNameDefault": "Angular Sample",
      "imageSrc": "assets/icon.png"
    },
    "descriptionKey": "sampleangulardescription",
    "descriptionDefault": "Sample App Showcasing Angular Adapter",
  }
}
```

4. Add the translated values to the translation file. For example, the German translation file example, `pluginDefinition.i18n.de.json`, would look like this:

```
{
  "sampleangular": "Beispiel Angular",
  "sampleangulardescription": "Beispiel Angular Anwendung"
}
```

5. Create logic to copy the translation files to the `web/assets` directory during the webpack process. For example, in the [Sample Angular Application](#) the following JavaScript in the `webClient/webpack.config.js` file copies files to the `web/assets` directory:

```
var config = {
  'entry': [
    path.resolve(__dirname, './src/plugin.ts')
  ],
  'output': {
    'path': path.resolve(__dirname, '../web'),
    'filename': 'main.js',
  },
  'plugins': [
    new CopyWebpackPlugin([
      {
        from: path.resolve(__dirname, './src/assets'),
        to: path.resolve('../web/assets')
      }
    ])
  ];
};
```

## Zowe Desktop and window management

The Zowe Desktop is a web component of Zowe, which is an implementation of `MVDWindowManagement`, the interface that is used to create a window manager.

The code for this software is in the `zlux-app-manager` repository.

The interface for building an alternative window manager is in the `zlux-platform` repository.

Window Management acts upon Windows, which are visualizations of an instance of an application plug-in. Application plug-ins are plug-ins of the type "application", and therefore the Zowe Desktop operates around a collection of plug-ins.

**Note:** Other objects and frameworks that can be utilized by application plug-ins, but not related to window management, such as application-to-application communication, Logging, URI lookup, and Auth are not described here.

## Loading and presenting application plug-ins

Upon loading the Zowe Desktop, a GET call is made to `/plugins?type=application`. The GET call returns a JSON list of all application plug-ins that are on the server, which can be accessed by the user. Application plug-ins can be composed of dataservices, web content, or both. Application plug-ins that have web content are presented in the Zowe Desktop UI.

The Zowe Desktop has a taskbar at the bottom of the page, where it displays each application plug-in as an icon with a description. The icon that is used, and the description that is presented are based on the application plug-in's `PluginDefinition`'s `webContent` attributes.

## Plug-in management

Application plug-ins can gain insight into the environment in which they were spawned through the Plugin Manager. Use the Plugin Manager to determine whether a plug-in is present before you act upon the existence of that plug-in. When the Zowe Desktop is running, you can access the Plugin Manager through `ZoweZLUX.PluginManager`

The following are the functions you can use on the Plugin Manager:

- `getPlugin(pluginID: string)`
  - Accepts a string of a unique plug-in ID, and returns the Plugin Definition Object (`DesktopPluginDefinition`) that is associated with it, if found.

## Application management

Application plug-ins within a Window Manager are created and acted upon in part by an Application Manager. The Application Manager can facilitate communication between application plug-ins, but formal application-to-application communication should be performed by calls to the Dispatcher. The Application Manager is not normally directly accessible by application plug-ins, instead used by the Window Manager.

The following are functions of an Application Manager:

Function	Description
<code>spawnApplication(plugin: DesktopPluginDefinition, launchMetadata: any): Promise&lt;MVDHosting.InstanceId&gt;;</code>	Opens an application instance into the Window Manager, with or without context on what actions it should perform after creation.
<code>killApplication(plugin: ZLUX.Plugin, appId:MVDHosting.InstanceId): void;</code>	Removes an application instance from the Window Manager.
<code>showApplicationWindow(plugin: DesktopPluginDefinitionImpl): void;</code>	Makes an open application instance visible within the Window Manager.
<code>isApplicationRunning(plugin: DesktopPluginDefinitionImpl): boolean;</code>	Determines if any instances of the application are open in the Window Manager.

## Windows and Viewports

When a user clicks an application plug-in's icon on the taskbar, an instance of the application plug-in is started and presented within a Viewport, which is encapsulated in a Window within the Zowe Desktop. Every instance of an application plug-in's web content within Zowe is given context and can listen on events about the Viewport

and Window it exists within, regardless of whether the Window Manager implementation utilizes these constructs visually. It is possible to create a Window Manager that only displays one application plug-in at a time, or to have a drawer-and-panel UI rather than a true windowed UI.

When the Window is created, the application plug-in's web content is encapsulated dependent upon its framework type. The following are valid framework types:

- *"angular2"*: The web content is written in Angular, and packaged with Webpack. Application plug-in framework objects are given through @injectables and imports.
- *"iframe"*: The web content can be written using any framework, but is included through an iframe tag. Application plug-ins within an iframe can access framework objects through *parent.RocketMVD* and callbacks.

In the case of the Zowe Desktop, this framework-specific wrapping is handled by the Plugin Manager.

## Viewport Manager

Viewports encapsulate an instance of an application plug-in's web content, but otherwise do not add to the UI (they do not present Chrome as a Window does). Each instance of an application plug-in is associated with a viewport, and operations to act upon a particular application plug-in instance should be done by specifying a viewport for an application plug-in, to differentiate which instance is the target of an action. Actions performed against viewports should be performed through the Viewport Manager.

The following are functions of the Viewport Manager:

Function	Description
<code>createViewport(providers: ResolvedReflectiveProvider[]): MVDHosting.ViewportId;</code>	Creates a viewport into which an application plug-in's webcontent can be embedded.
<code>registerViewport(viewportId: MVDHosting.ViewportId, instanceId: MVDHosting.InstanceId): void;</code>	Registers a previously created viewport to an application plug-in instance.
<code>destroyViewport(viewportId: MVDHosting.ViewportId): void;</code>	Removes a viewport from the Window Manager.
<code>getApplicationInstanceId(viewportId: MVDHosting.ViewportId): MVDHosting.InstanceId   null;</code>	Returns the ID of an application plug-in's instance from within a viewport within the Window Manager.

## Injection Manager

When you create Angular application plug-ins, they can use injectables to be informed of when an action occurs. Iframe application plug-ins indirectly benefit from some of these hooks due to the wrapper acting upon them, but Angular application plug-ins have direct access.

The following topics describe injectables that application plug-ins can use.

### Plug-in definition

```
@Inject(Angular2InjectionTokens.PLUGIN_DEFINITION) private pluginDefinition:  
ZLUX.ContainerPluginDefinition
```

Provides the plug-in definition that is associated with this application plug-in. This injectable can be used to gain context about the application plug-in. It can also be used by the application plug-in with other application plug-in framework objects to perform a contextual action.

### Logger

```
@Inject(Angular2InjectionTokens.LOGGER) private logger: ZLUX.ComponentLogger
```

Provides a logger that is named after the application plug-in's plugin definition ID.

## Launch Metadata

```
@Inject(Angular2InjectionTokens.LAUNCH_METADATA) private launchMetadata: any
```

If present, this variable requests the application plug-in instance to initialize with some context, rather than the default view.

## Viewport Events

```
@Inject(Angular2InjectionTokens.VIEWPORT_EVENTS) private viewportEvents:  
Angular2PluginViewportEvents
```

Presents hooks that can be subscribed to for event listening. Events include:

`resized: Subject<{width: number, height: number}>`

Fires when the viewport's size has changed.

## Window Events

```
@Inject(Angular2InjectionTokens.WINDOW_ACTIONS) private windowActions:  
Angular2PluginWindowActions
```

Presents hooks that can be subscribed to for event listening. The events include:

Event	Description
<code>maximized: Subject&lt;void&gt;</code>	Fires when the Window is maximized.
<code>minimized: Subject&lt;void&gt;</code>	Fires when the Window is minimized.
<code>restored: Subject&lt;void&gt;</code>	Fires when the Window is restored from a minimized state.
<code>moved: Subject&lt;{top: number, left: number}&gt;</code>	Fires when the Window is moved.
<code>resized: Subject&lt;{width: number, height: number}&gt;</code>	Fires when the Window is resized.
<code>titleChanged: Subject&lt;string&gt;</code>	Fires when the Window's title changes.

## Window Actions

```
@Inject(Angular2InjectionTokens.WINDOW_ACTIONS) private windowActions:  
Angular2PluginWindowActions
```

An application plug-in can request actions to be performed on the Window through the following:

Item	Description
<code>close(): void</code>	Closes the Window of the application plug-in instance.
<code>maximize(): void</code>	Maximizes the Window of the application plug-in instance.
<code>minimize(): void</code>	Minimizes the Window of the application plug-in instance.
<code>restore(): void</code>	Restores the Window of the application plug-in instance from a minimized state.
<code>setTitle(title: string):void</code>	Sets the title of the Window.

Item	Description
<code>setPosition(pos: {top: number, left: number, width: number, height: number}): void</code>	Sets the position of the Window on the page and the size of the window.
<code>spawnContextMenu(xPos: number, yPos: number, items: ContextMenuItem[]): void</code>	Opens a context menu on the application plug-in instance, which uses the Context Menu framework.
<code>registerCloseHandler(handler: () =&gt; Promise&lt;void&gt;): void</code>	Registers a handler, which is called when the Window and application plug-in instance are closed.

## Configuration Dataservice

The Configuration Dataservice is an essential component of the Zowe Application Framework, which acts as a JSON resource storage service, and is accessible externally by REST API and internally to the server by dataservices.

The Configuration Dataservice allows for saving preferences of applications, management of defaults and privileges within a Zowe ecosystem, and bootstrapping configuration of the server's dataservices.

The fundamental element of extensibility of the Zowe Application Framework is a *plug-in*. The Configuration Dataservice works with data for plug-ins. Every resource that is stored in the Configuration Service is stored for a particular plug-in, and valid resources to be accessed are determined by the definition of each plug-in in how it uses the Configuration Dataservice.

The behavior of the Configuration Dataservice is dependent upon the Resource structure for a plug-in. Each plug-in lists the valid resources, and the administrators can set permissions for the users who can view or modify these resources.

### Resource Scope

Data is stored within the Configuration Dataservice according to the selected *Scope*. The intent of *Scope* within the Dataservice is to facilitate company-wide administration and privilege management of Zowe data.

When a user requests a resource, the resource that is retrieved is an override or an aggregation of the broader scopes that encompass the *Scope* from which they are viewing the data.

When a user stores a resource, the resource is stored within a *Scope* but only if the user has access privilege to update within that *Scope*.

*Scope* is one of the following:

#### Product

Configuration defaults that come with the product. Cannot be modified.

#### Site

Data that can be used between multiple instances of the Zowe Application Server.

#### Instance

Data within an individual Zowe Application Server.

#### Group

Data that is shared between multiple users in a group.(Pending)

#### User

Data for an individual user.(Pending)

**Note:** While Authorization tuning can allow for settings such as GET from Instance to work without login, *User* and *Group* scope queries will be rejected if not logged in due to the requirement to pull resources from a specific

user. Because of this, *User* and *Group* scopes will not be functional until the Security Framework is merged into the mainline.

Where *Product* is the broadest scope and *User* is the narrowest scope.

When you specify *Scope User*, the service manages configuration for your particular username, using the authentication of the session. This way, the *User* scope is always mapped to your current username.

Consider a case where a user wants to access preferences for their text editor. One way they could do this is to use the REST API to retrieve the settings resource from the *Instance* scope.

The *Instance* scope might contain editor defaults set by the administrator. But, if there are no defaults in *Instance*, then the data in *Group* and *User* would be checked.

Therefore, the data the user receives would be no broader than what is stored in the *Instance* scope, but might have only been the settings they saved within their own *User* scope (if the broader scopes do not have data for the resource).

Later, the user might want to save changes, and they try to save them in the *Instance* scope. Most likely, this action will be rejected because of the preferences set by the administrator to disallow changes to the *Instance* scope by ordinary users.

## **REST API**

When you reach the Configuration Service through a REST API, HTTP methods are used to perform the desired operation.

The HTTP URL scheme for the configuration dataservice is:

```
<Server>/plugins/com.rs.configjs/services/data/<plugin ID>/<Scope>/<resource>/<optional subresources>?<query>
```

Where the resources are one or more levels deep, using as many layers of subresources as needed.

Think of a resource as a collection of elements, or a directory. To access a single element, you must use the query parameter "name="

### **REST query parameters**

#### **Name** (string)

Get or put a single element rather than a collection.

#### **Recursive** (boolean)

When performing a DELETE, specifies whether to delete subresources too.

#### **Listing** (boolean)

When performing a GET against a resource with content subresources, listing=true will provide the names of the subresources rather than both the names and contents.

## **REST HTTP methods**

Below is an explanation of each type of REST call.

Each API call includes an example request and response against a hypothetical application called the "code editor".

### **GET**

```
GET /plugins/com.rs.configjs/services/data/<plugin>/<scope>/<resource>?name=<element>
```

- This returns JSON with the attribute "content" being a JSON resource that is the entire configuration that was requested. For example:

```
/plugins/com.rs.configjs/services/data/org.openmainframe.zowe.codeeditor/user/sessions/default?name=tabs
```

The parts of the URL are:

- Plugin: org.openmainframe.zowe.codeeditor
- Scope: user
- Resource: sessions
- Subresource: default
- Element = tabs

The response body is a JSON config:

```
{
  "_objectType" : "com.rs.config.resource",
  "_metadataVersion" : "1.1",
  "resource" : "org.openmainframe.zowe.codeeditor/USER/sessions/default",
  "contents" : {
    "_metadataVersion" : "1.1",
    "_objectType" : "org.openmainframe.zowe.codeeditor.sessions.tabs",
    "tabs" : [ {
      "title" : "TSSPG.REXX.EXEC(ARCTEST2)",
      "filePath" : "TSSPG.REXX.EXEC(ARCTEST2)",
      "isDataset" : true
    }, {
      "title" : ".profile",
      "filePath" : "/u/tsspg/.profile"
    }
  ]
}
```

`GET /plugins/com.rs.configjs/services/data/<plugin>/<scope>/<resource>`

This returns JSON with the attribute `content` being a JSON object that has each attribute being another JSON object, which is a single configuration element.

`GET /plugins/com.rs.configjs/services/data/<plugin>/<scope>/<resource>`

(When subresources exist.)

This returns a listing of subresources that can, in turn, be queried.

**PUT**

`PUT /plugins/com.rs.configjs/services/data/<plugin>/<scope>/<resource>?name=<element>`

Stores a single element (must be a JSON object `{...}`) within the requested scope, ignoring aggregation policies, depending on the user privilege. For example:

`/plugins/com.rs.configjs/services/data/org.openmainframe.zowe.codeeditor/user/sessions/default?name=tabs`

Body:

```
{
  "_metadataVersion" : "1.1",
  "_objectType" : "org.openmainframe.zowe.codeeditor.sessions.tabs",
  "tabs" : [ {
    "title" : ".profile",
    "filePath" : "/u/tsspg/.profile"
  }, {
    "title" : "TSSPG.REXX.EXEC(ARCTEST2)",
    "filePath" : "TSSPG.REXX.EXEC(ARCTEST2)",
    "isDataset" : true
  }, {
    "title" : ".emacs",
    "filePath" : "/u/tsspg/.emacs"
  }
}
```

```

        "filePath" : "/u/tsspg/.emacs"
    }
}

```

Response:

```
{
  "_objectType" : "com.rs.config.resourceUpdate",
  "_metadataVersion" : "1.1",
  "resource" : "org.openmainframe.zowe.codeeditor/USER/sessions/default",
  "result" : "Replaced item."
}
```

### ***DELETE***

**DELETE /plugins/com.rs.configjs/services/data/<plugin>/<scope>/<resource>?**  
recursive=true

Deletes all files in all leaf resources below the resource specified.

**DELETE /plugins/com.rs.configjs/services/data/<plugin>/<scope>/<resource>?**  
name=<element>

Deletes a single file in a leaf resource.

**DELETE /plugins/com.rs.configjs/services/data/<plugin>/<scope>/<resource>**

- Deletes all files in a leaf resource.
- Does not delete the directory on disk.

### **Administrative access and group**

By means not discussed here, but instead handled by the server's authentication and authorization code, a user might be privileged to access or modify items that they do not own.

In the simplest case, it might mean that the user is able to do a PUT, POST, or DELETE to a level above *User*, such as *Instance*.

The more interesting case is in accessing another user's contents. In this case, the shape of the URL is different. Compare the following two commands:

**GET /plugins/com.rs.configjs/services/data/<plugin>/user/<resource>**

Gets the content for the current user.

**GET /plugins/com.rs.configjs/services/data/<plugin>/users/<username>/<resource>**

Gets the content for a specific user if authorized.

This is the same structure that is used for the *Group* scope. When requesting content from the *Group* scope, the user is checked to see if they are authorized to make the request for the specific group. For example:

**GET /plugins/com.rs.configjs/services/data/<plugin>/group/<groupname>/<resource>**

Gets the content for the given group, if the user is authorized.

### **Application API**

Retrieves and stores configuration information from specific scopes.

**Note:** This API should only be used for configuration administration user interfaces.

**ZLUX.UriBroker.pluginConfigForScopeUri(pluginDefinition: ZLUX.Plugin, scope: string, resourcePath:string, resourceName:string): string;**

A shortcut for the preceding method, and the preferred method when you are retrieving configuration information, is simply to "consume" it. It "asks" for configurations using the *User* scope, and allows the configuration service to decide which configuration information to retrieve and how to aggregate it. (See below on how the configuration service evaluates what to return for this type of request).

```
ZLUX.UriBroker.pluginConfigUri(pluginDefinition: ZLUX.Plugin,
resourcePath:string, resourceName:string): string;
```

## Internal and bootstrapping

Some dataservices within plug-ins can take configuration that affects their behavior. This configuration is stored within the Configuration Dataservice structure, but it is not accessible through the REST API.

Within the `deploy` directory of a Zowe installation, each plug-in might optionally have an `_internal` directory. An example of such a path is:

```
deploy/instance/ZLUX/pluginStorage/<pluginName>/_internal
```

Within each `_internal` directory, the following directories might exist:

- `services/<servicename>`: Configuration resources for the specific service.
- `plugin`: Configuration resources that are visible to all services in the plug-in.

The JSON contents within these directories are provided as Objects to dataservices through the dataservice context Object.

## Plug-in definition

Because the Configuration Dataservices stores data on a per-plug-in basis, each plug-in must define their resource structure to make use of the Configuration Dataservice. The resource structure definition is included in the plug-in's `pluginDefinition.json` file.

For each resource and subresource, you can define an `aggregationPolicy` to control how the data of a broader scope alters the resource data that is returned to a user when requesting a resource from a narrower Scope.

For example:

```
"configurationData": { //is a direct attribute of the pluginDefinition
JSON
  "resources": { //always required
    "preferences": {
      "locationType": "relative", //this is the only option for now, but
later absolute paths may be accepted
      "aggregationPolicy": "override" //override and none for now, but
more in the future
    },
    "sessions": { //the name at this level represents the name
used within a URL, such as /plugins/com.rs.configjs/services/data/
org.openmainframe.zowe.codeeditor/user/sessions
      "aggregationPolicy": "none",
      "subResources": {
        "sessionName": {
          "variable": true, //if variable=true is present, the resource
must be the only one in that group but the name of the resource is
substituted for the name given in the REST request, so it represents more
than one
          "aggregationPolicy": "none"
        }
      }
    }
  }
}
```

## Aggregation policies

Aggregation policies determine how the Configuration Dataservice aggregates JSON objects from different Scopes together when a user requests a resource. If the user requests a resource from the *User* scope, the data from the User scope might replace or be merged with the data from a broader scope such as *Instance*, to make a combined resource object that is returned to the user.

Aggregation policies are defined by a plug-in developer in the plug-in's definition for the Configuration Service, as the attribute `aggregationPolicy` within a resource.

The following policies are currently implemented:

- **NONE**: If the Configuration Dataservice is called for *Scope User*, only user-saved settings are sent, unless there are no user-saved settings for the query, in which case the dataservice attempts to send data that is found at a broader scope.
- **OVERRIDE**: The Configuration Dataservice obtains data for the resource that is requested at the broadest level found, and joins the resource's properties from narrower scopes, overriding broader attributes with narrower ones, when found.

## URI Broker

The URI Broker is an object in the application plug-in web framework, which facilitates calls to the Zowe Application Server by constructing URIs that use the context from the calling application plug-in.

### Accessing the URI Broker

The URI Broker is accessible independent of other frameworks involved such as Angular, and is also accessible through iframe. This is because it is attached to a global when within the Zowe Desktop. For more information, see [Zowe Desktop and window management](#) on page 202. Access the URI Broker through one of two locations:

Natively:

```
window.ZoweZLUX.uriBroker
```

In an iframe:

```
window.parent.ZoweZLUX.uriBroker
```

### Functions

The URI Broker builds the following categories of URIs depending upon what the application plug-in is designed to call.

#### Accessing an application plug-in's dataservices

Dataservices can be based on HTTP (REST) or Websocket. For more information, see [Dataservices](#) on page 195.

##### HTTP Dataservice URI

```
pluginRESTUri(plugin: ZLUX.Plugin, serviceName: string, relativePath:string): string
```

Returns: A URI for making an HTTP service request.

##### Websocket Dataservice URI

```
pluginWSUri(plugin: ZLUX.Plugin, serviceName:string, relativePath:string): string
```

Returns: A URI for making a Websocket connection to the service.

#### Accessing application plug-in's configuration resources

Defaults and user storage might exist for an application plug-in such that they can be retrieved through the Configuration Dataservice.

There are different scopes and actions to take with this service, and therefore there are a few URIs that can be built:

### *Standard configuration access*

```
pluginConfigUri(pluginDefinition: ZLUX.Plugin, resourcePath:string,
resourceName?:string): string
```

Returns: A URI for accessing the requested resource under the user's storage.

### *Scoped configuration access*

```
pluginConfigForScopeUri(pluginDefinition: ZLUX.Plugin, scope: string,
resourcePath:string, resourceName?:string): string
```

Returns: A URI for accessing a specific scope for a given resource.

## **Accessing static content**

Content under an application plug-in's web directory is static content accessible by a browser. This can be accessed through:

```
pluginResourceUri(pluginDefinition: ZLUX.Plugin, relativePath: string): string
```

Returns: A URI for getting static content.

For more information about the web directory, see [Application plug-in filesystem structure](#) on page 192.

## **Accessing the application plug-in's root**

Static content and services are accessed off of the root URI of an application plug-in. If there are other points that you must access on that application plug-in, you can get the root:

```
pluginRootUri(pluginDefinition: ZLUX.Plugin): string
```

Returns: A URI to the root of the application plug-in.

## **Server queries**

A client can find different information about a server's configuration or the configuration as seen by the current user by accessing specific APIs.

### *Accessing a list of plug-ins*

```
pluginListUri(pluginType: ZLUX.PluginType): string
```

Returns: A URI, which when accessed returns the list of existing plug-ins on the server by type, such as "Application" or "all".

## **Application-to-application communication**

Zowe application plug-ins can opt-in to various application framework abilities, such as the ability to have a Logger, use of a URI builder utility, and more. One ability that is unique to a Zowe environment with multiple application plug-ins is the ability for one application plug-in to communicate with another. The application framework provides constructs that facilitate this ability. The constructs are: the Dispatcher, Actions, Recognizers, Registry, and the features that utilize them such as the framework's Context menu.

1. [Why use application-to-application communication?](#) on page 212
2. [Actions](#) on page 213
3. [Recognizers](#) on page 214
4. [Dispatcher](#) on page 216

### **Why use application-to-application communication?**

When working with a computer, people often use multiple applications to accomplish a task, for example checking a dashboard before using a detailed program or checking email before opening a bank statement in a browser. In many environments, the relationship between one program and another is not well defined (you might open one program to learn of a situation, which you solve by opening another program and typing or pasting in content). Or perhaps a hyperlink is provided or an attachment, which opens a program using a lookup table of which the program is the default for handling a certain file extension. The application framework attempts to solve this problem by creating

structured messages that can be sent from one application plug-in to another. An application plug-in has a context of the information that it contains. You can use this context to invoke an action on another application plug-in that is better suited to handle some of the information discovered in the first application plug-in. Well-structured messages facilitate knowing what application plug-in is "right" to handle a situation, and explain in detail what that application plug-in should do. This way, rather than finding out that the attachment with the extension ".dat" was not meant for a text editor, but instead for an email client, one application plug-in might instead be able to invoke an action on an application plug-in, which can handle opening of an email for the purpose of forwarding to others (a more specific task than can be explained with filename extensions).

## Actions

To manage communication from one application plug-in to another, a specific structure is needed. In the application framework, the unit of application-to-application communication is an Action. The typescript definition of an Action is as follows:

```
export class Action implements ZLUX.Action {
    id: string; // id of action itself.
    i18nNameKey: string; // future proofing for I18N
    defaultName: string; // default name for display purposes, w/o I18N
    description: string;
    targetMode: ActionTargetMode;
    type: ActionType; // "launch", "message"
    targetPluginID: string;
    primaryArgument: any;

    constructor(id: string,
               defaultName: string,
               targetMode: ActionTargetMode,
               type: ActionType,
               targetPluginID: string,
               primaryArgument: any) {
        this.id = id;
        this.defaultName = defaultName;
        // proper name for ID/type
        this.targetPluginID = targetPluginID;
        this.targetMode = targetMode;
        this.type = type;
        this.primaryArgument = primaryArgument;
    }

    getDefaultName(): string {
        return this.defaultName;
    }
}
```

An Action has a specific structure of data that is passed, to be filled in with the context at runtime, and a specific target to receive the data. The Action is dispatched to the target in one of several modes, for example: to target a specific instance of an application plug-in, an instance, or to create a new instance. The Action can be less detailed than a message. It can be a request to minimize, maximize, close, launch, and more. Finally, all of this information is related to a unique ID and localization string such that it can be managed by the framework.

### Action target modes

When you request an Action on an application plug-in, the behavior is dependent on the instance of the application plug-in you are targeting. You can instruct the framework how to target the application plug-in with a target mode from the ActionTargetMode enum:

```
export enum ActionTargetMode {
    PluginCreate, // require pluginType
    PluginFindUniqueOrCreate, // required AppInstance/ID
    PluginFindAnyOrCreate, // plugin type
    //TODO PluginFindAnyOrFail
```

```

    System,           // something that is always present
}

```

## Action types

The application framework performs different operations on application plug-ins depending on the type of an Action. The behavior can be quite different, from simple messaging to requesting that an application plug-in be minimized. The types are defined by an enum:

```

export enum ActionType {          // not all actions are meaningful for all
  target modes
  Launch,           // essentially do nothing after target mode
  Focus,            // bring to fore, but nothing else
  Route,             // sub-navigate or "route" in target
  Message,           // "onMessage" style event to plugin
  Method,             // Method call on instance, more strongly
  typed
  Minimize,
  Maximize,
  Close,             // may need to call a "close handler"
}

```

## Loading actions

Actions can be created dynamically at runtime, or saved and loaded by the system at login.

### Dynamically

You can create Actions by calling the following Dispatcher method: `makeAction(id: string, defaultName: string, targetMode: ActionTargetMode, type: ActionType, targetPluginID: string, primaryArgument: any):Action`

### Saved on system

Actions can be stored in JSON files that are loaded at login. The JSON structure is as follows:

```

{
  "actions": [
    {
      "id": "org.zowe.explorer.openmember",
      "defaultName": "Edit PDS in MVS Explorer",
      "type": "Launch",
      "targetMode": "PluginCreate",
      "targetId": "org.zowe.explorer",
      "arg": {
        "type": "edit_pds",
        "pds": {
          "op": "dereference",
          "source": "event",
          "path": [
            "full_path"
          ]
        }
      }
    }
  ]
}

```

## Recognizers

Actions are meant to be invoked when certain conditions are met. For example, you do not need to open a messaging window if you have no one to message. Recognizers are objects within the application framework that use the context that the application plug-in provides to determine if there is a condition for which it makes sense to execute an

Action. Each recognizer has statements about what condition to recognize, and upon that statement being met, which Action can be executed at that time. The invocation of the Action is not handled by the Recognizer; it simply detects that an Action can be taken.

## Recognition clauses

Recognizers associate a clause of recognition with an action, as you can see from the following class:

```
export class RecognitionRule {
  predicate:RecognitionClause;
  actionID:string;

  constructor(predicate:RecognitionClause, actionID:string){
    this.predicate = predicate;
    this.actionID = actionID;
  }
}
```

A clause, in turn, is associated with an operation, and the subclauses upon which the operation acts. The following operations are supported:

```
export enum RecognitionOp {
  AND,
  OR,
  NOT,
  PROPERTY_EQ,
  SOURCE_PLUGIN_TYPE,      // syntactic sugar
  MIME_TYPE,               // ditto
}
```

## Loading Recognizers at runtime

You can add a Recognizer to the application plug-in environment in one of two ways: by loading from Recognizers saved on the system, or by adding them dynamically.

### *Dynamically*

You can call the Dispatcher method, `addRecognizer(predicate:RecognitionClause, actionID:string):void`

### *Saved on system*

Recognizers can be stored in JSON files that are loaded at login. The JSON structure is as follows:

```
{
  "recognizers": [
    {
      "id": "<actionID>",
      "clause": {
        <clause>
      }
    }
  ]
}
```

**clause** can take on one of two shapes:

```
"prop": [ "<keyString>" , "<valueString>" ]
```

Or,

```
"op": "<op enum as string>",
"args": [
```

```

    {<clause>}
]
```

Where this one can again, have subclauses.

### Recognizer example

Recognizers can be simple or complex. The following is an example to illustrate the mechanism:

```

{
  "recognizers": [
    {
      "id": "org.zowe.explorer.openmember",
      "clause": {
        "op": "AND",
        "args": [
          {"prop": ["sourcePluginID", "com.rs.mvd.tn3270"]}, {"prop": [
            "screenID", "ISRUDSM"]
        ]
      }
    }
  ]
}
```

In this case, the Recognizer detects whether it is possible to run the `org.zowe.explorer.openmember` Action when the TN3270 Terminal application plug-in is on the screen ISRUDSM (an ISPF panel for browsing PDS members).

### Dispatcher

The dispatcher is a core component of the application framework that is accessible through the Global `zLUX` Object at runtime. The Dispatcher interprets Recognizers and Actions that are added to it at runtime. You can register Actions and Recognizers on it, and later, invoke an Action through it. The dispatcher handles how the Action's effects should be carried out, acting in combination with the Window Manager and application plug-ins to provide a channel of communication.

### Registry

The Registry is a core component of the application framework, which is accessible through the Global `zLUX` Object at runtime. It contains information about which application plug-ins are present in the environment, and the abilities of each application plug-in. This is important to application-to-application communication, because a target might not be a specific application plug-in, but rather an application plug-in of a specific category, or with a specific featureset, capable of responding to the type of Action requested.

### Pulling it all together in an example

The standard way to make use of application-to-application communication is by having Actions and Recognizers that are saved on the system. Actions and Recognizers are loaded at login, and then later, through a form of automation or by a user action, Recognizers can be polled to determine if there is an Action that can be executed. All of this is handled by the Dispatcher, but the description of the behavior lies in the Action and Recognizer that are used. In the Action and Recognizer descriptions above, there are two JSON definitions: One is a Recognizer that recognizes when the Terminal application plug-in is in a certain state, and another is an Action that instructs the MVS Explorer to load a PDS member for editing. When you put the two together, a practical application is that you can launch the MVS Explorer to edit a PDS member that you have selected within the Terminal application plug-in.

### Error reporting UI

The `zLUX Widgets` repository contains shared widget-like components of the Zowe Desktop, including Button, Checkbox, Paginator, various pop-ups, and others. To maintain consistency in desktop styling across all applications, use, reuse, and customize existing widgets to suit the purpose of the application's function and look.

Ideally, a program should have little to no logic errors. Once in a while a few occur, but more commonly an error occurs from misconfigured user settings. A user might request an action or command that requires certain prerequisites, for example: a proper ZSS-Server configuration. If the program or method fails, the program should notify the user through the UI about the error and how to fix it. For the purposes of this discussion, we will use the Workflow application plug-in in the `zlux-workflow` repository.

### ZluxPopupManagerService

The `ZluxPopupManagerService` is a standard popup widget that can, through its `reportError()` method, be used to display errors with attributes that specify the title or error code, severity, text, whether it should block the user from proceeding, whether it should output to the logger, and other options you want to add to the error dialog. `ZluxPopupManagerService` uses both `ZluxErrorSeverity` and `ErrorReportStruct`.

```
`export declare class ZluxPopupManagerService {`  
  
    eventsSubject: any;  
    listeners: any;  
    events: any;  
    logger: any;  
    constructor();  
    setLogger(logger: any): void;  
    on(name: any, listener: any): void;  
    broadcast(name: any, ...args: any[]): void;  
    processButtons(buttons: any[]): any[];  
    block(): void;  
    unblock(): void;  
    getLoggerSeverity(severity: ZluxErrorSeverity): any;  
    reportError(severity: ZluxErrorSeverity, title: string, text: string,  
    options?: any): Rx.Observable<any>;  
}``
```

### ZluxErrorSeverity

`ZluxErrorSeverity` classifies the type of report. Under the popup-manager, there are the following types: error, warning, and information. Each type has its own visual style. To accurately indicate the type of issue to the user, the error or pop-up should be classified accordingly.

```
`export declare enum ZluxErrorSeverity {`  
  
    ERROR = "error",  
    WARNING = "warning",  
    INFO = "info",  
}``
```

### ErrorReportStruct

`ErrorReportStruct` contains the main interface that brings the specified parameters of `reportError()` together.

```
`export interface ErrorReportStruct {`  
  
    severity: string;  
    modal: boolean;  
    text: string;  
    title: string;  
    buttons: string[];  
}``
```

## Implementation

Import ZluxPopupManagerService and ZluxErrorSeverity from widgets. If you are using additional services with your error prompt, import those too (for example, LoggerService to print to the logger or GlobalVeilService to create a visible semi-transparent gray veil over the program and pause background tasks). Here, widgets is imported from node\_modules\@zlux\ so you must ensure zLUX widgets is used in your package-lock.json or package.json and you have run npm install.

```
import { ZluxPopupManagerService, ZluxErrorSeverity } from '@zlux/widgets';
```

## Declaration

Create a member variable within the constructor of the class you want to use it for. For example, in the Workflow application plug-in under \zlux-workflow\src\app\app\zosmf-server-config.component.ts is a ZosmfServerConfigComponent class with the pop-up manager service variable. To automatically report the error to the console, you must set a logger.

```
`export class ZosmfServerConfigComponent {`  
  
    constructor(  
        private popupManager: ZluxPopupManagerService, )  
    {   popupManager.setLogger(logger); } //Optional  
`}`
```

## Usage

Now that you have declared your variable within the scope of your program's class, you are ready to use the method. The following example describes an instance of the reload() method in Workflow that catches an error when the program attempts to retrieve a configuration from a configService and set it to the program's this.config. This method fails when the user has a faulty zss-Server configuration and the error is caught and then sent to the class' popupManager variable from the constructor above.

```
`reload(): void {`  
  
    this.globalVeilService.showVeil();  
    this.configService  
        .getConfig()  
        .then(config => (this.config = config))  
        .then(_ => setTimeout(() => this.test(), 0))  
        .then(_ => this.globalVeilService.hideVeil())  
        .catch(err => {  
            this.globalVeilService.hideVeil()  
            let errorTitle: string = "Error";  
            let errorMessage: string = "Server configuration not found. Please  
check your zss server.";  
            const options = {  
                blocking: true  
            };  
            this.popupManager.reportError(ZluxErrorSeverity.ERROR,  
errorTitle.toString() +": "+err.status.toString(), errorMessage  
+"\\n"+err.toString(), options);  
        });  
`}`
```

Here, the errorMessage clearly describes the error with a small degree of ambiguity as to account for all types of errors that might occur from that method. The specifics of the error are then generated dynamically and are printed with the err.toString(), which contains the more specific information that is used to pinpoint the problem. The this.popupManager.report() method triggers the error prompt to display. The error severity is set with ZluxErrorSeverity.ERROR and the err.status.toString() describes the status of the error (often classified by a code, for example: 404). The optional parameters in options specify that this error will block the user from interacting with the application plug-in until the error is closed or it until goes away on its own. globalVeilService is optional and is used to create a gray veil on the outside of the program when the error


is caused. You must import `globalVeilService` separately (see the `zlux-workflow` repository for more information).

## HTML

The final step is to have the recently created error dialog display in the application plug-in. If you do `this.popupManager.report()` without adding the component to your template, the error will not be displayed. Navigate to your component's `.html` file. On the Workflow application plug-in, this file will be in `\zlux-workflow\src\app\app\zosmf-server-config.component.html` and the only item left is to add the popup manager component alongside your other classes.

```
<zlux-popup-manager></zlux-popup-manager>
```

So now when the error is called, the new UI element should resemble the following:



The order in which you place the pop-up manager determines how the error dialog will overlap in your UI. If you want the error dialog to overlap other UI elements, place it at the end of the `.html` file. You can also create custom styling through a CSS template, and add it within the scope of your application plug-in.

## Logging utility

The `zlux-shared` repository provides a logging utility for use by dataservices and web content for an application plug-in.

### Logging objects

The logging utility is based on the following objects:

- **Component Loggers:** Objects that log messages for an individual component of the environment, such as a REST API for an application plug-in or to log user access.
- **Destinations:** Objects that are called when a component logger requests a message to be logged. Destinations determine how something is logged, for example, to a file or to a console, and what formatting is applied.
- **Logger:** Central logging object, which can spawn component loggers and attach destinations.

### Logger IDs

Because Zowe application plug-ins have unique identifiers, both dataservices and an application plug-in's web content are provided with a component logger that knows this unique ID such that messages that are logged can be prefixed with the ID. With the association of logging to IDs, you can control verbosity of logs by setting log verbosity by ID.

### Accessing logger objects

#### Logger

The core logger object is attached as a global for low-level access.

#### App Server

NodeJS uses `global` as its global object, so the logger is attached to: `global.COM_RS_COMMON_LOGGER`

## Web

Browsers use `window` as the global object, so the logger is attached to: `window.COM_RS_COMMON_LOGGER`

### Component logger

Component loggers are created from the core logger object, but when working with an application plug-in, allow the application plug-in framework to create these loggers for you. An application plug-in's component logger is presented to dataservices or web content as follows.

### App Server

See **Router Dataservice Context** in the topic [Dataservices](#) on page 195.

## Web

(Angular App Instance Injectable). See **Logger** in [Zowe Desktop and window management](#) on page 202.

### Logger API

The following constants and functions are available on the central logging object.

Attribute	Type	Description	Arguments
<code>makeComponentLogger</code> function		Creates a component logger - Automatically done by the application framework for dataservices and web content	<code>componentIDString</code>
<code>setLogLevelForComponentName</code> function		Sets the verbosity of an existing component logger	<code>componentIDString,</code> <code>logLevel</code>

### Component Logger API

The following constants and functions are available to each component logger.

Attribute	Type	Description	Arguments
<code>SEVERE</code>	const	Is a const for <code>logLevel</code>	
<code>WARNING</code>	const	Is a const for <code>logLevel</code>	
<code>INFO</code>	const	Is a const for <code>logLevel</code>	
<code>FINE</code>	const	Is a const for <code>logLevel</code>	
<code>FINER</code>	const	Is a const for <code>logLevel</code>	
<code>FINEST</code>	const	Is a const for <code>logLevel</code>	
<code>log</code>	function	Used to write a log, specifying the log level	<code>logLevel,</code> <code>messageString</code>
<code>severe</code>	function	Used to write a SEVERE log.	<code>messageString</code>
<code>warn</code>	function	Used to write a WARNING log.	<code>messageString</code>
<code>info</code>	function	Used to write an INFO log.	<code>messageString</code>
<code>debug</code>	function	Used to write a FINE log.	<code>messageString</code>
<code>makeSublogger</code>	function	Creates a new component logger with an ID appended by the string given	<code>componentNameSuffix</code>

## Log Levels

An enum, `LogLevel`, exists for specifying the verbosity level of a logger. The mapping is:

Level	Number
SEVERE	0
WARNING	1
INFO	2
FINE	3
FINER	4
FINEST	5

**Note:** The default log level for a logger is **INFO**.

## Logging verbosity

Using the component logger API, loggers can dictate at which level of verbosity a log message should be visible. You can configure the server or client to show more or less verbose messages by using the core logger's API objects.

Example: You want to set the verbosity of the `org.zowe.foo` application plug-in's dataservice, bar to show debugging information.

```
logger.setLevelForComponentName('org.zowe.foo.bar', LogLevel.DEBUG)
```

## Configuring logging verbosity

The application plug-in framework provides ways to specify what component loggers you would like to set default verbosity for, such that you can easily turn logging on or off.

### *Server startup logging configuration*

The server configuration file allows for specification of default log levels, as a top-level attribute `logLevel`, which takes key-value pairs where the key is a regex pattern for component IDs, and the value is an integer for the log levels.

For example:

```
"logLevel": {
    "com.rs.configjs.data.access": 2,
    //the string given is a regex pattern string, so .* at the end here will
    cover that service and its subloggers.
    "com.rs.myplugin.myservice.*": 4
    //
    // '_' char reserved, and '_' at beginning reserved for server. Just as
    we reserve
    // '_internal' for plugin config data for config service.
    // _unp = universal node proxy core logging
    //"_unp.dsauth": 2
},
```

For more information about the server configuration file, see [Zowe Application Framework configuration](#) on page 77.

## Tutorial: Stand up a local version of the Example Zowe Application Server

The `zlux-app-server` repository is an example of a server built upon the application framework. Within the repository, you will find a collection of build, deploy, and run scripts and configuration files that will help you to configure a simple Zowe Application Server with a few applications included.

## Server layout

At the core of the application infrastructure backend is an extensible server, written for nodeJS and utilizing expressJS for routing. It handles the backend components of an application, and can serve as a proxy for requests from applications to additional servers, as needed. One such proxy destination is the ZSS, the Zowe Application Framework backend component for **Z Secure Services**, a so called agent for the Zowe Application Server. If you want to set up a Zowe Application Framework installation, contact Rocket to obtain the ZSS binary to use in the installation process.

## ZSS and Zowe Application Server overlap

The Zowe Application Server and ZSS utilize the same deployment and Application/Plugin structure, and share some configuration parameters. It is possible to run ZSS and the Zowe Application Server from the same system, in which case you would be running under z/OS USS. This configuration requires that IBM's version of nodeJS is installed beforehand.

Another way to set up Zowe Application Framework is to have the Zowe Application Server running under LUW, while keeping ZSS under USS. This is the configuration scenario presented below. In this scenario, you must clone these github repositories to two different systems, and they will require compatible configurations. If this is your initial setup, it is fine to have identical configuration files and /plugins folders to get started.

## First-time Installation and Use

Getting started with the server requires the following steps:

1. [\(Optional\) Install git for z/OS](#)
2. [Acquire the source code](#)
3. [Acquire external components](#)
4. [Set the server configuration](#)
5. [Build application plug-ins](#)
6. [Deploy server configuration files](#)
7. [Run the server](#)
8. [Connect in a browser!](#)

Follow each step and you will be on your way to your first Zowe Application Server instance.

### 0. (Optional) Install git for z/OS

Because all of the code is on github, yet ZSS must run on z/OS and the Zowe Application Server can optionally run on z/OS as well, having git on z/OS is the most convenient way to work with the source code. The alternative would be to utilize FTP or another method to transfer contents to z/OS. If you'd like to go this route, you can find git for z/OS free of charge here: <http://www.rocketsoftware.com/product-categories/mainframe/git-for-zos>

### 1. Acquire the source code

To get started, first clone or download the GitHub capstone repository <https://github.com/zowe/zlux>.

**Note:** Make sure that you have your SSH key set up and added to GitHub. For how to do this, see [Generating SSH keys](#).

Because we will be configuring ZSS on z/OS's USS, and the Zowe Application Server on a LUW host, you will need to place the contents on both systems. If you are using git, use the following commands.

```
git clone --recursive git@github.com:zowe/zlux.git
cd zlux
git submodule foreach "git checkout master"
cd zlux-build
```

At this point, you have the latest code from each repository on your system. Continue from within `zlux-app-server`.

## 2. Acquire external components

Applications and external servers can require contents that are not in the Zowe github repositories. In the case of the `zlux-app-server`, there is a ZSS binary component which cannot be found in the repositories. To obtain the ZSS binary component, contact the Zowe project.

After you obtain the ZSS binary component, you should receive `zssServer`. This must be placed within `zlux-build/externals/Rocket`, on the z/OS host. For example:

```
mkdir externals
mkdir externals/Rocket

//(on z/OS only)
mv zssServer externals/Rocket
```

## 3. Set the server configuration

Read the [Configuration](#) wiki page for a detailed explanation of the primary items that you will want to configure for your first server.

In short, ensure that within the `config/zluxserver.json` file, `node.http.port` or `node.https.port` and the other HTTPS parameters are set to your liking on the LUW host, and that `zssPort` is set on the z/OS host.

Before you continue, if you intend to use the terminal, at this time (temporarily) it must be pre-configured to know the destination host. Edit `..tn3270-ng2\defaultTN3270.json` to set `host` and `port` to a valid TN3270 server telnet host and port and then save the file. Edit `..vt-ng2\defaultVT.json` to set `host` and `port` to a valid ssh host and port and then save the file.

## 4. Build application plug-ins

### Prerequisites:

- NPM is used when building application plug-ins. The version of NPM needed for the build to succeed should be at least 5.4. You can update NPM by executing `npm install -g npm`.
- You must have ant and ant-contrib installed.

Application plug-ins can contain server and web components. The web components must be built, as webpack is involved in optimized packaging. Server components are also likely to need building if they require external dependencies from NPM, use native code, or are written in typescript.

This example server only needs transpilation and packaging of web components, and therefore we do not need any special build steps for the host running ZSS.

Instead, on the host that runs the Zowe Application Server, run the script that will automatically build all included application plug-ins. Simply,

```
//Windows
build.bat

//Otherwise
build.sh
```

This will take some time to complete.

## 5. Deploy server configuration files

If you are running the Zowe Application Server separate from ZSS, ensure the ZSS installation configuration is deployed. You can accomplish this through:

```
ant deploy
```

On the other hand, if you are running ZSS and the Zowe Application Server on the same host, `build.sh` and `build.bat` execute `deploy` and therefore this task was accomplished in [Step 4](#).

However, if you need to change the server configuration files or if you want to add more application plug-ins to be included at startup, you must update the deploy content to reflect this. Simply running `deploy.bat` or `deploy.sh` will accomplish this, but files such as `zluxserver.json` are only read at startup, so a reload of the Zowe Application Server and ZSS would be required.

## 6. Run the server

At this point, all server files have been configured and the application plug-ins built, so ZSS and the Zowe Application Server are ready to run. First, from the z/OS system, start ZSS.

```
cd ../zlux-app-server/bin
./zssServer.sh
```

If the `zssServer` server did not start, two common sources of error are:

1. The `zssPort` chosen is already occupied. To fix this, edit `config/zluxserver.json` to choose a new one, and re-run `build/deploy.sh` to make the change take effect.
2. The `zssServer` binary does not have the APF bit set. Because this server is meant for secure services, it is required. To fix this, execute `extattr +a zssServer`. Note that you might need to alter the execute permissions of `zssServer.sh` in the event that the previous command is not satisfactory (for example: `chmod +x zssServer.sh`)

Second, from the system with the Zowe Application Server, start it with a few parameters to hook it to ZSS.

```
cd ../zlux-app-server/bin

// Windows:
nodeCluster.bat <parameters>

// Others:
nodeCluster.sh <parameters>
```

Valid parameters for `nodeCluster` are as follows:

- `-h`: Specifies the hostname where ZSS can be found. Use as `-h <hostname>`
- `-P`: Specifies the port where ZSS can be found. Use as `-P <port>`. This overrides `zssPort` from the configuration file.
- `-p`: Specifies the HTTP port to be used by the Zowe Application Server. Use as `-p <port>`. This overrides `node.http.port` from the configuration file.
- `-s`: Specifies the HTTPS port to be used by the Zowe Application Server. Use as `-s <port>`. This overrides `node.https.port` from the configuration file.
- `--noChild`: If specified, tells the server to ignore and skip spawning of child processes defined as `node.childProcesses` in the configuration file.

In the example where we run ZSS on a host named `mainframe.zowe.com`, running on `zssPort = 19997`, the Zowe Application Server running on Windows could be started with the following:

```
nodeCluster.bat -h mainframe.zowe.com -P 19997 -p 19998
```

After which we would be able to connect to the Zowe Application Server at port 19998.

**NOTE:** the parameter parsing is provided by [argumentParser.js](#), which allows for a few variations of input, depending on preference. For example, the following are all valid ways to specify the ZSS host:

- `-h myhost.com`
- `-h=myhost.com`
- `--hostServer myhost.com`
- `--hostServer=myhost.com`

When the Zowe Application Server has started, one of the last messages you will see as bootstrapping completes is that the server is listening on the HTTP/s port. At this time, you should be able to use the server.

## 7. Connect in a browser

Now that ZSS and the Zowe Application Server are both started, you can access this instance by pointing your web browser to the Zowe Application Server. In this example, the address you will want to go to first is the location of the window management application: the Zowe Desktop. The URL is:

```
http(s)://<zLUX App Server>:<node.http(s).port>/zLUX/plugins/
org.zowe.zlux.bootstrap/web/index.html
```

Once here, a Login window opens with a few example application plug-ins in the taskbar at the bottom of the window. To try the application plug-ins to see how they interact with the framework, can login with your mainframe credentials.

- tn3270-ng2: This application communicates with the Zowe Application Server to enable a TN3270 connection in the browser.
- z/OS Subsystems: This application shows various z/OS subsystems installed on the host the ZSS runs on. This is accomplished through discovery of these services by the application's portion running in the ZSS context.
- sample-angular-app: A simple app that show how a zLUX application frontend (here, Angular) component can communicate with an App backend (REST) component.
- sample-react-app: Similar to the Angular application, but using React instead to show how you have the flexibility to use a framework of your choice.
- sample-iframe-app: Similar in functionality to the Angular and React sample application, but presented by means of inclusion of an iframe, to show that pre-existing pages can be included.

### *Deploy example*

```
// All paths relative to zlux-app-server/js or zlux-app-server/bin
// In real installations, these values will be configured during the
install.
"rootDir": "../deploy",
"productDir": "../deploy/product",
"siteDir": "../deploy/site",
"instanceDir": "../deploy/instance",
"groupsDir": "../deploy/instance/groups",
"usersDir": "../deploy/instance/users"
```

## Application plug-in configuration

This section does not cover dynamic runtime inclusion of application plug-ins, but rather application plug-ins that are defined in advance. In the configuration file, a directory can be specified which contains JSON files that tell the server what application plug-in to include and where to find it on disk. The backend of these application plug-ins use the Server's Plugin structure, so much of the server-side references to application plug-ins use the term "Plugin".

To include application plug-ins, be sure to define the location of the Plugins directory in the configuration file, through the top-level attribute *pluginsDir*

**NOTE:** In this repository, the directory for these JSON files is /plugins. To separate configuration files from runtime files, the zlux-app-server repository copies the contents of this folder into /deploy/instance/zLUX/plugins. So, the example configuration file uses the latter directory.

### *Plugins directory example*

```
// All paths relative to zlux-app-server/js or zlux-app-server/bin
// In real installations, these values will be configured during the
install.
//...
"pluginsDir": "../deploy/instance/zLUX/plugins",
```

## ZSS Configuration

Running ZSS requires a JSON configuration file that is similar or the same as the one used for the Zowe Application Server. The attributes that are needed for ZSS, at minimum, are: *rootDir*, *productDir*, *siteDir*, *instanceDir*, *groupsDir*,

*usersDir*, *pluginsDir* and **zssPort**. All of these attributes have the same meaning as described above for the Zowe Application Server, but if the Zowe Application Server and ZSS are not run from the same location, then these directories can be different.

The **zssPort** attribute is specific to ZSS. This is the TCP port on which ZSS will listen to be contacted by the Zowe Application Server. Define this port in the configuration file as a value between 1024-65535.

### Connecting Zowe Application Server to ZSS

When running the Zowe Application Server, simply specify a few flags to declare which ZSS instance the Zowe Application Framework will proxy ZSS requests to:

- **-h**: Declares the host where ZSS can be found. Use as `-h <hostname>`
- **-P**: Declares the port at which ZSS is listening. Use as `-P <port>`

## Tutorial: User Browser Workshop App

This tutorial contains code snippets and descriptions that you can combine to build a complete application. It builds off the project skeleton code found at the [github project repo](#).

By the end of this tutorial, you will:

1. Know how to create an application that displays on the Zowe Desktop
2. Know how to create a Dataservice which implements a simple REST API
3. Be introduced to Typescript programming
4. Be introduced to simple Angular web development
5. Have experience in working with the Zowe Application Framework
6. Become familiar with one of the Zowe Application widgets: the grid widget

:::warning Before continuing, make sure you have completed the prerequisites for this tutorial:

- Setup up the [Tutorial: Stand up a local version of the Example Zowe Application Server](#) on page 221. :::

So, let's get started!

1. [Constructing an App Skeleton](#) on page 226
  - [Defining your first plugin](#) on page 227
  - [Constructing a Simple Angular UI](#) on page 227
  - [Packaging Your Web App](#) on page 229
  - [Adding Your App to the Desktop](#) on page 230
2. [Building your first Dataservice](#) on page 231
  - [Working with ExpressJS](#) on page 231
  - [Adding your Dataservice to the Plugin Definition](#) on page 233
3. [Adding your first Widget](#) on page 234
  - [Adding your Dataservice to the App](#) on page 234
  - [Introducing Zowe Application Server Grid](#) on page 235
4. [Adding Zowe App-to-App Communication](#) on page 237
  - [Calling back to the Starter App](#) on page 240

### Constructing an App Skeleton

Download the skeleton code from the [project repository](#). Next, move the project into the `zlux` source folder created in the prerequisite tutorial.

If you look within this repository, you'll see that a few boilerplate files already exist to help you get your first application plug-in running quickly. The structure of this repository follows the guidelines for Zowe application plug-in filesystem layout, which you can read more about [on the wiki](#).

## Defining your first plugin

Where do you start when making an application plug-in? In the Zowe Application Framework, an application plug-in is a plug-in of type "Application". Every plug-in is bound by their `pluginDefinition.json` file, which describes its properties. Let's start by creating this file.

Create a file, `pluginDefinition.json`, at the root of the `workshop-user-browser-app` folder. The file should contain the following:

```
{
  "identifier": "org.openmainframe.zowe.workshop-user-browser",
  "apiVersion": "1.0.0",
  "pluginVersion": "0.0.1",
  "pluginType": "application",
  "webContent": {
    "framework": "angular2",
    "launchDefinition": {
      "pluginShortNameKey": "userBrowser",
      "pluginShortNameDefault": "User Browser",
      "imageSrc": "assets/icon.png"
    },
    "descriptionKey": "userBrowserDescription",
    "descriptionDefault": "Browse Employees in System",
    "isSingleWindowApp": true,
    "defaultWindowSize": {
      "width": 1300,
      "height": 500
    }
  }
}
```

A description of the values that are placed into this file can be found [on the wiki](#).

Note the following attributes:

- Our application has the unique identifier of `org.openmainframe.zowe.workshop-user-browser`, which can be used to refer to it when running Zowe.
- The application has a `webContent` attribute, because it will have a UI component that is visible in a browser.
  - The `webContent` section states that the application's code will conform to Zowe's Angular application structure, due to it stating `"framework": "angular2"`
  - The application plug-in has certain characteristics that the user will see, such as:
    - The default window size (`defaultWindowSize`),
    - An application plug-in icon that we provided in `workshop-user-browser-app/webClient/src/assets/icon.png`,
    - That we should see it in the browser as an application plug-in named `User Browser`, the value of `pluginShortNameDefault`.

## Constructing a Simple Angular UI

Angular application plug-ins for Zowe are structured such that the source code exists within `webClient/src/app`. In here, you can create modules, components, templates and services in any hierarchy. For the application plug-in we are creating however, we will add three files:

- `userbrowser.module.ts`
- `userbrowser-component.html`
- `userbrowser-component.ts`

At first, let's just build a shell of an application plug-in that can display some simple content. Fill in each file with the following content.

**userbrowser.module.ts**

```

import { NgModule } from '@angular/core'
import { CommonModule } from '@angular/common'
import { FormsModule, ReactiveFormsModule } from '@angular/forms'
import { HttpClientModule } from '@angular/http'

import { UserBrowserComponent } from './userbrowser-component'

@NgModule({
  imports: [FormsModule, ReactiveFormsModule, CommonModule],
  declarations: [UserBrowserComponent],
  exports: [UserBrowserComponent],
  entryComponents: [UserBrowserComponent]
})
export class UserBrowserModule {}

```

**userbrowser-component.html**

```

<div class="parent col-11" id="userbrowserPluginUI">
  {{simpleText}}
</div>

<div class="userbrowser-spinner-position">
  <i class="fa fa-spinner fa-spin fa-3x" *ngIf="resultNotReady"></i>
</div>

```

**userbrowser-component.ts**

```

import {
  Component,
  ViewChild,
  ElementRef,
  OnInit,
  AfterViewInit,
  Inject,
  SimpleChange
} from '@angular/core'
import { Observable } from 'rxjs/Observable'
import { Http, Response } from '@angular/http'
import 'rxjs/add/operator/catch'
import 'rxjs/add/operator/map'
import 'rxjs/add/operator/debounceTime'

import {
  Angular2InjectionTokens,
  Angular2PluginWindowActions,
  Angular2PluginWindowEvents
} from 'pluginlib/inject-resources'

@Component({
  selector: 'userbrowser',
  templateUrl: 'userbrowser-component.html',
  styleUrls: ['userbrowser-component.css']
})
export class UserBrowserComponent implements OnInit, AfterViewInit {
  private simpleText: string
  private resultNotReady: boolean = false

  constructor(
    private element: ElementRef,
    private http: Http,

```

```

    @Inject(Angular2InjectionTokens.LOGGER) private log:
ZLUX.ComponentLogger,
    @Inject(Angular2InjectionTokens.PLUGIN_DEFINITION)
private pluginDefinition: ZLUX.ContainerPluginDefinition,
    @Inject(Angular2InjectionTokens.WINDOW_ACTIONS)
private windowAction: Angular2PluginWindowActions,
    @Inject(Angular2InjectionTokens.WINDOW_EVENTS)
private windowEvents: Angular2PluginWindowEvents
) {
    this.log.info(`User Browser constructor called`)
}

ngOnInit(): void {
    this.simpleText = `Hello World!`
    this.log.info(`App has initialized`)
}

ngAfterViewInit(): void {}
}

```

## Packaging Your Web App

At this time, we've made the source for a Zowe application plug-in that should open in the Zowe Desktop with a greeting to the planet. Before we're ready to use it however, we must transpile the typescript and package the application plug-in. This will require a few build tools first. We'll make an NPM package in order to facilitate this.

Let's create a package.json file within workshop-user-browser-app/webClient. While a package.json can be created through other means such as npm init and packages can be added through commands such as npm install --save-dev [typescript@2.9.0](#), we'll opt to save time by just pasting these contents in:

```
{
  "name": "workshop-user-browser",
  "version": "0.0.1",
  "scripts": {
    "start": "webpack --progress --colors --watch",
    "build": "webpack --progress --colors",
    "lint": "tslint -c tslint.json \"src/**/*.{ts,js}\""
  },
  "private": true,
  "dependencies": {},
  "devDependencies": {
    "@angular/animations": "~6.0.9",
    "@angular/common": "~6.0.9",
    "@angular/compiler": "~6.0.9",
    "@angular/core": "~6.0.9",
    "@angular/forms": "~6.0.9",
    "@angular/http": "~6.0.9",
    "@angular/platform-browser": "~6.0.9",
    "@angular/platform-browser-dynamic": "~6.0.9",
    "@angular/router": "~6.0.9",
    "@zlux/grid": "git+https://github.com/zowe/zlux-grid.git",
    "@zlux/widgets": "git+https://github.com/zowe/zlux-widgets.git",
    "angular2-template-loader": "~0.6.2",
    "copy-webpack-plugin": "~4.5.2",
    "core-js": "~2.5.7",
    "css-loader": "~1.0.0",
    "exports-loader": "~0.7.0",
    "file-loader": "~1.1.11",
    "html-loader": "~0.5.5",
    "rxjs": "~6.2.2",
    "rxjs-compat": "~6.2.2",
    "source-map-loader": "~0.2.3",
  }
}
```

```

    "ts-loader": "~4.4.2",
    "tslint": "~5.10.0",
    "typescript": "~2.9.0",
    "webpack": "~4.0.0",
    "webpack-cli": "~3.0.0",
    "webpack-config": "~7.5.0",
    "zone.js": "~0.8.26"
  }
}

```

Now we are ready to build.

Let's set up our system to automatically perform these steps every time we make updates to the application plug-in.

1. Open a command prompt to `workshop-user-browser-app/webClient`.
2. Set the environment variable `MVD_DESKTOP_DIR` to the location of `zlux-app-manager/virtual-desktop`. For example, set `MVD_DESKTOP_DIR=../../zlux-app-manager/virtual-desktop`. This is needed whenever building individual application web code due to the core configuration files being located in virtual-desktop.
3. Execute `npm install`.
4. Execute `npm run-script start`.

After the first execution of the transpilation and packaging concludes, you should have `workshop-user-browser-app/web` populated with files that can be served by the Zowe Application Server.

### Adding Your App to the Desktop

At this point, your `workshop-user-browser-app` folder contains files for an application plug-in that could be added to a Zowe instance. We will add this to our own Zowe instance. First, ensure that the Zowe Application Server is not running. Then, navigate to the instance's root folder, `/zlux-app-server`.

Within, you'll see a folder, `plugins`. Take a look at one of the files in the folder. You can see that these are JSON files with the attributes **identifier** and **pluginLocation**. These files are what we call **Plugin Locators**, since they point to a plug-in to be included into the server.

Let's make one ourselves. Make a file `/zlux-example-server/plugins/org.openmainframe.zowe.workshop-user-browser.json`, with the following contents:

```

{
  "identifier": "org.openmainframe.zowe.workshop-user-browser",
  "pluginLocation": "../../workshop-user-browser-app"
}

```

When the server runs, it will check for these types of files in its `pluginsDir`, a location known to the server through its specification in the server configuration file. In our case, this is `/zlux-app-server/deploy/instance/ZLUX/plugins/`.

You could place the JSON directly into that location, but the recommended way to place content into the deploy area is through running the server deployment process. Simply:

1. Open up a (second) command prompt to `zlux-build`
2. `ant deploy`

Now you're ready to run the server and see your application plug-in.

1. `cd /zlux-example-server/bin`.
2. `./nodeCluster.sh`.
3. Open your browser to `https://hostname:port`.
4. Login with your credentials.
5. Open the application plug-in on the bottom of the page with the green 'U' icon.

Do you see the Hello World message from [Constructing a Simple Angular UI](#) on page 227. If so, you're in good shape! Now, let's add some content to the application plug-in.

## Building your first Dataservice

An application plug-in can have one or more [Dataservices](#). A Dataservice is a REST or Websocket endpoint that can be added to the Zowe Application Server.

To demonstrate the use of a Dataservice, we'll add one to this application plug-in. The application plug-in needs to display a list of users, filtered by some value. Ordinarily, this sort of data would be contained within a database, where you can get rows in bulk and filter them in some manner. Retrieval of database contents, likewise, is a task that is easily representable through a REST API, so let's make one.

1. Create a file, `workshop-user-browser-app/nodeCluster/ts/tablehandler.ts` Add the following contents:

```
import { Response, Request } from 'express'
import * as table from './usertable'
import { Router } from 'express-serve-static-core'

const express = require('express')
const Promise = require('bluebird')

class UserTableDataservice {
  private context: any
  private router: Router

  constructor(context: any) {
    this.context = context
    let router = express.Router()

    router.use(function noteRequest(req: Request, res: Response, next: any)
    {
      context.logger.info('Saw request, method=' + req.method)
      next()
    })

    router.get('/', function(req: Request, res: Response) {
      res.status(200).json({ greeting: 'hello' })
    })

    this.router = router
  }

  getRouter(): Router {
    return this.router
  }
}

exports.tableRouter = function(context): Router {
  return new Promise(function(resolve, reject) {
    let dataservice = new UserTableDataservice(context)
    resolve(dataservice.getRouter())
  })
}
```

This is boilerplate for making a Dataservice. We lightly wrap ExpressJS Routers in a Promise-based structure where we can associate a Router with a particular URL space, which we will see later. If you were to attach this to the server, and do a GET on the root URL associated, you'd receive the `{"greeting":"hello"}` message.

## Working with ExpressJS

Let's move beyond hello world, and access this user table.

- Within workshop-user-browser-app/nodeCluster/ts/tablehandler.ts, add a function for returning the rows of the user table.

```

const MY_VERSION = '0.0.1'
const METADATA_SCHEMA_VERSION = '1.0'
function respondWithRows(rows: Array<Array<string>>, res: Response): void {
  let rowObjects = rows.map(row => {
    return {
      firstname: row[table.columns.firstname],
      mi: row[table.columns.mi],
      lastname: row[table.columns.lastname],
      email: row[table.columns.email],
      location: row[table.columns.location],
      department: row[table.columns.department]
    }
  })
  let responseBody = {
    _docType: 'org.openmainframe.zowe.workshop-user-browser.user-table',
    _metaDataVersion: MY_VERSION,
    metadata: table.metadata,
    resultMetaDataSchemaVersion: '1.0',
    rows: rowObjects
  }
  res.status(200).json(responseBody)
}

```

Because we reference the userable file through import, we are able to refer to its **metadata** and **columns** attributes here. This **respondWithRows** function expects an array of rows, so we'll improve the Router to call this function with some rows so that we can present them back to the user.

- Update the **UserTableDataservice** constructor, modifying and expanding upon the Router.

```

constructor(context: any){
  this.context = context;
  let router = express.Router();
  router.use(function noteRequest(req: Request,res: Response,next: any) {
    context.logger.info('Saw request, method=' + req.method);
    next();
  });
  router.get('/',function(req: Request,res: Response) {
    respondWithRows(table.rows,res);
  });

  router.get('/:filter/:filterValue',function(req: Request,res: Response)
  {
    let column = table.columns[req.params.filter];
    if (column==undefined) {
      res.status(400).json({ "error": "Invalid filter specified" });
      return;
    }
    let matches = table.rows.filter(row=> row[column] ==
req.params.filterValue);
    respondWithRows(matches,res);
  });

  this.router = router;
}

```

Zowe's use of ExpressJS Routers allows you to quickly assign functions to HTTP calls such as GET, PUT, POST, DELETE, or even websockets, and provides you with easy parsing and filtering of the HTTP requests so that there is very little involved in making a good API for users.

This REST API now allows for two GET calls to be made: one to root /, and the other to `/filter/value`. The behavior here is as is defined in [ExpressJS documentation](#) for routers, where the URL is parameterized to give us arguments that we can feed into our function for filtering the user table rows before giving the result to `respondWithRows` for sending back to the caller.

### Adding your Dataservice to the Plugin Definition

Now that the Dataservice is made, add it to our Plugin's definition so that the server is aware of it, and then build it so that the server can run it.

1. Open a (third) command prompt to `workshop-user-browser-app/nodeCluster`.
2. Install dependencies, `npm install`.
3. Invoke the NPM build process, `npm run-script start`.
  - a. If there are errors, go back to `(#building-your-first-dataservice)` and make sure the files look correct.
4. Edit `workshop-user-browser-app/pluginDefinition.json`, adding a new attribute which declares Dataservices.

```
"dataServices": [
  {
    "type": "router",
    "name": "table",
    "serviceLookupMethod": "external",
    "fileName": "tablehandler.js",
    "routerFactory": "tableRouter",
    "dependenciesIncluded": true
    "version": "1.0.0"
  }
],
```

Your full `pluginDefinition.json` should now be:

```
{
  "identifier": "org.openmainframe.zowe.workshop-user-browser",
  "apiVersion": "1.0.0",
  "pluginVersion": "0.0.1",
  "pluginType": "application",
  "dataServices": [
    {
      "type": "router",
      "name": "table",
      "serviceLookupMethod": "external",
      "fileName": "tablehandler.js",
      "routerFactory": "tableRouter",
      "dependenciesIncluded": true
      "version": "1.0.0"
    }
  ],
  "webContent": {
    "framework": "angular2",
    "launchDefinition": {
      "pluginShortNameKey": "userBrowser",
      "pluginShortNameDefault": "User Browser",
      "imageSrc": "assets/icon.png"
    },
    "descriptionKey": "userBrowserDescription",
    "descriptionDefault": "Browse Employees in System",
    "isSingleWindowApp": true,
    "defaultWindowStyle": {
      "width": 1300,
      "height": 500
    }
  }
}
```

```
}
```

There's a few interesting attributes about the Dataservice we have specified here. First is that it is listed as **type**: **router**, which is because there are different types of Dataservices that can be made to suit the need. Second, the **name** is **table**, which determines both the name seen in logs but also the URL this can be accessed at. Finally, **fileName** and **routerFactory** point to the file within `workshop-user-browser-app/lib` where the code can be invoked, and the function that returns the ExpressJS Router, respectively.

1. [Adding Your App to the Desktop](#) on page 230 (as was done when adding the application initially) to load this new Dataservice. This is not always needed but done here for educational purposes.
2. Access `https://host:port/ZLUX/plugins/org.openmainframe.zowe.workshop-user-browser/services/table/` to see the Dataservice in action. It should return all of the rows in the user table, as you did a GET to the root / URL that we just coded.

## Adding your first Widget

Now that you can get this data from the server's new REST API, we need to make improvements to the web content of the application plug-in to visualize this. This means not only calling this API from the application plug-in, but presenting it in a way that is easy to read and extract information from.

### Adding your Dataservice to the App

Let's make some edits to `userbrowser-component.ts`, replacing the **UserBrowserComponent** Class's **ngOnInit** method with a call to get the user table, and defining **ngAfterViewInit**:

```
ngOnInit(): void {
  this.resultNotReady = true;
  this.log.info(`Calling own dataservice to get user listing for filter= ${JSON.stringify(this.filter)}`);
  let uri = this.filter ?
    ZoweZLUX.uriBroker.pluginRESTUri(this.pluginDefinition.getBasePlugin(),
    'table', `${this.filter.type}/${this.filter.value}`) :
    ZoweZLUX.uriBroker.pluginRESTUri(this.pluginDefinition.getBasePlugin(),
    'table', null);
  setTimeout(()=> {
    this.log.info(`Sending GET request to ${uri}`);
    this.http.get(uri).map(res=>res.json()).subscribe(
      data=>{
        this.log.info(`Successful GET, data=${JSON.stringify(data)}`);
        this.columnMetaData = data.metadata;
        this.unfilteredRows = data.rows.map(x=>Object.assign({},x));
        this.rows = this.unfilteredRows;
        this.showGrid = true;
        this.resultNotReady = false;
      },
      error=>{
        this.log.warn(`Error from GET. error=${error}`);
        this.error_msg = error;
        this.resultNotReady = false;
      }
    );
  },100);
}

ngAfterViewInit(): void {
  // the flex table div is not on the dom at this point
  // have to calculate the height for the table by subtracting all
  // the height of all fixed items from their container
  let fixedElems =
    this.element.nativeElement.querySelectorAll('div.include-in-calculation');
  let height = 0;
  fixedElems.forEach(function (elem, i) {
    height += elem.clientHeight;
```

```

    });
    this.windowEvents.resized.subscribe(() => {
      if (this.grid) {
        this.grid.updateRowsPerPage();
      }
    });
}

```

You might notice that we are referring to several instance variables that we have not declared yet. Let's add those within the **UserBrowserComponent** Class too, above the constructor.

```

private showGrid: boolean = false;
private columnMetaData: any = null;
private unfilteredRows: any = null;
private rows: any = null;
private selectedRows: any[] = [];
private query: string;
private error_msg: any;
private url: string;
private filter: any;

```

Hopefully you are still running the command in the first command prompt, `npm run-script start`, which will rebuild your web content for the application whenever you make changes. You might see some errors, which we will resolve by adding the next portion of the application.

## Introducing Zowe Application Server Grid

When **ngOnInit** runs, it will call out to the REST Dataservice and put the table row results into our cache, but we haven't yet visualized this in any way. We need to improve our HTML a bit to do that, and rather than reinvent the wheel, we have a table visualization library we can rely on: **ZLUX Grid**.

If you inspect `package.json` in the **webClient** folder, you'll see that we've already included `@zlux/grid` as a dependency (as a link to one of the Zowe github repositories) so it should have been pulled into the **node\_modules** folder during the `npm install` operation. We just need to include it in the Angular code to make use of it. To do so, complete these steps:

1. Edit **webClient/src/app/userbrowser.module.ts**, adding import statements for the Zowe Application Server widgets above and within the `@NgModule` statement:

```

import { ZluxInputModule } from '@zlux/grid';
import { ZluxPopupWindowModule, ZluxButtonModule } from '@zlux/widgets'
//...
@NgModule({
  imports: [FormsModule, HttpClientModule, ReactiveFormsModule, CommonModule,
    ZluxInputModule, ZluxPopupWindowModule, ZluxButtonModule],
  //...
})

```

The full file should now be:

```

/*
  This Angular module definition will pull all of your Angular files
  together to form a coherent App
*/

import { NgModule } from '@angular/core';
import { CommonModule } from '@angular/common';
import { FormsModule, ReactiveFormsModule } from '@angular/forms';
import { HttpClientModule } from '@angular/http';
import { ZluxInputModule } from '@zlux/grid';
import { ZluxPopupWindowModule, ZluxButtonModule } from '@zlux/widgets'

import { UserBrowserComponent } from './userbrowser-component';

```

```

@NgModule({
  imports: [FormsModule, HttpClientModule, ReactiveFormsModule, CommonModule,
    ZluxButtonModule, ZluxGridModule, ZluxPopupWindowModule, ZluxButtonModule],
  declarations: [UserBrowserComponent],
  exports: [UserBrowserComponent],
  entryComponents: [UserBrowserComponent]
})
export class UserBrowserModule { }

```

1. Edit **userbrowser-component.html** within the same folder. Previously, it was just meant for presenting a Hello World message, so we should add some style to accommodate the zlux-grid element that we will also add to this template through a tag.

```

<!-- In this HTML file, an Angular Template should be placed that will work together with your Angular Component to make a dynamic, modern UI -->

<div class="parent col-11" id="userbrowserPluginUI">
  <div class="fixed-height-child include-in-calculation">
    <button type="button" class="wide-button btn btn-default"
    value="Send">
      Submit Selected Users
    </button>
  </div>
  <div class="fixed-height-child height-40" *ngIf="!showGrid && !viewConfig">
    <div class="">
      <p class="alert-danger">{{error_msg}}</p>
    </div>
  </div>
  <div class="container variable-height-child" *ngIf="showGrid">
    <zlux-grid [columns]="columnMetaData | zluxTableMetadataToColumns"
    [rows]="rows"
    [paginator]="true"
    selectionMode="multiple"
    selectionWay="checkbox"
    [scrollableHorizontal]="true"
    (selectionChange)="onTableSelectionChange($event)"
    #grid></zlux-grid>
  </div>
  <div class="fixed-height-child include-in-calculation" style="height: 20px; order: 3"></div>
</div>

<div class="userbrowser-spinner-position">
  <i class="fa fa-spinner fa-spin fa-3x" *ngIf="resultNotReady"></i>
</div>

```

Note the key functions of this template:

- There is a button which when clicked will submit selected users (from the grid). We will implement this ability later.
- We show or hide the grid based on a variable `ngIf="showGrid"` so that we can wait to show the grid until there is data to present.
- The zlux-grid tag pulls the Zowe Application Server Grid widget into our application, and it has many variables that can be set for visualization, as well as functions and modes.
  - We allow the columns, rows, and metadata to be set dynamically by using the square bracket template syntax, and allow our code to be informed when the user selection of rows changes through `(selectionChange)="onTableSelectionChange($event)"`

1. Small modification to **userbrowser-component.ts** to add the grid variable, and set up the aforementioned table selection event listener, both within the **UserBrowserComponent** Class:

```
@ViewChild('grid') grid; //above the constructor

onTableSelectionChange(rows: any[]):void{
    this.selectedRows = rows;
}
```

The previous section, [Adding your Dataservice to the App](#) on page 234 set the variables that are fed into the Zowe Application Server Grid widget, so at this point the application should be updated with the ability to present a list of users in a grid.

If you are still running `npm run-script start` in a command prompt, it should now show that the application has been successfully built, and that means we are ready to see the results. Reload your browser's webpage and open the user browser application once more. Do you see the list of users in columns and rows that can be sorted and selected? If so, great, you've built a simple yet useful application within Zowe! Let's move on to the last portion of the application tutorial where we hook the Starter application and the User Browser application together to accomplish a task.

### **Adding Zowe App-to-App Communication**

Applications in Zowe can be useful and provide insight all by themselves, but a big advantage to using the Zowe Desktop is that applications can track and share context by user interaction. By having the foreground application request the application best suited for a task, the requested application can perform the task with context regarding the task data and purpose and you can accomplish a complex task by simple and intuitive means.

In the case of this tutorial, we are not only trying find a list of employees in a company (as was shown in the last step where the Grid was added and populated with the REST API), but to filter that list to find those employees who are best suited to the task we need to accomplish. So, our user browser application needs to be enhanced with two new abilities:

- Filter the user list to show only those users that meet the filter
- Send the subset of users selected in the list back to the application that requested a user list.

How do we do either task? Application-to-application communication! Applications can communicate with other applications in a few ways, but can be categorized into two interaction groups:

1. Launching an application with a context of what it should do
2. Messaging an application that is already open to a request or alert it of something

In either case, the application framework provides Actions as the objects to perform the communication. Actions not only define what form of communication should happen, but between which applications. Actions are issued from one application, and are fulfilled by a target application. But, because there might be more than one instance or window of an application open, there are Target Modes:

- Open a new application window, where the message context is delivered in the form of a Launch Context
- Message a particular, or any of the currently open instances of the target application

### **Adding the Starter App**

In order to facilitate app-to-app communication, we need another application with which to communicate. A 'starter' application is provided which can be [found on github](#).

As we did previously in the [Adding Your App to the Desktop](#) on page 230 section, we need to move the application files to a location where they can be included in our `zlux-app-server`. We then need to add to the `plugins` folder in the example server and re-deploy.

1. Clone or download the starter application under the `zlux` folder
  - `git clone https://github.com/zowe/workshop-starter-app.git`
1. Navigate to starter application and build it as before.

- Install packages with `cd webClient` and then `npm install`
  - Build the project using `npm start`
1. Next navigate to the `zlux-app-server`:
- create a new file under `/zlux-app-server/plugins/org.openmainframe.zowe.workshop-starter.json`
  - Edit the file to contain:

```
{
  "identifier": "org.openmainframe.zowe.workshop-starter",
  "pluginLocation": "../../workshop-starter-app"
}
```

1. Make sure the `./nodeCluster` is stopped before running `ant deploy` under `zlux-build`
2. Restart the `./nodeCluster` under `zlux-app-server/bin` with the appropriate parameters passed in.
3. Refresh the browser and verify that the app with a **Green S** is present in Zowe Application Server.

## Enabling Communication

We've already done the work of setting up the application's HTML and Angular definitions, so in order to make our application compatible with application-to-application communication, it only needs to listen for, act upon, and issue Zowe application Actions. Let's edit the typescript component to do that. Edit the **UserBrowserComponent** Class's constructor within `userbrowser-component.ts` to listen for the launch context:

```
constructor(
  private element: ElementRef,
  private http: Http,
  @Inject(Angular2InjectionTokens.LOGGER) private log:
ZLUX.ComponentLogger,
  @Inject(Angular2InjectionTokens.PLUGIN_DEFINITION) private
pluginDefinition: ZLUX.ContainerPluginDefinition,
  @Inject(Angular2InjectionTokens.WINDOW_ACTIONS) private windowAction:
Angular2PluginWindowActions,
  @Inject(Angular2InjectionTokens.WINDOW_EVENTS) private windowEvents:
Angular2PluginWindowEvents,
  //Now, if this is not null, we're provided with some context of what to
do on launch.
  @Inject(Angular2InjectionTokens.LAUNCH_METADATA) private launchMetadata:
any,
) {
  this.log.info(`User Browser constructor called`);

  //NOW: if provided with some startup context, act upon it... otherwise
just load all.
  //Step: after making the grid... we add this to show that we can
instruct an app to narrow its scope on open
  this.log.info(`Launch metadata provided=
${JSON.stringify(launchMetadata)})`);

  if (launchMetadata != null && launchMetadata.data) {
    /* The message will always be an Object, but format can be specific. The
format we are using here is in the Starter App:
     https://github.com/zowe/workshop-starter-app/blob/master/webClient/
src/app/workshopstarter-component.ts#L177
    */
    switch (launchMetadata.data.type) {
      case 'load':
        if (launchMetadata.data.filter) {
          this.filter = launchMetadata.data.filter;
        }
        break;
      default:
    }
  }
}
```

```

        this.log.warn(`Unknown launchMetadata type`);
    }
} else {
    this.log.info(`Skipping launching in a context due to missing or
malformed launchMetadata object`);
}
}
}

```

Then, add a new method on the Class, **provideZLUXDispatcherCallbacks**, which is a web-framework-independent way to allow the Zowe applications to register for event listening of Actions.

```

/*
I expect a JSON here, but the format can be specific depending on the
Action - see the Starter App to see the format that is sent for the
Workshop:
https://github.com/zowe/workshop-starter-app/blob/master/webClient/src/app/workshopstarter-component.ts#L225
*/
zluxOnMessage(eventContext: any): Promise<any> {
    return new Promise((resolve, reject) => {
        if (!eventContext || !eventContext.data) {
            return reject('Event context missing or malformed');
        }
        switch (eventContext.data.type) {
            case 'filter':
                let filterParms = eventContext.data.parameters;
                this.log.info(`Messaged to filter table by column=
${filterParms.column}, value=${filterParms.value}`);

                for (let i = 0; i < this.columnMetaData.columnMetaData.length; i++) {
                    if (this.columnMetaData.columnMetaData[i].columnIdentifier ==
filterParms.column) {
                        //ensure it is a valid column
                        this.rows = this.unfilteredRows.filter((row) => {
                            if (row[filterParms.column] === filterParms.value) {
                                return true;
                            } else {
                                return false;
                            }
                        });
                        break;
                    }
                }
                resolve();
                break;
            default:
                reject('Event context missing or unknown data.type');
        };
    });
}

provideZLUXDispatcherCallbacks(): ZLUX.ApplicationCallbacks {
    return {
        onMessage: (eventContext: any): Promise<any> => {
            return this.zluxOnMessage(eventContext);
        }
    }
}

```

At this point, the application should build successfully and upon reloading the Zowe page in your browser, you should see that if you open the Starter application (the application with the green S), that clicking the **Find Users**

**from Lookup Directory** button should open the User Browser application with a smaller, filtered list of employees rather than the unfiltered list we see if opening the application manually.

We can also see that once this application has been opened, the Starter application's button, **Filter Results to Those Nearby**, becomes enabled and we can click it to see the open User Browser application's listing become filtered even more, this time using the browsers [Geolocation API](#) to instruct the User Browser application to filter the list to those employees who are closest to you!

### Calling back to the Starter App

We are almost finished. The application can visualize data from a REST API, and can be instructed by other applications to filter that data according to the situation. But, to complete this tutorial, we need the application communication to go in the other direction - inform the Starter application which employees you have chosen in the table!

This time, we will edit **provideZLUXDispatcherCallbacks** to issue Actions rather than to listen for them. We need to target the Starter application, since it is the application that expects to receive a message about which employees should be assigned a task. If that application is given an employee listing that contains employees with the wrong job titles, the operation will be rejected as invalid, so we can ensure that we get the correct result through a combination of filtering and sending a subset of the filtered users back to the starter application.

Add a private instance variable to the **UserBrowserComponent** Class:

```
private submitSelectionAction: ZLUX.Action;
```

Then, create the Action template within the constructor:

```
this.submitSelectionAction = ZoweZLUX.dispatcher.makeAction(
  'org.openmainframe.zowe.workshop-user-browser.actions.submitselections',
  'Sorts user table in App which has it',
  ZoweZLUX.dispatcher.constants.ActionTargetMode.PluginFindAnyOrCreate,
  ZoweZLUX.dispatcher.constants.ActionType.Message,
  'org.openmainframe.zowe.workshop-starter',
  { data: { op: 'deref', source: 'event', path: ['data'] } }
)
```

So, we created an Action which targets an open window of the Starter application, and provides it with an Object with a data attribute. We'll populate this object for the message to send to the application by getting the results from Zowe Application Server Grid (`this.selectedRows` will be populated from `this.onTableSelectionChange`).

For the final change to this file, add a new method to the Class:

```
submitSelectedUsers() {
  let plugin =
    ZoweZLUX.PluginManager.getPlugin("org.openmainframe.zowe.workshop-
starter");
  if (!plugin) {
    this.log.warn(`Cannot request Workshop Starter App... It was not in
the current environment!`);
    return;
  }

  ZoweZLUX.dispatcher.invokeAction(this.submitSelectionAction,
    { 'data':{
      'type':'loadusers',
      'value':this.selectedRows
    }})
};
```

And we'll invoke this through a button click action, which we will add into the Angular template, `userbrowser-component.html`, by changing the button tag for "Submit Selected Users" to:

```
<button type="button" class="wide-button btn btn-default" (click)="submitSelectedUsers()" value="Send">
```

Check that the application builds successfully, and if so, you've built the application for the tutorial! Try it out:

1. Open the Starter application.
2. Click the "Find Users from Lookup Directory" button.
  - a. You should see a filtered list of users in your user application.
3. Click the "Filter Results to Those Nearby" button on the Starter application.
  - a. You should now see the list be filtered further to include only one geography.
4. Select some users to send back to the Starter application.
5. Click the "Submit Selected Users" button on the User Browser application.
  - a. The Starter application should print a confirmation message that indicates success.

And that's it! Looking back at the beginning of this document, you should notice that we've covered all aspects of application building - REST APIs, persistent settings storage, Creating Angular applications and using Widgets within them, as well as having one application communicate with another. Hopefully you have learned a lot about application building from this experience, but if you have questions or want to learn more, please reach out to those in the Foundation so that we can assist.

## Zowe Conformance Program

---

### Introduction

Administered by the Open Mainframe Project, the Zowe Conformance Program aims to give users the confidence that when they use a product, app, or distribution that leverages Zowe, they can expect a high level of common functionality, interoperability, and user experience.

Conformance provides Independent Software Vendors (ISVs), System Integrators (SIs), and end users greater confidence that their software will behave as expected. Just like Zowe, the Zowe Conformance Program will continue to evolve and is being developed by committers and contributors in the Zowe community.

As vendors, you are invited to submit conformance testing results for review and approval by the Open Mainframe Project. If your company provides software based on Zowe, you are encouraged to get certified today.

### How to participate

To participate in the Zowe Conformance Program, follow the process on the [Zowe Conformance Program website](#). You can also find a list of products that have earned Zowe Conformant status.



---

# Chapter

# 4

---

## Troubleshooting

---

### Topics:

- Troubleshooting
- Troubleshooting API ML
- Zowe Application Framework
- Troubleshooting z/OS Services
- Troubleshooting Zowe CLI
- Troubleshooting Zowe through Zowe Open Community
- <<<<< HEAD Community members start to troubleshoot your issue.

## Troubleshooting

---

To isolate and resolve Zowe problems, you can use the troubleshooting and support information in this section.

### Topics

- [Troubleshooting API ML on page 244](#)
- [Troubleshooting Zowe Application Framework on page 246](#)
- [Troubleshooting z/OS Services on page 252](#)
- [Troubleshooting Zowe CLI on page 253](#)
- [Troubleshooting Zowe through Zowe Open Community on page 258](#)

## Troubleshooting API ML

---

As an API Mediation Layer user, you may encounter problems with the functioning of API ML. This article presents known API ML issues and their solutions.

### Enable API ML Debug Mode

Use debug mode to activate the following functions:

- Display additional debug messages for API ML
- Enable changing log level for individual code components

**Important:** We highly recommend that you enable debug mode only when you want to troubleshoot issues. Disable debug mode when you are not troubleshooting. Running in debug mode while operating API ML can adversely affect its performance and create large log files that consume a large volume of disk space.

#### Follow these steps:

1. Locate the following shell script files in the <Zowe install directory>/api-mediation/scripts directory:
  - api-mediation-start-catalog.sh
  - api-mediation-start-discovery.sh
  - api-mediation-start-gateway.sh

2. Open a file, for which you want to enable the debug mode.
3. Find the line which contains the `spring.profiles.include` parameter and change the value to `debug`:

```
-Dspring.profiles.include=debug \
```

4. Restart Zowe.

You have enabled the debug mode.

5. (Optional) Reproduce a bug that causes issues and review debug messages. If you are unable to resolve the issue, contact CA Support.
6. Disable the debug mode. Modify the line which contains the `spring.profiles.include` parameter back to default:

```
-Dspring.profiles.include= \
```

7. Restart Zowe.

You have disabled the debug mode.

### Change the Log Level of Individual Code Components

You can change the log level of a particular code component of the API ML internal service at run time.

### Follow these steps:

1. Enable API ML Debug Mode as described in Enable API ML Debug Mode. This activates the application/loggers endpoints in each API ML internal service (Gateway, Discovery Service, and Catalog).
2. List the available loggers of a service by issuing the GET request for the given service URL:

```
GET scheme://hostname:port/application/loggers
```

Where:

- **scheme**

API ML service scheme (http or https)

- **hostname**

API ML service hostname

- **port**

TCP port where API ML service listens on. The port is defined by the configuration parameter MFS\_GW\_PORT for the Gateway, MFS\_DS\_PORT for the Discovery Service (by default, set to gateway port + 1), and MFS\_AC\_PORT for the Catalog (by default, set to gateway port + 2).

**Exception:** For the catalog you will able to get list the available loggers by issuing the GET request for the given service URL:

```
GET [gateway-scheme]://[gateway-hostname]:[gateway-port]/api/v1/
apicatalog/application/loggers
```

**Tip:** One way to issue REST calls is to use the http command in the free HTTPie tool: <https://httpie.org/>.

**Example:**

```
HTTPie command:
http GET https://lpar.ca.com:10000/application/loggers

Output:
{"levels": ["OFF", "ERROR", "WARN", "INFO", "DEBUG", "TRACE"], "loggers": { "ROOT": { "configuredLevel": "INFO", "effectiveLevel": "INFO" }, "com": { "configuredLevel": null, "effectiveLevel": "INFO" }, "com.ca": { "configuredLevel": null, "effectiveLevel": "INFO" }, ... }}
```

3. Alternatively, you extract the configuration of a specific logger using the extended **GET** request:

```
GET scheme://hostname:port/application/loggers/{name}
```

Where:

- **{name}**

is the logger name

4. Change the log level of the given component of the API ML internal service. Use the POST request for the given service URL:

```
POST scheme://hostname:port/application/loggers/{name}
```

The POST request requires a new log level parameter value that is provided in the request body:

```
{
```

```

    "configuredLevel": "level"
}
```

Where:

- **level**

is the new log level: **OFF, ERROR, WARN, INFO, DEBUG, TRACE**

**Example:**

```
http POST https://hostname:port/application/loggers/com.ca.mfaas.enable.model configuredLevel=WARN
```

## Known Issues

### API ML stops accepting connections after z/OS TCP/IP stack is recycled

**Symptom:**

When z/OS TCP/IP stack is restarted, it is possible that the internal services of API Mediation Layer (Gateway, Catalog, and Discovery Service) stop accepting all incoming connections, go into a continuous loop, and write a numerous error messages in the log.

**Sample message:**

The following message is a typical error message displayed in STDOUT:

```

2018-Sep-12 12:17:22.850. org.apache.tomcat.util.net.NioEndpoint -- Socket
accept failed java.io.IOException: EDC5122I Input/output error.

.at sun.nio.ch.ServerSocketChannelImpl.accept0(Native Method) ~.na:1.8.0.
.at
sun.nio.ch.ServerSocketChannelImpl.accept(ServerSocketChannelImpl.java:478)
~.na:1.8.0.
.at
sun.nio.ch.ServerSocketChannelImpl.accept(ServerSocketChannelImpl.java:287)
~.na:1.8.0.
.at org.apache.tomcat.util.net.NioEndpoint
$Acceptor.run(NioEndpoint.java:455) ~.tomcat-coyote-8.5.29.jar!/:8.5.29.
.at java.lang.Thread.run(Thread.java:811) .na:2.9 (12-15-2017).
```

**Solution:**

Restart API Mediation Layer.

**Tip:** To prevent this issue from occurring, it is strongly recommended not to restart the TCP/IP stack while API ML is running.

## Zowe Application Framework

---

### Troubleshooting Zowe Application Framework

The following topics contain information that can help you troubleshoot problems when you encounter unexpected behavior installing and using Zowe Application Framework.

Before you reach out for support:

1. Is there already a GitHub issue (open or closed) that covers the problem? Check [Application Framework issues](#).
2. Review the current list of [Known Zowe Application Framework issues](#) on page 249 in documentation. Also try searching using the Zowe Docs search bar.

## Gathering information to troubleshoot Zowe Application Framework

Gather the following information to troubleshoot Zowe Application Framework issues:

- [z/OS release level](#)
- [Zowe version and release level](#) on page 247
- [Zowe application configuration](#) on page 248
- [Zowe Application Server ports](#) on page 248
- [Log output from the Zowe Application Server](#) on page 248
- [Error message codes](#) on page 249
- [Javascript console output](#) on page 249
- [Screen captures](#) on page 249
- [Other relevant information](#) on page 249

### **z/OS release level**

To find the z/OS release level, issue the following command in SDSF:

```
/D IPLINFO
```

Check the output for the release level, for example:

```
RELEASE z/OS 02.02.00
```

### **Zowe version and release level**

```
cd <zowe-installation-directory>
cat manifest.json
```

#### **Output:**

Displays zowe version

```
{
  "name": "Zowe",
  "version": "1.2.0",
  "description": "Zowe is an open source project created to host technologies that benefit the Z platform from all members of the Z community (Integrated Software Vendors, System Integrators and z/OS consumers). Zowe, like Mac or Windows, comes with a set of APIs and OS capabilities that applications build on and also includes some applications out of the box. Zowe offers modern interfaces to interact with z/OS and allows you to work with z/OS in a way that is similar to what you experience on cloud platforms today. You can use these interfaces as delivered or through plug-ins and extensions that are created by clients or third-party vendors.",
  "license": "EPL-2.0",
  "homepage": "https://zowe.org",
  "build": {
    "branch": "master",
    "number": 685,
    "commitHash": "63efa85df629db474197ec8481db50021e8fdd65",
    "timestamp": "1556733977010"
  }
}
```

## Zowe application configuration

Configuration file helps customize the Zowe app server, and is important to look at while you troubleshoot.

```
# navigate to zowe installation folder
cd <zowe-installation-folder>

# navigate to server configuration folder
cd zlux-app-server/deploy/instance/ZLUX/serverConfig

# display config
cat zluxserver.json
```

Read more about the Zowe app server [Zowe Application Framework configuration](#) on page 77 in the Zowe User Guide.

## Zowe Application Server ports

```
# navigate to zowe installation folder
cd <zowe-installation-folder>

# navigate to install log directory
cd install_log

# list file by most recent first
ls -lt

# pick latest file
cat 2019-05-02-17-13-09.log | grep ZOWE_ZLUX_SERVER_HTTPS_PORT
cat 2019-05-02-17-13-09.log | grep ZOWE_ZSS_SERVER_PORT
```

## Log output from the Zowe Application Server

There are two major components of Zowe application server: ZLUX and ZSS. They log to different files.

The default location for logs for both zlux and zss is folder `zlux-app-server/log`. You can customize the log location by using the environment variable.

```
env | grep ZLUX_NODE_LOG_DIR
env | grep ZSS_LOG_DIR
```

Read more about controlling the log location [Controlling the logging location](#) on page 87.

```
# navigate to zowe installation folder
cd <zowe-installation-folder>

# navigate to logs default location or custom location as described above
cd zlux-app-server/log

# custom log location can be found using environment variable

# list file by most recent first
ls -lt
```

### Output:

List of files by most recent timestamp for both nodeServer as well ZSS.

```
nodeServer-<yyyy-mm-dd-hh-mm>.log
zssServer-<yyyy-mm-dd-hh-mm>.log
```

## Error message codes

It is advisable to look into log files for capturing error codes.

## Javascript console output

Web Developer toolkit is accessible by pressing F12.

Read more about it [here](#).

## Screen captures

If possible, add a screen capture of the issue.

## Other relevant information

Node.js – v6.14.4 minimum for z/OS, elsewhere v6, v8, and v10 work well.

```
node -v
```

npm – v6.4 minimum

```
npm -v
```

Java – v8 minimum

```
java -version
```

## Known Zowe Application Framework issues

The following topics contain information that can help you troubleshoot problems when you encounter unexpected behavior installing and using Zowe Application Framework.

Most of the solutions below identify issues by referring to the Zowe [Gathering information to troubleshoot Zowe Application Framework](#) on page 247. To identify and resolve issues, you should become familiar with their names and locations.

### Cannot log in to the Zowe Desktop

#### Symptom:

When you attempt to log in to the Zowe Desktop, you receive the following error message, displayed beneath the **Username** and **Password** fields.

```
Authentication failed for 1 types:  Types: [ "zss" ]
```

#### Solution:

For the Zowe Desktop to work, the node server that runs under the ZOWESVR started task must be able to make cross memory calls to the ZWESIS01 load module running under the ZWESIS01 started task. If this communication fails, you see the authentication error.

To solve the problem, follow these steps:

1. Open the log file `/zlux-app-server/log/zssServer-yyyy-mm-dd-hh-ss.log`. This file is created each time ZOWESVR is started and only the last five files are kept.

- Look for the message that starts with ZIS status.

If communication is working the message includes Ok. For example:

```
ZIS status - Ok (name='ZWESIS_STD' , cmsRC=0, description='Ok')
```

If communication is not working the message includes Failure. For example:

```
ZIS status - Failure (name='ZWESIS_STD' , cmsRC=39, description='Cross-memory call ABENDED')
```

If communication is not working, check that the ZWESIS01 started task is running. If not, start it. Also, search the log for problems, for example statements saying that the server was unable to find the load module.

If the problem is not easily-fixable (such as the ZWESIS01 task not running), then it is likely that the cross memory server setup and configuration did not complete successfully. To set up and configure the cross memory server, follow steps as described in the topic [Manually installing the Zowe Cross Memory Server](#) on page 66.

If there is an authorization problem, the message might include Permission Denied. For example:

```
ZIS status - Failure (name='ZWESIS_STD' , cmsRC=33, description='Permission denied')
```

Check that the user ID of the ZOWESVR started task is authorized to access the load module. Only authorized code can call ZWESIS01 because it is an APF-authorized load module. The setup for each security manager is different and is documented in the section "Security requirements for the cross memory server" in the topic [Manually installing the Zowe Cross Memory Server](#) on page 66.

**Note** If you are using RACF security manager, a common reason for seeing Permission Denied is that the user running the started task ZOWESVR (typically IZUSVR) does not have READ access to the FACILITY class ZWES.IS.

If the message includes the following text, the configuration of the Application Framework server may be incomplete:

```
ZIS status - Failure read failed ret code 1121 reason 0x76650446
```

If you are using AT/TLS, then the "attls" : true statement might be missing from the zluxserver.json file. For more information, see [Configuring ZSS for HTTPS](#) on page 81

### Server startup problem ret=1115

**Symptom:** When ZOWESVR is restarted, the following message is returned in the output of the ZSS server log file, /zlux-app-server/log/zssServer-yyyy-mm-dd-hh-ss.log:

```
server startup problem ret=1115
```

**Solution:** This message means that some other process is already listening on port 7542, either at address 127.0.0.1 (localhost) or at 0.0.0.0 (all addresses). This prevents the ZSS server from starting.

One possibility is that a previously running ZSS server did not shut down correctly, and either the operating system has not released the socket after the ZSS server shut down, or the ZSS server is still running.

### Application plug-in not in Zowe Desktop

**Symptom:** An application plug-in is not appearing in the Zowe Desktop.

**Troubleshooting:** To check if the plug-in loaded successfully, enter the following URL in a browser to display all successfully loaded Zowe plug-ins:

```
https://my.mainframe.com:8544/plugins?type=application
```

You can also search the [Gathering information to troubleshoot Zowe Application Framework](#) on page 247 for the plug-in identifier, for example `org.zowe.sample.app`. If the plug-in loaded successfully, you will find the following message:

```
[2019-08-06 13:54:21.341 _zsf.bootstrap INFO] - Plugin org.zowe.sampleapp at path=zlux\org.zowe.sampleapp loaded.
```

If the plug-in did not load successfully, you will find the following message:

```
[2019-08-06 13:54:21.208 _zsf.bootstrap WARNING] - Error: org.zowe.sampleapp
```

If the identifier is not in the logs, make sure the plug-in's locator file is in the `/zlux-app-server/deploy/instance/ZLUX/plugins/` directory. The plug-in locator is a `.json` file, usually with same name as the identifier, for example `org.zowe.sampleapp.json`. Open the file and make sure that the path defined with the `pluginLocation` attribute is correct. If the path is relative, make sure it is relative to the `zlux-app-server/bin` directory.

For more information on loading plug-ins to the Desktop, see [Adding Your App to the Desktop](#) on page 230.

### Error: You must specify MVD\_DESKTOP\_DIR in your environment

#### Symptom:

A plug-in build in your local environment using `npm run start` or `npm run build` failed with an error message about a missing `MVD_DESKTOP_DIR` environment variable.

**Solution:** Add the Zowe Desktop directory path to the `MVD_DESKTOP_DIR` environment variable. To specify the path, run the following commands in your Windows console or Linux bash shell:

- Windows

```
export MVD_DESKTOP_DIR=<zlux-root-dir>/zlux-app-manager/virtual-desktop
```

- Mac Os/Linux

```
set MVD_DESKTOP_DIR=<zlux-root-dir>/zlux-app-manager/virtual-desktop
```

## Raising a Zowe Application Framework issue on GitHub

When necessary, you can raise GitHub issues against the Zowe `zlux` core repository [here](#). It is suggested that you use either the bug or enhancement template.

For issues with particular applications, such as [Code Editor](#) or [JES Explorer](#), create the issue in the application's project.

### Raising a bug report

Please provide as much of the information listed on [Troubleshooting Zowe Application Framework](#) on page 246 as possible. Anyone working on the issue might need to request this and other information if it is not supplied initially. A description of the error and how it can be reproduced is the most important information.

### Raising an enhancement report

Enhancement reports are just as important to the Zowe project as bug reports. Enhancement reports should be clear and detailed requirements for a potential enhancement.

## Troubleshooting z/OS Services

The following topics contain information that can help you troubleshoot problems when you encounter unexpected behavior installing and using Zowe z/OS Services.

### **z/OS Services are unavailable**

#### **Solution:**

If the z/OS Services are unavailable, take the following corrective actions.

- Ensure that the z/OSMF REST API services are working. Check the z/OSMF IZUSVR1 task output for errors and confirm that the z/OSMF RESTFILES services are started successfully. If no errors occur, you can see the following message in the IZUSVR1 job output:

```
CWWKZ0001I: Application IzuManagementFacilityRestFiles started in n.nnn
seconds.
```

To test z/OSMF REST APIs you can run curl scripts from your workstation.

```
curl --user <username>:<password> -k -X GET --header 'Accept: application/
json' --header 'X-CSRF-ZOSMF-HEADER: true' "https://<z/os host
name>:<securezosmfport>/zosmf/restjobs/jobs?prefix=&owner=*
```

where the *securezosmfport* is 443 by default. You can verify the port number by checking the *izu.https.port* variable assignment in the z/OSMF bootstrap.properties file.

If z/OSMF returns jobs correctly, you can test whether it is able to returns files by using the following curl scripts:

```
curl --user <username>:<password> -k -X GET --header 'Accept: application/
json' --header 'X-CSRF-ZOSMF-HEADER: true' "https://<z/os host
name>:<securezosmfport>/zosmf/restfiles/ds?dslevel=SYS1"
```

If the restfiles curl statement returns a TSO SERVLET EXCEPTION error, check that the the z/OSMF installation step of creating a valid IZUFPROC procedure in your system PROCLIB has been completed. For more information, see the [z/OSMF Configuration Guide](#).

The IZUFPROC member resides in your system PROCLIB, which is similar to the following sample:

```
//IZUFPROC PROC ROOT='/usr/lpp/zosmf' /* zOSMF INSTALL ROOT      */
//IZUFPROC EXEC PGM=IKJEFT01,DYNAMNBR=200
//SYSEXEC DD DISP=SHR,DSN=ISP.SISPEXEC
//
//      DD DISP=SHR,DSN=SYS1.SBPXEXEC
//SYSPROC DD DISP=SHR,DSN=ISP.SISPCLIB
//
//      DD DISP=SHR,DSN=SYS1.SBPXEXEC
//ISPLLIB  DD DISP=SHR,DSN=SYS1.SIEALNKE
//ISPPLIB  DD DISP=SHR,DSN=ISP.SISPENU
//ISPTLIB  DD RECFM=FB,LRECL=80,SPACE=(TRK,(1,0,1))
//
//      DD DISP=SHR,DSN=ISP.SISPTENU
//ISPSLIB  DD DISP=SHR,DSN=ISP.SISPSENU
//ISPMLIB  DD DISP=SHR,DSN=ISP.SISPMENU
//ISPPROF  DD DISP=NEW,UNIT=SYSDA,SPACE=(TRK,(15,15,5)),
//
//      DCB=(RECFM=FB,LRECL=80,BLKSIZE=3120)
//IZUSRVMP DD PATH='&ROOT./defaults/izurf.tsoservlet.mapping.json'
//SYSOUT   DD SYSOUT=H
//CEEDUMP  DD SYSOUT=H
//SYSUDUMP DD SYSOUT=H
```

//

**Note:** You might need to change paths and data sets names to match your installation.

A known issue and workaround for RESTFILES API can be found at [TSO SERVLET EXCEPTION ATTEMPTING TO USE RESTFILE INTERFACE](#).

- Check your system console log for related error messages and respond to them.

## Troubleshooting Zowe CLI

---

### Troubleshooting Zowe CLI

#### Problem

Zowe CLI is experiencing a problem. You need to collect information that will help you resolve the issue.

#### Environment

These instructions apply to Zowe CLI installed on Windows, Mac OS X, and Linux systems as a standalone installation via a Zowe download or an NPM registry.

#### Before reaching out for support

1. Is there already a GitHub issue (open or closed) that covers the problem? Check [CLI Issues](#).
2. Review the current list of [Known Zowe CLI issues](#) on page 256 in documentation. Also try searching using the Zowe Docs search bar.

#### Resolving the problem

Collect the following information to help diagnose the issue:

- Zowe CLI version installed.
- List of plug-ins installed and their version numbers.
- Node.js and NPM versions installed.
- List of environment variables in use.

For instructions on how to collect the information, see [Gathering information to troubleshoot Zowe CLI](#) on page 253.

The following information is also useful to collect:

- If you are experiencing HTTP errors, see [z/OSMF troubleshooting](#) on page 256 for information to collect.
- Is the CLI part of another Node application, such as VSCode, or is it a general installation?
- Which operating system version are you running on?
- What shell/terminal are you using (bash, cmd, powershell, etc...)?
- Which queue managers are you trying to administer, and on what systems are they located?
- Are the relevant API endpoints online and valid?

### Gathering information to troubleshoot Zowe CLI

Follow these instructions to gather specific pieces of information to help troubleshoot Zowe CLI issues.

[]

#### Identify the currently installed CLI version

Issue the following command:

```
zowe -V
```

Zowe CLI versions may vary depending upon if the @latest or @lts-incremental version is installed.

For the @latest (forward-development) version:

```
npm list -g @zowe/cli
```

For the @lts-incremental version:

```
npm list -g @brightside/core
```

More information regarding versioning conventions for Zowe CLI and plug-ins is located in [Versioning Guidelines](#).

### **Identify the currently installed versions of plug-ins**

Issue the following command:

```
zowe plugins list
```

The output describes version and the registry information. Note that the official downloads are located at <https://api.bintray.com/npm>

### **Environment variables**

The following settings are configurable via environment variables:

#### **Log levels**

Environment variables are available to specify logging level and the CLI home directory.

**Important!** Setting the log level to TRACE or ALL might result in "sensitive" data being logged. For example, command line arguments will be logged when TRACE is set.

Environment Variable	Description	Values	Default
ZOWE_APP_LOG_LEVEL	Zowe CLI logging level	Log4JS log levels (OFF, TRACE, DEBUG, INFO, WARN, ERROR, FATAL)	DEBUG
ZOWE_IMPERATIVE_LOG_LEVEL	Imperative CLI Framework logging level	Log4JS log levels (OFF, TRACE, DEBUG, INFO, WARN, ERROR, FATAL)	DEBUG

#### **Home directory**

You can set the location on your computer for the Zowe CLI home directory, which contains log files, profiles, and plug-ins for the product.

**Tip!** The default .zowe folder is created when you issue your first Zowe CLI command. If you change the location of the folder, you must reinstall plug-ins and recreate or move profiles and log files that you want to retain. In some cases, you might want to maintain a different set of profiles in multiple folders, then switch between them using the environment variable.

Environment Variable	Description	Values	Default
ZOWE_CLI_HOME	Zowe CLI home directory location	Any valid path on your computer	C:\Users\<username>\.zowe

The values for these variables can be **echoed**.

## Home directory structure

Name		Date Modified	Size
imperative		18 Jun 2019 at 14:40	
logs		Today at 14:38	
imperative.log		Today at 13:46	9
plugins		Today at 14:38	
installed		Today at 14:38	
lib		3 May 2019 at 08:50	
node_modules		19 Jun 2019 at 13:32	
plugins.json		Yesterday at 16:40	398
profiles		14 Jun 2019 at 07:10	
settings		3 Jun 2019 at 08:40	
imperative.json		10 Jun 2019 at 11:50	56
zowe		18 Jun 2019 at 14:02	
logs		11 Oct 2018 at 16:24	
zowe.log		24 Jun 2019 at 17:36	3

### Location of logs

There are two sets of logs to be aware of:

- Imperative CLI Framework log, which generally contains installation and configuration information.
- Zowe CLI log, which contains information about interaction between CLI and the server endpoints.

Analyze these logs for any information relevant to your issue.

### Profile configuration

The `profiles` folder stores connection information.

**Important!** The profile directory might contain "sensitive" information, such as your mainframe password. You should obfuscate any sensitive references before providing configuration files.

### Node.js and npm

Zowe CLI should be compatible with Node.js v8 and greater.

To gather Node.js and npm versions, use the following:

```
node --version
npm --version
```

### npm configuration

If you are having trouble installing Zowe CLI from an npm registry, gather your npm configuration to help identify issues with registry settings, global install paths, proxy settings, etc...

```
npm config ls -l
```

## **npm log files**

In case of errors, npm creates log files in the `npm_cache\_logs` location. To get the `npm_cache` location for a specific OS, run the following command:

```
npm config get cache
```

By default, npm keeps only 10 log files, but sometimes more are needed. Increase the log count by issuing the following command:

```
npm config set logs-max 50
```

This command increases the log count to 50, so that more log files will be stored on the system. Now you can run tests multiple times and not lose the log files. The logs can be passed to Support for analysis.

As the log files are created only when an npm command fails, but you are interested to see what is executed, you can increase the log level of npm. Issue the following command:

```
npm config set loglevel verbose
```

- With this change, you can see all actions taken by npm on the stdout. If the command is successful, it still does not generate a log file.
- The available log levels are: "silent", "error", "warn", "notice", "http", "timing", "info", "verbose", "silly", and "notice". "Notice" is the default.
- Alternatively, you can pass `--loglevel verbose` on the command line, but this only works with npm related commands. By setting log level in the config, it also works when you issue some zowe commands that use npm (for example, `zowe plugins install @zowe/cics`).

## **z/OSMF troubleshooting**

The core command groups use the z/OSMF REST APIs which can experience any number of problems.

If you encounter HTTP 500 errors with the CLI, consider gathering the following information:

1. The IZU\* (IZUSVR and IZUANG) joblogs (z/OSMF server)
2. z/OSMF USS logs (default location: `/global/zosmf/data/logs` - but may change depending on installation)

If you encounter HTTP 401 errors with the CLI, consider gathering the following information:

1. Any security violations for the TSO user in SYSLOG

### **Alternate methods**

At times, it may be beneficial to test z/OSMF outside of the CLI. You can use the CLI tool `curl` or a REST tool such as "Postman" to isolate areas where the problem might be occurring (CLI configuration, server-side, etc.).

Example `curl` command to GET `/zosmf/info`:

```
curl -k -H "Accept: application/json" -H "X-CSRF-ZOSMF-HEADER: true"
"https://zosmf.hostname.net:443/zosmf/info"
```

## **Known Zowe CLI issues**

The following topics contain information that can help you troubleshoot problems when you encounter unexpected behavior installing and using Zowe CLI.

### ***Command not found message displays when issuing `npm install` commands***

#### **Valid on all supported platforms**

##### **Symptom:**

When you issue NPM commands to install the CLI, the message *command not found* displays. The message indicates that Node.js and NPM are not installed on your computer, or that PATH does not contain the correct path to the NodeJS folder.

#### **Solution:**

To correct this behavior, verify the following:

- Node.js and NPM are installed.
- PATH contains the correct path to the NodeJS folder.

**More Information:** [System requirements](#) on page 31

### **npm install -g Command Fails Due to an EPERM Error**

#### **Valid on Windows**

##### **Symptom:**

This behavior is due to a problem with Node Package Manager (npm). There is an open issue on the npm GitHub repository to fix the defect.

#### **Solution:**

If you encounter this problem, some users report that repeatedly attempting to install Zowe CLI yields success. Some users also report success using the following workarounds:

- Issue the `npm cache clean` command.
- Uninstall and reinstall Zowe CLI. For more information, see [Installing Zowe CLI](#) on page 73.
- Add the `--no-optional` flag to the end of the `npm install` command.

### **Sudo syntax required to complete some installations**

#### **Valid on Linux and macOS**

##### **Symptom:**

The installation fails on Linux or macOS.

#### **Solution:**

Depending on how you configured Node.js on Linux or macOS, you might need to add the prefix `sudo` before the `npm install -g` command or the `npm uninstall -g` command. This step gives Node.js write access to the installation directory.

### **npm install -g command fails due to npm ERR! Cannot read property 'pause' of undefined error**

#### **Valid on Windows or Linux**

##### **Symptom:**

You receive the error message `npm ERR! Cannot read property 'pause' of undefined` when you attempt to install the product.

#### **Solution:**

This behavior is due to a problem with Node Package Manager (npm). If you encounter this problem, revert to a previous version of npm that does not contain this defect. To revert to a previous version of npm, issue the following command:

```
npm install npm@5.3.0 -g
```

### **Node.js commands do not respond as expected**

#### **Valid on Windows or Linux**

**Symptom:**

You attempt to issue node.js commands and you do not receive the expected output.

**Solution:**

There might be a program that is named *node* on your path. The Node.js installer automatically adds a program that is named *node* to your path. When there are pre-existing programs that are named *node* on your computer, the program that appears first in the path is used. To correct this behavior, change the order of the programs in the path so that Node.js appears first.

**Installation fails on Oracle Linux 6****Valid on Oracle Linux 6****Symptom:**

You receive error messages when you attempt to install the product on an Oracle Linux 6 operating system.

**Solution:**

Install the product on Oracle Linux 7 or another Linux or Windows OS. Zowe CLI is not compatible with Oracle Linux 6.

**Raising a CLI issue on GitHub**

When necessary, you can raise GitHub issues against the Zowe CLI repository [here](#). It is suggested that you use either the bug or enhancement template.

**Raising a bug report**

Please provide as much of the information listed on [Troubleshooting Zowe CLI](#) on page 253 as is reasonable. Anyone working on the issue might need to request this and other information if it is not supplied initially. A description of the error and how it can be reproduced is the most important information.

**Raising an enhancement report**

Enhancement reports are just as important to the Zowe project as bug reports. Enhancement reports should be clear and detailed requirements for a potential enhancement.

**Troubleshooting Zowe through Zowe Open Community**

---

To help Zowe Open Community effectively troubleshoot Zowe, we introduce a shell script that captures diagnostics data that is required for successful troubleshooting. By running the shell script on your z/OS environment, you receive a set of output files, which contain all relevant diagnostics data necessary to start a troubleshooting process. You can find the `zowe-support.sh` script in the `ZOWEDIR/scripts` folder with the rest of Zowe scripts. The script captures the following data:

- Started task output
  - Zowe server started task
  - Zowe Cross Memory started task (STC)
    - Zowe CLI or REXX (TSO output command, STATUS, capture all)
- Zowe Install log
- Scripts that are called from `run-zowe.sh`
- Versions:
  - `manifest.json`
  - z/OS version
  - Java version
  - Node version

- Additional logs
  - Zowe app server
  - zLUX app server
- Process list with CPU info with the following data points:
  - Running command and all arguments of the command
  - Real time that has elapsed since the process started
  - Job name
  - Process ID as a decimal number
  - Parent process ID as a decimal number
  - Processor time that the process used
  - Process user ID (in a form of user name if possible, or as a decimal user ID if not possible)

## Contact Zowe Open Community to Troubleshoot Zowe

Contact Zowe Open Community to address and troubleshoot a Zowe issue.

### Follow these steps:

1. Contact Open Zowe Community in [Slack](#) to address your issues.
2. Get instructions from the Community on whether you need to run the script that collects diagnostics data. If you do not need to run the script, the Community will proceed with troubleshooting.
3. If the Community instructs you to run the `zowe-support.sh` script, issue the following commands:

```
cd $ZOWE_ROOT_DIR/scripts  
./zowe-support.sh
```

4. Send the `.pax.Z` output file to Community members for further troubleshooting.

## **<<<<< HEAD Community members start to troubleshoot your issue.**

---

Community members will help you troubleshoot an issue.

master



---

# Chapter

# 5

---

## Contributing

---

**Topics:**

- [Code guidelines](#)
  - [UI guidelines](#)
  - [How to contribute](#)
- 

# Code guidelines

---

## Code categories

The Zowe codebase consists of a few key areas, with both unique and shared guidelines that define how to write new code. A few such areas are:

- Server Core
- Server Security
- Microservices
- Zowe Desktop Applications
- Zowe Application Framework
- Zowe CLI and CLI Plug-ins
- Imperative CLI Framework

## Programming languages

For each area of the codebase, there are established and favored programming languages. Each repository in Github identifies the primary language used. Some of the basic skills needed to contribute to the project include:

- **CLI** - Node.js, TypeScript
- **Desktop UI** - Node.js, JavaScript
- **APIs** - C, Assembler, Java, Spring
- **API Mediation Layer** - Java, Spring

**Note:** JavaScript is not recommended and should be avoided in favor of Typescript to utilize typing.

## Component-specific guidelines and tutorials

This "Code Guidelines" section provides high-level best practices. Each component may have more specific contribution guidelines. Look for a CONTRIBUTING.md file in the component's GitHub repository for specific details.

To learn more about how to develop Zowe applications and plug-ins or extending Zowe with APIs, see [Onboarding Overview](#) on page 130.

## General code style guidelines

All code written in the languages described in [Code categories](#) on page 262 should adhere to the following guidelines to facilitate collaboration and understanding.

**Note:** Uncertainties, unimplemented but known future action-items, and odd/specific constants should all be accompanied with a short comment to make others aware of the reasoning that went into the code.

### Whitespaces

Do not use tabs for whitespace. Use 2 spaces per tab instead.

### Naming Conventions

Self-documenting code reduces the need for extended code comments. It is encouraged to use names as long as necessary to describe what is occurring.

### Functions and methods

Methods should be named as verbs (for example, `get` or `set`), while Objects/Classes should be nouns.

Objects and functions should be CamelCase. Methods on Objects should be dromedaryCase.

## Variables

Constants should be CAPITALIZED\_AND\_UNDERSCORED for clarity, while variables can remain dromedaryCase.

Avoid non-descriptive variable names such as single letters (except for iteration in loops such as i or j) and variable names that have been arbitrarily shortened (Don't strip vowels; long variable names are OK).

## Pull requests guidelines

The Zowe source code is stored in GitHub repositories under the [Zowe GitHub project](#). You contribute to the project through Pull Requests in GitHub.

Each pull request is made against a repository that has assigned "maintainers". Pull requests cannot be merged without the approval of at least one maintainer, who will review Pull Requests to ensure that they meet the following criteria:

- The code in the pull request must adhere to the [General code style guidelines](#) on page 262.
- The code must compile/transpile (where applicable) and pass a smoke-test such that the code is not known to break the current state of Zowe.
- The pull request must describe the purpose and implementation to the extent that the maintainer understands what is being accomplished. Some pull requests need less details than others.
- The pull request must state how to test this change, if applicable, such that the maintainer or a QA team can check correctness. The explanation may simply be to run included test code.
- If a pull request depends upon a pull request from the same/another repository that is pending, this must be stated such that maintainers know in which order to merge open pull requests.

## Documentation Guidelines

Documentation of Zowe comes in various forms depending on the subject being detailed. In general, consider how you can help end users and contributors through external documentation, in-product help, error messages, etc... and open an issue in [zowe/docs-site](#) if you need assistance.

### Contributing to external documentation

The external documentation for the Zowe project, [Zowe Docs](#), is completely open-source. See [How to contribute](#) on page 277 for more information about contributing to the documentation.

Consider: Release Notes, Install/Config/User Guides, Developer Tutorials, etc...

### Component Categories

Provide the following documentation depending on the component that you contribute to:

#### Server Core

Principles of operation and end-user guides (configuration, troubleshooting) should be documented on Zowe Docs site. Code documentation follows language-specific formats.

#### Server Security

Principles of operation and end-user guides (configuration, troubleshooting) should be documented on Zowe Docs site. Code documentation follows language-specific formats.

#### Microservices

Microservices implement a web API, and therefore must be documented for understanding and testing. These web APIs must be accompanied with documentation in the Swagger (<https://swagger.io/>) format. These documents must be Swagger 2.0, .yaml extension files. Zowe Application Framework plug-ins that implement microservices should store these files within the /doc/swagger folder.

## Zowe Desktop Applications

Zowe Desktop applications should include documentation that explains how to use them, such that this documentation can integrate with a Zowe Desktop documentation reader. This is not strictly API documentation, but rather user guides that can display within the Desktop GUI. The preferred documentation format is a .md extension file that exists in the /doc/guide folder of an App.

### Web Framework

Principles of operation and end-user guides (configuration, troubleshooting) should be documented on Zowe Docs site. Code documentation follows language-specific formats.

### CLI Plugins

Provide a readme.md file for developers (overview, build, test) as well as end-user documentation for your plug-in on Zowe Docs site.

For more information, see the CLI [documentation contribution guidelines](#).

### Core CLI Imperative CLI Framework

Contributions that affect end users of the CLI should be documented on Zowe Docs site.

Contributions that affect the underlying Imperative CLI Framework should be documented in [the GitHub Wiki](#) for future developers using the framework.

Code documentation follows language-specific formats.

## Programming Languages

Each of the common languages in Zowe have code-documentation-generation tools, each with their own in-code comment style requirements to adhere to in order to generate readable API references. Objects and functions of interest should be commented in accordance to the language-specific tools to result in output that serves as the first point of documentation for APIs.

### TypeScript

When writing TypeScript code, comment objects and functions in compliance with [JSDoc](#). If you are writing in an area of the codebase that does not yet have a definition file for JSDoc, define a configuration file that can be used for future documentation of that code.

### Java

When writing TypeScript code, comment objects and functions in the Javadoc format.

### C

When writing C code, comment functions and structures in compliance with Doxygen.

---

## UI guidelines

### Introduction

This style guide is the visual language that represents Zowe. It is a living document that will be updated based on the needs of our users and software requirements.

### Clear

Our users rely on our software to help them be efficient in their work. The interfaces and experiences that we design should be clear so that there is never confusion about where to click or how to take the next step. Users should always feel confident in their actions.

## **Consistent**

Users should be able to look at Zowe software products and know that they are in a family. Each software product is different, but should use similar patterns, icons, and interactions. If a user switches to a new product within Zowe, it should feel familiar.

## **Smart**

Our users are intelligent, and they need smart software. Zowe design patterns should always compliment the user's intelligence and reflect the user's complex work environment. Designs should align with the Zowe design language by putting the human needs of the user first.

## **Colors**

Color brings a design to life. Color is versatile; it's used to express emotion and tone, as well as place emphasis and create associations. Color should always be used in meaningful and intentional ways to create patterns and visual cues.

### **Color palette**

The Zowe color palette is designed and implemented in a theme-able manner. The universal color variables are determined by common roles and usage; it is not based singularly on a color value (i.e. unique hex code). The same color value might be assigned to multiple variables in a theme's palette when the values have distinctly different roles.

A universal variable can also have multiple associated roles when the color is consistently used across those roles. This allows for uniform color application across themes, while giving each theme the freedom to express its own individuality at a more detailed level.

●	zBlue_10 #edf2fa	●	zCerulean_10 #eaf7fbv	●	zAqua_10 #edf7f7	●
●	zBlue_20 #c9d9f2	●	zCerulean_20 #c2e8f4	●	zAqua_20 #c9e8e8	●
●	zBlue_30 #82a8e1	●	zCerulean_30 #71cbe6	●	zAqua_30 #81cbcb	●
●	zBlue_40 #5e8fd9	●	zCerulean_40 #49bcdf	●	zAqua_40 #5dbcfc	●
● ●	zBlue_50 #3975d0	●	zCerulean_50 #1fa7d1	●	zAqua_50 #39aeae	●
●	zBlue_60 #3162ac	● ●	zCerulean_60 #1980a4	●	zAqua_60 #2f8f8f	●
●	zBlue_70 #264c86	●	zCerulean_70 #156f8b	●	zAqua_70 #256f6f	●
●	zBlue_80 #1b375f	●	zCerulean_80 #0f5063	●	zAqua_80 #1a5050	●
●	zBlue_90 #112139	●	zCerulean_90 #0c313a	●	zAqua_90 #103030	●
●	zBlue_100 #060b13	●	zCerulean_100 #031014	●	zAqua_100 #061010	●

●	zLime_10 #f3f9ea	●	zYellow_10 #fefae9	●	zOrange_10 #fdf4eb	●
●	zLime_20	●	zYellow_20	●	zOrange_20	●

Light theme

## Primary / Secondary Colors



**zBlue\_60**  
#3162ac



**zCoolGray\_60**  
#6d7176

## Support Colors



**zSupport\_01**  
#e0182d



**zSupport\_02**  
#e99023



**zSupport\_02**  
#97cf46



## UI Colors


**zCoolGray\_10**  
#f3f4f4

**zCoolGray\_20**  
#dddee0

Dark theme


## Primary / Secondary Colors



## Support Colors



## UI Colors



## Color contrast | WCAG AA standards

- Type colors

All type color combinations on Zowe must pass WCAG AA standards of 4.5:1 for normal text and 3:1 for large text. For larger text, if the font weight is light (300) or normal (400) the text should be no smaller than 24px. If the font weight is Semi-Bold (600) then the large text should be no smaller than 19px.

- Body Text (4.5:1)
- Large Text (3:1): at least 24px / 19px semi-bold

WCAG guidelines: <https://www.w3.org/WAI/standards-guidelines/wcag/>

Contrast Checker Tool: <https://webaim.org/resources/contrastchecker/>

## Typography

Typography is used to create clear hierarchies, useful organizations, and purposeful alignments that guide users through the product and experience. It is the core structure of any well designed interface.

### Typeface

Title typeface: Roboto Condensed

Body typeface: Roboto

Sample:

# Title Font: The spectacle before us was indeed sublime.

Body Font: Apparently we had reached a great height in the atmosphere, for it was a dead black, and the stars had ceased to twinkle. By the same illusion which makes the horizon of the sea to the level of the spectator on a hillside, the sable clouds dished out, and the car seemed to float in the middle of an immense dark space; the upper half was strewn with silver. Looking down into the dark gulf below, I could see a ruddy light streaming through a rift in the clouds.

### Font weight

Font weight is an important typographic style that can add emphasis and is used to differentiate content hierarchy. Font weight and size pairings must be carefully balanced. A bold weight will always have more emphasis than a lighter weight font of the same size. However, a lighter weight font can rank hierarchically higher than a bold font if the lighter weight type size is significantly larger than the bold.

Roboto font family provides a wide range of weights. However, only SemiBold, Regular, Light should be used for product design.

- Font-weight: 300 / Light

## Light

Should only be used at sizes greater than or equal to 18px / 1.125rem

- Font-weight: 400 / Normal

## Regular

- Font-weight: 500 / Semi-bold

## Semi-Bold

### Body copy

We recommended that you use two sizes for body copy. The first size is UI specific. To maximize screen real estate we chose a smaller 14px / 0.875rem body copy size for the standard UI console. However, for areas that have prolonged reading, such as Documentation, we use a larger body copy size of 16px / 1rem to enhance readability.

### Line scale

- 1.333 Perfect Fourth-type scale - desktop

3.157em A Visual Type Scale

2.369em A Visual Type Scale

1.777em A Visual Type Scale

1.333em A Visual Type Scale

1em A Visual Type Scale

0.75em A Visual Type Scale

0.563em A Visual Type Scale

0.422em A Visual Type Scale

- 1.2 Minor Third type-scale - mobile

## 2.074em A Visual Type Scale

### 1.728em A Visual Type Scale

#### 1.44em A Visual Type Scale

##### 1.2em A Visual Type Scale

###### 1em A Visual Type Scale

###### 0.833em A Visual Type Scale

###### 0.694em A Visual Type Scale

###### 0.579em A Visual Type Scale

## Line-height

Line-height, traditionally known as leading, is one of several factors that directly contribute to readability and pacing of copy. Line-heights are based on the size of the font itself. Ideal line-heights for standard copy have a ratio of 1:1.5 (type-size : line-height). For example, a type at 16px / 1rem would have a line-height of 1.5rem / 24px (16 x 1.5). The exception to this rule are headings, which need less spacing and therefore have a line-height ratio of 1:1.25.

## Embed font

To embed your selected fonts into a web page, copy the following code into the <head> of your HTML document:

```
<link href="https://fonts.googleapis.com/css?family=Roboto+Condensed|Roboto:300,400,500" rel="stylesheet">
```

## Import font

```
<style>
@import url('https://fonts.googleapis.com/css?family=Roboto+Condensed|Roboto:300,400,500');
</style>
```

## Specify in CSS

Use the following CSS rules to specify these families:

```
font-family: 'Roboto', sans-serif;
font-family: 'Roboto Condensed', sans-serif;
```

## Grid

Grid systems are used for creating page layouts through a series of rows and columns that house your content. Zowe uses a responsive, mobile-first, fluid grid system that appropriately scales up to 12 columns as the device or view port size increases.

### 12 column grid

A 12 column grid is recommended. 12 is a well-distributed division that provides a good range of widths to assign to content. It is dividable by 2, 3, 4 and 6, which allows flexibility. Many frameworks, such as Bootstrap and Pure, use a 12 column grid by default. Other grid systems like a 5 column grid can reduce flexibility, balance, and consistency.

## Gutters

Columns create gutters (gaps between column content) through padding. For devices with a screen width greater than 768px, the column padding is 20px. For devices with a screen width less than 768px, the column padding is 10px.

Screen width # 768px = 20px gutters

Screen width 768px = 10px gutters

## Columns

Zowe designs should be limited to 12 columns. If designers feel that they need fewer columns in their grid, they can specify the number of 12 available columns they wish to span.

This can translate to percentages of the twelve columns. Using this method, a designer can create a folded, less granular grid. For example, if your component spans three equal columns, that is equal to 25% of twelve columns.

Column count: 12

## Margins


The 12 column grid does not have a maximum width. It has a width of 100%, with built in margins that create padding between column count and the edges of the viewport.

In devices with a screen width greater than 768px, the margins are **5%** on the left, and **5%** on the right.

In devices with a screen width less than 768px, the margins are **3%** on the left, and **3%** on the right.


### Example: Screen Width > 768px

```
5% left = 38px (rounded to nearest whole pixel)
5% right = 38px (rounded to nearest whole pixel)
12 columns + gutters = 768px - 38px - 38px = 692px (rounded to nearest
whole pixel)
```



### Example: Screen Width 320px


```
3% left = 10px (rounded to nearest whole pixel)
3% right = 10px (rounded to nearest whole pixel)
12 columns + gutters = 320px - 10px - 10px = 300px (rounded to nearest
whole pixel)
```



### Iconography

Icons are key component for a successful UI design because they are a visual way to help add meaning to elements.

[Font Awesome](#) is a robust icon library that allows for an easy addition to any web project. Scalable vector icons that can instantly be customized — size, color, drop shadow, and anything that can be done with the power of CSS.



## 1480 Free Icons

- **One Font, Hundreds of Icons** – In a single collection, Font Awesome is a pictographic language of web-related actions.
- **No JavaScript Required** – Fewer compatibility concerns because Font Awesome doesn't require JavaScript.
- **Infinite Scalability** – Scalable vector graphics means every icon looks awesome at any size.
- **Free, as in Speech** – Font Awesome is completely free for commercial use. Check out the license.
- **CSS Control** – Easily style icon color, size, shadow, and anything that's possible with CSS.
- **Perfect on Retina Displays** – Font Awesome icons are vectors, which mean they're gorgeous on high-resolution displays.
- **Plays Well with Others** – Originally designed for Bootstrap, Font Awesome works great with all frameworks.
- **Desktop Friendly** – To use on the desktop or for a complete set of vectors, check out the cheatsheet.
- **Accessibility-minded** – Font Awesome loves screen readers and helps make your icons accessible on the web.

To learn more or download the library go to [www.fontawesome.com](http://www.fontawesome.com)

## Application icon

### General rules

**Embrace simplicity.** Use a simple, unique shape or element that represents the essence of the application. Avoid excessive details and redundant shading.

**Use the Zowe color palette.** Avoid using a monochromatic palette for your icons. Use the Zowe color palette to ensure that the icons have a consistent look.


**Use unique shapes and design elements.** Avoid using single commonly used design elements, such as the gear, document, or folder. These elements can reduce recognizability. Do not use photos and screenshots. Keep icons simple and abstract.

**Avoid labels and text.** Short, commonly used abbreviations are acceptable, if necessary. Remember that all icons have center-aligned labels beneath them.

**Use brand identity.** If your Zowe application has a brand identity element such as a logo, you can use it. Remember to include the copyright symbol.

### Shape, size, and composition

**Use a flat design style.** Flat design focuses on open space, bright colors, and flat graphics or illustrations. Our minimalist design approach puts the emphasis on usability.



### Preferable


### Avoid

A flat icon has clean, crisp edges and a flat dimensional layout.

**Use solid fill shapes.** Most Zowe App icons have solid fill shapes, which are more readable on dark backgrounds.

Use the circle shape for the background application icons. Set the outer corners to 100% opacity. Create an image file that is 87x87 pixels, and save the file in PNG format.


**Maintain consistent visual proportions.**



## Colors and shades

### Verify the contrast

Verify that the background color of the icon provides enough contrast against the desktop.



**Preferable**


**Avoid**

### Use the Zowe palette

To ensure that your app icons are clear and consistent, use the [Color palette](#) on page 265. If you need to use well-established brand identity elements, you can use the colors that are associated with the brand.

### Layer Shadows


Use smooth shadows to represent that some elements are on different layers and should be visually separated. Avoid using too many layers because they can overcomplicate the icon.



### Use the long shadow for consistency.

Although the long shadow effect does not have any semantic meaning, it adds focus to the main icon shape and identifies the central, most meaningful element.

Use the gradient shadow settings shown in the following image, or use a flat non-gradient shadow with 20% opacity and #000000 color.



## Gradient Setting

### Point A

Color #000000  
Opacity 30%

### Point B

Color #000000  
Opacity 8%

## How to contribute

---

:fireworks: :balloon: **First off, thanks for taking the time to contribute!** :sparkler: :confetti\_ball:

We provide you a set of guidelines for contributing to Zowe documentation, which are hosted in the <https://github.com/zowe/docs-site> on GitHub. These are mostly guidelines, not rules. Use your best judgment, and feel free to propose content changes to this documentation.

:arrow\_right: [Before you get started](#)

:arrow\_right: [Contributing to documentation](#)

:arrow\_right: [Documentation style guide](#)

:arrow\_right: [Word usage](#)

### Before you get started

The Zowe documentation is written in Markdown markup language. Not familiar with Markdown? <https://www.markdownguide.org/basic-syntax>

### Contributing to documentation

You can use one of the following ways to contribute to documentation:

- Send a GitHub pull request to provide a suggested edit for the content by clicking the **Propose content change in GitHub** link on each documentation page.
- Open an issue in GitHub to request documentation to be updated, improved, or clarified by providing a comment.

## Sending a GitHub pull request

You can provide suggested edit to any documentation page by using the **Propose content change in GitHub** link on each page. After you make the changes, you submit updates in a pull request for the Zowe content team to review and merge.

Follow these steps:

1. Click **Propose content change in GitHub** on the page that you want to update.
2. Make the changes to the file.
3. Scroll to the end of the page and enter a brief description about your change.
4. Optional: Enter an extended description.
5. Select **Propose file change**.
6. Select **Create pull request**.

## Opening an issue for the documentation

You can request the documentation to be improved or clarified, report an error, or submit suggestions and ideas by opening an issue in GitHub for the Zowe content team to address. The content team tracks the issues and works to address your feedback.

Follow these steps:

1. Click the **GitHub** link at the top of the page.
2. Select **Issues**.
3. Click **New issue**.
4. Enter a title and description for the issue.
5. Click **Submit new issue**.

## Documentation Style guide

This section gives writing style guidelines for the Zowe documentation. These are guidelines, not rules. Use your best judgment, and feel free to propose content changes to this documentation in a pull request.

:arrow\_right: [Headings and titles](#)  
 :arrow\_right: [Technical elements](#)  
 :arrow\_right: [Tone](#) on page 280  
 :arrow\_right: [Word usage](#)  
 :arrow\_right: [Graphics](#) on page 282  
 :arrow\_right: [Abbreviations](#) on page 282  
 :arrow\_right: [Structure and format](#)

### Headings and titles

#### Use sentence-style capitalization for headings

Capitalize only the initial letter of the first word in the text and other words that require capitalization, such as proper nouns. Examples of proper nouns include the names of specific people, places, companies, languages, protocols, and products.

Example: Verifying that your system meets the software requirements.

#### For tasks and procedures, use gerunds for headings.

Example:

- Building an API response
- Setting the active build configuration

**For conceptual and reference information, use noun phrases for headings.**

Example:

- Query language
- Platform and application integration

**Use headline-style capitalization for only these items:**

Titles of books, CDs, videos, and stand-alone information units.

Example:

- Installation and User's Guide
- Quick Start Guides or discrete sets of product documentation

**Make headings brief, descriptive, grammatically parallel, and, if possible, task oriented.**

If the subject is a functional overview, begin a heading with words such as Introduction or Overview rather than contriving a pseudo-task-oriented heading that begins with Understanding, Using, Introducing, or Learning.

## Technical elements

### Variables

Style:

- Italic when used outside of code examples,
- Example: *myHost*
- If wrap using angle brackets <> within code examples, italic font is not supported.

Example:

- put <pax-file-name>.pax
- Where *pax-file-name* is a variable that indicates the full name of the PAX file you download. For example, zoe-0.8.1.pax.

### Message text and prompts to the user

Style: Put messages in quotation marks.

Example: "The file does not exist."

### Code and code examples

Style: Monospace

Example: `java -version`

### Command names, and names of macros, programs, and utilities that you can type as commands

Style: Monospace

Example: Use the BROWSE command.

### Interface controls

Categories: check boxes, containers, fields, folders, icons, items inside list boxes, labels (such as **Note:**), links, list boxes, menu choices, menu names, multicolumn lists, property sheets, push buttons, radio buttons, spin buttons, and Tabs

Style: Bold

Example: From the **Language** menu, click the language that you want to use. The default selection is **English**.

## **Directory names**

Style: Monospace

Example: Move the `install.exe` file into the `newuser` directory.

## **File names, file extensions, and script names**

Style: Monospace

Example:

- Run the `install.exe` file.
- Extract all the data from the `.zip` file.

## **Search or query terms**

Style: Monospace

Example: In the Search field, enter Brightside.

## **Citations that are not links**

Categories: Chapter titles and section titles, entries within a blog, references to industry standards, and topic titles in IBM Knowledge Center

Style: Double quotation marks

Example:

- See the "Measuring the true performance of a cloud" entry in the Thoughts on Cloud blog.
- See "XML Encryption Syntax and Processing" on the W3C website.
- For installation information, see "Installing the product" in IBM Knowledge Center.

## **Tone**

### **Use simple present tense rather than future or past tense, as much as possible.**

Example:

:heavy\_check\_mark: The API returns a promise.

:x: The API will return a promise.

### **Use simple past tense if past tense is needed.**

Example:

:heavy\_check\_mark: The limit was exceeded.

:x: The limit has been exceeded.

### **Use active voice as much as possible**

Example:

:heavy\_check\_mark: In the Limits window, specify the minimum and maximum values.

:x: The Limits window is used to specify the minimum and maximum values.

Exceptions: Passive voice is acceptable when any of these conditions are true:

- The system performs the action.
- It is more appropriate to focus on the receiver of the action.
- You want to avoid blaming the user for an error, such as in an error message.

- The information is clearer in passive voice.

Example:

:heavy\_check\_mark: The file was deleted.

:x: You deleted the file.

### **Using second person such as "you" instead of first person such as "we" and "our".**

In most cases, use second person ("you") to speak directly to the reader.

### **End sentences with prepositions selectively**

Use a preposition at the end of a sentence to avoid an awkward or stilted construction.

Example:

:heavy\_check\_mark: Click the item that you want to search for.

:x: Click the item for which you want to search.

### **Avoid using "Please", "thank you"**

In technical information, avoid terms of politeness such as "please" and "thank you". "Please" is allowed in UI only when the user is being inconvenienced.

Example: Indexing might take a few minutes. Please wait.

### **Avoid anthropomorphism.**

Focus technical information on users and their actions, not on a product and its actions.

Example:

:heavy\_check\_mark: User focus: On the Replicator page, you can synchronize your local database with replica databases.

:x: Product focus: The Replicator page lets you synchronize your local database with replica databases.

### **Avoid complex sentences that overuse punctuation such as commas and semicolons.**

#### **Word usage**

**Note headings such as Note, Important, and Tip should be formatted using the lower case and bold format.**

Example:

- **Note:**
- **Important!**
- **Tip:**

### **Use of "following"**

For whatever list or steps we are introducing, the word "following" should precede a noun.

Example:

- Before a procedure, use "Follow these steps:"
- The <component\_name> supports the following use cases:
- Before you intall Zowe, review the following prerequisite installation tasks:

Avoid ending the sentence with "following".

Example:

:x: Complete the following.

:heavy\_check\_mark: Complete the following tasks.

## **Use a consistent style for referring to version numbers.**

When talking about a specific version, capitalize the first letter of Version.

Example:

:heavy\_check\_mark: Java Version 8.1 or Java V8.1

:x: Java version 8.1, Java 8.1, or Java v8.1

When just talking about version, use "version" in lower case.

Example: Use the latest version of Java.

## **Avoid "may"**

Use "can" to indicate ability, or use "might" to indicate possibility.

Example:

- Indicating ability:

:heavy\_check\_mark: You can use the command line interface to update your application."

:x: "You may use the command line interface to update your application."

- Indicating possibility:

:heavy\_check\_mark: "You might need more advanced features when you are integrating with another application."  
"

:x: "You may need more advanced features when you are integrating with another application."

## **Use "issue" when you want to say "run/enter" a command.**

Example: At a command prompt, type the following command:

## **Graphics**

- Use graphics sparingly.

Use graphics only when text cannot adequately convey information or when the graphic enhances the meaning of the text.

- When the graphic contains translatable text, ensure you include the source file for the graphic to the doc repository for future translation considerations.

## **Abbreviations**

**Do not use an abbreviation as a noun unless the sentence makes sense when you substitute the spelled-out form of the term.**

Example:

:x: The tutorials are available as PDFs.

:heavy\_check\_mark: The tutorials are available as PDF files.

## **Do not use abbreviations as verbs.**

Example:

:x: You can FTP the files to the server.

:heavy\_check\_mark: You can use the FTP command to send the files to the server.

## **Do not use Latin abbreviations.**

Use their English equivalents instead. Latin abbreviations are sometimes misunderstood.

Latin	English equivalent
e.g.	for example

Latin	English equivalent
etc.	and so on. When you list a clear sequence of elements such as "1, 2, 3, and so on" and "Monday, Tuesday, Wednesday, and so on." Otherwise, rewrite the sentence to replace "etc." with something more descriptive such as "and other output."
i.e.	that is

**Spell out the full name and its abbreviation when the word appears for the first time. Use abbreviations in the texts that follow.**

Example: Mainframe Virtual Desktop (MVD)

### Structure and format

Add "More information" to link to useful resources or related topics at the end of topics where necessary.

## Word usage

The following table alphabetically lists the common used words and their usage guidelines.

Do	Don't
API Mediation Layer	
application	app
Capitalize "Server" when it's part of the product name	
data set	dataset
Java	java
IBM z/OS Management Facility (z/OSMF) z/OSMF	zosmf (unless used in syntax)
ID	id
PAX	pax
personal computer PC server	machine
later	higher Do not use to describe versions of software or fix packs.
macOS	MacOS
Node.js	node.js Nodejs
plug-in	plugin
REXX	Rexx
UNIX System Services z/OS UNIX System Services	USS
zLUX	ZLUX zLux
Zowe CLI	

