Naming Convention

Last updated by | m.calderon.santiago@accenture.com | 16 mar 2026 at 15:49 CET

Contents

- Naming Convention
  - Salesforce API Naming Convention
  - Other Nomenclatures
    - Labels
    - List View
    - Home Pages
    - Documents
    - Letterhead
    - Apex Classes
    - Apex Variables
    - Apex Constants
    - Apex Triggers

Naming Convention

Salesforce API Naming Convention

Recommended naming convention is to use the customer name in the prefix (WERFEN – WE) and include the project stream:

- Sales – SAL: **WESAL_**
- Service – SER: **WESER_**
- Field Service – FSE: **WEFSE_**
- Marketing Cloud – MKT: **WEMKT_**
- Revenue Cloud – REV: **WEREV_**

If the functionality is cross-module, the prefix must use the common value **WERFEN_**.

Following the prefix, a distinction will be made based on the component type.

Component	Value
Object	obj
Field	fld
Path	pth
Job Schedule	job
Approval steps	apbs
Apex Class	cls
Apex Dispatcher	dsp
Sharing Rules	sh
Page Layouts	ply
Record Pages	rp
VisualForce	vf
Global Picklist	pl
Custom Label	lbl
Custom Setting	cs
Remote Sites	rm
Single Sign On	sso
Custom Permissions	cp
Trigger	trg
Button	bt
Process Builder	prcs
Workflow rule	wr
Visual Workflow	vw
Validation Rule	vr
Application	app
Permission Set	ps
Tab	tab
Approval process	apb

Component	Value
Assignment Rule	ar
Certificate	cert
Static Resource	sr
Role	rol
Report	rpt
Dashboard	dshb
Custom Report Type	crt
Record Type	rt
Group	grp
Folder	fldr
Matching rules	mr
Duplicate rules	dr
Queue	queue
Quick Action	qaction
Email template	eptl
Email template folder	eptlf
Compact layout	cly
Workflow field update	fu
listView	lstv
Sales Processes	salesPcr
Lead Processes	leadPcr
Case Processes	casePcr
Named Credential	nmc
Visualforce Component	vfc
Custom Metadata Type	cmt
Auto response rule	autorr
Workflow email alert	wea

Component	Value
Entitlement process	entPcr
Sharing set	sharingSet
Entitlement template	entplt
Sharing reason	shReason
Field set	fldSet
Email Application panel	mailRp
Change set	chs
Account Team	accTeam
Case Team	caseTeam
Territory Model	terriMod
Territpry Type	terriType
Territory	terri
Account Team Role	accTeamRol
Notification Type	nt
Platform Event	pev
Dataflow	dtf
Dataset	dts
Lens	lens
Permission Set Group	psg
Audience	aud
Decision Table	decTbl
Message Channel (LWC)	lwcChannel
Workflow Action Task	wtaska
Big Object	bigObj
CSP Trusted Site	cspTrust
Einstein Bot	bot
Data Processing Engine	dpe

Component	Value
Conversation Message Definition	cmd
Live Message Setup	lms
Feed Filters	ff
Einstein Activity Capture	eac
Data Lake Object	dlo
Data Stream	dstr
Data Source Object	dso
Data Model Object	dmo
Calculated Insight	cio
Data Graph	dg
Data Space	ds
Semantic Model	sm
Data Share	dshr

Lastly, the component name will follow the camel case methodology: customFieldName.

For example:

- Apex Class: WESAL_cls_**apexName**
- LWC: WESER_lwc_**componentName**
- RecordType: WERFEN_rt_**recordTypeName**

Other Nomenclatures

Labels

All labels must begin with an uppercase letter and continue in lowercase. For example: **Custom field**

List View

These components must use the application prefix, for example: **WESAL_nameOfTheListView**

Home Pages

These components must use the application prefix, for example: **WESAL_nameOfTheHomePage**

Documents

These components must use the application prefix, for example: **WESAL_nameOfDocument**

Letterhead

These components must use the application prefix, for example: **WESAL_nameOfLetterHead**

Apex Classes

For the different Apex class types, we will also use a special naming convention by means of suffixes.

For example, starting from a base Apex class: **WESAL_cls_nameApexClass**

- Test: **WESAL_cls_nameApexClass_test**
- Utils: **WESAL_cls_nameApexClass_utils**
- Batch: **WESAL_cls_nameApexClass_batch**
- Scheduled: **WESAL_cls_nameApexClass_sch**
- Queueable: **WESAL_cls_nameApexClass_queue**

Apex Variables

Use descriptive names for variables and avoid single-letter names such as Integer a or String c, except when used as counters or control variables.

- **Lists must begin with lst (e.g., lstCustomers).**
- **Maps must begin with map (e.g., mapDistributors).**
- **Sets must begin with set (e.g., setContacts).**

Apex Constants

Constants must be written in uppercase letters using an underscore _ as a separator: For example:
NAME_EXAMPLE

Apex Triggers

Triggers will be unique and centralized per object, invoking handler-type classes to manage the required logic. This approach allows, for example, the use of custom settings to enable or disable different handlers within a trigger without affecting the behavior of the remaining logic.

For example: **WERFEN_trg_Account & WESAL_cls_handlerAccountCustomers**