REST API

Last updated by | m.calderon.santiago@accenture.com | 18 mar 2026 at 13:09 CET

Contents

- Query Services Status Codes
  - Status Codes
  - Examples
    - 400 Bad Request
    - 403 Forbidden
    - 429 Too Many Requests
- Handle Errors in REST API
  - Validation
  - Authorization
  - Authentication
  - Runtime
- API Error Handling & Status Codes
  - Data Validation & Integrity (HTTP 400)
  - Security & Session Management (HTTP 401/403)
  - Execution & Flow Errors (HTTP 500/400)
    - Best Practices for Error Handling
    - Error Categorization & Remediation Matrix
    - Error Classification Table

Query Services Status Codes

The Query Services APIs return standard HTTP status codes to indicate the success or failure of a request. This document provides details about the status codes and their meanings.

Status Codes

Status Code	Description	Details
200 OK	Request successful	The request was processed successfully and the response contains the requested data.
400 Bad Request	Invalid request	The request was malformed or contained invalid parameters. Check the request syntax and parameters.
403 Forbidden	Authorization failed	The request failed to pass authorization. Verify your authentication credentials and permissions.
404 Not Found	Resource not found	The requested resource (callback ID, verification key, or both) was not found.
422 Unprocessable Entity	Invalid attribute	The attribute name used in fields/filter parameter doesn't exist. Verify the field names in your query.
429 Too Many Requests	Rate limit exceeded	Too many requests were made in a given time period. Query API supports up to 15 concurrent requests.
500 Server Error	Internal error	An unexpected error occurred on the server. Contact support if the issue persists.

When an error occurs, the response includes:

- `error`: Error message describing the issue
- `errorCode`: Unique identifier for the error type
- `details`: Additional information about the error (if available)

Examples

The following are examples of error code request and responses.

400 Bad Request

```
{
  "error": "Invalid SQL query syntax",
  "errorCode": "INVALID_SQL",
  "details": "Syntax error at line 1: unexpected token 'FROM'"
}
```

403 Forbidden

```
{
  "error": "Insufficient permissions",
  "errorCode": "FORBIDDEN",
  "details": "User does not have permission to access this resource"
}
```

429 Too Many Requests

```
{
  "error": "Rate limit exceeded",
  "errorCode": "RATE_LIMIT",
  "details": "Maximum of 15 concurrent requests allowed"
}
```

Handle Errors in REST API

Validation

Description	Resolution	HTTP Error	Custom
Generic Exception	Verify that you included the proper endpoint and resource.	400	10000
Invalid Data Type	Confirm that the parameters of your request include the required data types.	400	10001
Missing Required Field	Confirm that the request includes all required fields.	400	10002
Incorrect Format	Verify that the request is formatted correctly.	400	10003
Invalid Message Format	Make sure that the request body has balanced braces and brackets.	400	10004
Invalid Value	Make sure that all values in the request are of the correct data types.	400	10005
Aggregate Error	Check `additionalErrors` for detailed error messages.	400	10006
Unsupported Media Type	Make sure that all media formats in the request are valid and allowed.	415	

Authorization

Description	Resolution	HTTP Error	Custom
General Exception	Ensure you provide the correct resource.	403	20000
Business Rule Not Set	Review the associated permissions and ensure you provide the proper configuration.	403	20001
Insufficient Privileges	Your account lacks the privileges necessary to perform the request.	403	20002

Authentication

Description	Resolution	HTTP Error	Custom
Not Authorized	The access token in the request is missing, invalid, or expired.	401	0
Authorization token invalid on URL or request body	Verify that the request header contains a valid access token.	401	40004
General	Ensure the request specifies the correct resource.	403	40000
Not Authenticated	Verify that the request header contains a valid access token.	403	40001
Authorization token invalid on this endpoint	Use the stack-level endpoint that matches your token.	403	40002
Authorization token invalid on URL	Verify that the request header contains a valid access token.	403	40003
Internal Server Error	See the response returned by the HTTP routing assertion.	500	
Service Not Found	The resource you're trying to access doesn't exist. Verify that the request specifies the correct resource.	596	

Runtime

Description	Resolution	HTTP Error	Custom
Generic	Verify that your request specifies the correct resource.	400	30000
Invalid Operation	Your request uses an invalid HTTP operation for the resource. Modify the request to use a valid operation.	400	30001
Invalid State Transition	This operation requests an invalid state transition for the resource. Ensure you request a valid state transition.	409	30002
Object Not Found	Your request can't find any available data. Ensure you properly created your request.	404	30003
Execution Timeout Expired	Retry the API call using Exponential Backoff .	408	—
Object Already Exists	An existing object has the same ID, key, or name as the object specified in the request. Provide a unique value and try again.	409	30004
Too many requests	Retry the API call after number of seconds specified in "Retry-After" header field.	429	50100
Too many requests	Your API requests are temporarily blocked due to too many concurrent requests. Contact Salesforce Customer Support for more information about the issue.	429	50200
Service Unavailable	Retry the API call after number of seconds specified in "Retry-After" header field.	503	50300

API Error Handling & Status Codes

This section defines the standard Salesforce REST/SOAP API error responses that the integration layer (SAP/Middleware) must be prepared to handle. All error responses are returned as an **Array of Objects**, even if only one error occurs.

Data Validation & Integrity (HTTP 400)

These errors occur when the payload does not comply with the object's schema or business logic.

Error Code	Triggering Scenario	Integration Action
`REQUIRED_FIELD_MISSING`	A mandatory field (e.g., `Name`, `AccountId`) is null.	Check source data mapping.
`INVALID_FIELD_FOR_INSERT_UPDATE`	Attempting to write to a Formula, System, or Read-only field.	Remove the field from the payload.
`INVALID_OR_NULL_FOR_RESTRICTED_PICKLIST`	The value provided does not exist in a Restricted Picklist.	Map to a valid picklist value.
`FIELD_CUSTOM_VALIDATION_EXCEPTION`	A Salesforce **Validation Rule** blocked the transaction.	Review business logic requirements.
`DUPLICATES_DETECTED`	A **Duplicate Rule** blocked the record creation.	Use `upsert` or check for existing records.

Security & Session Management (HTTP 401/403)

Errors related to authentication tokens or User Profile permissions (FLS/CRUD).

Error Code	Triggering Scenario	Integration Action
`INVALID_SESSION_ID`	The OAuth token has expired or is invalid.	Refresh the Session Token.
`INSUFFICIENT_ACCESS_OR_READONLY`	Integration User lacks "Edit" permissions on the record/field.	Update User Profile/Permission Sets.
`INVALID_CROSS_REFERENCE_KEY`	Referencing an ID that exists but belongs to a different object or is inaccessible.	Validate the ID type and sharing rules.

Execution & Flow Errors (HTTP 500/400)

Errors triggered by internal Salesforce automation or platform limits.

Error Code	Triggering Scenario	Integration Action
`CANNOT_INSERT_UPDATE_ACTIVATE_ENTITY`	An Apex Trigger, Flow, or Process Builder failed during execution.	Inspect Salesforce Debug Logs for root cause.
`REQUEST_LIMIT_EXCEEDED`	Concurrent API limits or daily allocation reached.	Implement a retry strategy or increase limits.
`INVALID_FIELD`	The API Name used in the request does not exist in the target environment.	Check for typos or deployment status.

Best Practices for Error Handling

- **Batch Processing:** When using the SObject Collections API, Salesforce can return a mix of successes and failures. The middleware must parse each item in the response array to identify which records failed.
- **HTTP Status Mapping:**
  - **400 (Bad Request):** Fix the data or the logic.
  - **401 (Unauthorized):** Re-authenticate immediately.
  - **403 (Forbidden):** Escalation required (Permissions issue).
  - **429 (Too Many Requests):** Pause and retry later.

Error Categorization & Remediation Matrix

To ensure system resilience, the integration layer must categorize Salesforce API responses into specific action-oriented buckets. This prevents infinite loops on functional errors and ensures rapid recovery for technical glitches.

Error Classification Table

Category	Salesforce Error Codes	Type	Action / Remediation
VALIDATION	`REQUIRED_FIELD_MISSING`, `STRING_TOO_LONG`, `INVALID_FIELD`	Functional	**Do Not Retry.** Correct the mapping or source data.
BUSINESS	`FIELD_CUSTOM_VALIDATION_EXCEPTION`, `DUPLICATES_DETECTED`	Functional	**Do Not Retry.** Requires manual data correction by the user.
SECURITY	`INSUFFICIENT_ACCESS_OR_READONLY`, `INVALID_CROSS_REFERENCE_KEY`	Configuration	**Alert Admin.** Review FLS, CRUD, or sharing settings.
TECHNICAL	`INVALID_SESSION_ID`, `METHOD_NOT_ALLOWED`	Technical	**Automatic Retry.** Refresh OAuth token and resend.
LIMITS	`REQUEST_LIMIT_EXCEEDED`	Platform	**Retry with Backoff.** Wait for the limit window to reset.
PLATFORM	`CANNOT_INSERT_UPDATE_ACTIVATE_ENTITY`	Internal SF	**Alert Developer.** Analyze Debug Logs (Triggers/Flows).
NOT_FOUND	`NOT_FOUND`, `ENTITY_IS_DELETED`	Data Integrity	**Do Not Retry.** Check if the record was merged or removed.