PPO: A Complete Derivation and Its Design Motivations

Course home · 简体中文 · PDF

Item	Details
Applicability	PPO-Clip / GAE theory; PyTorch-style examples are instructional, not a tested training package
Documentation review date	2026-10-18
License	CC BY 4.0 · Xiong Zeng and contributors


Verification scope: Documentation organization and upstream reference snapshot; no tutorial runtime, training or hardware validation. See version notes for pinned source references. Original teaching content uses CC BY 4.0; third-party quotations, figures and code retain their original licenses. Citation alone does not grant relicensing rights.

Contents

- Part I. From Expected Return to Policy Gradients
  - 1. Formulating the reinforcement-learning objective
  - 2. Deriving policy gradients using the log-derivative trick
  - 3. Causality and reward-to-go
- Part II. Baselines, Value Functions, and Advantage
  - 4. Why can we subtract a baseline?
  - 5. Why use the value function as the baseline?
- Part III. Performance Differences, Surrogate Objectives, and Importance Sampling
  - 6. Why can't we reuse old data indefinitely?
  - 7. Step-by-step proof of the performance difference lemma
  - 8. Approximating true improvement by a surrogate objective
  - 9. Deriving the probability ratio by importance sampling
- Part IV. TRPO: Controlling Policy Updates with a Trust Region
  - 10. Why is unconstrained maximization of CPI dangerous?
  - 11. KL divergence and the TRPO constraint
  - 12. TRPO's local second-order approximation and natural gradient
- Part V. Deriving the PPO-Clipped Objective
  - 13. From a KL penalty to a clipped surrogate
  - 14. Positive advantage: stop rewarding overly large probability increases
  - 15. Negative advantage: stop rewarding overly large probability decreases
  - 16. Why do we need `min` instead of clipping alone?

    - 17. Gradient-level interpretation of clipping
    - 18. PPO does not enforce a hard ratio or KL constraint
- Part VI. GAE: How Do We Estimate the Advantage?
    - 19. Monte Carlo advantage: motivation and cost
    - 20. One-step TD advantage from the Bellman equation
    - 21. Deriving n-step advantage estimates
    - 22. Exponential weighting and the GAE derivation
    - 23. The $O(T)$ backward recursion for GAE
    - 24. Constructing critic targets from GAE
- Part VII. The Complete Actor–Critic Loss
    - 25. Actor loss
    - 26. Critic loss
    - 27. Motivation for the entropy bonus
    - 28. Final PPO training objective
- Part VIII. Continuous-Action PPO and Robot Control
    - 29. Gaussian policy log probabilities and importance ratios
    - 30. How does a Gaussian-policy gradient move the action mean?
    - 31. Example: residual PPO for robot manipulation
- Part IX. A Complete PPO Iteration
    - 32. Ten steps from rollout collection to policy updates
    - 33. Compact, adaptable PyTorch implementations
- Part X. Hyperparameters and Diagnostics
    - 34. Common starting hyperparameters and what they mean
- Part XI. Connections to REINFORCE, Actor–Critic, and TRPO
    - 35. Algorithmic progression: one design choice per problem
- Part XII. Final Formula Sheet and Research Takeaways
    - References and further reading

Chapter concept map



Part I. From Expected Return to Policy Gradients

1. Formulating the reinforcement-learning objective

Consider a Markov decision process (MDP)

$$\mathcal{M} = (\mathcal{S}, \mathcal{A}, P, r, \gamma, \rho_0),$$

where $s_t \in \mathcal{S}$ denotes a state, $a_t \in \mathcal{A}$ an action, $P(s_{t+1} \mid s_t, a_t)$ the environment transition kernel, r_t the reward, ρ_0 the initial-state distribution, and $\pi_\theta(a \mid s)$ a stochastic policy parameterized by θ. The goal is

$$\boxed{\theta^* = \arg\max_\theta J(\theta)}, \qquad \boxed{J(\theta) = \mathbb{E}_{\tau \sim p_\theta}\left[\sum_{t=0}^{\infty} \gamma^t r_t\right]}. \tag{1}$$

A trajectory is $\tau = (s_0, a_0, s_1, a_1, \ldots)$, with discounted return $R(\tau) = \sum_t \gamma^t r_t$. Consequently,

$$J(\theta) = \int p_\theta(\tau) R(\tau)\, d\tau.$$

Motivation and difficulty. Policy parameters influence actions, which affect future states and subsequent rewards:

$$\theta \longrightarrow a_0 \longrightarrow s_1 \longrightarrow a_1 \longrightarrow \cdots \longrightarrow R(\tau).$$

With contact, collision, friction, or unknown dynamics, differentiating the return through the physical environment may be unavailable or impractical. We need a gradient estimator that **does not require differentiable dynamics**.

2. Deriving policy gradients using the log-derivative trick

Differentiate the expected return:

$$\nabla_\theta J(\theta) = \int \nabla_\theta p_\theta(\tau) R(\tau)\, d\tau.$$

Apply the score-function identity

$$\boxed{\nabla_\theta p_\theta(\tau) = p_\theta(\tau) \nabla_\theta \log p_\theta(\tau)}. \tag{2}$$

We obtain

$$\boxed{\nabla_\theta J(\theta) = \mathbb{E}_{\tau \sim p_\theta}\left[R(\tau) \nabla_\theta \log p_\theta(\tau)\right]}. \tag{3}$$

This is the **likelihood-ratio (score-function) trick**. It converts the gradient of a probability density into a derivative of its log density. The second key observation is that an MDP trajectory probability factors:

$$p_\theta(\tau) = \rho_0(s_0) \prod_{t=0}^{\infty} \pi_\theta(a_t \mid s_t) P(s_{t+1} \mid s_t, a_t).$$

Taking logarithms, and assuming neither the initial-state distribution nor the transition kernel depends on θ,

$$\begin{aligned} \log p_\theta(\tau) &= \log \rho_0(s_0) + \sum_t \log \pi_\theta(a_t \mid s_t) + \sum_t \log P(s_{t+1} \mid s_t, a_t), \\ \boxed{\nabla_\theta \log p_\theta(\tau)} &= \boxed{\sum_t \nabla_\theta \log \pi_\theta(a_t \mid s_t)}. \end{aligned} \tag{4}$$

Thus, formally,

$$\boxed{\nabla_\theta J(\theta) = \mathbb{E}\left[R(\tau)\sum_t \nabla_\theta \log \pi_\theta(a_t \mid s_t)\right]}. \tag{5}$$

A rigorous infinite-horizon derivation requires the usual integrability and interchange-of-limits assumptions; alternatively, derive the result in finite horizon and take a suitable limit.

What did this accomplish? We differentiate only the policy network's $\log \pi_\theta(a_t \mid s_t)$. The environment is used in the forward direction to generate trajectories and rewards, without requiring its derivatives.

3. Causality and reward-to-go

Equation (5) multiplies every action's score gradient by the entire trajectory return. But the action a_t cannot change rewards that occurred before t. The zero-mean score identity makes the expected contribution of those past-reward cross terms vanish. Define reward-to-go

$$G_t = \sum_{k=t}^{\infty} \gamma^{k-t} r_k.$$

Then

$$\boxed{\nabla_\theta J(\theta) = \mathbb{E}\left[\sum_{t=0}^{\infty} \gamma^t \nabla_\theta \log \pi_\theta(a_t \mid s_t) G_t\right]}. \tag{6}$$

Motivation. Credit an action for outcomes that it can actually influence. Discarding past rewards often reduces variance while preserving the expected gradient. The explicit γ^t is needed for the return objective in Eq. (1); implementations commonly average sampled time steps without this explicit factor, which amounts to a particular sampling/weighting convention rather than an identical expression for every infinite-horizon formulation.

Part II. Baselines, Value Functions, and Advantage

4. Why can we subtract a baseline?

Reward-to-go still fluctuates because future outcomes are random. Introduce a state-dependent baseline $b(s_t)$:

$$g_t = \nabla_\theta \log \pi_\theta(a_t \mid s_t)\,[G_t - b(s_t)].$$

For a fixed state, the additional term has zero expectation:

$$\begin{aligned}
&\mathbb{E}_{a\sim\pi_\theta(\cdot|s)}[\nabla_\theta \log \pi_\theta(a \mid s) b(s)] \\
&= b(s) \int \pi_\theta(a \mid s) \nabla_\theta \log \pi_\theta(a \mid s)\, da \\
&= b(s) \int \nabla_\theta \pi_\theta(a \mid s)\, da \\
&= b(s) \nabla_\theta \int \pi_\theta(a \mid s)\, da \\
&= b(s) \nabla_\theta 1 = 0.
\end{aligned} \tag{7}$$

Therefore,

$$\boxed{\mathbb{E}[\nabla \log \pi_\theta \, G_t] = \mathbb{E}[\nabla \log \pi_\theta \, (G_t - b(s_t))]}. \tag{8}$$

Motivation. Remove a common, action-independent component of future return, leaving a more informative relative-action signal. Not every baseline necessarily reduces variance; the minimum-variance baseline can depend on the squared norm of the score gradient. Using $V^\pi(s)$ is a natural and highly practical choice.

5. Why use the value function as the baseline?

Define the state-value function, action-value function, and advantage function:

$$\begin{aligned} V^\pi(s) &= \mathbb{E}_\pi[G_t \mid s_t = s], \\ Q^\pi(s,a) &= \mathbb{E}_\pi[G_t \mid s_t = s, a_t = a], \\ \boxed{A^\pi(s,a)} &= \boxed{Q^\pi(s,a) - V^\pi(s)}. \end{aligned} \tag{9}$$

$V^\pi(s)$ measures expected return when continuing with the current policy. $Q^\pi(s,a)$ measures expected return when first taking action a, and then following the policy. Hence:

- $A^\pi(s,a) > 0$: action a performs better than the policy's average action at s; it should become more likely.
- $A^\pi(s,a) < 0$: the action is worse than average; it should become less likely.
- $A^\pi(s,a) = 0$: this estimate supplies no relative preference signal.

Robot grasping example. At a given grasping state, suppose $V^\pi(s) = 10$. Refining a finger contact has $Q = 15$ and advantage $+5$; maintaining the current posture has $Q = 10$ and advantage 0; prematurely closing the fingers has $Q = 3$ and advantage -7. Learning should reflect **relative quality**, not merely whether a reward is positive.

Using the exact value baseline yields the advantage policy-gradient formula:

$$\boxed{\nabla_\theta J(\theta) = \mathbb{E}\left[\sum_t \gamma^t \nabla_\theta \log \pi_\theta(a_t \mid s_t) A^{\pi_\theta}(s_t, a_t)\right]}. \tag{10}$$

This motivates the **actor–critic architecture**: the actor π_θ generates actions; the critic V_ϕ approximates state values; the advantage connects the two. An imperfect state-only baseline does not itself change the ideal score-function expectation, but bootstrapped advantage estimators constructed from an imperfect critic can be biased.

Part III. Performance Differences, Surrogate Objectives, and Importance Sampling

6. Why can't we reuse old data indefinitely?

The policy-gradient theorem describes expectations under the current policy. After data is collected with π_{θ_0} and the policy changes to π_{θ_1} or π_{θ_2}, the same rollout is still distributed according to π_{θ_0}, not the new policy. Recollecting trajectories after every optimizer step, however, is expensive.

One goal of PPO is to **perform several relatively safe first-order optimization steps on one batch of old-policy data**. Achieving this requires separating changes in the state distribution from changes in action probabilities at a given state.

7. Step-by-step proof of the performance difference lemma

Define the normalized discounted state-visitation distribution

$$\boxed{d_\pi(s) = (1-\gamma)\sum_{t=0}^{\infty} \gamma^t \Pr(s_t = s \mid \pi)}. \tag{11}$$

For continuous state spaces, this notation refers to the corresponding density or probability measure. For any new and old policies, the **performance difference lemma** gives the exact identity

$$\boxed{J(\pi_\theta) - J(\pi_{\text{old}}) = \frac{1}{1-\gamma}\mathbb{E}_{\substack{s\sim d_{\pi_\theta} \\ a\sim\pi_\theta}}[A^{\pi_{\text{old}}}(s,a)]}. \tag{12}$$

Proof. The Bellman equation for the old policy implies

$$A^{\pi_{\text{old}}}(s_t,a_t) = \mathbb{E}[r_t + \gamma V^{\pi_{\text{old}}}(s_{t+1}) - V^{\pi_{\text{old}}}(s_t) \mid s_t, a_t].$$

Sum the discounted advantages along a trajectory generated by the **new** policy:

$$\begin{aligned}
&\mathbb{E}_{\pi_\theta}\left[\sum_t \gamma^t A^{\pi_{\text{old}}}(s_t,a_t)\right] \\
&= \mathbb{E}_{\pi_\theta}\left[\sum_t \gamma^t r_t + \sum_t \gamma^{t+1} V^{\pi_{\text{old}}}(s_{t+1}) - \sum_t \gamma^t V^{\pi_{\text{old}}}(s_t)\right].
\end{aligned}$$

The last two sums telescope, leaving $-V^{\pi_{\text{old}}}(s_0)$ when the limiting tail vanishes. Thus

$$\mathbb{E}_{\pi_\theta}\left[\sum_t \gamma^t A^{\pi_{\text{old}}}(s_t,a_t)\right] = J(\pi_\theta) - J(\pi_{\text{old}}).$$

Re-expressing the discounted sum using the occupancy distribution gives Eq. (12).

Interpretation. A new policy improves performance when, in the states it *actually visits* and with the actions it *actually chooses*, it achieves positive advantage relative to the old policy.

8. Approximating true improvement by a surrogate objective

The challenge in Eq. (12) is the new-policy state distribution:

$$s \sim d_{\pi_\theta}.$$

We only possess trajectories from the old policy. If the policies remain close, we can make the **local approximation**

$$d_{\pi_\theta}(s) \approx d_{\pi_{\text{old}}}(s).$$

Ignoring the constant factor $1/(1-\gamma)$, define

$$\boxed{L_{\text{sur}}(\theta) = \mathbb{E}_{\substack{s\sim d_{\pi_{\text{old}}} \\ a\sim\pi_\theta}}[A^{\pi_{\text{old}}}(s,a)]}. \tag{13}$$

We have frozen the state distribution and need only reason about changes in action probabilities conditional on state. With exact advantages, this surrogate has the correct local first-order direction at the old policy (up to the discarded positive constant).

Crucial condition. The approximation is credible only while π_θ remains reasonably close to π_{old}. This is precisely the motivation behind trust regions and clipping.

9. Deriving the probability ratio by importance sampling

Equation (13) still takes actions from the new policy, whereas our stored actions were sampled by the old policy. Conditional on state s,

$$\begin{aligned}\mathbb{E}_{a\sim\pi_\theta}[A^{\pi_{\text{old}}}(s,a)] &= \int \pi_\theta(a \mid s) A^{\pi_{\text{old}}}(s,a)\, da \\ &= \int \pi_{\text{old}}(a \mid s) \frac{\pi_\theta(a \mid s)}{\pi_{\text{old}}(a \mid s)} A^{\pi_{\text{old}}}(s,a)\, da.\end{aligned}$$

Define the probability ratio

$$\boxed{r_\theta(s,a) = \frac{\pi_\theta(a \mid s)}{\pi_{\text{old}}(a \mid s)}}. \tag{14}$$

We arrive at a conservative-policy-iteration (CPI) surrogate:

$$\boxed{L^{\text{CPI}}(\theta) = \mathbb{E}_{\substack{s\sim d_{\pi_{\text{old}}} \\ a\sim\pi_{\text{old}}}}\left[r_\theta(s,a) A^{\pi_{\text{old}}}(s,a)\right]}. \tag{15}$$

In practice this is written $\mathbb{E}_t[r_t(\theta)\hat{A}_t]$.

For example, if the old policy assigns probability 0.2 to an action and the new policy assigns 0.3, then $r = 1.5$; a new probability of 0.1 gives $r = 0.5$. Positive advantage encourages a larger ratio; negative advantage encourages a smaller one.

Limits. This importance-sampling identity requires appropriate support / absolute continuity: an action receiving positive probability under the new policy cannot have zero probability under the old policy. Standard nondegenerate Gaussians typically satisfy this support condition. Importantly, the ratio corrects the **conditional action distribution**, not the discrepancy between d_{π_θ} and $d_{\pi_{\text{old}}}$. It therefore does not eliminate the state-distribution approximation in Eq. (13).

Part IV. TRPO: Controlling Policy Updates with a Trust Region

10. Why is unconstrained maximization of CPI dangerous?

For an action with positive advantage, $r_t\hat{A}_t$ increases as r_t grows. With $\hat{A} = 5$, ratios $1.2, 2, 10$ yield contributions $6, 10, 50$. It seems attractive to drive the probability of such an action arbitrarily high. But its advantage was estimated under the old policy, and may no longer predict performance after substantial policy changes.

A robot's changed action distribution can trigger a different contact mode, drop an object, or induce states almost absent from the old dataset. Hence increasing L^{CPI} does **not** guarantee an increase in actual return J.

11. KL divergence and the TRPO constraint

Measure changes between the action distributions at a fixed state using KL divergence:

$$D_{\mathrm{KL}}(\pi_{\mathrm{old}}\|\pi_\theta) = \mathbb{E}_{a\sim\pi_{\mathrm{old}}}\left[\log\frac{\pi_{\mathrm{old}}(a\mid s)}{\pi_\theta(a\mid s)}\right].$$

The practical TRPO optimization problem is

$$\boxed{\begin{aligned}&\max_\theta \quad \mathbb{E}_t[r_t(\theta)\hat{A}_t]\\ &\text{s.t.} \quad \mathbb{E}_{s\sim d_{\pi_{\mathrm{old}}}}[D_{\mathrm{KL}}(\pi_{\mathrm{old}}(\cdot\mid s)\|\pi_\theta(\cdot\mid s))]\le\delta.\end{aligned}} \tag{16}$$

The parameter δ controls the trust-region size. The motivation is not "always make the smallest change"; rather, **seek improvements inside a local region where the performance surrogate is comparatively reliable**.

The TRPO analysis yields performance bounds that penalize the worst-state policy discrepancy; a representative structural form is

$$J(\pi_\theta)\ge J(\pi_{\mathrm{old}})+\frac{L_{\mathrm{sur}}(\theta)}{1-\gamma}-C\max_s D_{\mathrm{KL}}(\pi_{\mathrm{old}}\|\pi_\theta). \tag{17}$$

Here C depends on bounds on advantages / returns and on γ; precise constants and KL orientation depend on the chosen inequality. The theoretical control of a **worst-state** discrepancy is stronger than the **average KL** constraint commonly implemented. Actual neural-network TRPO therefore has no unconditional monotonic-improvement guarantee.

12. TRPO's local second-order approximation and natural gradient

Write $\Delta\theta=\theta-\theta_{\mathrm{old}}$. Taylor-expand the surrogate:

$$L^{\mathrm{CPI}}(\theta)\approx L^{\mathrm{CPI}}(\theta_{\mathrm{old}})+g^\top\Delta\theta,\quad g=\nabla_\theta L^{\mathrm{CPI}}\big|_{\theta_{\mathrm{old}}}.$$

KL divergence is zero, and has zero first derivative, at identical distributions. Its second-order expansion is

$$\bar{D}_{\mathrm{KL}}\approx\tfrac{1}{2}\Delta\theta^\top F\Delta\theta,$$

where F is the Fisher information matrix evaluated at the old parameters. To make the evaluation point unambiguous, define $u_{\mathrm{old}}(s,a)=\nabla_\theta\log\pi_\theta(a\mid s)|_{\theta=\theta_{\mathrm{old}}}$. Then

$$F=\mathbb{E}_{s\sim d_{\pi_{\mathrm{old}}},\,a\sim\pi_{\mathrm{old}}}[u_{\mathrm{old}}(s,a)u_{\mathrm{old}}(s,a)^\top].$$

The local approximation is

$$\boxed{\max_{\Delta\theta} g^\top\Delta\theta\quad\text{s.t.}\quad\tfrac{1}{2}\Delta\theta^\top F\Delta\theta\le\delta.} \tag{18}$$

Its Lagrangian is

$$\mathcal{L}(\Delta\theta,\eta)=g^\top\Delta\theta-\eta\big(\tfrac{1}{2}\Delta\theta^\top F\Delta\theta-\delta\big).$$

Stationarity $g-\eta F\Delta\theta=0$ yields $\Delta\theta=\eta^{-1}F^{-1}g$. Enforcing the active constraint, assuming F positive definite and $g\neq0$, gives

$$\boxed{\Delta\theta^* = \sqrt{\frac{2\delta}{g^\top F^{-1} g}} F^{-1} g}. \tag{19}$$

The direction $F^{-1}g$ is the hallmark of **natural policy gradient**. A large policy network cannot directly invert its Fisher matrix, so TRPO relies on Fisher-vector products, conjugate gradients, line search, and often damping. **PPO's design motivation** is to retain conservative policy improvement while dispensing with this complicated second-order constrained optimization.

Part V. Deriving the PPO-Clipped Objective

13. From a KL penalty to a clipped surrogate

A straightforward first-order alternative is PPO-Penalty:

$$L^{\mathrm{KLPEN}}(\theta) = \mathbb{E}_t[r_t(\theta)\hat{A}_t] - \beta\,\mathbb{E}_t[D_{\mathrm{KL}}(\pi_{\mathrm{old}} \| \pi_\theta)]. \tag{20}$$

A small β may under-regularize updates, while a large β can make learning unnecessarily slow; adaptive tuning is commonly needed. PPO-Clip instead restricts the **additional surrogate gain** obtained from overly large changes in action probability. Define

$$\mathrm{clip}(r, 1-\epsilon, 1+\epsilon) = \min\{1+\epsilon, \max\{r, 1-\epsilon\}\}.$$

The familiar PPO objective is

$$\boxed{L^{\mathrm{CLIP}}(\theta) = \mathbb{E}_t\Big[\min\Big(r_t(\theta)\hat{A}_t, \mathrm{clip}(r_t(\theta), 1-\epsilon, 1+\epsilon)\hat{A}_t\Big)\Big]}. \tag{21}$$

Values around $\epsilon = 0.1$–0.2 are common starting points, not universal prescriptions. The key is to understand **why the `min` and `clip` operations must be used together**.

14. Positive advantage: stop rewarding overly large probability increases

If $\hat{A}_t > 0$, we want the probability of this action to increase, hence $r_t > 1$ is beneficial. Equation (21) reduces to

$$\boxed{L_t^{\mathrm{CLIP}} = \min(r_t, 1+\epsilon)\hat{A}_t = \begin{cases} r_t\hat{A}_t, & r_t \le 1+\epsilon, \\ (1+\epsilon)\hat{A}_t, & r_t > 1+\epsilon. \end{cases}} \tag{22}$$

Set $\hat{A}_t = 2$ and $\epsilon = 0.2$:

Ratio r_t	Unclipped $r_t\hat{A}_t$	PPO contribution
0.8	1.6	1.6
1.0	2.0	2.0
1.1	2.2	2.2
1.2	2.4	2.4
1.5	3.0	2.4

Ratio r_t	Unclipped $r_t\hat{A}_t$	PPO contribution
2.0	4.0	2.4

Once $r_t > 1.2$, that sample no longer rewards further increases in its probability; its derivative in that direction is zero. **Motivation:** Avoid excessively reinforcing a sample that appears advantageous under the old policy.

15. Negative advantage: stop rewarding overly large probability decreases

For $\hat{A}_t < 0$, reducing the action probability is beneficial. Multiplying by a negative advantage reverses the min/max relationship:

$$\boxed{L_t^{\text{CLIP}} = \max(r_t, 1-\epsilon)\hat{A}_t = \begin{cases} (1-\epsilon)\hat{A}_t, & r_t < 1-\epsilon, \\ r_t\hat{A}_t, & r_t \geq 1-\epsilon. \end{cases}} \tag{23}$$

With $\hat{A}_t = -2$ and $\epsilon = 0.2$:

Ratio r_t	Unclipped $r_t\hat{A}_t$	PPO contribution
0.5	-1.0	-1.6
0.7	-1.4	-1.6
0.8	-1.6	-1.6
1.0	-2.0	-2.0
1.2	-2.4	-2.4
1.5	-3.0	-3.0

PPO maximizes this objective, so reducing r_t is helpful for a negative-advantage sample. Once $r_t < 0.8$, however, further probability decreases produce no additional surrogate reward.

16. Why do we need `min` instead of clipping alone?

Suppose we optimized only $\text{clip}(r, 1-\epsilon, 1+\epsilon)\hat{A}$. If $\hat{A} > 0$, $r = 0.5$, and $\epsilon = 0.2$, then a good action has already been made much less likely—an **unfavorable** change. Clipping alone returns $0.8\hat{A}$ and gives zero derivative everywhere below $r = 0.8$, providing no correction signal.

With `min`, the selected term is instead $r\hat{A}$, because $r\hat{A} < 0.8\hat{A}$. The positive derivative persists and pushes the action probability back up. The symmetric argument applies to unfavorable probability increases for negative-advantage actions.

Direction beneficial but change excessive:	stop extra surrogate reward;
Direction unfavorable for the advantage:	retain corrective gradient.

Since $\min(x, y) \leq x$, the sample-wise bound $L^{\text{CLIP}} \leq L^{\text{CPI}}$ holds. This is a pessimistic **lower bound on the unclipped surrogate, not a guaranteed lower bound on the true return** J.

17. Gradient-level interpretation of clipping

Because the denominator in the probability ratio is fixed while optimizing the current rollout,

$$\boxed{\nabla_\theta r_t(\theta) = r_t(\theta)\nabla_\theta \log \pi_\theta(a_t \mid s_t)}. \tag{24}$$

Away from nonsmooth boundaries, the single-sample gradient is

$$\boxed{\nabla_\theta L_t^{\mathrm{CLIP}} = \begin{cases} 0, & \hat{A}_t > 0,\ r_t > 1+\epsilon, \\ 0, & \hat{A}_t < 0,\ r_t < 1-\epsilon, \\ \hat{A}_t r_t \nabla_\theta \log \pi_\theta(a_t \mid s_t), & \text{otherwise.} \end{cases}} \tag{25}$$

At $\theta = \theta_{\mathrm{old}}$, all ratios equal one. The initial local gradient therefore agrees with CPI / advantage policy gradient (up to the chosen normalization). **PPO does not change the initial improvement direction; it moderates the gain from further changes as repeated updates move the probability ratios away from one.**

18. PPO does not enforce a hard ratio or KL constraint

Choosing $\epsilon = 0.2$ does **not** ensure $0.8 \le r_t \le 1.2$ after an optimizer step. Clipping changes an objective, not the feasible parameter set. Parameters are shared across states and samples, and several mini-batch epochs can still drive the average KL too high.

Practical PPO systems therefore monitor

$$\bar{D}_{\mathrm{KL}}(\pi_{\mathrm{old}} \| \pi_\theta)$$

and often use target-KL early stopping, learning-rate adaptation, and/or gradient clipping. Distinguish three separate operations: **ratio clipping** limits surrogate incentives, **gradient clipping** limits gradient norms, and **action clipping** limits executed command values.

Part VI. GAE: How Do We Estimate the Advantage?

19. Monte Carlo advantage: motivation and cost

The $\hat{A}_t$ used by PPO is not directly observed. By definition $A^\pi = Q^\pi - V^\pi$. The simplest estimate substitutes the sampled reward-to-go for the action value:

$$\boxed{\hat{A}_t^{\mathrm{MC}} = G_t - V_\phi(s_t)}, \qquad G_t = \sum_{l=0}^{T-t-1} \gamma^l r_{t+l}. \tag{26}$$

For a properly completed episode, the conditional expectation of the sampled return G_t equals $Q^\pi(s_t, a_t)$. No value-function bootstrap of distant future outcomes is needed. However, imagine a grasping task where success is rewarded only at time 100. Whether an action at time 10 receives a large Monte Carlo return depends on many subsequent random events; the gradient estimate may therefore have high variance.

Question: Could we estimate advantage with shorter segments of experience instead of depending on the entire future trajectory?

20. One-step TD advantage from the Bellman equation

The Bellman identity reads

$$Q^\pi(s_t, a_t) = \mathbb{E}[r_t + \gamma V^\pi(s_{t+1}) \mid s_t, a_t].$$

Consequently, the one-step temporal-difference (TD) residual

$$\boxed{\delta_t = r_t + \gamma V_\phi(s_{t+1}) - V_\phi(s_t)} \tag{27}$$

is a candidate advantage estimator:

$$\boxed{\hat{A}_t^{(1)} = \delta_t}. \tag{28}$$

It needs just one transition s_t, a_t, r_t, s_{t+1}. Replacing random distant rewards by $V_\phi(s_{t+1})$ often reduces variance, but introduces bootstrap bias if the critic is inaccurate. At a true terminal state the future value is zero; at an artificial time cutoff it is usually appropriate to bootstrap.

Estimator	Main benefit	Main limitation
Monte Carlo	Less bias from bootstrapping future values	High variance from uncertain long-term returns
One-step TD	Lower variance and immediate feedback	Greater dependence on critic accuracy

21. Deriving n-step advantage estimates

The one-step estimate is

$$\hat{A}_t^{(1)} = r_t + \gamma V(s_{t+1}) - V(s_t) = \delta_t.$$

The two-step estimate is

$$\begin{aligned} \hat{A}_t^{(2)} &= r_t + \gamma r_{t+1} + \gamma^2 V(s_{t+2}) - V(s_t) \\ &= [r_t + \gamma V(s_{t+1}) - V(s_t)] \\ &\quad + \gamma[r_{t+1} + \gamma V(s_{t+2}) - V(s_{t+1})] \\ &= \boxed{\delta_t + \gamma \delta_{t+1}}. \end{aligned} \tag{29}$$

Similarly, the three-step estimate is

$$\hat{A}_t^{(3)} = \delta_t + \gamma \delta_{t+1} + \gamma^2 \delta_{t+2}.$$

For a general horizon n,

$$\boxed{\hat{A}_t^{(n)} = \sum_{l=0}^{n-1} \gamma^l \delta_{t+l}}. \tag{30}$$

Small n emphasizes value bootstrapping; large n uses more observed future rewards. **GAE's motivation:** Rather than choosing one n, smoothly aggregate many n-step estimators.

22. Exponential weighting and the GAE derivation

Let $0 \leq \lambda < 1$. Define

$$\boxed{\hat{A}_t^{\mathrm{GAE}(\gamma,\lambda)} = (1-\lambda)\sum_{n=1}^{\infty}\lambda^{n-1}\hat{A}_t^{(n)}}. \tag{31}$$

The weights sum to one: $(1-\lambda)\sum_{n\geq 1}\lambda^{n-1} = 1$. Substitute the n-step expansion and exchange the summation order:

$$\begin{aligned}\hat{A}_t^{\mathrm{GAE}} &= (1-\lambda)\sum_{n=1}^{\infty}\lambda^{n-1}\sum_{l=0}^{n-1}\gamma^l\delta_{t+l} \\ &= \sum_{l=0}^{\infty}\gamma^l\delta_{t+l}(1-\lambda)\sum_{n=l+1}^{\infty}\lambda^{n-1} \\ &= \sum_{l=0}^{\infty}\gamma^l\delta_{t+l}\lambda^l.\end{aligned}$$

Therefore,

$$\boxed{\hat{A}_t^{\mathrm{GAE}(\gamma,\lambda)} = \sum_{l=0}^{\infty}(\gamma\lambda)^l\delta_{t+l}}. \tag{32}$$

Equivalently,

$$\hat{A}_t = \delta_t + \gamma\lambda\delta_{t+1} + (\gamma\lambda)^2\delta_{t+2} + \cdots.$$

Two endpoints. With $\lambda = 0$, GAE becomes one-step TD: $\hat{A}_t = \delta_t$. As $\lambda \to 1$, GAE incorporates all later TD residuals; for a complete terminating episode, setting $\lambda = 1$ gives $G_t - V(s_t)$. Common initial choices are $\gamma = 0.99$ and $\lambda = 0.95$.

GAE does not mathematically guarantee lower variance in every problem. It introduces a tunable **bias–variance tradeoff**: smaller λ generally relies more on the critic, while larger λ generally relies more on sampled distant rewards.

23. The $O(T)$ backward recursion for GAE

Equation (32) implies

$$\boxed{\hat{A}_t = \delta_t + \gamma\lambda\hat{A}_{t+1}}. \tag{33}$$

Let $d_t = 1$ indicate a genuine MDP terminal transition. Then

$$\boxed{\begin{aligned}&\delta_t = r_t + \gamma(1-d_t)V_\phi(s_{t+1}) - V_\phi(s_t), \\ &\hat{A}_t = \delta_t + \gamma\lambda(1-d_t)\hat{A}_{t+1}.\end{aligned}} \tag{34}$$

A single backward pass from $T-1$ computes all advantages in $O(T)$ time. If a fixed-length rollout stops without the MDP actually terminating, bootstrap from $V(s_T)$. But a recursion must not accidentally propagate the next episode's advantage across a reset. Implementations must distinguish **terminated** (genuine terminal), **truncated** (external time limit), and **rollout boundary** (a sampling segment boundary).

24. Constructing critic targets from GAE

GAE estimates

$$\hat{A}_t \approx Q^{\pi_{\text{old}}}(s_t, a_t) - V_{\text{old}}(s_t).$$

Define the TD(λ) return target by

$$\boxed{\hat{R}_t^{\lambda} = \hat{A}_t^{\text{GAE}} + V_{\phi_{\text{old}}}(s_t)}. \tag{35}$$

$V_{\phi_{\text{old}}}$ denotes the critic values saved when targets for the rollout were calculated. Hold these values fixed during the PPO epochs. The construction aligns the actor's advantage estimates with the critic's regression target.

Part VII. The Complete Actor–Critic Loss

25. Actor loss

First calculate and freeze $\hat{A}_t$ for the old-policy rollout; advantage normalization is also common. The actor maximizes

$$L^{\text{CLIP}}(\theta) = \mathbb{E}_t \left[\min \left(r_t \hat{A}_t, \text{clip}(r_t, 1-\epsilon, 1+\epsilon) \hat{A}_t \right) \right].$$

For gradient-descent software such as PyTorch, minimize

$$\boxed{\mathcal{L}_{\text{actor}} = -L^{\text{CLIP}}}. \tag{36}$$

If the advantage estimates were produced by a differentiable critic currently inside the computational graph, detach them from the actor objective to avoid unintentionally backpropagating through the advantage targets.

26. Critic loss

Train the critic to regress the TD(λ) return:

$$\boxed{\mathcal{L}_{\text{critic}}(\phi) = \mathbb{E}_t[(V_\phi(s_t) - \hat{R}_t^{\lambda})^2]}. \tag{37}$$

Direct Monte Carlo return targets are another option. Some PPO implementations use value-function clipping or multiply the squared error by $1/2$; neither is essential to the basic PPO-Clip objective. An inaccurate critic can corrupt the sign or magnitude of advantages, so policy-update stability depends strongly on value estimation quality.

27. Motivation for the entropy bonus

A stochastic policy may become too concentrated early, ceasing to explore alternative grasps. Use the policy entropy

$$\boxed{H(\pi_\theta(\cdot \mid s)) = -\mathbb{E}_{a \sim \pi_\theta}[\log \pi_\theta(a \mid s)]}. \tag{38}$$

to encourage sufficient exploration. Let $L^{\text{entropy}} = \mathbb{E}_t[H(\pi_\theta(\cdot \mid s_t))]$. Higher entropy is not always preferable, particularly near robot deployment. The entropy coefficient may be zero or annealed during training.

28. Final PPO training objective

A common joint maximization objective combines all three terms:

$$\boxed{L^{\mathrm{PPO}}(\theta,\phi)=L^{\mathrm{CLIP}}(\theta)-c_v\mathcal{L}_{\mathrm{critic}}(\phi)+c_eL^{\mathrm{entropy}}(\theta)}. \tag{39}$$

Equivalently, minimize

$$\boxed{\mathcal{L}_{\mathrm{total}}=-L^{\mathrm{CLIP}}+c_v\mathcal{L}_{\mathrm{critic}}-c_eL^{\mathrm{entropy}}}. \tag{40}$$

- c_v determines the relative weight of value regression.
- c_e determines the strength of entropy regularization.
- With separate actor and critic parameters, the two networks can have separate updates; with shared parameters, their gradients interact.

A PPO optimization phase typically uses several mini-batch epochs over a fixed rollout, keeping the stored old log probabilities, advantages, and return targets constant during that phase.

Part VIII. Continuous-Action PPO and Robot Control

29. Gaussian policy log probabilities and importance ratios

Robot actions are often continuous vectors: joint position increments, desired velocities, or torques. A typical actor uses a diagonal Gaussian

$$\boxed{\pi_\theta(a\mid s)=\mathcal{N}(\mu_\theta(s),\mathrm{diag}(\sigma_1^2,\dots,\sigma_n^2))}. \tag{41}$$

The joint log probability of an action vector is

$$\boxed{\log\pi_\theta(a\mid s)=-\frac{1}{2}\sum_{i=1}^{n}\left[\frac{(a_i-\mu_i)^2}{\sigma_i^2}+2\log\sigma_i+\log(2\pi)\right]}. \tag{42}$$

The numerically convenient ratio is

$$\boxed{r_t=\exp\left(\log\pi_\theta(a_t\mid s_t)-\log\pi_{\mathrm{old}}(a_t\mid s_t)\right)}. \tag{43}$$

Implementation detail. Sum per-dimension log probabilities to obtain the **joint** action log probability *before* exponentiation. Clipping ratios separately for each action dimension is not standard PPO for a joint policy. A tanh-squashed Gaussian requires the appropriate change-of-variables correction to its log density. If an environment directly hard-clips sampled actions, carefully distinguish the density of the sampled action from that of the executed command.

30. How does a Gaussian-policy gradient move the action mean?

Consider a one-dimensional Gaussian with fixed variance:

$$a\sim\mathcal{N}(\mu_\theta(s),\sigma^2).$$

Differentiating its log density with respect to the mean gives

$$\boxed{\frac{\partial \log \pi_\theta(a \mid s)}{\partial \mu_\theta} = \frac{a - \mu_\theta(s)}{\sigma^2}}. \tag{44}$$

The mean-related component of the unclipped policy gradient is therefore

$$\boxed{\nabla_\theta J \propto \mathbb{E}\left[\hat{A}\frac{a - \mu_\theta(s)}{\sigma^2}\nabla_\theta \mu_\theta(s)\right]}. \tag{45}$$

For $\hat{A} > 0$, this tends to move the mean toward the sampled action; for $\hat{A} < 0$, it tends to move the mean away. PPO clipping limits further *surrogate benefit* from excessive probability changes. If σ is learned, there are additional gradient terms associated with variance.

31. Example: residual PPO for robot manipulation

Suppose a baseline controller produces

$$a_t^{\text{base}} = \pi_{\text{base}}(s_t),$$

while PPO learns a stochastic residual

$$\Delta a_t \sim \pi_\theta(\cdot \mid s_t).$$

The executed command is

$$\boxed{a_t = a_t^{\text{base}} + \Delta a_t}. \tag{46}$$

The residual may adjust joint targets, velocities, end-effector pose, or finger closing actions. In a screwdriver grasp-and-rotation task, a base trajectory provides the broad motion while PPO residual actions compensate for contact-location errors, initial-pose perturbations, changes in friction, and slippage.

The ratio must correspond to the **residual action distribution**:

$$r_t = \frac{\pi_\theta(\Delta a_t \mid s_t)}{\pi_{\text{old}}(\Delta a_t \mid s_t)}.$$

When residuals are scaled, transformed nonlinearly, or filtered through a safety controller, clearly distinguish which variables have the log density used for learning and which commands are actually executed. PPO does not require differentiable contact dynamics, but does require adequate rollouts, rewards, and state/value estimation.

Part IX. A Complete PPO Iteration

32. Ten steps from rollout collection to policy updates

1. **Freeze the old policy.** Set $\pi_{\text{old}} = \pi_{\theta_k}$ and sample several episodes or fixed-length rollouts.
2. **Store rollout data.** Record (s_t, a_t, r_t, s_{t+1}), termination flags, $\log \pi_{\text{old}}(a_t \mid s_t)$, and $V_{\text{old}}(s_t)$.
3. **Compute TD errors.** Use $\delta_t = r_t + \gamma V_{\text{old}}(s_{t+1}) - V_{\text{old}}(s_t)$ with proper true-terminal masking.
4. **Calculate GAE backward.** Use $\hat{A}_t = \delta_t + \gamma\lambda\hat{A}_{t+1}$ and prevent recursion across unrelated episodes.

5. **Compute critic targets.** Set $\hat{R}_t^{\lambda} = \hat{A}_t + V_{\text{old}}(s_t)$ and hold the targets fixed.
6. **Optionally normalize advantages.** Use $\tilde{A}_t = (\hat{A}_t - \mu_A)/(\sigma_A + \varepsilon_{\text{num}})$.
7. **Evaluate current log probabilities on stored actions.** For the **original actions** a_t sampled by the old policy, compute current $\log \pi_\theta(a_t \mid s_t)$.
8. **Compute ratios and clipped actor loss.** Use $r_t = \exp(\log \pi_\theta - \log \pi_{\text{old}})$ and Eq. (21).
9. **Optimize actor and critic.** Minimize the joint objective or separate losses for multiple epochs, monitoring KL, clip fraction, and value prediction.
10. **Collect new on-policy data.** Use the updated policy for the next rollout rather than treating arbitrarily old replay data as ordinary PPO training data.

33. Compact, adaptable PyTorch implementations

The following function implements the central PPO actor loss. Both `new_log_prob` and `old_log_prob` must contain **joint** action log probabilities, and the old log probabilities and advantages must remain fixed within the update phase.

```
import torch


def ppo_actor_loss(new_log_prob, old_log_prob,
                   advantages, clip_eps=0.2):
    # The old log probability and advantage are fixed rollout data.
    old_log_prob = old_log_prob.detach()
    advantages = advantages.detach()

    log_ratio = new_log_prob - old_log_prob
    ratio = torch.exp(log_ratio)

    objective_unclipped = ratio * advantages
    objective_clipped = torch.clamp(
        ratio, 1.0 - clip_eps, 1.0 + clip_eps
    ) * advantages

    return -torch.minimum(
        objective_unclipped, objective_clipped
    ).mean()
```

A minimal backward GAE calculation is shown next. The `bootstrap_mask[t]` determines whether a subsequent-state value is included in the TD target. The `continue_mask[t]` determines whether the advantage recursion is allowed to cross the current transition. Correct handling of true terminations, timeouts, and rollout boundaries must come from the environment and rollout buffer.

```
import torch


def compute_gae(rewards, values, next_values,
                bootstrap_mask, continue_mask,
                gamma=0.99, lam=0.95):
    """All tensors are indexed by rollout time."""
    T = rewards.shape[0]
    advantages = torch.zeros_like(rewards)
    running = torch.zeros_like(rewards[0])

    for t in reversed(range(T)):
        delta = (rewards[t]
                 + gamma * bootstrap_mask[t] * next_values[t]
```

```
                - values[t])
        running = (delta
                   + gamma * lam * continue_mask[t] * running)
        advantages[t] = running

    returns = advantages + values
    return advantages, returns
```

For parallel simulation, tensors can have shape `[T, N_env]`; never propagate `continue_mask` across an episode reset. The `values` and `next_values` used in return targets should come from the fixed rollout-time critic.

For a diagonal Gaussian policy:

```
# dist: torch.distributions.Normal, action shape [batch, action_dim]
new_log_prob = dist.log_prob(actions).sum(dim=-1)
# entropy shape [batch]
entropy = dist.entropy().sum(dim=-1)
```

These examples implement the essential formulas; a complete training program still needs a rollout buffer, environment interaction, network definitions, optimizers, correct `terminated/truncated` handling, and metric logging.

Part X. Hyperparameters and Diagnostics

34. Common starting hyperparameters and what they mean

Hyperparameter	Common starting point	Main role
Discount γ	0.99	Weight assigned to distant rewards
GAE λ	0.95	Advantage-estimator bias–variance tradeoff
Clip ϵ	0.1–0.2	Extra surrogate gains from overly large probability ratios
Actor learning rate	3×10^{-4}	Actor update speed
PPO epochs	3–10	Number of optimization passes over one rollout
Target KL	0.01–0.03	Threshold for early stopping of actor updates
Entropy coefficient	0 or small positive	Amount of exploration encouragement
Value-loss weight	About 0.5	Relative weight of critic regression

These are experimental starting points, not universal optima. Large-scale parallel locomotion frameworks such as RSL-RL may use quite different learning rates, batch sizes, clipping ranges, and numbers of epochs.

The distinction between γ and λ: The discount factor γ defines how the learning objective values distant rewards; λ determines how much an advantage estimator incorporates distant sampled TD information. Both appear through $(\gamma\lambda)^l$ in GAE, but their conceptual roles are different.

Useful diagnostics include episode return, task success rate, value loss, explained variance, policy entropy, approximate KL, clip fraction, and gradient norm. If a surrogate improves while actual robot success decreases, investigate distribution shift, critic error, excessive KL, and reward design.

Part XI. Connections to REINFORCE, Actor–Critic, and TRPO

35. Algorithmic progression: one design choice per problem

Algorithm	Core expression / idea	Problem addressed
REINFORCE	$\nabla \log \pi_\theta \, G$	Learn a policy without environment derivatives
Advantage actor–critic	$\nabla \log \pi_\theta \, \hat{A}$	Reduce variance using a state-value baseline
TRPO	Maximize $\mathbb{E}[r\hat{A}]$ subject to KL	Keep the surrogate useful in a local trust region
PPO-Clip	$\min(r\hat{A}, \text{clip}(r)\hat{A})$	Discourage excessive probability changes with first-order optimization
PPO with GAE	$\hat{A}_t = \sum_l (\gamma\lambda)^l \delta_{t+l}$	Control the bias–variance tradeoff of advantage estimates

PPO fundamentally remains an **on-policy policy-gradient / actor–critic algorithm**. At the beginning of each rollout update, the clipped and unclipped surrogate objectives have the same first-order gradient. Their difference arises as several optimization steps on the same dataset cause probability ratios to move away from one.

PPO is especially practical for simulated robotic control because large numbers of environments can be sampled in parallel, optimization is relatively simple, differentiable dynamics are unnecessary, and Gaussian policies naturally model continuous actions. On a physical robot, however, collecting interactions is expensive, so off-policy methods such as SAC may offer important sample-efficiency advantages. Diffusion and flow-matching action policies often lack the conveniently computable explicit log probabilities required by standard PPO, motivating specialized modifications.

Part XII. Final Formula Sheet and Research Takeaways

Formula 1: Policy gradient

$$\nabla_\theta J \propto \mathbb{E}\left[\nabla_\theta \log \pi_\theta(a \mid s) A^\pi(s,a)\right].$$

Motivation: Optimize without backpropagating through possibly nondifferentiable physical dynamics.

Formula 2: Importance sampling

$$r_t = \pi_\theta(a_t \mid s_t) / \pi_{\text{old}}(a_t \mid s_t).$$

Motivation: Construct a local new-policy surrogate from actions sampled by the old policy.

Formula 3: TRPO's trust-region idea

$$\bar{D}_{\mathrm{KL}}(\pi_{\mathrm{old}} \| \pi_\theta) \leq \delta.$$

Motivation: Control the risk that the surrogate becomes misleading under distribution shift.

Formula 4: PPO clipped surrogate

$$\boxed{L^{\mathrm{CLIP}} = \mathbb{E}_t \left[\min \left(r_t \hat{A}_t, \mathrm{clip}(r_t, 1-\epsilon, 1+\epsilon) \hat{A}_t \right) \right]}.$$

Motivation: Conservatively cap surrogate incentives for excessive favorable changes while retaining corrective gradients for unfavorable changes.

Formula 5: Generalized advantage estimation

$$\boxed{\hat{A}_t = \sum_{l \geq 0} (\gamma\lambda)^l \delta_{t+l}}, \qquad \delta_t = r_t^{\mathrm{reward}} + \gamma V(s_{t+1}) - V(s_t).$$

Motivation: Smoothly trade off reliance on long-term sampled rewards against reliance on short-horizon value bootstrapping. Here r_t^{reward} distinguishes the immediate reward from PPO's probability ratio $r_t(\theta)$.

Final loss to minimize:

$$\boxed{\mathcal{L}_{\mathrm{PPO}} = -L^{\mathrm{CLIP}} + c_v \mathcal{L}_{\mathrm{critic}} - c_e L^{\mathrm{entropy}}}.$$

> **Main research insight.** PPO is not a new method for differentiating environments. It uses policy gradients to identify local directions of improvement, importance sampling to construct a surrogate from stored actions, clipping to discourage over-optimization, and GAE to improve advantage estimation. **GAE principally addresses estimator quality; clipping principally addresses policy-update stability.** The two components solve different yet complementary problems.

References and further reading

1. Schulman, J., et al. (2017). *Proximal Policy Optimization Algorithms*. arXiv:1707.06347. https://arxiv.org/abs/1707.06347
2. Schulman, J., et al. (2015). *Trust Region Policy Optimization*. ICML. https://arxiv.org/abs/1502.05477
3. Schulman, J., et al. (2015). *High-Dimensional Continuous Control Using Generalized Advantage Estimation*. ICLR 2016. https://arxiv.org/abs/1506.02438
4. OpenAI Spinning Up. *PPO Documentation*. https://spinningup.openai.com/en/latest/algorithms/ppo.html

---

Editorial note: This document expands the preceding PPO derivation with explicit support assumptions for importance sampling, precise discounted occupancy notation, the fact that PPO-Clip does not impose a hard constraint, and the difference between true episode termination and rollout truncation.