Reinforcement Learning Post-Training for Embodied Foundation Models

Technical Tutorial

2026-10-19

Contents

1. Starting from a pretrained generative robot policy . . . 2
2. First ask: which part of the policy is updated? . . . 4
3. Three independent decisions . . . 4
4. Route I: updating the pretrained generator . . . 5
5. Route II: freezing the generator and learning a small module . . . 5
6. The actor–critic and online off-policy loop . . . 6
7. Choosing a post-training route . . . 7
8. Evaluation: benchmark performance is not deployability . . . 8
9. RLinf: from reusable RL infrastructure to physical deployment . . . 8
10. Open research questions at the learning–systems boundary . . . 11
11. Primary literature and official resources . . . 11

Course repository ·中文 Markdown ·RLinf documentation

Item	Details
Topic	RL Post-training
Revision	2026-10-19
License	CC BY 4.0 ·Xiong Zeng and contributors

1. Starting from a pretrained generative robot policy

Algorithms, RLinf Infrastructure, and the Boundaries of Real-Robot Deployment ·October 2026

> **Scope.** This tutorial studies RL improvement of **pretrained** Diffusion Policies, Flow Matching policies, and vision-language-action (VLA) models. The narrative follows **trainable interfaces → algorithms and experience → infrastructure → physical deployment**. PPO, SAC, and actor–critic appear only where needed. Training low-level controllers from scratch and executable tutorials are out of scope.
>
> **Evidence boundary (as of 19 October 2026).** We distinguish *documented system recipes*, *integration requirements inferred from those recipes*, and *unsolved research questions*. Support for model A, algorithm B, and robot C individually is **not evidence that A × B × C works as a validated combination**. No independent reproduction or real-robot verification is claimed.
>
> **Attribution.** Adapted from the Foundation of Embodied AI teaching materials by Xiong Zeng and contributors (CC BY 4.0). Papers and third-party projects retain their original licenses.

Imitation learning establishes initial manipulation competence. RL post-training then exploits interaction and reward to improve task completion, precision, robustness, failure recovery, and efficiency. The object being optimized is an existing policy—not a controller initialized from scratch.




Figure 1. RL post-training starts with a pretrained model. Training reward cannot replace independent evaluation or runtime safety.

Let o_t be the observation, g_t a task goal or language instruction, and A_t a generated action chunk:

$$\pi_{\theta_0}(A_t \mid o_t, g_t), \qquad A_t = (a_t, \dots, a_{t+H-1}),$$

where θ_0 is the pretrained parameter set and H the generated action horizon. Diffusion and Flow policies may sample continuous actions iteratively; a VLA may also contain a vision-language backbone, a separate Action Expert, and additional output heads. The canonical return objective is

$$J(\pi) = \mathbb{E}_{\tau\sim\pi}\left[\sum_{t=0}^{T}\gamma^t r_t\right].$$

Post-training must also preserve useful pretrained competencies. Crucially, **the exact** $\log \pi(A \mid o, g)$ **or KL divergence of an implicit generative policy cannot generally be assumed available**. Standard PPO/SAC therefore cannot be applied to

every generative action head without an appropriate policy interface.

2. First ask: which part of the policy is updated?

Two routes organize the methods: **update the pretrained generator / Action Expert**, or **freeze it and learn a separate adapter**. The boundary is not absolute; LoRA, partial fine-tuning, and hybrid residual approaches can combine the routes.




Figure 2. The branches describe distinct trainable interfaces, not sequential stages of training.

Full versus LoRA fine-tuning describes the **parameter scope**; velocity matching versus policy gradients describes the **learning objective**; on-policy versus off-policy describes the **relationship between the behavior data and policy updates**. These should not be collapsed into one mutually exclusive taxonomy.

3. Three independent decisions

Axis	Essential question	Representative choices
Pretrained model	Which existing policy is being adapted?	Diffusion, Flow Matching, VLA with Action Expert
Trainable interface	Which parameters receive RL signals?	Generator, LoRA, noise actor, action residual, feature actor
Experience and optimizer	Does new interaction continue, and can old data be replayed?	Online / offline; on-policy / off-policy; replay buffer

Online is not synonymous with on-policy. Online denotes a training process in which new interaction is continuously collected; off-policy permits the reuse of experience from older behavior policies. A real-robot learner that continually gathers trajectories and trains an SAC-style critic from a replay buffer is performing **online off-policy RL**. PPO is conventionally on-policy and SAC off-policy, but generative-policy methods need algorithm-specific modifications.

4. Route I: updating the pretrained generator

4.1 DPPO: diffusion-process policy gradients

DPPO incorporates the denoising process of a Diffusion Policy into RL optimization. It does not simply treat the resulting chunk distribution as an ordinary Gaussian actor with an immediately tractable log-probability. The familiar PPO clipped surrogate is

$$L_{\text{clip}} = \mathbb{E}\left[\min\left(\rho\hat{A},\ \text{clip}(\rho, 1-\epsilon, 1+\epsilon)\hat{A}\right)\right].$$

This is **not the complete DPPO objective**. Main costs include on-policy rollouts, multi-step denoising and gradient computation, optimization variability, and interference with previously learned skills.

4.2 OGPO: off-policy experience reuse with generator updates

OGPO trains an off-policy critic from historical and fresh trajectories, then propagates value information into a generative policy. The key pathway is **replay → critic / advantage → generator update**. PPO-inspired design terms do not make OGPO equivalent to on-policy PPO. Important failure modes are policy-distribution shift, critic error, and optimization cost through the generation process.

4.3 Q-VGM: value-guided Flow Matching

Q-VGM converts action-value gradients into local velocity-matching targets, updating a Flow Action Expert without differentiating through its entire iterative sampling trajectory. The paper combines offline IQL and online TD-style value learning. **It updates the pretrained generator; it is not a frozen-Flow method.**

The distinction among these methods is *where the policy-improvement gradient enters*: sequential diffusion-process gradients, generative-process optimization with replay, or local critic-guided velocity updates.

5. Route II: freezing the generator and learning a small module

5.1 DSRL: reinforcement learning in noise or latent space

DSRL fixes the generative policy and trains a compact actor to steer an injected noise or latent variable:

$$z \sim q_\phi(z \mid o, g), \qquad A = G_{\theta_0}(o, g, z), \qquad \theta_0 \text{ fixed}.$$

This reduces the number of trainable parameters and protects the fixed generator, but improvements are restricted to actions **reachable under that generator's interface**. RLinf's DSRL example uses a frozen π_0; this alone does not establish drop-in support for every $\pi_{0.5}$, Flow policy, or robot.

5.2 Residual RL: bounded action corrections

The frozen base produces A_0 and a small actor produces ΔA_ϕ. Before execution, they must be aligned in action scale, reference frame, and chunk timing, then passed through an execution-time safety interface:

$$A_{\text{cmd}} = \text{Safe}\left(A_0 + \lambda \Delta A_\phi\right).$$

Residual RL is an **architectural pattern**, not a fixed choice of on-policy or off-policy optimizer. It is often straightforward to integrate, but usually only modifies actions near those proposed by the base policy; ill-conditioned residuals can destabilize contact-rich manipulation.

5.3 RL Token: actor–critic control on VLA features

RL Token first constructs a compact, accessible VLA feature interface and then trains a lightweight off-policy actor–critic while freezing the principal feature model. RLinf's RLT documentation explicitly separates representation bootstrapping on demonstrations from the subsequent online RL stage. A token-space actor is not synonymous with action residuals; constructing the feature interface may require preliminary adaptation.

6. The actor–critic and online off-policy loop

A standard off-policy learner stores $\mathcal{D} = \{(o_t, A_t, r_t, o_{t+1}, d_t)\}$ and updates a critic. A deliberately simplified one-step Bellman target is

$$y_t = r_t + \gamma(1 - d_t)\ \mathbb{E}_{A' \sim \pi}[Q_{\bar{\psi}}(o_{t+1}, A')].$$

If a chunk executes K low-level actions before the next policy decision, the proper decision-time target instead has the form

$$y_t^{(K)} = \sum_{j=0}^{K-1} \gamma^j r_{t+j} + \gamma^K (1 - d_{t+K}) \mathbb{E}_{A' \sim \pi}[Q_{\bar{\psi}}(o_{t+K}, A')].$$

A model may **generate H actions but execute only K**. Replay transitions, rewards, timestamps, overlapping chunks, and critic targets must reflect the *executed* K. These expressions are teaching abstractions, not the full SAC, OGPO, or Q-VGM losses.




Figure 3. An online off-policy actor–learner loop. Replay is useful, but executed actions and checkpoint versions must remain traceable.

Four distinctions should remain explicit: training reward versus runtime safety, simulated versus physical data, actor versus critic updates, and VLA inference rate versus low-level robot control rate.

7. Choosing a post-training route

Method	RL-updated component	Common data mode	Important prerequisites and risks
DPPO	Diffusion generator	Primarily on-policy	Generator access; denoising and rollout cost
OGPO	Generative policy	Online off-policy	Replay useful; critic bias and distribution shift
Q-VGM	Flow Action Expert	Offline-to-online	Trainable velocity network and trustworthy Q gradient

Method	RL-updated component	Common data mode	Important prerequisites and risks
DSRL	Noise / latent actor	May be off-policy	Frozen generator; limited reachable action set
Residual RL	Action-correction actor	Algorithm dependent	Temporal and unit alignment, contact safety
RL Token	Feature actor–critic	Online off-policy	Exposed VLA features, feature bootstrapping, latency

Choose the **trainable interface first**, then the **optimizer and experience pipeline**. A repository that contains both SAC and a Flow model does not imply that arbitrary Flow/VLA policies can be trained with SAC by changing one configuration file.

8. Evaluation: benchmark performance is not deployability

Beyond return and success rate, report **physical robot-hours, reset and human-intervention overhead, GPU-hours and memory, mean and tail inference latency, chunk-boundary discontinuities, safety interventions, disturbance recovery, out-of-distribution generalization, and retention of old tasks**. Off-policy systems should also record offline/online replay fractions, data and model versions, critic calibration, and behavior-policy drift.

Five common but incorrect equivalences are: **online = on-policy; frozen generator = no trainable components; velocity matching = full fine-tuning; a PPO/GRPO recipe = an online off-policy recipe; simulation success = physical safety**.

9. RLinf: from reusable RL infrastructure to physical deployment

The preceding methods explain **how a policy can improve**. In practice, the policy must interact through a system linking models, simulators, experience, optimization, robot control, and evaluation. RLinf is a useful representative infrastructure: it has scalable VLA RL examples and selected physical online-learning workflows, but it is not a universal plug-and-play solution to all foundation-policy post-training problems.

9.1 Documented capabilities, with their actual scope

Capability	Public reference workflow	Scope to preserve
On-policy VLA RL	$\pi_0/\pi_{0.5}$ + PPO/GRPO on LIBERO and related simulators	Specific tested recipes—not generic off-policy Flow fine-tuning
Frozen-policy off-policy RL	DSRL with frozen π_0, small noise actor + SAC	Tied to the exposed noise interface; adaptation to new models needs proof
Flow + SAC	SAC-Flow in ManiSkill and Franka peg insertion	Trains a specialized Flow actor; not evidence of frozen $\pi_{0.5}$ + SAC
Feature actor–critic	RLT / RL Token, ManiSkill and Franka	Needs representation bootstrapping and consistent feature/action semantics
Physical data and learning	RLinf-USER, multi-robot training	Async collection and scheduling exist; new hardware still needs adapters
Overlapped inference and control	RTC with $\pi_{0.5}$ in LIBERO / Franka evaluation	Hides inference waiting; does not guarantee hard real-time control
Custom robots and tasks	Add a Robot, New Task	A structured extension path exists; drivers, control, and safety remain engineering work

RLinf also includes SFT, evaluation, simulator integration, and multiple learner backends. Its real-robot guide now covers

platforms such as Franka, Turtle2, GimArm, and DOS-W1 at different levels of workflow maturity. It is **wrong to claim that RLinf has no physical robot, no off-policy RL, or no RTC support**. The important distinction is between a checked-in combination and a new, untested cross-product.

9.2 Remaining training-side limitations

Gap	Why infrastructure alone is insufficient	What to validate for a new model
Model–algorithm compatibility	$\pi_{0.5}$+PPO/GRPO, π_0+DSRL, and specialized Flow+SAC are different recipes	Action head, noise and density interfaces, log-prob availability, frozen parameter scope, gradient path
General online off-policy Flow/VLA RL	Replay-based value learning and generative actor updates must fit the target policy	True target-model updates, replay sampling, actor/critic cadence, behavior-policy records, action support
Reliable visual/contact critics	Sparse rewards, occlusion, and off-policy error can compound into value bias	OOD Q calibration, twin/ensemble critics, successful/failed physical trajectories
Correct action-chunk semantics	Generated horizon H need not equal executed steps K; RTC adds timing and async complexity	K-step reward/discount, termination flags, timestamps, overwritten actions, version alignment
Compute costs and reproducibility	Large VLA actor–rollout–learner systems still face inference throughput, communication, and memory limits	GPU-hours per success gain, worker backpressure, FSDP settings, checkpoint conversion, normalization
Multitask retention	Online improvement on a few tasks may erode broad pretrained competence	Held-out tasks, regression suites, behavior constraints, SFT/replay mixture

The first two are principally **limitations of documented end-to-end combinations**; the others are **research and reliability challenges that need task-specific engineering**, not necessarily missing functions in the repository.

9.3 Remaining deployment-side limitations

Simulation success is insufficient to guarantee stable closed-loop operation on real hardware. RLinf's robot extension architecture reduces integration work, but it does not remove these system boundaries.

Gap	Typical failure mode	Deployment acceptance metric
Unlisted robot hardware	Vendor SDK, CAN/RS485, ROS, and arm/hand action semantics differ from sample systems	Units, joint/task frames, update rates, reset and fault-recovery contracts
Inference and network jitter	VLA inference may run more slowly than low-level control; RTC masks only part of the wait	End-to-end latency, P95/P99 jitter, timeout fallback, continuous servo behavior
Chunk stitching and contact	Delayed observations or conflicting chunks disrupt insertion or grasp stability	Transition discontinuity, force/current limits, recovery time under perturbation
Independent runtime safety	Reward optimization cannot replace collision checks, E-stop, limits, loss-of-link behavior, or human takeover	Hardware watchdogs, bounded actions, safe override, audited rollback
Perception and reward quality	Calibration drift, unsynchronized cameras, and false success labels can mislead learning	Sensor synchronization, independent success checks, reward error, confidence/OOD tests
Cost of physical data	Manual resets, breakage, human labor, and limited robot uptime constrain collection	Robot-hours, reset-hours, intervention count, recovery success

Gap	Typical failure mode	Deployment acceptance metric
Checkpoint promotion and rollback	Asynchronous learner checkpoints may degrade safety while replay contains older semantics	Versioned normalization/data, offline gating, independent hardware tests, rollback plan

RTC is an inference-latency mitigation method, not a hard real-time safety controller. A Franka demonstration establishes feasibility for that setup, not automatic deployment on a novel manipulator or dexterous hand. RLinf's RTC guide also discusses the additional residual overhead of asynchronous communication.

9.4 A complete training-to-deployment loop




Figure 4. RLinf supplies important training-system components. Hardware drivers, safe execution, reliable rewards, and physical feedback still require end-to-end validation.

For a custom **robot arm + dexterous hand + head/wrist cameras**, a defensible integration sequence has four acceptance gates: verify observations, frames, normalization, and chunk semantics; verify policy inference, control latency, and hardware safety; verify replay, critic learning, and asynchronous checkpoint versions; only then permit online RL to generate a deployable candidate. More GPUs or a more sophisticated optimizer will not repair failed sensor/control contracts.

Transition to open problems. RLinf helps organize *how to collect, update, and deploy.* It does not provide a general guarantee that enough informative physical data can be acquired, values are reliable, generative updates are safe, or the deployed system remains dependable over long time horizons.

10. Open research questions at the learning–systems boundary

Research question	Fundamental challenge	Required evidence
Improve with less physical data	Sparse rewards, nonstationary environments, costly resets, off-policy shift	Robot-hours per success gain, replay efficiency, multi-scene statistics
Frozen foundation policies + online off-policy RL	Can a compact actor improve policy performance without losing generality, and overcome a fixed action support?	Against full/LoRA adaptation, DSRL, RL Token, residual RL; old-skill retention
Trustworthy critics and rewards for contact	Visual reward proxies may miss true contact, while Q values amplify mistakes	Real failure data, Q error, false-positive success rate, contact recovery
Fast feedback with smooth, safe actuation	Asynchronous chunks, network latency, slow VLAs, and fast servo loops conflict	P95/P99 delay, chunk boundaries, safety events, recovery time
Sim/world-model to real generalization	Friction, compliance, long-horizon synthetic error, and model exploitation	Novel objects, poses, lighting, real insertion/slip and recovery tests
Continual learning and comparable reporting	Learning new skills can forget old ones; hardware and evaluation costs vary	Cross-task regression, compute/robot budget, intervention and failure accounting

High-value future work is not limited to designing a new policy-gradient loss. It must jointly address **reusable interaction, calibrated value estimation, controlled generative-policy updates, monitored physical interaction, and safe deployment**. Read RLinf-USER, RECAP, and WoVR for complementary perspectives.

11. Primary literature and official resources

Topic	Recommended sources
RL foundations	PPO ·SAC
Generator updates	DPPO ·OGPO ·Q-VGM
Frozen/auxiliary interfaces	DSRL ·RL Token
RLinf system	Repository ·Docs ·RLinf-USER
Documented recipes	$\pi_0/\pi_{0.5}$ RL ·DSRL ·SAC-Flow ·RLT
Real robots and deployment	Real-World Robots ·Add a Robot ·RTC
Simulators and world models	Isaac Lab ·ManiSkill ·WoVR

Core message. Identify the pretrained policy and its trainable interface first; then verify that sampling, optimization, control, and deployment form a genuinely reliable loop. RLinf can eliminate substantial system duplication, but does not replace scientific validation or physical-robot safety engineering.