

ST 30

Shaking Water Bath

For repetitive and reproducible shaking, the ST 30 offers precisely controlled conditions.

Microprocessor control permits homogeneous, stable temperatures throughout the bath.

Precise shaking speed is ensured by microprocessor control system and induction motor.

It is designed for shaking a variety of tubes and containers. High visibility displays and indicators ensure that the values can be read from far and near all across the laboratory.

Typical use include tissue culture studies, bacterial incubation, enzyme reactions and fermentation.

- Tank volume: 30 liters
- Temperature range: Ambient temperature +5°C / 99.9°C
- Shaking speed between 20 250 rpm
- Programmable microprocessor control system for shaking speed, temperature and time
- LED display for temperature, time and shaking speed
- Excellent temperature control of liquid for uniform and stable temperatures
- Seamless stainless steel tank
- Heater replaced outside the tank
- Triple insulation for homogeneous and stable temperature
- User friendly control panel
- · Possibility to use different type of tubes, flasks or erlenmeyers with wide range of accessories



| Technical Specifications | ST 30 SHAKING WATER BATH |
|---|--|
| Туре | Shaking |
| Temperature Range | Ambient Temp. + 5°C / 99,9°C |
| Shaking Speed Range | 20-250 rpm |
| Temperature Sensor | Fe-Const |
| Tank Volume, liters | 30 |
| Useful Volume, liters | 18 |
| Control System | Programmable PID Microprocessor |
| Displays | LED displays for temperature, time and shaking speed |
| Temperature Set and Display Sensitivity | 0.1°C |
| Temperature Variation at 37°C | ≤ ± 0.3°C |
| Temperature Fluctuation at 37°C | ≤ ± 0.1°C |
| Timer | 99,9 hours + Hold position |
| Internal Material | Stainless Steel |
| External Material | Epoxy-polyester powder coated stainless steel |
| Shaking Basket Dimensions (WxDxH) mm | 225x350x150 |
| Power Consumption | 1650 W |
| Power Supply | 230V, 50/60 Hz |
| Internal Dimensions (WxDxH) mm | 300x505x190 |
| External Dimensions (WxDxH) mm | 330x626x406 |
| Packing Dimensions (WxDxH) mm | 420x700x640 |
| Net/Packed Weight, kg | 19/25 |

ACCESSORIES

| K 52 018 | Stainless steel lid for ST 30 |
|----------|----------------------------------|
| A 08 185 | Tube rack 52xØ13 mm, wide 70 mm |
| A 08 184 | Tube rack 30xØ16 mm, wide 70 mm |
| A 08 182 | Tube rack 27xØ18 mm, wide 70 mm |
| A 08 186 | Tube rack 12xØ30 mm, wide 70 mm |
| R 01 078 | Shelf for 12x100 ml flasks ST 30 |
| R 01 015 | Shelf for 6x250 ml flasks ST 30 |
| R 01 036 | Shelf for 6x100 ml flasks ST 30 |
| R 01 038 | Shelf for 4x500 ml flasks ST 30 |
| R 01 079 | Shelf for 2x1000 ml flasks ST 30 |



NÜVE SANAYİ MALZEMELERİ **IMALAT VE TİCARET A.Ş.**

Esenboğa Yolu, 22 km. Akyurt 06750 Ankara / TURKEY Tel : (+90.312) 399 28 30 (pbx) Fax: (+90.312) 399 21 97 www.nuve.com.tr sales@nuve.com.tr

