Note: This datasheet may be out of date.

Please download the latest datasheet of NCU15XH103F6SRC from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NCU15XH103F6SRC

## NCU15XH103F6SRC














## Appearance & Shape







### **Applications**

Limited Usage	Automotive Grade
	1. Various engine control units 2. ABS
	control unit 3. High power devices
Other Usage	(IGBT) 4. Temperature compensation
	for various circuits required high
	temperature.



### Packaging Information

Packaging	Specifications	Standard Packing Quantity
RC	180mm Paper Tape	10000



#### **Features**

- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-constant
- 4. Reflow soldering possible
- 5. Lead is not contained in the product.
- 6. NCU series are recognized by UL/cUL (UL1434, File No.E137188).

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date.

Please download the latest datasheet of NCU15XH103F6SRC from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NCU15XH103F6SRC

# NCU15XH103F6SRC



# **Specifications**

Resistance (25°C)	10kΩ	
Resistance Value Tolerance	140/	
(at 25°C)	±1%	
B-Constant (25/50°C)	3380K	
B-Constant (25/50°C)	.40/	
Tolerance	±1%	
B-Constant(25/80°C)	3428K	
(Reference Value)	34286	
B-Constant(25/85°C)	3434K	
(Reference Value)		
B-Constant(25/100°C)	3455K	
(Reference Value)	343310	
Max. Voltage	5V	
Maximum Operating Current	0.1mA	
(25°C)	O. HIIA	
Typical Dissipation Constant	1mW/°C	
(25°C)		
Operating Temperature	-40℃ to 150℃	
Range		
Size Code (in mm)	1.0x0.5mm	
Size Code (in inch)	0.4x0.2inch	
Shape	SMD	
Mass	0.0012g	

2 of 3

#### Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




Note: This datasheet may be out of date.


Please download the latest datasheet of NCU15XH103F6SRC from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NCU15XH103F6SRC

# NCU15XH103F6SRC







Resistance-Temperature Characteristics

Maximum Operating Voltage Reduction Characteristics

3 of 3

#### Attentior

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata:

NCU15XH103F6SRC