

AIR VELOCITY AND TEMPERATURE TRANSMITTER IVL 02

IVL 02 air velocity and temperature transmitter is made for HVAC applications. Output signals are corresponding the air flow velocity and temperature inside the ventilation duct.

Transmitter is to be mounted in the duct, on a place where the air flow is as laminar as possible. At the commissioning both outputs can be selected either milliamper or voltage outputs (see the jumper table below).

IVL 02-N is like IVL 02, but with a display cover (m/s and °C). All models are also available with a 100 and 400 mm long stem.

Display is scanning between velocity and temperature and it can be fixed to show either velocity or temperature by loosening the jumper on back of the display board.

Output signal selection

	4...20 mA	0...10 V
out 1		
out 2		



Technical data:

supply	24 Vdc (23...28 V), < 1.5 W
ranges	air velocity 0...2 m/s, temperature 0...50 °C
outputs	0...10 V, < 2 mA, 4...20 mA, < 600 Ω
velocity deviation	< 0.1 m/s ±7 % from reading (at 25 °C)
temp. deviation	< 0,5 °C (25 °C, > 0,5 m/s)
operating temp.	0...50 °C
mounting	by adjustable flange
housing	IP54 (transmitter), probe or cable conduit downwards
materials	PBT, PC, PA and stainless steel

Wiring terminals:

1	supply 24 Vdc
2	0 V
3 (out 1)	output 0...10 V / 4...20mA = 0...2 m/s
4 (out 2)	output 0...10 V / 4...20mA = 0...50 °C

Ordering guide:

Model	Product number	Description
IVL 02	1130030	air flow transmitter 0...2 m/s, immersion length 50...190 mm
IVL 02-N	1130032	air flow transmitter 0...2 m/s with display, immersion length 50...190 mm
IVL 02-100		air flow transmitter 0...2 m/s, immersion length 50...90 mm
IVL 02-400	1130031	air flow transmitter 0...2 m/s immersion length 50...390 mm
DPM 7	1186026	display cover for IVL 02

AIR VELOCITY AND TEMPERATURE TRANSMITTER IVL 10

IVL 10 air velocity and temperature transmitter is made for HVAC applications. Output signals are corresponding the air flow velocity and temperature inside the ventilation duct.

Transmitter is to be mounted in the duct, on a place where the air flow is as laminar as possible. At the commissioning both outputs can be selected either milliampere or voltage outputs (see the jumper table below).

IVL 10-N is like IVL 10, but with a display cover (m/s and °C). All models are also available with a 100 and 400 mm long stem.

Display is scanning between velocity and temperature and it can be fixed to show either velocity or temperature by loosening the jumper on back of the display board.

Output signal selection

	4...20 mA	0...10 V
out 1		
out 2		



Technical data:

Supply	24 Vdc (23...28 V), < 1.5 W
Ranges	air velocity 0...10 m/s, temperature 0...50 °C
Outputs	0...10 V, < 2 mA, 4...20 mA, < 600 Ω
Velocity deviation	< 0.5 m/s ±7% from reading (at 25 °C)
Temp. deviation	< 0.5 °C (25 °C, > 0.5 m/s)
Operating temp.	0...50 °C
Mounting	by adjustable flange
Housing	IP54 (transmitter), probe or cable conduit downwards
Materials	PBT, PC, PA and stainless steel

Wiring terminals:

1	supply 24 Vdc
2	0 V
3 (out 1)	output 0...10 V / 4...20 mA = 0...10 m/s
4 (out 2)	output 0...10 V / 4...20mA = 0...50 °C

Ordering guide:

Model	Product number	Description
IVL 10	1130010	air flow transmitter 0...10 m/s, immersion length 50...190 mm
IVL 10-N	1130012	air flow transmitter 0...10 m/s with display, immersion length 50...190 mm
IVL 10-100	1130014	air flow transmitter 0...10 m/s, immersion length 50...90 mm
IVL 10-400	1130011	air flow transmitter 0...10 m/s immersion length 50...390 mm
DPM 7	1186026	display cover for IVL 10

AIR VELOCITY AND TEMPERATURE TRANSMITTER IVL 20

IVL 20 air velocity and temperature transmitter is made for HVAC applications. Output signals are corresponding the air flow velocity and temperature inside the ventilation duct.

Transmitter is to be mounted in the duct, on a place where the air flow is as laminar as possible. At the commissioning both outputs can be selected either milliampere or voltage outputs (see the jumper table below).

IVL 20-N is like IVL 20, but with a display cover (m/s and °C). All models are also available with a 100 and 400 mm long stem.

Display is scanning between velocity and temperature and it can be fixed to show either velocity or temperature by loosening the jumper on back of the display board.

Output signal selection

	4...20 mA	0...10 V
out 1		
out 2		



Technical data:

Supply	24 Vdc (23...28 V), < 1.5 W
Ranges	air velocity 0...20 m/s, temperature 0...50 °C
Outputs	0...10 V, < 2 mA, 4...20 mA, < 600 Ω
Velocity deviation	< 1 m/s ±7 % from reading (at 25 °C)
Temp. deviation	< 0.5 °C (25 °C, > 0.5 m/s)
Operating temp.	0...50 °C
Mounting	by adjustable flange
Housing	IP54 (transmitter), probe or cable conduit downwards
Materials	PBT, PC, PA and stainless steel

Wiring terminals:

1	supply 24 Vdc
2	0 V
3 (out 1)	output 0...10 V / 4...20 mA = 0...20 m/s
4 (out 2)	output 0...10 V / 4...20 mA = 0...50 °C

Ordering guide:

Model	Product number	Description
IVL 20	1130050	air flow transmitter 0...20 m/s, immersion length 50...190 mm
IVL 20-N	1130053	air flow transmitter 0...20 m/s with display, immersion length 50...190 mm
IVL 20-100		air flow transmitter 0...20 m/s, immersion length 50...90 mm
IVL 20-400	1130052	air flow transmitter 0...20 m/s immersion length 50...390 mm
DPM 7	1186026	display cover for IVL 20