



Indoor Digital Thermo-Hygrometer

SYS-TH-BT

Feature

- Clear and intuitive digital display of temperature, hygrometer and battery indicator
- Most popular applications for incubators, building, office, storage any other place that requires monitoring of temperature and humidity levels
- Quality Certifications : CE certification
- With LED, buzzer alarm and Max-Min temperature and humidity memory function
- Time, Offset adjustable ($\pm 3^{\circ}\text{C}$ and $\pm 5\%\text{RH}$)
- Fold-out stand and Gourd hole for wall fastening
- Selectable temperature units $^{\circ}\text{C} / ^{\circ}\text{F}$



Specification

Model	SYS-TH-BT	
Measure Type	Temperature & Humidity	
Sensing Method	CMOS	
Range	Temp	0~60°C
	RH	0~100%RH
Accuracy	Temp	$\pm 0.3^{\circ}\text{C}$ (20~40°C), $\pm 1^{\circ}\text{C}$ (other range) * @ 25°C
	RH	$\pm 3\%\text{RH}$ (20~80%RH), $\pm 5\%\text{RH}$ (other range) * @ 25°C
Sampling Rate	8 sec	
Operating Range	Temp	0 ~ 60°C
	RH	0 ~ 100% RH (non-condensing)
Display	LCD , 65×40 mm	
Alarm Indication	LED (red), Buzzer	
Power Supply	2×1.5V 'AAA' batteries (included)	
Dimensions	10×10×31.5 cm	
Test Report	Option	

Function	SYS-TH-BT
Time Display (24-hour clock)	<input type="radio"/>
Selectable Temperature units ($^{\circ}\text{C} / ^{\circ}\text{F}$)	<input type="radio"/>
Max-Min Temperature and humidity memory	<input type="radio"/>
Offset adjustable	<input type="radio"/>
Alarm setting (LED and buzzer indication)	<input type="radio"/>

Order Information

SYS-TH-BT Digital Thermo-Hygrometer
SYS-TH-BT-X Digital Thermo-Hygrometer with Test report