

# Find the Minimum length Unsorted Subarray, sorting which makes the complete array sorted

Difficulty Level : Medium • Last Updated : 16 Jun, 2022



Given an unsorted array  $arr[0..n-1]$  of size  $n$ , find the minimum length subarray  $arr[s..e]$  such that sorting this subarray makes the whole array sorted.

## Examples:

1. If the input array is  $[10, 12, 20, 30, 25, 40, 32, 31, 35, 50, 60]$ , your program should be able to find that the subarray lies between the indexes 3 and 8.
2. If the input array is  $[0, 1, 15, 25, 6, 7, 30, 40, 50]$ , your program should be able to find that the subarray lies between the indexes 2 and 5.

Recommended Practice

**Length Unsorted Subarray**

Try It!

## Solution:



No video with supported format and MIME type found.

### 1. Find the candidate unsorted subarray

1. Scan from left to right and find the first element which is greater than the next element. Let  $s$  be the index of such an element. In the above example 1,  $s$  is 3 (index of 30).
2. Scan from right to left and find the first element (first in right to left order) which is smaller than the next element (next in right to left order). Let  $e$  be the index of such an element. In the above example 1,  $e$  is 7 (index of 31).

### 2. Check whether sorting the candidate unsorted subarray makes the complete array sorted or not. If not, then include more elements in the subarray.

1. Find the minimum and maximum values in  $arr[s..e]$ . Let minimum and maximum values be  $min$  and  $max$ .  $min$  and  $max$  for  $[30, 25, 40, 32, 31]$  are 25 and 40 respectively.
2. Find the first element (if there is any) in  $arr[0..s-1]$  which is greater than  $min$ , change  $s$  to index of this element. There is no such element in above example 1.
3. Find the last element (if there is any) in  $arr[e+1..n-1]$  which is



smaller than max, change *e* to index of this element. In the above example 1, *e* is changed to 8 (index of 35)

### 3. Print *s* and *e*.

## Implementation:

---

### C++

```
// C++ program to find the Minimum length Unsorted Subarray,
// sorting which makes the complete array sorted
#include<bits/stdc++.h>
using namespace std;

void printUnsorted(int arr[], int n)
{
    int s = 0, e = n-1, i, max, min;

    // step 1(a) of above algo
    for (s = 0; s < n-1; s++)
    {
        if (arr[s] > arr[s+1])
            break;
    }
    if (s == n-1)
    {
        cout << "The complete array is sorted";
        return;
    }

    // step 1(b) of above algo
    for(e = n - 1; e > 0; e--)
    {
        if(arr[e] < arr[e-1])
            break;
    }

    // step 2(a) of above algo
    max = arr[s]; min = arr[s];
    for(i = s + 1; i <= e; i++)
    {
        if(arr[i] > max)
```



```
        max = arr[i];
        if(arr[i] < min)
            min = arr[i];
    }

    // step 2(b) of above algo
    for( i = 0; i < s; i++)
    {
        if(arr[i] > min)
        {
            s = i;
            break;
        }
    }

    // step 2(c) of above algo
    for( i = n -1; i >= e+1; i--)
    {
        if(arr[i] < max)
        {
            e = i;
            break;
        }
    }

    // step 3 of above algo
    cout << "The unsorted subarray which"
         << " makes the given array" << endl
         << "sorted lies between the indices "
         << s << " and " << e;
    return;
}

int main()
{
    int arr[] = {10, 12, 20, 30, 25,
                 40, 32, 31, 35, 50, 60};
    int arr_size = sizeof(arr)/sizeof(arr[0]);
    printUnsorted(arr, arr_size);
    getchar();
    return 0;
}

// This code is contributed
// by Akanksha Rai
```



## C

```
// C program to find the Minimum length Unsorted Subarray,  
// sorting which makes the complete array sorted  
#include<stdio.h>  
  
void printUnsorted(int arr[], int n)  
{  
    int s = 0, e = n-1, i, max, min;  
  
    // step 1(a) of above algo  
    for (s = 0; s < n-1; s++)  
    {  
        if (arr[s] > arr[s+1])  
            break;  
    }  
    if (s == n-1)  
    {  
        printf("The complete array is sorted");  
        return;  
    }  
  
    // step 1(b) of above algo  
    for(e = n - 1; e > 0; e--)  
    {  
        if(arr[e] < arr[e-1])  
            break;  
    }  
  
    // step 2(a) of above algo  
    max = arr[s]; min = arr[s];  
    for(i = s + 1; i <= e; i++)  
    {  
        if(arr[i] > max)  
            max = arr[i];  
        if(arr[i] < min)  
            min = arr[i];  
    }  
  
    // step 2(b) of above algo  
    for( i = 0; i < s; i++)  
    {  
        if(arr[i] > min)  
        {
```



```

        s = i;
        break;
    }
}

// step 2(c) of above algo
for( i = n -1; i >= e+1; i--)
{
    if(arr[i] < max)
    {
        e = i;
        break;
    }
}

// step 3 of above algo
printf(" The unsorted subarray which makes the given array "
       " sorted lies between the indees %d and %d", s, e);
return;
}

int main()
{
    int arr[] = {10, 12, 20, 30, 25, 40, 32, 31, 35, 50, 60};
    int arr_size = sizeof(arr)/sizeof(arr[0]);
    printUnsorted(arr, arr_size);
    getchar();
    return 0;
}

```

## Java

```

// Java program to find the Minimum length Unsorted Subarray,
// sorting which makes the complete array sorted
class Main
{
    static void printUnsorted(int arr[], int n)
    {
        int s = 0, e = n-1, i, max, min;

        // step 1(a) of above algo
        for (s = 0; s < n-1; s++)
        {

```



```
        if (arr[s] > arr[s+1])
            break;
    }
    if (s == n-1)
    {
        System.out.println("The complete array is sorted");
        return;
    }

    // step 1(b) of above algo
    for(e = n - 1; e > 0; e--)
    {
        if(arr[e] < arr[e-1])
            break;
    }

    // step 2(a) of above algo
    max = arr[s]; min = arr[s];
    for(i = s + 1; i <= e; i++)
    {
        if(arr[i] > max)
            max = arr[i];
        if(arr[i] < min)
            min = arr[i];
    }

    // step 2(b) of above algo
    for( i = 0; i < s; i++)
    {
        if(arr[i] > min)
        {
            s = i;
            break;
        }
    }

    // step 2(c) of above algo
    for( i = n - 1; i >= e+1; i--)
    {
        if(arr[i] < max)
        {
            e = i;
            break;
        }
    }
}
```



```
// step 3 of above algo
System.out.println(" The unsorted subarray which"+
                  " makes the given array sorted lies"+
                  " between the indices "+s+" and "+e);

return;
}

public static void main(String args[])
{
    int arr[] = {10, 12, 20, 30, 25, 40, 32, 31, 35, 50, 60};
    int arr_size = arr.length;
    printUnsorted(arr, arr_size);
}
}
```

## Python3

# Python3 program to find the Minimum length Unsorted Subarray,  
# sorting which makes the complete array sorted

```
def printUnsorted(arr, n):
    e = n-1
    # step 1(a) of above algo
    for s in range(0,n-1):
        if arr[s] > arr[s+1]:
            break

    if s == n-1:
        print ("The complete array is sorted")
        exit()

    # step 1(b) of above algo
    e = n-1
    while e > 0:
        if arr[e] < arr[e-1]:
            break
        e -= 1

    # step 2(a) of above algo
    max = arr[s]
    min = arr[s]
    for i in range(s+1,e+1):
        if arr[i] > max:
            max = arr[i]
```





```
        if arr[i] < min:
            min = arr[i]

# step 2(b) of above algo
for i in range(s):
    if arr[i] > min:
        s = i
        break

# step 2(c) of above algo
i = n-1
while i >= e+1:
    if arr[i] < max:
        e = i
        break
    i -= 1

# step 3 of above algo
print ("The unsorted subarray which makes the given array")
print ("sorted lies between the indexes %d and %d"%( s, e))

arr = [10, 12, 20, 30, 25, 40, 32, 31, 35, 50, 60]
arr_size = len(arr)
printUnsorted(arr, arr_size)

# This code is contributed by Shreyanshi Arun
```

## C#

```
// C# program to find the Minimum length Unsorted Subarray,
// sorting which makes the complete array sorted

using System;

class GFG
{
    static void printUnsorted(int []arr, int n)
    {
        int s = 0, e = n-1, i, max, min;

        // step 1(a) of above algo
        for (s = 0; s < n-1; s++)
        {
            if (arr[s] > arr[s+1])
```



```
        break;
    }
    if (s == n-1)
    {
        Console.WriteLine("The complete " +
                           "array is sorted");
        return;
    }

    // step 1(b) of above algo
    for(e = n - 1; e > 0; e--)
    {
        if(arr[e] < arr[e-1])
            break;
    }

    // step 2(a) of above algo
    max = arr[s]; min = arr[s];

    for(i = s + 1; i <= e; i++)
    {
        if(arr[i] > max)
            max = arr[i];

        if(arr[i] < min)
            min = arr[i];
    }

    // step 2(b) of above algo
    for( i = 0; i < s; i++)
    {
        if(arr[i] > min)
        {
            s = i;
            break;
        }
    }

    // step 2(c) of above algo
    for( i = n -1; i >= e+1; i--)
    {
        if(arr[i] < max)
        {
            e = i;
            break;
        }
    }
}
```



```
    }
}

// step 3 of above algo
Console.Write(" The unsorted subarray which"+
    " makes the given array sorted lies \n"+
    " between the indices "+s+" and "+e);
return;
}

public static void Main()
{
    int []arr = {10, 12, 20, 30, 25, 40,
                 32, 31, 35, 50, 60};
    int arr_size = arr.Length;

    printUnsorted(arr, arr_size);
}
}
```

// This code contributed by Sam007

## PHP

```
<?php
// PHP program to find the Minimum length Unsorted Subarray,
// sorting which makes the complete array sorted
function printUnsorted(&$arr, $n)
{
    $s = 0;
    $e = $n - 1;

    // step 1(a) of above algo
    for ($s = 0; $s < $n - 1; $s++)
    {
        if ($arr[$s] > $arr[$s + 1])
            break;
    }
    if ($s == $n - 1)
    {
        echo "The complete array is sorted";
        return;
    }
}
```



```
// step 1(b) of above algo
for($e = $n - 1; $e > 0; $e--)
{
    if($arr[$e] < $arr[$e - 1])
        break;
}

// step 2(a) of above algo
$max = $arr[$s];
$min = $arr[$s];
for($i = $s + 1; $i <= $e; $i++)
{
    if($arr[$i] > $max)
        $max = $arr[$i];
    if($arr[$i] < $min)
        $min = $arr[$i];
}

// step 2(b) of above algo
for( $i = 0; $i < $s; $i++)
{
    if($arr[$i] > $min)
    {
        $s = $i;
        break;
    }
}

// step 2(c) of above algo
for( $i = $n - 1; $i >= $e + 1; $i--)
{
    if($arr[$i] < $max)
    {
        $e = $i;
        break;
    }
}

// step 3 of above algo
echo " The unsorted subarray which makes " .
      "the given array " . "\n" .
      " sorted lies between the indees " .
      "$s . " and " . $e;

return;
}
```



```
// Driver code
$arr = array(10, 12, 20, 30, 25, 40,
            32, 31, 35, 50, 60);
$arr_size = sizeof($arr);
printUnsorted($arr, $arr_size);

// This code is contributed
// by ChitraNayal
?>
```

## Javascript

<script>

```
// Javascript program to find the Minimum length Unsorted Subarray,
// sorting which makes the complete array sorted
```

```
function printUnsorted(arr,n)
{
    let s = 0, e = n-1, i, max, min;
    // step 1(a) of above algo
    for (s = 0; s < n-1; s++)
    {
        if (arr[s] > arr[s+1])
            break;
    }
    if (s == n-1)
    {
        document.write("The complete array is sorted");
        return;
    }
    // step 1(b) of above algo
    for(e = n - 1; e > 0; e--)
    {
        if(arr[e] < arr[e-1])
            break;
    }
    // step 2(a) of above algo
    max = arr[s]; min = arr[e];
    for(i = s + 1; i <= e; i++)
    {
        if(arr[i] > max)
            max = arr[i];
```



```
        if(arr[i] < min)
            min = arr[i];
    }
    // step 2(b) of above algo
    for( i = 0; i < s; i++)
    {
        if(arr[i] > min)
        {
            s = i;
            break;
        }
    }
    // step 2(c) of above algo
    for( i = n -1; i >= e+1; i--)
    {
        if(arr[i] < max)
        {
            e = i;
            break;
        }
    }
    // step 3 of above algo
    document.write(" The unsorted subarray which"+
        " makes the given array sorted lies"+
        " between the indees "+s+" and "+e);

    return;
}
let arr=[10, 12, 20, 30, 25, 40, 32, 31, 35, 50, 60];
let arr_size = arr.length;
printUnsorted(arr, arr_size);

// This code is contributed by avanitrachhadiya2155
```

</script>

## Output :

The unsorted subarray which makes the given array sorted lies between the indexes 3 and 8



**Time Complexity :**  $O(n)$

**Auxiliary Space :**  $O(1)$

Please write comments if you find the above code/algorithm incorrect, or find better ways to solve the same problem.

## DSA Self-Paced Course

- ✓ Curated by experts
- ✓ Trusted by 1 Lac+ students.

[Enrol Now](#)

Like 90

Previous

Sort elements by frequency |  
Set 2

Next


Sort numbers stored on  
different machines

## RECOMMENDED ARTICLES

Page : 1 2 3

**01** Which sorting algorithm makes minimum number of memory writes?  
01, Feb 11

**05** Find a pair of elements swapping which makes sum of two arrays same  
30, Jun 17

 **02** Maximize partitions that if sorted individually makes the whole Array sorted  
13, Jan 22

**06** Minimize cost to sort given array by sorting unsorted subarrays  
03, Jan 22

**03** Check if removal of a subsequence of non-adjacent elements makes the array sorted  
23, May 21

**07** Find index of first occurrence when an unsorted array is sorted  
05, Aug 18

**04** Maximize M such that swapping  $\text{arr}[i]$  with  $\text{arr}[i+M]$  makes Array sorted  
13, Jul 22

**08** Why is it faster to process sorted array than an unsorted array ?  
11, Jul 17





## Article Contributed By :



GeeksforGeeks

## Vote for difficulty

Current difficulty : [Medium](#)

Easy

Normal

Medium

Hard

Expert

Improved By : [ukasp](#), [Akanksha\\_Rai](#), [avanitrachhadiya2155](#),  
[singhalrishabh0904](#), [codewithshinchan](#), [kothavvsaakash](#),  
[hardikkoriintern](#)

Article Tags : [Arrays](#), [Sorting](#)

Practice Tags : [Arrays](#), [Sorting](#)

Improve Article

Report Issue

Writing code in comment? Please use [ide.geeksforgeeks.org](https://ide.geeksforgeeks.org), generate link and share the link here.

Load Comments





A-143, 9th Floor, Sovereign Corporate Tower,  
Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

## Company

About Us  
Careers  
In Media  
Contact Us  
Privacy Policy  
Copyright Policy

## News

Top News  
Technology  
Work & Career  
Business  
Finance  
Lifestyle  
Knowledge

## Web Development

Web Tutorials  
Django Tutorial  
HTML  
JavaScript

## Learn

Algorithms  
Data Structures  
SDE Cheat Sheet  
Machine learning  
CS Subjects  
Video Tutorials  
Courses

## Languages

Python  
Java  
CPP  
Golang  
C#  
SQL  
Kotlin

## Contribute

Write an Article  
Improve an Article  
Pick Topics to Write  
Write Interview Experience



---

NodeJS

@geeksforgeeks , Some rights reserved

Do Not Sell My Personal Information

