ECE 508 Manycore Parallel Algorithms

Lecture 2:

Scatter-to-Gather Transformation

Objective

• to understand the performance implications of parallelization over inputs ('scatter') vs. parallelization over outputs ('gather')

• to understand methods by which input parallelism can be transformed to output parallelism

What Do Scatter and Gather Mean?

In the high-performance literature,

- scatter refers to writing values
 to non-contiguous memory locations, and
- gather refers to reading values from non-contiguous memory locations.

Consider a Common Input-Output Computation

The data:

- an array of inputs, and
- an array of outputs.

The computation:

- a (logical) bipartite graph from inputs to outputs,
- a way of calculating the effect for each pair, and
- an operator—typically associative and commutative*—that accumulates results for each output.


^{*} In real codes, remember that floating-point is not associative.

Even Simpler: a Complete Bipartite Graph

Doubly iterate over outputs
Nested
Loop
iterate over inputs

Simple Example: Regularization of MRI Data

```
for (m = 0; m < M; m++) {
  for (n = 0; n < N; n++) {
    out[n] += f(in[m], m, n);
  }
}</pre>
```



- Map data in radial coordinates to Cartesian coordinates.
- Input in: M scan points
- Output out:N regularized scan points
- Complexity O(MN).
- Output tends to be more regular than input.

Which Loop Should We Transform to Threads?


The big question:

How should we parallelize?

Over inputs?


Or over outputs?

Parallelization Over Inputs Produces a Scatter




Scatter is Often Slow on GPUs

- An output may be updated by many threads.
 - Updates serialized with atomic operations.
 - Costly (slow) for large numbers of threads.
 - Worse when input-output graph is complete.




Parallelization Over Outputs Produces a Gather



Gather Can be Fast on GPUs

- Avoids serialization!
 - Can leverage caches (or shared memory, if graph structure provides locality).
 - Even better when input-output graph is complete
 (all threads read the same inputs).



Another Historical Concept: the Owner Computes Rule

Another term for output parallelism

- borrowed from parallel literature
- on programming systems with distributed memory.

Consider a cluster of many processors/chips, each with a memory.


- Moving computation from memory to memory is complicated and error-prone.
- Instead, move data to the memory in which an output / result is to be stored, and the associated processor—the "owner" of that memory—computes the result.
- The term? The "owner computes" rule.

Owner Computes? No, But May Help.

- In GPU community, output parallelization is sometimes referred to as "owner computes."
- It doesn't quite fit. Memory has no owner.
- However, thinking of the approach in this way may help one
 - remember that only one thread (choose an owner!)
 - should access an output
 - to avoid serialization (as with parallelization of inputs).

Computation Often Used to Regularize Data So why do any codes parallelize over inputs?


- Many practical input-output graphs
 - are **sparse** (not complete), and
 - output tends to be more regular than input.



Input-Output Relationship May Make Scatter Easier

So why do any codes parallelize over inputs?

- Calculating outputs affected by an input is often easier than calculating inputs that affect an output.
- Thus writing a scatter kernel is easier.



Today, Assume a Complete Input-Output Relation

One approach that we'll discuss later,

- in the Cut-off Binning Lecture, is to
- regularize input elements to make finding relevant inputs for an output easier.


For this lecture,

- assume a complete bipartite graph.
- In other words, all inputs effect all outputs.

Example: Ion Placement in Molecular Modeling

Let's use an example:

- ion placement for molecular modeling
- (drawn from Klaus Schulten's group).




Ion Placement is Part of Biomolecular Simulation

• Biomolecular simulations attempt to replicate in vivo conditions in silico.

• First, model structures constructed in vacuum.


Then solvent (water)
 and ions added as
 necessary to reproduce
 required biological
 conditions.



Calculate Electrostatic Potential Induced by Atoms

The core computation? Calculate

- an initial electrostatic potential map
- around the simulated structure,
- considering the contributions of all atoms.



Consumes significant time in VMD, the source of our example.

Today's Example is Not the Entire Application We'll ignore this part, but...

- Ions are placed one at a time:
 - find grid point with minimum potential,
 - add an ion at that point,
 - add potential contribution of new ion to map,
 - and repeat until required number of ions added.

We Explore Direct Coulomb Summation (DCS)

How do we find electrostatic potential at each grid point?

Remember basic electromagnetics:

for each grid/lattice point P and atom Apotential[P] += charge[A] / distance (A,P)

All atoms affect all grid points.

Most accurate method: Direct Coulomb Summation (**DCS**)

- sum all pairwise (atom to grid point) potentials
- (a complete bipartite graph computation!),
- ideally suited to GPUs.

DCS is Not the Fastest Algorithm

Note: approximation-based methods


- such as cut-off summation
- can achieve much higher performance
- at the cost of numerical accuracy and flexibility.

We will cover these later (in the Binning lecture).

Visualize the DCS Computation

Let's visualize the update rule:

potential[P] += charge[A] / distance(A,P)



Interface to Our DCS Function

What's the function interface?

Given

- grid potential (logically a 3D array; the output),
- grid size and spacing, and
- array of atom positions and charges, we'll write a function to compute one X-Y slice (a fixed Z coordinate) of the potential.

Connect the Function to the Visualization


```
void cenergy (float* energygrid,
                                    dim3 grid,
               float gridspacing, float z,
               const float* atoms, int numatoms);
                                   X, Y, and Z dimensions
pointer to 3D (logical)
                                         of the grid
 array of electrostatic
       potential
   (the output data)
```

Connect the Function to the Visualization

modeled physical distance between grid points

Note: spatial Z coordinate is logical Z coordinate times gridspacing.

spatial Z coordinate of X-Y grid slice to compute



Connect the Function to the Visualization

```
void cenergy (float* energygrid, dim3 grid,
               float gridspacing, float z,
               const float* atoms, int numatoms);
  1D array of X, Y, Z
                               number of atoms in array
coordinates and charge
 of atoms (4-tuples, in
     order stated)
```

First, Calculate Constants

Let's start by looking at intuitive sequential version of DCS.

Outer Loop Iterates Over Atoms

```
int atomarrdim = numatoms * 4;

for (int n = 0; n < atomarrdim; n += 4) {

    Outer loop iterates
    over atoms.

Loop body on
    following slides.</pre>
* 4;

Each "atom" is
    a 4-tuple of
    floats: X, Y, Z,
    and charge.
```

Precalculate Values Constant Over Gridpoints

Why iterate first over atoms?

```
float dz = z - atoms[n + 2];
float dz2 = dz * dz;
```

All grid points have the same Z value.

```
float charge = atoms[n + 3];
```

Atom's charge is the same for all grid points.

Next, loop over gridpoints.

Precalculate Values Constant Over Row

Next, loop over rows (Y dimension).

```
for (int j = 0; j < grid.y; j++) {
  float y = gridspacing * (float)j;
  float dy = y - atoms[n + 1];
  float dy2 = dy * dy;</pre>
```

All grid points in row have same Y value.

```
int grid_row_offset =
   grid_slice_offset + grid.x * j;
```

Loop across columns here.

first gridpoint for row

Precalculate Values Constant Over Row

Finally, loop over columns (X dimension).

```
for (int i = 0; i < grid.x; i++) {
  float x = gridspacing * (float)i;
  float dx = x - atoms[n + 0];</pre>
```

Compute X value and distance.

```
energygrid[grid_row_offset + i] +=
    charge / sqrtf (dx * dx + dy2 + dz2);
```

Apply update rule (charge over distance).

Reference Version: Intuitive Sequential DCS

```
void cenergy (float* energygrid, dim3 grid, float gridspacing, float z,
             const float* atoms, int numatoms) {
  int grid slice offset = (grid.x * grid.y * z) / gridspacing;
                                 // X,Y,Z, and charge info for each atom
  int atomarrdim = numatoms * 4;
  for (int n = 0; n < atomarrdim; <math>n += 4) { // Calculate potential contribution of each atom.
   float dz = z - atoms[n + 2]; // All grid points in a slice have the same Z value.
    float dz^2 = dz * dz:
   float charge = atoms[n + 3];
   for (int j = 0; j < grid.y; j++) {
     float y = gridspacing * (float)j;
     float dy = y - atoms[n + 1]; // All grid points in a row have the same Y value.
     float dy2 = dy * dy;
      int grid row offset = grid slice offset + grid.x * j;
      for (int i = 0; i < grid.x; i++) {
        float x = gridspacing * (float)i;
        float dx = x - atoms[n + 0];
        energygrid[grid row offset + i] += charge / sqrtf (dx * dx + dy2 + dz2);
```


Summary of Sequential DCS

- **Input-oriented**: for each input atom, calculate potential contribution for all gridpoints in X-Y slice.
- Output (energygrid)
 - is a regular lattice, with
 - a linear mapping from indices to spatial coordinates.
- Input (atom positions) is irregular: spatial coordinates of atoms (X, Y, Z) stored as data in atom.
- Algorithm minimizes computation by moving invariants out of loops and pre-computing partial expressions.

Irregular Input vs. Regular Output

 Atoms come from modeled molecular structures, solvent (water) and ions irregular by necessity

Energy grid models the electrostatic potential value at regularly spaced points
 regular by design



Create a Simple CUDA Version as Usual

Recall the canonical process for producing a simple CUDA kernel.

- 1. Input atom coordinates and charges to host memory.
- 2. Allocate and initialize host copy memory of potential map.
- 3. Allocate potential map slice buffer on GPU.
- 4. Loop over potential map slices:
 - a. Copy potential map slice from host to GPU.
 - b. Loop over groups of atoms:
 - Copy atom data to GPU.
 - ii. Run CUDA Kernel on atoms and potential map slice on GPU.
 - c. Copy potential map slice from GPU to host.
- 5. Free resources.

Straightforward CUDA Parallelization

- Parallelize the outer loop (over atoms).
 - Each thread computes
 - the contribution of an atom
 - to all grid points in the X-Y slice.
 - Scatter parallelization.
- Strip outer loop from CPU version to obtain kernel.
 - Each thread executes an outer loop iteration
 - (plus redundant constant computation).
- numatoms used in host code to configure kernel launch.

From Sequential to Kernel

```
void cenergy (float* energygrid, dim3 grid, float gridspacing, float z,
             const float* atoms, int numatoms) {
  int grid slice offset = (grid.x * grid.y * z) / gridspacing;
  int atomarrdim = numatoms * 4;
                                          // X,Y,Z, and charge info for each atom
  for (int n = 0; n < atomarrdim; <math>n += 4) { // Calculate potential contribution of each atom.
                                       // All grid points in a slice have the same Z value.
   float dz = z - atoms[n + 2];
    float dz2 = dz * dz;
                                          Replace with calculation of n
   float charge = atoms[n + 3];
   for (int j = 0; j < grid.y; j++) {
                                                 from thread indices.
      float y = gridspacing * (float);;
                                       All grid points in a row have the same Y value.
      float dy = y - atoms[n + 1];
      float dy2 = dy * dy;
      int grid row offset = grid slice offset + grid.x * j;
      for (int i = 0; i < grid.x; i++) {
        float x = gridspacing * (float)i;
        float dx = x - atoms[n + 0];
        energygrid[grid row offset + i] += charge / sqrtf (dx * dx + dy2 + dz2);
```

DCS Scatter Kernel (Slow!)

```
void global cenergy (float* energygrid, dim3 grid, float gridspacing, float z,
                        const float* atoms /* numatoms not passed */) {
  int n = (blockIdx.x * blockDim.x + threadIdx.x) * 4;
  int grid slice offset = (grid.x * grid.y * z) / gridspacing;
 // no loop over atoms
  float dz = z - atoms[n + 2];
                                   // All grid points in a slice have the same Z value.
  float dz2 = dz * dz;
  float charge = atoms[n + 3];
  for (int j = 0; j < grid.y; j++) {
   float y = gridspacing * (float)j;
   float dy = y - atoms[n + 1]; // All grid points in a row have the same Y value.
   float dy2 = dy * dy;
                                                               Oops! Update
   int grid row offset = grid slice offset + grid.x * j;
   for (int i = 0; i < grid.x; i++) {
                                                           needs to be atomic!
      float x = gridspacing * (float)i;
      float dx = x - atoms[n + 0];
      energygrid[grid row offset + i] += charge / sqrtf (dx * dx + dy2 + dz2);
    }
                                                  New code in blue.
  // no loop over atoms
```

Review Atomic Operations in CUDA

Atomic operations in CUDA

- look like function calls syntactically, but
- compiler translates them into single instructions
 (synchronization primitives, or intrinsics
 in CUDA terminology);
- examples include fetch-and-op (add, sub, inc, dec, min, max), swap/exchange, CAS (compare and swap).

(For details: CUDA C programming Guide 4.0+)

Example of Fetch-and-Add Operation

Example: atomic fetch-and-add

```
int atomicAdd (int* address, int val);
```

- Reads the 32-bit word at address
 (global or shared memory) into OLD,
- stores (OLD + val) back to memory at address, and
- returns OLD.

Several Fetch-and-Op Data Types Supported

32-bit unsigned: unsigned int atomicAdd (unsigned int* address, unsigned int val); 64-bit unsigned: unsigned long int atomicAdd (unsigned long long int* address, unsigned long long int val); single-precision floating-point (capability > 2.0): float atomicAdd (float* address, float val);

Pros and Cons of the Scatter Kernel

- Pros
 - easy to write based on CPU version
 - good for software engineering and code maintenance
 - preserves computation efficiency (coordinates, distances, offsets) of sequential code
- Cons
 - atomic add serializes the execution, so slow!

Again, Calculate Constants First

Let's examine an output-oriented sequential DCS.

Remainder on following slides.

size of atoms array and logical Z coordinate (constants)

Outer Loop Iterates Over Rows

```
for (int j = 0; j < grid.y; j++)
```

Outer loop iterates over rows.

```
float y = gridspacing * (float)j;
```

Remaining loop body on following slides.

Spatial Y coordinate is constant for each row.

Second Loop Iterates Over Columns

Next, loop over columns.

```
float x = gridspacing * (float)i;
float energy = 0.0f;
```

for (int i = 0; i < grid.x; i++) {

Second loop iterates over columns.

Remaining loop body on following slides.

Spatial X coordinate is constant for each grid point.

```
energygrid[grid.x * grid.y * k + grid.x * j + i]
+= energy;
```

Use a Local Variable to Accumulate Contributions

Local variable accumulates all contributions.

Remaining loop body on following slides.

Accumulate here.

```
energygrid[grid.x * grid.y * k + grid.x * j + i]
+= energy;
```

Add accumulation into grid point.

Inner Loop Iterates Over Atoms

Loop over atoms to accumulate contribution.

```
for (int n = 0; n < atomarrdim; n += 4) {
  float dx = x - atoms[n + 0];
  float dy = y - atoms[n + 1];
  float dz = z - atoms[n + 2];

energy += atoms[n + 3] /
  sqrtf (dx * dx + dy * dy + dz * dz);
}</pre>
Inner loop
iterates

Over atoms
(4-tuples).
```

Accumulate Contribution from Each Atom

Compute distance and accumulate atom's contribution.

```
for (int n = 0; n < atomarrdim; n += 4) {

float dx = x - atoms[n + 0];

float dy = y - atoms[n + 1];

float dz = z - atoms[n + 2];

Compute per-atom distance components.
```

```
energy += atoms[n + 3] /
   sqrtf (dx * dx + dy * dy + dz * dz);
```

Accumulate contribution (charge over distance).

Reference Version: Output-Oriented Sequential DCS

Pros and Cons of the Output-Oriented Sequential DCS

- Pros
 - fewer accesses to energygrid array
 - simpler code structure
- Cons
 - more calculations on the coordinates.
 - more accesses to atom array
 - slower execution (due to extra calculations)

Parallelize New Version with Two Loops

- Parallelize two outer loops (over grid points).
 - Each thread computes
 - the contribution to one grid point in the X-Y slice
 - from all atoms.
 - Gather parallelization.
- Strip outer loops from CPU version to obtain kernel.
 - Each thread executes a loop iteration
 - (plus redundant constant computation).


From Output-Oriented Sequential to Kernel

```
void cenergy (float* energygrid, dim3 grid, float gridspacing, float z,
             const float* atoms, int numatoms) {
  int atomarrdim = numatoms * 4;
  int k = z / gridspacing;
 for (int j = 0; j < grid.y; j++) {
                                              Replace with calculation
    float y = gridspacing * (float)j;
    for (int i = 0; i < grid.x; i++) {
                                             of i, j from thread indices.
      float x = gridspacing * (float)i;
      float energy = 0.0f;
      for (int n = 0; n < atomarrdim; <math>n + = 4) {
                                                // Calculate contribution of each atom.
        float dx = x - atoms[n + 0]
        float dy = y - atoms[n + 1];
        float dz = z - atoms[n + 2];
       energy += atoms [n + 3] / sqrtf (dx * dx + dy * dy + dz * dz);
      energygrid[grid.x * grid.y * k + grid.x * j + i] += energy;
```

DCS Gather Kernel (Fast!)

```
void global cenergy (float* energygrid, dim3 grid, float gridspacing, float z,
                        const float* atoms, int numatoms) {
  int i = blockIdx.x * blockDim.x + threadIdx.x;
  int j = blockIdx.y * blockDim.y + threadIdx.y;
  int atomarrdim = numatoms * 4;
  int k = z / gridspacing;
  // no loop over rows
  float y = gridspacing * (float)j;
  // no loop over columns
  float x = gridspacing * (float)i;
  float energy = 0.0f;
  for (int n = 0; n < atomarrdim; n += 4) { // Calculate contribution of each atom.
   float dx = x - atoms[n + 0];
   float dy = y - atoms[n + 1];
   float dz = z - atoms[n + 2];
   energy += atoms[n + 3] / sqrtf (dx * dx + dy * dy + dz * dz);
  energygrid[grid.x * grid.y * k + grid.x * j + i] += energy;
  // no loop over columns
                                                   New code in blue.
  // no loop over rows
```

Block/Grid Decomposition (no thread coarsening)




Compare Gather Kernel with Scatter Kernel

- Threads
 - do not require atomic operations (no serialization),
 - read same atom array values in the same order, and
 - read/write unique energygrid value at end of thread.
- Optionally, dz*dz can be sent in place of z.
- Implications
 - Gather kernel is much faster than scatter kernel!
 - Compute-efficient sequential algorithm may not translate to fastest parallel kernel (gather vs. scatter).
 - We will return to this point later.


Case study: Scatter vs. Gather

• Scatter vs. Gather: most data negligible at this scale




Case study: Scatter vs. Gather

• Zoom in vertical axis by $23 \times$



Case study: Scatter vs. gather

• Zoom in vertical axis another 13.3×



Cache Performance also Dominates CPU Timing

- In modern **CPUs**,
 - cache effectiveness often more important
 - than compute efficiency.
- "Intuitive" sequential DCS (scatter)
 - has bad cache performance
 - energygrid is large, typically >20× larger than atom
 - Code sweeps through energygrid for each atom, trashing cache.
- Fastest sequential code is actually an optimized, output-oriented code!

Outline of A Fast Sequential Code

```
Use additional,
for all z {
                                        pre-computed
  for all atoms { precompute dz^2 }
                                           arrays.
  for all y {
    for all atoms { precompute dy^2 (+ dz^2) }
    for all x {
      for all atoms {
        compute contribution to (x,y,z) grid point
            using precomputed dy^2 and dz^2
                    Extra arrays? So ...
                Why better cache behavior?
```

More Thoughts on Fast Sequential Code

Why does this code have better cache behavior on CPUs?

- Recall that atom is much smaller than energygrid.
- Sweeping atom repeatedly leverages the cache.
- Even several copies (the extra arrays) can fit!
 (Read: atom group size chosen based on cache size.)

The lesson: Writing high performance code of any type (sequential or parallel) is an engineering design effort.

Tradeoffs often depend on data sizes.

What About Other Ways of Parallelizing?


Other choices are possible for parallelization...

In fact, those who have taken 408 have implemented some.

Consider reduction.
One output.
Complete bipartite graph

(all inputs affect the output)!


A Reduction Pattern



Reduction Has No Output Parallelism!

- Output parallelization ... one thread?
- But scatter-style code is not acceptable:
 - each thread reads one input and accumulates into one reduction variable with atomic operation, so
 - ALL input threads write to ONE output location?
- Privatization or Tree reduction makes more sense.

Solution: Create Multiple Outputs



ANY QUESTIONS?