

Maximum length substring having all same characters after k changes

Difficulty Level : Hard • Last Updated : 14 Jul, 2022



We have a string of length n , which consist only UPPER and LOWER CASE characters and we have a number k (always less than n and greater than 0). We can make at most k changes in our string such that we can get a sub-string of maximum length which have all same characters.

Examples:

n = length of string

k = changes you can make

Input : $n = 5$ $k = 2$

str = ABABA

Output : maximum length = 5

which will be (AAAAA)

Input : $n = 6$ $k = 4$

str = HHHHHH

Output : maximum length=6

which will be(HHHHHH)



Recommended Practice

Maximum Sub-String after at most K changes

Try It!

We check for each character of English alphabet (both upper and lower cases one by one). We are basically looking for maximum length of sub-string that can be formed by each character and whichever character will form the sub-string of maximum length then that length will be our answer.

1. We check for maximum length of sub-string that can be formed by every character in a set of 52 characters (From 'A' to 'Z' and from 'a' to 'z').
2. For doing this we traverse whole string and whenever we find a different character, we increase the count.
3. If count becomes greater than k (at right index), we again start from 0th index and if we found different character we will decrease the count.
4. When count will be equal to k (at left index) then at that point the length will be $\text{rightIndex} - \text{leftIndex} + 1$.
5. We repeat this process until we reach at the end of string and at that point we will return the maximum length.
6. We do this for all characters and finally return the maximum length.

Implementation:

C++

```
// C++ program to find maximum length equal
// character string with k changes
#include <iostream>
using namespace std;

// function to find the maximum length of
// substring having character ch
int findLen(string& A, int n, int k, char ch)
{
    int maxlen = 1;
    int cnt = 0;
    int l = 0, r = 0;
```



```
// traverse the whole string
while (r < n) {

    /* if character is not same as ch
    increase count */
    if (A[r] != ch)
        ++cnt;

    /* While count > k traverse the string
    again until count becomes less than k
    and decrease the count when characters
    are not same */
    while (cnt > k) {
        if (A[l] != ch)
            --cnt;
        ++l;
    }

    /* length of substring will be rightIndex -
    leftIndex + 1. Compare this with the maximum
    length and return maximum length */
    maxlen = max(maxlen, r - l + 1);
    ++r;
}

return maxlen;
}

// function which returns maximum length of substring
int answer(string& A, int n, int k)
{
    int maxlen = 1;
    for (int i = 0; i < 26; ++i) {
        maxlen = max(maxlen, findLen(A, n, k, i+'A'));
        maxlen = max(maxlen, findLen(A, n, k, i+'a'));
    }
    return maxlen;
}

// Driver code
int main()
{
    int n = 5, k = 2;
    string A = "ABABA";
    cout << "Maximum length = " << answer(A, n, k) << endl;
}
```



```
n = 6, k = 4;
string B = "HHHHHH";
cout << "Maximum length = " << answer(B, n, k) << endl;
return 0;
}
```

Java

```
// Java program to find maximum length equal
// character string with k changes

public class GFG
{
    // method to find the maximum length of
    // substring having character ch
    static int findLen(String A, int n, int k, char ch)
    {
        int maxlen = 1;
        int cnt = 0;
        int l = 0, r = 0;

        // traverse the whole string
        while (r < n) {

            /* if character is not same as ch
            increase count */
            if (A.charAt(r) != ch)
                ++cnt;

            /* While count > k traverse the string
            again until count becomes less than k
            and decrease the count when characters
            are not same */
            while (cnt > k) {
                if (A.charAt(l) != ch)
                    --cnt;
                ++l;
            }

            /* length of substring will be rightIndex -
            leftIndex + 1. Compare this with the maximum
            length and return maximum length */
            maxlen = Math.max(maxlen, r - l + 1);
            ++r;
        }
    }
}
```



```
    }
    return maxlen;
}

// method which returns maximum length of substring
static int answer(String A, int n, int k)
{
    int maxlen = 1;
    for (int i = 0; i < 26; ++i) {
        maxlen = Math.max(maxlen, findLen(A, n, k, (char) (i+'A')));
        maxlen = Math.max(maxlen, findLen(A, n, k, (char) (i+'a')));
    }
    return maxlen;
}

// Driver Method
public static void main(String[] args)
{
    int n = 5, k = 2;
    String A = "ABABA";
    System.out.println("Maximum length = " + answer(A, n, k));

    n = 6; k = 4;
    String B = "HHHHHH";
    System.out.println("Maximum length = " + answer(B, n, k));
}
}
```

Python3

```
# Python3 program to find maximum length
# equal character string with k changes

# function to find the maximum length of
# substring having character ch
def findLen(A, n, k, ch):
    maxlen = 1
    cnt = 0
    l = 0
    r = 0

    # traverse the whole string
    while r < n:
```



```
# if character is not same as ch
# increase count
if A[r] != ch:
    cnt += 1

# While count > k traverse the string
# again until count becomes less than k
# and decrease the count when characters
# are not same
while cnt > k:
    if A[l] != ch:
        cnt -= 1
    l += 1

# length of substring will be rightIndex -
# leftIndex + 1. Compare this with the
# maximum length and return maximum length
maxlen = max(maxlen, r - l + 1)
r += 1

return maxlen

# function which returns
# maximum length of substring
def answer(A, n, k):
    maxlen = 1
    for i in range(26):
        maxlen = max(maxlen, findLen(A, n, k,
                                     chr(i + ord('A'))))
        maxlen = max(maxlen, findLen(A, n, k,
                                     chr(i + ord('a'))))

    return maxlen

# Driver Code
if __name__ == "__main__":
    n = 5
    k = 2
    A = "ABABA"
    print("Maximum length =",
          answer(A, n, k))

n = 6
k = 4
```



```
B = "HHHHHHH"
print("Maximum length =",
      answer(B, n, k))
```

```
# This code is contributed by
# sanjeev2552
```

C#

```
// C# program to find maximum length equal
// character string with k changes
using System;

class GFG
{
    // method to find the maximum length of
    // substring having character ch
    public static int findLen(string A, int n,
                              int k, char ch)
    {
        int maxlen = 1;
        int cnt = 0;
        int l = 0, r = 0;

        // traverse the whole string
        while (r < n)
        {
            // if character is
            // not same as ch
            // increase count
            if (A[r] != ch)
            {
                ++cnt;
            }

            // While count > k traverse
            // the string again until
            // count becomes less than
            // k and decrease the
            // count when characters
            // are not same
            while (cnt > k)
```



```
{
    if (A[l] != ch)
    {
        --cnt;
    }
    ++l;
}

// length of substring
// will be rightIndex -
// leftIndex + 1.
// Compare this with the maximum
// length and return maximum length
maxlen = Math.Max(maxlen, r - l + 1);
++r;
}
return maxlen;
}

// method which returns
// maximum length of substring
public static int answer(string A, int n, int k)
{
    int maxlen = 1;
    for (int i = 0; i < 26; ++i)
    {
        maxlen = Math.Max(maxlen,
            findLen(A, n, k, (char)(i + 'A')));

        maxlen = Math.Max(maxlen,
            findLen(A, n, k, (char)(i + 'a')));
    }
    return maxlen;
}

// Driver Method
public static void Main(string[] args)
{
    int n = 5, k = 2;
    string A = "ABABA";
    Console.WriteLine("Maximum length = "
        + answer(A, n, k));

    n = 6;
    k = 4;
```




```
        string B = "HHHHHH";
        Console.WriteLine("Maximum length = "
                           + answer(B, n, k));
    }
}

// This code is contributed by Shrikant13
```

PHP

```
<?php
// PHP program to find maximum length equal
// character string with k changes

// function to find the maximum length
// of substring having character ch
function findLen($A, $n, $k, $ch)
{
    $maxlen = 1; $cnt = 0;
    $l = 0; $r = 0;

    // traverse the whole string
    while ($r < $n)
    {
        /* if character is not same as
        ch increase count */
        if ($A[$r] != $ch)
            ++$cnt;

        /* While count > k traverse the string
        again until count becomes less than k
        and decrease the count when characters
        are not same */
        while ($cnt > $k)
        {
            if ($A[$l] != $ch)
                --$cnt;
            ++$l;
        }

        /* length of substring will be rightIndex -
        leftIndex + 1. Compare this with the maximum
        length and return maximum length */
        $maxlen = max($maxlen, $r - $l + 1);
    }
}
```



```

        ++$r;
    }
    return $maxlen;
}

// function which returns maximum
// length of substring
function answer($A, $n, $k)
{
    $maxlen = 1;
    for ($i = 0; $i < 26; ++$i)
    {
        $maxlen = max($maxlen,
                      findLen($A, $n, $k, $i + 'A'));
        $maxlen = max($maxlen,
                      findLen($A, $n, $k, $i + 'a'));
    }
    return $maxlen;
}

// Driver code
$n = 5; $k = 2; $A = "ABABA";
echo "Maximum length = " . answer($A, $n, $k) . "\n";

$n = 6; $k = 4; $B = "HHHHHH";
echo "Maximum length = " . answer($B, $n, $k) . "\n";

// This code is contributed by ita_c
?>

```

Javascript

```

<script>
// Javascript program to find maximum length equal
// character string with k changes

// method to find the maximum length of
// substring having character ch
function findLen(A,n,k,ch)
{
    let maxlen = 1;
    let cnt = 0;
    let l = 0, r = 0;

```



```
// traverse the whole string
while (r < n) {

    /* if character is not same as ch
    increase count */
    if (A[r] != ch)
        ++cnt;

    /* While count > k traverse the string
    again until count becomes less than k
    and decrease the count when characters
    are not same */
    while (cnt > k) {
        if (A[l] != ch)
            --cnt;
        ++l;
    }

    /* length of substring will be rightIndex -
    leftIndex + 1. Compare this with the maximum
    length and return maximum length */
    maxlen = Math.max(maxlen, r - l + 1);
    ++r;
}
return maxlen;
}

// method which returns maximum length of substring
function answer(A,n,k)
{
    let maxlen = 1;
    for (let i = 0; i < 26; ++i) {
        maxlen = Math.max(maxlen, findLen(A, n, k, String.fromCharCode(i)))
        maxlen = Math.max(maxlen, findLen(A, n, k, String.fromCharCode(i)))
    }
    return maxlen;
}

// Driver Method
let n = 5, k = 2;
let A = "ABABA";
document.write("Maximum length = " + answer(A, n, k)+"<br>");

n = 6; k = 4;
```



```
let B = "HHHHHH";  
document.write("Maximum length = " + answer(B, n, k));  
  
//This code is contributed by rag2127
```

</script>

Output

Maximum length = 5

Maximum length = 6

Time Complexity: $O(n)$

Auxiliary Space: $O(1)$

This article is contributed by **Niteesh Kumar**. If you like GeeksforGeeks and would like to contribute, you can also write an article using write.geeksforgeeks.org or mail your article to review-team@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

**DSA Self-Paced
Course**

- ✓ Curated by experts
- ✓ Trusted by 1 Lac+ students.

Enrol Now


GeeksforGeeks

Liked 29



Previous

**Largest substring with same
Characters**

Next

**Smallest window that
contains all characters of
string itself**



RECOMMENDED ARTICLES

Page : 1 2 3

01 Length of longest substring having all characters as K
16, Jul 19

05 Generate an N-length string having longest palindromic substring of length K
14, Dec 20

02 Maximum length of a substring required to be flipped repeatedly to make all characters of binary string equal to 0
05, Aug 21

06 Minimum substring removals required to make all remaining characters of a string same
03, Jan 21

03 Check if a K-length substring exists having only 2 distinct characters, each with frequency greater than $K/3$
30, Nov 21

07 Substring of length K having maximum frequency in the given string
16, Sep 20

04 Modify string by inserting characters such that every K-length substring consists of unique characters only
14, Feb 21

08 Minimize changes to make all characters equal by changing vowel to consonant and vice versa
08, Sep 21



A-143, 9th Floor, Sovereign Corporate Tower,
Sector-136, Noida, Uttar Pradesh - 201305

Article Contributed By :

feedback@geeksforgeeks.org



Vote for difficulty
Current difficulty : Hard

[Learn](#)

About Us

EasyNormalrMediumHardExpert

In Media

Contact Us

Algorithms

Data Structures

SDE Cheat Sheet

Machine learning

Improved By: [shrikanth13](#), [ukasp](#), [sanjeev2552](#), [rag2123](#), [shivanandirj9](#), [hardikkoriintern](#)

Privacy Policy

Copyright Policy

Article Tags : [Misc](#), [Strings](#)

Practice Tags : [Misc](#), [Strings](#), [Misc](#)

News

Top News

Improve ArticleReport Issue

Technology

Work & Career

Business

Finance

Lifestyle

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Knowledge

CS Subjects

Video Tutorials

Courses

Languages

Python

Java

CPP

Golang

C#

SQL

Kotlin

Load Comments

Web Development

Web Tutorials

Django Tutorial

HTML

JavaScript

Bootstrap

ReactJS

NodeJS

Contribute

Write an Article

Improve an Article

Pick Topics to Write

Write Interview Experience

Internships

Video Internship

@geeksforgeeks , Some rights reserved

Do Not Sell My Personal Information

