

Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes
Attend the Live Class

Register Now

Subarray Sum Equals K

November 12, 2021

in f t




Table Of Contents

Problem Statement

Naive Approach

C++ Code

Java Code

Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes


Attend the Live Class

Register Now

Problem Statement

Given an array $a[]$, find the number of subarrays in it, which have a sum of k .

Subarray: A subarray of an array is formed by deleting some(possibly zero) elements from the beginning or end of the array.



The red region shows a subarray of the original array.

Sample Test Cases

Input 1: $a = [10, 2, -2, -20, 10]$, $k = -10$

Output 1: 3



Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes

Attend the Live Class

Register Now

Explanation 2: All subarrays of length 2 are valid subarrays in this case, and there are a total of 2 such subarrays.

Naive Approach

The naive approach is to generate all the subarrays of the array and calculate their sum. Whenever we find a subarray with a sum equal to **k**, we increment our counter by 1. Finally, we return the count which keeps track of the number of subarrays with a sum equal to **k**.

Since there are a total of $(n * (n + 1)) / 2$ subarrays of an array, and each subarray will take **O(n)** time to traverse and calculate their sum, the required time complexity of this approach will be cubic in nature.

C++ Code

```
int countSubarraysWithSumK(vector < int > & a, int K) {
    int n = a.size();
    int count = 0;
    for (int i = 0; i < n; i++) {
        for (int j = i; j < n; j++) {
            int sum = 0;
            for (int k = i; k <= j; k++) {
```



Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes
Attend the Live Class

[Register Now](#)

Java Code

```
public static int countSubarraysWithSumK(int[] a, int K) {  
    int n = a.length;  
    int count = 0;  
    for (int i = 0; i < n; i++) {  
        for (int j = i; j < n; j++) {  
            int sum = 0;  
            for (int k = i; k <= j; k++) {  
                sum += a[k];  
            }  
            count += (sum == K ? 1 : 0);  
        }  
    }  
    return count;  
}
```

Python Code

```
def countSubarrayswithSumK(a, K):  
    n = len(a)  
    count = 0
```



Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes

Attend the Live Class

Register Now

Complexity Analysis

- Time Complexity: $O(n^3)$
- Space Complexity: $O(1)$

Optimal Approach

We can solve this problem in linear time complexity using a **hashmap-based** approach. The algorithm is described as follows:

- Traverse the array, and keep track of the current running sum up to the **ith** index in a variable, say **sum**.
- Also, hash the different values of the **sum** obtained so far, into a hashmap.
- If the **sum** equals **k** at any point in the array, increment the count of subarrays by 1.
- If this value of **sum** has exceeded **k** by a value of **sum - k**, we can find the number of subarrays, found so far with **sum = sum - k**, from our hashmap. Observe that if these subarrays are deleted from our current array, we will again obtain a sum of **k**. So, we add to our answer, the **number of subarrays with sum = sum - k found so far** from our hashmap.
- After traversing through the entire array once and applying the above steps, return the calculated result.





Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes

Attend the Live Class

Register Now

C++ Implementation

```
int countSubarraysWithSumK(vector < int > & a, int K) {
    int n = a.size();
    unordered_map < int, int > hash;
    int count = 0, sum = 0;
    for (int i = 0; i < n; i++) {
        sum += a[i];
        if (sum == K) {
            count++;
        }
        if (hash.find(sum - K) != hash.end()) {
            count += hash[sum - K];
        }
        hash[sum]++;
    }
    return count;
}
```

Java Implementation

```
public static int countSubarraysWithSumK(int[] a, int K) {
    int n = a.length;
```



Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes

Attend the Live Class

Register Now

```
        count += hash.get(sum - K);
    }
    if (hash.get(sum) != null) {
        hash.put(sum, hash.get(sum) + 1);
    } else {
        hash.put(sum, 1);
    }
}
return count;
}
```

Python Implementation

```
from collections import defaultdict
```

```
def countSubarrayswithSumK(a, K):
    n = len(a)
    hash = defaultdict(lambda: 0)
    count = 0
    sum = 0
    for i in range(n):
        sum += a[i]
        if sum == K:
            count += 1
```



Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes

Attend the Live Class

Register Now

- Time Complexity: $O(n)$
- Space Complexity: $O(1)$

Practice Problem

Subarray With Given XOR

FAQs

Q. What is the time complexity of lookup in a hashmap?

A. The time complexity of lookup in a hashmap is **$O(1)$** amortized.

Q. Why is the number of subarrays of an array given by $(n * (n + 1)) / 2$?

A. The number of subarrays of an array can be calculated as there are,

- 1 subarray of length n
- 2 subarrays of length $n - 1$
-
- n subarrays of length 1

So, the total number of subarrays count out to a total of $1 + 2 + 3 + \dots + n = (n * (n + 1)) / 2$.

Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes
Attend the Live Class

[Register Now](#)



CODING PROBLEMS

Graph Coloring Problem


November 12, 2021

[NEXT POST](#)

CODING PROBLEMS

Reverse Words in a String

November 12, 2021



SCALER 

Software Developers Invited

Create a
**LinkedIn
Profile**
that 'Clicks' with **Recruiters**

 **FREE
MASTERCLASS** | By **Akhil Sharma**
Founder, Myrl.tech

 25th July, Monday |  8-9 PM

[BOOK NOW](#)



Categories

[Applications](#)

[Architecture](#)

[Books](#)

[Careers](#)

[Characteristics](#)

[Coding Problems](#)

[Commands](#)

[Compare](#)

[Components](#)

[Courses](#)

Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes
Attend the Live Class

Register Now

November 12, 2021

Libraries

Methodologies

**Table Of Contents [show]**

- Problem Statement
- Sample Test Cases
- Approach
 - Naive Approach
 - C++ Code
 - Java Code
 - Python Code



Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes
Attend the Live Class

[Register Now](#)

Problem Statement

Given a **sentence** of the form of words separated by spaces, return a new sentence that consists of the words of the original sentence in the reverse order.

Sample Test Cases

Input 1:

s = "Hello World"

Output 1:

World Hello

Input 2:

s = "This is a good day"

Output 2:

day good a is This



Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes
Attend the Live Class

[Register Now](#)

The naive approach for this problem is to **split** the string into individual words using the **spaces** as delimiters, and then print the words in reverse order.



Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes

Attend the Live Class

Register Now

```
vector < string > words;
string word = "";
for (char c: s) {
    if (c == ' ') {
        words.push_back(word);
        word = "";
    } else {
        word += c;
    }
}
words.push_back(word);
string ans = "";
reverse(words.begin(), words.end());
for (auto x: words) {
    ans += x;
    ans += " ";
}
return ans;
}
```

Java Code

```
public static void reverse(char[] ch, int left, int right) {
    while (left <= right) {
        char temp = ch[right];
```



Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes

Attend the Live Class

Register Now

```
int beg = 0;
for (int i = 0; i < ch.length; i++) {
    if (ch[i] == ' ') {
        reverse(ch, beg, i);
        beg = i + 1;
    }
}
reverse(ch, beg, ch.length - 1);
reverse(ch, 0, ch.length - 1);
String ans = Arrays.toString(ch);
return ans;
}
```

Python Code

```
def reverse(s, left, right):
    while left <= right:
        s[left], s[right] = s[right], s[left]
        left += 1
        right -= 1
```

```
def reverseByWords(s):
    s = list(s)
    n = len(s)
```



Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes

Attend the Live Class

Register Now

```
return s
```

Complexity Analysis:

- Time Complexity: $O(n)$
- Space Complexity: $O(n)$

Optimal Approach

The optimal approach tries to swap the words of the string from the beginning and end, using a **two-pointers-based** approach, to reverse the string in **constant space**. The algorithm is as follows:

- Convert the string into an array of strings, which will store the words.
- Initialize the 2 pointers **left** and **right** to **0** and **string.length() - 1** respectively.
- While the **left** pointer does not exceed the **right** pointer, swap the elements at the **left** and **right** pointer, move the **left** pointer forward and the **right** pointer backward by **1** place.
- Finally, return the final calculated string.

Implementation:



Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes

Attend the Live Class

Register Now

```
        words.push_back(str);
        str = "";
    } else {
        str += c;
    }
}
words.push_back(str);
int left = 0, right = words.size() - 1;
while (left <= right) {
    swap(words[left], words[right]);
    left++;
    right--;
}
string ans = "";
for (auto x: words) {
    ans += x;
    ans += " ";
}
ans.pop_back();
return ans;
}
```

Java Code

```
public static String reverseBvWords(String s) {
```




Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes

Attend the Live Class

[Register Now](#)

```
}  
String ans = String.join(" ", words);  
return ans;  
}
```

Python Code

```
def reverseByWords(s):  
    s = s.split(" ")  
    left = 0  
    right = len(s) - 1  
    while left <= right:  
        s[left], s[right] = s[right], s[left]  
        left += 1  
        right -= 1  
    s = " ".join(s)  
    return s
```

Complexity Analysis:

- Time Complexity: $O(n)$
- Space Complexity: $O(1)$



Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes

Attend the Live Class

Register Now

1. When a problem is asked to be solved in constant space, what should be the thought process?

A. While the idea may vary from problem to problem, **swapping** is a very common method used in problems requiring to be solved in constant space.

2. What is the time complexity of the swap function in C++?

A. The swap function in C++ works in $O(1)$ time complexity.

Reverse Words in a String



PREVIOUS POST

CODING PROBLEMS

Subarray Sum Equals K

November 12, 2021

NEXT POST

Must-know S.O.L.I.D Principles for every Developer

learn how to implement S.O.L.I.D Principles and create robust codes
Attend the Live Class

Register Now



Careers

Characteristics

Coding Problems

Commands

Compare

Components

Courses

Features

Frameworks

IDE

IT Companies

Job Roles

Libraries

Methodologies

Model

Principles

Projects

Resume

Salaries



Must-know S.O.L.I.D Principles for every Developer

**learn how to implement S.O.L.I.D Principles and create robust codes
Attend the Live Class**

Register Now



© 2021 InterviewBit

