



[Array](#) [Matrix](#) [Strings](#) [Hashing](#) [Linked List](#) [Stack](#) [Queue](#) [Binary Tree](#) [Binary Search](#)

Beat the competition and land yourself a top job. [Register for Job-a-thon now!](#)

Given an array `arr[]`, find the maximum $j - i$ such that `arr[j] > arr[i]`

Difficulty Level : Hard • Last Updated : 05 Jul, 2022



Given an array `arr[]`, find the maximum $j - i$ such that `arr[j] > arr[i]`.

Examples :

Input: {34, 8, 10, 3, 2, 80, 30, 33, 1}

Output: 6 ($j = 7, i = 1$)

Input: {9, 2, 3, 4, 5, 6, 7, 8, 18, 0}

Output: 8 ($j = 8, i = 0$)

Input: {1, 2, 3, 4, 5, 6}

Output: 5 ($j = 5, i = 0$)

Input: {6, 5, 4, 3, 2, 1}

Output: -1

[Recommended Practice](#)[Maximum Index](#)[Try It!](#)

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

inner loop when you see an element greater than the picked element and keep updating the maximum $j-i$ so far.



Complete Interview Preparation - Self Paced

By Sandeep Jain Beginner to Advance Level ★★★★★

Find 360 solution to all of your interview woes. Learn 4 years' worth of programming knowledge in just 6 months and ace coding interviews at top tech companies.

[Explore Now](#)

C++

```
// CPP program for the above approach
#include <bits/stdc++.h>
using namespace std;

/* For a given array arr[],
   returns the maximum j - i such
   that arr[j] > arr[i] */
int maxIndexDiff(int arr[], int n)
{
    int maxDiff = -1;
    int i, j;

    for (i = 0; i < n; ++i) {
        for (j = n - 1; j > i; --j) {
            if (arr[j] > arr[i] && maxDiff < (j - i))
                maxDiff = j - i;
        }
    }
}
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

    int arr[] = { 9, 2, 3, 4, 5, 6, 7, 8, 18, 0 };
    int n = sizeof(arr) / sizeof(arr[0]);
    int maxDiff = maxIndexDiff(arr, n);
    cout << "\n" << maxDiff;
    return 0;
}

// This code is contributed
// by Akanksha Rai(Abby_akku)

```

C

```

// C program for the above approach
#include <stdio.h>
/* For a given array arr[],
   returns the maximum j - i such
   that arr[j] > arr[i] */
int maxIndexDiff(int arr[], int n)
{
    int maxDiff = -1;
    int i, j;

    for (i = 0; i < n; ++i) {
        for (j = n - 1; j > i; --j) {
            if (arr[j] > arr[i] && maxDiff < (j - i))
                maxDiff = j - i;
        }
    }

    return maxDiff;
}

int main()
{
    int arr[] = { 9, 2, 3, 4, 5, 6, 7, 8, 18, 0 };
    int n = sizeof(arr) / sizeof(arr[0]);
    int maxDiff = maxIndexDiff(arr, n);
    printf("\n %d", maxDiff);
    getchar();
}

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

Java

```
// Java program for the above approach
class FindMaximum {
    /* For a given array arr[],
       returns the maximum j-i such
       that arr[j] > arr[i] */
    int maxIndexDiff(int arr[], int n)
    {
        int maxDiff = -1;
        int i, j;

        for (i = 0; i < n; ++i) {
            for (j = n - 1; j > i; --j) {
                if (arr[j] > arr[i] && maxDiff < (j - i))
                    maxDiff = j - i;
            }
        }

        return maxDiff;
    }

    /* Driver program to test above functions */
    public static void main(String[] args)
    {
        FindMaximum max = new FindMaximum();
        int arr[] = { 9, 2, 3, 4, 5, 6, 7, 8, 18, 0 };
        int n = arr.length;
        int maxDiff = max.maxIndexDiff(arr, n);
        System.out.println(maxDiff);
    }
}
```

Python3

```
# Python3 program to find the maximum
# j - i such that arr[j] > arr[i]
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

[HIDE AD](#) • [AD VIA BUYSPELLADS](#)

```
def maxIndexDiff(arr, n):
    maxDiff = -1
    for i in range(0, n):
        j = n - 1
        while(j > i):
            if arr[j] > arr[i] and maxDiff < (j - i):
                maxDiff = j - i
            j -= 1

    return maxDiff
```

```
# driver code
arr = [9, 2, 3, 4, 5, 6, 7, 8, 18, 0]
n = len(arr)
maxDiff = maxIndexDiff(arr, n)
print(maxDiff)
```

This article is contributed by Smitha Dinesh Semwal

C#

```
// C# program to find the maximum
// j - i such that arr[j] > arr[i]
using System;
class GFG {
    // For a given array arr[], returns
    // the maximum j-i such that arr[j] > arr[i]
    static int maxIndexDiff(int[] arr, int n)
    {
        int maxDiff = -1;
        int i, j;

        for (i = 0; i < n; ++i) {
            for (j = n - 1; j > i; --j) {
                if (arr[j] > arr[i] && maxDiff < (j - i))
                    maxDiff = j - i;
            }
        }
    }
}
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```
// Driver program
public static void Main()
{
    int[] arr = { 9, 2, 3, 4, 5, 6, 7, 8, 18, 0 };
    int n = arr.Length;
    int maxDiff = maxIndexDiff(arr, n);
    Console.Write(maxDiff);
}
}
// This Code is Contributed by Sam007
```

PHP

```
<?php
// PHP program to find the maximum
// j - i such that arr[j] > arr[i]

// For a given array arr[], returns
// the maximum j - i such that
// arr[j] > arr[i]
function maxIndexDiff($arr, $n)
{
    $maxDiff = -1;

    for ($i = 0; $i < $n; ++$i)
    {
        for ($j = $n - 1; $j > $i; --$j)
        {
            if($arr[$j] > $arr[$i] &&
                $maxDiff < ($j - $i))
                $maxDiff = $j - $i;
        }
    }

    return $maxDiff;
}

// Driver Code
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```
echo $maxDiff ;
```

```
// This code is contributed by Sam007  
?>
```

Javascript

```
<script>  
// JavaScript program for the above approach  
  
/* For a given array arr[],  
returns the maximum j - i such  
that arr[j] > arr[i] */  
function maxIndexDiff(arr, n)  
{  
    let maxDiff = -1;  
    let i, j;  
  
    for (i = 0; i < n; ++i)  
    {  
        for (j = n - 1; j > i; --j)  
        {  
            if (arr[j] > arr[i] && maxDiff < (j - i))  
                maxDiff = j - i;  
        }  
    }  
  
    return maxDiff;  
}  
  
// Driver code  
let arr = [ 9, 2, 3, 4, 5, 6, 7, 8, 18, 0 ];  
let n = arr.length;  
let maxDiff = maxIndexDiff(arr, n);  
document.write(maxDiff);  
  
// This code is contributed by Manoj.  
</script>
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

Time Complexity: $O(n^2)$

Auxiliary Space: $O(1)$

Method 2: Improvising the Brute Force Algorithm and looking for BUD, i.e Bottlenecks, unnecessary and duplicated works. A quick observation actually shows that we have been looking to find the first greatest element traversing from the end of the array to the current index. We can see that we are trying to find the first greatest element again and again for each element in the array. Let's say we have an array with us for example [1, 5, 12, 4, 9] now we know that 9 is the element that is greater than 1, 5, and 4 but why do we need to find that again and again. We can actually keep a track of the maximum number moving from the end to the start of the array. The approach will help us understand better and also this improvisation is great to come up with in an interview.

Approach :

1. Traverse the array from the end and keep a track of the maximum number to the right of the current index including self
2. Now we have a monotonous decreasing array, and we know we can use binary search to find the index of the rightmost greater element
3. Now we will just use binary search for each of the elements in the array and store the maximum difference of the indices and that's it we are done.

C++

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS


```

using namespace std;

int main()
{
    vector<long long int> v{
        34, 8, 10, 3, 2, 80, 30, 33, 1
    };
    int n = v.size();
    vector<long long int> maxFromEnd(n + 1, INT_MIN);

    // create an array maxfromEnd
    for (int i = v.size() - 1; i >= 0; i--) {
        maxFromEnd[i] = max(maxFromEnd[i + 1], v[i]);
    }

    int result = 0;

    for (int i = 0; i < v.size(); i++) {
        int low = i + 1, high = v.size() - 1, ans = i;

        while (low <= high) {
            int mid = (low + high) / 2;

            if (v[i] <= maxFromEnd[mid]) {

                // We store this as current answer and look
                // for further larger number to the right
                // side
                ans = max(ans, mid);
                low = mid + 1;
            }
            else {
                high = mid - 1;
            }
        }
        // keeping a track of the
        // maximum difference in indices
        result = max(result, ans - i);
    }
    cout << result << endl;
}

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

/* C program to implement
the above approach */

/* For a given array arr[],
calculates the maximum j - i
such that arr[j] > arr[i] */
#include <limits.h>
#include <stdio.h>

/* Function for maximum of
two numbers in C */
int max(int num1, int num2)
{
    return (num1 > num2 ) ? num1 : num2;
}

int main()
{
    int v[] = { 34, 8, 10, 3, 2, 80, 30, 33, 1 };
    int n = sizeof(v) / sizeof(v[0]);
    int maxFromEnd[n+1];
    for (int i = 0; i < n+1; i++) {
        maxFromEnd[i] = INT_MIN;
    }
    // create an array maxfromEnd
    for (int i = n - 1; i >= 0; i--) {
        maxFromEnd[i] = max(maxFromEnd[i + 1], v[i]);
    }

    int result = 0;

    for (int i = 0; i < n; i++) {
        int low = i + 1, high = n - 1, ans = i;

        while (low <= high) {
            int mid = (low + high) / 2;

            if (v[i] <= maxFromEnd[mid]) {

                // We store this as current answer and look
                // for further larger number to the right
            }
        }
    }
}

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

        else {
            high = mid - 1;
        }
    }
    // keeping a track of the
    // maximum difference in indices
    result = max(result, ans - i);
}
printf("\n %d", result);
}

/* This code is contributed by Pushpesh Raj */

```

Java

```

// Java program to implement
// the above approach

// For a given array arr[],
// calculates the maximum j - i
// such that arr[j] > arr[i]
import java.util.*;
class GFG{

public static void main(String[] args)
{
    int []v = {34, 8, 10, 3, 2,
               80, 30, 33, 1};
    int n = v.length;
    int []maxFromEnd = new int[n + 1];
    Arrays.fill(maxFromEnd, Integer.MIN_VALUE);

    // Create an array maxfromEnd
    for (int i = v.length - 1; i >= 0; i--)
    {
        maxFromEnd[i] = Math.max(maxFromEnd[i + 1],
                                v[i]);
    }

    int result = 0;

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

        ans = i;

    while (low <= high)
    {
        int mid = (low + high) / 2;

        if (v[i] <= maxFromEnd[mid])
        {
            // We store this as current
            // answer and look for further
            // larger number to the right side
            ans = Math.max(ans, mid);
            low = mid + 1;
        }
        else
        {
            high = mid - 1;
        }
    }

    // Keeping a track of the
    // maximum difference in indices
    result = Math.max(result, ans - i);
}
System.out.print(result + "\n");
}
}

// This code is contributed by shikhasingrajput

```

Python3

```

# Python3 program to implement
# the above approach

# For a given array arr,
# calculates the maximum j - i
# such that arr[j] > arr[i]

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

n = len(v);
maxFromEnd = [-38749432] * (n + 1);

# Create an array maxfromEnd
for i in range(n - 1, 0, -1):
    maxFromEnd[i] = max(maxFromEnd[i + 1],
                        v[i]);

result = 0;

for i in range(0, n):
    low = i + 1; high = n - 1; ans = i;

    while (low <= high):
        mid = int((low + high) / 2);

        if (v[i] <= maxFromEnd[mid]):

            # We store this as current
            # answer and look for further
            # larger number to the right side
            ans = max(ans, mid);
            low = mid + 1;
        else:
            high = mid - 1;

    # Keeping a track of the
    # maximum difference in indices
    result = max(result, ans - i);

print(result, end = "");

# This code is contributed by Rajput-Ji

```

C#

```

// C# program to implement
// the above approach

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

class GFG{

public static void Main(String[] args)
{
    int []v = {34, 8, 10, 3, 2,
               80, 30, 33, 1};
    int n = v.Length;
    int []maxFromEnd = new int[n + 1];

    for (int i = 0;
         i < maxFromEnd.Length; i++)
        maxFromEnd[i] = int.MinValue;

    // Create an array maxfromEnd
    for (int i = v.Length - 1;
         i >= 0; i--)
    {
        maxFromEnd[i] = Math.Max(maxFromEnd[i + 1],
                                  v[i]);
    }

    int result = 0;

    for (int i = 0; i < v.Length; i++)
    {
        int low = i + 1,
            high = v.Length - 1,
            ans = i;

        while (low <= high)
        {
            int mid = (low + high) / 2;

            if (v[i] <= maxFromEnd[mid])
            {
                // We store this as current
                // answer and look for further
                // larger number to the right side
                ans = Math.Max(ans, mid);
                low = mid + 1;
            }
        }
    }
}

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

    }

    // Keeping a track of the
    // maximum difference in indices
    result = Math.Max(result, ans - i);
}
Console.Write(result + "\n");
}
}

// This code is contributed by shikhasingrajput

```

Javascript

```

<script>

// Javascript program to implement
// the above approach

// For a given array []arr,
// calculates the maximum j - i
// such that arr[j] > arr[i]

let v = [34, 8, 10, 3, 2, 80, 30, 33, 1];
let n = v.length;
let maxFromEnd = new Array(n + 1);

for (let i = 0; i < maxFromEnd.length; i++)
    maxFromEnd[i] = Number.MIN_VALUE;

// Create an array maxfromEnd
for (let i = v.length - 1; i >= 0; i--)
{
    maxFromEnd[i] = Math.max(maxFromEnd[i + 1], v[i]);
}

let result = 0;

for (let i = 0; i < v.length; i++)
{

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

        let mid = parseInt((low + high) / 2, 10);

        if (v[i] <= maxFromEnd[mid])
        {
            // We store this as current
            // answer and look for further
            // larger number to the right side
            ans = Math.max(ans, mid);
            low = mid + 1;
        }
        else
        {
            high = mid - 1;
        }
    }

    // Keeping a track of the
    // maximum difference in indices
    result = Math.max(result, ans - i);
}
document.write(result);

</script>

```

Output

6

Time complexity : $O(N \cdot \log(N))$

Space complexity: $O(N)$

Method 3 $O(n \log n)$: Use hashing and sorting to solve this problem in less than quadratic complexity after taking special care of the duplicates.

Approach :

1. Traverse the array and store the index of each element in a list (to

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

and j.

4. For j consider the last index from the list of possible indexes of the element and for i consider the first index from the list. (As the index was appended in ascending order).
5. Keep updating the max difference till the end of the array.

Below is the implementation of the above approach:

C++

```
// C++ implementation of
// the hashmap approach
#include <bits/stdc++.h>
using namespace std;

// Function to find maximum
// index difference
int maxIndexDiff(vector<int>& arr, int n)
{
    // Initialise unordered_map
    unordered_map<int, vector<int> > hashmap;

    // Iterate from 0 to n - 1
    for (int i = 0; i < n; i++) {
        hashmap[arr[i]].push_back(i);
    }

    // Sort arr
    sort(arr.begin(), arr.end());
    int maxDiff = INT_MIN;
    int temp = n;

    // Iterate from 0 to n - 1
    for (int i = 0; i < n; i++) {
        if (temp > hashmap[arr[i]][0]) {
            temp = hashmap[arr[i]][0];
        }
    }
}
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

    }
    return maxDiff;
}

// Driver Code
int main()
{

    int n = 9;
    vector<int> arr{ 34, 8, 10, 3, 2, 80, 30, 33, 1 };

    // Function Call
    int ans = maxIndexDiff(arr, n);
    cout << "The maxIndexDiff is : " << ans << endl;

    return 1;
}

```

Java

```

// Java implementation of
// the hashmap approach
import java.io.*;
import java.util.*;

class GFG{

    // Function to find maximum
    // index difference
    static int maxIndexDiff(ArrayList<Integer> arr, int n)
    {

        // Initialise unordered_map
        Map<Integer,
        ArrayList<Integer>> hashmap = new HashMap<Integer,
        ArrayList<Integer>>();

        // Iterate from 0 to n - 1
        for(int i = 0; i < n; i++)

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

    }
    else
    {
        hashmap.put(arr.get(i), new ArrayList<Integer>());
        hashmap.get(arr.get(i)).add(i);
    }
}

// Sort arr
Collections.sort(arr);
int maxDiff = Integer.MIN_VALUE;
int temp = n;

// Iterate from 0 to n - 1
for(int i = 0; i < n; i++)
{
    if (temp > hashmap.get(arr.get(i)).get(0))
    {
        temp = hashmap.get(arr.get(i)).get(0);
    }
    maxDiff = Math.max(maxDiff,
        hashmap.get(arr.get(i)).get(
            hashmap.get(arr.get(i)).size() - 1) - temp);
}
return maxDiff;
}

// Driver Code
public static void main(String[] args)
{
    int n = 9;
    ArrayList<Integer> arr = new ArrayList<Integer>(
        Arrays.asList(34, 8, 10, 3, 2, 80, 30, 33, 1));

    // Function Call
    int ans = maxIndexDiff(arr, n);

    System.out.println("The maxIndexDiff is : " + ans);
}
}

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSSELLADS

```

# Python3 implementation of the above approach
n = 9
a = [34, 8, 10, 3, 2, 80, 30, 33, 1]

# To store the index of an element.
index = dict()
for i in range(n):
    if a[i] in index:
        # append to list (for duplicates)
        index[a[i]].append(i)
    else:
        # if first occurrence
        index[a[i]] = [i]

# sort the input array
a.sort()
maxDiff = 0

# Temporary variable to keep track of minimum i
temp = n
for i in range(n):
    if temp > index[a[i]][0]:
        temp = index[a[i]][0]
    maxDiff = max(maxDiff, index[a[i]][-1]-temp)

print(maxDiff)

```

C#

```

// C# implementation of
// the hashmap approach

using System;
using System.Collections.Generic;

public class GFG

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

static int maxIndexDiff(List<int> arr, int n)
{
    Dictionary<int,List<int>> hashmap = new Dictionary<int,List<int>>>();

    // Iterate from 0 to n - 1
    for(int i = 0; i < n; i++)
    {
        if(hashmap.ContainsKey(arr[i]))
        {
            hashmap[arr[i]].Add(i);
        }
        else
        {
            hashmap.Add(arr[i], new List<int>());
            hashmap[arr[i]].Add(i);
        }
    }

    // Sort arr
    arr.Sort();

    int maxDiff = -1;
    int temp = n;

    // Iterate from 0 to n - 1
    for(int i = 0; i < n; i++)
    {
        if(temp > hashmap[arr[i]][0] )
        {
            temp = hashmap[arr[i]][0];
        }
        maxDiff = Math.Max(maxDiff,hashmap[arr[i]][hashmap[arr[i]].Count - 1] - temp);
    }
    return maxDiff;
}

// Driver Code
static public void Main (){
    int n = 9;
    List<int> arr = new List<int>();
    arr.Add(34);

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

arr.Add(80);
arr.Add(30);
arr.Add(33);
arr.Add(1);

// Function Call
int ans = maxIndexDiff(arr, n);

Console.WriteLine("The maxIndexDiff is : " + ans );
}
}

// This code is contributed by rag2127.

```

Javascript

```

<script>
// JavaScript implementation of
// the hashmap approach

// Function to find maximum
// index difference
function maxIndexDiff(arr,n)
{

    // Initialise map in JavaScript
    let hashmap = new Map()

    // Iterate from 0 to n - 1
    for (let i = 0; i < n; i++) {

        hashmap[arr[i]] = hashmap[arr[i]] || []
        hashmap[arr[i]].push(i)

    }

    // Sort arr
    arr.sort((a,b)=> (a - b))

    let maxDiff = 0

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

        if (temp > hashmap[arr[i]][0]) {
            temp = hashmap[arr[i]][0]
        }
        maxDiff = Math.max( maxDiff,hashmap[arr[i]][hashmap[arr[i]].length-1])
    }
    return maxDiff
}

// Driver Code

let n = 9
const arr = [ 34, 8, 10, 3, 2, 80, 30, 33, 1 ]

// Function Call
let ans = maxIndexDiff(arr, n)
document.write(`The maxIndexDiff is : ${ans}`)

// This code is contributed by shinjanpatra
</script>

```

Output

The maxIndexDiff is : 6

Time complexity : $O(N \cdot \log(N))$

Auxiliary Space: $O(N)$

Method 4 (Efficient): To solve this problem, we need to get two optimum indexes of arr[]: left index i and right index j. For an element arr[i], we do not need to consider arr[i] for left index if there is an element smaller than arr[i] on left side of arr[i]. Similarly, if there is a greater element on right side of arr[j] then we do not need to consider this j for the right index. So we construct two auxiliary arrays LMin[] and RMax[] such that LMin[i] holds the smallest element on left side of

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

traversing LMin[] and RMax[] if we see that LMin[i] is greater than RMax[j], then we must move ahead in LMin[] (or do i++) because all elements on left of LMin[i] are greater than or equal to LMin[i]. Otherwise, we must move ahead in RMax[j] to look for a greater j - i value.

Thanks to celicom for suggesting the algorithm for this method.

Working Example:

Lets consider any example [7 3 1 8 9 10 4 5 6]

what is maxRight ?

Filling from right side 6 is first element now $6 > 5$ so again we fill 6 till we reach $10 > 6$:

[10 10 10 10 10 10 6 6 6] this is maxR

[7 3 1 1 1 1 1 1 1] this is minL

now we see that how to reach answer from these to and its proof !!!

lets compare first elements of the arrays now we see $10 > 7$,

now we increase maxR by 1 till it becomes lesser than 7 i.e at index 5

hence answer till now is. $5 - 0 = 5$

now we will increase minL we get 3 which is lesser than 6 so we increase maxR till it reaches last index and the answer becomes $8 - 1 = 7$

so we see how we are getting correct answer

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

before index i.

in previous hint, make 2 arrays,

First, will store smallest occurring element before the element

Second, will store largest occurring element after the element

Traverse the Second array, till the element in second array is larger than or equal to First array, and store the index difference.

And if it becomes smaller, traverse the first array till it again becomes larger.

And store the max difference of this index difference.

Below is the implementation of the above approach:

C++

```
#include <bits/stdc++.h>
using namespace std;

/* For a given array arr[],
   returns the maximum j - i such that
   arr[j] > arr[i] */
int maxIndexDiff(int arr[], int n)
{
    int maxDiff;
    int i, j;

    int* LMin = new int[(sizeof(int) * n)];
    int* RMax = new int[(sizeof(int) * n)];

    /* Construct LMin[] such that
       LMin[i] stores the minimum value
       from (arr[0], arr[1], ... arr[i]) */
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSSELLADS

```

/* Construct RMax[] such that
RMax[j] stores the maximum value from
(arr[j], arr[j+1], ..arr[n-1]) */
RMax[n - 1] = arr[n - 1];
for (j = n - 2; j >= 0; --j)
    RMax[j] = max(arr[j], RMax[j + 1]);

/* Traverse both arrays from left to right
to find optimum j - i. This process is similar to
merge() of MergeSort */
i = 0, j = 0, maxDiff = -1;
while (j < n && i < n) {
    if (LMin[i] <= RMax[j]) {
        maxDiff = max(maxDiff, j - i);
        j = j + 1;
    }
    else
        i = i + 1;
}

return maxDiff;
}

// Driver Code
int main()
{
    int arr[] = { 9, 2, 3, 4, 5,
                  6, 7, 8, 18, 0 };
    int n = sizeof(arr) / sizeof(arr[0]);
    int maxDiff = maxIndexDiff(arr, n);
    cout << maxDiff;
    return 0;
}

// This code is contributed by rathbhupendra

```

C

```
#include <stdio.h>
```



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

}

int min(int x, int y)
{
    return x < y ? x : y;
}

/* For a given array arr[], returns the maximum j - i such that
   arr[j] > arr[i] */
int maxIndexDiff(int arr[], int n)
{
    int maxDiff;
    int i, j;

    int* LMin = (int*)malloc(sizeof(int) * n);
    int* RMax = (int*)malloc(sizeof(int) * n);

    /* Construct LMin[] such that LMin[i] stores the minimum value
       from (arr[0], arr[1], ... arr[i]) */
    LMin[0] = arr[0];
    for (i = 1; i < n; ++i)
        LMin[i] = min(arr[i], LMin[i - 1]);

    /* Construct RMax[] such that RMax[j] stores the maximum value
       from (arr[j], arr[j+1], ..arr[n-1]) */
    RMax[n - 1] = arr[n - 1];
    for (j = n - 2; j >= 0; --j)
        RMax[j] = max(arr[j], RMax[j + 1]);

    /* Traverse both arrays from left to right to find optimum j - i
       This process is similar to merge() of MergeSort */
    i = 0, j = 0, maxDiff = -1;
    while (j < n && i < n) {
        if (LMin[i] <= RMax[j]) {
            maxDiff = max(maxDiff, j - i);
            j = j + 1;
        }
        else
            i = i + 1;
    }
}

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

int main()
{
    int arr[] = { 9, 2, 3, 4, 5, 6, 7, 8, 18, 0 };
    int n = sizeof(arr) / sizeof(arr[0]);
    int maxDiff = maxIndexDiff(arr, n);
    printf("\n %d", maxDiff);
    getchar();
    return 0;
}

```

Java

```

class FindMaximum {
    /* Utility Functions to get max and minimum of two integers */
    int max(int x, int y)
    {
        return x > y ? x : y;
    }

    int min(int x, int y)
    {
        return x < y ? x : y;
    }

    /* For a given array arr[], returns the maximum j-i such that
       arr[j] > arr[i] */
    int maxIndexDiff(int arr[], int n)
    {
        int maxDiff;
        int i, j;

        int RMax[] = new int[n];
        int LMin[] = new int[n];

        /* Construct LMin[] such that LMin[i] stores the minimum value
           from (arr[0], arr[1], ... arr[i]) */
        LMin[0] = arr[0];
        for (i = 1; i < n; ++i)
            LMin[i] = min(arr[i], LMin[i - 1]);
    }
}

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

        RMax[j] = max(arr[j], RMax[j + 1]);

    /* Traverse both arrays from left to right to find optimum j - i
       This process is similar to merge() of MergeSort */
    i = 0;
    j = 0;
    maxDiff = -1;
    while (j < n && i < n) {
        if (LMin[i] <= RMax[j]) {
            maxDiff = max(maxDiff, j - i);
            j = j + 1;
        }
        else
            i = i + 1;
    }

    return maxDiff;
}

/* Driver program to test the above functions */
public static void main(String[] args)
{
    FindMaximum max = new FindMaximum();
    int arr[] = { 9, 2, 3, 4, 5, 6, 7, 8, 18, 0 };
    int n = arr.length;
    int maxDiff = max.maxIndexDiff(arr, n);
    System.out.println(maxDiff);
}
}

```

Python3

```

# Utility Functions to get max
# and minimum of two integers
def max(a, b):
    if(a > b):
        return a
    else:
        return b

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

    return b

# For a given array arr[],
# returns the maximum j - i
# such that arr[j] > arr[i]
def maxIndexDiff(arr, n):
    maxDiff = 0;
    LMin = [0] * n
    RMax = [0] * n

    # Construct LMin[] such that
    # LMin[i] stores the minimum
    # value from (arr[0], arr[1],
    # ... arr[i])
    LMin[0] = arr[0]
    for i in range(1, n):
        LMin[i] = min(arr[i], LMin[i - 1])

    # Construct RMax[] such that
    # RMax[j] stores the maximum
    # value from (arr[j], arr[j + 1],
    # ..arr[n-1])
    RMax[n - 1] = arr[n - 1]
    for j in range(n - 2, -1, -1):
        RMax[j] = max(arr[j], RMax[j + 1]);

    # Traverse both arrays from left
    # to right to find optimum j - i
    # This process is similar to
    # merge() of MergeSort
    i, j = 0, 0
    maxDiff = -1
    while (j < n and i < n):
        if (LMin[i] <= RMax[j]):
            maxDiff = max(maxDiff, j - i)
            j = j + 1
        else:
            i = i + 1

    return maxDiff

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

n = len(arr)
maxDiff = maxIndexDiff(arr, n)
print (maxDiff)

# This code is contributed
# by gautam karakoti

```

C#

```

// C# program to find the maximum
// j - i such that arr[j] > arr[i]
using System;

class GFG {
    // Utility Functions to get max
    // and minimum of two integers
    static int max(int x, int y)
    {
        return x > y ? x : y;
    }

    static int min(int x, int y)
    {
        return x < y ? x : y;
    }

    // For a given array arr[], returns
    // the maximum j-i such that arr[j] > arr[i]
    static int maxIndexDiff(int[] arr, int n)
    {
        int maxDiff;
        int i, j;

        int[] RMax = new int[n];
        int[] LMin = new int[n];

        // Construct LMin[] such that LMin[i]
        // stores the minimum value
        // from (arr[0], arr[1], ... arr[i])
        LMin[0] = arr[0];
    }
}

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

// RMax[j] stores the maximum value
// from (arr[j], arr[j+1], ..arr[n-1])
RMax[n - 1] = arr[n - 1];
for (j = n - 2; j >= 0; --j)
    RMax[j] = max(arr[j], RMax[j + 1]);

// Traverse both arrays from left
// to right to find optimum j - i
// This process is similar to merge()
// of MergeSort
i = 0;
j = 0;
maxDiff = -1;
while (j < n && i < n) {
    if (LMin[i] <= RMax[j]) {
        maxDiff = max(maxDiff, j - i);
        j = j + 1;
    }
    else
        i = i + 1;
}

return maxDiff;
}

// Driver program
public static void Main()
{

    int[] arr = { 9, 2, 3, 4, 5, 6, 7, 8, 18, 0 };
    int n = arr.Length;
    int maxDiff = maxIndexDiff(arr, n);
    Console.Write(maxDiff);
}
}
// This Code is Contributed by Sam007

```

PHP

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS


```

// For a given array arr[],
// returns the maximum j - i
// such that arr[j] > arr[i]
function maxIndexDiff($arr, $n)
{
    $maxDiff = 0;
    $LMin = array_fill(0, $n, NULL);
    $RMax = array_fill(0, $n, NULL);

    // Construct LMin[] such that
    // LMin[i] stores the minimum
    // value from (arr[0], arr[1],
    // ... arr[i])
    $LMin[0] = $arr[0];
    for($i = 1; $i < $n; $i++)
        $LMin[$i] = min($arr[$i],
                        $LMin[$i - 1]);

    // Construct RMax[] such that
    // RMax[j] stores the maximum
    // value from (arr[j], arr[j+1],
    // ..arr[n-1])
    $RMax[$n - 1] = $arr[$n - 1];
    for($j = $n - 2; $j >= 0; $j--)
        $RMax[$j] = max($arr[$j],
                        $RMax[$j + 1]);

    // Traverse both arrays from left
    // to right to find optimum j - i
    // This process is similar to
    // merge() of MergeSort
    $i = 0;
    $j = 0;
    $maxDiff = -1;
    while ($j < $n && $i < $n)
        if ($LMin[$i] <= $RMax[$j])
        {
            $maxDiff = max($maxDiff, $j - $i);
            $j = $j + 1;
        }
        else

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```
// Driver Code
$arr = array(9, 2, 3, 4, 5,
            6, 7, 8, 18, 0);
$n = sizeof($arr);
$maxDiff = maxIndexDiff($arr, $n);
echo $maxDiff;

// This code is contributed
// by ChitraNayal
?>
```

Javascript

```
<script>
    // Javascript program to find the maximum
    // j - i such that arr[j] > arr[i]

    // Utility Functions to get max
    // and minimum of two integers
    function max(x, y)
    {
        return x > y ? x : y;
    }

    function min(x, y)
    {
        return x < y ? x : y;
    }

    // For a given array arr[], returns
    // the maximum j-i such that arr[j] > arr[i]
    function maxIndexDiff(arr, n)
    {
        let maxDiff;
        let i, j;

        let RMax = new Array(n);
        let LMin = new Array(n);
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

    for (i = 1; i < n; ++i)
        LMin[i] = min(arr[i], LMin[i - 1]);

    // Construct RMax[] such that
    // RMax[j] stores the maximum value
    // from (arr[j], arr[j+1], ..arr[n-1])
    RMax[n - 1] = arr[n - 1];
    for (j = n - 2; j >= 0; --j)
        RMax[j] = max(arr[j], RMax[j + 1]);

    // Traverse both arrays from left
    // to right to find optimum j - i
    // This process is similar to merge()
    // of MergeSort
    i = 0;
    j = 0;
    maxDiff = -1;
    while (j < n && i < n) {
        if (LMin[i] <= RMax[j]) {
            maxDiff = max(maxDiff, j - i);
            j = j + 1;
        }
        else
            i = i + 1;
    }

    return maxDiff;
}

let arr = [ 9, 2, 3, 4, 5, 6, 7, 8, 18, 0 ];
let n = arr.length;
let maxDiff = maxIndexDiff(arr, n);
document.write(maxDiff);
</script>

```

Output

8

Time Complexity: $O(n)$

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

[HIDE AD](#) • [AD VIA BUYSPELLADS](#)

Please write comments if you find the above codes/algorithms incorrect, or find other ways to solve the same problem.

Another Approach: (only using one extra array): We consider an auxiliary array : `rightMax[]` , such that, `rightMax[i] = max` element of the subarray `arr[i... (n-1)]`, the largest or equal element after `arr[i]` element. Suppose `(arr[i], arr[jLast])` is a pair, such that `arr[jLast]` is the last greater or equal element than `arr[i]`. For the pairs ending with `arr[jLast]` : `(arr[k], arr[jLast])` for all `k = (i+1) to jLast` we don't need to consider `(jLast - k)` because `(jLast - i) > (jLast - k)` for all such `k`'s. So we can skip those pairs. Traversing from left to right of both arrays : `arr[]` and `rightMax[]` , when we first encounter `rightMax[j] < arr[i]` , we know that `jLast = j-1`, and we can skip the pairs `(arr[k], arr[jLast])` for all `k = (i+1) to jLast`. And also `rightMax[]` is non increasing sequence , so all elements at right side of `rightMax[j]` is smaller than or equal to `rightMax[j]`. But there may be `arr[x]` after `arr[i]` (`x > i`) such that `arr[x] < rightMax[j]` for `x > i`, so increment `i` when `rightMax[j] < arr[i]` is encountered.

Below is the implementation of the above approach:

C++

```
#include <bits/stdc++.h>
using namespace std;

/* For a given array arr[],
   returns the maximum j - i such that
   arr[j] > arr[i] */
int maxIndexDiff(int arr[], int n)
{
```

• • • • •

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

//rightMax[i] = max{ arr[i...(n-1] }

int maxDist = INT_MIN;
int i = 0, j = 0;
while(i<n && j<n)
{
    if(rightMax[j] >= arr[i])
    {
        maxDist = max( maxDist, j-i );
        j++;
    }
    else // if(rightMax[j] < leftMin[i])
        i++;
}

return maxDist;

}

// Driver Code
int main()
{
    int arr[] = { 34,8,10,3,2,80,30,33,1};
    int n = sizeof(arr) / sizeof(arr[0]);
    int maxDiff = maxIndexDiff(arr, n);
    cout << maxDiff;
    return 0;
}

// This code is contributed by Sourashis Mondal

```

Java

```

import java.util.*;

class GFG{

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

static int maxIndexDiff(int arr[], int n)
{

    int []rightMax = new int[n];
    rightMax[n-1]= arr[n-1];
    for(int i = n-2; i>=0; i--)
        rightMax[i] = Math.max(rightMax[i+1] , arr[i]);

    // rightMax[i] = max{ arr[i...(n-1)] }
    int maxDist = Integer.MIN_VALUE;
    int i = 0, j = 0;
    while(i < n && j < n)
    {
        if(rightMax[j] >= arr[i])
        {
            maxDist = Math.max( maxDist, j-i );
            j++;
        }
        else // if(rightMax[j] < leftMin[i])
            i++;
    }

    return maxDist;

}

// Driver Code
public static void main(String[] args)
{
    int arr[] = {34, 8, 10, 3, 2, 80, 30, 33, 1};
    int n = arr.length;
    int maxDiff = maxIndexDiff(arr, n);
    System.out.print(maxDiff);
}

// This code is contributed by Rajput-Ji

```

Python3

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSSELLADS

```

rightMax = [0] * n
rightMax[n - 1] = arr[n - 1]
for i in range(n - 2, -1, -1):
    rightMax[i] = max(rightMax[i + 1], arr[i])

# rightMax[i] = max arr[i...(n-1)]
maxDist = -2**31
i = 0
j = 0

while (i < n and j < n):
    if (rightMax[j] >= arr[i]):
        maxDist = max(maxDist, j - i)
        j += 1

    else:

        # if(rightMax[j] < leftMin[i])
        i += 1

return maxDist

# Driver Code
arr = [ 34, 8, 10, 3, 2, 80, 30, 33, 1 ]
n = len(arr)
maxDiff = maxIndexDiff(arr, n)

print(maxDiff)

# This code is contributed by Shubham Singh

```

C#

```

/* For a given array arr[],
returns the maximum j - i such that
arr[j] > arr[i] */
using System;

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

{

    int []rightMax = new int[n];
    rightMax[n - 1] = arr[n - 1];
    int i = 0, j = 0;
    for(i = n - 2; i >= 0; i--)
        rightMax[i] = Math.Max(rightMax[i+1] , arr[i]);

    // rightMax[i] = max{ arr[i...(n-1) ]
    int maxDist = Int32.MinValue;
    i = 0;
    while(i < n && j < n)
    {
        if(rightMax[j] >= arr[i])
        {
            maxDist = Math.Max( maxDist, j - i);
            j++;
        }
        else // if(rightMax[j] < leftMin[i])
            i++;
    }

    return maxDist;
}

// Driver Code
public static void Main()
{
    int[] arr = {34, 8, 10, 3, 2, 80, 30, 33, 1};
    int n = arr.Length;
    int maxDiff = maxIndexDiff(arr, n);
    Console.Write(maxDiff);
}
}

// This code is contributed by Shubham Singh

```

Javascript

```
<script>
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS


```

function maxIndexDiff(arr, n)
{
    var rightMax = new Array(n).fill(0);
    rightMax[n - 1] = arr[n - 1];
    for(var i = n - 2; i >= 0; i--){
        rightMax[i] = Math.max(rightMax[i+1] , arr[i]);
    }

    // rightMax[i] = max{ arr[i...(n-1) ]
    var maxDist = Number.MIN_VALUE;
    var i = 0;
    var j = 0;
    while(i < n && j < n)
    {
        if(rightMax[j] >= arr[i])
        {
            maxDist = Math.max( maxDist, j-i );
            j++;
        }
        else // if(rightMax[j] < leftMin[i])
        {
            i++;
        }
    }
    return maxDist;
}

// Driver Code
var arr = [ 34,8,10,3,2,80,30,33,1];
var n = arr.length;
var maxDiff = maxIndexDiff(arr, n);
document.write(maxDiff);

// This code is contributed by Shubham Singh
</script>

```

Output

6

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

Auxiliary Space: $O(n)$

Using leftMin[]: We can also do this using leftMin[] array only , where leftMin[i] = min element of the subarray arr[0...i]

C++

```
#include <bits/stdc++.h>
using namespace std;

/* For a given array arr[],
   returns the maximum j - i such that
   arr[j] > arr[i] */
int maxIndexDiff(int arr[], int n)
{
    int leftMin[n] ;
    leftMin[0] = arr[0];
    for(int i = 1 ; i<n; i++)
        leftMin[i] = min(leftMin[i-1], arr[i]);

    //leftMin[i] = min{ arr[0...i] }

    int maxDist = INT_MIN;
    int i = n-1, j = n-1;

    while(i>=0 && j>=0)
    {
        if(arr[j] >= leftMin[i])
        {
            maxDist = max(maxDist, j-i);
            i--;
        }
        else
            j--;
    }

    return maxDist;
}
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```
// Driver Code
int main()
{
    int arr[] = { 34,8,10,3,2,80,30,33,1};
    int n = sizeof(arr) / sizeof(arr[0]);
    int maxDiff = maxIndexDiff(arr, n);
    cout << maxDiff;
    return 0;
}

// This code is contributed by Sourashis Mondal
```

Java

```
import java.util.*;
class GFG
{
    /* For a given array arr[],
    returns the maximum j - i such that
    arr[j] > arr[i] */
    static int maxIndexDiff(int arr[], int n)
    {
        int []leftMin = new int[n];
        leftMin[0] = arr[0];
        for(int i = 1; i < n; i++)
            leftMin[i] = Math.min(leftMin[i - 1] , arr[i]);

        // leftMin[i] = min{ arr[i...(n-1)] }

        int maxDist = Integer.MIN_VALUE;
        int i = n - 1, j = n - 1;
        while(i >= 0 && j >= 0)
        {
            if(arr[j] >= leftMin[i])
            {
                maxDist = Math.max( maxDist, j - i );
                i--;
            }
        }
    }
}
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```

        return maxDist;
    }

    // Driver Code
    public static void main(String[] args)
    {
        int arr[] = {34, 8, 10, 3, 2, 80, 30, 33, 1};
        int n = arr.length;
        int maxDiff = maxIndexDiff(arr, n);
        System.out.print(maxDiff);
    }
}

// This code is contributed by Shubham Singh

```

Python3

```

# For a given array arr[],
# returns the maximum j - i such that
# arr[j] > arr[i] */
def maxIndexDiff(arr, n):

    leftMin = [0]*n
    leftMin[0] = arr[0]
    for i in range(1,n):
        leftMin[i] = min(leftMin[i-1], arr[i])

    # leftMin[i] = min arr[0...i]
    maxDist = - 2**32
    i = n-1
    j = n-1

    while(i>=0 and j>=0):

        if(arr[j] >= leftMin[i]):
            maxDist = max(maxDist, j-i)
            i-=1
        else:
            j-=1

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```
arr = [34,8,10,3,2,80,30,33,1]
n = len(arr)
maxDiff = maxIndexDiff(arr, n)
print(maxDiff)

# This code is contributed by Shubham Singh
```

C#

```
using System;

public class GFG{

    /* For a given array arr[],
    returns the maximum j - i such that
    arr[j] > arr[i] */
    static int maxIndexDiff(int[] arr, int n)
    {

        int []leftMin = new int[n];
        leftMin[0] = arr[0];
        int i,j;
        for( i = 1; i < n; i++)
            leftMin[i] = Math.Min(leftMin[i - 1] , arr[i]);

        // leftMin[i] = min{ arr[i...(n-1)] }

        int maxDist = Int32.MinValue;
        i = n - 1;
        j = n - 1;
        while(i >= 0 && j >= 0)
        {
            if(arr[j] >= leftMin[i])
            {
                maxDist = Math.Max( maxDist, j - i );
                i--;
            }
            else
                j--;
        }
    }
}
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```
// Driver Code
static public void Main ()
{
    int[] arr = {34, 8, 10, 3, 2, 80, 30, 33, 1};
    int n = arr.Length;
    int maxDiff = maxIndexDiff(arr, n);
    Console.Write(maxDiff);
}
}

// This code is contributed by Shubham Singh
```

Javascript

```
<script>

/* For a given array arr[],
   returns the maximum j - i such that
   arr[j] > arr[i] */
function maxIndexDiff(arr, n)
{
    var leftMin = new Array(n).fill(0);
    leftMin[0] = arr[0];
    for(var i = 1; i < n; i++){
        leftMin[i] = Math.min(leftMin[i-1] , arr[i]);
    }

    // leftMin[i] = min{ arr[i...(n-1)] }
    var maxDist = Number.MIN_VALUE;
    var i = n-1;
    var j = n-1;
    while(i >= 0 && j >= 0)
    {
        if(arr[j] >= leftMin[i])
        {
            maxDist = Math.max( maxDist, j-i );
            i--;
        }
        else // if(rightMax[j] < leftMin[i])
            j--;
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

HIDE AD • AD VIA BUYSPELLADS

```
// Driver Code
var arr = [ 34,8,10,3,2,80,30,33,1];
var n = arr.length;
var maxDiff = maxIndexDiff(arr, n);
document.write(maxDiff);

// This code is contributed by Shubham Singh

</script>
```

Output

6

Time Complexity: $O(n)$

Auxiliary Space: $O(n)$

Please suggest if someone has a better solution that is more efficient in terms of space and time.

This article is contributed by [Aarti_Rathi](#). Please write comments if you find anything incorrect, or if you want to share more information about the topic discussed above

AMAZON TEST SERIES
To Help Crack Your SDE Interview

//

Enrol Now


GeeksforGeeks

Liked 273

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

SIGN UP

HIDE AD • AD VIA BUYSPELLADS

between two elements such (Maximum of all subarrays of
that larger element appears size k)
after the smaller number

RECOMMENDED ARTICLES

Page : 1 2 3

- 01

Count pairs (i, j) from an array such that $|arr[i]|$ and $|arr[j]|$ both lies between $|arr[i] - arr[j]|$ and $|arr[i] + arr[j]|$

12, Mar 21
- 02

Check whether (i,j) exists such that $arr[i] \neq arr[j]$ and $arr[arr[i]]$ is equal to $arr[arr[j]]$

15, Nov 18
- 03

Maximum value of $|arr[0] - arr[1]| + |arr[1] - arr[2]| + \dots + |arr[n - 2] - arr[n - 1]|$ when elements are from 1 to n

07, Mar 19
- 04

Minimize last remaining element of Array by selecting pairs such that $arr[i] \geq arr[j]$ and replace $arr[i]$ with $arr[i] - arr[j]$

27, Jan 22
- 05

Count quadruples (i, j, k, l) in an array such that $i < j < k < l$ and $arr[i] = arr[k]$ and $arr[j] = arr[l]$

17, Sep 20
- 06

C++ Program to Rearrange array such that $arr[i] \geq arr[j]$ if i is even and $arr[i] \leq arr[j]$ if i is odd and $j < i$

30, Dec 21
- 07

Java Program to Rearrange array such that $arr[i] \geq arr[j]$ if i is even and $arr[i] \leq arr[j]$ if i is odd and $j < i$

30, Dec 21
- 08

Python3 Program to Rearrange array such that $arr[i] \geq arr[j]$ if i is even and $arr[i] \leq arr[j]$ if i is odd and $j < i$

30, Dec 21

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

[HIDE AD](#) • [AD VIA BUYSPELLADS](#)

Article Contributed By :



GeeksforGeeks

Vote for difficulty

Current difficulty : [Hard](#)

Easy

Normal

Medium

Hard

Expert

Improved By : [Sam007](#), [Gautam Karakoti](#), [ukasp](#), [Akanksha_Rai](#), [rathbhupendra](#), [msg](#), [executable](#), [shikhasingrajput](#), [Rajput-Ji](#), [winter_soldier](#), [avanitrachhadiya2155](#), [rag2127](#), [mank1083](#), [decode2207](#), [suresh07](#), [abhijit gupta 1](#), [2011harshgupta](#), [dheerwani2498](#), [sourashis69](#), [SHUBHAMSINGH10](#), [simranarora5sos](#), [shinjanpatra](#), [pushpeshrajdx01](#), [sachinvinod1904](#)

Article Tags : [Amazon](#), [Snapdeal](#), [Arrays](#)

Practice Tags : [Amazon](#), [Snapdeal](#), [Arrays](#)

Improve Article

Report Issue

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

[HIDE AD](#) • [AD VIA BUYSPELLADS](#)



A-143, 9th Floor, Sovereign Corporate Tower,
Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

Company

[About Us](#)
[Careers](#)
[In Media](#)
[Contact Us](#)
[Privacy Policy](#)
[Copyright Policy](#)

Learn

[Algorithms](#)
[Data Structures](#)
[SDE Cheat Sheet](#)
[Machine learning](#)
[CS Subjects](#)
[Video Tutorials](#)
[Courses](#)

News

[Top News](#)
[Technology](#)
[Work & Career](#)
[Business](#)
[Finance](#)
[Lifestyle](#)
[Knowledge](#)

Languages

[Python](#)
[Java](#)
[CPP](#)
[Golang](#)
[C#](#)
[SQL](#)
[Kotlin](#)

Web Development

Contribute



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

[SIGN UP](#)

[HIDE AD](#) • [AD VIA BUYSSELLADS](#)

NodeJS

@geeksforgeeks , Some rights reserved

Do Not Sell My Personal Information

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge



Try Mailchimp automations today to start sending data-backed emails that speak to your customers' interests.

SIGN UP

HIDE AD • AD VIA BUYSSELLADS