

Build Video Distribution System

Real-life examples

- Youtube
- Netflix
- Vimeo

Requirements clarification

- Functional requirements
 - o Upload video: Users can upload videos.
 - Watch video: Users can watch videos.
 - Search video: Users can search videos.
 - Comment video: Users can leave comments to videos, also like or dislike.
- Non-functional requirements
 - High reliability (Any video uploaded should not be lost).
 - High availability.
 - High consistency is desirable (It should be ok for a user doesn't see a video for a while).

Estimation

Traffic estimation

- o Our system will be read-heavy.
- Read-write ratio (View-upload ratio) is 200 : 1 (Assumed)
- Users
 - 1.5 billion users. (Assumed)
 - 150 million daily active users. (Assumed)
 - 1% of users are creators, every week will publish one new video. (Assumed)
 - Each user watches 3 videos per day. (Assumed)
- Number of read actions and write actions per week
 - Number of writes (upload) per week = 1.5 billion x 1% = 15 million
 - Number of reads (watch) per week = 15 millions x 200 = 3 billion
- Frequency of read actions and write actions per second (QPS)
 - Frequency of writes per second = 15 millions / (7 days x 24 hours x 3600 seconds) = 24 videos/s
 - Frequency of reads per second = 24 videos/s x 200 = 4800 videos/s

Storage estimation

- Types
 - Data: Yes
 - File: Yes
- Capacity
 - Size of each video: 500 MB (Assumed)
 - Total capacity needed in week = Number of writes (upload) per week x Size of one record = 15 million x 500 MB = 7152 TB

• Bandwidth estimation

- Size of each video: 500 MB (Assumed)
- Write bandwidth = Frequency of writes per second x Size of one record = 24
 videos/s x 500 MR = 11 GR/s

viueus/s x u ivib/s (1000p) - 20 db/s

System interface definition

- Interface 1
 - uploadVideo(api_key, video_title, video_description, video_content)
 - Function

• • •

- Upload a video
- Parameters
 - api_key (string): The API developer key of a registered account.
 - video_title (string): The title of the video.
 - video_description (string): The description of the video.
 - video_content (stream): The content stream of the video.


Interface 2

- o streamVideo(api_key, video_id, offset, codec, resolution)
 - Function
 - Watch a video
 - Parameters
 - api_key (string): The API developer key of a registered account.
 - video_id (string): The ID of the video.
 - offset (number): A playing time in seconds from the beginning of the video.
 - codec: The encoding format of the video.
 - resolution: The resolution of the video.

Data model definition

- Schema
 - o Table 1: VideoMetadata
 - o Table 2: Comment
 - o Table 3: User
- Data storage
 - Database
 - File storage (to store video and thumbnails)
 - HDFS
 - GlusterFS
 - Amazon S3

High-level design



Upload Service

- Handle upload requests
- Create a encoding task and push it into the processing queue.

Processing Queue

- Store all the encoding tasks.
- Decouple uploading works and encoding works
- It can act as a buffer if the encoder is unavailable or overloaded.

Encoder

• Encode each uploaded video into multiple formats.

Thumbnails generator

Generate a few thumbnails for each video.

Video Storage

Store video contents.

Thumbnails Storage

Store thumbnails.

Video Metadata Database

• Store all the information about videos like title, file path in the system, uploading user, total views, likes, dislikes, comments.

User Database

Store user's information.

Key points

- Use queue to decouple upload works with encoding works.
- Use proper storage for storing videos and thumbnails.
 - Object storages
 - o CDN
- Read traffic for thumbnails will be huge compared to videos
 - Users will be watching one video at a time, but they might be looking at a page with 20 thumbnails of other videos.