

[Array](#) [Matrix](#) [Strings](#) [Hashing](#) [Linked List](#) [Stack](#) [Queue](#) [Binary Tree](#) [Binary Search](#)

# Maximum adjacent difference in an array in its sorted form

Difficulty Level : Hard • Last Updated : 24 Jun, 2021



Given an array, find the maximum difference between its two consecutive elements in its sorted form.

## Examples:

**Input:** `arr[] = {1, 10, 5}`

**Output:** 5

Sorted array would be {1, 5, 10} and maximum adjacent difference would be  $10 - 5 = 5$

**Input:** `arr[] = {2, 4, 8, 11}`

**Output:** 4

Recommended Practice

**Maximum Gap**

Try It!

## Naive Solution:

First sort the array, then traverse it and keep track of the maximum difference between adjacent elements.



Start building apps today with 40+ free services.

[LEARN MORE](#)

HIDE AD • AD VIA BUYSSELLADS

## Efficient Solution:

This **solution** is based on the idea of [Pigeonhole sorting](#). No need to sort the array, just have to fill the buckets and keep track of the maximum and minimum value of each bucket. If found an empty bucket, The maximum gap would be the difference of **maximum value in the previous bucket – minimum value in the next bucket**.

As we want to almost sort these so that, we can have maximum gap. Also for any  $i$ th element, the value of  $(arr[i] - min\_value) / (max\_value - min\_value)$  keeps increasing as  $arr[i]$  keeps increasing and this value always varies from 0 to 1. As we want to put the sorted results in bucket of size  $n$ . We multiply this value by  $(n-1)$  hence make a variable  **$\delta = (max\_value - min\_value) / (n-1)$** . Now in `maxBucket` or `minBucket`, all the value at any index  $j$  before index any  $i$  will always less than the value at index  $i$ ,  $minBucket[j] < minBucket[i]$  for  $j < i$ . It is possible that two different  $arr[i]$ , might have same value of  **$(arr[i] - min\_value) / \delta$** , therefore we are making 2 different buckets `maxBucket` and `minBucket`.

As we have find the max difference between **consecutive values**, we must consider the max possible value upto to previous index as `prev_val` and the `minBucket[i]` for current index  $i$ , and `ans` will be max of `ans` and `minBucket[i] - prev_val`.

Let us solve the above example by this approach.

## Working Example:

**Input:** `arr[] = {1, 10, 5}`

**Output:** 5

**Step1:** Find `max_val` and `min_val`



Start building apps today with 40+ free services.

[LEARN MORE](#)

HIDE AD • AD VIA BUYSPELLADS

$$\text{delta} = (\text{max\_val} - \text{min\_val}) / (n - 1)$$

$$\text{delta} = (10 - 1) / (3 - 1) = 4.5$$

**Step3:** Initialize buckets,  $\text{maxBucket} = \{\text{INT\_MIN}\}$ ,  $\text{minBucket} = \{\text{INT\_MAX}\}$

**Step4:** For any index  $i$ , calculate index  $\text{arr}[i]$  in bucket and update in buckets,

$$\text{in} = (\text{arr}[i] - \text{min\_val}) / \text{delta}$$

$$\text{maxBucket}[\text{in}] = \max(\text{maxBucket}[\text{in}], \text{arr}[i])$$

$$\text{minBucket}[\text{in}] = \min(\text{minBucket}[\text{in}], \text{arr}[i])$$

for all index in arr in values are  $\Rightarrow 0, 2, 0$

$$\text{maxBucket} = [5, \text{INT\_MIN}, 10]$$

$$\text{minBucket} = [1, \text{INT\_MAX}, 10]$$

**Step5:** Hence ans is max of  $\text{minBucket}[i] - (\text{max of value upto previous index})$

in this case for  $i=2$ :  $\text{max\_gap} = \max(\text{max\_gap}, \text{minBucket}[2] - \max(\text{maxBucket}[1], \text{maxBucket}[0]))$

$$\text{max\_gap} = 10 - 5 = 5$$

This is just for presenting the concept, all other basic validations are in the main code.

Below is the code for the above approach:

**C++**



Start building apps today with 40+ free services.

[LEARN MORE](#)

HIDE AD • AD VIA BUYSSELLADS

```
using namespace std;

int maxSortedAdjacentDiff(int* arr, int n)
{
    // Find maximum and minimum in arr[]
    int maxVal = arr[0], minVal = arr[0];
    for (int i = 1; i < n; i++) {
        maxVal = max(maxVal, arr[i]);
        minVal = min(minVal, arr[i]);
    }

    // Arrays to store maximum and minimum values
    // in n-1 buckets of differences.
    int maxBucket[n - 1];
    int minBucket[n - 1];
    fill_n(maxBucket, n - 1, INT_MIN);
    fill_n(minBucket, n - 1, INT_MAX);

    // Expected gap for every bucket.
    float delta = (float)(maxVal - minVal) / (float)(n - 1);

    // Traversing through array elements and
    // filling in appropriate bucket if bucket
    // is empty. Else updating bucket values.
    for (int i = 0; i < n; i++) {
        if (arr[i] == maxVal || arr[i] == minVal)
            continue;

        // Finding index of bucket.
        int index = (float)(floor(arr[i] - minVal) / delta);

        maxBucket[index] = max(maxBucket[index], arr[i]);
        minBucket[index] = min(minBucket[index], arr[i]);
    }

    // Finding maximum difference between maximum value
    // of previous bucket minus minimum of current bucket.
    int prev_val = minVal;
    int max_gap = 0;
    for (int i = 0; i < n - 1; i++) {
        if (minBucket[i] == INT_MAX)
            continue;
```



```

        max_gap = max(max_gap, maxVal - prev_val);

    return max_gap;
}

int main()
{
    int arr[] = { 1, 10, 5 };
    int n = sizeof(arr) / sizeof(arr[0]);
    cout << maxSortedAdjacentDiff(arr, n) << endl;
    return 0;
}

```

## Java

```

// Java program for the above approach
import java.util.Arrays;

// Java program to find maximum adjacent difference
// between two adjacent after sorting.
class GFG {

    static int maxSortedAdjacentDiff(int[] arr, int n)
    {
        // Find maximum and minimum in arr[]
        int maxVal = arr[0];
        int minVal = arr[0];
        for (int i = 1; i < n; i++) {
            maxVal = Math.max(maxVal, arr[i]);
            minVal = Math.min(minVal, arr[i]);
        }

        // Arrays to store maximum and minimum values
        // in n-1 buckets of differences.
        int maxBucket[] = new int[n - 1];
        int minBucket[] = new int[n - 1];
        Arrays.fill(maxBucket, 0, n - 1, Integer.MIN_VALUE);
        Arrays.fill(minBucket, 0, n - 1, Integer.MAX_VALUE);

        // Expected gap for every bucket.
        float delta

```



Start building apps today with 40+ free services.

[LEARN MORE](#)

HIDE AD • AD VIA BUYSPELLADS

```
// filling in appropriate bucket if bucket
// is empty. Else updating bucket values.
for (int i = 0; i < n; i++) {
    if (arr[i] == maxVal || arr[i] == minVal) {
        continue;
    }

    // Finding index of bucket.
    int index = (int)(Math.round((arr[i] - minVal)
                                / delta));

    // Filling/Updating maximum value of bucket
    if (maxBucket[index] == Integer.MIN_VALUE) {
        maxBucket[index] = arr[i];
    }
    else {
        maxBucket[index]
            = Math.max(maxBucket[index], arr[i]);
    }

    // Filling/Updating minimum value of bucket
    if (minBucket[index] == Integer.MAX_VALUE) {
        minBucket[index] = arr[i];
    }
    else {
        minBucket[index]
            = Math.min(minBucket[index], arr[i]);
    }
}

// Finding maximum difference between maximum value
// of previous bucket minus minimum of current
// bucket.
int prev_val = minVal;
int max_gap = 0;
for (int i = 0; i < n - 1; i++) {
    if (minBucket[i] == Integer.MAX_VALUE) {
        continue;
    }
    max_gap = Math.max(max_gap,
                        minBucket[i] - prev_val);
    prev_val = maxBucket[i];
}
```



Start building apps today with 40+ free services.

[LEARN MORE](#)

HIDE AD • AD VIA BUYSSELLADS

```

        return max_gap;
    }

    // Driver program to run the case
    public static void main(String[] args)
    {

        int arr[] = { 1, 10, 5 };
        int n = arr.length;
        System.out.println(maxSortedAdjacentDiff(arr, n));
    }
}

```

## Python3

# Python3 program to find maximum adjacent  
# difference between two adjacent after sorting.

```

def maxSortedAdjacentDiff(arr, n):

    # Find maximum and minimum in arr[]
    maxVal, minVal = arr[0], arr[0]
    for i in range(1, n):
        maxVal = max(maxVal, arr[i])
        minVal = min(minVal, arr[i])

    # Arrays to store maximum and minimum
    # values in n-1 buckets of differences.
    maxBucket = [INT_MIN] * (n - 1)
    minBucket = [INT_MAX] * (n - 1)

    # Expected gap for every bucket.
    delta = (maxVal - minVal) // (n - 1)

    # Traversing through array elements and
    # filling in appropriate bucket if bucket
    # is empty. Else updating bucket values.
    for i in range(0, n):
        if arr[i] == maxVal or arr[i] == minVal:
            continue

```



Start building apps today with 40+ free services.

[LEARN MORE](#)

HIDE AD • AD VIA BUYSSELLADS

```
# Filling/Updating maximum value
# of bucket
if maxBucket[index] == INT_MIN:
    maxBucket[index] = arr[i]
else:
    maxBucket[index] = max(maxBucket[index],
                           arr[i])

# Filling/Updating minimum value of bucket
if minBucket[index] == INT_MAX:
    minBucket[index] = arr[i]
else:
    minBucket[index] = min(minBucket[index],
                           arr[i])

# Finding maximum difference between
# maximum value of previous bucket
# minus minimum of current bucket.
prev_val, max_gap = minVal, 0

for i in range(0, n - 1):
    if minBucket[i] == INT_MAX:
        continue

    max_gap = max(max_gap,
                  minBucket[i] - prev_val)
    prev_val = maxBucket[i]

max_gap = max(max_gap, maxVal - prev_val)

return max_gap

# Driver Code
if __name__ == "__main__":

    arr = [1, 10, 5]
    n = len(arr)
    INT_MIN, INT_MAX = float('-inf'), float('inf')

    print(maxSortedAdjacentDiff(arr, n))
```

# This code is contributed by Rituraj Jain



Microsoft

Start building apps today with 40+ free services.

[LEARN MORE](#)

HIDE AD • AD VIA BUYSPELLADS



```
// C# program to find maximum
// adjacent difference between
// two adjacent after sorting.
using System;
using System.Linq;

class GFG
{
    static int maxSortedAdjacentDiff(int[] arr,
                                     int n)
    {
        // Find maximum and minimum in arr[]
        int maxVal = arr[0];
        int minVal = arr[0];
        for (int i = 1; i < n; i++)
        {
            maxVal = Math.Max(maxVal, arr[i]);
            minVal = Math.Min(minVal, arr[i]);
        }

        // Arrays to store maximum and
        // minimum values in n-1 buckets
        // of differences.
        int []maxBucket = new int[n - 1];
        int []minBucket = new int[n - 1];
        maxBucket = maxBucket.Select(i => int.MinValue).ToArray();
        minBucket = minBucket.Select(i => int.MaxValue).ToArray();

        // maxBucket.Fill(int.MinValue);
        // Arrays.fill(minBucket, 0, n - 1, Integer.MAX_VALUE);

        // Expected gap for every bucket.
        float delta = (float) (maxVal - minVal) /
                      (float) (n - 1);

        // Traversing through array elements and
        // filling in appropriate bucket if bucket
        // is empty. Else updating bucket values.
        for (int i = 0; i < n; i++)
        {
            if (arr[i] == maxVal || arr[i] == minVal)
```



```
// Finding index of bucket.
int index = (int) (Math.Round((arr[i] -
                             minVal) / delta));

// Filling/Updating maximum value of bucket
if (maxBucket[index] == int.MinValue)
{
    maxBucket[index] = arr[i];
}
else
{
    maxBucket[index] = Math.Max(maxBucket[index],
                                arr[i]);
}

// Filling/Updating minimum value of bucket
if (minBucket[index] == int.MaxValue)
{
    minBucket[index] = arr[i];
}
else
{
    minBucket[index] = Math.Min(minBucket[index],
                                arr[i]);
}
}

// Finding maximum difference between
// maximum value of previous bucket
// minus minimum of current bucket.
int prev_val = minVal;
int max_gap = 0;
for (int i = 0; i < n - 1; i++)
{
    if (minBucket[i] == int.MaxValue)
    {
        continue;
    }
    max_gap = Math.Max(max_gap, minBucket[i] -
                        prev_val);
    prev_val = maxBucket[i];
}
```



Start building apps today with 40+ free services.

[LEARN MORE](#)

HIDE AD • AD VIA BUYSPELLADS

```

        return max_gap;
    }

    // Driver Code
    public static void Main()
    {
        int []arr = {1, 10, 5};
        int n = arr.Length;
        Console.Write(maxSortedAdjacentDiff(arr, n));
    }
}

// This code contributed by 29AjayKumar

```

## Javascript

```

<script>

// JavaScript program to find maximum adjacent difference
// between two adjacent after sorting.

function maxSortedAdjacentDiff(arr, n)
{
    // Find maximum and minimum in arr[]
    var maxVal = arr[0], minVal = arr[0];
    for (var i = 1; i < n; i++) {
        maxVal = Math.max(maxVal, arr[i]);
        minVal = Math.min(minVal, arr[i]);
    }

    // Arrays to store maximum and minimum values
    // in n-1 buckets of differences.
    var maxBucket = Array(n-1).fill(-1000000000);
    var minBucket = Array(n-1).fill(1000000000);

    // Expected gap for every bucket.
    var delta = (maxVal - minVal) / (n - 1);

    // Traversing through array elements and
    // filling in appropriate bucket if bucket
    // is empty. Else updating bucket values

```



Start building apps today with 40+ free services.

[LEARN MORE](#)

HIDE AD • AD VIA BUYSSELLADS

```
        continue;

// Finding index of bucket.
var index = Math.floor((arr[i] - minVal) / delta);

maxBucket[index] = Math.max(maxBucket[index], arr[i]);
minBucket[index] = Math.min(minBucket[index], arr[i]);
}

// Finding maximum difference between maximum value
// of previous bucket minus minimum of current bucket.
var prev_val = minVal;
var max_gap = 0;
for (var i = 0; i < n - 1; i++) {
    if (minBucket[i] == 1000000000)
        continue;
    max_gap = Math.max(max_gap, minBucket[i] - prev_val);
    prev_val = maxBucket[i];
}
max_gap = Math.max(max_gap, maxVal - prev_val);

return max_gap;
}

var arr = [1, 10, 5];
var n = arr.length;
document.write( maxSortedAdjacentDiff(arr, n));

</script>
```

## Output

5

**Time complexity:**  $O(n)$

**Auxiliary Space:**  $O(n)$



**DSA Self-Paced  
Course**



Curated by experts



Trusted by 1 Lac+ students

**Enrol Now**



GeeksforGeeks



Start building apps today with 40+ free services.

**LEARN MORE**

HIDE AD • AD VIA BUYSPELLADS

Like 30

Next

## Pigeonhole Sort

### RECOMMENDED ARTICLES

Page : 1 2 3

**01** Check if two sorted arrays can be merged to form a sorted array with no adjacent pair from the same array  
16, Nov 20

**05** Maximum number of partitions that can be sorted individually to make sorted  
28, Feb 18

**02** Maximum array elements that can be removed along with its adjacent values to empty given array  
05, Nov 20

**06** Count number of common elements between a sorted array and a reverse sorted array  
12, May 21

**03** Count triplets from a sorted array having difference between adjacent elements equal to D  
12, May 21

**07** Circularly Sorted Array (Sorted and Rotated Array)  
01, Jun 22

**04** Generate longest possible array with product K such that



Microsoft

Start building apps today with 40+ free services.

[LEARN MORE](#)

HIDE AD • AD VIA BUYSPELLADS

12, Mar 21

10, Sep 20

## Article Contributed By :



**Aashish Chauhan**  
@Aashish Chauhan

## Vote for difficulty

Current difficulty : [Hard](#)

Easy

Normal

Medium

Hard

Expert

**Improved By :** [Rajput-Ji](#), [29AjayKumar](#), [rituraj\\_jain](#), [nehal sharma](#),  
[2701gouravgoel](#), [rrrtxn](#), [khushboogoyal499](#)

**Article Tags :** [Pigeonhole Principle](#), [Arrays](#), [Searching](#)

**Practice Tags :** [Arrays](#), [Searching](#)

Improve Article

Report Issue

Writing code in comment? Please use [ide.geeksforgeeks.org](https://ide.geeksforgeeks.org), generate link and share the link here.



Load Comments



Microsoft

Start building apps today with 40+ free services.

[LEARN MORE](#)

HIDE AD • AD VIA BUYSSELLADS



A-143, 9th Floor, Sovereign Corporate Tower,  
Sector-136, Noida, Uttar Pradesh - 201305

[feedback@geeksforgeeks.org](mailto:feedback@geeksforgeeks.org)

## Company

[About Us](#)  
[Careers](#)  
[In Media](#)  
[Contact Us](#)  
[Privacy Policy](#)  
[Copyright Policy](#)

## Learn

[Algorithms](#)  
[Data Structures](#)  
[SDE Cheat Sheet](#)  
[Machine learning](#)  
[CS Subjects](#)  
[Video Tutorials](#)  
[Courses](#)

## News

[Top News](#)  
[Technology](#)  
[Work & Career](#)  
[Business](#)  
[Finance](#)  
[Lifestyle](#)  
[Knowledge](#)

## Languages

[Python](#)  
[Java](#)  
[CPP](#)  
[Golang](#)  
[C#](#)  
[SQL](#)  
[Kotlin](#)

## Web Development

[Web Tutorials](#)  
[Django Tutorial](#)

## Contribute

[Write an Article](#)  
[Improve an Article](#)



Start building apps today with 40+ free services.

[LEARN MORE](#)

HIDE AD • AD VIA BUYSSELLADS

---

NodeJS

@geeksforgeeks , Some rights reserved

Do Not Sell My Personal Information



Start building apps today with 40+ free services.

[LEARN MORE](#)

HIDE AD • AD VIA BUYSSELLADS