



OFFER

Android Online Course by
MindOrks

Start your career in Android
Development. Learn by doing real
projects.

ENROLL
NOW



Admin AfterAcademy

29 Feb 2020

Median of Two Sorted Array of the Same Size

$$\frac{[] []}{2}$$

Median of Two Sorted
Array of the Same Size

Understanding The Problem

Problem Description

There are two sorted arrays **nums1** and **nums2** of size n . Find the median of the two sorted arrays.

You may assume **nums1** and **nums2** cannot be both empty.

Example 1:

```
nums1 = [1, 3]
nums2 = [2, 4]
```

The median is 2.5 as $(2 + 3) / 2 = 2.5$

Example 2:

```
nums1 = [1, 2, 9]
nums2 = [3, 4, 7]
```

The median is $(3 + 4) / 2 = 3.5$

What is Median?

The median is the value separating the higher half of a data sample, a population, or a probability distribution, from the lower half. For a data set,

it may be thought of as the “middle” value.

For odd n , Median (M) = value of $((n + 1)/2)$ th item term.

For even n , Median (M) = value of $\{(n/2)$ th item term + $(n/2 + 1)$ th item term $\}/2$

Note → Since the size of the two input arrays for which we are looking for the median is even($2n$), we need to take the average of the middle two numbers and return it.

Solutions

We will be discussing linear and logarithmic solutions for the problem

1. **Counting while comparing**—Find the middle elements after merging the sorted array using the merge procedure of merge sort.
2. **Comparing medians**—Get the medians of two sorted arrays and compare the medians and move accordingly until the two medians become equal following divide and conquer approach.

1. Counting While Comparing

For this approach, we actually have to find those two elements that could be in the middle when the two arrays are merged in sorted order.

If we follow the merge procedure like the one in merge sort then we could just compare the values at the two pointers pointing to the indexes of the two arrays and then increment the pointers accordingly while keeping track of the count. If count becomes n (For $2n$ elements), we have reached the median. Take the average of the elements at indexes $n-1$ and n in the

merged array.

Solution Steps

1. Create two pointers `i` and `j` pointing to `nums1` and `nums2` respectively and initialize them with `0`
2. If the value at `nums1[i] < nums2[j]` then increment `i` otherwise, increment `j`
3. Repeat step 2 until `i` or `j` becomes `i+j` equals to `n`
4. Return median of the two elements at `i`th and `j`th indexes.

Pseudo Code

```
float getMedian(int num1[], int num2[], int size) {  
    int i = 0  
    int j = 0  
    int m1 = -1, m2 = -1  
    for (count = 0 to size) {  
        if (i == size) {  
            m1 = m2  
            m2 = num2[0]  
            break  
        }  
        else if (j == size) {  
            m1 = m2  
            m2 = num1[0]  
            break  
        }  
        if (num1[i] < num2[j]) {  
            m1 = m2  
            m2 = num1[i]  
            i = i + 1  
        } else {  
            m1 = m2
```

```
        m2 = num2[j]
        j = j + 1
    }
}
return (m1 + m2)/2
}
```

Complexity Analysis

Time Complexity: $O(n)$, where n is the size of both the input arrays

Space Complexity: $O(1)$

Critical Ideas to Think

- Did you recognize that the merge approach is similar to the one used in merge sort?
- Why we are returning $(m1 + m2) / 2$ in the end?
- If we have created an auxiliary array and save both the arrays in a sorted manner and then return its median, will it give the correct result? If yes then what would be its time and space complexity?



NEW

Android App Development Online Course by MindOrks

Start your career in Android Development. Learn by doing real projects.

[CHECK NOW](#)

2. Comparing medians

This approach works by comparing the two medians of both the array following the Divide & Conquer paradigm. If the first median is greater than the second median then we will look for the median of the two sorted arrays in $\text{num1}[0 \text{ to } \text{median1}]$ and $\text{num2}[\text{median2} \text{ to } n]$. **(Why?)**

We know that median1 is larger than or equal to the first half of num1 . And the same for median2 and num2 . At the same time, we also know that median1 is smaller than or equal to the second half of num1 .

Let's consider the case $\text{median1} > \text{median2}$

```
num1:      [.....median1.....]
num2:      [.....median2.....]
num1+num2: [.....median2...median1.....]
```

Let us call the median of the merged array m^* . Since the first halves of `num1` and `num2` come before `median1`. So, `median1` $\geq m^*$, this means that no values larger than `median1` need to be considered in `num1`. So we only need to look in the first half or `ar1`.

Similarly, since the second halves of `num1` and `num2` come after `median1`, we have that `median2` $\leq m^*$, this means that no values smaller than `median2` need to be considered and we only need to look in the second half of `num2`.

Example →

```
num1 = {1, 12, 15, 26, 38}
num2 = {2, 13, 17, 30, 45}
```

```
med1 = 15 and med2 = 17 for num1[0 to 4] and num2[0 to 4]
```

```
med1 < med2. So median is present in {15, 26, 38} and {2, 13, 17}
now, med1 = 26 and med2 = 13
```

```
med1 > med2. So median is present in {15, 26} and {13, 17}
```

```
The size of both the subarrays are now 2. So,
median = (max(15,13) + min(26, 17))/2 = 16
```

Solution Steps

1. Calculate the median of both the arrays, say `m1` and `m2` for `num1[]`

and `num2[]` .

2. Repeat till the size of `num1` and `num2` becomes two.

- If `m1 == m2` then return `m1`.
- If `m1 > m2` then median will be present in either of the sub-arrays `num1[0..m1]` and `num2[m2 to n]` .
- If `m2 > m1` then median will be present in either of the sub-arrays `num1[m1 to n]` and `num2[0 to m2]` .

3. Return Median = $(\max(\text{array1}[0], \text{array2}[0]) + \min(\text{array1}[1], \text{array2}[1])) / 2$

Pseudo Code

```
float getMedian(int num1[], int num2[], int size) {  
    // base cases  
    if (size <= 0)  
        return -1  
    if (size == 1)  
        return (num1[0] + num2[0]) / 2  
    if (size == 2)  
        return (max(num1[0], num2[0]) + min(num1[1], num2[1])) / 2  
    int med1 = median(num1, size)  
    int med2 = median(num2, size)  
    // compare the medians  
    if (med1 == med2)  
        return med1  
    if (med1 < med2) {  
        // recurse for the subarray num1[m1 to size] and num2[0 to m2]  
        if (size % 2 == 0)  
            return getMedian(num1 + size/2 - 1, num2, size - size/2 + 1)  
        else  
            return getMedian(num1 + size / 2, num2, size - size / 2)  
    } else {  

```



```
// recurse for the subarray num1[0 to m1] and num2[m2 to n]
if (size % 2 == 0)
    return getMedian(num2 + size / 2 - 1, num1, size - size / 2 + 1)
else
    return getMedian(num2 + size / 2, num1, size - size / 2)
}

// Utility function to find median of array
int median(int arr[], int array_size) {
    if (array_size % 2 == 0)
        return (arr[array_size / 2] + arr[array_size / 2 - 1]) / 2
    else
        return arr[array_size / 2]
}
```

Complexity Analysis

Time Complexity: $O(\log n)$, where n is the size of both the arrays

Space Complexity: $O(\log n)$ (Why?)

Critical Ideas to Think

- Can you code this approach in an iterative manner?
- Why does the comparison of medians and moving accordingly will reach the correct result?
- What would be the median when the two sorted arrays are of length two?

Comparison of Different Solutions

Approach	Time Complexity	Space Complexity
Counting while	$O(n)$	$O(1)$

comparing		
Comparing medians (Divide & Conquer)	$O(\log n)$	$O(\log n)$

Suggested Problems to Solve

- Median of two sorted arrays of different sizes
- Median in a row-wise sorted matrix

 SHARE ON FACEBOOK

 SHARE ON TWITTER

 SHARE ON LINKEDIN

 SHARE ON TELEGRAM

 SHARE ON REDDIT

 SHARE ON WHATSAPP

[CHECK NOW](#)



Interview

Google Android Engineer Interview Process and Preparation.

Recommended for You



Average of levels of Binary tree

afteracademy.com

Average of Levels in Binary Tree



Admin AfterAcademy

4 Nov 2020

Given a binary tree, write a program to return

Interview question

LRU Cache implementation

k1 k2 k3 k4

N1

N2

N3

N4

Asked in    

afteracademy.com

LRU Cache Implementation



Admin AfterAcademy

12 Oct 2020

Design and implement a data structure for Least Recently Used (LRU) cache. Your data

the average value of the nodes on each level in the form of an array. The range of the node's value is in the range of 32-bit signed integer.

structure must support two operations: get(key) and put(). The problem expects a constant time solution

Pushed → [1 2 3]

Popped → [3 2 1]

Validate Stack Sequences

afteracademy.com

Validate Stack Sequences

Given two sequences pushed and popped with distinct values, write a program to return true if and only if this could have been the result of a sequence of push and pop operations on an initially empty stack.



Admin AfterAcademy
4 Oct 2020



Recursive Insertion Sort

afteracademy.com

Recursive Insertion Sort

Write a program for the recursive implementation of Insertion Sort. Insertion Sort is used to sort a given array. This problem will sharpen your recursion skills.



Admin AfterAcademy
22 Sep 2020



When to Convert a 2-D DP array to 1-D DP array And How

afteracademy.com

When to Convert a 2-D DP



Admin AfterAcademy
15 Sep 2020
And How?



Merge sort in linked list

afteracademy.com

Sort List - Merge Sort



Admin AfterAcademy
12 Sep 2020
linked list using Merge Sort. This is a very famous interview problem that

In which situation 2 dimensional DP can be dropped to 1 dimension? Is there any principle or regular pattern? This is a very important question when it comes to optimization of DP arrays. Let's find out.

demonstrates the concept of recursion. This problem is quite similar to Merge Sort in Arrays.

Our Learners Work At



AfterAcademy

Stay up to date. Follow us on



© Copyright 2019

MindOrks Nextgen Private Limited
Gurgaon, Haryana, India
+91-8287460223

About Us

MindOrks
Amit Shekhar
Janishar Ali

Quick Links

[Contact Us](#)
[Privacy Policy](#)
[Terms And Conditions](#)
[Cookie Policy](#)

Free Resources

[Publication](#)
[Medium](#)
[Video Lessons](#)
[Open Source](#)