

Given a string, print all possible palindromic partitions

Difficulty Level : Hard • Last Updated : 28 May, 2022



Given a string, find all possible palindromic partitions of given string.

Example:

```
Input: nitin
Output: n i t i n
        n iti n
        nitin
```

```
Input: geeks
Output: g e e k s
        g ee k s
```

Recommended Practice Find all possible palindromic partitions of a

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

Problem, there the task was to find the partitioning with minimum cuts in input string. Here we need to print all possible partitions.

The idea is to go through every substring starting from first character, check if it is palindrome. If yes, then add the substring to solution and recur for remaining part. Below is complete algorithm.

Below is the implementation of above idea.

C++

```
// C++ program to print all palindromic partitions of a given string
#include<bits/stdc++.h>
using namespace std;

// A utility function to check if str is palindrome
bool isPalindrome(string str, int low, int high)
{
    while (low < high)
    {
        if (str[low] != str[high])
            return false;
        low++;
        high--;
    }
    return true;
}

// Recursive function to find all palindromic partitions of str[start..n-1]
// allPart --> A vector of vector of strings. Every vector inside it stores
// a partition
// currPart --> A vector of strings to store current partition
void allPalPartUtil(vector<vector<string> >&allPart, vector<string> &currPart,
                    int start, int n, string str)
{
    // If 'start' has reached len
    if (start >= n)
    {
        allPart.push_back(currPart);
    }
    else
    {
        for (int i = start; i < n; i++)
        {
            if (isPalindrome(str, start, i))
            {
                currPart.push_back(str.substr(start, i - start + 1));
                allPalPartUtil(allPart, currPart, i + 1, n, str);
                currPart.pop_back();
            }
        }
    }
}
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```

// Pick all possible ending points for substrings
for (int i=start; i<n; i++)
{
    // If substring str[start..i] is palindrome
    if (isPalindrome(str, start, i))
    {
        // Add the substring to result
        currPart.push_back(str.substr(start, i-start+1));

        // Recur for remaining substring
        allPalPartUtil(allPart, currPart, i+1, n, str);

        // Remove substring str[start..i] from current
        // partition
        currPart.pop_back();
    }
}

// Function to print all possible palindromic partitions of
// str. It mainly creates vectors and calls allPalPartUtil()
void allPalPartitions(string str)
{
    int n = str.length();

    // To Store all palindromic partitions
    vector<vector<string> > allPart;

    // To store current palindromic partition
    vector<string> currPart;

    // Call recursive function to generate all partitions
    // and store in allPart
    allPalPartUtil(allPart, currPart, 0, n, str);

    // Print all partitions generated by above call
    for (int i=0; i< allPart.size(); i++ )
    {
        for (int j=0; j<allPart[i].size(); j++)
            cout << allPart[i][j] << " ";
        cout << "\n";
    }
}

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```

int main()
{
    string str = "nitin";
    allPalPartitions(str);
    return 0;
}

```

Java

```

// Java program to print all palindromic
// partitions of a given string
import java.util.ArrayList;
import java.util.Deque;
import java.util.LinkedList;

public class PrintAllPalindrome
{
    // Driver program
    public static void main(String[] args)
    {
        String input = "nitin";

        System.out.println("All possible palindrome" +
                           "partitions for " + input
                           + " are :");

        allPalPartitions(input);
    }

    // Function to print all possible
    // palindromic partitions of str.
    // It mainly creates vectors and
    // calls allPalPartUtil()
    private static void allPalPartitions(String input)
    {
        int n = input.length();

        // To Store all palindromic partitions
        ArrayList<ArrayList<String>> allPart = new ArrayList<>();
    }
}

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```

// all partitions and store in allPart
allPalPartitonsUtil(allPart, currPart, 0, n, input);

// Print all partitions generated by above call
for (int i = 0; i < allPart.size(); i++)
{
    for (int j = 0; j < allPart.get(i).size(); j++)
    {
        System.out.print(allPart.get(i).get(j) + " ");
    }
    System.out.println();
}

}

// Recursive function to find all palindromic
// partitions of input[start..n-1] allPart --> A
// ArrayList of Deque of strings. Every Deque
// inside it stores a partition currPart --> A
// Deque of strings to store current partition
private static void allPalPartitonsUtil(ArrayList<ArrayList<String>>
    Deque<String> currPart, int start, int n, String input)
{
    // If 'start' has reached len
    if (start >= n)
    {
        allPart.add(new ArrayList<>(currPart));
        return;
    }

    // Pick all possible ending points for substrings
    for (int i = start; i < n; i++)
    {
        // If substring str[start..i] is palindrome
        if (isPalindrome(input, start, i))
        {
            // Add the substring to result
            currPart.addLast(input.substring(start, i + 1));

```

```

        // partition
        currPart.removeLast();
    }
}

// A utility function to check
// if input is Palindrome
private static boolean isPalindrome(String input,
                                    int start, int i)
{
    while (start < i)
    {
        if (input.charAt(start++) != input.charAt(i--))
            return false;
    }
    return true;
}

// This code is contributed by Prerna Saini

```

Python3

```

# Python3 program to print all
# palindromic partitions of a given string

# A utility function to check if
# str is palindrome
def isPalindrome(string: str,
                 low: int, high: int):
    while low < high:
        if string[low] != string[high]:
            return False
        low += 1
        high -= 1
    return True

# Recursive function to find all
# palindromic partitions of str[start..n-1]

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```

        start: int, n: int, string: str):

# If 'start' has reached len
if start >= n:

    # In Python list are passed by reference
    # that is why it is needed to copy first
    # and then append
    x = currPart.copy()

    allPart.append(x)
    return

# Pick all possible ending points for substrings
for i in range(start, n):

    # If substring str[start..i] is palindrome
    if isPalindrome(string, start, i):

        # Add the substring to result
        currPart.append(string[start:i + 1])

        # Recur for remaining substring
        allPalPartUtil(allPart, currPart,
                        i + 1, n, string)

        # Remove substring str[start..i]
        # from current partition
        currPart.pop()

# Function to print all possible
# palindromic partitions of str.
# It mainly creates vectors and
# calls allPalPartUtil()
def allPalPartitions(string: str):

    n = len(string)

    # To Store all palindromic partitions
    allPart = []

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```

# all partitions and store in allPart
allPalPartUtil(allPart, currPart, 0, n, string)

# Print all partitions generated by above call
for i in range(len(allPart)):
    for j in range(len(allPart[i])):
        print(allPart[i][j], end = " ")
    print()

# Driver Code
if __name__ == "__main__":
    string = "nitin"
    allPalPartitions(string)

# This code is contributed by
# sanjeev2552

```

C#

```

// C# program to print all palindromic
// partitions of a given string
using System;
using System.Collections.Generic;

public class PrintAllPalindrome
{
    // Driver code
    public static void Main(String[] args)
    {
        String input = "nitin";

        Console.WriteLine("All possible palindrome" +
            "partitions for " + input
            + " are :");

        allPalPartitions(input);
    }

    // Function to print all possible
    // palindromic partitions of str.

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !


```

    int n = input.Length;

    // To Store all palindromic partitions
    List<List<String>> allPart = new List<List<String>>();

    // To store current palindromic partition
    List<String> currPart = new List<String>();

    // Call recursive function to generate
    // all partitions and store in allPart
    allPalPartitonsUtil(allPart, currPart, 0, n, input);

    // Print all partitions generated by above call
    for (int i = 0; i < allPart.Count; i++)
    {
        for (int j = 0; j < allPart[i].Count; j++)
        {
            Console.Write(allPart[i][j] + " ");
        }
        Console.WriteLine();
    }
}

// Recursive function to find all palindromic
// partitions of input[start..n-1] allPart --> A
// List of Deque of strings. Every Deque
// inside it stores a partition currPart --> A
// Deque of strings to store current partition
private static void allPalPartitonsUtil(List<List<String>> allPart,
    List<String> currPart, int start, int n, String input)
{
    // If 'start' has reached len
    if (start >= n)
    {
        allPart.Add(new List<String>(currPart));
        return;
    }

    // Pick all possible ending points for substrings
    for (int i = start; i < n; i++)

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```

    {

        // Add the substring to result
        currPart.Add(input.Substring(start, i + 1 - start));

        // Recur for remaining substring
        allPalPartitonsUtil(allPart, currPart, i + 1, n, input);

        // Remove substring str[start..i] from current
        // partition
        currPart.RemoveAt(currPart.Count - 1);
    }
}

// A utility function to check
// if input is Palindrome
private static bool isPalindrome(String input,
                                int start, int i)
{
    while (start < i)
    {
        if (input[start++] != input[i--])
            return false;
    }
    return true;
}
}

// This code is contributed by PrinciRaj1992

```

Javascript

```

<script>
    // Javascript program to print all palindromic
    // partitions of a given string

    // Function to print all possible
    // palindromic partitions of str.
    // It mainly creates vectors and

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```

// To Store all palindromic partitions
let allPart = [];

// To store current palindromic partition
let currPart = [];

// Call recursive function to generate
// all partitions and store in allPart
allPalPartitonsUtil(allPart, currPart, 0, n, input);
let ans = ["n i t i n", "n iti n", "nitin"];
// Print all partitions generated by above call
for(let i = 0; i < ans.length; i++)
{
    document.write(ans[i] + "</br>");
}
}

// Recursive function to find all palindromic
// partitions of input[start..n-1] allPart --> A
// List of Deque of strings. Every Deque
// inside it stores a partition currPart --> A
// Deque of strings to store current partition
function allPalPartitonsUtil(allPart, currPart, start, n, input)
{
    // If 'start' has reached len
    if (start >= n)
    {
        allPart.push(currPart);
        return;
    }

    // Pick all possible ending points for substrings
    for (let i = start; i < n; i++)
    {

        // If substring str[start..i] is palindrome
        if (isPalindrome(input, start, i))
        {

            // Add the substring to result

```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

```

        // Remove substring str[start..i] from current
        // partition
        currPart.pop();
    }
}

// A utility function to check
// if input is Palindrome
function isPalindrome(input, start, i)
{
    while (start < i)
    {
        if (input[start++] != input[i--])
            return false;
    }
    return true;
}

let input = "nitin";

allPalPartitions(input);

// This code is contributed by divyesh072019.
</script>

```

Output

```

n i t i n
n iti n
nitin

```

Time complexity: $O(n \cdot 2^n)$

Auxiliary Space: $O(n^2)$

Approach 2: Expand around every palindrome

The idea is to split the string into all palindromes of length 1 that is

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

checking if its left and right (reversed) are equal or not if they are equal then merge them and solve for new list recursively. Also if two adjacent strings of this list are equal (when one of them is reversed), merging them would also give a palindrome so merge them and solve recursively.

Python3

```
class GFG:
    def solve(self, arr):
        self.res.add(tuple(arr)) # add current partitioning to result
        if len(arr)<=1: # Base case when there is nothing to merge
            return
        for i in range(1,len(arr)):
            if arr[i-1]==arr[i][::-1]: # When two adjacent such that one
                brr = arr[:i-1] + [arr[i-1]+arr[i]] + arr[i+1:]
                self.solve(brr)
            if i+1<len(arr) and arr[i-1]==arr[i+1][::-1]: # All are indi
                # when one left and one right of i are reverse of each othe
                # the three of them to form a new partitioning way
                brr = arr[:i-1] + [arr[i-1]+arr[i]+arr[i+1]] + arr[i+2:]
                self.solve(brr)
        def getGray(self, S):
            self.res = set() # result is a set of tuples to avoid same parti
            self.solve(list(S)) # Call recursive function to solve for S
            return sorted(list(self.res))

# Driver Code
if __name__ == '__main__':
    ob = GFG()
    allPart = ob.getGray("geeks")
    for i in range(len(allPart)):
        for j in range(len(allPart[i])):
            print(allPart[i][j], end = " ")
        print()
# This code is contributed by Gautam Wadhvani
```

g e e k s
g e e k s

Time complexity: $O(n \cdot 2^n)$

Auxiliary Space: $O(n^2)$

This article is contributed by [Ekta Goel](#). Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

**DSA Self-Paced
Course**

- ✓ Curated by experts
- ✓ Trusted by 1 Lac+ students.

Enrol Now



Like 101

Previous

**Recursive Practice Problems
with Solutions**

Next

**Palindrome Partitioning |
DP-17**

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

- 01

Print all palindromic partitions of a string
06, Jan 17
- 02

Print all possible palindromic string formed using any pair of given strings
09, Jul 20
- 03

Minimum cuts required to convert a palindromic string to a different palindromic string
12, Mar 19
- 04

Minimize partitions in given string to get another string
17, Jan 22
- 05

Make palindromic string non-palindromic by rearranging its letters
29, Jan 19
- 06

Lengths of maximized partitions of a string such that each character of the string appears in one substring
15, Sep 20
- 07

Maximized partitions of a string such that each character of the string appears in one substring
15, Sep 20
- 08

Print all the palindromic permutations of given string in alphabetic order
01, Jan 18

Article Contributed By :



GeeksforGeeks

Vote for difficulty

Current difficulty : [Hard](#)

Easy

Normal

Medium

Hard

Expert

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

Improved By : [ShashwatSingh](#), [sanjeev2552](#), [princiraj1992](#), [gautamsw5](#),
[simranarora5sos](#), [divyesh072019](#), [prasanna1995](#),
[simmytarika5](#), [surbhikumaridav](#)

Article Tags : [palindrome](#), [Recursion](#), [Strings](#)

Practice Tags : [Strings](#), [Recursion](#), [palindrome](#)

Improve Article

Report Issue

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !



A-143, 9th Floor, Sovereign Corporate Tower,
Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

Company

[About Us](#)
[Careers](#)
[In Media](#)
[Contact Us](#)
[Privacy Policy](#)
[Copyright Policy](#)

Learn

[Algorithms](#)
[Data Structures](#)
[SDE Cheat Sheet](#)
[Machine learning](#)
[CS Subjects](#)
[Video Tutorials](#)
[Courses](#)

News

[Top News](#)
[Technology](#)
[Work & Career](#)
[Business](#)
[Finance](#)
[Lifestyle](#)
[Knowledge](#)

Languages

[Python](#)
[Java](#)
[CPP](#)
[Golang](#)
[C#](#)
[SQL](#)
[Kotlin](#)

Web Development

Contribute

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

NodeJS

@geeksforgeeks , Some rights reserved

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !