

macOS	✓
Windows	>
Android	>
iOS / iPadOS	>
Routers	>
NAS	>
IoT	▼
Low Bandwidth Mode	
Multithreading	
Layer 2 Bridge	
Layer 5 Proxy (Pylon)	
Route between ZeroTier and Physical Networks	
FreeBSD	>
FAQ & Troubleshooting	
Glossary	

Multithreading

As of version `1.14.1` ZeroTier is capable of utilizing more than one CPU core for traffic processing. This enables greater total throughput and more efficient use of machines handling large amounts of traffic.

 BETA

This is currently a beta feature and we welcome any feedback and/or test results. For now it is only available for Linux and is disabled by default. It will be ported to FreeBSD, macOS, and Windows in a future release.

The feature requires manual activation using the `local.conf` file in the same home directory that stores your node's identity files. If that file is not already present, create it.

Example usage

Example local.conf

```
{
  "settings":
  {
    "multicoreEnabled": true,
    "concurrency": 2,
    "cpuPinningEnabled": true
  }
}
```

See [here](#) for more info on how to configure the client using `local.conf`

Tip for success

It is recommended that you choose a concurrency level that is reflective of the actual number of physical (not virtual) cores on your machine. For instance, if `nproc` reports `4`, set a concurrency level of `2`. Additionally, enabling [pinning](#) seems to improve performance in more cases than not.

Multithreading is unlikely to improve performance over the Internet but will over a physical LAN in most cases.

Tags:

tutorial

troubleshooting

local-config

Example usage

Tip for success

Product	Documentation	Community & Support	Company
Download 	Getting Started	Discussion Forum 	About 
ZeroTier Central 	This is ZeroTier	GitHub 	Blog 
Pricing	Guides	Contact Support 	Careers 
Security	FAQ		Privacy Policy 