



# Parallelized DeepFlow

We changed the project title since our parallelization performs well on both images and videos

Team: Shiyu Huang, Hongxiang Qiu, Zeyu Zhao, Zongren Zou

# DeepFlow and Existing Work



- DeepFlow algorithm

- For a pair of consecutive images, DeepFlow algorithm minimizes following energy function (non-convex and non-linear), by solving Euler-Lagrange equations (variational method), which is a general technique for minimizing energy functions, or objective functions with integral

$$E(\mathbf{w}) = \int_{\Omega} E_D + \alpha E_S + \beta E_M d\mathbf{x}$$

$$E_D = \delta \Psi \left( \sum_{i=1}^c \mathbf{w}^\top \bar{\mathbf{J}}_0^i \mathbf{w} \right) + \gamma \Psi \left( \sum_{i=1}^c \mathbf{w}^\top \bar{\mathbf{J}}_{xy}^i \mathbf{w} \right) \quad E_S = \Psi \left( \|\nabla u\|^2 + \|\nabla v\|^2 \right) \quad E_M = c\phi \Psi \left( \|\mathbf{w} - \mathbf{w}'\|^2 \right).$$

- Existing work uses SOR method to iteratively solve those equations, with no parallelization (serial). SOR part takes over 78% of total running time.

- Data

- Data can be any two consecutive images or a video
- Need for HPC: two-way flow for 20-minute 1080p video takes **29.5 days!**

- Problem

- SOR (existing implementation) has serial dependencies and thus not parallelizable

# Our Solution



- Algorithm Change

- Besides SOR, there are other parallelizable iterative methods for solving linear equations. Namely, **Jacobi** and **RedBlack SOR (RBSOR)**

1	4	7
2	5	8
3	6	9

SOR

1	4	7
2	5	8
3	6	9

Jacobi



5	2	8
1	7	4
6	3	9

RBSOR (Advanced Feature)

Numbers in cells are serial calculation order. We are calculating black cell, it depends on the last iteration values of blue cells and current iteration values of the red cells.


- Empirical Convergence and Quality

- SOR is the best (but not parallelizable)
- **RBSOR is better than Jacobi! We'll use RBSOR**



Diff. for Jacobi (left) and RBSOR (right)

# Parallelization Design



Shared-memory  
parallelization  
(OpenMP and OpenACC)

Since pgcc does not support v4sf,  
we have to drop this optimization,  
which adds overheads to OpenACC  
implementation.

DeepFlow solves about 300 linear  
systems and each linear system  
has different size. So we have to  
reassign MPI jobs every time. Thus  
our MPI has a lot of overheads.

A	B	C	D
E	F	G	H
I	J	K	L
M	N	O	P




A	B	C	D
E	F	G	H
I	J	K	L

E	F	G	H
I	J	K	L
M	N	O	P

MPI

The implementation of MPI is very  
complicated since linear solver is not the  
only part in DeepFlow algorithm.

For OpenACC, data is copied to GPU only once.



## MapReduce + OpenMP for Video

Worker nodes get frames and matches from HDFS  
and compute flows using OpenMP DeepFlow. The  
calculated flow is uploaded to HDFS.

## MPI + OpenMP

# Performance Evaluation



- For 2 Consecutive Images

(Tested on AWS m4.2xlarge instances, all parallelization is based on RBSOR Serial)


	360p	720p	1080p
Original Serial	4.598	19.382	42.582
RBSOR Serial	3.687	15.812	34.476
OpenACC (g3.4xlarge)	3.737	16.499	28.385
OMP (4 threads)	1.910	9.160	19.730
MPI (4 processes)	7.654	30.553	73.249
MPI (3) + OMP (4)	7.133	28.026	69.213

Time (**seconds**) spent for generating one flow for images

- For 1-second Video (MapReduce)


	SOR	OMP	2 nodes	4 nodes	8 nodes
720p	752	414	280	193	112

Time (**seconds**) spent for generating two-way flows



OpenMP Speedup Plot

(For 8 threads, we have results for 4core-8thread CPU and 8core-16thread CPU)



MapReduce + OpenMP Speedup Plot

# Application



- DeepFlow is useful in
  - Object tracking and activity recognition
  - Motion based segmentation
  - Video processing
    - Slow motion video (Advanced Feature)
    - Stabilize synthesized video



Left: Stylization

Right: Slow Motion



# Appendix



- Links

- Source code and documentation: <https://github.com/zeruniverse/CS205-project>
- Website Report: <https://zeruniverse.github.io/CS205-project/>

- Goals Achieved

- Changed the linear system solver of DeepFlow to a parallelizable one (RBSOR)
- Implemented multiple parallelization techniques
  - OpenMP
  - MPI (not working well)
  - OpenACC (not working well)
  - MPI + OpenMP (not working well)
  - MapReduce + OpenMP for video
- Implemented two applications of DeepFlow (code in the above link)

- Citations

- See here: <https://zeruniverse.github.io/CS205-project/conclusion.html#reference>