

Needle Drivers And Methods Of Manufacture And Use Thereof

DOCUMENT ID DATE PUBLISHED

US 11937806 B2 2024-03-26

INVENTOR INFORMATION

NAME	CITY	STATE	ZIP CODE	COUNTRY
Almodovar; Luis Jose	San Juan	PR	N/A	US

ASSIGNEE INFORMATION

NAME	CITY	STATE	ZIP CODE	COUNTRY
Ergosurgical Group Corp.	N/A	PR	N/A	US

TYPE CODE
02

APPLICATION NO DATE FILED

16/447543 2019-06-20

DOMESTIC PRIORITY (CONTINUITY DATA)

us-provisional-application US 62687752 20180620

US CLASS CURRENT:

[1/1](#)

CPC CURRENT

TYPE	CPC	DATE
CPCI	A 61 B 17/0483	2013-01-01
CPCI	A 61 B 17/0469	2013-01-01
CPCI	A 61 B 17/06066	2013-01-01
CPCI	A 61 B 17/0482	2013-01-01
CPCI	A 61 B 17/062	2013-01-01
CPCA	A 61 B 2017/2932	2013-01-01
CPCA	A 61 B 2017/0472	2013-01-01
CPCA	A 61 B 2017/2903	2013-01-01
CPCA	A 61 B 2017/2933	2013-01-01
CPCA	A 61 B 2017/2937	2013-01-01
CPCA	A 61 B 2017/2927	2013-01-01
CPCA	A 61 B 2017/2943	2013-01-01
CPCA	A 61 B 2017/2912	2013-01-01
CPCA	A 61 B 2017/2923	2013-01-01

KWIC Hits

A needle driver can include a first jaw hosting a first shaft and a second jaw hosting a second shaft. The first shaft hosts a first roller and a first set of teeth. The second shaft hosts a second roller and a second set of teeth. The second jaw moves relative to the first jaw between an open position and a closed position. The first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims the benefit of U.S. Provisional Patent Application No. 62/687,752 filed 20 Jun. 2018, which is herein incorporated by reference for all purposes.

TECHNICAL FIELD

(1) Generally, this disclosure relates to surgical instruments. More particularly, this disclosure relates to needle drivers.

BACKGROUND

(2) A surgeon operating on a tissue within a patient may need to suture through the tissue, grasp the tissue, or dissect the tissue. However, these actions require a set of different surgical instruments, which can be expensive to obtain, incompatible with each other, laborious to disinfect, non-ergonomic, bulky, or time consuming to insert into the patient or to withdraw from within the patient. Additionally, if suturing requires a needle and the needle varies in size, then the set of different surgical instruments may need to contain a needle specific driver, which can be expensive to obtain, incompatible with other members of the set of different surgical instruments, laborious to disinfect, non-ergonomic, bulky, or time consuming to insert into the patient or to withdraw from within the patient. Moreover, if the needle needs to be driven into the tissue at various angles, then the set of different surgical instruments may need to contain an angle specific needle driver, which can be expensive to obtain, incompatible with other members of the set of different surgical instruments, laborious to disinfect, non-ergonomic, bulky, or time consuming to insert into the patient or to withdraw from within the patient. Also, if the surgeon is not right handed or ambidextrous, then some member of the set of different surgical instruments may need to be configured for left-handed use, which may be expensive to locate, non-existent, or incompatible with some right-handed surgical instruments if corresponding left-handed surgical instruments are not readily available.

(3) Laparoscopic surgery can be challenging to master and requires a different set of skills from open surgery. For example, during the laparoscopic surgery, the surgeon has a limited range of motion, enters the patient through a small incision in the patient, and uses a set of laparoscopic surgical instruments with limited visibility in a crowded surgical area within the patient. Moreover, some member of the set of laparoscopic surgical instruments can have some endpoints that move in directions opposite to movements of the surgeon due to a presence of a pivot point, thereby making at least some surgical movements non-intuitive or difficult to learn. Additionally, at least some visualization of laparoscopic procedures occurs using a two-dimensional display at a distance with a limited haptic feedback, thereby limiting at least some depth perception and cumulatively complicating the laparoscopic procedures.

(4) Laparoscopic suturing and knot tying can be laborious and time consuming, requiring coordination of multiple steps, significant concentration and effort, and thereby presenting a challenge for at least some laparoscopic surgeons. This may be so because during the laparoscopic surgery, at least some surgeons have difficulty assessing depth and three-dimensional orientation to place the set of laparoscopic surgical instruments. Those surgeons can be challenged by limited visibility (visualization occurs using a two-dimensional display at a distance), limited range of motion and haptic feedback, and some tool endpoints moving in directions opposite to that of the surgeon.

(5) Extended surgical time needed to perform laparoscopic suturing and knot tying can also be problematic. Numerous studies have shown an association between longer duration of anesthesia and negative outcomes, postoperative nausea and vomiting, thromboembolism, postoperative infection, postoperative core hypothermia, postoperative cardiopulmonary complications, and death in cosmetic surgery. Analysis of a large corpus of surgical operations has found that operative duration is independently associated with increased risk-adjusted infection complications and length of stay.

SUMMARY

(6) In an embodiment, a needle driver comprises a first jaw hosting a first shaft, wherein the first shaft hosts a first roller and a first set of teeth; and a second jaw hosting a second shaft, wherein the second shaft hosts a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth.

(7) In an embodiment, a method comprises causing a device to be inserted into a first object, wherein the device includes a first jaw hosting a first shaft and a second jaw hosting a second shaft, wherein the first shaft hosts a first roller and a first set of teeth, wherein the second shaft hosts a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth; and causing the first roller and the second roller to grasp a second object therebetween within the first object when the second jaw is in the closed position.

(8) In an embodiment, a method comprises causing a device to be inserted into a first object, wherein the device includes a first jaw hosting a first shaft and a second jaw hosting a second shaft, wherein the first shaft hosts a first roller and a first set of teeth, wherein the second shaft hosts a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth; and causing the first roller and the second roller to manipulate a second object within the first object when the second jaw is in the closed position.

(9) In an embodiment, a method comprises causing a device to be inserted into a first object, wherein the device includes a first jaw hosting a first shaft and a second jaw hosting a second shaft, wherein the first shaft hosts a first roller and a first set of teeth, wherein the second shaft hosts a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth; and causing the first roller and the second roller to dissect a second object within the first object when the second jaw is in the closed position.

(10) In an embodiment, a method comprises causing a device to be inserted into a first object, wherein the device includes a first jaw hosting a first shaft and a second jaw hosting a second shaft, wherein the first shaft hosts a first roller and a first set of teeth, wherein the second shaft hosts a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth; and causing the first roller and the second roller to isolate a second object within the first object when the second jaw is in the closed position.

(11) In an embodiment, a method comprises causing a device to be inserted into a first object, wherein the device includes a first jaw hosting a first shaft and a second jaw hosting a second shaft, wherein the first shaft hosts a first roller and a first set of teeth, wherein the second shaft hosts a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth; and causing the first roller and the second roller to separate a second object within the first object when the second jaw is in the closed position.

(12) In an embodiment, a needle driver comprises a first jaw hosting a first shaft, wherein the first shaft hosts a first roller and a first set of teeth; and a second jaw hosting a second shaft, wherein the second shaft hosts a second roller including a cylindrical portion, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth abuts the cylindrical portion when the second jaw is in the closed position such that (a) the cylindrical portion can drive the first set of teeth, and (b) the first roller and the second roller can drive a needle therebetween when the cylindrical portion drives the first set of teeth.

(13) In an embodiment, a method comprises causing a device to be inserted into a first object, wherein the device includes a first jaw hosting a first shaft and a second jaw hosting a second shaft, wherein the first shaft hosts a first roller and a first set of teeth, wherein the second shaft hosts a second roller including a cylindrical portion, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth abuts the cylindrical portion when the second jaw is in the closed position such that (a) the cylindrical portion can drive the first set of teeth, and (b) the first roller and the second roller can drive a needle therebetween when the cylindrical portion drives the first set of teeth; and causing the first roller and the second roller to at least one of grasp, separate, manipulate, dissect, or isolate a second object within the first object when the second jaw is in the closed position.

(14) In an embodiment, when the second jaw is in the closed position, the first roller and the second roller grasp a needle in a plane of orientation. In an embodiment, the plane of orientation is perpendicular to the axis of the first shaft. In an embodiment, the plane of orientation is parallel to the axis of the first shaft. In an embodiment, the plane of orientation is at an angle to the axis of the first shaft.

Description

DESCRIPTION OF DRAWINGS

(1) FIG. 1 shows a rear view of an embodiment of a needle driver in a closed position according to this disclosure.

(2) FIG. 2 shows a rear view of an embodiment of a needle driver in an open position according to this disclosure.

(3) FIG. 3 shows a front view of an embodiment of a needle driver in an open position according to this disclosure.

(4) FIG. 4 shows a front view of an embodiment of a needle driver in a closed position according to this disclosure.

(5) FIG. 5 shows a front view of an embodiment of a pair of shafts in a gear engagement according to this disclosure.

(6) FIG. 6 shows a front view of an embodiment of a first jaw hosting a first shaft according to this disclosure.

(7) FIG. 7 shows a front view of an embodiment of a second jaw hosting a second shaft according to this disclosure.

(8) FIG. 8 shows a front view of an embodiment of a needle being inserted between a pair of rollers when the pair of rollers is in an open position according to this disclosure.

(9) FIG. 9 shows a front view of an embodiment of a needle being engaged via a pair of rollers when the pair of rollers is in a closed position according to this disclosure.

(10) FIG. 10 shows a front view of an embodiment of a testing device for a needle driver according to this disclosure.

(11) FIG. 11 shows a rear view of an embodiment of a testing device hosting a needle driver according to this disclosure.

(12) FIG. 12 shows a front view of an embodiment of a rotary mechanism for a needle driver according to this disclosure.

(13) FIG. 13 shows a rear view of an embodiment of a testing device with a rotary mechanism hosting a needle driver according to this disclosure.

(14) FIG. 14 shows a front view of an embodiment of a needle driver hosting a line according to this disclosure.

(15) FIG. 15 shows a front view of an embodiment of a needle driver hosting a mating mechanism according to this disclosure.

(16) FIG. 16 shows a diagram of an embodiment of a bevel gear assembly for a needle driver according to this disclosure.

(17) FIG. 17 shows a rear view of an embodiment of a needle driver hosting a bevel gear assembly according to this disclosure.

(18) FIG. 18 shows a front view of an embodiment of a needle driver hosting a bevel gear assembly according to this disclosure.

(19) FIG. 19 shows a diagram of an embodiment of a side profile of a pair of rollers engaging an arcuate needle according to this disclosure.

(20) FIG. 20 shows a diagram of an embodiment of a side profile of a pair of rollers engaging an arcuate needle according to this disclosure.

(21) FIG. 21 shows a pair of diagrams of a pair of embodiments of a pair of side profiles of a pair of rollers engaging a pair of arcuate needles of a pair of different sizes according to this disclosure.

(22) FIG. 22 shows a diagram of an embodiment of a side profile of a roller having a plurality of slanted grooves according to this disclosure.

(23) FIG. 23 shows a diagram of an embodiment of a side profile of a roller having a plurality of wave grooves according to this disclosure.

(24) FIG. 24 shows a pair of diagrams of a pair of embodiments of a pair of side profiles of a pair of rollers with a plurality of wave grooves engaging a pair of arcuate needles of a pair of different sizes according to this disclosure.

(25) FIG. 25 shows a pair of diagrams of a pair of embodiments of a pair of side profiles of a pair of rollers with a pair of different groove designs engaging a pair of arcuate needles of a pair of different sizes according to this disclosure.

(26) FIG. **26** shows a diagram of an embodiment of a pair of rollers with a slanted groove design according to this disclosure.

(27) FIG. **27** shows a rear view of an embodiment of a needle driver with a plurality of levers according to this disclosure.

(28) FIG. **28** shows a rear view of an embodiment of a needle driver with a plurality of levers according to this disclosure.

(29) FIG. **29** shows a rear view of an embodiment of a needle driver with a linkage according to this disclosure.

(30) FIG. **30** shows an exploded view of an embodiment of a needle driver with a linkage according to this disclosure.

(31) FIG. **31** shows a diagram of a side profile of a roller according to this disclosure.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

(32) Generally, this disclosure discloses various needle drivers and methods of manufacture and use thereof. The needle drivers can include a plurality of rollers that can move between a closed position and an open position. The rollers can rotationally drive a needle therebetween when the rollers are in the closed position. Likewise, the rollers can be used to grasp an object (e.g., animate, inanimate, tissue, instrument, implantable) when the rollers are in the closed position or in the open position or act (e.g., manipulate, dissect, isolate, separate, intervene, mount, drop, move, drag) with the object when the rollers are in the closed position or in the open position. For example, the object, when animate, can include a tissue, an organ, a body part, whether of human or animal, or others. For example, the tissue can be a muscle tissue, a bone tissue, a nerve tissue, an organ tissue, or others. For example, the object, when inanimate, can include a medical device, a prosthesis, an implantable, a machine, a surgical instrument, or others. The closed position can be a clamping position. Note that this disclosure may be embodied in many different forms and should not be construed as necessarily being limited to various embodiments disclosed herein. Rather, these embodiments are provided so that this disclosure is thorough and complete, and fully conveys various concepts of this disclosure to skilled artisans.

(33) Note that various terminology used herein can imply direct or indirect, full or partial, temporary or permanent, action or inaction. For example, when an element is referred to as being “on,” “connected,” or “coupled” to another element, then the element can be directly on, connected, or coupled to another element or intervening elements can be present, including indirect or direct variants. In contrast, when an element is referred to as being “directly connected” or “directly coupled” to another element, then there are no intervening elements present.

(34) As used herein, various singular forms “a,” “an” and “the” are intended to include various plural forms as well, unless specific context clearly indicates otherwise.

(35) As used herein, various presence verbs “comprises,” “includes” or “comprising,” “including” when used in this specification, specify a presence of stated features, integers, steps, operations, elements, or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, or groups thereof.

(36) As used herein, a term “or” is intended to mean an inclusive “or” rather than an exclusive “or.” That is, unless specified otherwise, or clear from context, “X employs A or B” is intended to mean any of a set of natural inclusive permutations. That is, if X employs A; X employs B; or X employs both A and B, then “X employs A or B” is satisfied under any of the foregoing instances.

(37) As used herein, a term “or others,” “combination,” “combinatory,” or “combinations thereof” refers to all permutations and combinations of listed items preceding that term. For example, “A, B, C, or combinations thereof” is intended to include at least one of: A, B, C, AB, AC, BC, or ABC, and if order

is important in a particular context, also BA, CA, CB, CBA, BCA, ACB, BAC, or CAB. Continuing with this example, expressly included are combinations that contain repeats of one or more item or term, such as BB, AAA, AB, BBC, AAABCCCC, CBBAAA, CABABB, and so forth. Skilled artisans understand that typically there is no limit on number of items or terms in any combination, unless otherwise apparent from the context.

(38) As used herein, unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in an art to which this disclosure belongs. Various terms, such as those defined in commonly used dictionaries, should be interpreted as having a meaning that is consistent with a meaning in a context of a relevant art and should not be interpreted in an idealized or overly formal sense unless expressly so defined herein.

(39) As used herein, relative terms such as “below,” “lower,” “above,” and “upper” can be used herein to describe one element's relationship to another element as illustrated in the set of accompanying illustrative drawings. Such relative terms are intended to encompass different orientations of illustrated technologies in addition to an orientation depicted in the set of accompanying illustrative drawings. For example, if a device in the set of accompanying illustrative drawings were turned over, then various elements described as being on a “lower” side of other elements would then be oriented on “upper” sides of other elements. Similarly, if a device in one of illustrative figures were turned over, then various elements described as “below” or “beneath” other elements would then be oriented “above” other elements. Therefore, various example terms “below” and “lower” can encompass both an orientation of above and below.

(40) As used herein, a term “about” or “substantially” refers to a $\pm 10\%$ variation from a nominal value/term. Such variation is always included in any given value/term provided herein, whether or not such variation is specifically referred thereto.

(41) FIG. 1 shows a rear view of an embodiment of a needle driver in a closed position according to this disclosure. FIG. 2 shows a rear view of an embodiment of a needle driver in an open position according to this disclosure. FIG. 3 shows a front view of an embodiment of a needle driver in an open position according to this disclosure. FIG. 4 shows a front view of an embodiment of a needle driver in a closed position according to this disclosure. FIG. 5 shows a front view of an embodiment of a pair of shafts in a gear engagement according to this disclosure. FIG. 6 shows a front view of an embodiment of a first jaw hosting a first shaft according to this disclosure. FIG. 7 shows a front view of an embodiment of a second jaw hosting a second shaft according to this disclosure. FIG. 8 shows a front view of an embodiment of a needle being inserted between a pair of rollers when the pair of rollers is in an open position according to this disclosure. FIG. 9 shows a front view of an embodiment of a needle being engaged via a pair of rollers when the pair of rollers is in a closed position according to this disclosure.

(42) In particular, a needle driver **100** can be used for an open surgery, a minimally invasive surgery, a laparoscopic surgery, or an end effector robotic surgery. As such, the needle driver **100** can be used for manual surgery or automated surgery. Some examples of surgeries where the needle driver **100** can be employed include laparoscopic surgery, robotic surgery, video-assisted or unassisted thoracoscopic surgery, arthroscopic surgery, natural orifice surgery, endoscopic surgery, gynecologic surgery, cardiac surgery, colorectal surgery, pulmonary surgery, gastric bypass surgery, hysterectomy surgery, dental surgery, urological surgery, brain surgery, or bariatric surgery, or among many others in human (e.g., between newborn until 120 years old, male, female) or animal (e.g., mammal, birds, fish, land animals) applications.

(43) The needle driver **100** includes a first jaw **102** hosting (e.g., holding, supporting, suspending) a first shaft **108** and a second jaw **104** hosting (e.g., holding, supporting, suspending) a second shaft **106**. For example, the first jaw **102** can be embodied as a housing or a case. For example, the second jaw **102** can be embodied as a housing or a case. The second jaw **104** can be separate and distinct from the first jaw **102**, but can be unitary therewith (e.g., monolithic, same material).

(44) The first jaw **102** is shown as having a lateral cross-section that is hemispherical, but this shaping can vary (e.g., rectangular, square, triangular, oval). The second jaw **104** is shown as having a lateral cross-section that is hemispherical, but this shaping can vary (e.g., rectangular, square, triangular, oval). As shown in FIGS. **1** and **4**, together, the first jaw **102** and the second jaw **104** define an oval lateral cross-section, although this shaping can vary (e.g., rectangular, square, triangular, circular). The first jaw **102** is longitudinally longer than the second jaw **104**, although this can vary where the first jaw **102** can be longitudinally equivalent or longitudinally shorter than the second jaw **104**. The first jaw **102** or the second jaw **104** include a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(45) As shown in FIGS. **1** and **4**, the first shaft **106** extends parallel to the second shaft **108** between the first jaw **102** and the second jaw **104**. Likewise, the first shaft **106** extends parallel to the second shaft **108** external to the first jaw **102** and to the second jaw **104**. Similarly, the first shaft **106** and the second shaft **108** are positioned between the first jaw **102** and the second jaw **104**.

(46) The first shaft **106** and the second shaft **108** are rectilinear, but either or both can be non-rectilinear (e.g., arcuate, sinusoidal, pulse-shaped). The first shaft **106** or the second shaft **108** include a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(47) The first shaft **106** can cantileveredly extend from the first jaw **102**. The second shaft **108** can cantileveredly extend from the second jaw **104**. The first shaft **106** can be parallel to the second shaft **108** external to the first jaw **102**. The first shaft **106** can be parallel to the second shaft external to the second jaw **104**. The first shaft **106** can be parallel to the second shaft **108** external to the first jaw **102** and to the second jaw **104**. The first shaft **106** can be rotationally driven automatically (e.g., motor, engine, actuator, mechanical linkage, gear mechanism, pulley mechanism, hydraulic mechanism, pneumatic mechanism) or can be rotationally driven manually (e.g., user rotation).

(48) The first jaw **102** has a first longitudinal axis and the second jaw **104** has a second longitudinal axis. As shown in FIGS. **1** and **4**, the first longitudinal axis is parallel to the second longitudinal axis. As shown in FIGS. **2** and **3**, the first longitudinal axis is not parallel (e.g., acute, obtuse, perpendicular) to the second longitudinal axis. Regardless, the first shaft **106** rotates about the first longitudinal axis. Likewise, the second shaft **108** rotates about the second longitudinal axis.

(49) The first shaft **106** hosts a first roller **110** and a first set of teeth **140**. For example, the first roller **110** can be embodied as a sleeve mounted onto the first shaft **106**. The first roller **110** can be unitary (e.g., monolithic, same material) with the first shaft **106** or assembled with the first shaft **106** (e.g., adhering, fastening, mating, interlocking, magnetizing). For example, the first roller **110** can be mounted onto the first shaft **106** (e.g., end portion, not-end-portion, middle). For example, the first shaft **106** can include an end portion on which the first roller **110** is mounted, where the end portion is distal to the first jaw **102**. For example, the first roller **110** can be a cap that is mountable onto the first shaft **106**. The first roller **110** is diametrically larger than the first shaft **106**, but this configuration can vary where the first roller **110** is diametrically equivalent or diametrically lesser than the first shaft **106**. The first roller **110** can be external to the first jaw **102**.

(50) The first roller **110** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(51) The first roller **110** includes a first groove portion **112**, which has a plurality of grooves. The grooves define a plurality of peak/valley portions, male/female portions, or projection/depression portions, any of which can be perpendicular to the first roller **110** or non-perpendicular to the first roller

110 (e.g., acute, obtuse). For example, the grooves can be slanted, wavy, pulse-shaped, or others. For example, the grooves can be internally U-shaped, C-shaped, V-shaped, W-shaped, or others. The first roller **110** can avoid the first groove portion **112**. In an embodiment, the first roller comprises a flat surface. In an embodiment, the first roller comprises a textured surface without grooves.

(52) The first roller **110** has a conical end portion proximal to the first jaw **102** and a cylindrical portion that is circular and distal to the first jaw **102**. However, note that this shaping can vary. For example, the conical end portion can be absent or the cylindrical portion can be rectangular, pentagonal, octagonal, triangular, oval, or others.

(53) The first set of teeth **140** is or defines a gear, which can be a gear strip, a gear wheel, or others. For example, the gear can be a spur gear, a helical gear, or others. For example, the first shaft **106** can host a spur gear including the first set of teeth **140**. However, note that other forms of gear are possible (e.g., bevel, linear, helical). The first set of teeth **140** can be unitary (e.g., monolithic, same material) with the first shaft **106** or assembled with the first shaft **106** (e.g., adhering, fastening, mating, interlocking, magnetizing). For example, the first set of teeth **140** can be mounted onto the first shaft **106** (e.g., end portion, not end portion, middle). For example, the first shaft **106** can include a not-end-portion or middle portion on which the first set of teeth **140** is mounted, where the not-end-portion is distal to the first roller **110**. The first set of teeth **140** is housed within the first jaw **102**, but can be housed outside the first jaw **102**.

(54) The first set of teeth **140** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(55) The second shaft **108** hosts a second roller **114** and a second set of teeth **120**. For example, the second roller **114** can be embodied as a sleeve mounted onto the second shaft **108**. The second roller **114** can be unitary (e.g., monolithic, same material) with the second shaft **108** or assembled with the second shaft **108** (e.g., adhering, fastening, mating, interlocking, magnetizing). For example, the second roller **114** can be mounted onto the second shaft **108** (e.g., end portion, not-end-portion, middle). For example, the second shaft **108** can include an end portion on which the second roller **114** is mounted, where the end portion is distal to the second jaw **104**. For example, the second roller **114** can be a cap that is mountable onto the second shaft **108**. The second roller **114** is diametrically larger than the second shaft **108**, but this configuration can vary where the second roller **114** is diametrically equivalent or diametrically lesser than the second shaft **108**. The first shaft **106** can be longitudinally longer than the second shaft **108**, but this configuration can vary (e.g., longitudinally equivalent, longitudinally shorter). The second roller **114** can be external to the second jaw **104**. The second shaft **108** can be rotationally driven automatically (e.g., motor, engine, actuator, mechanical linkage, gear mechanism, pulley mechanism, hydraulic mechanism, pneumatic mechanism) or can be rotationally driven manually (e.g., user rotation).

(56) The second roller **114** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(57) The second roller **114** includes a second groove portion **116**, which has a plurality of grooves. The grooves define a plurality of peak/valley portions, male/female portions, or projection/depression portions, any of which can be perpendicular to the second roller **114** or non-perpendicular to the second roller **114** (e.g., acute, obtuse). For example, the grooves can be slanted, wavy, pulse-shaped, or others. For example, the grooves can be internally U-shaped, C-shaped, V-shaped, W-shaped, or others. The second roller **114** can avoid the second groove portion **116**. In an embodiment, the second roller comprises a flat surface. In an embodiment, the second roller comprises a textured surface without grooves.

(58) The second roller **114** has a conical end portion proximal to the second jaw **104** and a cylindrical portion that is circular and distal to the second jaw **104**. However, note that this shaping can vary. For example, the conical end portion can be absent or the cylindrical portion can be rectangular, pentagonal, octagonal, triangular, oval, or others. Further, the first roller **110** and the second roller **114** can be identical or non-identical to each other in terms of material, properties, or dimensions (e.g., length, width, thickness, diameter, radius). For example, although the first roller **110** and the second roller **114** are identical in length (or other dimensions), the first roller **110** and the second roller **114** can be non-identical in length (or other dimensions).

(59) The second set of teeth **120** is or defines a gear, which can be a gear strip, a gear wheel, or others. For example, the gear can be a spur gear, a helical gear, or others. The second shaft **108** can host a spur gear including the second set of teeth **120**. However, note that other forms of gear are possible (e.g., bevel, linear, helical). The second set of teeth **120** can be unitary (e.g., monolithic, same material) with the second shaft **108** or assembled with the second shaft **108** (e.g., adhering, fastening, mating, interlocking, magnetizing). For example, the second set of teeth **120** can be mounted onto the second shaft **108** (e.g., end portion, not end portion, middle). For example, the second shaft **108** can include a not-end-portion or middle portion on which the second set of teeth **120** is mounted, where the not-end-portion is distal to the second roller **114**. The second set of teeth **120** is housed within the second jaw **104**, but can be housed outside the second jaw **104**. For example, the first roller **106** can host a first spur gear including the first set of teeth **140** and the second roller **108** can host a second spur gear including the second set of teeth **120**, where the first spur gear engages the second spur gear such that the first spur gear drives the second spur gear.

(60) The second jaw **104** defines an opening **118**. The opening **118** is arcuate and rectangular, but this shaping can vary (e.g., rectilinear, square, dimpled, circle, triangular). The opening **118** provides a physical access or a visible access to the second set of teeth **120**, such as for maintenance, if needed. The second jaw **104** can avoid defining the opening **118**.

(61) The second set of teeth **120** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(62) As shown in FIGS. **1** and **4**, the first groove portion **112** faces the second groove portion **116** and the first groove portion **112** can contact the second groove portion **116**. Likewise, the first set of teeth **140** and the second set of teeth **120** are positioned between the first jaw **102** and the second jaw **104**. Similarly, the first set of teeth **140** can mesh with the second set of teeth **120**. However, note that variations are possible. For example, the first groove portion **112** can be longitudinally offset relative to the second groove portion **116** or vice versa. Likewise, the first set of teeth **140** or the second set of teeth **120** can be positioned outside the first jaw **102** or the second jaw **104**.

(63) The second jaw **104** defines a channel **132**. The channel **132** is internally open (e.g., U-shaped, C-shaped, V-shaped, W-shaped), but can be internally closed (e.g., O-shaped, D-shaped). The second jaw **104** can avoid defining the channel **132**.

(64) The second jaw **104** is coupled to a first end portion of a line **122** as the line **122** extends through the channel **132**. The line **122** can be embodied in various ways (e.g., tether, string, cable, chain, strap, rope, braid, bar, shaft, planar member). The line **122** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(65) The first end of the line **122** can be coupled to the second jaw **104** in various ways (e.g., knot, adhering, fastening, lassoed). The line **122** has a second end portion coupled to a control interface. The second end of the line **122** can be coupled to the control interface in various ways (e.g., knot, adhering, fastening, lassoed). However, note that this configuration can vary, such as where the line is U-shaped or C-shaped and the first end of the line **122** and the second end of the line **122** are coupled

to the control interface and a non-end portion of the line **122** (e.g., middle portion) is coupled (e.g., looped, hooked) to the second jaw **104**.

(66) The control interface can be a manual interface or an automated interface. For example, the manual interface can include a user input device (e.g., trigger, button, switch, dial, lever). For example, the automated interface can include a mover (e.g., motor, engine, actuator, mechanical linkage, gear mechanism, pulley mechanism, hydraulic mechanism, pneumatic mechanism). For example, the automated interface can be included in a robot (e.g., articulating arm, single or multi-joint end effector). For example, the needle driver **100** can include a distal portion hosting the first jaw **102** and the second jaw **104** and a proximal portion hosting the control interface. For example, the end effector can host (e.g., support, suspend, fasten, mate, interlock) the first jaw **102** or the second jaw **104**. For example, the first jaw **102** and the second jaw **104** can be housed in a housing (e.g., tube, case, encasement, arm). For example, the housing includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(67) The second jaw **104** includes a male portion **124** (e.g., tail) extending therefrom. The male portion **124** can be unitary (e.g., monolithic, same material) with the second jaw **104** or assembled with the second jaw **104** (e.g., adhering, fastening, mating, interlocking, magnetizing, mounting). For example, the male portion **124** can be distal to the second set of teeth **120**. The male portion **124** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(68) The first jaw **104** defines a female portion **126** extending thereinto. The female portion **126** is structured to mate with the male portion **124** or vice versa. As such, the male portion **124** is inserted into the female portion **126** such that a coupling relationship is established.

(69) The coupling relationship can enable the second jaw **104** to move relative to the first jaw **102** between an open position, as shown in FIGS. **2** and **3**, and a closed position, as shown in FIGS. **1** and **4**. For example, the second jaw **104** can move relative to the first jaw **102** via pivoting, rotation, sliding, or others, or any combination of the foregoing. For example, the second jaw **104** can move between the closed position and the open position relative to the first jaw **102** inclusively about or less than 180, 175, 170, 165, 160, 155, 150, 145, 140, 135, 130, 125, 120, 115, 110, 105, 100, 95, 90, 85, 80, 75, 70, 65, 60, 55, 50, 45, 44, 43, 42, 41, 40, 39, 38, 37, 36, 35, 34, 33, 32, 31, 30, 29, 28, 27, 26, 25, 24, 23, 22, 21, 20, 19, 18, 17, 16, 15, 14, 13, 12, 11, 10, 9, 8, 7, 6, 5, 4, 3, 2, or 1 degrees. For example, the second jaw **104** can form an angle relative to the first jaw **102**, where the angle can be acute, perpendicular, or obtuse. For example, the first shaft **106** can be not parallel to the second shaft **108** in the open position. For example, the second jaw **104** can be biased open (e.g., spring, elastic member) or biased closed (e.g., spring, elastic member) relative to the first jaw **102**. For example, the second jaw **104** can be default position open or default position closed relative to the first jaw **102**. In other embodiments, the second jaw **104** can move between the closed position and the open position relative to the first jaw **102** inclusively about or less than 360, 345, 330, 315, 300, 285, 270, 255, 240, 225, 210, 195, 180, 165, 150, 135, 120, 105, 90, 80, 70, 60, 50, 45, 40, 35, 30, 25, 20, 15, 10, and 5 degrees, or less than 5 degrees.

(70) The closed position can be a terminal position (e.g., last, extreme, lower bound) or the open position is a terminal position (e.g., last, extreme, upper bound). For example, the second jaw **104** has a range of motion spanning between the closed position and the open position. However, this configuration can vary where the closed position is not a terminal position (e.g., within range of positions, between terminal positions) or the open position is not a terminal position (e.g., within range of positions, between terminal positions).

(71) The first set of teeth **140** meshes with the second set of teeth **120** when the second jaw **102** is in the closed position such that (a) the first set of teeth **140** can drive (e.g., rotationally) the second set of

teeth **120** and (b) the first roller **110** and the second roller **114** can drive a needle (e.g., rectilinear, non-rectilinear, arcuate, helical, spiral) therebetween when the first set of teeth **140** drives (e.g., rotationally) the second set of teeth **120**. The first set of teeth **140** can avoid meshing with the second set of teeth **120** when the second jaw **104** is in the open position. However, note that in some open positions at least some meshing between the first set of teeth **140** can avoid meshing with the second set of teeth **120** can be possible.

(72) In the open position or in the closed position, the first set of teeth **140** can be exposed to the second jaw **102** when the second jaw **102** is in the open position. Likewise, the first set of teeth **140** can be exposed to the second set of teeth **120** when the second jaw **102** is in the open position. Similarly, the second set of teeth **120** can be exposed to the first jaw **102** when the second jaw **104** is in the open position. Also, the second set of teeth **120** can be exposed to the first set of teeth **140** when the second jaw **104** is in the open position. Additionally, the first set of teeth **140** and the second set of teeth **120** can be positioned between the first jaw **102** and the second jaw **104**.

(73) In the coupling relationship between the first jaw **102** and the second jaw **104**, the second jaw **104** can be hingedly coupled to the first jaw **102** such that the second jaw **104** can move relative to the first jaw **102** between the open position and the closed position. For example, the first jaw **102** or the second jaw **104** can host a hinge (e.g., spring, barrel, pivot, butt, mortise, case, continuous, piano, concealed, butterfly, flag, strap, biased). For example, the first jaw **102** or the second jaw **104** can be attached, fastened, mated, interlocked, adhered, or magnetized to the hinge. The second jaw **104** can be hingedly coupled to the first jaw **102** without using a pin (e.g., rectilinear pin, arcuate pin, sinusoidal pin) about which the second jaw **104** moves relative to the first jaw **102** between the open position and the closed position. However, note that the second jaw **104** can be hingedly coupled to the first jaw **102** via a pin (e.g., rectilinear pin, arcuate pin, sinusoidal pin) about which the second jaw **104** moves relative to the first jaw **102** between the open position and the closed position, where the pin laterally traverses the first jaw **102** or the second jaw **104**.

(74) In the coupling relationship between the first jaw **102** and the second jaw **104**, the second jaw **104** can be pivotally coupled to the first jaw **102** such that the second jaw **104** moves relative to the first jaw **102** between the open position and the closed position. The second jaw **104** can be pivotally coupled to the first jaw **102** without using a pin about which the second jaw **104** moves relative to the first jaw **102** between the open position and the closed position. However, note that the second jaw **104** can be pivotally coupled to the first jaw **102** via a pin (e.g., rectilinear pin, arcuate pin, sinusoidal pin) about which the second jaw **104** moves relative to the first jaw **102** between the open position and the closed position, where the pin laterally traverses the first jaw **102** or the second jaw **104**.

(75) As shown in FIGS. 1-4, the first jaw **102** includes the female portion **126** and the first set of teeth **140** is positioned between the first roller **110** and the female portion **126**. Correspondingly, the second jaw **104** includes the male portion **124** and the second set of teeth **120** is positioned between the second roller **114** and the male portion **124**. Resultantly, the female portion **126** and the male portion **114** pivotably mate such that the second jaw **104** moves relative to the first jaw **102** between the open position and the closed position. The second jaw **104** can be pivotably mated to the first jaw **102** without using a pin (e.g., rectilinear pin, arcuate pin, sinusoidal pin) about which the second jaw **104** moves relative to the first jaw **102** between the open position and the closed position. However, the second jaw **104** can be pivotably mated to the first jaw **102** via a pin (e.g., rectilinear pin, arcuate pin, sinusoidal pin) about which the second jaw **104** moves relative to the first jaw **102** between the open position and the closed position, where the pin laterally traverses the first jaw **102** or the second jaw **104**.

(76) The second jaw **104** can move relative to the first jaw from the closed position to the open position based on the line **122** being pulled in a direction away from the first jaw **102**, the second jaw **104**, the first set of teeth **140**, the second set of teeth **140**, the first roller **110**, or the second roller **114**. For example, the direction can be longitudinal to the first jaw **102**, but can include a vertical component or a lateral component. Note that another configuration is possible where the line **122** can be moved from the open position to the closed position based on the line **122** being pushed in a direction toward the first jaw **102**, the second jaw **104**, the first set of teeth **140**, the second set of teeth **140**, the first

roller **110**, or the second roller **114**. Note that in such configuration the line **122** can be sufficiently rigid to enable such force application.

(77) As shown in FIGS. **1-4**, the first jaw **102** and the second jaw **104** are self-aligning when moving from the open position to the closed position or in the closed position. However, this can vary, such as when the first jaw **102** and the second jaw **104** are not self-aligning when moving from the open position to the closed position or in the closed position. For example, the first jaw **102** and the second jaw **104** can be misaligned or offset relative to each other in the closed position.

(78) As shown in FIGS. **2** and **3**, the second shaft **108** is rotationally unconstrained in the open position. For example, the second shaft **108** can rotate freely, whether clockwise or counterclockwise, in the open position (e.g., continual rotation, several full rotations, less than one full rotation, inclusively about 720, 360, 270, 180, 120, 90, 75, 60, 50, 45, 33, 30, 20, 15, 10, or 5 degrees or more or less). However, this configuration can vary and the second shaft **108** can be rotationally constrained in the open position (e.g., locked).

(79) The first jaw **102** hosts a retaining block **128**. For example, the retaining block **128** can be fastened, adhered, mated, interlocked, mounted, or magnetized to the first jaw **102**. The retaining block **128** is positioned between the first shaft **106** and the second shaft **108**, which can occur when the second jaw **104** is in the closed position or in the open position. The retaining block **128** is square shaped, but this shaping can vary (e.g., circular, oval, triangular, pentagonal, octagonal, rectangular). The retaining block **128** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(80) The second jaw **104** hosts a retaining block **130**. For example, the retaining block **130** can be fastened, adhered, mated, interlocked, mounted, or magnetized to the second jaw **104**. The retaining block **130** is positioned between the first shaft **106** and the second shaft **108**, which can occur when the second jaw **104** is in the closed position or in the open position. The retaining block **130** is square shaped, but this shaping can vary (e.g., circular, oval, triangular, pentagonal, octagonal, rectangular). The retaining block **130** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others. Although the retaining block **128** and the retaining block **130** are identical in shape, size, material, and orientation, the retaining block **128** and the retaining block **130** can be non-identical in shape, size, material, and orientation.

(81) As shown in FIGS. **1** and **4**, in the closed position, the retaining block **128** and the retaining block **130** face each other or contact each other. In some configurations, the retaining block **128** and the retaining block **130** are magnetically attracted to each other or magnetically repulsed from each other. As shown in FIGS. **2** and **3**, in the open position, the retaining block **128** and the retaining block **130** face each other, but this can vary with angling of the second jaw **104** relative to the first jaw **102**. For example, when the second jaw **104** is in the open position and angled more than 90 degrees relative to the first jaw **104**, then the retaining block **128** and the retaining block **130** can avoid facing each other, yet still be exposed to each other. However, when the second jaw **104** is in the open position and angled less than 90 degrees relative to the first jaw **104**, then the retaining block **128** and the retaining block **130** can face and be exposed to each other.

(82) The first jaw **102** can host the retaining block **128** between the first shaft **106** and the second shaft **108**. The second jaw **104** can host the retaining block **130** between the first shaft **106** and the second shaft **108**. The retaining block **128** can contact the retaining block **130** when the second jaw **104** is in the closed position.

(83) The first jaw **102** defines a plurality of lateral channels **134** that longitudinally extend along the first jaw **102** parallel to the first shaft **106**. The lateral channels **134** oppose each other on the first jaw **102**, but can avoid opposing each other as well (e.g., offset relative to each other). The lateral channels **134**

are rectilinear, but can be non-rectilinear (e.g., arcuate, sinusoidal). For example, the lateral channels **134** can define a plurality of ledges or shelves on the first jaw **102**, whether rectilinear or non-rectilinear. The lateral channels **134** can be open or be internally U-shaped, C-shaped, V-shaped, W-shaped, or others. The lateral channels **134** can be closed or be internally D-shaped, O-shaped, or others. Note that the lateral channels **134** can avoid longitudinal extension parallel to the first shaft **106** (e.g., merging toward each other, diverging from each other). Further, note that the first jaw **102** can avoid the lateral channels **134**.

(84) The second jaw **104** defines a channel **136** that longitudinally extends lateral to the second jaw **104**, while being non-parallel to the second shaft **108** (e.g., perpendicular, acute, obtuse). The channel **136** is rectilinear, but can be non-rectilinear (e.g., arcuate, sinusoidal). The channel **136** is longitudinally arcuate, but can be longitudinally rectilinear when the second jaw **104** is configured accordingly. The channel **136** can be open or be internally U-shaped, C-shaped, V-shaped, W-shaped, or others. The channel **136** can be closed or be internally D-shaped, O-shaped, or others. Note that the second jaw **104** can avoid the channel **136**.

(85) The first jaw **102** hosts a plurality of lateral walls **138** that longitudinally extend along the first jaw **102** parallel to the first shaft **106**. The lateral walls **138** oppose each other on the first jaw **102**, but can avoid opposing each other as well (e.g., offset relative to each other). The lateral walls **138** are rectilinear, but can be non-rectilinear (e.g., arcuate, sinusoidal). Each of the lateral walls **138** defines the female portion **126** corresponding thereto. As such, the lateral walls **138** allow the second jaw **104** to move relative to the first jaw **102** via the walls **138** functioning as a support structure to the second jaw **104**. Note that the lateral walls **138** can avoid longitudinal extension parallel to the first shaft **106** (e.g., merging toward each other, diverging from each other).

(86) As shown in FIG. 4, the first jaw hosts a line **142** extending within the lateral channels **134** within the channel **136** over the second jaw **104**. The line **142** extends in three directions: a first direction (towards the first jaw **102**, the second jaw **104**, the first set of teeth **140**, the second set of teeth **140**, the first roller **110**, or the second roller **114**), a second direction (laterally traversing the second jaw **104** nonparallel to the first shaft **106** or the second shaft **108**), and a third direction (away from the first jaw **102**, the second jaw **104**, the first set of teeth **140**, the second set of teeth **140**, the first roller **110**, or the second roller **114**). When observed from a lateral side profile view, the line **142** extends in an L-shape when the line **142** extends from one of the lateral channels **134** within the channel **136** over the second jaw **104**. When observed from a top view, the line **142** extends in a U-shape when the line **142** extends from one of the lateral channels **134** within the channel **136** over the second jaw **104**. Note that these shapes of extension can vary. For example, the line **142** can extend in a V-shape or a J-shape or an S-shape or a W-shape from the lateral side profile view. Likewise, the line **142** can extend in a C-shape or a V-shape or an S-shape from the top view.

(87) The line **142** can avoid going over the second jaw **104** or spanning between the lateral channels **134**. For example, the line **142** can stop somewhere (e.g., middle portion, non-middle portion) on the second jaw **104** (e.g., J-shape extension, L-shape extension). For example, the line **142** can be at least two different lines **142**, which can be unconnected to each other in proximity of the second jaw **104** yet extending within the lateral channels **134** and each still being separately coupled to the second jaw **104** (e.g., knot, adhering, fastening, lassoed) in a manner, whether identical or non-identical to each other.

(88) The line **142** can be embodied in various ways (e.g., tether, string, wire, cable, chain, strap, rope, braid, bar, shaft, planar member). The line **142** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(89) The line **142** has a plurality of end portions coupled to a control interface (same one as described above or different one). These end portions can be coupled to the control interface in various ways (e.g., knot, adhering, fastening, lassoed). However, note that this configuration can vary, such as when there are different control interfaces.

(90) The control interface can be a manual interface or an automated interface. For example, the manual interface can include a user input device (e.g., trigger, button, switch, dial, lever). For example, the automated interface can include a mover (e.g., motor, engine, actuator, mechanical linkage, gear mechanism, pulley mechanism, hydraulic mechanism, pneumatic mechanism). For example, the automated interface can be included in a robot (e.g., articulating arm, single or multi-joint end effector). For example, the needle driver **100** can include a distal portion hosting the first jaw **102** and the second jaw **104** and a proximal portion hosting the control interface.

(91) As shown in FIGS. **2-4**, the line **142** extends along the first jaw **102** (e.g., within lateral channels **134**) and over the second jaw **104** (e.g., within channel **136**) when the second jaw **104** is in the closed position or the open position. Therefore, the first set of teeth **140** can extend between the first roller **110** and the line **142**, which can be in the closed position or in the open position. The second set of teeth **120** can extend between the second roller **114** and the line **142**, which can be in the closed position or in the open position. Since the first jaw **102** can host the lateral channel **134**, then the line **142** can extend along the lateral channel **134** before extending over the second jaw **104**. The line **142** can extend along the first jaw **102** and over the second jaw **104** when the second jaw **104** is in the closed position or in the open position. The line **142** can extend along the first jaw **102** toward the first set of teeth **140** and away from the first set of teeth **140**. Since the first jaw **102** can host the lateral channel **134**, then the line **142** can extend along the lateral channel **134** after extending over the second jaw **104**, which can be away from the first jaw **102**, the second jaw **104**, the first set of teeth **140**, the second set of teeth **140**, the first roller **110**, or the second roller **114**. Since the lateral channels **134** can oppose each other, then the line **142** can extend along the lateral channels **134**, where at least two portions of the line **142** can oppose each other. Since the lateral channels **134** can oppose each other, the line **142** can also span between the lateral channels **134**.

(92) The line **142** can move the second jaw **104** between the open position and the closed position. The line **142**, when pulled from the end portions thereof, can cause the second jaw **104** to move from the open position to the closed position. The second jaw **104** can move from the open position to the closed position based on a tension applied to the line **142**, where the tension is in a direction away from the second set of teeth **120**. The second jaw **104** can move from the open position to the closed position based on a tension applied to the line **142**, where the tension is in a direction away from the second roller **114**. The second jaw **104** can move from the open position to the closed position based on a tension applied to the line **142**, where the tension is in a direction away from the second jaw **104**. The second jaw **104** can move from the open position to the closed position based on the line **142** being pulled in a direction away from the second set of teeth **120**. The second jaw **104** can move from the open position to the closed position based on the line **142** being pulled in a direction away from the second roller **114**. The second jaw **104** can move from the open position to the closed position based on the line **142** being pulled in a direction away from the second jaw **104**.

(93) Note that various combinatorics of above are possible. For example, the second jaw **104** can move from the open position to the closed position based on the line **142** being pulled in a direction away from at least two of the second set of teeth **120**, the second roller **114**, or the second jaw **104**. For example, since the first jaw **102** hosts the lateral channels **134** that oppose each other, then the line **142** can extend along the lateral channels **134** and the second jaw **104** can move from the open position to the closed position based on the line **142** being pulled in a plurality of directions away from at least one of the second set of teeth **120**, the second roller **114**, or the second jaw **104**. The directions can be identical or non-identical to each other. The directions can be parallel or non-parallel to each other. The directions can be toward a same area or point.

(94) As shown in FIGS. **1** and **4**, the first roller **110** and the second roller **114** can clamp or grab an object therebetween when the second jaw is in the closed position. The object can be animate or inanimate. For example, the object when animate can include a tissue, an organ, a body part, whether of human or animal, or others. For example, the tissue can be a muscle tissue, a bone tissue, a nerve tissue, an organ tissue, or others. For example, the object when inanimate can include a medical device, a prosthesis, an implantable, a machine, a surgical instrument, or others. The closed position can be a clamping position.

(95) As shown in FIG. 8, the second jaw **104** is in the open position and a needle **144** is positioned on the first groove portion **112**. For example, the needle **144** can be positioned within the first groove portion **112**. The needle **144** is arcuate, but can be shaped non-arcuate (e.g., rectilinear, non-rectilinear, sinusoidal, helical). The needle **144** can be one of a group of needles, where the needles can vary from each other based on at least one of a size, a cross-sectional-shape, a lateral profile, a material, a longitudinal shape, or a lateral diameter.

(96) The needle **144** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(97) As shown in FIG. 9, the second jaw **104** is in the closed position and the needle **144** is positioned between the first groove portion **112** and the second groove portion **116**. For example, the needle **144** can be interposed or sandwiched between the first groove portion **112** and the second groove portion **116**. As such, the needle **144** can be rotationally driven between the first groove portion **112** and the second groove portion **116** based on the first shaft **106** being driven (or the second shaft **108** being driven) when the second jaw **104** is in the closed position.

(98) As shown in FIG. 9, the needle **144** can be driven rotationally about an axis parallel to the first shaft **106** when the needle **144** is positioned between the first roller **106** and the second roller **108**. Likewise, the needle **144** can be driven rotationally about an axis parallel to the second shaft **108** when the needle **144** is positioned between the first roller **106** and the second roller **108**. Similarly, the needle **144** can be driven rotationally about an axis parallel to the first shaft **106** and to the second shaft **108** when the needle **144** is positioned between the first roller **106** and the second roller **108**. However, note that the needle **144** driven rotationally about an axis non-parallel (e.g., perpendicular, obtuse, acute) to the first shaft **106** when the needle **144** is positioned between the first roller **106** and the second roller **108**. Likewise, the needle **144** can be driven rotationally about an axis non-parallel (e.g., perpendicular, obtuse, acute) to the second shaft **108** when the needle **144** is positioned between the first roller **106** and the second roller **108**. Similarly, the needle **144** driven rotationally about an axis non-parallel (e.g., perpendicular, acute, obtuse) to the first shaft **106** and to the second shaft **108** when the needle **144** is positioned between the first roller **106** and the second roller **108**. Also, the needle **144** can be driven rotationally about an axis perpendicular to the first shaft **106** or the second shaft **108** when the needle **144** is positioned between the first roller **106** and the second roller **108**.

(99) The first shaft **106** can rotate between about 0 degrees and about 360 degrees or greater, which can include a plurality of full revolutions (e.g., about 720 degrees, about 1080 degrees, or more). For example, the first shaft **106** or the second shaft **108** can rotate at least about 180 degrees, about 270 degrees, or about 360 degrees, when the needle **144** is positioned between the first roller **106** and the second roller **108**.

(100) FIG. 10 shows a front view of an embodiment of a testing device for a needle driver according to this disclosure. FIG. 11 shows a rear view of an embodiment of a testing device hosting a needle driver according to this disclosure. FIG. 12 shows a front view of an embodiment of a rotary mechanism for a needle driver according to this disclosure. FIG. 13 shows a rear view of an embodiment of a testing device with a rotary mechanism hosting a needle driver according to this disclosure. In particular, a testing device **200** can be used to test the needle driver **100**, such as for manufacturing purposes, quality assurance purposes, investigative purposes, or others.

(101) The testing device **200** includes a frame **202**, a plate **204**, a plurality of levers **206**, a shaft **212**, a bracket **214**, and a knob **216**, any of which include a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(102) The frame **202** defines a channel **208**, which can be open (e.g., U-shape, V-shape, C-shape) or closed (e.g., D-shape, O-shape). The channel **208** hosts a tube **210** (e.g., cantileveredly, snugly). The tube **210** is hollow. The tube **210** can include a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others. The tube **210** contains the needle driver **100**. For example, the needle driver **100** can be inserted into the tube **210** toward the channel **208**.

(103) The frame **202** hosts a plurality of structures **218**. The structures **218** can include a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others. The structures **218** can be used for fastening or mating to a cover for the frame **202**. The structures **218** can be used to engage (e.g., tension) the line **142** when the line **142** extends along the lateral channels **134** towards and away from the first jaw **102**, the second jaw **104**, the first set of teeth **140**, the second set of teeth **140**, the first roller **110**, or the second roller **114**). The channel **208** extends between the structures **218**. The line **122** can extend over the channel **208**. The line **142** can extend within the channel **208**.

(104) The plate **204** hosts a plurality of stops **220**. The stops **220** engage with the levers **206** to limit travel thereof when the levers **206** are pressed in a direction towards the plate **204**. The stops **220** can include a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(105) The shaft **212** is rectilinear but can be non-rectilinear (e.g., sinusoidal, arcuate). The shaft **212** extends through the bracket **214**. The shaft **212** has an end portion to which the knob **216** is mounted (or otherwise coupled). The bracket **214** is U-shaped, but can be shaped differently (e.g., C-shaped, L-shaped, J-shaped). As shown in FIG. **13**, the shaft **212** is coupled to the first shaft **106** such that if the knob **216** is rotated, whether clockwise or counterclockwise, then that movement rotates or translates into rotation of the first shaft **106**, which in turn drives the second shaft **108** based on the first set of teeth **140** driving the second set of teeth **120**. For example, the knob **216** can be coupled to the first shaft **104** and the first shaft **104** is rotated via the knob **216**. When pressed, the levers **206** can control which direction the shaft **212** rotates.

(106) FIG. **14** shows a front view of an embodiment of a needle driver hosting a line according to this disclosure. Unlike FIGS. **1-9**, the line **142** (red) extends along the first jaw **102** and over the second jaw **104** such that the line **142** extends between the first roller **110** and the first set of teeth **140**. For example, the line **142** can extend along the first jaw **102** and over the second jaw **104** as distally as possible, although this feature can be omitted or modified (e.g., not distally as possible). This configuration increases or maximizes at least some leverage (and therefore at least some closing force of the second jaw **104**) the line **142** can exert when moving the second jaw **104** to the closing position or closing the second jaw **104** shut. Further, this configuration allows the line **142** to act as a guard keeping at least some tissue out of reach of the first set of teeth **140** or the second set of teeth **120** behind the line **142**. Resultantly, the line **142** can extend along the first jaw **102** and over the second jaw **104** when the second jaw **104** is in the closed position or the open position. The line **142** can extend between the first set of teeth **140** and the first roller **110**, or the second set of teeth **120** and the second roller **114**. The line **142** can extend along the first jaw **102** and over the second jaw **104** when the second jaw **104** is in the closed position and in the open position, where the line **142** extends between the first set of teeth **140** and the first roller **110** and between the second set of teeth **120** and the second roller **114**.

(107) FIG. **15** shows a front view of an embodiment of a needle driver hosting a mating mechanism according to this disclosure. Unlike FIGS. **1-9**, the retaining block **128** is U-shaped and configured to receive (e.g., loosely, snugly) the retaining block **130** when the second jaw **104** is in the closed position. This feature allows for a more robust and stable coupling of the first jaw **102** and the second

jaw **104** when the second jaw **104** is in the closed position and minimizes jaw wobble, which may affect directional stability of the needle **144** while driving the needle **144**. As such, the retaining block **128** can be hosted via the first jaw **102** and can include an enclosed area. The second retaining block **130** can be hosted via the second jaw **104**. The retaining block **130** can be positioned within the enclosed area when the second jaw **104** is in the closed position. The enclosed area can be defined by the retaining block **128** when the retaining block is U-shaped.

(108) FIG. **16** shows a diagram of an embodiment of a bevel gear assembly for a needle driver according to this disclosure. FIG. **17** shows a rear view of an embodiment of a needle driver hosting a bevel gear assembly according to this disclosure. FIG. **18** shows a front view of an embodiment of a needle driver hosting a bevel gear assembly according to this disclosure. In particular, a needle driver **500** includes a first shaft **502**, a double faced bevel gear **510**, and a second shaft **514**. The first shaft **502** is housed within a first housing **522** (e.g., tube, frame, case). The second shaft **514** is housed within a second housing **524** (e.g., tube, frame, case).

(109) The first shaft **502** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(110) The first shaft **502** a proximal end portion hosting a handle **504** and a distal end portion hosting a first bevel gear **506**, whether assembled therewith (e.g., fastened, mated) or unitary (e.g., monolithic, same material). The first shaft **502** can be rotated clockwise or counterclockwise about an axis **508**. This rotation can be less than about 360 degrees or more than about 360 degrees. The first shaft **502** can be internally solid or hollow (e.g., to pass lines therethrough). The first shaft **502** can have a lateral cross-section that is circular, oval, square, or others.

(111) The second shaft **514** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(112) The second shaft **514** has a proximal end portion hosting a second bevel gear **518**, whether assembled therewith (e.g., fastened, mated) or unitary (e.g., monolithic, same material), and a distal end portion **516** hosting the first jaw **102** and the second jaw **104**. The second shaft **514** can be internally solid or hollow (e.g., to pass lines therethrough). The second shaft **514** can have a lateral cross-section that is circular, oval, square, or others.

(113) The first housing **522** or the second housing **524** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(114) The double faced bevel gear **510** has a first face (e.g., upper) meshing with the first bevel gear **506** and a second face (e.g., lower) meshing with the second bevel gear **518**. The first face opposes the second face. The double faced bevel gear **510** rotates about an axis **512**, which is non-parallel to the axis **508**. For example, the axis **508** is perpendicular to the axis **512**.

(115) The double faced bevel gear **510** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(116) As shown in FIGS. **16-18**, when the first shaft **502** is rotated about the axis **508**, whether clockwise or counterclockwise, the first bevel gear **506** rotationally meshes with the first side of the double faced bevel gear **510**. This rotational meshing enables the double faced bevel gear **510** to rotate about the axis **512** and thereby enable the second side of the double faced bevel gear **510** to rotationally mesh with the second bevel gear **518**. Resultantly, the second shaft **514** can move relative

to the first shaft **502** or the double faced bevel gear **510** about the axis **512**. Therefore, when a user is holding the first housing **522** and rotating the first shaft **502** along the axis **508**, then the double faced bevel gear **510** causes the second shaft **514** to rotate about the axis **512**. Since the second shaft **514** is secured (e.g., fastened, mated, interlocked, adhered) to the second housing **524**, then this configuration causes the second housing **524** to move relative to the first housing **522** about the axis **512**. Resultantly, the first housing **522** can host the first shaft **502** equipped with the first bevel gear **506**. The second housing **524** can host the first jaw **102**, the second jaw **104**, and the second shaft **514** equipped with the second bevel gear **518** distal to the first roller **110** and the second roller **114**. The first bevel gear **506** and the second bevel gear **518** can engage a third bevel gear such that the second housing **524** can move relative to the first housing **522** based on the first shaft **502** being rotated about the axis **508**. The third bevel gear can be the double faced bevel gear **510** having the first side and the second side, where the first side opposes the second side. Consequently, the first side engages the first bevel gear **506** and the second side engages the second bevel gear **518** such that the second housing **524** can move relative to the first housing **522** based on the first shaft **502** being rotated about the axis **508**.

(117) The second housing **524** can move relative to the first housing **522** based on the double faced bevel gear **510** functioning as a pivot point **520**. As such, the first housing **522** and the second housing **524** are structured accordingly so that when the first housing **522** and the second housing **524** are rectilinearly positioned relative to each other, then there is a relatively seamless or flush transition therebetween. For example, as shown in FIG. **17**, the first housing **522** and the second housing **524** can have corresponding adjacent end portions complementing or supplementing each other in shape. However, note that this feature is absent in FIG. **18**.

(118) FIG. **19** shows a diagram of an embodiment of a side profile of a pair of rollers engaging an arcuate needle according to this disclosure. The needle **144** can be of a RB-1 type and is positioned between the first roller **110** and the second roller **114**. As such, this configuration approximates a groove design guidance accept for a reversed rake as flat on needle faces away from the proximal end of needle driver **100**. The needle **144** is shown in parallel forward facing and perpendicular downward facing positions. Perpendicular upward facing is possible. Note that the needle **144** can be of a non RB-1 type. For example, the needle **144** can be any type of cuticular needle, plastic/cosmetic needle, orthopedic needle, endoscopic needle, general surgery needle, microsurgery needle, cardiovascular needle, ophthalmic needle, or any other type, size, shape, taper, leading point, trailing point, material, suture gauge, taper point, trocar point, blunt point, sternum point, short cutting tip, precision point, micropoint, reverse cutting type, straight cutting type, circle heavy type, lancet type, eyed, or others.

(119) FIG. **20** shows a diagram of an embodiment of a side profile of a pair of rollers engaging an arcuate needle according to this disclosure. Unlike FIG. **19**, the needle **144** can be of a SH type. The needle **144** is shown in parallel forward facing and perpendicular downward facing positions. Perpendicular upward facing is possible. Note that the needle **144** can be of a non SH type. For example, the needle **144** can be any type of cuticular needle, plastic/cosmetic needle, orthopedic needle, endoscopic needle, general surgery needle, microsurgery needle, cardiovascular needle, ophthalmic needle, or any other type, size, shape, taper, leading point, trailing point, material, suture gauge, taper point, trocar point, blunt point, sternum point, short cutting tip, precision point, micropoint, reverse cutting type, straight cutting type, circle heavy type, lancet type, eyed or others.

(120) FIG. **21** shows a pair of diagrams of a pair of embodiments of a pair of side profiles of a pair of rollers engaging a pair of arcuate needles of a pair of different sizes according to this disclosure. Regarding the needle **144**, note that at least some free space around the RB-1 needle **144** is due to compromises required to allow the SH needle **144** to fit same grooves. Stability of either needle **144** in these grooves is possible. Note that the needle **144** can be of a non SH type or a non RB-1 type. For example, the needle **144** can be any type of cuticular needle, plastic/cosmetic needle, orthopedic needle, endoscopic needle, general surgery needle, microsurgery needle, cardiovascular needle, ophthalmic needle, or any other type, size, shape, taper, leading point, trailing point, material, suture gauge, taper point, trocar point, blunt point, sternum point, short cutting tip, precision point, micropoint, reverse cutting type, straight cutting type, circle heavy type, lancet type, eyed or others.

(121) FIG. **22** shows a diagram of an embodiment of a side profile of a roller having a plurality of slanted grooves according to this disclosure. The first roller **110** and the second roller **114** are shown with sutures 2-0 and 0 in cross section. When tying sutures, even though at least some “hooked” grooves along bottom of the first roller **110** could theoretically snag sutures, these are still usable. Note that sutures can be non 2-0 and 0 in cross-section. For example, sutures can be 6-0 or any other size defined by United States Pharmacopeia. For example, suture can be any suture from #7 to #10-0, whether collagen (or another material) or synthetic (or natural).

(122) FIG. **23** shows a diagram of an embodiment of a side profile of a roller having a plurality of wave grooves according to this disclosure. The first roller **110** and the second roller **114** are shown with sutures 2-0 and 0 in cross section. Rounded wave grooves could prove to be less likely to snag sutures during tying process. Note that sutures can be non 2-0 and 0 in cross-section. For example, sutures can be 6-0 or any other size defined by United States Pharmacopeia. For example, suture can be any suture from #7 to #10-0, whether collagen (or another material) or synthetic (or natural).

(123) FIG. **24** shows a pair of diagrams of a pair of embodiments of a pair of side profiles of a pair of rollers with a plurality of wave grooves engaging a pair of arcuate needles of a pair of different sizes according to this disclosure. The first roller **110** and the second roller **114** are shown with RB-1 and SH needles **144**. The RB-1 needle **144** runs low in bottom of groove as does the SH needle **144** when parallel to the first jaw **102** or the second jaw **104**. The SH needle **144** runs high in groove when oriented perpendicular to the first jaw **102** or the second jaw **104** due of its larger, oval, cross section. Stability of either needle **144** in this groove is possible. Note that the needle **144** can be of a non SH type or a non RB-1 type. For example, the needle **144** can be any type of cuticular needle, plastic/cosmetic needle, orthopedic needle, endoscopic needle, general surgery needle, microsurgery needle, cardiovascular needle, ophthalmic needle, or any other type, size, shape, taper, leading point, trailing point, material, suture gauge, taper point, trocar point, blunt point, sternum point, short cutting tip, precision point, micropoint, reverse cutting type, straight cutting type, circle heavy type, lancet type, eyed or others.

(124) FIG. **25** shows a pair of diagrams of a pair of embodiments of a pair of side profiles of a pair of rollers with a pair of different groove designs engaging a pair of arcuate needles of a pair of different sizes according to this disclosure. These are two different sets of rollers with groove designs that would allow driving the needle **144** and grasping a suture (no gap between the first roller **110** and the second roller **114**). Note that the rollers **110**, **114** in the second jaw **102** and the first jaw **104** of each set are asymmetrical (although symmetrical is possible), meaning that a shape of the second roller **114** is not identical to the first roller **110**, but rather complimentary in shape to fill at least some space. The slanted groove rollers could have two variations, one with the slanted wall of the groove slanting backwards (as in the left-sided drawing) or slanted forward as shown in FIG. **26**.

(125) FIG. **26** shows a diagram of an embodiment of a pair of rollers with a slanted groove design according to this disclosure. Note that the slanted wall of the groove is slanted forward (rollers are pointing to the right) and the flat wall is on the back part of each groove.

(126) As shown in FIGS. **19-26**, the first roller **110** can host a plurality of slanted grooves. The slanted grooves can be slanted in a direction away from the first set of teeth **140**. The slanted grooves can be slanted in a direction toward the first set of teeth **140**. The first roller **110** can host a plurality of wavy grooves. Likewise, the second roller **114** can host a plurality of slanted grooves. The slanted grooves can be slanted in a direction away from the second set of teeth **120**. The slanted grooves can be slanted in a direction toward the second set of teeth **120**.

(127) FIG. **27** shows a rear view of an embodiment of a needle driver with a plurality of levers according to this disclosure. FIG. **28** shows a rear view of an embodiment of a needle driver with a plurality of levers according to this disclosure. In particular, a needle driver **600** includes a tube **602** having a distal end portion hosting the needle driver **100** inclusive of the first jaw **102** and the second jaw **104**. The tube **602** has a lateral cross-section of a circle, but this shaping can vary (e.g., oval, square, triangle, rectangle, pentagon, octagon). The tube **602** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be

disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(128) The needle driver **600** includes a housing **604** hosting a handle **606**, a first lever **608**, and a second lever **610**, any of which includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(129) The tube **602** longitudinally extends from the housing **604** such that the first jaw **102** and the second jaw **104** are distal to the housing **604**. The first lever **608** (rotational driver) rotationally drives the first shaft **106** of the first jaw **102**, whether clockwise or counterclockwise, as explained above. For example, the first lever **608** can be iteratively or repeatedly pressed or released, as needed, similar to a trigger of a firearm. The second lever **610** (clamp lever) moves the second jaw **104** relative to the first jaw **102** between the open position and the closed position, as explained above. For example, the second lever **610** can be iteratively or repeatedly pressed or released, as needed, similar to a parking handbrake lever in a car. The first lever **608** is movable relative to the handle **606**, whether towards or away therefrom. The second lever **610** is movable relative to the handle **606**, whether towards or away therefrom.

(130) The housing **604** hosts a switch **612**, a shaft **616**, a first bevel gear **618** (right side), a second bevel gear **618** (left side), and a third bevel gear **614** (central), any of which includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(131) The shaft **616** hosts the third bevel gear **614**. Although the shaft **616** has a proximal end portion that hosts the third bevel gear **614**, this configuration can vary where the shaft **616** can host the third bevel gear **614** not at the proximal end portion, but another portion thereof, which can be a medial or a non-medial portion of the shaft **616**.

(132) The first bevel gear **618** and the second bevel gear **618** are rotationally mounted onto the switch **612** such that the first bevel gear **618** and the second bevel gear face each other or oppose each other, while avoiding contact with each other. The switch **612** is U-shaped or C-shaped, but can be shaped differently (e.g., rotary). The switch **612** hosts a projection to enable a user to selectively move the switch **612** between a first lateral position and a second lateral position. For example, the switch **612** can be either at the first position or at the second position, but not both. With the projection, the switch **612** is Y-shaped, but can be shaped differently, such as when the projection is absent. The tube **602** has a longitudinal axis, the switch **612** moves lateral to the longitudinal axis. However, this movement can vary (e.g., longitudinal, parallel, arcuate, circular), which can depend on what type of the switch **612** is used.

(133) In the first lateral position, the switch **612** moves the first bevel gear **618** to enable the first bevel gear **618** to mesh with the third bevel gear **614** and avoid the third bevel gear **614** meshing with the second bevel gear **618**. Note that this configuration can be reversed where instead of the first bevel gear **618** being moved by the switch **612**, the third bevel gear **614** can be moved by the switch **612** to enable the first bevel gear **618** to mesh with the third bevel gear **614** and avoid the third bevel gear **614** meshing with the second bevel gear **618**. For example, the shaft **616** can be moved.

(134) In the second lateral position, the switch **612** moves the second bevel gear **618** to enable the second bevel gear **618** to mesh with the third bevel gear **614** and avoid the third bevel gear **614** meshing with the first bevel gear **618**. Note that this configuration can be reversed where instead of the second bevel gear **618** being moved by the switch **612**, the third bevel gear **614** can be moved by the switch **612** to enable the second bevel gear **618** to mesh with the third bevel gear **614** and avoid the third bevel gear **614** meshing with the first bevel gear **618**. For example, the shaft **616** can be moved.

(135) As shown in FIGS. **27-28**, the first bevel gear **618** or the second bevel gear **618** can selectively engage the third bevel gear **616** based on how the switch **612** is positioned. For example, the third bevel gear **616** enables the first set of teeth **140** of the first jaw **102** to drive the second set of teeth **140** of the second jaw **104**. The first bevel gear **618** rotates the shaft **616** in a first direction (e.g., clockwise, counterclockwise). The second bevel gear **618** rotates the shaft **616** in a second direction (e.g., clockwise, counterclockwise). The first direction is different (e.g., opposite) from the second direction. The switch **612** moves between the first position and the second position, where the first position corresponds to the first direction and the second position corresponds to the second direction. For example, the first direction can be clockwise and the second direction can be counterclockwise.

(136) FIG. **29** shows a rear view of an embodiment of a needle driver with a linkage according to this disclosure. FIG. **30** shows an exploded view of an embodiment of a needle driver with a linkage according to this disclosure. A needle driver **700** contrasts with the needle driver of FIGS. **1-15** in various ways.

(137) The first shaft **106** is unitary (e.g., monolithic, same material) with the first roller **110**. The first shaft **106** has a proximal end portion **714** distal to the first roller **110**. The first shaft **106** hosts a first teathed interface **712** between the first roller **110** and the proximal end portion **714**. The first teathed interface **712** is unitary to the first shaft **106** (e.g., monolithic, same material), but can be coupled to the first shaft **106** in other ways (e.g., mounted, fastened, adhered, mated, interlocked). Although the first shaft **106** steps down from the first roller **110** to the proximal end portion **714**, this configuration can be omitted or modified and the first shaft **106** can avoid stepping down or can step up from the first roller **110** to the proximal end portion **714**.

(138) The first teathed interface **712** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(139) The second shaft **108** is unitary (e.g., monolithic, same material) with the second roller **114**. The second shaft **108** has a proximal end portion **716** distal to the second roller **114**. The second shaft **108** hosts a second teathed interface **718** between the second roller **114** and the proximal end portion **716**. The second teathed interface **718** is unitary to the second shaft **108** (e.g., monolithic, same material), but can be coupled to the second shaft **108** in other ways (e.g., mounted, fastened, adhered, mated, interlocked). Although the second shaft **108** steps down from the second roller **114** to the proximal end portion **716**, this configuration can be omitted or modified and the second shaft **108** can avoid stepping down or can step up from the second roller **110** to the proximal end portion **716**.

(140) The second teathed interface **718** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(141) The second shaft **108** hosts a collar **708**. The collar **708** has a lateral cross-section of a circle, but this can vary (e.g., oval, square, octagon, pentagon, rectangle, triangle). The collar **708** is internally hollow, smooth or rough, and sized such that the proximal end portion **716** of the second shaft **108** can be inserted into the collar **720**, whether freely or snugly. When the proximal end portion **716** of the second shaft **108** is externally threaded and the collar **708** is internally threaded, then the proximal end portion **716** can thread into the collar **708**. As such, the second shaft **108** can host the collar **708** such that the second set of teeth **120** is positioned between the second roller **114** and the collar **708** when the collar **708** receives the proximal end portion **716** of the second shaft **108**. Although the collar **708** is open on both end portions, this can vary where the collar **706** is open on only one end portion that receives the proximal end portion **716** of the second shaft **108**. For example, the collar **708** can be a cap. As such, the collar **708** can extend about the second shaft **108** such that the second set of teeth **120** is positioned between the second roller **114** and the collar.

(142) The collar **708** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(143) The first set of teeth **140** is embodied as a first gear wheel. The first gear wheel defines a first interior channel having a first teathed interior surface configured to engage with the first teathed interface **712**. As such, when the first gear wheel is mounted onto the first shaft **106**, the first teathed interior surface meshes with the first teathed interface **712** and the first gear wheel is correspondingly rotated when the first shaft **106** is rotated.

(144) The second set of teeth **120** is embodied as a second gear wheel. The second gear wheel defines a second interior channel having a second teathed interior surface configured to mesh with the second teathed interface **718**. As such, when the second gear wheel is mounted onto the second shaft **108**, the second teathed surface engages with the second teathed interface **718**. Therefore, when the first gear wheel rotates and thereby rotates the second gear wheel, this movement causes the second teathed interior surface of the second gear wheel to mesh with the second teathed interface **718** and thereby rotate the second shaft **108**. For example, the first set of teeth **140** can be mounted in the first gear wheel and the first shaft **106** can be teathed such that the first shaft **106** engages the gear wheel. The second set of teeth **120** can be mounted in a second gear wheel and the second shaft **108** is teathed such that the second shaft **108** engages the second gear wheel.

(145) The second jaw **104** is pivotably coupled to the first jaw **102** via a pin **720**. The pin **720** is rectilinear, but can be non-rectilinear (e.g., arcuate, sinusoidal). The pin **720** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others. As such, the second jaw **104** can move relative to the first jaw **102** between the open position and the closed position based on pivoting about the pin **720**.

(146) The proximal end portion **714** of the first shaft **106** is inserted into the first jaw **102** and, internal to or external from the first jaw **102**, is inserted into a third shaft **702**. For example, the third shaft **702** can be used to drive the first shaft **106**, which can be when the first jaw **102** hosts the third shaft **702**. The third shaft **702** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(147) The third shaft **702** has a lateral cross-section that is circular, but this can vary (e.g., square, oval, triangular). The third shaft **702** is hollow and has an interior surface, which can be rough or smooth. As such, the proximal end portion **714** of the first shaft **106** can freely or snugly remain within the third shaft **702**. Note that this configuration can be reversed and the third shaft **702** can be inserted into the first shaft **106**. For example, the third shaft **702** can extend into the first shaft **106**, where the third shaft **702** drives the first shaft **106** and the first jaw **102** hosts the third shaft **702**.

(148) The second jaw **104** is coupled to a distal end portion of a link **706**. This coupling can be pivotal, hinged, or others. For example, the second jaw **104** can couple to the distal end portion of the link **706** via a pin such that the second jaw **104** can move between the closed position and the open position based on pivoting about the pin. Although the link **706** is shown a plate, this configuration can vary and the link **706** can be embodied differently (e.g., clip, bracket).

(149) The link **706** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(150) The link **706** has a proximal end portion coupled to a bar **704**. The bar **704** has a cross-section of an I-beam, but this can vary (e.g., T-shape, L-shape, J-shape, U-shape, D-shape, O-shape). The bar **704** is solid, but can be hollow. The bar **704** can be hosted (e.g., supported, suspended, mounted, fastened, interlocked, mated) via the first jaw **102** or the second jaw **104**.

(151) The bar **704** includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(152) The proximal end portion of the link **706** is coupled to the bar **704** in various ways, such as pivotal, hinged, or others. For example, the proximal end portion of the bar **704** can couple to the link **706** via a pin such that the link **706** can move in accordance with the second jaw **104** moving between the closed position and the open position based on the link **706** pivoting about the pin.

(153) The proximal end portion of the bar **704** is coupled to a control interface. The proximal end portion of the bar **704** can be coupled to the control interface in various ways (e.g., linkage, fastening, mating, interlocking, adhering, hooked). As such, the bar **704** functions similarly to the line **122** or the line **144**. For example, when the bar **704** is pulled in a direction away from the second roller **114**, the second shaft **108**, the second set of teeth **120**, or the sleeve **708** via the control interface, then the second jaw **104** can be moved from the closed position to the open position. Likewise, when the bar **704** is pushed in a direction towards the second roller **114**, the second shaft **108**, the second set of teeth **120**, or the sleeve **708** via the control interface, then the second jaw **104** can be moved from the open position to the closed position. Note that the bar **704** can be replaced with a cable or another form of a line, as explained above.

(154) The control interface can be a manual interface or an automated interface. For example, the manual interface can include a user input device (e.g., trigger, button, switch, dial, lever). For example, the automated interface can include a mover (e.g., motor, engine, actuator, mechanical linkage, gear mechanism, pulley mechanism, hydraulic mechanism, pneumatic mechanism). For example, the automated interface can be included in a robot (e.g., articulating arm, single or multi-joint end effector). For example, the needle driver **700** can include a distal portion hosting the first jaw **102** and the second jaw **104** and a proximal portion hosting the control interface. For example, the end effector can host (e.g., support, suspend, fasten, mate, interlock) the first jaw **102** or the second jaw **104**. For example, the first jaw **102** and the second jaw **104** can be housed in a housing (e.g., tube, case, encasement, arm). For example, the housing includes a material suitable for a medical use. The material can be, flexible, elastic, or resilient. The material can be suitable to be disinfected, sterilized, or sanitized, which can be with a hot steam, an autoclave, or others. For example, the material can include plastic, metal, rubber, shape memory, fabric, foam, or others.

(155) As shown in FIGS. **29-30**, the link **706**, which can be a plate, can be coupled to the bar **704** and the second jaw **104**, where the second jaw **104** moves relative to the first jaw **102** between the closed position and the open position based on the bar **704** being moved along the first jaw **102**. The second jaw **104** can move from the closed position to the open position based on the bar **704** moving away from the first set of teeth **140**. The second jaw **104** can move from the open position to the closed position based on the bar **704** moving toward the first set of teeth **140**. The link **706** can cause the second jaw **104** to move between the closed position and the open position based on the bar **704** being moved along the first jaw **102**. The third shaft **702** can receive the first shaft **106**, where the third shaft **702** can drive the first shaft **106** and the bar **704** can move along the third shaft **704**, while the first jaw **102** hosts the third shaft **702**. The third shaft **702** can extend into the first shaft **106**, where the third shaft **702** drives the first shaft **106** and the bar **704** moves along the third shaft **702**, while the first jaw **102** hosts the third shaft **704**.

(156) Therefore, as shown in FIGS. **29-30**, the first roller **110** and the first shaft **106** can be unitary (e.g., monolithic, same material) and the second roller **114** and the second shaft **108** are unitary (e.g., monolithic, same material). The first set of teeth **140** and the second set of teeth **120** can be embodied as spur gears that are mounted to shaft ends and retained with the collar **720**, which can be welded-

on. Therefore, unlike FIGS. 1-15, no retaining plate or screws can be required. The jaw hinge pin **720** can be more robust than slip joint design (e.g., male/female of FIGS. 1-15). The push/pull bar **704** with the link **706** can actuates the second jaw **104** relative to the first jaw **102**. In contrast to FIGS. 1-15, loss of at least some cables can simplify actuation trigger mechanism or can free-up handle internal space, potentially leaving more room for rotation drive mechanism.

(157) FIG. **31** shows a diagram of a side profile of a roller according to this disclosure. In particular, a roller **800** can be configured as any other roller described herein. The roller **800** has a plurality of grooves, which can be microgrooves, that are configured (e.g. sized, dimensioned, structured) to allow grasping of both a needle and its suture thread due to a small size of the grooves or a shallow depth of the grooves. Unlike some rollers described above where the grooves are staggered with crests/ridges of the grooves in one roller fitting into troughs of the grooves in opposing roller, the grooves of the roller **800** revert back to a parallel orientation in which the grooves in one roller align symmetrically with the grooves in opposing roller, but leaving a gap so small therebetween that would not only allow the rollers to grasp a needle therebetween but would also allow the suture thread to be grasped between the rollers even if the suture thread fell in a space between the grooves. Note that although FIG. **8** shows various sizes, dimensions, and angles, the roller **800** is not limited to any of these shown values and, for any shown value, the roller **800** can vary in sizes, dimensions, and angles (e.g. greater, lesser, remain same).

(158) As shown in FIGS. 1-31, the first shaft **106** can extend into the first jaw **102** or can avoid extending into the second jaw **104**. The first shaft **106** can extend out of the first jaw **102** on two opposing sides thereof. The first shaft **106** can cantileveredly extend out of the first jaw **102**. Likewise, the second shaft **108** can extend into the second jaw **104** or can avoid extending into the first jaw **102**. The second shaft **108** can extend out of the second jaw **104** on only one side thereof. The second shaft **108** cantileveredly extends out of the second jaw **104**. The first shaft can **106** avoid contacting the second shaft **108** when the second jaw **104** is in the closed position. The first shaft **106** can avoids contacting the second shaft **108** when the second jaw **104** is in the open position. The first roller **110** and the first set of teeth **140** can be spaced apart from each other on the first shaft **106**. The second roller **114** and the second set of teeth **120** can be spaced apart from each other on the second shaft **108**. For example, the first roller **110** and the first set of teeth **140** can be spaced apart from each other on the first shaft **106** to define a first distance (e.g., less than 1 inch) therebetween and the second roller **114** and the second set of teeth **120** can be spaced apart from each other on the second shaft **108** to define a second distance (e.g., less than 1 inch) therebetween. The first distance can be greater than, equal to, or lesser than the second distance.

(159) A needle driver, as shown in FIGS. 1-31, can be a multifunctional device that is able to function as a needle driver, a grasper, or a dissector. The multifunctional device can drive needle of various sizes, in a multiplicity of angles, which can, in certain cases, be up to about 310 degrees about a long axis of the multifunctional device. The multifunctional device can also be used as a grasper and dissector. The multifunctional device can be used to enable faster recovery time, increased patient convenience, reducing suturing time, reduce patient and surgeon discomfort, smaller blood loss, or others. The multifunctional device can be an intuitive, easy to use, and versatile suturing technology that mimics traditional suturing devices surgeons are commonly trained with. The multifunctional device can integrate tips allowing users to grasp or rotate a curved surgical needle without requiring rotational motion at a user's wrist. The multifunctional device can enable a bi-directional motion or manipulation of the needle for easier, more convenient or safer handling. For example, a needle driver, as shown in FIGS. 1-31, can simplify suturing based on enhancing surgeons' suturing capabilities with minimal device specific training, enables easy transfer of skills from open to minimally invasive surgery, and decreasing time and need for instrument exchange with the needle driver's versatile multifunctional capabilities.

(160) A needle driver, as shown in FIGS. 1-31, can include a counter (e.g., mechanical, mechatronic, electronic, analog, digital, chemical reaction) to count how many times the first shaft **106** or the second shaft **106** have been rotated, how many times the second jaw **104** has moved relative to the first jaw **102** from the open position to the closed position (or vice versa), how many times the needle driver has undergone a sterilization procedure (e.g. hot steam, autoclave), or how many times a lever (e.g.,

rotation, clamp) has been pulled. For example, this can be a physical or chemical process that causes a change, which can be a cumulative change, in a measurable way to assess the number of times the needle driver has been used in accordance with use instructions. The counter can be of odometer-type, digital display type, color-type, scale-type, or others.

(161) A needle driver, as shown in FIGS. 1-31, can be used to perform a method. The method can include causing a device (e.g., needle driver) to be inserted into a first object (e.g., animate, inanimate, human, animal, mannequin, doll). The device includes the first jaw 102 hosting the first shaft 106 and the second jaw 104 hosting the second shaft 108. The first shaft 106 hosts the first roller 110 and the first set of teeth 140. The second shaft 108 hosts the second roller 114 and the second set of teeth 120. The second jaw 104 moves relative to the first jaw 102 between an open position and a closed position. The first set of teeth 140 meshes with the second set of teeth 120 when the second jaw 104 is in the closed position such that (a) the first set of teeth 140 can drive the second set of teeth 120 and (b) the first roller 110 and the second roller 114 can drive a needle therebetween when the first set of teeth 140 drives the second set of teeth 120. The method can include acting with the device. An example of such acting can include causing the first roller 110 and the second roller 114 to grasp a second object (e.g., animate, inanimate, tissue, organ, body part, implantable, wearable, surgical instrument) therebetween within the first object when the second jaw 104 is in the closed position. An example of such acting can include causing the first roller 110 and the second roller 114 to manipulate the second object within the first object when the second jaw 104 is in the closed position. An example of such acting can include causing the first roller 110 and the second roller 114 to dissect the second object within the first object when the second jaw 104 is in the closed position. An example of such acting can include causing the first roller 110 and the second roller 114 to isolate the second object within the first object when the second jaw 104 is in the closed position. An example of such acting can include causing the first roller 110 and the second roller 114 to separate the second object within the first object when the second jaw 104 is in the closed position. Note that these are examples and the first roller 110 and the second roller 114 can be used to grasp an object (e.g., animate, inanimate, tissue, instrument, implantable) when the first roller 110 and the second roller 114 are in the closed position or in the open position or act (e.g., manipulate, dissect, isolate, separate, intervene, mount, drop, move, drag) with the object when the first roller 110 and the second roller 114 are in the closed position or in the open position. For example, the object when animate can include a tissue, an organ, a body part, whether of human or animal, or others. For example, the tissue can be a muscle tissue, a bone tissue, a nerve tissue, an organ tissue, or others. For example, the object when inanimate can include a medical device, a prosthesis, an implantable, a machine, a surgical instrument, or others. The closed position can be a clamping position.

(162) A needle driver, as shown in FIGS. 1-31, which can include a needle or a thread, can be packaged, whether alone or with any other devices, whether disclosed herein or not, in a kit. For example, the kit can include a package (e.g., plastic bag, sealed bag, storage container, cardboard box, transport package, consumer package, bubble wrap, foam blanket, garment blanket, can, shrink-wrap, molded pulp, blister pack, box). For example, the package can include a cuboid box, a shipping box, an intermodal container, or others. The package can include one or more devices, as disclosed herein or not disclosed herein. The kit can include a set of instructions on a memory (e.g., mechanical memory, electronic memory, paper page, booklet, laminated card, flash drive, computer disc, website link). The set of instructions can instruct (e.g., text, graphics) a user on how to use a needle driver, as disclosed herein.

(163) Features described with respect to certain embodiments may be combined in or with various some embodiments in any permutational or combinatory manner. Different aspects or elements of example embodiments, as disclosed herein, may be combined in a similar manner.

(164) Although the terms first, second, can be used herein to describe various elements, components, regions, layers, or sections, these elements, components, regions, layers, or sections should not necessarily be limited by such terms. These terms are used to distinguish one element, component, region, layer or section from another element, component, region, layer or section. Thus, a first element, component, region, layer, or section discussed below could be termed a second element, component, region, layer, or section without departing from various teachings of this disclosure.

(165) Features described with respect to certain example embodiments can be combined and sub-combined in or with various other example embodiments. Also, different aspects or elements of example embodiments, as disclosed herein, can be combined and sub-combined in a similar manner as well. Further, some example embodiments, whether individually or collectively, can be components of a larger system, wherein other procedures can take precedence over or otherwise modify their application. Additionally, a number of steps can be required before, after, or concurrently with example embodiments, as disclosed herein. Note that any or all methods or processes, at least as disclosed herein, can be at least partially performed via at least one entity in any manner.

(166) Example embodiments of this disclosure are described herein with reference to illustrations of idealized embodiments (and intermediate structures) of this disclosure. As such, variations from various illustrated shapes as a result, for example, of manufacturing techniques or tolerances, are to be expected. Thus, various example embodiments of this disclosure should not be construed as necessarily limited to various particular shapes of regions illustrated herein, but are to include deviations in shapes that result, for example, from manufacturing.

(167) Any or all elements, as disclosed herein, can be formed from a same, structurally continuous piece, such as being unitary, or be separately manufactured or connected, such as being an assembly or modules. Any or all elements, as disclosed herein, can be manufactured via any manufacturing processes, whether additive manufacturing, subtractive manufacturing, or other any other types of manufacturing. For example, some manufacturing processes include three dimensional (3D) printing, laser cutting, computer numerical control routing, milling, pressing, stamping, vacuum forming, hydroforming, injection molding, lithography, and so forth.

(168) Various corresponding structures, materials, acts, and equivalents of all means or step plus function elements in various claims below are intended to include any structure, material, or act for performing the function in combination with other claimed elements as specifically claimed. Various embodiments were chosen and described in order to best explain various principles of this disclosure and various practical applications thereof, and to enable others of ordinary skill in a pertinent art to understand this disclosure for various embodiments with various modifications as are suited to a particular use contemplated.

(169) This detailed description has been presented for various purposes of illustration and description, but is not intended to be fully exhaustive or limited to this disclosure in various forms disclosed. Many modifications and variations in techniques and structures will be apparent to those of ordinary skill in an art without departing from a scope and spirit of this disclosure as set forth in various claims that follow. Accordingly, such modifications and variations are contemplated as being a part of this disclosure. Scope of this disclosure is defined by various claims, which include known equivalents and unforeseeable equivalents at a time of filing of this disclosure.

Claims

1. A needle driver comprising: a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; and a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth, wherein the second jaw is biased open or biased closed relative to the first jaw.
2. The needle driver of claim 1, wherein the first roller includes a first groove portion, wherein the second roller includes a second groove portion, wherein the first groove portion faces the second groove portion when the second jaw is in the closed position, wherein the needle is driven between the first groove portion and the second groove portion when the second jaw is in the closed position.
3. The needle driver of claim 1, wherein the first jaw houses the first set of teeth.

4. The needle driver of claim 1, wherein the second jaw houses the second set of teeth.
5. The needle driver of claim 1, further comprising a line coupled to the second jaw, wherein the line pulls the second jaw from the closed position to the open position.
6. The needle driver of claim 5, comprising the line coupled to the second jaw, wherein the line pulls the second jaw from the closed position to the open position, wherein the first set of teeth extends between the first roller and the line.
7. The needle driver of claim 5, comprising the line coupled to the second jaw, wherein the line pulls the second jaw from the closed position to the open position, wherein the second set of teeth extends between the second roller and the line.
8. The needle driver of claim 5, comprising the line coupled to the second jaw, wherein the line pulls the second jaw from the closed position to the open position, wherein the line extends along the first jaw and over the second jaw when the second jaw is in at least one of the closed position or the open position.
9. The needle driver of claim 5, comprising the line coupled to the second jaw, wherein the line pulls the second jaw from the closed position to the open position, wherein the line extends along the first jaw toward the first set of teeth and away from the second set of teeth.
10. The needle driver of claim 5, comprising the line coupled to the second jaw, wherein the line pulls the second jaw from the closed position to the open position, wherein the first jaw has a lateral channel, wherein the line extends along the lateral channel after extending over the second jaw.
11. The needle driver of claim 5, comprising the line coupled to the second jaw, wherein the line pulls the second jaw from the closed position to the open position, wherein the first jaw has a plurality of lateral channels that oppose each other, wherein the line extends along or spans between the plurality of lateral channels.
12. The needle driver of claim 5, comprising the line coupled to the second jaw, wherein the line pulls the second jaw from the closed position to the open position, wherein the second jaw moves from the open position to the closed position based on the line being pulled in a direction away from at least one of the second set of teeth, the second roller, or the second jaw.
13. The needle driver of claim 5, comprising the line coupled to the second jaw, wherein the line pulls the second jaw from the closed position to the open position, and wherein the second jaw moves from the open position to the closed position based on the line being pulled in a direction away from at least two of the second set of teeth, the second roller, or the second jaw.
14. The needle driver of claim 5, comprising the line coupled to the second jaw, wherein the line pulls the second jaw from the closed position to the open position, wherein the first jaw has a plurality of lateral channels that oppose each other, wherein the line extends along the lateral channels, and wherein the second jaw moves from the open position to the closed position based on the line being pulled in a plurality of directions away from at least one of the second set of teeth, the second roller, or the second jaw.
15. The needle driver of claim 5, wherein at least one of the first shaft cantileveredly extends out of the first jaw, or the second shaft cantileveredly extends out of the second jaw.
16. The needle driver of claim 5, wherein the second shaft extends out of the second jaw on only one side thereof.
17. The needle driver of claim 1, wherein the second shaft is rotationally constrained or unconstrained in the open position.

18. The needle driver of claim 17, wherein the first shaft is parallel to the second shaft external to the first jaw.
19. The needle driver of claim 17, wherein a line extends between at least one of the first set of teeth and the first roller, or the second set of teeth and the second roller.
20. The needle driver of claim 17, wherein a line extends along the first jaw and over the second jaw when the second jaw is in the closed position and in the open position, and wherein the line extends between the first set of teeth and the first roller and between the second set of teeth and the second roller.
21. The needle driver of claim 1, wherein the first roller and the second roller can clamp a tissue therebetween when the second jaw is in the closed position.
22. The needle driver of claim 1, wherein the closed position is a clamping position.
23. The needle driver of claim 1, wherein the first shaft supports a spur gear including the first set of teeth.
24. The needle driver of claim 23, wherein the second shaft includes an end portion on which the second roller is mounted.
25. The needle driver of claim 1, wherein the first set of teeth is exposed to the second jaw when the second jaw is in the open position.
26. The needle driver of claim 1, wherein the second set of teeth is exposed to the first jaw when the second jaw is in the open position.
27. The needle driver of claim 1, wherein the needle is rectilinear, non-rectilinear, or arcuate.
28. The needle driver of claim 1, wherein the second jaw is in the closed position.
29. The needle driver of claim 1, wherein the closed position is a terminal position.
30. The needle driver of claim 1, wherein the open position is a terminal position.
31. The needle driver of claim 1, wherein the first roller and the first set of teeth are spaced apart from each other on the first shaft.
32. The needle driver of claim 1, wherein the second roller and the second set of teeth are spaced apart from each other on the second shaft.
33. A needle driver comprising: a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; and a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth, wherein at least one of the first jaw or the second jaw supports a retaining block between the first shaft and the second shaft.
34. The needle driver of claim 33, wherein the first retaining block is U-shaped thereby defining an enclosed area.
35. The needle driver of claim 33, wherein the first jaw supports a first retaining block between the first shaft and the second shaft, wherein the second jaw supports a second retaining block between the first shaft and the second shaft, and wherein the first retaining block at least one of faces the second retaining block or contacts the second retaining block when the second jaw is in the closed position.

36. The needle driver of claim 1, wherein at least one of the first jaw has a longitudinal axis and wherein the first shaft rotates about the longitudinal axis, the second jaw has a longitudinal axis, wherein the second shaft rotates about the longitudinal axis, or the first jaw has a first longitudinal axis, wherein the first shaft rotates about the first longitudinal axis, and the second jaw has a second longitudinal axis, wherein the second shaft rotates about the second longitudinal axis.
37. The needle driver of claim 36, wherein the first longitudinal axis is parallel to the second longitudinal axis.
38. The needle driver of claim 1, wherein the first jaw houses the first set of teeth and wherein the second jaw houses the second set of teeth.
39. The needle driver of claim 1, wherein the second jaw is at least one of hingedly coupled or pivotally coupled to the first jaw such that the second jaw moves relative to the first jaw between the open position and the closed position.
40. The needle driver of claim 1, wherein the second jaw is separate and distinct from the first jaw.
41. The needle driver of claim 1, wherein the second jaw has a range of motion spanning between the closed position and the open position.
42. The needle driver of claim 1, further comprising a line coupled to the second jaw, wherein the line pushes the second jaw from the open position to the closed position.
43. The needle driver of claim 1, further comprising an end effector supporting at least one of the first jaw, the second jaw, or the first jaw and the second jaw.
44. The needle driver of claim 1, further comprising a tube supporting the first jaw and the second jaw; and a housing supporting a handle, a first lever, and a second lever, wherein the tube extends from the housing such that the first jaw and the second jaw are distal to the housing, wherein the first lever drives the first jaw, wherein the second lever moves the second jaw relative to the first jaw between the open position and the closed position, wherein the first lever is movable relative to the handle, and wherein the second lever is movable relative to the handle.
45. The needle driver of claim 1, further comprising a third shaft at least one of receiving the first shaft or extending into the first shaft, wherein the third shaft drives the first shaft, and wherein the first jaw supports the third shaft.
46. The needle driver of claim 1, further comprising a counter that counts how many times at least one of the first shaft has been rotated, the second shaft has been rotated, or the second jaw has moved relative to the first jaw.
47. The needle driver of claim 1, further comprising a lever coupled to at least one of the first jaw or the second jaw; and a counter that counts how many times the lever has been pulled.
48. The needle driver of claim 1, further comprising a counter that counts how many times the first jaw and the second jaw have concurrently undergone a sterilization procedure.
49. The needle driver of claim 1, wherein the first roller is diametrically larger than the first shaft, and wherein the second roller is diametrically larger than the second shaft.
50. The needle driver of claim 1, wherein at least one of the first roller is external to the first jaw, the second roller is external to the second jaw, or the first roller is external to the first jaw and the second roller is external to the second jaw.
51. The needle driver of claim 1, wherein at least one of the first roller is mounted on the first shaft or the second roller is mounted on the second shaft.

52. The needle driver of claim 1, wherein at least one of the first roller or the second roller supports a plurality of wavy grooves.
53. The needle driver of claim 1, wherein the second shaft supports a spur gear including the second set of teeth.
54. The needle driver of claim 1, wherein the second shaft extends into the second jaw.
55. The needle driver of claim 1, wherein the first shaft extends parallel to the second shaft between the first jaw and the second jaw.
56. The needle driver of claim 1, wherein the first shaft extends parallel to the second shaft external to the first jaw and to the second jaw.
57. The needle driver of claim 1, wherein the first shaft is positioned between the first jaw and the second jaw and the second shaft is positioned between the first jaw and the second jaw.
58. The needle driver of claim 1, wherein the first shaft supports a first spur gear including the first set of teeth, wherein the second shaft supports a second spur gear including the second set of teeth, and wherein the first spur gear engages the second spur gear such that the first spur gear drives the second spur gear.
59. The needle driver of claim 1, wherein the first shaft includes an end portion on which the first roller is mounted.
60. The needle driver of claim 1, wherein at least one of the first shaft cantileveredly extends from the first jaw, the second shaft cantileveredly extends from the second jaw, or the first shaft cantileveredly extends from the first jaw and the second shaft cantileveredly extends from the second jaw.
61. The needle driver of claim 1, wherein the first shaft is rotationally driven manually.
62. The needle driver of claim 1, wherein at least one of the first shaft or the second shaft rotates at least about **180** degrees when the needle is between the first roller and the second roller.
63. The needle driver of claim 1, wherein at least one of the first shaft or the second shaft rotates at least about 270 degrees when the needle is between the first roller and the second roller.
64. The needle driver of claim 1, wherein at least one of the first shaft or the second shaft rotates at least about 360 degrees when the needle is between the first roller and the second roller.
65. The needle driver of claim 1, wherein the first shaft is not parallel to the second shaft in the open position.
66. The needle driver of claim 1, wherein the first shaft extends into the first jaw and avoids contacting the second shaft when the second jaw is in the closed position.
67. The needle driver of claim 1, wherein the first shaft avoids contacting the second shaft when the second jaw is in the open position.
68. The needle driver of claim 1, wherein at least one of the first shaft or the second shaft is rectilinear.
69. The needle driver of claim 1, wherein at least one of the first set of teeth is exposed to the second set of teeth or the second set of teeth is exposed to the first set of teeth when the second jaw is in the open position.
70. The needle driver of claim 1, wherein the first set of teeth is positioned between the first jaw and the second jaw and the second set of teeth is positioned between the first jaw and the second jaw.

71. The needle driver of claim 1, wherein the first set of teeth avoids meshing with the second set of teeth when the second jaw is in the open position.

72. The needle driver of claim 1, wherein the needle is non- rectilinear.

73. The needle driver of claim 1, wherein the needle is arcuate.

74. The needle driver of claim 1, wherein the needle is driven rotationally about an axis parallel to at least one of the first shaft, the second shaft, or the first shaft and the second shaft when the needle is between the first roller and the second roller.

75. The needle driver of claim 1, wherein the needle is driven rotationally about an axis non-parallel to at least one of the first shaft, the second shaft, or the first shaft and the second shaft when the needle is between the first roller and the second roller.

76. The needle driver of claim 1, wherein the needle is driven rotationally about an axis perpendicular to at least one of the first shaft or the second shaft when the needle is between the first roller and the second roller.

77. The needle driver of claim 1, wherein the needle is a plurality of needles, and wherein the needles vary from each other based on at least one of a size, a cross-sectional-shape, a lateral profile, a material, a longitudinal shape, or a lateral diameter.

78. The needle driver of claim 1, wherein the second jaw is in the open position.

79. The needle driver of claim 1, wherein at least one of the closed position or the open position is not a terminal position.

80. The needle driver of claim 1, wherein the first roller and the first set of teeth are spaced apart from each other on the first shaft to define a first distance therebetween, wherein the second roller and the second set of teeth are spaced apart from each other on the second shaft to define a second distance therebetween, and wherein the first distance is equal to the second distance.

81. The needle driver of claim 1, wherein the first roller and the first set of teeth are spaced apart from each other on the first shaft to define a first distance therebetween, wherein the second roller and the second set of teeth are spaced apart from each other on the second shaft to define a second distance therebetween, wherein the first distance is not equal to the second distance.

82. A needle driver comprising: a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; and a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth, wherein at least one of the first roller is diametrically larger than the first shaft or the second roller is diametrically larger than the second shaft.

83. The needle driver of claim 82, wherein at least one of the first shaft avoids extending into the second jaw or the second shaft avoids extending into the first jaw.

84. The needle driver of claim 82, wherein the first shaft extends out of the first jaw on two opposing sides thereof.

85. A needle driver comprising: a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the

second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth, a line coupled to the second jaw, wherein the line pulls the second jaw from the closed position to the open position, wherein the first jaw has a lateral channel, wherein the line extends along the lateral channel before extending over the second jaw.

86. A needle driver comprising: a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth; and a counter that counts how many times the first jaw and the second jaw have concurrently undergone a sterilization procedure.

87. A needle driver comprising: a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; and a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth, wherein the first jaw includes a female portion, wherein the first set of teeth is positioned between the first roller and the female portion, wherein the second jaw includes a male portion, wherein the second set of teeth is positioned between the second roller and the male portion, and wherein the female portion and the male portion pivotably mate such that the second jaw moves relative to the first jaw between the open position and the closed position.

88. A needle driver comprising: a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; and a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth, wherein the first jaw is self-aligning and the second jaw is self-aligning.

89. A needle driver comprising, a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; and a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth, wherein the second jaw is at least one of hingedly coupled, pivotally coupled, or pivotally mated to the first jaw without using a pin about which the second jaw moves relative to the first jaw between the open position and the closed position.

90. A needle driver comprising: a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth; and a line extending along the

first jaw and over the second jaw when the second jaw is in at least one of the closed position or the open position.

91. The needle driver of claim 90, wherein the line extends between at least one of the first set of teeth and the first roller, or the second set of teeth and the second roller.

92. A needle driver comprising: a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth; and a housing supporting the first jaw and the second jaw.

93. A needle driver comprising: a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth; and a knob coupled to the first shaft, wherein the first shaft is rotated via the knob.

94. A needle driver comprising: a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth: a first retaining block supported via the first jaw, wherein the first retaining block includes an enclosed area; and a second retaining block supported via the second jaw, wherein the second retaining block is positioned within the enclosed area when the second jaw is in the closed position.

95. A needle driver comprising: a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth; and a collar extending about the second shaft such that the second set of teeth is positioned between the second roller and the collar.

96. A needle driver comprising: a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth: a bar supported via the first jaw; and a plate coupled to the bar and the second jaw, wherein the second jaw moves between the closed position and the open position based on the bar being moved along the first jaw.

97. The needle driver of claim 96, wherein the second jaw moves from the closed position to the open position based on the bar moving away from the first set of teeth.

98. The needle driver of claim 96, further comprising: a third shaft receiving the first shaft, wherein the third shaft drives the first shaft, wherein the bar moves along the third shaft, wherein the first jaw supports the third shaft.

99. The needle driver of claim 96, wherein the second jaw moves from the open position to the closed position based on the bar moving toward the first set of teeth.

100. The needle driver of claim 96, wherein the plate causes the second jaw to move between the closed position and the open position based on the bar being moved along the first jaw.

101. The needle driver of claim 96, further comprising: a third shaft extending into the first shaft, wherein the third shaft drives the first shaft, wherein the bar moves along the third shaft, and wherein the first jaw supports the third shaft.

102. A needle driver comprising: a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; and a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth; and a line coupled to the second jaw, wherein the line pulls the second jaw from the closed position to the open position, wherein the second jaw moves from the open position to the closed position based on a tension applied to the line, wherein the tension is in a direction away from at least one of the second set of teeth or the second roller.

103. A needle driver comprising, a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; and a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth, wherein the first shaft is longitudinally longer than the second shaft.

104. A needle driver comprising: a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; and a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth, wherein the first shaft is rotationally driven automatically.

105. A needle driver comprising a first jaw supporting a first shaft, wherein the first shaft supports a first roller and a first set of teeth; and a second jaw supporting a second shaft, wherein the second shaft supports a second roller and a second set of teeth, wherein the second jaw moves relative to the first jaw between an open position and a closed position, wherein the first set of teeth meshes with the second set of teeth when the second jaw is in the closed position such that (a) the first set of teeth can drive the second set of teeth and (b) the first roller and the second roller can drive a needle therebetween when the first set of teeth drives the second set of teeth, wherein at least one of the first set of teeth is mounted in a gear wheel and the first shaft is teathed such that the first shaft engages the gear wheel, or the second set of teeth is mounted in a gear wheel and the second shaft is teathed such that the second shaft engages the gear wheel.

106. The needle driver of claim 105, wherein the first set of teeth is mounted in a first gear wheel, wherein the first shaft is teathed such that the first shaft engages the first gear wheel, wherein the

second set of teeth is mounted in a second gear wheel, and wherein the second shaft is teethed such that the second shaft engages the second gear wheel.