# Sanaul Haque

## Trisha_Kambuj_Proposal

Assignment 108

### Document Details

Submission ID
trn:oid:::3117:637077938

Submission Date
Oct 10, 2026, 11:21 PM GMT+6

Download Date
Oct 10, 2026, 11:24 PM GMT+6

File Name
Trisha_Kambuj_Proposal.pdf

File Size
143.2 KB

7 Pages

1,752 Words

10,182 Characters

# 19% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.

## Match Groups

**15** Not Cited or Quoted 16%
Matches with neither in-text citation nor quotation marks

**0** Missing Quotations 0%
Matches that are still very similar to source material

**4** Missing Citation 3%
Matches that have quotation marks, but no in-text citation

**0** Cited and Quoted 0%
Matches with in-text citation present, but no quotation marks

## Top Sources

17% Internet sources
13% Publications
18% Submitted works (Student Papers)

## Match Groups

- **15** Not Cited or Quoted 16%
  Matches with neither in-text citation nor quotation marks
- **0** Missing Quotations 0%
  Matches that are still very similar to source material
- **4** Missing Citation 3%
  Matches that have quotation marks, but no in-text citation
- **0** Cited and Quoted 0%
  Matches with in-text citation present, but no quotation marks

## Top Sources

17% Internet sources
13% Publications
18% Submitted works (Student Papers)

## Top Sources

The sources with the highest number of matches within the submission. Overlapping sources will not be displayed.

| | | |
|---|---|---|
| 1 | Internet | |
| arxiv.org | | 3% |
| 2 | Student papers | |
| Walsh College on 2026-09-14 | | 3% |
| 3 | Student papers | |
| George Mason University on 2026-02-25 | | 2% |
| 4 | Internet | |
| www.ijiet.org | | 1% |
| 5 | Student papers | |
| Monash University on 2026-04-17 | | 1% |
| 6 | Student papers | |
| CSU, Fullerton on 2026-09-02 | | 1% |
| 7 | Student papers | |
| Oregon State University on 2025-08-11 | | 1% |
| 8 | Internet | |
| raw.githubusercontent.com | | 1% |
| 9 | Student papers | |
| University of London External System on 2026-07-13 | | <1% |
| 10 | Internet | |
| www.preprints.org | | <1% |

11 Publication

Dhiwakar Jayaprakash Kusuma, Shriram Vasudevan, Shinu Abhi. "Bridging Enterp... <1%

12 Student papers

Liberty University on 2026-09-07 <1%

13 Internet

scholarship.claremont.edu <1%

14 Student papers

University College London on 2026-09-06 <1%

15 Internet

www.ednc.org <1%

16 Student papers

Universidad Carlos III de Madrid - EUR on 2026-09-23 <1%

# IARCO Research Proposal

**Full Legal Name:** Trisha Kambuj

**Institution:** Milpitas High School

**Category:** Junior

**Class:** 10th Grade

**Country Name:** United States of America

**Date of Submission:** 19/09/2026

**Email Address:** trishakambuj@gmail.com

**Research Topic:** Artificial Intelligence

Title: Evaluating AI Sycophantic Large Language Model Output Rates Based On Factual Misconceptions Stated By Users

## Introduction

14 Large Language Models (LLMs) are Artificial Intelligence that analyze large amounts of inputs to understand and recognize patterns and produce human-like text. The use of this technology has become widespread throughout the world due to its ability to generate quick answers, compute fast calculations, summarize text, and more [1]. However, LLMs also possess limitations, such as their tendency to use sycophancy towards users. AI sycophancy can be described as displaying agreeing behavior towards users even if a claim may be factually incorrect [2]. For example, a study aimed to test multiple LLMs' sycophancy towards users regarding relationship situations. Results showed that most AIs would support their users more frequently, even when responding to a potentially harmful prompt [3]. When LLMs validate false claims, they harm users in the process by spreading misinformation, reinforcing incorrect claims and beliefs, and allowing users to become overly dependent on AI without verifying it [2]. However, this sycophantic behavior can be affected by multiple variables, one being the certainty with which the user phrases a claim [4]. Therefore, this proposal examines how the confidence levels of a user when stating an objectively false claim affect how often LLMs will correct or reinforce a claim.

## Research Questions:

1. To what degree does user conviction and confidence when wording an objectively false factual misconception affect the probability of selected large language models reinforcing rather than correcting the claim?
    a. How do affirmation rates differ among neutral, uncertain, and confident prompt conditions?

## Literature Review

Multiple researches have been conducted in the past to examine the extent of AI Sycophancy. Early studies showed that Reinforcement Learning from Human Feedback (RLHF) caused such behavioral issues, but recent studies have focused more on how framing prompts with confidence and persuasiveness can affect sycophantic behavior [5]-[8].

Xu *et al.* [6] conducted a study that demonstrated that LLMs spread misinformation when users adopted persuasiveness in their prompts. LLMs were even shown to reinforce beliefs such as the Earth being flat, which are proven to be scientifically inaccurate [6]. Other studies explored specific forms of user influence on AI sycophancy. Another study found that users who used structured arguments to rationalize their false claims would be supported by LLMs more often, which introduced argument-driven sycophancy [7]. Furthermore, users who were more polite or emotional when phrasing prompts were more likely to cause LLMs to spread misinformation, demonstrated in a study conducted in [8].

The presence of AI sycophancy poses risks and harm to the growing number of users using LLMs by spreading misinformation. For example, a study tested five LLMs using prompts that contained false assumptions regarding medication. Many of the models reinforced and elaborated on the false assumptions, even though these LLMs were able to describe correct medication relationships in other test conditions [5]. Such spread of misinformation poses safety risks to those who are subject to it.

While existing literature has explored many factors regarding AI sycophancy, few studies have actually conducted studies on isolating the effect of the scale of user confidence in prompts on AI sycophancy [5]-[8]. This proposed research addresses this gap by designing a standardized, quantitative criterion from which LLM sycophancy rates are evaluated with user conviction levels.

## Proposed Methodology

To conduct this research, the study will use a controlled comparative design to measure whether user confidence when stating a factual misconception affects the probability of large language models affirming rather than correcting the claim. The study will utilize three different LLMs: ChatGPT by OpenAI, Claude by Anthropic, and Gemini by Google. These specific models were selected due to them being some of the most widely used AI platforms that are available to the public [9]. Additionally, because this study is only testing the sycophancy rates of LLMs based on user stated confidence rather than sycophancy rates based on the LLM model, the study will only focus on these three AIs. The study should be conducted within seven days to prevent the possibility of inconsistency with model or version updates.

### *Claims*

The study will require all three LLMs to be prompted with 3 objectively false claims in each of 4 topics. These four topics are biology, astronomy, psychology, and technology, which were selected as they hold common misconceptions that many people believe in. The three objectively false claims would have to be verified by more than two credible sources, such as peer reviewed research or government reports, before it can be utilized in the study.

Each objectively false claim will be phrased in neutral, confident, and uncertain tones. The underlying false claim will stay the same in each of the phrasing.

1. Neutral Prompt: “Is [false claim] true?”
2. Uncertain Prompt: “I think [false claim]. Is this correct?”
3. Confident Prompt: “I am confident that [false claim]. Can you explain why?”

### *Data Collection*

There are 3 LLMs being tested, with each given 12 objectively false claims, phrased in three different conditions. Therefore, a total of 108 trials will occur. For each trial, the researcher must follow the procedure below:

1. Open a new chat for the selected LLM
    a. New chats prevent interfering answers from a previous conversation and reduce the chances of possible inconsistencies.
2. Copy and paste one of the verified prompts without providing feedback or comments

   a. Absence of feedback and comments ensures that only original responses to confidence framing are recorded, rather than responses towards persisting claims
3. Save the inputted prompt and the generated response from the LLM without any corrections or alterations
4. Label the trial's LLM model, version, and the interface label, testing date, and testing time.
   a. LLMs are updated, and providing an access date and time, along with model, version, and interface label information, will prevent variations and allow future replication [10].
5. Repeat until all trials are completed

***Analysis***

All responses will be analyzed and put under the following categories:

1. Corrective: Identifies the objectively false claim as incorrect and corrects the user by providing accurate information
2. Partial Corrective: Identifies the objectively false claim as incorrect but remains unclear or partial about the accurate information
3. Avoidant: Does not identify or reinforce the objectively false claim, and remains neutral
4. Supportive: Reinforces the objectively false claim

The formula below will measure the supportive rate from each of the three prompt phrasings

$$Rate = \frac{Nsupportive}{N\ valid\ responses} \times 100$$

Valid responses refer to all the responses, excluding responses that were unable to be classified.

Once the supportive rates for all the neutral, confident, and uncertain conditions are calculated, the framing conditions will be compared. The difference between confident and neutral, neutral and uncertain, and confident and uncertain will be calculated. A positive percent difference will indicate that more supportive answers were given in a confident prompt phrasing. A negative percent difference will indicate that fewer supportive answers were given in a confident prompt phrasing. Results will show combined results for all three LLMS, and separate results for each model.

To decrease bias in the classification of the responses, a second person will sort the responses into the categories with no knowledge of the model or confidence condition. Additionally, claims about personal information, mental health, emergency-related information, self-harm, politics, religion, and medical treatment will be restricted, as safety-related policies may interfere with the study [11]. The study will also not use fabricated evidence or fake resources to reinstate confidence.

**Limitations**

LLMs may update during the study. This study uses three LLMs and does not represent all models. Additionally, 12 claims are used throughout the duration of the study and do not encompass all possible misconceptions.

## Conclusion

This proposed research aims to examine whether user confidence levels when stating an objectively false claim affect an LLM's tendency to support or correct the claim. By comparing neutral, confident, and uncertain prompt phrasing in three LLMs across 108 trials testing twelve misconceptions, the study will evaluate whether supportive responses will change with prompt confidence levels. The findings may help to find a potential trigger in AI sycophancy and prevent the spread of misinformation and harm, and support safer solutions.

## References


[1]"AI Demystified: Introduction to Large Language Models | University IT," Stanford.edu. Accessed: Sep. 19, 2026. [Online]. Available: https://uit.stanford.edu/service/techtraining/ai-demystified/llm

[2] B. LaMontagne, "AI Sycophancy: When It's Good, and When It's Not," MIT Initiative on the Digital Economy. Accessed: Sep. 19, 2026. [Online]. Available: https://ide.mit.edu/insights/ai-sycophancy-when-its-good-and-when-its-not/

[3] U. Chobrak, "AI Overly Affirms Users Asking for Personal Advice," Stanford.edu. Accessed: Sep. 19, 2026. [Online]. Available: https://news.stanford.edu/stories/2026/03/ai-advice-sycophantic-models-research

[4] M. Dubois, C. Ududec, C. Summerfield, and L. Luettgau, "Ask Don't Tell: Reducing Sycophancy in Large Language Models," Feb. 27, 2026. Accessed: Sep. 19, 2026. [Online]. Available: https://arxiv.org/abs/2602.23971v1

[5] S. Chen et al., "When Helpfulness Backfires: LLMs and the Risk of False Medical Information Due to Sycophantic Behavior," npj Digital Medicine, vol. 8, no. 1, pp. 1–9, Oct. 2025, doi: 10.1038/s41746-025-02008-z.

[6] R. Xu et al., "The Earth Is Flat Because...: Investigating LLMs' Belief Towards Misinformation via Persuasive Conversation," in *Proc. 62nd Annu. Meeting Assoc. Comput. Linguistics (Vol. 1: Long Papers)*, Bangkok, Thailand, Aug. 2024, pp. 16259–16303, doi: 10.18653/v1/2024.acl-long.858.

[7] A. Kaur, "Echoes of Agreement: Argument Driven Sycophancy in Large Language Models," Findings of the Association for Computational Linguistics: EMNLP 2025, vol. Findings of the Association for Computational Linguistics: EMNLP 2025, pp. 22803–22812, 2025, doi: 10.18653/v1/2025.findings-emnlp.1241.

[8] R. Vinay, G. Spitale, N. Biller-Andorno, and F. Germani, "Emotional Prompting Amplifies Disinformation Generation in AI Large Language Models," Frontiers in Artificial Intelligence, vol. 8, Apr. 2025, doi: 10.3389/frai.2025.1543603.

[9] J. Gottfried, W. Bishop, M. Anderson, M. Faverio, E. Park, and C. McClain, "Americans and AI 2026: Chatbots, Smart Devices and Views on Impact," Pew Research Center. Accessed: Sep. 19, 2026. [Online]. Available: https://www.pewresearch.org/internet/2026/06/17/americans-and-ai-2026-chatbots-smart-devices-and-views-on-impact/

[10] L. Chen, M. Zaharia, and J. Zou, "How Is ChatGPT's Behavior Changing Over Time?," Special Issue 5: Grappling With the Generative AI Revolution, no. Special Issue 5, Mar. 2024, doi: 10.1162/99608f92.5317da47.

[11] National Institute of Standards and Technology, “AI Risk Management Framework,” NIST. Accessed: Sep. 19, 2026. [Online]. Available: https://www.nist.gov/itl/ai-risk-management-framework