# F1 Facts API (1.0.0)

Download OpenAPI specification: Download

A fun, community-driven F1 Facts API. Track drivers & teams, build favourite lists, predict championships, play trivia quizzes, compare drivers head-to-head, and share hot takes!

# Auth

## Register

Create a new user account and return access + refresh tokens.

REQUEST BODY SCHEMA: application/json

| | |
|---|---|
| `username` required | string (Username) [ 3 .. 30 ] characters |
| `email` required | string (Email) >= 5 characters |
| `display_name` required | string (Display Name) [ 1 .. 50 ] characters |
| `password` required | string (Password) >= 6 characters |

### Responses

> **201** Successful Response

> **422** Validation Error

POST /auth/register

## Request samples

Payload

Content type
application/json

Copy

```
{
    "username": "string",
    "email": "string",
    "display_name": "string",
    "password": "string"
}
```

## Response samples

201 422

Content type
application/json

Copy Expand all Collapse all

```
{
    "access_token": "string",
    "refresh_token": "string",
    "token_type": "bearer",
```

```
  - "user": {
        "_id": "string",
        "created_at": "string",
        "username": "string",
        "email": "string",
        "display_name": "string",
        "role": "user",
        "is_admin": false
    }
}
```

## Login

Authenticate with username & password and return access + refresh tokens.

REQUEST BODY SCHEMA: application/x-www-form-urlencoded

| | |
|---|---|
| `grant_type` > | Grant Type (string) or Grant Type (null) (Grant Type) |
| `username` required | string (Username) |
| `password` required | string (Password) |
| `scope` | string (Scope)<br>Default: `""` |
| `client_id` > | Client Id (string) or Client Id (null) (Client Id) |
| `client_secret` > | Client Secret (string) or Client Secret (null) (Client Secret) |

## Responses

> **200** Successful Response

> **422** Validation Error

POST /auth/login

**Response samples**

200 422

Content type
application/json

Copy Expand all Collapse all


```
{
    "access_token": "string",
    "refresh_token": "string",
    "token_type": "bearer",
  - "user": {
        "_id": "string",
        "created_at": "string",
        "username": "string",
        "email": "string",
        "display_name": "string",
        "role": "user",
        "is_admin": false
    }
}
```


## Refresh Token

Exchange a valid refresh token for a new access + refresh token pair.

The old refresh token is revoked (token rotation).

REQUEST BODY SCHEMA: application/json

refresh_token
required

string (Refresh Token)

## Responses

> **200** Successful Response

> **422** Validation Error

POST /auth/refresh

### Request samples

Payload

Content type
application/json

Copy

```
{
    "refresh_token": "string"
}
```

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all

```
{
    "access_token": "string",
    "refresh_token": "string",
    "token_type": "bearer",
```

```
  - "user": {
        "_id": "string",
        "created_at": "string",
        "username": "string",
        "email": "string",
        "display_name": "string",
        "role": "user",
        "is_admin": false
    }
}
```

## Logout

Revoke the supplied refresh token and blacklist the current access token.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json

| | |
|---|---|
| refresh_token<br>required | string (Refresh Token) |

### Responses

> **200** Successful Response

> **422** Validation Error

POST /auth/logout

**Request samples**

Payload

Content type
application/json

Copy

```
{
    "refresh_token": "string"
}
```

### Response samples

200 422

Content type
application/json

Copy

```
{
    "status": "ok",
    "message": ""
}
```

## Logout All

Revoke all refresh tokens for the current user (all devices).

AUTHORIZATIONS: > *OAuth2PasswordBearer*

### Responses

> **200** Successful Response

POST /auth/logout-all

**Response samples**

200

Content type
application/json

Copy

```
{
    "status": "ok",
    "message": ""
}
```

## Get Me

Return the authenticated user's profile.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

### Responses

> **200** Successful Response

GET /auth/me

**Response samples**

200

Content type
application/json

Copy

```
{
    "_id": "string",
    "created_at": "string",
    "username": "string",
    "email": "string",
    "display_name": "string",
    "role": "user",
    "is_admin": false
}
```


## Delete Me

Delete the authenticated user's account.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

### Responses

> **200** Successful Response

DELETE /auth/me

**Response samples**

200

**Content type**
application/json

Copy


```
{
    "status": "ok",
    "message": ""
```

```
}
```

## Update Me

Update the authenticated user's profile fields.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json

- `display_name` > Display Name (string) or Display Name (null) (Display Name)
- `email` > Email (string) or Email (null) (Email)

## Responses

> **200** Successful Response

> **422** Validation Error

PATCH `/auth/me`

### Request samples

Payload

Content type
application/json

Copy

```
{
    "display_name": "string",
    "email": "string"
```

```
}
```

### Response samples

200 422

Content type
application/json

Copy

```
{
    "_id": "string",
    "created_at": "string",
    "username": "string",
    "email": "string",
    "display_name": "string",
    "role": "user",
    "is_admin": false
}
```

# Drivers

## List Drivers

List all F1 drivers. No auth required.

QUERY PARAMETERS

`active_only` boolean (Active Only)
Default: `false`
Only return active drivers

`skip` integer (Skip) `>= 0`
Default: `0`

Number of records to skip

limit

integer (Limit) [ 1 .. 200 ]

Default: 50

Max records to return

## Responses

> **200** Successful Response

> **422** Validation Error

GET /drivers

### Response samples

200 422

Content type

application/json

Copy Expand all Collapse all


```
{
 - "data": [
     + { … }
   ],
   "total": 0,
   "skip": 0,
   "limit": 0
}
```


## Create Driver

Create a new driver (admin only).

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json

- `name` required — string (Name)
- `number` required — integer (Number)
- `team` required — string (Team)
- `nationality` — string (Nationality) Default: `""`
- `date_of_birth` — string (Date Of Birth) Default: `""`
- `championships` — integer (Championships) Default: `0`
- `wins` — integer (Wins) Default: `0`
- `podiums` — integer (Podiums) Default: `0`
- `poles` — integer (Poles) Default: `0`
- `bio` — string (Bio) Default: `""`
- `active` — boolean (Active) Default: `true`
- `kaggle_driver_id` — integer (Kaggle Driver Id) Default: `0`
- `driver_ref` — string (Driver Ref) Default: `""`
- `code` — string (Code) Default: `""`

## Responses

> **201** Successful Response

> **422** Validation Error

POST /drivers

### Request samples

Payload

Content type
application/json

Copy

```
{
    "name": "string",
    "number": 0,
    "team": "string",
    "nationality": "",
    "date_of_birth": "",
    "championships": 0,
    "wins": 0,
    "podiums": 0,
    "poles": 0,
    "bio": "",
    "active": true,
    "kaggle_driver_id": 0,
    "driver_ref": "",
    "code": ""
}
```

### Response samples

201 422

**Content type**
application/json

Copy


```
{
    "_id": "string",
    "created_at": "string",
    "name": "string",
    "number": 0,
    "team": "string",
    "nationality": "",
    "date_of_birth": "",
    "championships": 0,
    "wins": 0,
    "podiums": 0,
    "poles": 0,
    "bio": "",
    "active": true,
    "kaggle_driver_id": 0,
    "driver_ref": "",
    "code": ""
}
```


## Search

Search drivers by name or team (case-insensitive partial match).

QUERY PARAMETERS

| | |
|---|---|
| `name` > | Name (string) or Name (null) (Name) |
| `team` > | Team (string) or Team (null) (Team) |
| `skip` | integer (Skip) `>= 0`<br>Default: `0`<br>Number of records to skip |
| `limit` | integer (Limit) `[ 1 .. 200 ]`<br>Default: `50` |

Max records to return

## Responses

> **200** Successful Response

> **422** Validation Error

GET /drivers/search

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all

```
{
 - "data": [
     + { … }
   ],
   "total": 0,
   "skip": 0,
   "limit": 0
}
```

# Get Driver

Get a single driver by ID.

PATH PARAMETERS

driver_id
required

string (Driver Id)

## Responses

> **200** Successful Response

> **422** Validation Error

GET /drivers/{driver_id}

### Response samples

200 422

Content type
application/json

Copy

```
{
    "_id": "string",
    "created_at": "string",
    "name": "string",
    "number": 0,
    "team": "string",
    "nationality": "",
    "date_of_birth": "",
    "championships": 0,
    "wins": 0,
    "podiums": 0,
    "poles": 0,
    "bio": "",
    "active": true,
    "kaggle_driver_id": 0,
    "driver_ref": "",
    "code": ""
}
```


## Update Driver

Update a driver's details (admin only).

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

| | |
|---|---|
| driver_id<br>required | string (Driver Id) |

REQUEST BODY SCHEMA: application/json

| | |
|---|---|
| name > | Name (string) or Name (null) (Name) |
| number > | Number (integer) or Number (null) (Number) |
| team > | Team (string) or Team (null) (Team) |
| nationality > | Nationality (string) or Nationality (null) (Nationality) |

| | |
|---|---|
| `championships` > | Championships (integer) or Championships (null) (Championships) |
| `wins` > | Wins (integer) or Wins (null) (Wins) |
| `podiums` > | Podiums (integer) or Podiums (null) (Podiums) |
| `poles` > | Poles (integer) or Poles (null) (Poles) |
| `bio` > | Bio (string) or Bio (null) (Bio) |
| `active` > | Active (boolean) or Active (null) (Active) |
| `kaggle_driver_id` > | Kaggle Driver Id (integer) or Kaggle Driver Id (null) (Kaggle Driver Id) |
| `driver_ref` > | Driver Ref (string) or Driver Ref (null) (Driver Ref) |
| `code` > | Code (string) or Code (null) (Code) |

## Responses

> **200** Successful Response

> **422** Validation Error

PATCH `/drivers/{driver_id}`

### Request samples

Payload

**Content type**
application/json

Copy

```
{
    "name": "string",
    "number": 0,
```

```
    "team": "string",
    "nationality": "string",
    "championships": 0,
    "wins": 0,
    "podiums": 0,
    "poles": 0,
    "bio": "string",
    "active": true,
    "kaggle_driver_id": 0,
    "driver_ref": "string",
    "code": "string"
}
```

## Response samples

200 422

**Content type**
application/json

Copy

```
{
    "_id": "string",
    "created_at": "string",
    "name": "string",
    "number": 0,
    "team": "string",
    "nationality": "",
    "date_of_birth": "",
    "championships": 0,
    "wins": 0,
    "podiums": 0,
    "poles": 0,
    "bio": "",
    "active": true,
    "kaggle_driver_id": 0,
    "driver_ref": "",
    "code": ""
}
```

# Delete Driver

Delete a driver (admin only).

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

driver_id
required

string (Driver Id)

## Responses

> **200** Successful Response

> **422** Validation Error

DELETE /drivers/{driver_id}

### Response samples

200 422

Content type
application/json

Copy

```
{
    "status": "ok",
    "message": ""
}
```

# Driver Season Stats

Get historical season stats for a driver (by MongoDB _id).

Returns aggregated season performance data including wins, podiums, points, and championship positions across all seasons.

PATH PARAMETERS

| | |
|---|---|
| driver_id<br>required | string (Driver Id) |

QUERY PARAMETERS

| | |
|---|---|
| season_year > | Season Year (integer) or Season Year (null) (Season Year)<br>Filter to a specific season |

## Responses

> **200** Successful Response

> **422** Validation Error

GET /drivers/{driver_id}/stats

**Response samples**

200 422

**Content type**
application/json

Copy Expand all Collapse all

```
[
  - {
        "constructor_id": 0,
        "constructor_name": "string",
        "driver_id": 0,
        "driver_name": "string",
        "season_year": 0,
        "_id": "string",
        "created_at": "string",
        "starts": 0,
        "wins": 0,
        "podiums": 0,
        "poles": 0,
        "race_points": 0,
        "sprint_points": 0,
        "sprint_wins": 0,
        "sprint_podiums": 0,
        "classified_finishes": 0,
        "dnfs": 0,
        "best_finish": 0,
        "championship_position": 0,
        "champion": false,
        "total_points": 0
    }
]
```


## All Driver Stats For Season

Get all driver season stats for a given championship year.

PATH PARAMETERS

| | |
|---|---|
| season_year<br>required | integer (Season Year) |

## Responses

> **200** Successful Response

> **422** Validation Error

GET /drivers/stats/season/{season_year}

## Response samples

200 422

**Content type**
application/json

Copy Expand all Collapse all

```
[
  - {
        "constructor_id": 0,
        "constructor_name": "string",
        "driver_id": 0,
        "driver_name": "string",
        "season_year": 0,
        "_id": "string",
        "created_at": "string",
        "starts": 0,
        "wins": 0,
        "podiums": 0,
        "poles": 0,
        "race_points": 0,
        "sprint_points": 0,
        "sprint_wins": 0,
        "sprint_podiums": 0,
        "classified_finishes": 0,
        "dnfs": 0,
        "best_finish": 0,
        "championship_position": 0,
        "champion": false,
        "total_points": 0
    }
]
```


# Teams

## List Teams

List all F1 teams. No auth required.

QUERY PARAMETERS

`active_only` boolean (Active Only)
Default: `false`
Only return active teams

`skip` integer (Skip) `>= 0`
Default: `0`
Number of records to skip

`limit` integer (Limit) `[ 1 .. 200 ]`
Default: `50`
Max records to return

## Responses

> **200** Successful Response

> **422** Validation Error

GET /teams

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
{
 - "data": [
     + { … }
   ],
   "total": 0,
   "skip": 0,
   "limit": 0
}
```

# Create Team

Create a new team (admin only).

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json

- `name` required — string (Name)
- `full_name` — string (Full Name) Default: `""`
- `base` — string (Base) Default: `""`
- `team_principal` — string (Team Principal) Default: `""`
- `nationality` — string (Nationality) Default: `""`
- `championships` — integer (Championships) Default: `0`
- `first_entry` — integer (First Entry) Default: `0`
- `car` — string (Car) Default: `""`
- `engine` — string (Engine) Default: `""`
- `active` — boolean (Active) Default: `true`
- `kaggle_constructor_id` — integer (Kaggle Constructor Id) Default: `0`

constructor_ref string (Constructor Ref)
Default: ""

## Responses

> **201** Successful Response

> **422** Validation Error

POST /teams

### Request samples

Payload

Content type
application/json

Copy

```
{
    "name": "string",
    "full_name": "",
    "base": "",
    "team_principal": "",
    "nationality": "",
    "championships": 0,
    "first_entry": 0,
    "car": "",
    "engine": "",
    "active": true,
    "kaggle_constructor_id": 0,
    "constructor_ref": ""
}
```

### Response samples

201 422

Content type
application/json

Copy


```
{
    "_id": "string",
    "created_at": "string",
    "name": "string",
    "full_name": "",
    "base": "",
    "team_principal": "",
    "nationality": "",
    "championships": 0,
    "first_entry": 0,
    "car": "",
    "engine": "",
    "active": true,
    "kaggle_constructor_id": 0,
    "constructor_ref": ""
}
```


## Search

Search teams by name (case-insensitive partial match).

QUERY PARAMETERS

| | |
|---|---|
| name > | Name (string) or Name (null) (Name) |
| skip | integer (Skip) >= 0<br>Default: 0<br>Number of records to skip |
| limit | integer (Limit) [ 1 .. 200 ]<br>Default: 50<br>Max records to return |

## Responses

> **200** Successful Response

> **422** Validation Error

GET /teams/search

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
{
 - "data": [
     + { … }
   ],
   "total": 0,
   "skip": 0,
   "limit": 0
}
```


# Get Team

Get a single team by ID.

PATH PARAMETERS

| | |
|---|---|
| team_id<br>required | string (Team Id) |

## Responses

> **200** Successful Response

> **422** Validation Error

GET /teams/{team_id}

### Response samples

200 422

Content type
application/json

Copy


```
{
    "_id": "string",
    "created_at": "string",
    "name": "string",
    "full_name": "",
    "base": "",
    "team_principal": "",
    "nationality": "",
    "championships": 0,
    "first_entry": 0,
    "car": "",
    "engine": "",
    "active": true,
    "kaggle_constructor_id": 0,
    "constructor_ref": ""
}
```

# Update Team

Update a team's details (admin only).

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

| | |
|---|---|
| team_id<br>required | string (Team Id) |

REQUEST BODY SCHEMA: application/json

| | |
|---|---|
| name > | Name (string) or Name (null) (Name) |
| full_name > | Full Name (string) or Full Name (null) (Full Name) |
| base > | Base (string) or Base (null) (Base) |
| team_principal > | Team Principal (string) or Team Principal (null) (Team Principal) |
| nationality > | Nationality (string) or Nationality (null) (Nationality) |
| championships > | Championships (integer) or Championships (null) (Championships) |
| first_entry > | First Entry (integer) or First Entry (null) (First Entry) |
| car > | Car (string) or Car (null) (Car) |
| engine > | Engine (string) or Engine (null) (Engine) |
| active > | Active (boolean) or Active (null) (Active) |
| kaggle_constructor_id > | Kaggle Constructor Id (integer) or Kaggle Constructor Id (null) (Kaggle Constructor Id) |
| constructor_ref > | Constructor Ref (string) or Constructor Ref (null) (Constructor Ref) |

## Responses

> **200** Successful Response

> **422** Validation Error

PATCH /teams/{team_id}

## Request samples

Payload

Content type
application/json

Copy

```
{
    "name": "string",
    "full_name": "string",
    "base": "string",
    "team_principal": "string",
    "nationality": "string",
    "championships": 0,
    "first_entry": 0,
    "car": "string",
    "engine": "string",
    "active": true,
    "kaggle_constructor_id": 0,
    "constructor_ref": "string"
}
```

## Response samples

200 422

Content type
application/json

Copy

```
{
    "_id": "string",
    "created_at": "string",
    "name": "string",
    "full_name": "",
    "base": "",
    "team_principal": "",
    "nationality": "",
    "championships": 0,
    "first_entry": 0,
    "car": "",
    "engine": "",
    "active": true,
    "kaggle_constructor_id": 0,
    "constructor_ref": ""
}
```


## Delete Team

Delete a team (admin only).

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

| | |
|---|---|
| team_id<br>required | string (Team Id) |

## Responses

> **200** Successful Response

> **422** Validation Error

DELETE /teams/{team_id}

### Response samples

200 422

Content type
application/json

Copy

```
{
    "status": "ok",
    "message": ""
}
```

## Team Season Stats

Get historical season stats for a team (by MongoDB _id).

Returns aggregated season performance data including wins, points, podiums, and championship positions across all seasons.

PATH PARAMETERS

| | |
|---|---|
| team_id<br>required | string (Team Id) |

QUERY PARAMETERS

| | |
|---|---|
| season_year > | Season Year (integer) or Season Year (null) (Season Year)<br>Filter to a specific season |

## Responses

> **200** Successful Response

> **422** Validation Error

GET /teams/{team_id}/stats

**Response samples**

200 422

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "constructor_id": 0,
      "constructor_name": "string",
      "season_year": 0,
      "_id": "string",
      "created_at": "string",
      "race_entries": 0,
      "total_points": 0,
      "wins": 0,
      "podium_finishes": 0,
      "championship_position": 0,
      "champion": false
   }
]
```


## All Team Stats For Season

Get all constructor season stats for a given championship year.

PATH PARAMETERS

season_year
required

integer (Season Year)

## Responses

> **200** Successful Response

> **422** Validation Error

GET /teams/stats/season/{season_year}

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "constructor_id": 0,
      "constructor_name": "string",
      "season_year": 0,
      "_id": "string",
      "created_at": "string",
      "race_entries": 0,
      "total_points": 0,
      "wins": 0,
      "podium_finishes": 0,
      "championship_position": 0,
      "champion": false
   }
]
```

# Team Standings

Get constructor championship standings history for a team.

PATH PARAMETERS

| | |
|---|---|
| `team_id` required | string (Team Id) |

QUERY PARAMETERS

| | |
|---|---|
| `season_year` > | Season Year (integer) or Season Year (null) (Season Year)<br>Filter to a specific season |
| `final_only` | boolean (Final Only)<br>Default: `false`<br>Only return end-of-season standings |

## Responses

> **200** Successful Response

> **422** Validation Error

GET `/teams/{team_id}/standings`

**Response samples**

200 422

**Content type**
application/json

Copy Expand all Collapse all

```
[
 - {
      "constructor_id": 0,
      "constructor_name": "string",
      "season_year": 0,
      "race_id": 0,
      "round": 0,
      "race_name": "string",
      "_id": "string",
      "created_at": "string",
      "constructor_standing_id": 0,
      "points": 0,
      "position": 0,
      "position_text": "",
      "wins": 0,
      "is_final_race": false
   }
]
```


## Team Results

Get constructor race results history for a team.

PATH PARAMETERS

| | |
|---|---|
| team_id<br>required | string (Team Id) |

QUERY PARAMETERS

| | |
|---|---|
| season_year > | Season Year (integer) or Season Year (null) (Season Year)<br>Filter to a specific season |

## Responses

> **200** Successful Response

> **422** Validation Error

GET /teams/{team_id}/results

**Response samples**

200 422

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "constructor_id": 0,
      "constructor_name": "string",
      "season_year": 0,
      "race_id": 0,
      "round": 0,
      "race_name": "string",
      "_id": "string",
      "created_at": "string",
      "constructor_result_id": 0,
      "points": 0,
      "status": ""
   }
]
```


# Favourites

# List Favourites

Return all favourite lists for the authenticated user.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

QUERY PARAMETERS

list_type > List Type (string) or List Type (null) (List Type)

## Responses

> **200** Successful Response

> **422** Validation Error

GET /favourites

**Response samples**

200 422

**Content type**
application/json

Copy Expand all Collapse all

```
[
 - {
       "_id": "string",
       "created_at": "string",
       "user_id": "string",
       "name": "string",
       "list_type": "string",
       "items": [ ],
       "updated_at": "string"
    }
]
```


## Create Favourite

Create a new favourite list (e.g. 'My Top Drivers').

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json

| | |
|---|---|
| name<br>required | string (Name) [ 1 .. 100 ] characters |
| list_type<br>required | string (List Type) ^(drivers\|teams)$ |

## Responses

> **201** Successful Response

> **422** Validation Error

POST /favourites

**Request samples**

Payload

Content type
application/json

Copy

```
{
    "name": "string",
    "list_type": "string"
}
```

### Response samples

201 422

Content type
application/json

Copy Expand all Collapse all

```
{
    "_id": "string",
    "created_at": "string",
    "user_id": "string",
    "name": "string",
    "list_type": "string",
    "items": [ ],
    "updated_at": "string"
}
```

## Get Favourite

Get a single favourite list by ID.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

fav_id
required

string (Fav Id)

## Responses

> **200** Successful Response

> **422** Validation Error

GET /favourites/{fav_id}

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all

```
{
    "_id": "string",
    "created_at": "string",
    "user_id": "string",
    "name": "string",
    "list_type": "string",
    "items": [ ],
    "updated_at": "string"
}
```

# Update Favourite

Rename a favourite list.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

| | |
|---|---|
| fav_id<br>required | string (Fav Id) |

REQUEST BODY SCHEMA: application/json

| | |
|---|---|
| name > | Name (string) or Name (null) (Name) |

## Responses

> **200** Successful Response

> **422** Validation Error

PATCH /favourites/{fav_id}

### Request samples

Payload

Content type
application/json

Copy

```
{
    "name": "string"
}
```

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
{
    "_id": "string",
    "created_at": "string",
    "user_id": "string",
    "name": "string",
    "list_type": "string",
    "items": [ ],
    "updated_at": "string"
}
```


## Delete Favourite

Delete a favourite list.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

| | |
|---|---|
| fav_id<br>required | string (Fav Id) |

## Responses

> **200** Successful Response

> **422** Validation Error

DELETE /favourites/{fav_id}

**Response samples**

200 422

**Content type**
application/json

Copy

```
{
    "status": "ok",
    "message": ""
}
```

# Add Item

Add a driver or team to a favourite list.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

| | |
|---|---|
| `fav_id` required | string (Fav Id) |

REQUEST BODY SCHEMA: application/json

| | |
|---|---|
| `item_id` required | string (Item Id) |
| `name` required | string (Name) |

## Responses

> **200** Successful Response

> **422** Validation Error

POST /favourites/{fav_id}/items

### Request samples

Payload

Content type
application/json

Copy

```
{
    "item_id": "string",
    "name": "string"
}
```

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all

```
{
    "_id": "string",
    "created_at": "string",
    "user_id": "string",
    "name": "string",
    "list_type": "string",
    "items": [ ],
    "updated_at": "string"
}
```

## Remove Item

Remove a driver or team from a favourite list.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

| | |
|---|---|
| `fav_id` required | string (Fav Id) |
| `item_id` required | string (Item Id) |

## Responses

> **200** Successful Response

> **422** Validation Error

DELETE `/favourites/{fav_id}/items/{item_id}`

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all

```
{
    "_id": "string",
    "created_at": "string",
    "user_id": "string",
    "name": "string",
    "list_type": "string",
    "items": [ ],
    "updated_at": "string"
}
```

# Predictions

## List My Predictions

List the authenticated user's predictions.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

QUERY PARAMETERS

| | |
|---|---|
| season > | Season (integer) or Season (null) (Season) |
| category > | Category (string) or Category (null) (Category) |

### Responses

> **200** Successful Response

> **422** Validation Error

GET /predictions

**Response samples**

200 422

**Content type**
application/json

Copy Expand all Collapse all

```
[
 - {
      "_id": "string",
      "created_at": "string",
      "user_id": "string",
      "season": 0,
      "category": "string",
      "predicted_id": "string",
      "predicted_name": "string",
      "confidence": 5,
      "reasoning": ""
   }
]
```


## Create Prediction

Submit a championship prediction (one per category per season).

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json

| | |
|---|---|
| season<br>required | integer (Season) |
| category<br>required | string (Category) ^(driver_championship\|constructor_championshi... Show pattern |
| predicted_id<br>required | string (Predicted Id) |
| predicted_name<br>required | string (Predicted Name) |
| confidence | integer (Confidence) [ 1 .. 10 ]<br>Default: 5 |
| reasoning | string (Reasoning) <= 500 characters<br>Default: " " |

## Responses

> **201** Successful Response

> **422** Validation Error

POST /predictions

### Request samples

Payload

Content type
application/json

Copy

```
{
    "season": 0,
    "category": "string",
    "predicted_id": "string",
    "predicted_name": "string",
    "confidence": 5,
    "reasoning": ""
}
```

### Response samples

201 422

Content type
application/json

Copy

```
{
    "_id": "string",
    "created_at": "string",
    "user_id": "string",
    "season": 0,
```

```
    "category": "string",
    "predicted_id": "string",
    "predicted_name": "string",
    "confidence": 5,
    "reasoning": ""
}
```

## Get Prediction

Get a single prediction by ID.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

| | |
|---|---|
| pred_id<br>required | string (Pred Id) |

## Responses

> **200** Successful Response

> **422** Validation Error

GET /predictions/view/{pred_id}

### Response samples

200 422

**Content type**
application/json

Copy

```
{
    "_id": "string",
    "created_at": "string",
    "user_id": "string",
    "season": 0,
    "category": "string",
    "predicted_id": "string",
    "predicted_name": "string",
    "confidence": 5,
    "reasoning": ""
}
```

## Update Prediction

Update your prediction (change pick, confidence, reasoning).

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

| | |
|---|---|
| pred_id<br>required | string (Pred Id) |

REQUEST BODY SCHEMA: application/json

| | |
|---|---|
| predicted_id > | Predicted Id (string) or Predicted Id (null) (Predicted Id) |
| predicted_name > | Predicted Name (string) or Predicted Name (null) (Predicted Name) |
| confidence > | Confidence (integer) or Confidence (null) (Confidence) |
| reasoning > | Reasoning (string) or Reasoning (null) (Reasoning) |

## Responses

> **200** Successful Response

> **422** Validation Error

PATCH /predictions/{pred_id}

## Request samples

Payload

Content type
application/json

Copy

```
{
    "predicted_id": "string",
    "predicted_name": "string",
    "confidence": 1,
    "reasoning": "string"
}
```

## Response samples

200 422

Content type
application/json

Copy

```
{
    "_id": "string",
    "created_at": "string",
    "user_id": "string",
    "season": 0,
    "category": "string",
    "predicted_id": "string",
    "predicted_name": "string",
    "confidence": 5,
    "reasoning": ""
}
```

# Delete Prediction

Delete one of your predictions.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

| | |
|---|---|
| pred_id<br>required | string (Pred Id) |

## Responses

> **200** Successful Response

> **422** Validation Error

DELETE /predictions/{pred_id}

**Response samples**

200 422

**Content type**
application/json

Copy

```
{
    "status": "ok",
    "message": ""
}
```

# Driver Championship Leaderboard

Who does the community think will win the Drivers' Championship?

QUERY PARAMETERS

season — integer (Season)
Default: 2025
Season year

## Responses

> **200** Successful Response

> **422** Validation Error

GET /predictions/leaderboard/drivers

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "predicted_id": "string",
      "predicted_name": "string",
      "vote_count": 0,
      "avg_confidence": 0
   }
]
```

# Constructor Championship Leaderboard

Who does the community think will win the Constructors' Championship?

QUERY PARAMETERS

season — integer (Season)
Default: 2025
Season year

## Responses

> **200** Successful Response

> **422** Validation Error

GET /predictions/leaderboard/constructors

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
      "predicted_id": "string",
      "predicted_name": "string",
      "vote_count": 0,
      "avg_confidence": 0
   }
```

```
]
```

# Circuits

## List Circuits

List all F1 circuits. No auth required.

QUERY PARAMETERS

| | |
|---|---|
| `active_only` | boolean (Active Only)<br>Default: `false`<br>Only return currently active circuits |
| `country` > | Country (string) or Country (null) (Country)<br>Filter by country |
| `skip` | integer (Skip) `>= 0`<br>Default: `0`<br>Number of records to skip |
| `limit` | integer (Limit) `[ 1 .. 200 ]`<br>Default: `50`<br>Max records to return |

## Responses

> **200** Successful Response

> **422** Validation Error

GET /circuits

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
{
 - "data": [
     + { … }
   ],
   "total": 0,
   "skip": 0,
   "limit": 0
}
```


## Search

Search circuits by name or country.

QUERY PARAMETERS

| | |
|---|---|
| name > | Name (string) or Name (null) (Name)<br>Circuit name (partial match) |
| country > | Country (string) or Country (null) (Country)<br>Country (partial match) |
| skip | integer (Skip) >= 0<br>Default: 0<br>Number of records to skip |
| limit | integer (Limit) [ 1 .. 200 ]<br>Default: 50 |

Max records to return

## Responses

> **200** Successful Response

> **422** Validation Error

GET /circuits/search

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
{
 - "data": [
     + { … }
   ],
   "total": 0,
   "skip": 0,
   "limit": 0
}
```


# Get Circuit

Get a single circuit by its Kaggle circuitId.

PATH PARAMETERS

circuit_id
required

integer (Circuit Id)

## Responses

> **200** Successful Response

> **422** Validation Error

GET /circuits/{circuit_id}

### Response samples

200 422

Content type
application/json

Copy


```
{
    "_id": "string",
    "created_at": "string",
    "circuit_id": 0,
    "circuit_ref": "",
    "name": "string",
    "location": "",
    "country": "",
    "latitude": 0,
    "longitude": 0,
    "altitude": 0,
    "url": "",
    "race_count": 0,
    "first_used_year": 0,
    "last_used_year": 0,
    "active": false
}
```

# Seasons

## List Seasons

List all F1 seasons, optionally filtered by year range. Newest first.

QUERY PARAMETERS

| | |
|---|---|
| `start_year` > | Start Year (integer) or Start Year (null) (Start Year)<br>Start year (inclusive) |
| `end_year` > | End Year (integer) or End Year (null) (End Year)<br>End year (inclusive) |
| `skip` | integer (Skip) `>= 0`<br>Default: `0`<br>Number of records to skip |
| `limit` | integer (Limit) `[ 1 .. 200 ]`<br>Default: `50`<br>Max records to return |

### Responses

> **200** Successful Response

> **422** Validation Error

GET /seasons

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
{
 - "data": [
     + { … }
   ],
   "total": 0,
   "skip": 0,
   "limit": 0
}
```


## Get Season

Get a single season by championship year.

PATH PARAMETERS

| | |
|---|---|
| year<br>required | integer (Year) |

## Responses

> 200 Successful Response

> **422** Validation Error

GET /seasons/{year}

**Response samples**

200 422

Content type
application/json

Copy


```
{
    "_id": "string",
    "created_at": "string",
    "year": 0,
    "url": "",
    "race_count": 0,
    "sprint_round_count": 0,
    "opening_race": "",
    "final_race": "",
    "champion_driver_id": 0,
    "champion_driver_name": "",
    "champion_constructor_id": 0,
    "champion_constructor_name": ""
}
```


# Races

## List Races

List races, optionally filtered by season year or circuit.

QUERY PARAMETERS

| | |
|---|---|
| `season_year` > | Season Year (integer) or Season Year (null) (Season Year)<br>Filter by season year |
| `circuit_id` > | Circuit Id (integer) or Circuit Id (null) (Circuit Id)<br>Filter by circuit id |
| `skip` | integer (Skip) `>= 0`<br>Default: `0`<br>Number of records to skip |
| `limit` | integer (Limit) `[ 1 .. 200 ]`<br>Default: `50`<br>Max records to return |

## Responses

> **200** Successful Response

> **422** Validation Error

GET /races

**Response samples**

200 422

**Content type**
application/json

Copy Expand all Collapse all

```
{
  - "data": [
      + { … }
    ],
    "total": 0,
    "skip": 0,
    "limit": 0
}
```


## List Statuses

List all race finish status codes.

### Responses

> **200** Successful Response

GET /races/statuses

**Response samples**

200

**Content type**
application/json

Copy Expand all Collapse all


```
[
  - {
        "_id": "string",
        "created_at": "string",
        "status_id": 0,
        "status": "string"
    }
```

```
]
```

## Get Race

Get a single race by its Kaggle raceId.

PATH PARAMETERS

| | |
|---|---|
| race_id<br>required | integer (Race Id) |

## Responses

> **200** Successful Response

> **422** Validation Error

GET /races/{race_id}

### Response samples

200 422

Content type
application/json

Copy

```
{
    "season_year": 0,
    "_id": "string",
    "created_at": "string",
    "race_id": 0,
    "round": 0,
```

```
    "name": "string",
    "circuit_id": 0,
    "circuit_name": "",
    "location": "",
    "country": "",
    "date": "",
    "time": "",
    "url": "",
    "has_sprint": false,
    "winner_driver_id": 0,
    "winner_driver_name": "",
    "winner_constructor_id": 0,
    "winner_constructor_name": ""
}
```


## Get Race By Round

Get a race by season year and round number.

PATH PARAMETERS

| | |
|---|---|
| season_year<br>required | integer (Season Year) |
| round_number<br>required | integer (Round Number) |

### Responses

> **200** Successful Response

> **422** Validation Error

GET /races/season/{season_year}/round/{round_number}

### Response samples

200 422

Content type
application/json

Copy


```
{
    "season_year": 0,
    "_id": "string",
    "created_at": "string",
    "race_id": 0,
    "round": 0,
    "name": "string",
    "circuit_id": 0,
    "circuit_name": "",
    "location": "",
    "country": "",
    "date": "",
    "time": "",
    "url": "",
    "has_sprint": false,
    "winner_driver_id": 0,
    "winner_driver_name": "",
    "winner_constructor_id": 0,
    "winner_constructor_name": ""
}
```


# Results

## List Race Results

List race results with flexible filtering.

QUERY PARAMETERS

| | |
|---|---|
| `race_id` > | Race Id (integer) or Race Id (null) (Race Id)<br>Filter by race id |
| `season_year` > | Season Year (integer) or Season Year (null) (Season Year)<br>Filter by season year |
| `driver_id` > | Driver Id (integer) or Driver Id (null) (Driver Id)<br>Filter by Kaggle driver id |
| `constructor_id` > | Constructor Id (integer) or Constructor Id (null) (Constructor Id)<br>Filter by Kaggle constructor id |
| `limit` | integer (Limit) [ 1 .. 1000 ]<br>Default: `100`<br>Max results to return |

## Responses

> **200** Successful Response

> **422** Validation Error

GET /results/race

**Response samples**

200 422

**Content type**
application/json

Copy Expand all Collapse all

```
[
  - {
        "circuit_id": 0,
        "circuit_name": "",
        "constructor_id": 0,
        "constructor_name": "string",
        "driver_id": 0,
        "driver_name": "string",
        "season_year": 0,
        "race_id": 0,
        "round": 0,
        "race_name": "string",
        "_id": "string",
        "created_at": "string",
        "result_id": 0,
        "grid": 0,
        "position": 0,
        "position_text": "",
        "position_order": 0,
        "points": 0,
        "laps": 0,
        "time": "",
        "milliseconds": 0,
        "status_id": 0,
        "status": "",
        "classified_finish": false,
        "number": 0,
        "fastest_lap": 0,
        "fastest_lap_time": "",
        "fastest_lap_speed": 0
    }
]
```


## List Sprint Results

List sprint results with flexible filtering.

QUERY PARAMETERS

`race_id` >
Race Id (integer) or Race Id (null) (Race Id)
Filter by race id

`season_year` >
Season Year (integer) or Season Year (null) (Season Year)
Filter by season year

`driver_id` >
Driver Id (integer) or Driver Id (null) (Driver Id)
Filter by Kaggle driver id

`limit`
integer (Limit) [ 1 .. 1000 ]
Default: `100`
Max results to return

## Responses

> **200** Successful Response

> **422** Validation Error

GET /results/sprint

### Response samples

200 422

**Content type**
application/json

Copy Expand all Collapse all

```
[
 - {
        "constructor_id": 0,
        "constructor_name": "string",
        "driver_id": 0,
        "driver_name": "string",
        "season_year": 0,
        "race_id": 0,
        "round": 0,
        "race_name": "string",
        "_id": "string",
        "created_at": "string",
        "result_id": 0,
        "grid": 0,
        "position": 0,
        "position_text": "",
        "position_order": 0,
        "points": 0,
        "laps": 0,
        "time": "",
        "milliseconds": 0,
        "status_id": 0,
        "status": "",
        "classified_finish": false,
        "fastest_lap": 0,
        "fastest_lap_time": ""
    }
]
```


## List Lap Time Summaries

List lap-time summaries with flexible filtering.

QUERY PARAMETERS

| | |
|---|---|
| race_id > | Race Id (integer) or Race Id (null) (Race Id)<br>Filter by race id |
| driver_id > | Driver Id (integer) or Driver Id (null) (Driver Id) |

Filter by Kaggle driver id

season_year >

Season Year (integer) or Season Year (null) (Season Year)

Filter by season year

limit

integer (Limit) [ 1 .. 1000 ]

Default: 100

Max results to return

## Responses

> **200** Successful Response

> **422** Validation Error

GET /results/lap-times

### Response samples

200 422

Content type

application/json

Copy Expand all Collapse all

```
[
 - {
        "constructor_id": 0,
        "constructor_name": "string",
        "driver_id": 0,
        "driver_name": "string",
        "season_year": 0,
        "race_id": 0,
        "round": 0,
        "race_name": "string",
        "_id": "string",
        "created_at": "string",
        "lap_count": 0,
        "best_lap_time_ms": 0,
        "best_lap_number": 0,
        "average_lap_time_ms": 0,
        "total_lap_time_ms": 0
    }
]
```


# Trivia & Facts

## Random Fact

Get a random approved F1 fact.

QUERY PARAMETERS

| | |
|---|---|
| category > | Category (string) or Category (null) (Category)<br>history, records, fun, technical |

### Responses

> **200** Successful Response

> **422** Validation Error

GET /trivia/random

### Response samples

200 422

**Content type**
application/json

**Example**
Fact

Copy Expand all Collapse all


```
{
    "_id": "string",
    "created_at": "string",
    "content": "string",
    "category": "fun",
    "source": "",
    "submitted_by": "system",
    "approved": false,
    "likes": 0,
  - "liked_by": [
        "string"
    ]
}
```


## List Facts

List all approved facts, optionally filtered by category.

QUERY PARAMETERS

category > Category (string) or Category (null) (Category)

## Responses

> **200** Successful Response

> **422** Validation Error

GET /trivia

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
[
 - {
       "_id": "string",
       "created_at": "string",
       "content": "string",
       "category": "fun",
       "source": "",
       "submitted_by": "system",
       "approved": false,
       "likes": 0,
     + "liked_by": [ … ]
   }
]
```

# Submit Fact

Submit a new F1 fact (requires admin approval before it shows publicly).

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json

- `content` required — string (Content) [ 10 .. 1000 ] characters
- `category` — string (Category) ^(history|records|fun|technical)$
  Default: `"fun"`
- `source` — string (Source)
  Default: `""`

## Responses

> **201** Successful Response

> **422** Validation Error

POST /trivia

### Request samples

Payload

Content type
application/json

Copy

```
{
    "content": "stringstri",
    "category": "fun",
```

```
    "source": ""
}
```

### Response samples

201 422

Content type
application/json

Copy Expand all Collapse all

```
{
    "_id": "string",
    "created_at": "string",
    "content": "string",
    "category": "fun",
    "source": "",
    "submitted_by": "system",
    "approved": false,
    "likes": 0,
  - "liked_by": [
        "string"
    ]
}
```

## Toggle Like

Toggle like on a fact.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

| | |
|---|---|
| fact_id<br>required | string (Fact Id) |

## Responses

> **200** Successful Response

> **422** Validation Error

POST /trivia/{fact_id}/like

**Response samples**

200 422

Content type
application/json

Copy Expand all Collapse all


```
{
    "_id": "string",
    "created_at": "string",
    "content": "string",
    "category": "fun",
    "source": "",
    "submitted_by": "system",
    "approved": false,
    "likes": 0,
  - "liked_by": [
        "string"
    ]
}
```


## Approve Fact

Approve a user-submitted fact so it appears publicly (admin only).

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

fact_id
required

string (Fact Id)

## Responses

**200** Successful Response

**422** Validation Error

PATCH /trivia/{fact_id}/approve

### Response samples

200 422

Content type
application/json

Copy Expand all Collapse all


```
{
    "_id": "string",
    "created_at": "string",
    "content": "string",
    "category": "fun",
    "source": "",
    "submitted_by": "system",
    "approved": false,
    "likes": 0,
  - "liked_by": [
        "string"
    ]
}
```

# Delete Fact

Delete a fact (admin only).

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

| | |
|---|---|
| fact_id<br>required | string (Fact Id) |

## Responses

> **200** Successful Response

> **422** Validation Error

DELETE /trivia/{fact_id}

### Response samples

200 422

**Content type**
application/json

Copy

```
{
    "status": "ok",
    "message": ""
}
```

# Get Quiz Question

Get a random multiple-choice F1 trivia question.

## Responses

> **200** Successful Response

GET /trivia/quiz

**Response samples**

200

**Content type**
application/json

Copy Expand all Collapse all


```
{
    "question_id": "string",
    "question": "string",
  - "options": [
        "string"
    ],
    "category": "quiz"
}
```


# Answer Quiz

Check your answer to a quiz question.

REQUEST BODY SCHEMA: application/json

| | |
|---|---|
| question_id<br>required | string (Question Id) |
| answer<br>required | string (Answer) |

## Responses

> **200** Successful Response

> **422** Validation Error

POST /trivia/quiz/answer

### Request samples

Payload

Content type
application/json

Copy

```
{
    "question_id": "string",
    "answer": "string"
}
```

### Response samples

200 422

Content type
application/json

Copy

```
{
    "correct": true,
    "correct_answer": "string",
    "fun_fact": ""
}
```

# Hot Takes

## List Hot Takes

List hot takes. Sort: recent, spicy (most disagreed), popular (most agreed).

QUERY PARAMETERS

| | |
|---|---|
| `category` > | Category (string) or Category (null) (Category) |
| `sort_by` | string (Sort By) ^(recent\|spicy\|popular)$<br>Default: `"recent"` |
| `skip` | integer (Skip) `>= 0`<br>Default: `0`<br>Number of records to skip |
| `limit` | integer (Limit) `[ 1 .. 200 ]`<br>Default: `50`<br>Max records to return |

### Responses

> **200** Successful Response

> **422** Validation Error

GET /hot-takes

**Response samples**

200 422

Content type
application/json

Copy Expand all Collapse all


```
{
  - "data": [
      + { … }
    ],
    "total": 0,
    "skip": 0,
    "limit": 0
}
```


# Post Hot Take

Post a controversial F1 opinion.

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json

- **content** required — string (Content) [ 10 .. 500 ] characters
- **category** — string (Category) ^(general|driver|team|rule|prediction)$
  Default: "general"

## Responses

> **201** Successful Response

> **422** Validation Error

POST /hot-takes

### Request samples

Payload

Content type
application/json

Copy

```
{
    "content": "stringstri",
    "category": "general"
}
```

### Response samples

201 422

Content type
application/json

Copy Expand all Collapse all

```
{
    "_id": "string",
    "created_at": "string",
    "user_id": "string",
    "user_display_name": "",
    "content": "string",
    "category": "general",
    "agrees": 0,
    "disagrees": 0,
```

```
  - "agreed_by": [
        "string"
    ],
  - "disagreed_by": [
        "string"
    ]
}
```

## Get Hot Take

Get a single hot take.

PATH PARAMETERS

| | |
|---|---|
| take_id<br>required | string (Take Id) |

## Responses

> **200** Successful Response

> **422** Validation Error

GET /hot-takes/{take_id}

**Response samples**

200 422

**Content type**
application/json

Copy Expand all Collapse all

```
{
    "_id": "string",
    "created_at": "string",
    "user_id": "string",
    "user_display_name": "",
    "content": "string",
    "category": "general",
    "agrees": 0,
    "disagrees": 0,
  - "agreed_by": [
        "string"
    ],
  - "disagreed_by": [
        "string"
    ]
}
```


## Delete Hot Take

Delete your own hot take (admins can delete any).

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

| | |
|---|---|
| take_id<br>required | string (Take Id) |

## Responses

> **200** Successful Response

> **422** Validation Error

DELETE /hot-takes/{take_id}

### Response samples

200 422

Content type
application/json

Copy

```
{
    "status": "ok",
    "message": ""
}
```

## React

Agree or disagree with a hot take (toggleable).

AUTHORIZATIONS: > *OAuth2PasswordBearer*

PATH PARAMETERS

| | |
|---|---|
| take_id<br>required | string (Take Id) |

REQUEST BODY SCHEMA: application/json

| | |
|---|---|
| reaction<br>required | string (Reaction) ^(agree\|disagree)$ |

## Responses

> **200** Successful Response

> **422** Validation Error

POST /hot-takes/{take_id}/react

## Request samples

Payload

Content type
application/json

Copy

```
{
    "reaction": "string"
}
```

## Response samples

200 422

Content type
application/json

Copy Expand all Collapse all

```
{
    "_id": "string",
    "created_at": "string",
    "user_id": "string",
    "user_display_name": "",
    "content": "string",
    "category": "general",
    "agrees": 0,
    "disagrees": 0,
  - "agreed_by": [
        "string"
    ],
  - "disagreed_by": [
        "string"
    ]
```

```
  }
```

# Head-to-Head

## Compare Drivers

Compare two drivers' stats side-by-side with community vote results.

PATH PARAMETERS

| | |
|---|---|
| driver1_name<br>required | string (Driver1 Name) |
| driver2_name<br>required | string (Driver2 Name) |

### Responses

> **200** Successful Response

> **422** Validation Error

GET /head-to-head/compare/{driver1_name}/{driver2_name}

**Response samples**

200 422

**Content type**
application/json

Copy Expand all Collapse all

```
{
    "driver1": { },
    "driver2": { },
    "community_votes": { }
}
```

## Vote Head To Head

Vote for your preferred driver in a head-to-head matchup.

Supply driver IDs **or** driver names (or a mix) for driver1, driver2, and winner. One vote per user per matchup (can change your vote).

AUTHORIZATIONS: > *OAuth2PasswordBearer*

REQUEST BODY SCHEMA: application/json

- `driver1_id` >
  Driver1 Id (string) or Driver1 Id (null) (Driver1 Id)
  Driver 1 MongoDB ID
- `driver2_id` >
  Driver2 Id (string) or Driver2 Id (null) (Driver2 Id)
  Driver 2 MongoDB ID
- `winner_id` >
  Winner Id (string) or Winner Id (null) (Winner Id)
  Winner MongoDB ID
- `driver1_name` >
  Driver1 Name (string) or Driver1 Name (null) (Driver1 Name)
  Driver 1 name (resolved to ID)
- `driver2_name` >
  Driver2 Name (string) or Driver2 Name (null) (Driver2 Name)
  Driver 2 name (resolved to ID)
- `winner_name` >
  Winner Name (string) or Winner Name (null) (Winner Name)
  Winner name (resolved to ID)

## Responses

> **201** Successful Response

> **422** Validation Error

POST /head-to-head/vote

### Request samples

Payload

Content type
application/json

Copy

```
{
    "driver1_id": "string",
    "driver2_id": "string",
    "winner_id": "string",
    "driver1_name": "string",
    "driver2_name": "string",
    "winner_name": "string"
}
```

### Response samples

201 422

Content type
application/json

Copy

```
{
    "_id": "string",
    "created_at": "string",
    "driver1_id": "string",
    "driver2_id": "string",
```

```
    "user_id": "string",
    "winner_id": "string"
}
```

# MCP

## Mcp Discovery

Basic discovery endpoint for humans and health checks.

### Responses

> **200** Successful Response

GET /mcp

**Response samples**

200

**Content type**
application/json

Copy

```
{ }
```

# Mcp Rpc

Handle MCP JSON-RPC messages.

Supported methods:

- **initialize** — handshake, returns server info & capabilities
- **tools/list** — discover available tools
- **tools/call** — execute a tool

REQUEST BODY SCHEMA: application/json

| | |
|---|---|
| `jsonrpc` | string (Jsonrpc)<br>Default: `"2.0"`<br>Must be '2.0'. |
| `id` > | Id (integer) or Id (string) or Id (null) (Id)<br>Request identifier. |
| `method`<br>required | string (Method)<br>MCP method: initialize, tools/list, or tools/call. |
| `params` | object (Params)<br>Method parameters. For tools/call send {"name": "", "arguments": {...}}. |

## Responses

> **200** Successful Response

> **422** Validation Error

POST /mcp

### Request samples

Payload

**Content type**
application/json

Copy Expand all Collapse all

```
{
    "jsonrpc": "2.0",
    "id": 1,
    "method": "initialize",
    "params": { }
}
```

### Response samples

200 422

**Content type**
application/json

Copy

```
{ }
```

# Health

## Root

Health check endpoint.

### Responses

> **200** Successful Response

GET /

## Response samples

200

Content type
application/json

Copy

```
null
```