

ITU Computer Engineering Department BLG 223E Data Structures, Fall 2021 Recitation #6

Problem Definition

You have an orders.txt file whose name will be given as a **command line argument** in this homework. Each row indicates an order in this text file. There are 4 columns which are separated by one space. For each order, the first column indicates the product, the second column indicates the product price, the third column indicates the product quantity and the fourth column indicates the order day. In this recitation, mainly you calculate each production revenue from orders. 5 products with the highest revenue will be displayed on the screen for total and each day. Revenue is calculated for each order as below:

 $revenue = product \ price \times quantity$

```
orders.txt
     Product Product Price Quantity Day
     egg 1.4 4 Saturday
  3
     chips 0.8 2 Tuesday
  4
     egg 1.4 2 Thursday
  5
      tomato 1.1 3 Sunday
     chips 0.8 4 Saturday
     biscuit 0.7 3 Tuesday
     cake 0.6 3 Thursday
  9
     chips 0.8 1 Monday
 10
     milk 1.2 3 Monday
 11
     cornflakes 1.5 1 Wednesday
 12
     bread 1.0 3 Friday
 13
     bread 1.0 4 Sunday
     bread 1.0 3 Monday
 14
 15
     biscuit 0.7 l Tuesday
     cake 0.6 1 Friday
```

Figure 1: 'orders.txt' file.

Revenue for the first order in 'orders.txt' file is calculated as below:

```
#1 \ order \ revenue = 1.4 \times 4 = 5.6
```

fstream library can be used in order to read from orders.txt file. You can create a map value which holds the total revenue for each product. So, its key and value types should be <string,double>. When you read file row by row and column by column from orders.txt file, you can calculate total revenue for each product using this map value. Afterwards, Multimap, map iterator and multimap reverse_iterator can be used to sort the total products revenue.

Similarly, you can also calculate the total revenue of products for each day. You should only fill listProducts and listDay functions in the code file. There is a sample scenario below.

Example

```
Choose an operation
L: List 5 products with the highest revenue for total
D: List 5 products with the highest revenue for each day
E: Exit
Enter a choice {L, D, E}:
```

Figure 2: Terminal screen when the program is run.




Figure 3: When you select 'L', the output of the program.

BLG 223E Data Structures

```
PROBLEMS
                     TERMINIAL
                                PORTS
                                        DEBUG CONSOLE
Choose an operation
L: List 5 products with the highest revenue for total
D: List 5 products with the highest revenue for each day
E: Exit
Enter a choice {L, D, E}: D
5 products with the highest revenue for Monday are:
egg 53.20
milk 39.60
oil 36.00
bread 32.00
fish 31.20
5 products with the highest revenue for Sunday are:
cornflakes 39.00
oil 37.50
meat 35.00
egg 32.20
tomato 31.90
5 products with the highest revenue for Tuesday are:
meat 45.50
bread 43.00
oil 36.00
cornflakes 36.00
tomato 33.00
5 products with the highest revenue for Wednesday are:
cornflakes 36.00
oil 33.00
milk 31.20
egg 29.40
meat 24.50
5 products with the highest revenue for Thursday are:
meat 50.75
fish 40.30
tomato 36.30
milk 28.80
oil 27.00
5 products with the highest revenue for Friday are:
milk 46.80
meat 36.75
egg 32.20
tomato 25.30
fish 23.40
5 products with the highest revenue for Saturday are:
egg 47.60
meat 45.50
tomato 36.30
cornflakes 36.00
fish 28.60
Choose an operation
L: List 5 products with the highest revenue for total
D: List 5 products with the highest revenue for each day
E: Exit
Enter a choice {L, D, E}: []
```

Figure 4: When you select 'D', the output of the program.

Note: You can use 'setprecision' function from 'iomanip' for two decimal precision display. You can find the explanations about 'setprecision' function at the link below.

Link: https://www.cplusplus.com/reference/iomanip/setprecision/

BLG 223E Data Structures Recitation #6

Note: To get the file path(name) from the command line argument, the args parameter of the launch.json file should be changed as in the figure below.

Figure 5: The args parameter of the launch.json file.

Submission Rules

• Make sure you write your name and number in all of the files of your project, in the following format:

```
/* @Author
Student Name: <student_name>
Student ID : <student_id>
Date: <date> */
```

- Use comments wherever necessary in your code to explain what you did.
- Your program will be checked by using Calico(https://bitbucket.org/uyar/calico) automatic checker.
- Do not share any code or text that can be submitted as a part of an assignment (discussing ideas is okay).
- Only electronic submissions through Ninova will be accepted no later than deadline.
- You may discuss the problems at an abstract level with your classmates, but you should not share
 or copy code from your classmates or from the Internet. You should submit your own, individual
 homework.
- Academic dishonesty, including cheating, plagiarism, and direct copying, is unacceptable.
- A different input file will be used for evaluating the homework.
- If you have any question about the recitation, you cand send e-mail to Yunus Emre Cebeci(cebeci16@itu.edu.tr).
- Note that YOUR CODES WILL BE CHECKED WITH THE PLAGIARISM TOOLS!



This work is licensed under a Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International License.