# Wayfare Travel Planning API Documentation

Base URL: https://api.wayfare.com **Authentication:** Bearer Token (JWT) Content-Type: application/json

# - Privacy System Implementation\*\*

\*\* IMPORTANT\*\*: The backend has been updated with a comprehensive privacy system that affects route creation and retrieval. Please update your code accordingly.

## \*\* Migration Required:\*\*

1. Route Creation Changes:

```
// OLD - No privacy control
const route = {
 title: "My Trip",
 city: "Paris",
 start_date: "2025-06-01",
  end date: "2025-06-07"
}
// NEW - Privacy control added
const route = {
 title: "My Trip",
 city: "Paris",
 start_date: "2025-06-01",
 end_date: "2025-06-07",
  is_public: false // NEW FIELD - Routes are PRIVATE by default
2. Response Schema Changes: // All route responses now include: {
"route_id": "...", "title": "...", // ... other fields ... "is_public": true, // NEW
```

FIELD in all route responses "stats": { ... } }

```
#### **3. Public Route Access Changes:**
// BEHAVIOR CHANGE: These endpoints now only return PUBLIC routes
GET /routes/public
                      // Only shows is_public: true routes
GET /routes/search
                      // Only searches is_public: true routes
// UNCHANGED: User routes still return all routes (public + private)
GET /routes/user
                      // Shows all user's routes regardless of privacy
```

```
** New Endpoints:**
// Toggle route privacy PATCH /routes/{route id}/privacy?is public=true
// Make public PATCH /routes/{route_id}/privacy?is_public=false // Make
private
// Advanced public route search GET /routes/search?q=Rome&city=Paris&sort_by=popularity
### ** Required Code Updates:**
1. **Update route creation forms** to include optional `is_public` checkbox
2. **Handle `is_public` field** in all route response parsers
3. **Update route listing UI** to show privacy status (lock icon for private routes)
4. **Add privacy toggle buttons** in route management interfaces
5. **Test public route discovery** to ensure only public routes appear
### ** Database Impact:**
- **All existing routes** automatically set to `is_public: false` (private)
- **No data loss** - all routes preserved with privacy protection
- **Database migration** completed automatically
## **Configuration**
### **Email Configuration**
- **Location:** `backend/config/email.py`
- **Development Mode: ** Email sending suppressed, codes printed to console
- **Production Options:** Gmail (App Password), Mailtrap, Outlook
- **Verification Codes:** 6-digit, 10-minute expiry, in-memory storage
To switch email providers:
1. Edit `backend/config/email.py`
2. Change `mail_config = your_chosen_config`
3. Update credentials and restart server
## **User Management Endpoints**
### **@POST /user/register**
It allows users to:
- Create a new user account
- Register with username, email, and personal information
```

- Automatically hash passwords and set default preferences

```
**Request Body:**
```json
{
    "username": "traveler123",
    "password": "securepass123",
    "email": "user@example.com",
    "first_name": "John",
    "last_name": "Doe"
}

Response:
{
    "message": "User registered successfully",
    "success": true,
    "user_id": "64a1b2c3d4e5f6789abcdef0"
}
```

## @POST /user/login

It allows users to: - Authenticate with username and password - Receive access token for API authorization - Maintain secure session management

## Request Body:

```
{
    "username": "traveler123",
    "password": "securepass123"
}

Response:
{
    "message": "User logged in successfully",
    "success": true,
    "access_token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9..."
}
```

## @POST /user/addInfo

### Requires Authentication

It allows users to: - Add travel preferences and interests - Set budget and travel style preferences - Define home city for personalized recommendations

```
{
    "preferences": {
        "interests": ["museums", "architecture", "food"],
        "budget": "medium",
        "travel_style": "moderate"
    },
        "home_city": "New York"
}

Response:
{
    "message": "User information updated successfully",
    "success": true,
    "status_code": 200
}
```

## @GET /user/getCurrentUser

### Requires Authentication

It allows users to: - Retrieve current user profile information - Access personal preferences and settings - View account details and travel preferences

### Response:

```
{
    "user_id": "64a1b2c3d4e5f6789abcdef0",
    "email": "user@example.com",
    "username": "traveler123",
    "name": "John",
    "surname": "Doe",
    "preferences": {
        "interests": ["museums", "architecture", "food"],
        "budget": "medium",
        "travel_style": "moderate"
    },
    "home_city": "New York"
}
```

## @POST /user/changePassword

## Requires Authentication

It allows users to: - Update account password securely - Verify current password before change - Ensure password confirmation matches

# Request Body:

```
{
    "current_password": "oldpassword123",
    "new_password": "newpassword456",
    "confirm_password": "newpassword456"
}
Response:
{
    "message": "Password changed successfully",
    "success": true,
    "status_code": 200
}
```

## @DELETE /user/delete

### Requires Authentication

It allows users to: - Permanently delete their account - Remove all associated data and routes - Verify identity with password confirmation

## Request Body:

```
{
    "password": "userpassword123"
}

Response:
{
    "message": "User account deleted successfully",
    "success": true,
    "status_code": 200
}
```

## @POST /user/sendVerification

It allows users to: - Send verification code to email address - Start email verification process during registration - Receive 6-digit verification code valid for 10 minutes

```
{
    "email": "user@example.com"
}
```

```
Response:
{
    "success": true,
    "message": "Code sent successfully",
    "status_code": 200
}
```

## @POST /user/sendVerification/verifyCode

It allows users to: - Verify email verification code - Complete email verification process - Validate 6-digit code within 10-minute expiry

## Request Body:

```
{
    "verification_code": "123456"
}
Response:
{
    "success": true,
    "message": "Code verified successfully",
    "status_code": 200
Error Responses:
// Invalid code
{
    "detail": "Invalid verification code"
}
// Expired code (after 10 minutes)
    "detail": "Verification code has expired"
}
```

## Route Management Endpoints

@POST /route/create

## Requires Authentication

It allows users to: - Create a customized daily schedule of activities (linked to places) - Specify must-visit places with notes and preferences - Generate

AI-powered route recommendations based on travel style - Automatically store place images in activities during creation for optimal retrieval performance

### Request Body:

```
{
    "title": "Trip to Rome",
    "city": "Rome",
    "start_date": "2025-06-01",
    "end date": "2025-06-07",
    "category": "city_break",
    "season": "summer",
    "is_public": false,
    "must_visit": [
        {
            "place_id": "abc123",
            "place name": "Colosseum",
            "address": "Rome",
            "notes": "Morning preferred",
            "source": "google",
            "coordinates": { "lat": 41.89, "lng": 12.49 }
        },
            "place_name": "Hidden Bookstore",
            "notes": "TikTok place",
            "source": "user"
        }
    ],
    "days": [
        {
            "date": "2025-06-01",
            "activities": [
                {
                    "place id": "abc123",
                    "place_name": "Colosseum",
                    "time": "10:00",
                    "notes": "Visit the Colosseum"
                }
            ]
        }
    ]
```

Request Body Parameters: - title (string, required): Route title/name - city (string, required): Destination city name - start\_date (string, required): Trip start date in YYYY-MM-DD format - end\_date (string, required): Trip end date in YYYY-MM-DD format - category (string, optional): Route cate-

gory (default: "city\_break") - season (string, optional): Travel season (auto-detected if not provided) - is\_public (boolean, optional): Route visibility - false = private (default), true = public - must\_visit (array, required): List of must-visit places with details

Privacy Control: - Private Routes (is\_public: false): Only visible to the creator via /routes/user - Public Routes (is\_public: true): Visible to all users via /routes/public and /routes/search - Default: All routes are private unless explicitly set to public

## Response:

```
{
    "message": "Route created successfully",
    "success": true,
    "route_id": "string",
    "status_code": 200
}
```

### @GET /routes/user

## Requires Authentication

It allows users to: - Retrieve all routes created by the authenticated user - View route summaries and basic information - Access personal travel planning history - Get stored place images for each activity in the daily itinerary (images are stored during route creation for optimal performance)

```
{
    "success": true,
    "message": "User routes retrieved successfully",
    "status_code": 200,
    "data": [
        {
            "route id": "64a1b2c3d4e5f6789abcdef1",
            "user id": "64a1b2c3d4e5f6789abcdef0",
            "title": "Trip to Rome",
            "city": "Rome",
            "country": "Italy",
            "start_date": "2025-06-01",
            "end_date": "2025-06-07",
            "budget": "medium",
            "travel_style": "moderate",
            "category": "city_break",
            "season": "summer",
```

## @GET /routes/{route\_id}

### Requires Authentication

It allows users to: - Retrieve detailed information for a specific route - Access complete daily schedules and activities - View all must-visit places and their details

Path Parameters: - route\_id (string): Unique identifier of the route

# Response:

{

```
"success": true,
"message": "Route retrieved successfully",
"status_code": 200,
"data": {
    "route_id": "64a1b2c3d4e5f6789abcdef1",
    "user_id": "64a1b2c3d4e5f6789abcdef0",
    "title": "Trip to Rome",
    "city": "Rome",
    "country": "Italy",
    "start_date": "2025-06-01",
    "end_date": "2025-06-07",
    "budget": "medium",
    "travel_style": "moderate",
    "category": "city_break",
    "season": "summer",
    "is_public": false,
    "stats": {
        "views_count": 5,
        "copies_count": 2,
        "likes_count": 8
    "must_visit": [
```

```
"place_id": "abc123",
                "place_name": "Colosseum",
                "address": "Rome",
                "coordinates": { "lat": 41.89, "lng": 12.49 },
                "notes": "Morning preferred",
                "source": "google",
                "image": "https://dynamic-media-cdn.tripadvisor.com/media/photo-o/15/f0/6b/
                "opening_hours": {
                    "monday": "08:30-19:15",
                    "tuesday": "08:30-19:15"
                }
            }
        ],
        "days": [
            {
                "date": "2025-06-01",
                "activities": [
                    {
                         "place_id": "abc123",
                         "place_name": "Colosseum",
                         "time": "10:00",
                         "notes": "Visit the Colosseum",
                         "image": "https://dynamic-media-cdn.tripadvisor.com/media/photo-o/19
                    }
                ]
            }
        ],
        "created_at": "2024-12-01T10:00:00Z",
        "updated_at": "2024-12-01T10:00:00Z"
    }
}
```

## @PUT /routes/{route\_id}

## Requires Authentication

It allows users to: - Update existing route information - Modify travel dates, destinations, or preferences - Add or remove must-visit places and activities

Path Parameters: - route\_id (string): Unique identifier of the route

```
Request Body:
```

```
{
    "title": "Updated Trip to Rome",
```

```
"city": "Rome",
    "start_date": "2025-06-15",
    "end_date": "2025-06-20",
    "category": "cultural",
    "season": "summer",
    "must_visit": [
        {
            "place_name": "Vatican Museums",
            "notes": "Book tickets in advance",
            "source": "user"
        }
    ]
}
Response:
    "message": "Route updated successfully",
    "success": true,
    "status_code": 200
}
```

## @DELETE /routes/{route\_id}

## Requires Authentication

It allows users to: - Permanently delete a specific route - Remove all associated activities and schedules - Clean up travel planning history

Path Parameters: - route\_id (string): Unique identifier of the route

## Response:

```
{
    "message": "Route deleted successfully",
    "success": true,
    "status_code": 200
}
```

## @PATCH /routes/{route\_id}/privacy

### Requires Authentication Owner Only

It allows users to: - Toggle route privacy settings between public and private - Control route visibility and discoverability - Manage sharing preferences for travel plans - Update privacy settings in real-time

```
Path Parameters: - route_id (string): Unique identifier of the route
Query Parameters: - is_public (boolean, required): true = make public,
false = make private
Request Examples:
PATCH /routes/64a1b2c3d4e5f6789abcdef1/privacy?is_public=true
  # Make public
PATCH /routes/64a1b2c3d4e5f6789abcdef1/privacy?is_public=false # Make private
Response:
{
    "success": true,
    "message": "Route privacy updated to public",
    "status_code": 200
}
Error Responses:
// User doesn't own the route
{
    "success": false,
    "message": "Unauthorized: You can only modify your own routes",
    "status_code": 403
}
// Route not found
{
    "success": false,
```

Privacy Effects: - Making Public: Route becomes discoverable via /routes/public and /routes/search - Making Private: Route removed from public listings, only accessible to owner - Ownership: Users can only change privacy of their own routes

### @GET /routes/public

### Requires Authentication

"message": "Route not found",

"status\_code": 404

}

It allows users to: - Browse **only public routes** shared by other users (excludes private routes) - Filter public routes by category, season, and budget - Discover travel inspiration and ideas from the community - Access routes with <code>is\_public: true</code> setting only

Query Parameters: - category (string, optional): Filter by route category - season (string, optional): Filter by travel season - budget (string, optional): Filter by budget level - limit (int): Maximum number of routes to return (default: 10)

## Response:

```
{
    "success": true,
    "message": "Public routes retrieved successfully",
    "status code": 200,
    "data": [
        {
            "route_id": "64a1b2c3d4e5f6789abcdef2",
            "user id": "64a1b2c3d4e5f6789abcdef9",
            "title": "Rome in 5 Days",
            "city": "Rome",
            "country": "Italy",
            "category": "city_break",
            "season": "spring",
            "budget": "medium",
            "stats": {
                 "views_count": 156,
                 "copies_count": 23,
                 "likes_count": 89
            }
        }
    ]
}
```

### @GET /routes/search

### **Requires Authentication**

It allows users to: - **Search only public routes** with advanced filtering options - Find routes by title/name, city, or country - Filter by category, season, budget, and travel style - Sort results by popularity, rating, recent, or alphabetically - Discover travel content through flexible search queries

Query Parameters: - q (string, optional): Search query for route title (minimum 2 characters) - city (string, optional): Filter by exact city name - country (string, optional): Filter by exact country name - category (string, optional): Filter by route category - season (string, optional): Filter by travel season - budget (string, optional): Filter by budget level - travel\_style (string, optional): Filter by travel style - limit (int, optional): Maximum results (default: 20, max: 50) - sort\_by (string, optional): Sort order - "popularity" (default),

```
"rating", "recent", "title"
Request Examples:
  # Search by title
GET /routes/search?q=Rome&limit=10
GET /routes/search?city=Paris&sort_by=popularity
  # Search by city
GET /routes/search?country=Italy&budget=medium
  # Search by country + budget
GET /routes/search?q=cultural&city=Rome&travel_style=relaxed # Combined search
Response:
{
    "success": true,
    "message": "Found 3 public routes for: title containing 'Rome', budget 'medium'",
    "status_code": 200,
    "data": [
        {
            "route id": "64a1b2c3d4e5f6789abcdef2",
            "user_id": "64a1b2c3d4e5f6789abcdef9",
            "title": "Rome in 5 Days",
            "city": "Rome",
            "country": "Italy",
            "category": "city_break",
            "season": "spring",
            "budget": "medium",
            "is_public": true,
            "stats": {
                "views count": 156,
                "copies_count": 23,
                "likes_count": 89
            }
        }
    ]
}
** Search Features: - Public Routes Only: Searches only routes with
is_public: true - Smart Messages: Response message shows what fil-
ters were applied - Flexible Sorting: Multiple sort options for different
discovery needs - Exact Matching: City and country filters use exact
```

## Places Management Endpoints

@GET /places/city

Requires Authentication

matches - Text Search\*\*: Route title search supports partial matching

It allows users to: - Retrieve all available places in a specific city - Access place details including coordinates and categories - Browse destinations for route planning

Query Parameters: - city (string): Name of the city to search places in

## Response:

```
{
    "success": true,
    "message": "Places retrieved successfully",
    "status code": 200,
    "data": [
        {
            "place_id": "abc123",
            "name": "Colosseum",
            "address": "Piazza del Colosseo, 1, 00184 Roma RM, Italy",
            "coordinates": { "lat": 41.8902, "lng": 12.4922 },
            "category": "historical_site",
            "rating": 4.5,
            "price_level": 3,
            "opening_hours": {
                "monday": "08:30-19:15",
                "tuesday": "08:30-19:15"
            }
        }
    ]
}
```

## @POST /places/id

### Requires Authentication

It allows users to: - Retrieve detailed information for specific places by their  ${\it IDs}$  - Get multiple place details in a single request - Access comprehensive place data for route planning

```
{
    "place_ids": ["abc123", "def456", "ghi789"]
}
Response:
{
    "success": true,
    "message": "Places retrieved successfully",
```

```
"status_code": 200,
    "data": [
        {
            "place_id": "abc123",
            "name": "Colosseum",
            "address": "Piazza del Colosseo, 1, 00184 Roma RM, Italy",
            "coordinates": { "lat": 41.8902, "lng": 12.4922 },
            "category": "historical_site",
            "rating": 4.5,
            "price_level": 3,
            "opening_hours": {
                "monday": "08:30-19:15",
                "tuesday": "08:30-19:15"
            }
        }
    ]
}
```

## @POST /places/search

## Requires Authentication

It allows users to: - Search for places using text queries - Filter results by city, category, and other criteria - Find specific attractions and points of interest

```
{
    "query": "museum",
    "city": "Rome",
    "category": "cultural",
    "limit": 20
}
Response:
{
    "success": true,
    "message": "Search results retrieved successfully",
    "status_code": 200,
    "data": [
        {
            "place_id": "mus123",
            "name": "Vatican Museums",
            "address": "00120 Vatican City",
            "coordinates": { "lat": 41.9065, "lng": 12.4536 },
            "category": "museum",
```

### @GET /places/search-must-visit

## Requires Authentication

It allows users to: - Search and discover places for must-visit selection in route creation - Browse places by category with autocomplete functionality - Get comprehensive place information including ratings, images, and coordinates - Reduce typos and improve place selection accuracy in the UI

Query Parameters: - city (string, required): Name of the city to search places in - query (string, optional): Search term for place names (autocomplete) - category (string, optional): Filter by wayfare\_category (Cultural Sites, Entertainment, etc.) - limit (integer, optional): Maximum number of results (default: 20, max: 50)

## **Example Request:**

GET /places/search-must-visit?city=Rome&query=colos&category=Cultural%20Sites&limit=10

```
{
    "success": true,
    "message": "Found 1 places in Rome matching 'colos' for category 'Cultural Sites'",
    "status_code": 200,
    "data": [
        {
            "place_id": "ChIJrRMgU7ZhLxMR...",
            "name": "Colosseum",
            "category": "historical_site",
            "wayfare category": "museum",
            "rating": 4.7,
            "image": "https://example.com/colosseum.jpg",
            "coordinates": {
                "lat": 41.8902,
                "lng": 12.4922
            },
            "address": "Piazza del Colosseo, 1, Roma RM, Italy"
        }
    ]
}
```

Usage in UI: - Autocomplete: Call with query parameter as user types - Browse: Call with city only to show popular places - Filter: Use category to filter by place types - Selection: Use returned place\_id and name directly in route creation

Integration with Route Creation: The response data can be directly used in the /route/create endpoint's must\_visit array:

```
{
    "place_id": "ChIJrRMgU7ZhLxMR...",
    "place_name": "Colosseum",
    "source": "database",
    "notes": "Morning visit preferred"
}
```

## @POST /places/autocomplete

### Requires Authentication

It allows users to: - Get autocomplete suggestions for place names - Provide real-time search assistance - Improve user experience during place selection

```
{
    "query": "colo",
    "city": "Rome",
    "limit": 5
}
Response:
{
    "success": true,
    "message": "Autocomplete results retrieved successfully",
    "status_code": 200,
    "data": [
        {
            "place_id": "abc123",
            "name": "Colosseum",
            "category": "historical_site"
        },
            "place_id": "abc124",
            "name": "Colonna di Traiano",
            "category": "monument"
        }
```

```
}
```

]

## @GET /places/top-rated

## Requires Authentication

It allows users to: - Retrieve the top 5 rated places based on aggregated user feedback - Get places with calculated average ratings from multiple feedback entries - Access complete place details including original ratings and feedback statistics - View places sorted by average feedback rating (highest first) and alphabetically by name

```
{
    "success": true,
    "message": "Top rated places retrieved successfully",
    "status code": 200,
    "data": [
        {
            "place_id": "abc123",
            "name": "Vatican Museums",
            "city": "Rome",
            "category": "museum",
            "wayfare_category": "cultural",
            "price": "€17",
            "rating": 4.5,
            "wayfare_rating": 4.8,
            "total feedback count": 15,
            "image": "https://example.com/vatican.jpg",
            "detail_url": "https://example.com/vatican-museums",
            "opening_hours": {
                "monday": "09:00-18:00",
                "tuesday": "09:00-18:00"
            },
            "coordinates": {
                "lat": 41.9065,
                "lng": 12.4536
            },
            "address": "Viale Vaticano, 00165 Roma RM, Italy",
            "source": "wayfare",
            "country": "Italy",
            "country_id": "IT",
            "city_id": "rome_001",
            "popularity": 1.2,
```

```
"duration": 240,
            "created_at": "2024-01-15T10:30:00Z",
            "updated at": "2024-01-15T10:30:00Z"
        },
            "place_id": "def456",
            "name": "Colosseum",
            "city": "Rome",
            "category": "historical site",
            "wayfare_category": "historical",
            "price": "€16",
            "rating": 4.3,
            "wayfare_rating": 4.7,
            "total feedback count": 12,
            "image": "https://example.com/colosseum.jpg",
            "detail url": "https://example.com/colosseum",
            "opening_hours": {
                "monday": "08:30-19:15",
                "tuesday": "08:30-19:15"
            },
            "coordinates": {
                "lat": 41.8902,
                "lng": 12.4922
            },
            "address": "Piazza del Colosseo, 1, 00184 Roma RM, Italy",
            "source": "wayfare",
            "country": "Italy",
            "country_id": "IT",
            "city_id": "rome_001",
            "popularity": 1.5,
            "duration": 180,
            "created at": "2024-01-15T10:30:00Z",
            "updated at": "2024-01-15T10:30:00Z"
        }
    ]
}
```

Response Fields: - place\_id: Unique identifier for the place - name: Name of the place - city: City where the place is located - category: Primary category of the place - wayfare\_category: Wayfare-specific category classification - price: Price information for visiting the place - rating: Original place rating from the database - wayfare\_rating: Calculated average rating from user feedback (rounded to 2 decimal places) - total\_feedback\_count: Number of feedback entries for this place - image: URL to place image - detail\_url: URL to detailed information about the place - opening\_hours: Opening hours for each day of the week - coordinates: Geographical coordinates (latitude and

longitude) - address: Full address of the place - source: Source of the place data - country: Country where the place is located - country\_id: Country identifier - city\_id: City identifier - popularity: Popularity score (lower numbers indicate higher popularity) - duration: Recommended visit duration in minutes - created\_at: Timestamp when the place was added to the database - updated\_at: Timestamp when the place was last updated

**Sorting Logic:** - Primary sort: Wayfare rating (highest first) - Secondary sort: Place name (alphabetical order) in case of rating ties

## Cities Management Endpoints

@GET /cities/search

### Requires Authentication

It allows users to: - Search for cities by name with real-time autocomplete functionality - Get city suggestions as users type in the destination field - Retrieve city details including coordinates for UI integration - Ensure only valid cities can be selected for route creation

Query Parameters: - q (required): Search query string (minimum 2 characters) - limit (optional): Maximum number of results to return (default: 10, max: 20)

## Request Examples:

```
GET /cities/search?q=Ro&limit=5
GET /cities/search?q=Rome
GET /cities/search?q=Par&limit=3
Response:
{
    "success": true,
    "message": "Found 2 cities matching 'Ro'",
    "status_code": 200,
    "data": [
        {
            "city_id": "68824f500658a953e0de8233",
            "name": "Rome",
            "country": "Italy",
            "country_id": "IT",
            "display text": "Rome, Italy",
            "coordinates": {
                "lat": 41.9028,
                "lng": 12.4964
            }
```

```
},
{
    "city_id": "68824f506d75e9efdf51f44c",
    "name": "Rotterdam",
    "country": "Netherlands",
    "country_id": "NL",
    "display_text": "Rotterdam, Netherlands",
    "coordinates": {
        "lat": 51.9244424,
        "lng": 4.47775
    }
}
}
```

Response Fields: - city\_id: Unique identifier for the city - name: City name (use this for route creation) - country: Country where the city is located - country\_id: ISO country code - display\_text: Formatted text for UI display (e.g., "Rome, Italy") - coordinates: Geographical coordinates (latitude and longitude)

**Usage in UI:** 1. User types in search box  $\rightarrow$  Call this endpoint when query 2 characters 2. Display display\_text in dropdown options 3. When user selects a city  $\rightarrow$  Use name field for route creation 4. Store full city object for reference and validation

**Error Responses:** - 401: Invalid or missing authentication token - 400: Query parameter missing or too short - 500: Server error during search

### @GET /cities/all

#### Requires Authentication

It allows users to: - Retrieve a complete list of all available cities - Access city information including country, coordinates, timezone, and status - Browse destinations for travel planning with geographical data

```
"country": "Italy",
            "country_id": "IT",
            "active": true,
            "coordinates": {
                "lat": 41.9028,
                "lng": 12.4964
            },
            "timezone": "Europe/Rome",
            "created_at": "2025-07-30T15:34:43.551000",
            "updated_at": "2025-07-30T15:34:43.551000"
        },
            "city_id": "68824f50960d81e2439af257",
            "name": "Paris",
            "country": "France",
            "country_id": "FR",
            "active": true,
            "coordinates": {
                "lat": 48.8566,
                "lng": 2.3522
            },
            "timezone": "Europe/Paris",
            "created_at": "2025-07-30T15:34:43.551000",
            "updated_at": "2025-07-30T15:34:43.551000"
        }
   ]
}
```

# @POST /cities/specific

### Requires Authentication

It allows users to: - Retrieve cities within a specific country - Filter destinations by country preference with complete geographical data - Narrow down location options for trip planning with coordinates and timezone info

```
{
    "country": "Italy"
}

Response:
{
    "success": true,
    "message": "Cities in Italy retrieved successfully",
```

```
"status_code": 200,
    "data": [
        {
            "city_id": "68824f500e3bd95431ee840c",
            "name": "Rome",
            "country": "Italy",
            "country_id": "IT",
            "active": true,
            "coordinates": {
                "lat": 41.9028,
                "lng": 12.4964
            },
            "timezone": "Europe/Rome",
            "created at": "2025-07-30T15:34:43.551000",
            "updated_at": "2025-07-30T15:34:43.551000"
        },
            "city_id": "68824f50b1c9d54783ee842f",
            "name": "Milan",
            "country": "Italy",
            "country_id": "IT",
            "active": true,
            "coordinates": {
                "lat": 45.4642,
                "lng": 9.1900
            },
            "timezone": "Europe/Rome",
            "created at": "2025-07-30T15:34:43.551000",
            "updated_at": "2025-07-30T15:34:43.551000"
        }
    ]
}
```

# **Countries Management Endpoints**

## @GET /countries/all

### Requires Authentication

It allows users to: - Retrieve a complete list of all available countries - Access country information with creation/update timestamps - Browse destinations by country for travel planning

### Response:

{

```
"success": true,
    "message": "Countries fetched successfully",
    "status_code": 200,
    "data": [
        {
            "name": "Italy",
            "country_id": "IT",
            "region": "Europe",
            "active": true,
            "created_at": "2025-07-30T16:06:03.201000",
            "updated_at": "2025-07-30T16:06:03.201000"
        },
        {
            "name": "France",
            "country_id": "FR",
            "region": "Europe",
            "active": true,
            "created_at": "2025-07-30T16:06:03.201000",
            "updated_at": "2025-07-30T16:06:03.201000"
        }
   ]
}
```

## @POST /countries/region

## Requires Authentication

It allows users to: - Retrieve countries within a specific geographical region - Filter destinations by regional preferences - Explore travel options by geographical area

```
"region": "Southern Europe"
},
{
    "_id": "country126",
    "name": "Spain",
    "region": "Southern Europe"
}
]
```

# @POST /countries/search

### Requires Authentication

It allows users to: - Search for countries using text queries - Find specific destinations quickly - Filter countries by name or other criteria

### Request Body:

```
{
    "query": "ital",
    "limit": 10
}
Response:
{
    "success": true,
    "message": "Search results retrieved successfully",
    "status_code": 200,
    "data": [
        {
            "_id": "country123",
            "name": "Italy",
            "region": "Southern Europe"
        }
    ]
}
```

## @GET /countries/allRegions

## Requires Authentication

It allows users to: - Retrieve a complete list of all geographical regions - Access regional classification for countries - Browse destinations by geographical regions

```
{
    "success": true,
    "message": "Regions retrieved successfully",
    "status_code": 200,
    "data": [
        "Northern Europe",
        "Southern Europe",
        "Western Europe",
        "Eastern Europe",
        "North America",
        "South America",
        "Asia",
        "Africa",
        "Oceania"
    ]
}
```

## Authentication & Error Handling

### Authentication

- All endpoints marked with require a valid JWT token
- Include token in the Authorization header: Bearer <your\_jwt\_token>
- $\bullet\,$  Tokens expire after 30 minutes and need to be refreshed

### Common Error Responses

```
401 Unauthorized:
{
    "detail": "Could not validate credentials",
    "success": false,
    "status_code": 401
}
400 Bad Request:
{
    "detail": "Invalid input data",
    "success": false,
    "status_code": 400
}
404 Not Found:
{
    "detail": "Resource not found",
```

```
"success": false,
    "status_code": 404
}
500 Internal Server Error:
{
    "detail": "Internal server error",
    "success": false,
    "status_code": 500
}
```

## **API** Usage Guidelines

### Rate Limiting

- 1000 requests per hour per authenticated user
- 100 requests per hour for unauthenticated endpoints

#### **Data Formats**

- $\bullet\,$  All dates should be in YYYY-MM-DD format
- Coordinates use decimal degrees (latitude, longitude)
- Times are in 24-hour format HH:MM

## Travel Styles

- relaxed: Slower pace, longer visits, more downtime
- moderate: Balanced schedule with reasonable activities
- accelerated: Fast-paced, maximum activities per day

### **Budget Levels**

- low: Budget-conscious options
- medium: Balanced cost options
- high: Premium experiences

## Categories

- city\_break: Urban exploration and cultural sites
- beach: Coastal and water-based activities
- mountain: Outdoor and adventure activities
- road\_trip: Multi-destination driving routes

## Feedback Management Endpoints

## @POST /feedback/place

It allows users to: - Submit feedback and ratings for places they've visited - Add comments about their experience - Provide visit date information - Prevent duplicate feedback for the same place

## Request Body:

```
{
    "place_id": "ChIJyWEHuEmuEmsRm9hTkapTCrk",
    "rating": 5,
    "comment": "Amazing place! The view was breathtaking and the staff was very friendly.",
    "visited_on": "2024-12-01"
}

Response:
{
    "success": true,
    "message": "Place feedback submitted successfully",
    "status_code": 201,
    "feedback_id": "64f8a1b2c3d4e5f6789abc01",
    "created_at": "2024-12-01T10:30:00Z"
}
```

## @GET /feedback/place/{place\_id}

It allows users to: - Retrieve all feedback for a specific place - View ratings and comments from other users - Access feedback history and statistics

```
}
]
```

## @GET /feedback/place/{place\_id}/user/{user\_id}

It allows users to: - Retrieve specific user's feedback for a place - Check if a user has already provided feedback - Access user-specific feedback details

## Response:

```
{
    "success": true,
    "message": "User feedback retrieved successfully",
    "status_code": 200,
    "data": [
        {
            "feedback id": "64f8a1b2c3d4e5f6789abc01",
            "user_id": "64a1b2c3d4e5f6789abcdef0",
            "place_id": "ChIJyWEHuEmuEmsRm9hTkapTCrk",
            "rating": 5,
            "comment": "Amazing place!",
            "visited_on": "2024-12-01",
            "created at": "2024-12-01T10:30:00Z",
            "updated_at": "2024-12-01T10:30:00Z"
        }
    ]
}
```

## @PUT /feedback/place/{feedback\_id}

It allows users to: - Update their existing place feedback - Modify rating, comment, or visit date - Maintain feedback history with updated timestamps

```
{
    "rating": 4,
    "comment": "Updated review - still great but had some issues.",
    "visited_on": "2024-12-02"
}
Response:
{
    "success": true,
```

```
"message": "Place feedback updated successfully",
    "status_code": 200,
    "updated_at": "2024-12-01T11:45:00Z"
}
```

## @DELETE /feedback/place/{feedback\_id}

It allows users to: - Delete their own place feedback - Remove feedback from the system - Maintain data integrity with proper authorization checks

## Response:

```
{
    "success": true,
    "message": "Place feedback deleted successfully",
    "status_code": 200,
    "deleted_at": "2024-12-01T12:00:00Z"
}
```

## @GET /feedback/place/{place\_id}/stats

It allows users to: - Get aggregated statistics for place feedback - View average ratings and rating distribution - Access comprehensive feedback analytics

```
{
    "success": true,
    "message": "Place feedback statistics retrieved successfully",
    "status_code": 200,
    "data": {
        "total_feedback": 120,
        "average_rating": 4.2,
        "rating_distribution": {
            "1": 5,
            "2": 10,
            "3": 25,
            "4": 35,
            "5": 45
        }
    }
}
```

## $@POST\ /feedback/route$

It allows users to: - Submit feedback and ratings for routes they've followed - Share their experience with route planning - Help other users with route recommendations

## Request Body:

```
{
    "route_id": "68877b97cd6e495f565e416c",
    "rating": 4,
    "comment": "Great route! Well planned with good timing between locations.",
    "visited_on": "2024-12-01"
}

Response:
{
    "success": true,
    "message": "Route feedback submitted successfully",
    "status_code": 201,
    "feedback_id": "64f8a1b2c3d4e5f6789abc02",
    "created_at": "2024-12-01T14:30:00Z"
}
```

## @GET /feedback/route/{route\_id}

It allows users to: - Retrieve all feedback for a specific route - View user experiences and recommendations - Access route quality information

```
}
```

## @GET /feedback/route/{route\_id}/user/{user\_id}

It allows users to: - Retrieve specific user's feedback for a route - Check if a user has already provided route feedback - Access user-specific route feedback details

## Response:

```
{
    "success": true,
    "message": "User route feedback retrieved successfully",
    "status_code": 200,
    "data": [
        {
            "feedback id": "64f8a1b2c3d4e5f6789abc02",
            "user_id": "64a1b2c3d4e5f6789abcdef0",
            "route_id": "68877b97cd6e495f565e416c",
            "rating": 4,
            "comment": "Great route! Well planned.",
            "visited_on": "2024-12-01",
            "created at": "2024-12-01T14:30:00Z",
            "updated_at": "2024-12-01T14:30:00Z"
        }
    ]
}
```

## @PUT /feedback/route/{feedback\_id}

It allows users to: - Update their existing route feedback - Modify rating, comment, or visit date - Maintain feedback history with updated timestamps

```
{
    "rating": 3,
    "comment": "Updated review - route was okay but had some timing issues.",
    "visited_on": "2024-12-02"
}
Response:
{
    "success": true,
```

```
"message": "Route feedback updated successfully",
    "status_code": 200,
    "updated_at": "2024-12-01T15:45:00Z"
}
```

## @DELETE /feedback/route/{feedback\_id}

It allows users to: - Delete their own route feedback - Remove feedback from the system - Maintain data integrity with proper authorization checks

## Response:

```
{
    "success": true,
    "message": "Route feedback deleted successfully",
    "status_code": 200,
    "deleted_at": "2024-12-01T16:00:00Z"
}
```

## @GET /feedback/route/{route\_id}/stats

It allows users to: - Get aggregated statistics for route feedback - View average ratings and success metrics - Access route performance analytics

```
{
    "success": true,
    "message": "Route feedback statistics retrieved successfully",
    "status_code": 200,
    "data": {
        "total_feedback": 45,
        "average_rating": 4.1,
        "rating_distribution": {
            "1": 2,
            "2": 3,
            "3": 8,
            "4": 15,
            "5": 17
        }
    }
}
```

### **Database Collections Schema**

The Wayfare API uses MongoDB with the following collections structure:

```
User Collection
{
    "_id": ObjectId, // MongoDB auto-generated unique identifier
    "email": "user@example.com", // Required, unique
    "first_name": "John",
    "last_name": "Doe",
    "username": "johndoe", // Display name, required
    "hashed password": "bcrypt hashed password string",
    "preferences": {
        "interests": ["Museums and Art Galleries", "Food & Drinks", "Outdoors", "Hidden Gem;
        "budget": "medium", // can be: low, medium, high
        "travel_style": "relaxed" // can be: relaxed, moderate, accelerated
    },
    "home_city": "New York"
}
Route Collection
    "_id": ObjectId, // MongoDB auto-generated unique identifier
    "route_id": "string", // Application-level route ID
    "user_id": "64a1b2c3d4e5f6789abcdef0", // Reference to user who created route
    "title": "Trip to Rome",
    "city": "Rome",
    "city_id": "city_objectid_string",
    "country": "Italy",
    "country_id": "country_objectid_string",
    "start_date": "2025-06-01",
    "end date": "2025-06-07",
    "budget": "medium", // low, medium, high - inherited from user preferences
    "travel_style": "moderate", // relaxed, moderate, accelerated
    "category": "city_break", // city_break, beach, mountain, road_trip
    "season": "summer", // spring, summer, autumn, winter
    "stats": {
        "views_count": 0,
        "copies_count": 0,
        "likes_count": 0
    },
    "must_visit": [
```

"place\_name": "Colosseum",

"place\_id": "abc123", // Optional - from places collection

{

```
"address": "Piazza del Colosseo, 1, 00184 Roma RM, Italy",
            "coordinates": { "lat": 41.89, "lng": 12.49 },
            "notes": "Morning preferred",
            "source": "google", // google, user, database
            "opening_hours": {
                "monday": "08:30-19:15",
                "tuesday": "08:30-19:15",
                "wednesday": "08:30-19:15",
                "thursday": "08:30-19:15",
                "friday": "08:30-19:15",
                "saturday": "08:30-19:15",
                "sunday": "08:30-19:15"
            }
        }
   ],
    "days": [
        {
            "date": "2025-06-01",
            "activities": [
                {
                    "place_id": "abc123", // Optional - from places collection
                    "place_name": "Colosseum",
                    "time": "10:00", // 24-hour format
                    "notes": "Visit the ancient amphitheater"
                }
            ]
        }
    ],
    "created_at": "2024-12-01T10:00:00Z",
    "updated_at": "2024-12-01T10:00:00Z"
}
Places Collection
{
    "_id": ObjectId, // MongoDB auto-generated unique identifier
    "place_id": "abc123", // Unique place identifier (from Google Places API or generated)
    "city": "Rome",
    "city_id": "city_objectid_string", // Reference to cities collection
    "country": "Italy",
    "country_id": "country_objectid_string", // Reference to countries collection
    "name": "Colosseum",
    "category": "historical_site", // attraction category
    "wayfare_category": "must_see", // Optional - our internal categorization
    "price": "€15-25", // Price range or specific price
    "rating": "4.5", // User rating (string format)
```

```
"popularity": "4.8", // Popularity score (string format)
    "image": "https://example.com/colosseum.jpg", // Optional image URL
    "detail_url": "https://maps.google.com/place/...", // Optional detail URL
    "opening_hours": {
        "monday": "08:30-19:15",
        "tuesday": "08:30-19:15",
        "wednesday": "08:30-19:15",
        "thursday": "08:30-19:15",
        "friday": "08:30-19:15",
        "saturday": "08:30-19:15",
        "sunday": "08:30-19:15"
    },
    "coordinates": {
        "lat": 41.8902,
        "lng": 12.4922
    },
    "address": "Piazza del Colosseo, 1, 00184 Roma RM, Italy",
    "source": "google", // google, manual, scraping
    "duration": 120, // Recommended visit duration in minutes
    "created_at": "2024-01-01T00:00:00Z",
    "updated_at": "2024-01-01T00:00:00Z"
}
Cities Collection
{
    "_id": ObjectId, // MongoDB auto-generated unique identifier
    "name": "Rome",
    "country": "Italy",
    "country_id": "country_objectid_string", // Reference to countries collection
    "active": true, // Whether city is available for route planning
    "coordinates": { // Optional - city center coordinates
        "lat": 41.9028,
        "lng": 12.4964
    },
    "timezone": "Europe/Rome", // Optional timezone information
    "created at": "2024-01-01T00:00:00Z",
    "updated_at": "2024-01-01T00:00:00Z"
}
Countries Collection
    "_id": ObjectId, // MongoDB auto-generated unique identifier
    "name": "Italy",
    "country_id": "IT", // ISO country code identifier
```

```
"region": "Europe", // Geographical region classification
    "active": true, // Whether country is available for route planning
    "created_at": "2025-07-30T16:06:03.201000",
    "updated_at": "2025-07-30T16:06:03.201000"
Place Feedback Collection
    "_id": ObjectId, // MongoDB auto-generated unique identifier
    "user_id": "64a1b2c3d4e5f6789abcdef0", // Reference to user who submitted feedback
    "place_id": "ChIJyWEHuEmuEmsRm9hTkapTCrk", // Google Places ID or internal place identi:
    "rating": 5, // Integer from 1-5 rating scale
    "comment": "Amazing place! The view was breathtaking and staff was very friendly.", //
    "visited_on": "2024-12-01", // Date when user visited the place (YYYY-MM-DD format)
    "created_at": "2024-12-01T10:30:00Z", // Timestamp when feedback was submitted
    "updated_at": "2024-12-01T10:30:00Z" // Timestamp when feedback was last modified
}
Route Feedback Collection
{
    "_id": ObjectId, // MongoDB auto-generated unique identifier
    "user_id": "64a1b2c3d4e5f6789abcdef0", // Reference to user who submitted feedback
    "route_id": "68877b97cd6e495f565e416c", // Reference to route from routes collection
    "rating": 4, // Integer from 1-5 rating scale
    "comment": "Great route! Well planned with good timing between locations.", // Optional
    "visited_on": "2024-12-01", // Date when user followed the route (YYYY-MM-DD format)
    "created_at": "2024-12-01T14:30:00Z", // Timestamp when feedback was submitted
    "updated_at": "2024-12-01T14:30:00Z" // Timestamp when feedback was last modified
}
Collection Relationships
Countries (1) ←→ (many) Cities ←→ (many) Places
Users (1) ←→ (many) Routes ←→ (many) Must_Visit_Places
(many) Place_Feedback + Route_Feedback ←→ Places
  • Users create multiple Routes and submit Feedback
  • Routes reference Cities and Countries
  • Routes contain Must Visit places which may reference Places
  • Places belong to Cities which belong to Countries
  • Place Feedback links Users to Places with ratings and comments
```

• Route Feedback links Users to Routes with ratings and comments

• All collections use MongoDB ObjectIds for relationships

}

## **Key Features**

- Flexible Schema: MongoDB allows for optional fields and schema evolution
- Geocoding Integration: Places can be added from external APIs (Google Places)
- User-Generated Content: Routes can include custom places not in the places collection
- Hierarchical Data: Countries  $\rightarrow$  Cities  $\rightarrow$  Places relationship
- Feedback System: Users can rate and review places and routes with validation
- **Duplicate Prevention**: One feedback per user per place/route to maintain data integrity
- Statistics: Dynamic calculation of ratings, averages, and distributions
- Audit Trail: All collections include created\_at and updated\_at timestamps

Ready to start building amazing travel experiences? Check out our Getting Started Guide and API Examples for implementation details!