Letting a Robot Train Itself: What Helps, What Doesn't, and What Only Looks Like It Helps

Anonymous CVPR submission




Figure 1. **A robot policy that trains on its own attempts.** (a) One practice placement of a LIBERO-Spatial task and two attempts by the initial OpenVLA-OFT policy, shown as its camera saw them. The simulator's success check labels each attempt, and the loop trains on such labelled attempts. (b) LIBERO-Goal, behaviour cloning on the policy's own samples. When every new version is accepted, success on the round's 200 held-out placements falls from 58.5% to 7% within six rounds. When a version is kept only if it does not regress on fresh paired placements, the same recipe stays at its starting level.

Abstract

A robot policy can improve without new demonstrations: it attempts tasks, a verifier marks the successes, it trains on them, and the improved policy practises again. Such self-improvement loops are reported to work for language models and for vision-language-action (VLA) policies, but the reports rarely say which part of the loop produced the gain: the verifier, the recursion, a gate that rejects regressions, a meta level that rewrites the training recipe, or simply the extra RL compute. We built one framework in which each part is a switch, preregistered every comparison and bar, kept the benchmark sealed until all decisions were made, and averaged every final score over repeated evaluations. With a 7B OpenVLA-OFT policy on LIBERO-Goal (31 runs, two GPU platforms), the gate is what makes self-training safe: a recipe that collapses from 58.5% to 5.5% when every version is accepted stays at its starting level under the gate. Beyond safety the gains are small at six rounds (recursion $+1.7$ points, 95% CI $[-0.3, +3.7]$; verifier $+1.2$ $[-0.4, +2.9]$), and one round of plain RL at equal compute does as well. At twelve rounds recursion separates by $+7.8$ $[+5.2, +10.5]$, because the loop without it drifts below its start. A meta level adds nothing once the recipe works (within ± 1.2 points), but repairs a broken recipe to the hand-tuned level ($+2.7$ $[+0.7, +4.6]$ over the gate alone, short of our $+3$ bar). Finally, a published VLA-RL score owes $+16.8$ points $[+9.8, +23.4]$ to training on the benchmark's own test states. Code, preregistrations and all run records are released.

1. Introduction

Collecting demonstrations is the expensive part of training a robot policy. An attractive alternative is to let the policy teach itself: give it a task, let it try, keep the attempts that worked, train on them, and let the improved policy try again. For language models this recipe is called self-improvement and has several working versions [3, 6, 21–23]; reinforcement learning with a verifiable reward is its standard form for reasoning models [4, 19]. Robot learning has started to follow: a vision-language-action (VLA) policy can be improved by RL in simulation from a success flag alone [12, 14]. The most ambitious version, often called recursive self-improvement, goes one step further and lets the system also revise the procedure by which it improves.

Reading these papers, we kept asking two plain questions. First, *which part is doing the work?* A self-improvement loop contains at least four ideas that could each be responsible for a gain: the verifier that labels attempts as successes, the recursion that lets the newest policy

generate the next practice, a gate that keeps only versions that beat their parent, and a meta level that edits the recipe. It also contains ordinary RL as a special case, so a positive result does not by itself show that any of the four mattered. Second, *is the gain real?* Benchmarks such as LIBERO [13] test on a fixed list of initial object placements, and nothing stops a method from training on that list. We show that a widely used VLA-RL checkpoint does, and that about a fifth of its score comes from it (Sec. 5.4).

This paper answers both questions by experiment. We built a framework (Sec. 3) in which every ingredient of the loop is a switch inside one engine: the verifier can be real or replaced by shuffled labels; practice can come from the latest policy or from the frozen initial one; the meta level can be off, a numeric search, or a language model that reads the round records and edits the recipe inside a declared space; and the whole budget can instead be spent on one long round of plain RL. Flipping one switch at a time attributes a difference to one ingredient.

Self-improvement results are easy to inflate: the loop selects versions, evaluation is noisy, and the experimenter sees the intermediate numbers. So we fixed the rules before playing (Sec. 4). Every comparison, bar and statistic was written down and committed to a public repository before the corresponding runs started; every later change is a dated amendment that says what had been seen; the official test was never used for training, sampling or selection and was opened once per study; and every final score is the average of three evaluations, because a single one carries about ± 1.5 points of noise.

What we found. Figure 1 shows the setting and the clearest result; Tab. 2 lists every registered comparison.

1. **The gate makes self-training safe, with a condition.** Across 31 six-round runs with an OpenVLA-OFT policy on LIBERO-Goal, no gated run ends below its start beyond evaluation noise, while the same recipe collapses from 58.5% to 5.5% when every version is accepted; over twelve rounds the protection holds only when practice is recursive (Sec. 5.1, Sec. 5.2).
2. **Beyond safety the gains are small, and no single ingredient clears its bar at six rounds.** The loop gains one to two points. Recursion contributes $+1.7$ points $[-0.3, +3.7]$ and the verifier $+1.2$ $[-0.4, +2.9]$; one round of plain RL with the same budget does as well. At twelve rounds recursion separates by $+7.8$ $[+5.2, +10.5]$, but because the loop without it drifts below its start while the recursive loop holds its level; plain RL still ties (Sec. 5.2).
3. **A meta level does not help a recipe that already works, and we can say why.** Four variants, including a language model allowed to edit nine components of the training harness, land within ± 1.2 points of a fixed recipe; a second, separately registered study gives -0.3 and $+0.3$ points on two platforms. The model's diagnoses are correct, but every recipe in the space reaches the same plateau (Sec. 5.3).
4. **When the recipe fails, a meta level repairs it, to the level of the hand-tuned recipe and no further.** Starting from a recipe that collapses without the gate, the language model names the cause unprompted and the gate keeps its repair; the repaired loop ends $+2.7$ points $[+0.7, +4.6]$ above the gate alone, under its preregistered $+3$ bar, level with the hand-tuned loop ($+0.3$ $[-1.4, +2.0]$), and $+1.2$ $[-0.6, +2.9]$ ahead of a numeric search over the same knobs (Sec. 5.3).
5. **A published VLA-RL score owes about a fifth of itself to the test states** ($+16.8$ points $[+9.8, +23.4]$; Sec. 5.4).

Contributions. (i) A self-improvement framework for VLA policies in which every control is a switch inside one engine, with behaviour cloning and GRPO as interchangeable update rules, and a language-model meta level that edits a declared recipe space under an attribution guard. (ii) A preregistered, sealed-test protocol for self-improvement claims, with every amendment public. (iii) The first controlled decomposition of such a loop on a VLA benchmark, including its negative results and the mechanism behind them. (iv) A measurement of train-on-test inflation in a published VLA-RL result. Code, preregistrations and all run records are released.

2. Related work

Self-improvement with verifiers. STaR [22], ReST [6] and ReST-EM [20] fine-tune a language model on its own verified rationales; SPIN [3] and self-rewarding models [21] close the loop with the model as its own judge; Absolute Zero [23] lets the model write its own tasks and uses a code executor as the verifier. RLVR with group-relative policy optimisation [4, 19] is the dominant update rule. These works report that the loop helps. We ask which part of it helps, with every part switchable and every comparison registered in advance. The closest analyses are the iterated on-policy convergence results of [8], whose predicted shape (early saturation of a learner restricted to samples from the initial policy) is what our non-recursive control shows at twelve rounds.

Meta levels that edit the procedure. LLM-driven search over programs and training recipes has produced strong results when the search space is large and evaluation is cheap [7, 15, 18]. Recent outer-loop systems put the weight on the harness around the proposer: Meta-Harness [11] hands it the code, scores and raw traces of every earlier candidate as files instead of a summary, EvoTrainer [2]




Figure 2. **The framework.** One engine, every ingredient a switch. The object loop practises on fresh scenes with the latest policy; the gate keeps a candidate only if it does not regress on paired held-out placements; the meta level versions the training program and may let a numeric search or an LLM edit it inside a declared space, seeing only gate records. Controls flip one switch each.

adds layered diagnostics and a memory that keeps failed branches, and LLMZero [5] has agents diagnose training signals at checkpoints. Our last meta level follows them (Sec. 3.4). In our setting evaluation is expensive (hundreds of simulator episodes per candidate) and noisy, and the space is a few dozen knobs and harness components. Under these conditions, we find, a language-model meta level that diagnoses correctly still cannot beat a fixed recipe that already works, and we isolate the one case where it could.

RL for VLA policies. OpenVLA [9] and OpenVLA-OFT [10] are the policies we improve; SimpleVLA-RL [12], RL4VLA [14] and related work [16] apply on-policy RL to such policies in simulation with a binary success reward. We use the SimpleVLA-RL training stack as one update operator and its released checkpoints as starting points. Our train-on-test measurement (Sec. 5.4) concerns the evaluation practice of this line of work rather than its methods.

Preregistration. Preregistered designs are standard in the experimental sciences [17] and have been proposed for machine learning [1]. We follow the practice literally: every bar, statistic and read-once rule was committed to a public repository before the corresponding runs, and every change is a dated amendment that states what had been seen.

3. Framework

Figure 2 shows the framework. In plain terms: a policy practises on freshly sampled scenes, a verifier marks each attempt, the verified attempts update the policy, and a gate decides whether the updated policy replaces the current one. Above this sits an optional meta level that may edit the training recipe. The rest of this section states that picture precisely, together with the switches the experiments flip.

3.1. Setting and notation

A policy π_θ acts in scenes $s \sim \mathcal{S}$ (object placements of a task); an attempt $\tau \sim \pi_\theta(\cdot \mid s)$ is a trajectory, and an external oracle $v(s,\tau) \in \{0,1\}$ the policy cannot influence labels it (the simulator's success flag). A *program* P is a JSON document with four sections—`curriculum` (which scenes to practise, how many, how allocated across tasks), `solver` (attempts per scene K, temperature T), `curation` (which attempts become training items) and `update` (the operator and its hyperparameters)—and $\mathcal{P}$ is a declared edit space of allowed values. A *version* is a pair (θ, P). The framework keeps an archive of versions; the one it currently trusts is the *retained* version $(\theta^\star, P^\star)$.

3.2. The loop (Algorithm 1)

One *inner step* runs program P from policy θ: propose scenes, attempt each K times, verify, curate, update. Curation `mixed_groups` keeps every attempt of scenes whose success rate lies strictly inside a band (used by GRPO [19]: the group-centred advantage is zero when all attempts agree); `verified` keeps successful attempts only (behaviour cloning, BC). The update is a LoRA step on θ. A *round* is three inner steps from the same parent, producing a *candidate* θ'. Because the next round starts from

Algorithm 1 Gated recursive self-improvement with a meta level

Require: initial policy θ_0, seed program P_0, oracle v, gate set size n_g, rounds R, candidates per round c

$(\theta^\star, P^\star) \leftarrow (\theta_0, P_0)$; evaluate $\theta^\star$ on fresh gate and audit sets
for $r = 1 \dots R$ **do**
  draw a fresh gate set G_r of n_g paired placements; re-evaluate $\theta^\star$ on G_r
  $\{P_1, \dots, P_c\} \leftarrow \{P^\star\} \cup$ PROPOSE(round records, $\mathcal{P}$) ▷ meta level: fixed / numeric / LLM
  for each candidate program P_i **do**
    $\theta_i \leftarrow \theta^\star$
    for inner step $= 1 \dots 3$ **do**
      scenes $\leftarrow$ PROPOSE$(P_i, \theta_{\text{gen}})$ with $\theta_{\text{gen}} = \theta_i$ (recursive) or θ_0 (`nonrec`)
      attempts $\leftarrow K$ samples per scene at temperature T; labels $\leftarrow v(\cdot)$ (or permuted: `shuffled`)
      items $\leftarrow$ CURATE(attempts, P_i); $\theta_i \leftarrow$ UPDATE(θ_i, items, P_i)
    end for
    $g_i \leftarrow$ success of θ_i on G_r (greedy); record audit, never use it
  end for
  $i^\star \leftarrow \arg\max_i g_i$; **if** $g_{i^\star} \geq g(\theta^\star, G_r)$ **then** $(\theta^\star, P^\star) \leftarrow (\theta_{i^\star}, P_{i^\star})$ ▷ gate
end for
read the sealed test of $\theta^\star$ once, after every run of the study has ended

the retained version, practice is always generated by the latest policy: this is the *data recursion*, and the control `nonrec` breaks exactly it by proposing and attempting with the frozen initial policy θ_0 while still updating from $\theta^\star$.

3.3. Gate, audit and sealed test

Three disjoint evaluation sets are drawn per run from seeds that never overlap the official benchmark states. The *gate* (20 placements per task, 200 episodes, greedy decoding, environment re-seeded per episode so that versions are compared on identical placements) decides: a candidate is kept iff its gate success is at least the parent's on the same placements. In the *fresh-paired* mode used in every main run a new gate set is drawn every round and the parent is re-evaluated on it, so acceptance is always a paired comparison on placements never seen before, and a version cannot overfit a fixed gate. The *audit* (200 more) is recorded but never decides anything; it exposes gate overfitting. The *test* is the official benchmark (50 initial states per task, 500 episodes) and is *sealed*: no process in the loop can read it, and it is opened once, after every decision in every run of a study has been made. Because the loop practises on sampled placements while the official states are a fixed list, we add a second sealed test, registered before any of its evaluations existed: 1000 freshly sampled placements per suite that no run trained, gated or audited on, the same for every run.

This is the *selection recursion*: the system's own verification result decides its next version, and the kept version decides who generates the next practice.

3.4. Meta level

The meta level versions the program and lets it be improved under the same gate. Each round the incumbent $P^\star$ and $c-1$ proposed programs are each trained for real from the same parent, and the gate picks the version to keep; a program is credited only when its child wins. Three proposers:

- `fixed`: no change (the meta level is off).
- `numeric`: random mutation of declared knobs, biased toward knobs whose past changes raised the gate.
- `llm`: a language model (Claude Sonnet) reads the current program, the edit space with a neutral description of what each option computes, and, for every past candidate, its program diff, gate score, acceptance and per-step statistics (sampled success, share of mixed scenes, item counts, first/last training loss). It must write a diagnosis, then return one new program.
- `llm+harness`: the same model behind a harness of its own, following [2, 11]. Instead of one prompt with a truncated summary it gets a *workspace* of files (the full record of every candidate of the run, per-task gate tables, an evidence ledger that pools gate changes per edited field), a frozen *memory* of earlier runs (their gate-side records and a playbook the model distilled from them before launch), its own notes from earlier rounds, and three tools (list, read, search) used over several turns before it answers. The prompt states the measured gate noise. Building it exposed a defect in the plain `llm` proposer: the training loss it was told to watch never reached it (a field-name error), in every run reported for it below.

The edit space has two sizes. The *knob* space has ten hyperparameters (scenes, allocation, samples, temperature, curation rule and budget, operator, learning rate, steps, batch). The *harness* space adds nine components of the procedure itself: the ratio computation of the policy gradient (legacy or matched), the loss aggregation (token or episode), the BC likelihood temperature (unit or rollout), advantage normalisation, the curation band, the per-scene cap, the allocation floor and the two clip bounds. Each corresponds to a change that was made by hand during development after diagnosing round records; the LLM is never told which option is better, so rediscovering them is a test of the meta level. This is the *procedure recursion*.

Table 1. **Controls.** Each arm flips one switch of Algorithm 1.

arm	change in Algorithm 1	isolates
`fixed`	none (proposer off)	gated recursive loop
`nonrec`	$\theta_{\text{gen}} = \theta_0$	data recursion
`shuffled`	labels permuted per scene	the verifier
`onebig`	R=1, $3R$ inner steps	gate + iteration vs one-shot RL
`full`	numeric proposer, c=2	meta level (equal compute)
`llm`∗	LLM proposer, c=2	meta level (equal compute)

∗ `llm`: knob space; `llm_harness`: harness space; `llm_harness_cap`: harness space under the compute cap.

Attribution guard. The meta level never sees the audit or test, the policy weights, the scenes or the episodes; it only chooses values inside $\mathcal{P}$, every proposal passes the same validator as a numeric mutation, invalid proposals and failed calls fall back to numeric search and are counted, and a *compute cap* scales any proposal so that no candidate does more rollouts or optimiser work per step than the starting program. All practice data still comes from the policy's own attempts and all verdicts from the oracle; the LLM is a source of procedure choices, not of data.

3.5. Every control is a switch

Table 1 lists the arms used in the experiments. Each differs from `fixed` in exactly one line of Algorithm 1, so a difference between an arm and `fixed` is attributable to that line; `full` and the `llm` arms train the same number of candidates and so cost the same.

4. Experimental setup

4.1. Benchmarks, policies and starting points

LIBERO / OpenVLA-OFT. LIBERO-Goal [13] has ten goal-conditioned tasks in one scene; LIBERO-10 ten long-horizon tasks. The policy is OpenVLA-OFT [10] (7B, action chunks of 8), started from a supervised fine-tune on *one* demonstration per task [12] so that there is room to improve (about 59% on LIBERO-Goal, 19% on LIBERO-10). Rollouts and GRPO/BC training use the SimpleVLA-RL stack with LoRA (r=32). The seed program—chosen from sealed pilots and frozen by amendment before any main run—is GRPO with learning rate 3×10^{-5}, matched-ratio log-probabilities, episode-balanced loss, 8 samples per scene at temperature 1.5, 160 scenes per inner step, 200 optimiser steps of batch 64; 6 rounds of 3 inner steps; fresh paired gates.

4.2. Arms and baselines

The LIBERO-Goal main study runs the eight arms of Sec. 3.5 with three seeds each (a fourth seed was added to the `nonrec`, `shuffled`, `onebig` and `fixed` arms by amendment before any of their runs ended), 31 runs in all, on two GPU platforms: a shared 8×A800 node and a 16-GPU cloud pool with its own evaluation stack. The stacks are not bit-identical, so every comparison is paired within a platform and the platforms serve as replicates. `onebig` is the plain-RL baseline: the whole six-round rollout and update budget in one round of 18 on-policy inner steps from the initial policy, with the same sampling and update code; it is read both through the gate and as its ungated single candidate.

4.3. Preregistered protocol

Self-improvement claims are easy to inflate: the loop selects versions, evaluation is noisy, and the experimenter sees the intermediate numbers. We therefore fixed the protocol before the runs and release the preregistration documents (27 dated amendments for the VLA study) with the code.

Sealing. The official LIBERO test states are never used for training, sampling, gating or program selection, and no test file is opened before a study's read-once. Only two sealed pilots per model were allowed before the seed program was frozen.

Finals and reference. A single 500-episode evaluation is itself noisy: the *same* initial policy evaluated in different runs scored between 57.2% and 60.0% (sd $\approx$ 0.7), and about 40% of episodes flip between nearby policies. Each run's final is therefore the per-episode mean of three evaluations of its retained policy (the run's own test and two replicate evaluations from the same plan and source tree), and the initial reference is the per-episode mean of every in-run evaluation of the initial policy on that platform (36 evaluations on the cloud pool, 21 on the A800). A noise check—the same statistic between two halves of the initial-policy evaluations—is reported with every verdict.

Claims and bars. Seed-averaged per-episode paired bootstrap (10,000 draws), 95% CI. "CI $>$ 0" means the interval excludes zero.

claim	comparison	bar (points)
R1 improvement	`fixed`, `full` − reference	$\geq +5$, CI > 0, 2/3 seeds > 0
R2 verifier	`fixed` − `shuffled`	$\geq +3$, CI > 0
R3 recursion	`fixed` − `nonrec`	$\geq +2$, CI > 0
R4 meta level	each meta arm − `fixed`	$\geq +2$, CI > 0
R5 vs one-shot RL	best gated arm − `onebig`	$\geq +2$, CI > 0
M2-A meta v2	`llm` − identical-recipe replica	$\geq +3$, CI > 0
S1 self-repair	`llm_harness` − `fixed` (failing start)	$\geq +3$, CI > 0

Negative readings are reported as such; the reading scripts were committed before each read and their outputs are released.

5. Results

We organise the results around five questions. Every number below comes from a preregistered read of a sealed test

unless it is marked *gate-level*.

5.1. RQ1: Does the gated loop improve a VLA policy, and is it safe?

Finding 1: safe, and modestly effective. Table 3 gives the finals per arm. Every gated run ends within noise of its start or above it (finals 57.1–62.2% against a reference of 58.4–58.9%; the two runs below their reference are within -1.3 and -1.7 points). The typical gain is one to two points and the best single seed gains $+3.3$ $[+0.1, +6.6]$. The registered R1 claim (Tab. 2) comes to $+1.71$ $[-0.76, +4.23]$ for `fixed` and $+1.28$ for `full`, below the $+5$ bar. The safety is the gate's doing, not the recipe's. In always-accept pilot curves on LIBERO-10 every recipe stayed within ± 3 points of its start for 18 on-policy steps, but the behaviour-cloning recipe of Sec. 5.3 collapsed from 58.5% to 5.5% when its versions were accepted unconditionally (Fig. 1b); under fresh paired gates the same recipes do not fall below their start beyond noise on the sealed test. Two qualifications. The price is noise: a 200-episode paired gate has a standard deviation of about 3.4 points, so it accepts and rejects many candidates by chance. And the protection is not unconditional: at twelve rounds the arm whose practice comes from the frozen initial policy drifts 4–11 points below its start through a chain of accepted versions (Sec. 5.2, Finding 2b), so the finding is that the gate keeps a loop with recursive practice safe at this budget, not that it is a ratchet. Acceptance rates are in the released records.

5.2. RQ2: Which part of the loop helps?

Finding 2: recursion and the verifier are the largest ingredients, neither clears its bar, and plain RL ties. Recursion (R3) comes to $+1.72$ $[-0.28, +3.68]$ against a $+2$ bar. A preliminary read on single evaluations had passed it at $+2.40$; the pass did not survive averaging over replicates, which is exactly what the protocol is for. The verifier (R2) is worth $+1.22$; without it the loop ends where it started (57.8–60.7%). One round of plain RL with the same budget matches or beats the loop (R5 -0.58; on seed 0 the one-shot policy scores 62.7 against the gated loop's 57.2). Figure 3 shows what happens at the gate: `nonrec` stops climbing after round 3 while `fixed` keeps going.

Finding 2b: at twelve rounds recursion separates by $+7.8$ points, because the non-recursive loop degrades. A registered extension (amendment 27; three seeds each of `fixed12`, `nonrec12` and a 36-step `onebig12`, same rule for finals) gives R3-long $= +7.84$ $[+5.22, +10.49]$ against its $+2$ bar, positive on every seed ($+14.4$, $+4.9$, $+4.2$). The mechanism is not the one we predicted. `fixed12` ends where `fixed` ended at six rounds (-0.09 $[-1.98, +1.78]$ against the same seeds' 6-round finals; $+1.60$ $[-0.88, +4.13]$ over the reference, below the $+5$ bar), while `nonrec12` ends 4–11 points *below its own start* on every seed (-6.44 $[-9.00, -3.96]$ against its 6-round finals), although every one of its versions was accepted by a fresh paired gate. With one candidate per round, acceptance on $\geq$, and candidates that are truly a little worse than their parent (their practice is generated by a policy the learner has drifted away from), noise-driven acceptances accumulate. Recursion is what keeps the gated loop from drifting down at this horizon; it does not lift it. Against plain RL the picture is unchanged: R5-long $= -0.38$ $[-2.42, +1.64]$, and `onebig12`'s single candidate was kept by the gate on all three seeds.

5.3. RQ3: Does a meta level help, and when could it?

Finding 3: no meta level beats a working fixed recipe, on two studies and two platforms. All four R4 arms land within ± 1.2 points of `fixed` (Tab. 2). One could object that these arms give the LLM little to work with: each round compares only the newest edit against the incumbent, and the LLM never sees per-task results. So we registered a second study ("v2") in which the LLM sees per-task gate rates with their noise, each candidate starts from its parent's statistics, and the comparison is between an `llm` arm and a *replica* arm that trains the identical recipe at the same compute, from two starting policies. The primary bar fails on both platforms: -0.27 $[-2.53, +2.00]$ (cloud, seeds 1–3) and $+0.30$ $[-1.60, +2.15]$ (A800, seeds 0–3). Pooled over seven seed pairs, any true effect is within about ± 2 points.

Finding 4: the null has a mechanism. Over the v2 study the LLM's proposals scored -1.2 points against the incumbent at the gate (n=30), while replicas of the identical recipe scored $+0.6$ (sd 3.4, n=36): there is no edit effect for a finer gate to resolve. The LLM's diagnoses, logged verbatim, read the loop correctly. They point to the task that is never solved (so GRPO gets no signal), the task that is already saturated, and the remaining gate changes that sit inside the noise, and the edits they propose are the ones a practitioner would try. None of them moves success within six rounds: the final retained gates are 62.8 (`fixed`), 63.5 (`full`), 65.0 (`llm_harness`) and 61.7 (`onebig`), all within gate noise. *The object loop reaches the same plateau under every recipe in the space*, so a correct diagnosis of a recipe that already works has nothing to repair.

Self-repair: a recipe that fails. A meta level can be told apart from RL only where RL's recipe fails and a different recipe would not. The study contains one such case, found before any meta-level run: behaviour cloning on the policy's own temperature-1.6 samples with a unit-temperature likelihood collapses when its versions are accepted unconditionally (58.5% $\rightarrow$ 5.5%). The repair is a one-knob change (the BC temperature, the sampling temperature, or the update operator), and all three knobs are

Table 2. **Registered claims on LIBERO-Goal** (official 500-episode test, 3-evaluation finals, pooled initial reference, seed-averaged paired bootstrap). No bar is met. Platform Y = cloud pool, A = A800.

claim	comparison	points	95% CI	bar	seeds
R1	`fixed` − ref. (Y)	+1.71	[−0.76, +4.23]	+5	1–3
R1	`full` − ref. (Y)	+1.28	[−1.37, +3.99]	+5	1–3
R2	`fixed` − `shuffled` (Y)	+1.22	[−0.37, +2.85]	+3	0–3
R3	`fixed` − `nonrec` (Y)	+1.72	[−0.28, +3.68]	+2	0–3
R4	`full` − `fixed` (Y)	−0.42	[−2.40, +1.56]	+2	1–3
R4	`llm_harness` − `fixed` (Y)	−0.73	[−2.58, +1.07]	+2	1–3
R4	`llm` − `fixed` (A)	+1.04	[−0.84, +3.00]	+2	1–3
R4	`llm_harness_cap` − `fixed` (A)	+1.16	[−0.76, +3.16]	+2	1–3
R5	best gated − `onebig` (Y)	−0.58	[−2.12, +0.95]	+2	0–3
noise	half vs. half of the n0 evaluations (Y / A)	+0.64 / +0.54	[−0.07, +1.36] / [−0.24, +1.35]		




Figure 3. **Gate success of the retained policy by round** (cloud platform; thin lines are seeds 1–3, the thick line their mean). A dot marks a round that accepted a new version; every round is scored on 200 newly drawn placements, so a retained version's score can fall from one round to the next. The number in each panel is the change of the mean from round 0 to round 6. The gated arms climb 4–5 points at the gate within six rounds; `shuffled` (verifier removed) stays flat; `nonrec` (practice from the frozen initial policy) stops after round 3. Gate gains overstate test gains by the winner's curse (Tab. 3).

Table 3. **Per-arm finals** (%, mean of the 3-evaluation finals over seeds 1–3; seed-0 runs listed separately). Reference 58.9 (Y) / 58.4 (A).

	`fixed`	`full`	`llm*`	`nonrec`	`shuf.`	`onebig`
Y, s1–3	60.6	60.2	59.9	59.1	58.9	59.1
A, s1–3	59.1	–	60.1 / 60.2	–	–	–
A, s0	57.2	–	–	54.8	57.5	62.7

∗ Y: `llm_harness`; A: `llm` / `llm_harness_cap`.

in the harness space. We registered a study (amendments 24 and 26) before any of its runs: start from the collapsing recipe; arms `fixed` (the gate alone), `full` (numeric search) and `llm_harness` (same compute); four seeds; bars S1 = `llm_harness` − `fixed` ≥ +3 with CI above 0, and S2 = `llm_harness` − `full` reported with its CI. The failure case was written down in advance: if S1 fails, the meta level has no demonstrated effect in this study.

Finding 5: when the recipe fails, a meta level repairs it to the hand-tuned level and no further; S1 misses its bar. The registered read (finals averaged over three evaluations, seed-averaged paired bootstrap over seeds 0–3) gives S1 = +2.65 points [+0.73, +4.58]: positive on three seeds, individually significant on one, CI above zero, but under the +3 bar, so the registered claim is not made. S2 = +1.15 [−0.63, +2.92] and `full` − `fixed` = +1.50 [−0.33, +3.38]: the diagnosis cannot be told apart from blind search over the same knobs, the case the preregistration named in advance ("the loop repairs itself when the space contains the repair"). S3: the repaired loop ends level with the hand-tuned GRPO loop (+0.28 [−1.43, +1.97]), while the gate-only loop from the failing recipe ends below it (−2.37 [−4.12, −0.62]). The record explains the numbers. The gate alone holds the policy at its start (`fixed` finals 56.1–58.7% against initial tests of 57.2–59.8%) and nothing more. The LLM's first-round diagnoses on all four seeds name the mismatch between the sampling and likelihood temperatures and the missing failure signal (ver-




Figure 4. **Self-repair study, gate level.** Left: the starting BC recipe collapses when every version is accepted. Right (narrower scale): under the gate the same recipe stays at its starting level (`fixed`); both proposers find repairs; at the gate the LLM arm looks 4–8 points ahead, on the sealed test it is +2.65 (Tab. 4).

Table 4. **Self-repair study**: retained version, its gate / its sealed-test final (%, three evaluations), and what the meta level did. Registered read: S1 = `llm_harness` − `fixed` = +2.65 [+0.73, +4.58], bar +3 missed; S2 = `llm_harness` − `full` = +1.15 [−0.63, +2.92]; S3 = `llm_harness` − hand-tuned GRPO loop = +0.28 [−1.43, +1.97].

seed	`fixed` (gate only)	`full` (numeric search)	`llm_harness`
1 (Y)	r6, 60.0 / 56.1; BC unchanged	r5, 62.5 / 56.7; BC unchanged	r5, 65.5 / 60.1; LLM switched to GRPO in round 1, kept
2 (Y)	n0 / 58.7; all 6 refused	r6, 65.0 / 59.9; switched to GRPO	r6, 68.5 / 61.3; LLM switched to GRPO in round 1, kept
3 (Y)	r5, 63.0 / 57.5; BC unchanged	r6, 61.0 / 60.2; BC, rollout-temp. likelihood	r6, 64.5 / 57.9; GRPO refused twice, BC repaired: T 1.6→1.3
0 (A)	r6, 64.5 / 57.4; BC unchanged	r4, 61.5 / 58.8; BC unchanged (rounds 5–6 refused)	r6, 68.5 / 60.9; LLM's GRPO child kept in round 2, lineage re-tuned by the LLM

batim in the released logs), and its first proposal on every seed is the same: switch to GRPO on mixed-outcome scenes at a lower temperature. The gate kept that switch in round 1–2 on three seeds and refused it twice on the fourth, where the LLM repaired BC instead (sampling temperature 1.6 → 1.3). Numeric search also reaches a repair, on two seeds and only in round 6. Both repaired arms then gain what the hand-tuned GRPO loop gains, one to two points. The LLM's advantage is therefore speed, not the end result. One more lesson is in the table: retained gates exceed the finals by 5–8 points on the LLM arm and 4–7 on `fixed`, because an arm that accepts a candidate almost every round carries more winner's curse in its retained gate; gate-level comparisons between arms are biased in favour of the arm that edits more. We looked for a second failing scenario with six gate-only pilots (four extreme GRPO/BC recipes, both platforms); none degraded under the gate, so no second scenario was registered.

5.4. RQ4: How much of a published VLA-RL number is the test set?

Finding 7: about a fifth of the headline number. LIBERO is tested on 50 fixed initial states per task, and the released SimpleVLA-RL LIBERO-10 checkpoint was trained by RL on exactly those states. We evaluated it, and its own SFT starting point, on the 500 official episodes and on 500 placements freshly drawn by LIBERO's own sampler (the same distribution, not a perturbation): SFT 14.6% official against 20.0% fresh; RL 87.4% against 76.0%. The difference of the two gaps, which cancels any difference in difficulty between the two placement sets, is +16.8 points [+9.8, +23.4]; a replication on 500 further never-seen placements gives +16.0 [+9.2, +22.4] (Fig. 5). The checkpoint is still far better than its start on fresh placements (+56 points), so the method works. The point is that about a fifth of the headline number is memorisation of the test states. Every number in this paper is measured on the official states *without* ever training, sampling or selecting on them, so our finals should be compared with the "fresh"




Figure 5. **Train-on-test inflation** (LIBERO-10). Left: official vs. fresh placements for the SFT start and the RL checkpoint trained on the official states. Right: the RL checkpoint per task; the loss is concentrated on tasks 4 and 6.

column of such results.

6. Discussion

What we claim. (1) A gated self-improvement loop for VLA policies is safe at this budget: with fresh paired gates no run degrades on the sealed test, including runs whose recipe collapses without the gate. (2) Its gains on LIBERO-Goal are small, one to two points, and cannot be told apart from one round of plain RL at equal compute, at six and at twelve rounds; recursion is the largest ingredient, just under its bar at six rounds and far over it at twelve, where the loop without recursion degrades. (2b) The gate's protection is conditional: it holds for recursive practice at this budget and fails over twelve rounds for practice from a frozen policy. (3) A meta level that edits hyperparameters or harness components does not beat a fixed, tuned recipe, on two studies and two platforms, and the reason is visible in the records: every recipe in the space reaches the same plateau within six rounds. (3b) When the recipe fails, a meta level allowed to edit it restores the loop to the hand-tuned level, $+2.7$ points over the gate alone; this is below the $+3$ bar we registered, and a numeric search over the same knobs lands within 1.2 points of the language model. (4) A published VLA-RL score is inflated by about 17 points by training on the test states.

What we do not claim. We do not claim that recursion lifts a VLA policy at this budget: at twelve rounds it keeps the loop from drifting down, which is a different and smaller thing than a gain, and the verifier's estimate is positive but under its bar. We do not claim that the language model's diagnosis, rather than the knob space it edits, carries the repair: its margin over blind search is $+1.2$ points $[-0.6, +2.9]$, and the registered self-repair bar ($+3$ over the gate alone) was missed at $+2.7$.

For practitioners. Three things in these records can be used directly. A fresh paired gate turns an unsafe self-training recipe into a safe one for the price of one extra evaluation per candidate, and it is the only ingredient whose effect is unambiguous here. Averaged finals and a pooled initial reference are necessary at this scale: a single 500-episode evaluation carries about ± 1.5 points of noise, enough to turn a preliminary pass into a registered fail, which is what happened to our recursion claim. And a language-model meta level is worth its cost only where the recipe can fail; on a tuned recipe its correct diagnoses buy nothing, and on a broken one it finds the repair in the first round where a numeric search needs several, with the same end result within noise.

Limitations. The VLA results are on one simulated benchmark family with a 7B policy and a few-demonstration start; longer horizons, other policies and real robots are untested here (real-robot data collection is in progress). The gate is noisy (sd 3.4 points at 200 episodes), which both limits the meta level and makes the loop conservative; a larger gate costs proportionally more simulation. Evaluation noise on the official test is about ± 1.5 points per evaluation, which is why finals are averaged and why bars below $+2$ would not be readable at this budget. Some runs were continued after hardware or wall-time interruptions, in each case from a completed round with the same plan; the amendments disclose every such event. Finally, preregistration constrains the analysis but not the design: we chose the seed recipe and the harness space, and a different space might leave more for a meta level to find.

7. Conclusion

We set out to learn which part of a self-improvement loop helps a robot policy, and to find out under rules that could not bend to the answer. The answer on LIBERO-Goal is modest and, we think, useful. The gate is the part that matters: it turns a recipe that would collapse into one that never regresses. Recursion and the verifier each add about a point and a half at six rounds, less than the bars we set; at twelve rounds recursion is what keeps the loop from drifting below its start, and it is still not better than one round of plain RL. A meta level that edits the recipe adds nothing while the recipe works, for a reason the records make visible; when the recipe is broken it repairs the loop to the hand-tuned level, $+2.7$ points over the gate alone, short of the $+3$ bar we set and about a point ahead of blind search over the same knobs. Along the way we measured that a published VLA-RL score owes about a fifth of itself to the benchmark's fixed test states. We hope the protocol—sealed tests, fresh placements, averaged finals, public amendments, one read—outlives the particular numbers.

References

[1] Samuel Albanie, James Thewlis, Sébastien Ehrhardt, and João F. Henriques. On the preregistration of machine learning experiments. *NeurIPS Workshop on Preregistration in ML*, 2021. 3

[2] Guhong Chen, Yingcheng Shi, Yongbin Li, Binhua Li, Xander Xu, Hu Wei, Shiwen Ni, Min Yang, and Jieping Ye. EvoTrainer: Co-evolving LLM policies and training harnesses for autonomous agentic reinforcement learning. *arXiv:2606.03108*, 2026. 2, 4

[3] Zixiang Chen, Yihe Deng, Huizhuo Yuan, Kaixuan Ji, and Quanquan Gu. Self-play fine-tuning converts weak language models to strong language models. In *ICML*, 2024. 1, 2

[4] DeepSeek-AI. DeepSeek-R1: Incentivizing reasoning capability in LLMs via reinforcement learning. *arXiv:2501.12948*, 2025. 1, 2

[5] Haoyang Fang, Wei Zhu, Boran Han, Alex Zhang, Zhenyu Pan, Shuo Yang, Shuai Zhang, Jiading Gai, Peng Tang, Cuixiong Hu, Xuan Zhu, Huzefa Rangwala, George Karypis, and Bernie Wang. LLMZero: Discovering adaptive training strategies for RL post-training via LLM agents. *arXiv:2606.18388*, 2026. 3

[6] Caglar Gulcehre, Tom Le Paine, Srivatsan Srinivasan, Ksenia Konyushkova, Lotte Weerts, Abhishek Sharma, Aditya Siddhant, Alex Ahern, Miaosen Wang, Chenjie Gu, et al. Reinforced self-training (ReST) for language modeling. *arXiv:2308.08998*, 2023. 1, 2

[7] Shengran Hu, Cong Lu, and Jeff Clune. Automated design of agentic systems. In *ICLR*, 2025. 2

[8] Juno Kim, Jihun Yun, Jason D. Lee, and Kwang-Sung Jun. Coverage improvement and fast convergence of on-policy preference learning. *arXiv:2601.08421*, 2026. 2

[9] Moo Jin Kim, Karl Pertsch, Siddharth Karamcheti, Ted Xiao, Ashwin Balakrishna, Suraj Nair, Rafael Rafailov, Ethan Foster, Grace Lam, Pannag Sanketi, et al. OpenVLA: An open-source vision-language-action model. In *CoRL*, 2024. 3

[10] Moo Jin Kim, Chelsea Finn, and Percy Liang. Fine-tuning vision-language-action models: Optimizing speed and success. *arXiv:2502.19645*, 2025. 3, 5

[11] Yoonho Lee, Roshen Nair, Qizheng Zhang, Kangwook Lee, Omar Khattab, and Chelsea Finn. Meta-Harness: End-to-end optimization of model harnesses. *arXiv:2603.28052*, 2026. 2, 4

[12] Haozhan Li, Yuxin Zuo, Jiale Yu, Yuhao Zhang, Zhaoyang Yang, Kaiyan Zhang, Xuekai Zhu, Yuchen Zhang, Tianxing Chen, Ganqu Cui, et al. SimpleVLA-RL: Scaling VLA training via reinforcement learning. *arXiv:2509.09674*, 2025. 1, 3, 5

[13] Bo Liu, Yifeng Zhu, Chongkai Gao, Yihao Feng, Qiang Liu, Yuke Zhu, and Peter Stone. LIBERO: Benchmarking knowledge transfer for lifelong robot learning. In *NeurIPS Datasets and Benchmarks*, 2023. 2, 5

[14] Jijia Liu, Feng Gao, Bingwen Wei, Xinlei Chen, Qingmin Liao, Yi Wu, Chao Yu, and Yu Wang. What can RL bring to VLA generalization? an empirical study. *arXiv:2505.19789*, 2025. 1, 3

[15] Chris Lu, Cong Lu, Robert Tjarko Lange, Jakob Foerster, Jeff Clune, and David Ha. The AI scientist: Towards fully automated open-ended scientific discovery. *arXiv:2408.06292*, 2024. 2

[16] Guanxing Lu, Wenkai Guo, Chaoyi Zhang, Yue Zhou, Haonan Jiang, Zifeng Gao, Yansong Tang, and Ziwei Wang. VLA-RL: Towards masterful and general robotic manipulation with scalable reinforcement learning. *arXiv:2505.18719*, 2025. 3

[17] Brian A. Nosek, Charles R. Ebersole, Alexander C. DeHaven, and David T. Mellor. The preregistration revolution. *PNAS*, 115(11):2600–2606, 2018. 3

[18] Alexander Novikov, Ngân Vũ, Marvin Eisenberger, Emilien Dupont, Po-Sen Huang, Adam Zsolt Wagner, Sergey Shirobokov, Borislav Kozlovskii, Francisco J. R. Ruiz, Abbas Mehrabian, et al. AlphaEvolve: A coding agent for scientific and algorithmic discovery. *arXiv:2506.13131*, 2025. 2

[19] Zhihong Shao, Peiyi Wang, Qihao Zhu, Runxin Xu, Junxiao Song, Xiao Bi, Haowei Zhang, Mingchuan Zhang, Y. K. Li, Y. Wu, and Daya Guo. DeepSeekMath: Pushing the limits of mathematical reasoning in open language models. *arXiv:2402.03300*, 2024. 1, 2, 3

[20] Avi Singh, John D. Co-Reyes, Rishabh Agarwal, Ankesh Anand, Piyush Patil, Xavier Garcia, Peter J. Liu, James Harrison, Jaehoon Lee, Kelvin Xu, et al. Beyond human data: Scaling self-training for problem-solving with language models. In *TMLR*, 2024. 2

[21] Weizhe Yuan, Richard Yuanzhe Pang, Kyunghyun Cho, Xian Li, Sainbayar Sukhbaatar, Jing Xu, and Jason Weston. Self-rewarding language models. In *ICML*, 2024. 1, 2

[22] Eric Zelikman, Yuhuai Wu, Jesse Mu, and Noah D. Goodman. STaR: Bootstrapping reasoning with reasoning. In *NeurIPS*, 2022. 2

[23] Andrew Zhao, Yiran Wu, Yang Yue, Tong Wu, Quentin Xu, Matthieu Lin, Shenzhi Wang, Qingyun Wu, Zilong Zheng, and Gao Huang. Absolute zero: Reinforced self-play reasoning with zero data. *arXiv:2505.03335*, 2025. 1, 2