

CENG 2010 - Programming Language Concepts

Week 3: Regular Expressions and Lexical Analysis

Burak Ekici

March 20, 2022

Table of Contents

- 1 Languages
- 2 Compilers and Interpreters
- 3 Pattern Matching and Regular Expressions
- 4 Finite State Automaton
- 5 Lexer

Definitions

- alphabet is finite set; its elements are called symbols or letters

Definitions

- alphabet is finite set; its elements are called symbols or letters
- string over alphabet Σ is finite sequence of elements of Σ

Example

strings over $\Sigma = \{0, 1\}$: 0 0110

Definitions

- alphabet is finite set; its elements are called symbols or letters
- string over alphabet Σ is finite sequence of elements of Σ
- length $|x|$ of string x is number of symbols in x

Example

strings over $\Sigma = \{0, 1\}$: 0 0110

Definitions

- alphabet is finite set; its elements are called symbols or letters
- string over alphabet Σ is finite sequence of elements of Σ
- length $|x|$ of string x is number of symbols in x
- empty string is unique string of length 0 and denoted by ϵ

Example

strings over $\Sigma = \{0, 1\}$: 0 0110

Definitions

- alphabet is finite set; its elements are called symbols or letters
- string over alphabet Σ is finite sequence of elements of Σ
- length $|x|$ of string x is number of symbols in x
- empty string is unique string of length 0 and denoted by ϵ
- Σ^* is set of all strings over Σ ($\emptyset^* = \{\epsilon\}$)

Example

strings over $\Sigma = \{0, 1\}$: 0 0110

Definitions

- alphabet is finite set; its elements are called symbols or letters
- string over alphabet Σ is finite sequence of elements of Σ
- length $|x|$ of string x is number of symbols in x
- empty string is unique string of length 0 and denoted by ϵ
- Σ^* is set of all strings over Σ ($\emptyset^* = \{\epsilon\}$)
- language \mathcal{L} over Σ is subset of Σ^*

Example

strings over $\Sigma = \{0, 1\}$: 0 0110

languages over Σ :

- $\{\epsilon, 0, 1, 00, 01, 10, 11\}$ (all strings having at most two symbols)

Definitions

- alphabet is finite set; its elements are called symbols or letters
- string over alphabet Σ is finite sequence of elements of Σ
- length $|x|$ of string x is number of symbols in x
- empty string is unique string of length 0 and denoted by ϵ
- Σ^* is set of all strings over Σ ($\emptyset^* = \{\epsilon\}$)
- language \mathcal{L} over Σ is subset of Σ^*

Example

strings over $\Sigma = \{0, 1\}$: 0 0110

languages over Σ :

- $\{\epsilon, 0, 1, 00, 01, 10, 11\}$ (all strings having at most two symbols)
- $\{x \mid x \text{ is valid program in some machine language}\}$

Definitions (Operations on Languages)

Let Σ be an alphabet and let $\mathcal{L}, \mathcal{L}_1, \mathcal{L}_2$ be languages over Σ

Definitions (Operations on Languages)

Let Σ be an alphabet and let $\mathcal{L}, \mathcal{L}_1, \mathcal{L}_2$ be languages over Σ

$$\text{Concatenation } \mathcal{L}_1\mathcal{L}_2 \quad := \quad \{xy \mid x \in \mathcal{L}_1 \wedge y \in \mathcal{L}_2\}$$

Definitions (Operations on Languages)

Let Σ be an alphabet and let $\mathcal{L}, \mathcal{L}_1, \mathcal{L}_2$ be languages over Σ

Concatenation $\mathcal{L}_1\mathcal{L}_2 \quad := \quad \{xy \mid x \in \mathcal{L}_1 \wedge y \in \mathcal{L}_2\}$

Union $\mathcal{L}_1 \cup \mathcal{L}_2 \quad := \quad \{x \mid x \in \mathcal{L}_1 \vee x \in \mathcal{L}_2\}$

Definitions (Operations on Languages)

Let Σ be an alphabet and let $\mathcal{L}, \mathcal{L}_1, \mathcal{L}_2$ be languages over Σ

Concatenation $\mathcal{L}_1\mathcal{L}_2 \quad := \quad \{xy \mid x \in \mathcal{L}_1 \wedge y \in \mathcal{L}_2\}$

Union $\mathcal{L}_1 \cup \mathcal{L}_2 \quad := \quad \{x \mid x \in \mathcal{L}_1 \vee x \in \mathcal{L}_2\}$

Intersection $\mathcal{L}_1 \cap \mathcal{L}_2 \quad := \quad \{x \mid x \in \mathcal{L}_1 \wedge x \in \mathcal{L}_2\}$

Definitions (Operations on Languages)

Let Σ be an alphabet and let $\mathcal{L}, \mathcal{L}_1, \mathcal{L}_2$ be languages over Σ

Concatenation $\mathcal{L}_1\mathcal{L}_2 \quad := \quad \{xy \mid x \in \mathcal{L}_1 \wedge y \in \mathcal{L}_2\}$

Union $\mathcal{L}_1 \cup \mathcal{L}_2 \quad := \quad \{x \mid x \in \mathcal{L}_1 \vee x \in \mathcal{L}_2\}$

Intersection $\mathcal{L}_1 \cap \mathcal{L}_2 \quad := \quad \{x \mid x \in \mathcal{L}_1 \wedge x \in \mathcal{L}_2\}$

Kleene star $\Sigma^* = \mathcal{L} \quad := \quad \{x \mid x = \varepsilon \vee x \in \mathcal{L} \vee x \in \mathcal{L}\mathcal{L} \vee x \in \mathcal{L}\mathcal{L}\mathcal{L} \vee \dots\}$

Definitions (Operations on Languages)

Let Σ be an alphabet and let $\mathcal{L}, \mathcal{L}_1, \mathcal{L}_2$ be languages over Σ

Concatenation	$\mathcal{L}_1\mathcal{L}_2$	$:=$	$\{xy \mid x \in \mathcal{L}_1 \wedge y \in \mathcal{L}_2\}$
Union	$\mathcal{L}_1 \cup \mathcal{L}_2$	$:=$	$\{x \mid x \in \mathcal{L}_1 \vee x \in \mathcal{L}_2\}$
Intersection	$\mathcal{L}_1 \cap \mathcal{L}_2$	$:=$	$\{x \mid x \in \mathcal{L}_1 \wedge x \in \mathcal{L}_2\}$
Kleene star	$\Sigma^* = \mathcal{L}$	$:=$	$\{x \mid x = \varepsilon \vee x \in \mathcal{L} \vee x \in \mathcal{L}\mathcal{L} \vee x \in \mathcal{L}\mathcal{L}\mathcal{L} \vee \dots\}$
Kleene plus	Σ^+	$:=$	$\Sigma^* - \{\varepsilon\}$

Example (Operations on Languages)

- let

$$\Sigma = \{a, b, c, d\}$$

$$\mathcal{L}_1 = \{a, ab, c, d, \varepsilon\}$$

$$\mathcal{L}_2 = \{d\}$$

$$\mathcal{L}_3 := \mathcal{L}_1 \mathcal{L}_2$$

$$\mathcal{L}_4 := \mathcal{L}_1 \cup \mathcal{L}_2$$

Example (Operations on Languages)

- let

$$\Sigma = \{a, b, c, d\}$$

$$\mathcal{L}_1 = \{a, ab, c, d, \varepsilon\}$$

$$\mathcal{L}_2 = \{d\}$$

$$\mathcal{L}_3 := \mathcal{L}_1 \mathcal{L}_2$$

$$\mathcal{L}_4 := \mathcal{L}_1 \cup \mathcal{L}_2$$

- which of the following strings are in \mathcal{L}_3 ? – a, abd, cd, d

Example (Operations on Languages)

- let

$$\Sigma = \{a, b, c, d\}$$

$$\mathcal{L}_1 = \{a, ab, c, d, \varepsilon\}$$

$$\mathcal{L}_2 = \{d\}$$

$$\mathcal{L}_3 := \mathcal{L}_1 \mathcal{L}_2$$


$$\mathcal{L}_4 := \mathcal{L}_1 \cup \mathcal{L}_2$$

- which of the following strings are in \mathcal{L}_3 ? – a, abd, cd, d
- which of the following strings are in \mathcal{L}_4 ? – a, abd, cd, d


Table of Contents

- 1 Languages
- 2 Compilers and Interpreters
- 3 Pattern Matching and Regular Expressions
- 4 Finite State Automaton
- 5 Lexer

Architecture of Compilers and Interpreters




Front-End: Lexer and Parser



scanner/lexer : source code \mapsto tokens (keywords, variables, numbers, etc.) regular expressions

Front-End: Lexer and Parser



scanner/lexer	:	source code	→	tokens (keywords, variables, numbers, etc.)	regular expressions
parser	:	tokens	→	ASTs	context free grammars

Implementation (Front-End)

- goal: map program texts into PTs/ASTs

Implementation (Front-End)

- goal: map program texts into PTs/ASTs
- PTs and ASTs are easier to work with – analyze, optimize, execute the program

Implementation (Front-End)

- goal: map program texts into PTs/ASTs
- PTs and ASTs are easier to work with – analyze, optimize, execute the program
- front end use regular expressions at scanning/lexing

Implementation (Front-End)

- goal: map program texts into PTs/ASTs
- PTs and ASTs are easier to work with – analyze, optimize, execute the program
- front end use regular expressions at scanning/lexing
- regular expressions cannot reliably parse paired braces `{ { ... } }` and parentheses `(((...)))`, etc.

Implementation (Front-End)

- goal: map program texts into PTs/ASTs
- PTs and ASTs are easier to work with – analyze, optimize, execute the program
- front end use regular expressions at scanning/lexing
- regular expressions cannot reliably parse paired braces `{ { ... } }` and parentheses `(((...)))`, etc.
- **regular expressions for tokenizing (scanning/lexing)**, and context free grammars for parsing tokens

Table of Contents

- 1 Languages
- 2 Compilers and Interpreters
- 3 Pattern Matching and Regular Expressions**
- 4 Finite State Automaton
- 5 Lexer

Pattern matching is important for

- lexical analysis of programs
- scripting languages (Perl, Ruby)
- search engines (Google Code Search)
- DNA analysis

Applications of Regular expressions: grep

- `grep foo file` returns lines in file containing pattern `foo`

Applications of Regular expressions: grep

- `grep foo file` returns lines in file containing pattern `foo`
- basis for more powerful tools like `awk`, `sed`, `perl`

Applications of Regular expressions: grep

- `grep foo file` returns lines in file containing pattern `foo`
- basis for more powerful tools like `awk`, `sed`, `perl`

Some Patterns

`^` matches beginning of line

Applications of Regular expressions: grep

- `grep foo file` returns lines in file containing pattern `foo`
- basis for more powerful tools like `awk`, `sed`, `perl`

Some Patterns

- `^` matches beginning of line
- `$` matches end of line

Applications of Regular expressions: grep

- `grep foo file` returns lines in file containing pattern `foo`
- basis for more powerful tools like `awk`, `sed`, `perl`

Some Patterns

- | | |
|-----------------|----------------------------------|
| <code>^</code> | matches beginning of line |
| <code>\$</code> | matches end of line |
| <code>c</code> | matches character <code>c</code> |

Applications of Regular expressions: grep

- `grep foo file` returns lines in file containing pattern `foo`
- basis for more powerful tools like `awk`, `sed`, `perl`

Some Patterns

<code>^</code>	matches beginning of line	<code>.</code>	matches any character
<code>\$</code>	matches end of line		
<code>c</code>	matches character <code>c</code>		

Applications of Regular expressions: grep

- `grep foo file` returns lines in file containing pattern `foo`
- basis for more powerful tools like `awk`, `sed`, `perl`

Some Patterns

<code>^</code>	matches beginning of line	<code>.</code>	matches any character
<code>\$</code>	matches end of line	<code>[abc]</code>	matches a or b or c
<code>c</code>	matches character c		

Applications of Regular expressions: grep

- `grep foo file` returns lines in file containing pattern `foo`
- basis for more powerful tools like `awk`, `sed`, `perl`

Some Patterns

<code>^</code>	matches beginning of line	<code>.</code>	matches any character
<code>\$</code>	matches end of line	<code>[abc]</code>	matches a or b or c
<code>c</code>	matches character c	<code>[a-zA-Z]</code>	matches any letter

Applications of Regular expressions: grep

- `grep foo file` returns lines in file containing pattern `foo`
- basis for more powerful tools like `awk`, `sed`, `perl`

Some Patterns

<code>^</code>	matches beginning of line	<code>.</code>	matches any character
<code>\$</code>	matches end of line	<code>[abc]</code>	matches a or b or c
<code>c</code>	matches character c	<code>[a-zA-Z]</code>	matches any letter

Example

`grep "0" file` returns lines containing 0

Applications of Regular expressions: grep

- `grep foo file` returns lines in file containing pattern `foo`
- basis for more powerful tools like `awk`, `sed`, `perl`

Some Patterns

<code>^</code>	matches beginning of line	<code>.</code>	matches any character
<code>\$</code>	matches end of line	<code>[abc]</code>	matches a or b or c
<code>c</code>	matches character c	<code>[a-zA-Z]</code>	matches any letter

Example

```
grep "0" file    returns lines containing 0
grep "0$" file   returns lines ending with 0
```

Applications of Regular expressions: grep

- `grep foo file` returns lines in file containing pattern `foo`
- basis for more powerful tools like `awk`, `sed`, `perl`

Some Patterns

<code>^</code>	matches beginning of line	<code>.</code>	matches any character
<code>\$</code>	matches end of line	<code>[abc]</code>	matches a or b or c
<code>c</code>	matches character c	<code>[a-zA-Z]</code>	matches any letter

Example

```
grep "0" file      returns lines containing 0
grep "0$" file     returns lines ending with 0
grep "b.g" file    returns lines containing e.g. bag, big, bug, buggy
```


Pattern matching is important for

- lexical analysis of programs
- scripting languages (Perl, Ruby)
- search engines (Google Code Search)
- DNA analysis

Definitions

- pattern is string α that represents set of strings $L(\alpha) \subseteq \Sigma^*$

Pattern matching is important for

- lexical analysis of programs
- scripting languages (Perl, Ruby)
- search engines (Google Code Search)
- DNA analysis

Definitions

- pattern is string α that represents set of strings $L(\alpha) \subseteq \Sigma^*$

$$\frac{\text{atomic pattern } \alpha \quad L(\alpha)}{\mathbf{a} \in \Sigma \quad \{a\}}$$

-

Pattern matching is important for

- lexical analysis of programs
- scripting languages (Perl, Ruby)
- search engines (Google Code Search)
- DNA analysis

Definitions

- pattern is string α that represents set of strings $L(\alpha) \subseteq \Sigma^*$

atomic pattern α	$L(\alpha)$
$\mathbf{a} \in \Sigma$	$\{\mathbf{a}\}$
$\boldsymbol{\varepsilon}$	$\{\boldsymbol{\varepsilon}\}$

-

Pattern matching is important for

- lexical analysis of programs
- scripting languages (Perl, Ruby)
- search engines (Google Code Search)
- DNA analysis

Definitions

- pattern is string α that represents set of strings $L(\alpha) \subseteq \Sigma^*$

atomic pattern α	$L(\alpha)$
$\mathbf{a} \in \Sigma$	$\{a\}$
ϵ	$\{\epsilon\}$
• \emptyset	\emptyset

Pattern matching is important for

- lexical analysis of programs
- scripting languages (Perl, Ruby)
- search engines (Google Code Search)
- DNA analysis

Definitions

- pattern is string α that represents set of strings $L(\alpha) \subseteq \Sigma^*$

atomic pattern α	$L(\alpha)$
$\mathbf{a} \in \Sigma$	$\{a\}$
ϵ	$\{\epsilon\}$
• \emptyset	\emptyset
$\#$	Σ

Pattern matching is important for

- lexical analysis of programs
- scripting languages (Perl, Ruby)
- search engines (Google Code Search)
- DNA analysis

Definitions

- pattern is string α that represents set of strings $L(\alpha) \subseteq \Sigma^*$

atomic pattern α	$L(\alpha)$
$\mathbf{a} \in \Sigma$	$\{a\}$
ϵ	$\{\epsilon\}$
• \emptyset	\emptyset
$\#$	Σ
$@$	Σ^*

Pattern matching is important for

- lexical analysis of programs
- search engines (Google Code Search)
- scripting languages (Perl, Ruby)
- DNA analysis

Definitions

- pattern is string α that represents set of strings $L(\alpha) \subseteq \Sigma^*$

atomic pattern α	$L(\alpha)$	compound pattern α	$L(\alpha)$
$a \in \Sigma$	$\{a\}$	$\beta + \gamma$	$L(\beta) \cup L(\gamma)$
ϵ	$\{\epsilon\}$		
\emptyset	\emptyset		
$\#$	Σ		
$@$	Σ^*		

Pattern matching is important for

- lexical analysis of programs
- search engines (Google Code Search)
- scripting languages (Perl, Ruby)
- DNA analysis

Definitions

- pattern is string α that represents set of strings $L(\alpha) \subseteq \Sigma^*$

atomic pattern α	$L(\alpha)$
$a \in \Sigma$	$\{a\}$
ϵ	$\{\epsilon\}$
\emptyset	\emptyset
$\#$	Σ
$@$	Σ^*

compound pattern α	$L(\alpha)$
$\beta + \gamma$	$L(\beta) \cup L(\gamma)$
$\beta \cap \gamma$	$L(\beta) \cap L(\gamma)$

Pattern matching is important for

- lexical analysis of programs
- search engines (Google Code Search)
- scripting languages (Perl, Ruby)
- DNA analysis

Definitions

- pattern is string α that represents set of strings $L(\alpha) \subseteq \Sigma^*$

atomic pattern α	$L(\alpha)$	compound pattern α	$L(\alpha)$
$a \in \Sigma$	$\{a\}$	$\beta + \gamma$	$L(\beta) \cup L(\gamma)$
ϵ	$\{\epsilon\}$	$\beta \cap \gamma$	$L(\beta) \cap L(\gamma)$
\emptyset	\emptyset	$\beta \gamma$	$L(\beta)L(\gamma)$
$\#$	Σ		
$@$	Σ^*		

Pattern matching is important for

- lexical analysis of programs
- search engines (Google Code Search)
- scripting languages (Perl, Ruby)
- DNA analysis

Definitions

- pattern is string α that represents set of strings $L(\alpha) \subseteq \Sigma^*$

atomic pattern α	$L(\alpha)$	compound pattern α	$L(\alpha)$
$\mathbf{a} \in \Sigma$	$\{a\}$	$\beta + \gamma$	$L(\beta) \cup L(\gamma)$
ϵ	$\{\epsilon\}$	$\beta \cap \gamma$	$L(\beta) \cap L(\gamma)$
• \emptyset	\emptyset	$\beta\gamma$	$L(\beta)L(\gamma)$
$\#$	Σ	β^*	$L(\beta)^*$
$@$	Σ^*		

Pattern matching is important for

- lexical analysis of programs
- search engines (Google Code Search)
- scripting languages (Perl, Ruby)
- DNA analysis

Definitions

- pattern is string α that represents set of strings $L(\alpha) \subseteq \Sigma^*$

atomic pattern α	$L(\alpha)$	compound pattern α	$L(\alpha)$
$\mathbf{a} \in \Sigma$	$\{a\}$	$\beta + \gamma$	$L(\beta) \cup L(\gamma)$
ϵ	$\{\epsilon\}$	$\beta \cap \gamma$	$L(\beta) \cap L(\gamma)$
• \emptyset	\emptyset	$\beta\gamma$	$L(\beta)L(\gamma)$
$\#$	Σ	β^*	$L(\beta)^*$
$@$	Σ^*	β^+	$L(\beta)^+$

Pattern matching is important for

- lexical analysis of programs
- search engines (Google Code Search)
- scripting languages (Perl, Ruby)
- DNA analysis

Definitions

- pattern is string α that represents set of strings $L(\alpha) \subseteq \Sigma^*$

atomic pattern α	$L(\alpha)$	compound pattern α	$L(\alpha)$
$\mathbf{a} \in \Sigma$	$\{a\}$	$\beta + \gamma$	$L(\beta) \cup L(\gamma)$
ϵ	$\{\epsilon\}$	$\beta \cap \gamma$	$L(\beta) \cap L(\gamma)$
• \emptyset	\emptyset	$\beta\gamma$	$L(\beta)L(\gamma)$
$\#$	Σ	β^*	$L(\beta)^*$
$@$	Σ^*	β^+	$L(\beta)^+$
		$\sim \beta$	$\sim L(\beta) = \Sigma^* - L(\beta)$

Pattern matching is important for

- lexical analysis of programs
- search engines (Google Code Search)
- scripting languages (Perl, Ruby)
- DNA analysis

Definitions

- pattern is string α that represents set of strings $L(\alpha) \subseteq \Sigma^*$

atomic pattern α	$L(\alpha)$	compound pattern α	$L(\alpha)$
$\mathbf{a} \in \Sigma$	$\{a\}$	$\beta + \gamma$	$L(\beta) \cup L(\gamma)$
ϵ	$\{\epsilon\}$	$\beta \cap \gamma$	$L(\beta) \cap L(\gamma)$
• \emptyset	\emptyset	$\beta\gamma$	$L(\beta)L(\gamma)$
$\#$	Σ	β^*	$L(\beta)^*$
$@$	Σ^*	β^+	$L(\beta)^+$
		$\sim \beta$	$\sim L(\beta) = \Sigma^* - L(\beta)$

- string $x \in \Sigma^*$ **matches** pattern α if $x \in L(\alpha)$

Example

pattern	matched string
@a@a@a@	strings containing at least 3 occurrences of a

Example

pattern	matched string
@a@a@a@	strings containing at least 3 occurrences of <i>a</i>
@a@b@	strings containing <i>a</i> followed later by <i>b</i>

Example

pattern	matched string
@a@a@a@	strings containing at least 3 occurrences of <i>a</i>
@a@b@	strings containing <i>a</i> followed later by <i>b</i>
#n ~ a	single letters except <i>a</i>

Example

pattern	matched string
@a@a@a@	strings containing at least 3 occurrences of <i>a</i>
@a@b@	strings containing <i>a</i> followed later by <i>b</i>
#n ~ <i>a</i>	single letters except <i>a</i>
(#n ~ <i>a</i>)*	strings without <i>a</i>

Questions

- which operators are **redundant**?

Questions

- which operators are **redundant**?

$$\epsilon \quad \equiv \quad \sim (\# @) \equiv \emptyset^*$$

Questions

- which operators are **redundant**?

$$\begin{array}{lcl} \epsilon & \equiv & \sim (\# @) \equiv \emptyset^* \\ @ & \equiv & \#^* \end{array}$$

Questions

- which operators are **redundant**?

$$\begin{array}{lcl} \epsilon & \equiv & \sim (\# @) \equiv \emptyset^* \\ @ & \equiv & \#^* \\ \alpha^+ & \equiv & \alpha \alpha^* \end{array}$$

Questions

- which operators are **redundant**?

$$\epsilon \equiv \sim (\# @) \equiv \emptyset^*$$

$$@ \equiv \#^*$$

$$\alpha^+ \equiv \alpha\alpha^*$$

$$\# \equiv a_1 \dots a_n \quad \text{if } \Sigma = \{a_1 \dots a_n\}$$

Questions

- which operators are **redundant**?

$$\begin{array}{lll} \epsilon & \equiv & \sim (\# @) \equiv \emptyset^* \\ @ & \equiv & \#^* \\ \alpha^+ & \equiv & \alpha \alpha^* \\ \# & \equiv & a_1 \dots a_n \quad \text{if } \Sigma = \{a_1 \dots a_n\} \\ \alpha \cap \beta & \equiv & \sim (\sim \alpha + \sim \beta) \end{array}$$

Questions

- which operators are **redundant**?

ϵ	\equiv	$\sim (\# @) \equiv \emptyset^*$	
$@$	\equiv	$\#^*$	
α^+	\equiv	$\alpha\alpha^*$	
$\#$	\equiv	$a_1 \dots a_n$	if $\Sigma = \{a_1 \dots a_n\}$
$\alpha \cap \beta$	\equiv	$\sim (\sim \alpha + \sim \beta)$	
$\sim \alpha$	\equiv	$?$	

Questions

- which operators are **redundant**?

ϵ	\equiv	$\sim (\# @) \equiv \emptyset^*$	
$@$	\equiv	$\#^*$	
α^+	\equiv	$\alpha\alpha^*$	
$\#$	\equiv	$a_1 \dots a_n$	if $\Sigma = \{a_1 \dots a_n\}$
$\alpha \cap \beta$	\equiv	$\sim (\sim \alpha + \sim \beta)$	
$\sim \alpha$	\equiv	$?$	

Notation

$\alpha \equiv \beta$ if $L(\alpha) = L(\beta)$

Definition

regular expressions are restricted patterns which use only

$$a \in \Sigma \quad \epsilon \quad \emptyset \quad \alpha + \beta \quad \alpha^* \quad \alpha\beta$$

Definition

regular expressions are restricted patterns which use only

$$\mathbf{a} \in \Sigma \quad \epsilon \quad \emptyset \quad \alpha + \beta \quad \alpha^* \quad \alpha\beta$$

Remark (Precedence)

Kleene closure $*$ > concatenation > union $+$

$$\begin{aligned} \mathbf{ab + c} &:= (\mathbf{ab}) + \mathbf{c} &= \{ab, c\} \\ \mathbf{ab^*} &:= \mathbf{a(b^*)} &= \{a, ab, abb, \dots\} \\ \mathbf{a + b^*} &:= \mathbf{a + (b^*)} &= \{a, \epsilon, b, bb, bbb, \dots\} \end{aligned}$$

Definition

a language A is called regular if it is generated by a regular expression α . Namely $A = L(\alpha)$

Example

$$\begin{array}{lll} \mathbf{a} & & = \{a\} \\ \mathbf{a + b} & := \{a\} \cup \{b\} & = \{a, b\} \\ \mathbf{a^*} & := \{\epsilon\} \cup \{a\} \cup \{aa\} \cup \{aaa\} \cup \dots & = \{\epsilon, a, aa, aaa, \dots\} \\ \mathbf{ab^*(c + \epsilon)} & & = \{a, ac, ab, abc, abb, abbc, \dots\} \end{array}$$

Theorem

patterns, and regular expressions and regular languages are **equivalent**:

Theorem

patterns, and regular expressions and regular languages are **equivalent**:

- for all $A \subseteq \Sigma^*$
- ① A is regular
 - \iff ② $A = L(\alpha)$ for some pattern α
 - \iff ③ $A = L(\alpha)$ for some regular expression α

Implementing Regular Expressions

- by finite automaton – “machines” recognize regular languages

Implementing Regular Expressions

- by finite automaton – “machines” recognize regular languages




Table of Contents

- 1 Languages
- 2 Compilers and Interpreters
- 3 Pattern Matching and Regular Expressions
- 4 Finite State Automaton**
- 5 Lexer

Definitions

- **deterministic finite automaton (DFA)** is quintuple $M = (Q, \Sigma, \delta, s, F)$ with

Definitions

- **deterministic finite automaton (DFA)** is quintuple $M = (Q, \Sigma, \delta, s, F)$ with
 - 1 Q : finite set of states

Definitions


- **deterministic finite automaton (DFA)** is quintuple $M = (Q, \Sigma, \delta, s, F)$ with
 - 1 Q : finite set of states
 - 2 Σ : input alphabet

Definitions

- **deterministic finite automaton (DFA)** is quintuple $M = (Q, \Sigma, \delta, s, F)$ with
 - ① Q : finite set of states
 - ② Σ : input alphabet
 - ③ $\delta: Q \times \Sigma \rightarrow Q$: transition function


Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$



Example (DFAs → Regular Sets)


$M = (Q, \Sigma, \delta, s, F)$



① $Q = \{1, 2, 3, 4\}$

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$




① $Q = \{1, 2, 3, 4\}$

② $\Sigma = \{a, b\}$

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$




① $Q = \{1, 2, 3, 4\}$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$



① $Q = \{1, 2, 3, 4\}$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

Definitions


- **deterministic finite automaton (DFA)** is quintuple $M = (Q, \Sigma, \delta, s, F)$ with
 - ① Q : finite set of states
 - ② Σ : input alphabet
 - ③ $\delta : Q \times \Sigma \rightarrow Q$: transition function
 - ④ $s \in Q$: start state

Definitions

- **deterministic finite automaton (DFA)** is quintuple $M = (Q, \Sigma, \delta, s, F)$ with
 - ① Q : finite set of states
 - ② Σ : input alphabet
 - ③ $\delta : Q \times \Sigma \rightarrow Q$: transition function
 - ④ $s \in Q$: start state
 - ⑤ $F \subseteq Q$: final (accept) states

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$



① $Q = \{1, 2, 3, 4\}$


② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$



① $Q = \{1, 2, 3, 4\}$

② $\Sigma = \{a, b\}$


③ $\delta : Q \times \Sigma \rightarrow Q$

④ $s = 1$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$



① $Q = \{1, 2, 3, 4\}$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$


④ $s = 1$

⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$



① $Q = \{1, 2, 3, 4\}$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$


④ $s = 1$

⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

b a b a a
1 1 2 3 4 4

Example (DFAs → Regular Sets)


 $M = (Q, \Sigma, \delta, s, F)$ ① $Q = \{1, 2, 3, 4\}$ ② $\Sigma = \{a, b\}$ ③ $\delta : Q \times \Sigma \rightarrow Q$ ④ $s = 1$ ⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

b a b a a

1 1 2 3 4 4

Example (DFAs → Regular Sets)

 $M = (Q, \Sigma, \delta, s, F)$ 


- ① $Q = \{1, 2, 3, 4\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

b **a** **b** **a** **a**
1 1 2 3 4 4

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q = \{1, 2, 3, 4\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

b a b a a
1 1 2 3 4 4

Example (DFAs → Regular Sets)


$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3, 4\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4


Example (DFAs → Regular Sets)

 $M = (Q, \Sigma, \delta, s, F)$ ① $Q = \{1, 2, 3, 4\}$ ② $\Sigma = \{a, b\}$ ③ $\delta : Q \times \Sigma \rightarrow Q$ ④ $s = 1$ ⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q = \{1, 2, 3, 4\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

b a b a a
1 1 2 3 4 4


Example (DFAs → Regular Sets)

 $M = (Q, \Sigma, \delta, s, F)$ ① $Q = \{1, 2, 3, 4\}$ ② $\Sigma = \{a, b\}$ ③ $\delta : Q \times \Sigma \rightarrow Q$ ④ $s = 1$ ⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q = \{1, 2, 3, 4\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

b a b a a
1 1 2 3 4 4

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3, 4\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{4\}$


δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

b a b a a

1 1 2 3 4 4

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$



① $Q = \{1, 2, 3, 4\}$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$


④ $s = 1$

⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q = \{1, 2, 3, 4\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q = \{1, 2, 3, 4\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

b a b a a
1 1 2 3 4 4

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$



① $Q = \{1, 2, 3, 4\}$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$


④ $s = 1$

⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

b a b a a
1 1 2 3 4 4


Example (DFAs → Regular Sets)

 $M = (Q, \Sigma, \delta, s, F)$ 

- ① $Q = \{1, 2, 3, 4\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{4\}$


Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3, 4\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{4\}$

Example (DFAs → Regular Sets)

 $M = (Q, \Sigma, \delta, s, F)$ 


- ① $Q = \{1, 2, 3, 4\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

	b	a	b	a	a
1	1	2	3	4	4
	a	a	b	b	b
1	2	2	3	1	1

Example (DFAs → Regular Sets)


$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3, 4\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{4\}$

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$



① $Q = \{1, 2, 3, 4\}$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$


④ $s = 1$

⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

	b	a	b	a	a
1	1	2	3	4	4
	a	a	b	b	b
1	2	2	3	1	1


Example (DFAs → Regular Sets)

 $M = (Q, \Sigma, \delta, s, F)$ 

- ① $Q = \{1, 2, 3, 4\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{4\}$

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$



① $Q = \{1, 2, 3, 4\}$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$


④ $s = 1$

⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

	b	a	b	a	a
1	1	2	3	4	4
	a	a	b	b	b
1	2	2	3	1	1

Example (DFAs → Regular Sets)


 $M = (Q, \Sigma, \delta, s, F)$ ① $Q = \{1, 2, 3, 4\}$ ② $\Sigma = \{a, b\}$ ③ $\delta : Q \times \Sigma \rightarrow Q$ ④ $s = 1$ ⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

	b	a	b	a	a
1	1	2	3	4	4
	a	a	b	b	b
1	2	2	3	1	1

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q = \{1, 2, 3, 4\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4


	b	a	b	a	a
1	1	2	3	4	4
	a	a	b	b	b
1	2	2	3	1	1

Example (DFAs → Regular Sets)

 $M = (Q, \Sigma, \delta, s, F)$ ① $Q = \{1, 2, 3, 4\}$ ② $\Sigma = \{a, b\}$ ③ $\delta : Q \times \Sigma \rightarrow Q$ ④ $s = 1$ ⑤ $F = \{4\}$

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$



① $Q = \{1, 2, 3, 4\}$


② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$

④ $s = 1$


⑤ $F = \{4\}$

Example (DFAs → Regular Sets)

 $M = (Q, \Sigma, \delta, s, F)$ ① $Q = \{1, 2, 3, 4\}$ ② $\Sigma = \{a, b\}$ ③ $\delta : Q \times \Sigma \rightarrow Q$ ④ $s = 1$ ⑤ $F = \{4\}$

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$



① $Q = \{1, 2, 3, 4\}$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$

④ $s = 1$

⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

	b	a	b	a	a
1	1	2	3	4	4
	a	a	b	b	b
1	2	2	3	1	1

Definitions

- **deterministic finite automaton (DFA)** is quintuple $M = (Q, \Sigma, \delta, s, F)$ with

- ① Q : finite set of states
- ② Σ : input alphabet
- ③ $\delta: Q \times \Sigma \rightarrow Q$: transition function
- ④ $s \in Q$: start state
- ⑤ $F \subseteq Q$: final (accept) states

- $\hat{\delta}: Q \times \Sigma^* \rightarrow Q$ is inductively defined by

$$\hat{\delta}(q, \varepsilon) := q$$

$$\hat{\delta}(q, xa) := \delta(\hat{\delta}(q, x), a)$$

Example (Unfolding of the multistep function $\widehat{\delta}$)

Let $x = abbaab$ over the alphabet $\Sigma = \{a, b\}$

Example (Unfolding of the multistep function $\widehat{\delta}$)

Let $x = abbaab$ over the alphabet $\Sigma = \{a, b\}$

$$\delta(\widehat{\delta}(q_0, abbaa), b)$$

first recursive call

Example (Unfolding of the multistep function $\widehat{\delta}$)

Let $x = abbaab$ over the alphabet $\Sigma = \{a, b\}$

$$\delta(\widehat{\delta}(q_0, abbaa), b)$$

first recursive call

$$\delta(\delta(\widehat{\delta}(q_0, abba), a), b)$$

second recursive call

Example (Unfolding of the multistep function $\widehat{\delta}$)

Let $x = abbaab$ over the alphabet $\Sigma = \{a, b\}$

$\delta(\widehat{\delta}(q_0, abbaa), b)$

first recursive call

$\delta(\delta(\widehat{\delta}(q_0, abba), a), b)$

second recursive call

$\delta(\delta(\delta(\widehat{\delta}(q_0, abb), a), a), b)$

third recursive call

Example (Unfolding of the multistep function $\widehat{\delta}$)

Let $x = abbaab$ over the alphabet $\Sigma = \{a, b\}$

$$\delta(\widehat{\delta}(q_0, abbaa), b)$$

first recursive call

$$\delta(\delta(\widehat{\delta}(q_0, abba), a), b)$$

second recursive call

$$\delta(\delta(\delta(\widehat{\delta}(q_0, abb), a), a), b)$$

third recursive call

$$\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, ab), b), a), a), b)$$

fourth recursive call

Example (Unfolding of the multistep function $\widehat{\delta}$)

Let $x = abbaab$ over the alphabet $\Sigma = \{a, b\}$

$\delta(\widehat{\delta}(q_0, abbaa), b)$

first recursive call

$\delta(\delta(\widehat{\delta}(q_0, abba), a), b)$

second recursive call

$\delta(\delta(\delta(\widehat{\delta}(q_0, abb), a), a), b)$

third recursive call

$\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, ab), b), a), a), b)$

fourth recursive call

$\delta(\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, a), b), b), a), a), b)$

fifth recursive call

Example (Unfolding of the multistep function $\widehat{\delta}$)

Let $x = abbaab$ over the alphabet $\Sigma = \{a, b\}$

$\delta(\widehat{\delta}(q_0, abbaa), b)$	first recursive call
$\delta(\delta(\widehat{\delta}(q_0, abba), a), b)$	second recursive call
$\delta(\delta(\delta(\widehat{\delta}(q_0, abb), a), a), b)$	third recursive call
$\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, ab), b), a), a), b)$	fourth recursive call
$\delta(\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, a), b), b), a), a), b)$	fifth recursive call
$\delta(\delta(\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, \varepsilon), a), b), b), a), a), b)$	sixth recursive call

Example (Unfolding of the multistep function $\widehat{\delta}$)

Let $x = abbaab$ over the alphabet $\Sigma = \{a, b\}$

$\delta(\widehat{\delta}(q_0, abbaa), b)$	first recursive call
$\delta(\delta(\widehat{\delta}(q_0, abba), a), b)$	second recursive call
$\delta(\delta(\delta(\widehat{\delta}(q_0, abb), a), a), b)$	third recursive call
$\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, ab), b), a), a), b)$	fourth recursive call
$\delta(\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, a), b), b), a), a), b)$	fifth recursive call
$\delta(\delta(\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, \varepsilon), a), b), b), a), a), b)$	sixth recursive call
$\delta(\delta(\delta(\delta(\delta(\delta(\delta(q_0, a), b), b), a), a), b)$	

Example (Unfolding of the multistep function $\widehat{\delta}$)

Let $x = abbaab$ over the alphabet $\Sigma = \{a, b\}$

$\delta(\widehat{\delta}(q_0, abbaa), b)$	first recursive call
$\delta(\delta(\widehat{\delta}(q_0, abba), a), b)$	second recursive call
$\delta(\delta(\delta(\widehat{\delta}(q_0, abb), a), a), b)$	third recursive call
$\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, ab), b), a), a), b)$	fourth recursive call
$\delta(\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, a), b), b), a), a), b)$	fifth recursive call
$\delta(\delta(\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, \varepsilon), a), b), b), a), a), b)$	sixth recursive call
$\delta(\delta(\delta(\delta(\delta(\delta(q_0, a), b), b), a), a), b)$	
$\delta(\delta(\delta(\delta(\delta(q_1, b), b), a), a), b)$	assuming $\delta(q_0, a) = q_1$

Example (Unfolding of the multistep function $\widehat{\delta}$)

Let $x = abbaab$ over the alphabet $\Sigma = \{a, b\}$

$\delta(\widehat{\delta}(q_0, abbaa), b)$	first recursive call
$\delta(\delta(\widehat{\delta}(q_0, abba), a), b)$	second recursive call
$\delta(\delta(\delta(\widehat{\delta}(q_0, abb), a), a), b)$	third recursive call
$\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, ab), b), a), a), b)$	fourth recursive call
$\delta(\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, a), b), b), a), a), b)$	fifth recursive call
$\delta(\delta(\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, \epsilon), a), b), b), a), a), b)$	sixth recursive call
$\delta(\delta(\delta(\delta(\delta(q_0, a), b), b), a), a), b)$	
$\delta(\delta(\delta(\delta(q_1, b), b), a), a), b)$	assuming $\delta(q_0, a) = q_1$
$\delta(\delta(\delta(q_2, b), a), a), b)$	assuming $\delta(q_1, b) = q_2$

Example (Unfolding of the multistep function $\widehat{\delta}$)

Let $x = abbaab$ over the alphabet $\Sigma = \{a, b\}$

$\delta(\widehat{\delta}(q_0, abbaa), b)$	first recursive call
$\delta(\delta(\widehat{\delta}(q_0, abba), a), b)$	second recursive call
$\delta(\delta(\delta(\widehat{\delta}(q_0, abb), a), a), b)$	third recursive call
$\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, ab), b), a), a), b)$	fourth recursive call
$\delta(\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, a), b), b), a), a), b)$	fifth recursive call
$\delta(\delta(\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, \epsilon), a), b), b), a), a), b)$	sixth recursive call
$\delta(\delta(\delta(\delta(\delta(q_0, a), b), b), a), a), b)$	
$\delta(\delta(\delta(\delta(q_1, b), b), a), a), b)$	assuming $\delta(q_0, a) = q_1$
$\delta(\delta(\delta(q_2, b), a), a), b)$	assuming $\delta(q_1, b) = q_2$
$\delta(\delta(\delta(q_3, a), a), b)$	assuming $\delta(q_2, b) = q_3$

Example (Unfolding of the multistep function $\widehat{\delta}$)

Let $x = abbaab$ over the alphabet $\Sigma = \{a, b\}$

$\delta(\widehat{\delta}(q_0, abbaa), b)$	first recursive call
$\delta(\delta(\widehat{\delta}(q_0, abba), a), b)$	second recursive call
$\delta(\delta(\delta(\widehat{\delta}(q_0, abb), a), a), b)$	third recursive call
$\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, ab), b), a), a), b)$	fourth recursive call
$\delta(\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, a), b), b), a), a), b)$	fifth recursive call
$\delta(\delta(\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, \varepsilon), a), b), b), a), a), b)$	sixth recursive call
$\delta(\delta(\delta(\delta(\delta(q_0, a), b), b), a), a), b)$	
$\delta(\delta(\delta(\delta(q_1, b), b), a), a), b)$	assuming $\delta(q_0, a) = q_1$
$\delta(\delta(\delta(q_2, b), a), a), b)$	assuming $\delta(q_1, b) = q_2$
$\delta(\delta(q_3, a), a), b)$	assuming $\delta(q_2, b) = q_3$
$\delta(\delta(q_4, a), b)$	assuming $\delta(q_3, a) = q_4$

Example (Unfolding of the multistep function $\widehat{\delta}$)

Let $x = abbaab$ over the alphabet $\Sigma = \{a, b\}$

$\delta(\widehat{\delta}(q_0, abbaa), b)$	first recursive call
$\delta(\delta(\widehat{\delta}(q_0, abba), a), b)$	second recursive call
$\delta(\delta(\delta(\widehat{\delta}(q_0, abb), a), a), b)$	third recursive call
$\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, ab), b), a), a), b)$	fourth recursive call
$\delta(\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, a), b), b), a), a), b)$	fifth recursive call
$\delta(\delta(\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, \varepsilon), a), b), b), a), a), b)$	sixth recursive call
$\delta(\delta(\delta(\delta(\delta(q_0, a), b), b), a), a), b)$	
$\delta(\delta(\delta(\delta(q_1, b), b), a), a), b)$	assuming $\delta(q_0, a) = q_1$
$\delta(\delta(\delta(q_2, b), a), a), b)$	assuming $\delta(q_1, b) = q_2$
$\delta(\delta(q_3, a), a), b)$	assuming $\delta(q_2, b) = q_3$
$\delta(q_4, a), b)$	assuming $\delta(q_3, a) = q_4$
$\delta(q_5, b)$	assuming $\delta(q_4, a) = q_5$

Example (Unfolding of the multistep function $\widehat{\delta}$)

Let $x = abbaab$ over the alphabet $\Sigma = \{a, b\}$

$\delta(\widehat{\delta}(q_0, abbaa), b)$

first recursive call

$\delta(\delta(\widehat{\delta}(q_0, abba), a), b)$

second recursive call

$\delta(\delta(\delta(\widehat{\delta}(q_0, abb), a), a), b)$

third recursive call

$\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, ab), b), a), a), b)$

fourth recursive call

$\delta(\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, a), b), b), a), a), b)$

fifth recursive call

$\delta(\delta(\delta(\delta(\delta(\delta(\widehat{\delta}(q_0, \epsilon), a), b), b), a), a), b)$

sixth recursive call

$\delta(\delta(\delta(\delta(\delta(\delta(q_0, a), b), b), a), a), b)$

$\delta(\delta(\delta(\delta(q_1, b), b), a), a), b)$

assuming $\delta(q_0, a) = q_1$

$\delta(\delta(\delta(q_2, b), a), a), b)$

assuming $\delta(q_1, b) = q_2$

$\delta(\delta(\delta(q_3, a), a), b)$

assuming $\delta(q_2, b) = q_3$

$\delta(\delta(q_4, a), b)$

assuming $\delta(q_3, a) = q_4$

$\delta(q_5, b)$

assuming $\delta(q_4, a) = q_5$

assuming $\delta(q_5, b) = q_6$

q_6

Definitions

- **deterministic finite automaton (DFA)** is quintuple $M = (Q, \Sigma, \delta, s, F)$ with

- ① Q : finite set of states
- ② Σ : input alphabet
- ③ $\delta : Q \times \Sigma \rightarrow Q$: transition function
- ④ $s \in Q$: start state
- ⑤ $F \subseteq Q$: final (accept) states

- $\hat{\delta} : Q \times \Sigma^* \rightarrow Q$ is inductively defined by

$$\hat{\delta}(q, \varepsilon) := q$$

$$\hat{\delta}(q, xa) := \delta(\hat{\delta}(q, x), a)$$

- string $x \in \Sigma^*$ is **accepted** by M if $\hat{\delta}(s, x) \in F$

Definitions

- **deterministic finite automaton (DFA)** is quintuple $M = (Q, \Sigma, \delta, s, F)$ with

- ① Q : finite set of states
- ② Σ : input alphabet
- ③ $\delta : Q \times \Sigma \rightarrow Q$: transition function
- ④ $s \in Q$: start state
- ⑤ $F \subseteq Q$: final (accept) states

- $\hat{\delta} : Q \times \Sigma^* \rightarrow Q$ is inductively defined by


$$\hat{\delta}(q, \varepsilon) := q$$

$$\hat{\delta}(q, xa) := \delta(\hat{\delta}(q, x), a)$$

- string $x \in \Sigma^*$ is **accepted** by M if $\hat{\delta}(s, x) \in F$
- string $x \in \Sigma^*$ is **rejected** by M if $\hat{\delta}(s, x) \notin F$

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3, 4\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

	b	a	b	a	a	$\in L(M)$
1	1	2	3	4	4	
	a	a	b	b	b	$\notin L(M)$
1	2	2	3	1	1	

Definitions

- **deterministic finite automaton (DFA)** is quintuple $M = (Q, \Sigma, \delta, s, F)$ with

- ① Q : finite set of states
- ② Σ : input alphabet
- ③ $\delta : Q \times \Sigma \rightarrow Q$: transition function
- ④ $s \in Q$: start state
- ⑤ $F \subseteq Q$: final (accept) states

- $\hat{\delta} : Q \times \Sigma^* \rightarrow Q$ is inductively defined by


$$\hat{\delta}(q, \varepsilon) := q$$

$$\hat{\delta}(q, xa) := \delta(\hat{\delta}(q, x), a)$$

- string $x \in \Sigma^*$ is **accepted** by M if $\hat{\delta}(s, x) \in F$
- string $x \in \Sigma^*$ is **rejected** by M if $\hat{\delta}(s, x) \notin F$
- language accepted by M is given by $L(M) := \{x \mid \hat{\delta}(s, x) \in F\}$

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3, 4\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4


	b	a	b	a	a	$\in L(M)$
1	1	2	3	4	4	
	a	a	b	b	b	$\notin L(M)$
1	2	2	3	1	1	

$L(M) := \{x \mid$

$\}$

Example (DFAs → Regular Sets)

$M = (Q, \Sigma, \delta, s, F)$



① $Q = \{1, 2, 3, 4\}$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$

④ $s = 1$

⑤ $F = \{4\}$

δ	a	b
1	2	1
2	2	3
3	4	1
4	4	4

b a b a a $\in L(M)$

1 1 2 3 4 4

a a b b b $\notin L(M)$

1 2 2 3 1 1

$L(M) := \{x \mid x \text{ contains } aba \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$

② $\Sigma = \{a, b\}$

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$

① $Q =$

② $\Sigma = \{a, b\}$

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$

① $Q =$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$

- ① $Q =$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s =$

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$

① $Q =$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$

④ $s =$

⑤ $F =$

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$

$M \text{ start} \rightarrow \textcircled{1}$

① $Q =$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$

④ $s =$

⑤ $F =$

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$

$M \text{ start} \rightarrow \textcircled{1} \quad \textcircled{2}$

① $Q =$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$


④ $s =$

⑤ $F =$

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q =$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s =$
- ⑤ $F =$

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q =$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s =$
- ⑤ $F =$

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q =$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s =$
- ⑤ $F =$

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q =$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s =$
- ⑤ $F =$

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$


Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q =$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s =$
- ⑤ $F =$

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ ① $Q = \{1, 2\}$ ② $\Sigma = \{a, b\}$ ③ $\delta : Q \times \Sigma \rightarrow Q$ ④ $s = 1$ ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1


 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ ① $Q = \{1, 2\}$ ② $\Sigma = \{a, b\}$ ③ $\delta : Q \times \Sigma \rightarrow Q$ ④ $s = 1$ ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

	a	b	a	b	a
1	1	2	2	1	1

 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$


Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ ① $Q = \{1, 2\}$ ② $\Sigma = \{a, b\}$ ③ $\delta : Q \times \Sigma \rightarrow Q$ ④ $s = 1$ ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

a b a b a

1 1 2 2 1 1

 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 


- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

a b a b a

1 1 2 2 1 1

 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$


Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ ① $Q = \{1, 2\}$ ② $\Sigma = \{a, b\}$ ③ $\delta : Q \times \Sigma \rightarrow Q$ ④ $s = 1$ ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

a b a b a

1 1 2 2 1 1

 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 


- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

a b a b a

1 1 2 2 1 1


 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 

- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{2\}$

δ	a	b
1	1	2
2	2	1

 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ ① $Q = \{1, 2\}$ ② $\Sigma = \{a, b\}$ ③ $\delta : Q \times \Sigma \rightarrow Q$ ④ $s = 1$ ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

a b a b a

1 1 2 2 1 1


 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

$$M = (Q, \Sigma, \delta, s, F)$$


- | δ | a | b |
|----------|---|---|
| 1 | 1 | 2 |
| 2 | 2 | 1 |

1 1 2 2 1 1

$$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 


- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

a b a b a

1 1 2 2 1 1

 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 


- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

a b a b a

1 1 2 2 1 1

 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$


Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ ① $Q = \{1, 2\}$ ② $\Sigma = \{a, b\}$ ③ $\delta : Q \times \Sigma \rightarrow Q$ ④ $s = 1$ ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

a b a b a

1 1 2 2 1 1

 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 


- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

a b a b a

1 1 2 2 1 1

 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$


Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 

- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

a b a b a $\in L(M)$
1 1 2 2 1 1

 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$


Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 

- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

a b a b a $\in L(M)$
1 1 2 2 1 1
b a a a a
1 2 2 2 2 2

 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 

- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$


δ	a	b
1	1	2
2	2	1

a b a b a $\in L(M)$
1 2 2 1 1
b a a a a
1 2 2 2 2

 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$


δ	a	b
1	1	2
2	2	1

$a \quad b \quad a \quad b \quad a \quad \in L(M)$
 1 2 2 1 1
 $b \quad a \quad a \quad a \quad a$
 1 2 2 2 2

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

$a \quad b \quad a \quad b \quad a \quad \in L(M)$
 1 2 2 1 1
 $b \quad a \quad a \quad a \quad a$
 1 2 2 2 2

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$


Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 

- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

a b a b a $\in L(M)$
1 2 2 1 1
b a a a a
1 2 2 2 2 2

 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 

- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

$a \quad b \quad a \quad b \quad a \quad \in L(M)$

1 2 2 1 1


$b \quad a \quad a \quad a \quad a$

1 2 2 2 2

 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

$a \quad b \quad a \quad b \quad a \quad \in L(M)$
 1 2 2 1 1
 $b \quad a \quad a \quad a \quad a$
 1 2 2 2 2

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 

- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1


$a \quad b \quad a \quad b \quad a \quad \in L(M)$

1 2 2 1 1

$b \quad a \quad a \quad a \quad a$

1 2 2 2 2 2

 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$


Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 

- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

$a \quad b \quad a \quad b \quad a \quad \in L(M)$
1 2 2 1 1
 $b \quad a \quad a \quad a \quad a$
1 2 2 2 2

 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 

- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

$a \quad b \quad a \quad b \quad a \quad \in L(M)$

1 2 2 1 1


$b \quad a \quad a \quad a \quad a$

1 2 2 2 2

 $L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$


δ	a	b
1	1	2
2	2	1

$a \quad b \quad a \quad b \quad a \quad \in L(M)$
 1 2 2 1 1
 $b \quad a \quad a \quad a \quad a$
 1 2 2 2 2

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$


δ	a	b
1	1	2
2	2	1

$a \quad b \quad a \quad b \quad a \quad \in L(M)$
 1 2 2 1 1
 $b \quad a \quad a \quad a \quad a$
 1 2 2 2 2 2

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{1\}$

δ	a	b
1	1	2
2	2	1

	a	b	a	b	a	$\in L(M)$
	1	2	2	1	1	
	b	a	a	a	a	$\notin L(M)$
	1	2	2	2	2	

$L(M) := \{x \mid x \text{ contains even number of } bs \text{ over } \Sigma\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$

② $\Sigma = \{a, b\}$

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring} \}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$

① $Q =$

② $\Sigma = \{a, b\}$

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$

- ① $Q =$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring} \}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$

- ① $Q =$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s =$

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring} \}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$

- ① $Q =$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s =$
- ⑤ $F =$

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$

M start \rightarrow ①

① $Q =$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$

④ $s =$

⑤ $F =$

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



① $Q =$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$


④ $s =$

⑤ $F =$

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



① $Q =$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$


④ $s =$

⑤ $F =$

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring} \}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



① $Q =$

② $\Sigma = \{a, b\}$

③ $\delta : Q \times \Sigma \rightarrow Q$


④ $s =$

⑤ $F =$

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q =$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s =$
- ⑤ $F =$

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q =$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s =$
- ⑤ $F =$

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q =$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s =$
- ⑤ $F =$

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q =$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s =$
- ⑤ $F =$

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring} \}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q =$
- ② $\Sigma = \{a, b\}$
- ③ $\delta : Q \times \Sigma \rightarrow Q$
- ④ $s =$
- ⑤ $F =$

$$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$$

Example (Regular Language \rightarrow DFA)


$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$

δ	a	b
1	1	2
2	1	3
3	3	3

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$


Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 

- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$

δ	a	b
1	1	2
2	1	3
3	3	3

1 2 1 2 3 3

 $L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 

- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

1 2 1 2 3 3
b a b b a

 $L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$

δ	a	b
1	1	2
2	1	3
3	3	3

1 2 1 2 3 3

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 

- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

1 2 1 2 3 3

 $L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$

δ	a	b
1	1	2
2	1	3
3	3	3

1 2 1 2 3 3

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 

- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

1 2 1 2 3 3

 $L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

1 2 1 2 3 3

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

1 2 1 2 3 3

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$

δ	a	b
1	1	2
2	1	3
3	3	3

1 2 1 2 3 3

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 

- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

1 2 1 2 3 3

 $L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$

δ	a	b
1	1	2
2	1	3
3	3	3

1 2 1 2 3 3

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA) $M = (Q, \Sigma, \delta, s, F)$ 

- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

b a b b a
1 2 1 2 3 3

 $L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$




- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$

δ	a	b
1	1	2
2	1	3
3	3	3

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

$b \quad a \quad b \quad b \quad a \quad \in L(M)$
 1 2 1 2 3 3
 $a \quad a \quad b \quad a \quad b$
 1 1 1 2 1 2

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring} \}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

$b \quad a \quad b \quad b \quad a \quad \in L(M)$
 1 2 1 2 3 3
 a a b a b
 1 1 1 2 1 2

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring} \}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

$b \quad a \quad b \quad b \quad a \quad \in L(M)$
 1 2 1 2 3 3
 a a b a b
 1 1 1 2 1 2

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring} \}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

$b \quad a \quad b \quad b \quad a \quad \in L(M)$
 1 2 1 2 3 3
 $a \quad a \quad b \quad a \quad b$
 1 1 2 1 2

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

$b \quad a \quad b \quad b \quad a \quad \in L(M)$
 1 2 1 2 3 3
 $a \quad a \quad b \quad a \quad b$
 1 1 1 2 1 2

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring} \}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

$b \quad a \quad b \quad b \quad a \quad \in L(M)$
 1 2 1 2 3 3
 $a \quad a \quad b \quad a \quad b$
 1 1 1 2 1 2

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring} \}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

$b \quad a \quad b \quad b \quad a \quad \in L(M)$
 1 2 1 2 3 3
 $a \quad a \quad b \quad a \quad b$
 1 1 1 2 1 2

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring} \}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

$b \quad a \quad b \quad b \quad a \quad \in L(M)$
 1 2 1 2 3 3
 $a \quad a \quad b \quad a \quad b$
 1 1 1 2 1 2

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring} \}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

	b	a	b	b	a	
						$\in L(M)$
1	2	1	2	3	3	
	a	a	b	a	b	
1	1	1	2	1	2	

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

$b \quad a \quad b \quad b \quad a \quad \in L(M)$
 1 2 1 2 3 3
 $a \quad a \quad b \quad a \quad b$
 1 1 1 2 1 2

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring} \}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

$b \quad a \quad b \quad b \quad a \quad \in L(M)$
 1 2 1 2 3 3
 a a b a b
 1 1 1 2 1 2

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring} \}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$


δ	a	b
1	1	2
2	1	3
3	3	3

$b \quad a \quad b \quad b \quad a \quad \in L(M)$
 1 2 1 2 3 3
 $a \quad a \quad b \quad a \quad b$
 1 1 1 2 1 2

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring}\}$

Example (Regular Language \rightarrow DFA)

$M = (Q, \Sigma, \delta, s, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\delta: Q \times \Sigma \rightarrow Q$
- ④ $s = 1$
- ⑤ $F = \{3\}$

δ	a	b
1	1	2
2	1	3
3	3	3

	b	a	b	b	a	
	$\in L(M)$					
1	2	1	2	3	3	
	a	a	b	a	b	
	$\notin L(M)$					
1	1	1	2	1	2	

$L(M) := \{x \mid x \text{ contains } bb \text{ as substring} \}$

Definitions

- **nondeterministic finite automaton (NFA)** is quintuple $N = (Q, \Sigma, \Delta, S, F)$ with

Definitions

- **nondeterministic finite automaton (NFA)** is quintuple $N = (Q, \Sigma, \Delta, S, F)$ with
 - 1 Q : finite set of states

Definitions

- **nondeterministic finite automaton (NFA)** is quintuple $N = (Q, \Sigma, \Delta, S, F)$ with
 - 1 Q : finite set of states
 - 2 Σ : input alphabet

Definitions

- **nondeterministic finite automaton (NFA)** is quintuple $N = (Q, \Sigma, \Delta, S, F)$ with
 - ① Q : finite set of states
 - ② Σ : input alphabet
 - ③ $\Delta : Q \times \Sigma \rightarrow 2^Q$: transition function

Definitions


- **nondeterministic finite automaton (NFA)** is quintuple $N = (Q, \Sigma, \Delta, S, F)$ with
 - ① Q : finite set of states
 - ② Σ : input alphabet
 - ③ $\Delta : Q \times \Sigma \rightarrow 2^Q$: transition function
 - ④ $S \subseteq Q$: set of start states

Definitions

- **nondeterministic finite automaton (NFA)** is quintuple $N = (Q, \Sigma, \Delta, S, F)$ with
 - ① Q : finite set of states
 - ② Σ : input alphabet
 - ③ $\Delta : Q \times \Sigma \rightarrow 2^Q$: transition function
 - ④ $S \subseteq Q$: set of start states
 - ⑤ $F \subseteq Q$: final (accept) states


Example

$N = (Q, \Sigma, \Delta, S, F)$



Example


$N = (Q, \Sigma, \Delta, S, F)$



① $Q = \{1, 2, 3\}$

Example

$N = (Q, \Sigma, \Delta, S, F)$




① $Q = \{1, 2, 3\}$

② $\Sigma = \{a, b\}$

Example


$N = (Q, \Sigma, \Delta, S, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\Delta : Q \times \Sigma \rightarrow 2^Q$

Example

$N = (Q, \Sigma, \Delta, S, F)$




- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\Delta : Q \times \Sigma \rightarrow 2^Q$

Δ	a	b
1	{1, 2}	{1}
2	{3}	{1, 3}
3	{3}	\emptyset

Example

$N = (Q, \Sigma, \Delta, S, F)$




- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\Delta : Q \times \Sigma \rightarrow 2^Q$
- ④ $S = \{1\}$

Δ	a	b
1	{1, 2}	{1}
2	{3}	{1, 3}
3	{3}	\emptyset

Example

$N = (Q, \Sigma, \Delta, S, F)$



- ① $Q = \{1, 2, 3\}$
- ② $\Sigma = \{a, b\}$
- ③ $\Delta : Q \times \Sigma \rightarrow 2^Q$
- ④ $S = \{1\}$
- ⑤ $F = \{3\}$

Δ	a	b
1	{1, 2}	{1}
2	{3}	{1, 3}
3	{3}	\emptyset

Definitions

- **nondeterministic finite automaton (NFA)** is quintuple $N = (Q, \Sigma, \Delta, S, F)$ with

- ① Q : finite set of states
- ② Σ : input alphabet
- ③ $\Delta : Q \times \Sigma \rightarrow 2^Q$: transition function
- ④ $S \subseteq Q$: set of start states
- ⑤ $F \subseteq Q$: final (accept) states

- $\widehat{\Delta} : 2^Q \times \Sigma^* \rightarrow 2^Q$ is inductively defined by

$$\widehat{\Delta}(A, \varepsilon) := A$$

$$\widehat{\Delta}(A, xa) := \bigcup_{q \in \widehat{\Delta}(A, x)} \Delta(q, a)$$

Definitions

- **nondeterministic finite automaton (NFA)** is quintuple $N = (Q, \Sigma, \Delta, S, F)$ with

- ① Q : finite set of states
- ② Σ : input alphabet
- ③ $\Delta : Q \times \Sigma \rightarrow 2^Q$: transition function
- ④ $S \subseteq Q$: set of start states
- ⑤ $F \subseteq Q$: final (accept) states

- $\widehat{\Delta} : 2^Q \times \Sigma^* \rightarrow 2^Q$ is inductively defined by

$$\widehat{\Delta}(A, \varepsilon) := A$$

$$\widehat{\Delta}(A, xa) := \bigcup_{q \in \widehat{\Delta}(A, x)} \Delta(q, a)$$

- string $x \in \Sigma^*$ is **accepted** by N if $\widehat{\Delta}(S, x) \cap F \neq \emptyset$

Theorem

- 1 every set accepted by NFA is regular (procedure: subset construction – $\text{NFA} \rightarrow \text{DFA}$)

Theorem

- 1 every set accepted by NFA is regular (procedure: subset construction – $\text{NFA} \rightarrow \text{DFA}$)
- 2 every DFA M minimizes into a DFA M' such that $L(M) = L(M')$ (unless M is minimal)

Theorem

- 1 every set accepted by NFA is regular (procedure: subset construction – $\text{NFA} \rightarrow \text{DFA}$)
- 2 every DFA M minimizes into a DFA M' such that $L(M) = L(M')$ (unless M is minimal)

Theorem

- 1 every set accepted by NFA is regular (procedure: subset construction – $NFA \rightarrow DFA$)
- 2 every DFA M minimizes into a DFA M' such that $L(M) = L(M')$ (unless M is minimal)

Theorem

regular languages are closed under

- union

Theorem

- 1 every set accepted by NFA is regular (procedure: subset construction – $\text{NFA} \rightarrow \text{DFA}$)
- 2 every DFA M minimizes into a DFA M' such that $L(M) = L(M')$ (unless M is minimal)

Theorem

regular languages are closed under

- union
- intersection

Theorem

- 1 every set accepted by NFA is regular (procedure: subset construction – $\text{NFA} \rightarrow \text{DFA}$)
- 2 every DFA M minimizes into a DFA M' such that $L(M) = L(M')$ (unless M is minimal)

Theorem

regular languages are closed under

- union
- intersection
- complementation

Theorem

- 1 every set accepted by NFA is regular (procedure: subset construction – $\text{NFA} \rightarrow \text{DFA}$)
- 2 every DFA M minimizes into a DFA M' such that $L(M) = L(M')$ (unless M is minimal)

Theorem

regular languages are closed under

- union
- intersection
- complementation
- concatenation

Theorem

- 1 every set accepted by NFA is regular (procedure: subset construction – $\text{NFA} \rightarrow \text{DFA}$)
- 2 every DFA M minimizes into a DFA M' such that $L(M) = L(M')$ (unless M is minimal)

Theorem

regular languages are closed under

- union
- intersection
- complementation
- concatenation
- asterate

Theorem

- 1 every set accepted by NFA is regular (procedure: subset construction – $\text{NFA} \rightarrow \text{DFA}$)
- 2 every DFA M minimizes into a DFA M' such that $L(M) = L(M')$ (unless M is minimal)

Theorem

regular languages are closed under

- union
- intersection
- complementation
- concatenation
- asterate
- homomorphic image and preimage

Table of Contents

- 1 Languages
- 2 Compilers and Interpreters
- 3 Pattern Matching and Regular Expressions
- 4 Finite State Automaton
- 5 Lexer**

Lexical Analyzers (Lexers)

translator tool : strings (programs) → list of tokens (or error)

- simulate **finite state automaton** to create tokens

Lexical Analyzers (Lexers)

translator tool : strings (programs) → list of tokens (or error)

- simulate **finite state automaton** to create tokens
- lexer generators

Lexical Analyzers (Lexers)

translator tool : strings (programs) → list of tokens (or error)

- simulate **finite state automaton** to create tokens
- lexer generators
 - Alex for Haskell

Lexical Analyzers (Lexers)

translator tool : strings (programs) → list of tokens (or error)

- simulate **finite state automaton** to create tokens
- lexer generators
 - Alex for Haskell
 - JLex for Java

Lexical Analyzers (Lexers)

translator tool : strings (programs) → list of tokens (or error)

- simulate **finite state automaton** to create tokens
- lexer generators
 - Alex for Haskell
 - JLex for Java
 - Flex for C

Lexical Analyzers (Lexers)

translator tool : strings (programs) → list of tokens (or error)

- simulate **finite state automaton** to create tokens
- lexer generators
 - Alex for Haskell
 - JLex for Java
 - Flex for C
 - *ocamllex* for OCaml

ocamllex

- generates **lexers** in compatible with OCaml programs
 - input : list of *lexing rules* in the form of *regular expressions* with corresponding *tokens*
 - output : a **lexer** as a DFA accepting the language generated by the input expressions

ocamllex

- generates **lexers** in compatible with OCaml programs
 - input : list of *lexing rules* in the form of *regular expressions* with corresponding *tokens*
 - output : a **lexer** as a DFA accepting the language generated by the input expressions
- recognizes patterns specified by the rules, associates the corresponding tokens

ocamllex (Specifications)

```
{ header }  
  
rule entrypoint = parse  
| regexp { action }  
| ...  
| regexp { action }  
| ...  
  
{ trailer }
```

ocamllex (Specifications)

```
{ header }
```

```
rule entrypoint = parse  
  | regexp { action }  
  | ...  
  | regexp { action }  
  | ...
```

```
{ trailer }
```

```
where
```

actions are OCaml expressions of the same type

ocamllex (Specifications)

```
{ header }
```

```
rule entrypoint = parse
```

```
| regexp { action }
```

```
| ...
```

```
| regexp { action }
```

```
| ...
```

```
{ trailer }
```

```
where
```

actions are OCaml expressions of the same type

header define functions used in tokenization (before tokenization)

ocamllex (Specifications)

```
{ header }
```

```
rule entrypoint = parse
| regexp { action }
| ...
| regexp { action }
| ...
```

```
{ trailer }
```

where

actions	are OCaml expressions of the same type	
header	define functions used in tokenization	(before tokenization)
trailer	define functions using tokenization	(after tokenization)

Example (ocamllex: Balanced Parentheses – Header)

```
(* lexer.mll *)
{
  open Lexing
  open Printf
  exception Bad_char of char

  type token =
    | BLANK : token
    | LPAREN : token
    | RPAREN : token
    | EOL    : token
    | IDENT  : string → token
    | NUM    : int    → token

  let rec token2String (t: token): string =
    match t with
    | BLANK   → "BLANK"
    | LPAREN  → "LPAREN"
    | RPAREN  → "RPAREN"
    | EOL     → "EOL"
    | IDENT s → "IDENT=[" ^ s ^ "]"
    | NUM x   → "NUM=" ^ string_of_int x ^ "]"

  let printToken (t: token): unit = printf "%s_" (token2String t)
}
```

Example (ocamllex: Balanced Parentheses – Rules)

```
rule tokenize = parse
| ',' ' ' { BLANK }
| '[' ' ' { LPAREN }
| ']' ' ' { RPAREN }
| [ α'- 'z' 'A'- 'Z' ' _ ' ]+ as s { IDENT s }
| [ '0'- '9' ]+ as i { NUM (int_of_string i) }
| eof { EOL }
| _ as c { raise (Bad_char c) }
```

Example (ocamllex: Balanced Parentheses – Trailer)

```
{  
  let rec getTokensFromBuffer (b: lexbuf): token list =  
    let tkn = tokenize b in  
    match tkn with  
    | EOL → [EOL]  
    | t   → t :: getTokensFromBuffer b  
  
  let getTokensFromString (s: string): token list =  
    getTokensFromBuffer (from_string s)  
}
```

Example (ocamllex: Balanced Parentheses – Trailer)

```
{  
  let rec getTokensFromBuffer (b: lexbuf): token list =  
    let tkn = tokenize b in  
    match tkn with  
    | EOL → [EOL]  
    | t   → t :: getTokensFromBuffer b  
  
  let getTokensFromString (s: string): token list =  
    getTokensFromBuffer (from_string s)  
}
```


Remark (in OCaml “Lexing” library)

where

lexbuf	input stream that delivers characters one at a time
from_string: string → lexbuf	function converts the input string into a stream


```
let main: unit =
    let tl = getTokensFromString "[[][]][[2023][burak]]" in
    printTokenList tl;
```

ocamllex (DFA – tokenize)



where

- 1 RPAREN
- 2 LPAREN
- 3 BLANK
- 4 IDENT
- 5 NUM

Thanks! & Questions?