

# CENG 2010 - Programming Language Concepts

## Week 4: Context-Free Grammars and Syntactical Analysis

Burak Ekici

March 27, 2023

# Table of Contents

1 A Quick Recap

2 Context-Free Grammars

3 Ambiguity

4 Push Down Automaton

5 Parser

## Syntax

- keywords, formatting and **grammatical** structure of the language

## Syntax

- keywords, formatting and **grammatical** structure of the language
- usually superficial differences in between languages:

```
/* in C */  
if (x == y) then {...} else {...}
```

```
(* in OCaml *)  
if x = y then begin ... end else begin ... end
```

## Syntax


- keywords, formatting and **grammatical** structure of the language
- usually superficial differences in between languages:

```
/* in C */  
if (x == y) then {...} else {...}
```


```
(* in OCaml *)  
if x = y then begin ... end else begin ... end
```

- regular expressions, context-free grammars, and parsing constitute the syntax of a language

## Architecture of Compilers and Interpreters




## Front-End: Lexer and Parser



scanner/lexer : source code  $\mapsto$  tokens (keywords, variables, numbers, etc.) regular expressions

## Front-End: Lexer and Parser



scanner/lexer	:	source code	→	tokens (keywords, variables, numbers, etc.)	regular expressions
parser	:	tokens	→	abstract syntax trees/parse trees	context free grammars



## Implementation (Front-End)

- goal: map program texts into PTs/ASTs

## Implementation (Front-End)

- goal: map program texts into PTs/ASTs
- PTs and ASTs are easier to work with – analyze, optimize, execute the program

## Implementation (Front-End)

- goal: map program texts into PTs/ASTs
- PTs and ASTs are easier to work with – analyze, optimize, execute the program
- front end use regular expressions at scanning/lexing

## Implementation (Front-End)

- goal: map program texts into PTs/ASTs
- PTs and ASTs are easier to work with – analyze, optimize, execute the program
- front end use regular expressions at scanning/lexing
- regular expressions cannot reliably parse paired braces  $\{\{...\}\}$  and parentheses  $(((...)))$ , etc.

## Implementation (Front-End)

- goal: map program texts into PTs/ASTs
- PTs and ASTs are easier to work with – analyze, optimize, execute the program
- front end use regular expressions at scanning/lexing
- regular expressions cannot reliably parse paired braces  $\{\{...\}\}$  and parentheses  $(((...)))$ , etc.
- regular expressions for tokenizing (scanning/lexing), and **context free grammars for parsing tokens**

## Table of Contents

- 1 A Quick Recap
- 2 Context-Free Grammars**
- 3 Ambiguity
- 4 Push Down Automaton
- 5 Parser

## Definitions

- **context-free grammar (CFG)** is quadruple  $G = (N, \Sigma, P, S)$  with

## Definitions

- **context-free grammar (CFG)** is quadruple  $G = (N, \Sigma, P, S)$  with
  - 1  $N$  : finite set of **nonterminals**



## Definitions

- **context-free grammar (CFG)** is quadruple  $G = (N, \Sigma, P, S)$  with
  - ①  $N$ : finite set of nonterminals
  - ②  $\Sigma$ : finite set of **terminals**, disjoint from  $N$

## Definitions

- **context-free grammar (CFG)** is quadruple  $G = (N, \Sigma, P, S)$  with
  - ①  $N$ : finite set of nonterminals
  - ②  $\Sigma$ : finite set of terminals, disjoint from  $N$
  - ③  $P$ : finite set of **productions** of the form  $A \rightarrow \alpha$  with  $A \in N$  and  $\alpha \in (N \cup \Sigma)^*$

## Definitions

- **context-free grammar (CFG)** is quadruple  $G = (N, \Sigma, P, S)$  with
  - ①  $N$ : finite set of nonterminals
  - ②  $\Sigma$ : finite set of terminals, disjoint from  $N$
  - ③  $P$ : finite set of productions of the form  $A \rightarrow \alpha$  with  $A \in N$  and  $\alpha \in (N \cup \Sigma)^*$
  - ④  $S \in N$ : **start symbol**

## Definitions

- context-free grammar (CFG) is quadruple  $G = (N, \Sigma, P, S)$  with
  - ①  $N$ : finite set of nonterminals
  - ②  $\Sigma$ : finite set of terminals, disjoint from  $N$
  - ③  $P$ : finite set of productions of the form  $A \rightarrow \alpha$  with  $A \in N$  and  $\alpha \in (N \cup \Sigma)^*$
  - ④  $S \in N$ : start symbol
- one step derivation relation  $\xrightarrow[G]{1}$  on  $(N \cup \Sigma)^*$ :  $\beta A \gamma \xrightarrow[G]{1} \beta \alpha \gamma$  if  $A \rightarrow \alpha \in P$  and  $\beta, \gamma \in (N \cup \Sigma)^*$

## Example

CFG  $G = (N, \Sigma, P, S)$

- ①  $N = \{S\}$
- ②  $\Sigma = \{a, b\}$
- ③  $P = \{S \rightarrow aSb, S \rightarrow \epsilon\}$

## Example

CFG  $G = (N, \Sigma, P, S)$

①  $N = \{S\}$

②  $\Sigma = \{a, b\}$

③  $P = \{S \rightarrow aSb, S \rightarrow \epsilon\}$

two derivations:

$$S \xrightarrow[G]{1} aSb$$

## Example

CFG  $G = (N, \Sigma, P, S)$

①  $N = \{S\}$

②  $\Sigma = \{a, b\}$

③  $P = \{S \rightarrow aSb, S \rightarrow \epsilon\}$

two derivations:

$$S \xrightarrow[G]{1} aSb \xrightarrow[G]{1} ab$$

## Example

CFG  $G = (N, \Sigma, P, S)$

①  $N = \{S\}$

②  $\Sigma = \{a, b\}$

③  $P = \{S \rightarrow aSb, S \rightarrow \epsilon\}$

two derivations:

$$S \xrightarrow[G]{1} aSb \xrightarrow[G]{1} ab$$

$$S \xrightarrow[G]{1} aSb \xrightarrow[G]{1} aaSbb$$



## Example

CFG  $G = (N, \Sigma, P, S)$

①  $N = \{S\}$

②  $\Sigma = \{a, b\}$

③  $P = \{S \rightarrow aSb, S \rightarrow \epsilon\}$

two derivations:

$$S \xrightarrow[G]{1} aSb \xrightarrow[G]{1} ab$$

$$S \xrightarrow[G]{1} aSb \xrightarrow[G]{1} aaSbb \xrightarrow[G]{1} aabb$$

## Example

CFG  $G = (N, \Sigma, P, S)$

①  $N = \{S\}$

②  $\Sigma = \{a, b\}$

③  $P = \{S \rightarrow aSb, S \rightarrow \epsilon\} = \{S \rightarrow aSb \mid \epsilon\}$

two derivations:

$$S \xrightarrow[G]{1} aSb \xrightarrow[G]{1} ab$$

$$S \xrightarrow[G]{1} aSb \xrightarrow[G]{1} aaSbb \xrightarrow[G]{1} aabb$$

## Definitions

- context-free grammar (CFG) is quadruple  $G = (N, \Sigma, P, S)$  with
  - ①  $N$ : finite set of nonterminals
  - ②  $\Sigma$ : finite set of terminals, disjoint from  $N$
  - ③  $P$ : finite set of productions of the form  $A \rightarrow \alpha$  with  $A \in N$  and  $\alpha \in (N \cup \Sigma)^*$
  - ④  $S \in N$ : start symbol
- one step derivation relation  $\xrightarrow{G}$  on  $(N \cup \Sigma)^*$ :  $\beta A \gamma \xrightarrow{G} \beta \alpha \gamma$  if  $A \rightarrow \alpha \in P$  and  $\beta, \gamma \in (N \cup \Sigma)^*$
- $\xrightarrow[n]{G} = (\xrightarrow{G})^n \quad \forall n \geq 0$

## Definitions

- context-free grammar (CFG) is quadruple  $G = (N, \Sigma, P, S)$  with
  - ①  $N$ : finite set of nonterminals
  - ②  $\Sigma$ : finite set of terminals, disjoint from  $N$
  - ③  $P$ : finite set of productions of the form  $A \rightarrow \alpha$  with  $A \in N$  and  $\alpha \in (N \cup \Sigma)^*$
  - ④  $S \in N$ : start symbol
- one step derivation relation  $\xrightarrow{1}_G$  on  $(N \cup \Sigma)^*$ :  $\beta A \gamma \xrightarrow{1}_G \beta \alpha \gamma$  if  $A \rightarrow \alpha \in P$  and  $\beta, \gamma \in (N \cup \Sigma)^*$
- $\xrightarrow{n}_G = (\xrightarrow{1}_G)^n \quad \forall n \geq 0 \quad \xrightarrow{*}_G = \bigcup_{n \geq 0} \xrightarrow{n}_G$

## Definitions

- context-free grammar (CFG) is quadruple  $G = (N, \Sigma, P, S)$  with
  - ①  $N$ : finite set of nonterminals
  - ②  $\Sigma$ : finite set of terminals, disjoint from  $N$
  - ③  $P$ : finite set of productions of the form  $A \rightarrow \alpha$  with  $A \in N$  and  $\alpha \in (N \cup \Sigma)^*$
  - ④  $S \in N$ : start symbol
- one step derivation relation  $\xrightarrow{1}_G$  on  $(N \cup \Sigma)^*$ :  $\beta A \gamma \xrightarrow{1}_G \beta \alpha \gamma$  if  $A \rightarrow \alpha \in P$  and  $\beta, \gamma \in (N \cup \Sigma)^*$
- $\xrightarrow{n}_G = (\xrightarrow{1}_G)^n \quad \forall n \geq 0 \quad \xrightarrow{*}_G = \bigcup_{n \geq 0} \xrightarrow{n}_G$
- members of the set  $(N \cup \Sigma)^*$  are called **strings**

## Definitions

- context-free grammar (CFG) is quadruple  $G = (N, \Sigma, P, S)$  with
  - ①  $N$ : finite set of nonterminals
  - ②  $\Sigma$ : finite set of terminals, disjoint from  $N$
  - ③  $P$ : finite set of productions of the form  $A \rightarrow \alpha$  with  $A \in N$  and  $\alpha \in (N \cup \Sigma)^*$
  - ④  $S \in N$ : start symbol
- one step derivation relation  $\xrightarrow{G}$  on  $(N \cup \Sigma)^*$ :  $\beta A \gamma \xrightarrow{G} \beta \alpha \gamma$  if  $A \rightarrow \alpha \in P$  and  $\beta, \gamma \in (N \cup \Sigma)^*$
- $\xrightarrow{G}^n = (\xrightarrow{G})^n \quad \forall n \geq 0 \quad \xrightarrow{G}^* = \bigcup_{n \geq 0} \xrightarrow{G}^n$
- members of the set  $(N \cup \Sigma)^*$  are called strings
- string  $s$  is called a **sentential form** if  $S \xrightarrow{G}^* s$  (derivable from the start symbol  $S$ )

## Definitions

- context-free grammar (CFG) is quadruple  $G = (N, \Sigma, P, S)$  with
  - ①  $N$ : finite set of nonterminals
  - ②  $\Sigma$ : finite set of terminals, disjoint from  $N$
  - ③  $P$ : finite set of productions of the form  $A \rightarrow \alpha$  with  $A \in N$  and  $\alpha \in (N \cup \Sigma)^*$
  - ④  $S \in N$ : start symbol
- one step derivation relation  $\xrightarrow{G}$  on  $(N \cup \Sigma)^*$ :  $\beta A \gamma \xrightarrow{G} \beta \alpha \gamma$  if  $A \rightarrow \alpha \in P$  and  $\beta, \gamma \in (N \cup \Sigma)^*$
- $\xrightarrow{G}^n = (\xrightarrow{G})^n \quad \forall n \geq 0 \quad \xrightarrow{G}^* = \bigcup_{n \geq 0} \xrightarrow{G}^n$
- members of the set  $(N \cup \Sigma)^*$  are called strings
- string  $s$  is called a sentential form if  $S \xrightarrow{G}^* s$  (derivable from the start symbol  $S$ )
- sentential form  $x$  is called a **sentence** if  $x \in \Sigma^*$  (consisting terminal symbols only)

## Definitions

- context-free grammar (CFG) is quadruple  $G = (N, \Sigma, P, S)$  with
  - ①  $N$ : finite set of nonterminals
  - ②  $\Sigma$ : finite set of terminals, disjoint from  $N$
  - ③  $P$ : finite set of productions of the form  $A \rightarrow \alpha$  with  $A \in N$  and  $\alpha \in (N \cup \Sigma)^*$
  - ④  $S \in N$ : start symbol
- one step derivation relation  $\xrightarrow{G}$  on  $(N \cup \Sigma)^*$ :  $\beta A \gamma \xrightarrow{G} \beta \alpha \gamma$  if  $A \rightarrow \alpha \in P$  and  $\beta, \gamma \in (N \cup \Sigma)^*$
- $\xrightarrow{G}^n = (\xrightarrow{G})^n \quad \forall n \geq 0 \quad \xrightarrow{G}^* = \bigcup_{n \geq 0} \xrightarrow{G}^n$
- members of the set  $(N \cup \Sigma)^*$  are called strings
- string  $s$  is called a sentential form if  $S \xrightarrow{G}^* s$  (derivable from the start symbol  $S$ )
- sentential form  $x$  is called a sentence if  $x \in \Sigma^*$  (consisting terminal symbols only)
- language generated by  $G$ :  $L(G) = \{x \in \Sigma^* \mid S \xrightarrow{G}^* x\}$



## Example

CFG  $G = (N, \Sigma, P, S)$

- ①  $N = \{S\}$
- ②  $\Sigma = \{a, b\}$
- ③  $P = \{S \rightarrow aSb, S \rightarrow \varepsilon\} = \{S \rightarrow aSb \mid \varepsilon\}$

two derivations:

$$S \xrightarrow[G]{1} aSb \xrightarrow[G]{1} ab$$

$$S \xrightarrow[G]{1} aSb \xrightarrow[G]{1} aaSbb \xrightarrow[G]{1} aabb$$

## Lemma

$$L(G) = \{a^n b^n \mid n \geq 0\}$$

## Definitions

- context-free grammar (CFG) is quadruple  $G = (N, \Sigma, P, S)$  with
  - ①  $N$ : finite set of nonterminals
  - ②  $\Sigma$ : finite set of terminals, disjoint from  $N$
  - ③  $P$ : finite set of productions of the form  $A \rightarrow \alpha$  with  $A \in N$  and  $\alpha \in (N \cup \Sigma)^*$
  - ④  $S \in N$ : start symbol
- one step derivation relation  $\xrightarrow{G}$  on  $(N \cup \Sigma)^*$ :  $\beta A \gamma \xrightarrow{G} \beta \alpha \gamma$  if  $A \rightarrow \alpha \in P$  and  $\beta, \gamma \in (N \cup \Sigma)^*$
- $\xrightarrow{G}^n = (\xrightarrow{G})^n \quad \forall n \geq 0 \quad \xrightarrow{G}^* = \bigcup_{n \geq 0} \xrightarrow{G}^n$
- members of the set  $(N \cup \Sigma)^*$  are called strings
- string  $s$  is called a sentential form if  $S \xrightarrow{G}^* s$  (derivable from the start symbol  $S$ )
- sentential form  $x$  is called a sentence if  $x \in \Sigma^*$  (consisting terminal symbols only)
- language generated by  $G$ :  $L(G) = \{x \in \Sigma^* \mid S \xrightarrow{G}^* x\}$
- set  $B \subseteq \Sigma^*$  is **context-free** if  $B = L(G)$  for some CFG  $G$

## Example

- grammar  $G = (\{S, T, U\}, \{a, b, c\}, P, S)$  with  $P$  :

$$S \rightarrow aS \mid T$$
$$T \rightarrow bT \mid U$$
$$U \rightarrow cU \mid \varepsilon$$

## Example

- grammar  $G = (\{S, T, U\}, \{a, b, c\}, P, S)$  with  $P$  :

$$S \rightarrow aS \mid T$$
$$T \rightarrow bT \mid U$$
$$U \rightarrow cU \mid \varepsilon$$

- provide derivations for the following strings:

"b"

## Example

- grammar  $G = (\{S, T, U\}, \{a, b, c\}, P, S)$  with  $P$  :

$$S \rightarrow aS \mid T$$
$$T \rightarrow bT \mid U$$
$$U \rightarrow cU \mid \varepsilon$$

- provide derivations for the following strings:

"b"       $S \xrightarrow{1}_G T \xrightarrow{1}_G bT \xrightarrow{1}_G bU \xrightarrow{1}_G b\varepsilon = b$

## Example

- grammar  $G = (\{S, T, U\}, \{a, b, c\}, P, S)$  with  $P$  :

$$S \rightarrow aS \mid T$$
$$T \rightarrow bT \mid U$$
$$U \rightarrow cU \mid \varepsilon$$

- provide derivations for the following strings:

"b"       $S \xrightarrow{G} T \xrightarrow{G} bT \xrightarrow{G} bU \xrightarrow{G} b\varepsilon = b$

"ac"

## Example

- grammar  $G = (\{S, T, U\}, \{a, b, c\}, P, S)$  with  $P$  :

$$S \rightarrow aS \mid T$$

$$T \rightarrow bT \mid U$$

$$U \rightarrow cU \mid \varepsilon$$

- provide derivations for the following strings:

$$\text{"b"} \quad S \xrightarrow[G]{1} T \xrightarrow[G]{1} bT \xrightarrow[G]{1} bU \xrightarrow[G]{1} b\varepsilon = b$$

$$\text{"ac"} \quad S \xrightarrow[G]{1} aS \xrightarrow[G]{1} aT \xrightarrow[G]{1} aU \xrightarrow[G]{1} acU \xrightarrow[G]{1} ac\varepsilon = ac$$

## Example

- grammar  $G = (\{S, T, U\}, \{a, b, c\}, P, S)$  with  $P$  :

$$S \rightarrow aS \mid T$$

$$T \rightarrow bT \mid U$$

$$U \rightarrow cU \mid \varepsilon$$

- provide derivations for the following strings:

$$\text{"b"} \quad S \xrightarrow[G]{1} T \xrightarrow[G]{1} bT \xrightarrow[G]{1} bU \xrightarrow[G]{1} b\varepsilon = b$$

$$\text{"ac"} \quad S \xrightarrow[G]{1} aS \xrightarrow[G]{1} aT \xrightarrow[G]{1} aU \xrightarrow[G]{1} acU \xrightarrow[G]{1} ac\varepsilon = ac$$

*"bbc"*



## Example

- grammar  $G = (\{S, T, U\}, \{a, b, c\}, P, S)$  with  $P$  :

$$S \rightarrow aS \mid T$$
$$T \rightarrow bT \mid U$$
$$U \rightarrow cU \mid \varepsilon$$

- provide derivations for the following strings:

$$\text{"b"} \quad S \xrightarrow[G]{1} T \xrightarrow[G]{1} bT \xrightarrow[G]{1} bU \xrightarrow[G]{1} b\varepsilon = b$$

$$\text{"ac"} \quad S \xrightarrow[G]{1} aS \xrightarrow[G]{1} aT \xrightarrow[G]{1} aU \xrightarrow[G]{1} acU \xrightarrow[G]{1} ac\varepsilon = ac$$

$$\text{"bbc"} \quad S \xrightarrow[G]{1} T \xrightarrow[G]{1} bT \xrightarrow[G]{1} bbT \xrightarrow[G]{1} bbU \xrightarrow[G]{1} bbcU \xrightarrow[G]{1} bbc\varepsilon = bbc$$

## Example

- grammar  $G = (\{S, T, U\}, \{a, b, c\}, P, S)$  with  $P$  :

$$S \rightarrow aS \mid T$$

$$T \rightarrow bT \mid U$$

$$U \rightarrow cU \mid \varepsilon$$

- provide derivations for the following strings:

$$\text{"b"} \quad S \xrightarrow{G} T \xrightarrow{G} bT \xrightarrow{G} bU \xrightarrow{G} b\varepsilon = b$$

$$\text{"ac"} \quad S \xrightarrow{G} aS \xrightarrow{G} aT \xrightarrow{G} aU \xrightarrow{G} acU \xrightarrow{G} ac\varepsilon = ac$$

$$\text{"bbc"} \quad S \xrightarrow{G} T \xrightarrow{G} bT \xrightarrow{G} bbT \xrightarrow{G} bbU \xrightarrow{G} bbcU \xrightarrow{G} bbc\varepsilon = bbc$$

- does  $G$  generate following strings?

$$S \xrightarrow{G}^+ \text{"ccc"}$$

## Example

- grammar  $G = (\{S, T, U\}, \{a, b, c\}, P, S)$  with  $P$  :

$$S \rightarrow aS \mid T$$
$$T \rightarrow bT \mid U$$
$$U \rightarrow cU \mid \varepsilon$$

- provide derivations for the following strings:

$$\text{"b"} \quad S \xrightarrow{G} T \xrightarrow{G} bT \xrightarrow{G} bU \xrightarrow{G} b\varepsilon = b$$
$$\text{"ac"} \quad S \xrightarrow{G} aS \xrightarrow{G} aT \xrightarrow{G} aU \xrightarrow{G} acU \xrightarrow{G} ac\varepsilon = ac$$
$$\text{"bbc"} \quad S \xrightarrow{G} T \xrightarrow{G} bT \xrightarrow{G} bbT \xrightarrow{G} bbU \xrightarrow{G} bbcU \xrightarrow{G} bbc\varepsilon = bbc$$

- does  $G$  generate following strings?

$$S \xrightarrow{G}^+ \text{"ccc"} \quad \text{yes}$$

## Example

- grammar  $G = (\{S, T, U\}, \{a, b, c\}, P, S)$  with  $P$  :

$$S \rightarrow aS \mid T$$

$$T \rightarrow bT \mid U$$

$$U \rightarrow cU \mid \varepsilon$$

- provide derivations for the following strings:

$$\text{"b"} \quad S \xrightarrow{G} T \xrightarrow{G} bT \xrightarrow{G} bU \xrightarrow{G} b\varepsilon = b$$

$$\text{"ac"} \quad S \xrightarrow{G} aS \xrightarrow{G} aT \xrightarrow{G} aU \xrightarrow{G} acU \xrightarrow{G} ac\varepsilon = ac$$

$$\text{"bbc"} \quad S \xrightarrow{G} T \xrightarrow{G} bT \xrightarrow{G} bbT \xrightarrow{G} bbU \xrightarrow{G} bbcU \xrightarrow{G} bbc\varepsilon = bbc$$

- does  $G$  generate following strings?

$$S \xrightarrow{G}^+ \text{"ccc"} \quad \text{yes}$$

$$S \xrightarrow{G}^+ \text{"bab"}$$

## Example

- grammar  $G = (\{S, T, U\}, \{a, b, c\}, P, S)$  with  $P$  :

$$\begin{aligned} S &\rightarrow aS \mid T \\ T &\rightarrow bT \mid U \\ U &\rightarrow cU \mid \varepsilon \end{aligned}$$

- provide derivations for the following strings:

$$\text{"b"} \quad S \xrightarrow[G]{1} T \xrightarrow[G]{1} bT \xrightarrow[G]{1} bU \xrightarrow[G]{1} b\varepsilon = b$$

$$\text{"ac"} \quad S \xrightarrow[G]{1} aS \xrightarrow[G]{1} aT \xrightarrow[G]{1} aU \xrightarrow[G]{1} acU \xrightarrow[G]{1} ac\varepsilon = ac$$

$$\text{"bbc"} \quad S \xrightarrow[G]{1} T \xrightarrow[G]{1} bT \xrightarrow[G]{1} bbT \xrightarrow[G]{1} bbU \xrightarrow[G]{1} bbcU \xrightarrow[G]{1} bbc\varepsilon = bbc$$

- does  $G$  generate following strings?

$$S \xrightarrow[G]{+} \text{"ccc"} \quad \text{yes}$$

$$S \xrightarrow[G]{+} \text{"bab"} \quad \text{no}$$

## Example

- grammar  $G = (\{S, T, U\}, \{a, b, c\}, P, S)$  with  $P$  :

$$S \rightarrow aS \mid T$$
$$T \rightarrow bT \mid U$$
$$U \rightarrow cU \mid \varepsilon$$

constructs  $\mathcal{L} = \{a^i b^j c^k \mid i, j, k \geq 0\}$

## Example

- grammar  $G = (\{S, T, U\}, \{a, b, c\}, P, S)$  with  $P$  :

$$S \rightarrow aS \mid T$$
$$T \rightarrow bT \mid U$$
$$U \rightarrow cU \mid \varepsilon$$

constructs  $\mathcal{L} = \{a^i b^j c^k \mid i, j, k \geq 0\}$

- grammar  $G' = (\{S, A, B, C\}, \{a, b, c\}, P, S)$  with  $P$  :

$$S \rightarrow ABC$$
$$A \rightarrow aA \mid \varepsilon$$
$$B \rightarrow bB \mid \varepsilon$$
$$C \rightarrow cC \mid \varepsilon$$

constructs the same language  $\mathcal{L}$

## Some Useful Tricks to Design Grammars

### 1 arbitrary number of symbols:

$S \rightarrow aS \mid \epsilon$       zero or more a's

$S \rightarrow bS \mid b$       one or more b's



## Some Useful Tricks to Design Grammars

### 1 arbitrary number of symbols:

$$S \rightarrow aS \mid \varepsilon \quad \text{zero or more } a\text{'s}$$
$$S \rightarrow bS \mid b \quad \text{one or more } b\text{'s}$$

### 2 disjoint parts of a language:

$$A \rightarrow aA \mid \varepsilon \quad \text{zero or more } a\text{'s}$$
$$B \rightarrow bB \mid \varepsilon \quad \text{zero or more } b\text{'s}$$
$$S \rightarrow AB \quad \text{combining above generations}$$

generates  $\mathcal{L} = \{a^i b^j \mid i, j \geq 0\}$

## Some Useful Tricks to Design Grammars

### 1 arbitrary number of symbols:

$$S \rightarrow aS \mid \varepsilon \quad \text{zero or more } a\text{'s}$$
$$S \rightarrow bS \mid b \quad \text{one or more } b\text{'s}$$

### 2 disjoint parts of a language:

$$A \rightarrow aA \mid \varepsilon \quad \text{zero or more } a\text{'s}$$
$$B \rightarrow bB \mid \varepsilon \quad \text{zero or more } b\text{'s}$$
$$S \rightarrow AB \quad \text{combining above generations}$$

generates  $\mathcal{L} = \{a^i b^j \mid i, j \geq 0\}$

### 3 matching (balanced) symbols:

$$S \rightarrow aSb \mid \varepsilon$$

generates  $\mathcal{L} = \{a^n b^n \mid n \geq 0\}$

## Some Useful Tricks to Design Grammars

- 1 arbitrary number of symbols:

$S \rightarrow aS \mid \epsilon$       zero or more a's

$S \rightarrow bS \mid b$       one or more b's

- 2 disjoint parts of a language:

$A \rightarrow aA \mid \epsilon$       zero or more a's

$B \rightarrow bB \mid \epsilon$       zero or more b's

$S \rightarrow AB$       combining above generations

generates  $\mathcal{L} = \{a^i b^j \mid i, j \geq 0\}$

- 3 matching (balanced) symbols:

$S \rightarrow aSb \mid \epsilon$

generates  $\mathcal{L} = \{a^n b^n \mid n \geq 0\}$

- 4 matching *linearly* related symbols:

$S \rightarrow aSbb \mid \epsilon$

generates  $\mathcal{L} = \{a^n b^{2n} \mid n \geq 0\}$

## Example

- $\{0^n 1^m \mid m \leq n\}$       $G = (\{S\}, \{0, 1\}, P, S)$

## Example

- $\{0^n 1^m \mid m \leq n\}$       $G = (\{S\}, \{0, 1\}, P, S)$   
     where  $P = \{S \rightarrow 0S1 \mid 0S \mid \varepsilon\}$

## Example

- $\{0^n 1^m \mid m \leq n\}$       $G = (\{S\}, \{0, 1\}, P, S)$   
where  $P = \{S \rightarrow 0S1 \mid 0S \mid \varepsilon\}$
- $\{1^n 0 \mid n \geq 0\}$       $G = (\{S\}, \{0, 1\}, P, S)$

## Example

- $\{0^n 1^m \mid m \leq n\}$       $G = (\{S\}, \{0, 1\}, P, S)$   
where  $P = \{S \rightarrow 0S1 \mid 0S \mid \varepsilon\}$
- $\{1^n 0 \mid n \geq 0\}$       $G = (\{S\}, \{0, 1\}, P, S)$   
where  $P = \{S \rightarrow 0 \mid 1S\}$

## Example

- $\{0^n 1^m \mid m \leq n\}$       $G = (\{S\}, \{0, 1\}, P, S)$   
where  $P = \{S \rightarrow 0S1 \mid 0S \mid \varepsilon\}$
- $\{1^n 0 \mid n \geq 0\}$       $G = (\{S\}, \{0, 1\}, P, S)$   
where  $P = \{S \rightarrow 0 \mid 1S\}$
- $\{a^n (b^m \mid c^k) \mid n \geq 0, m, k > n\}$



## Example

- $\{0^n 1^m \mid m \leq n\}$       $G = (\{S\}, \{0, 1\}, P, S)$   
 where  $P = \{S \rightarrow 0S1 \mid 0S \mid \varepsilon\}$
- $\{1^n 0 \mid n \geq 0\}$       $G = (\{S\}, \{0, 1\}, P, S)$   
 where  $P = \{S \rightarrow 0 \mid 1S\}$
- $\{a^n(b^m \mid c^k) \mid n \geq 0, m, k > n\} = \{a^n b^m \mid m > n \geq 0\} \cup \{a^n c^k \mid k > n \geq 0\}$       $G = (\{S, T, U, V, Y\}, \{a, b, c\}, P, S)$

## Example

- $\{0^n 1^m \mid m \leq n\}$       $G = (\{S\}, \{0, 1\}, P, S)$   
 where  $P = \{S \rightarrow 0S1 \mid 0S \mid \varepsilon\}$
- $\{1^n 0 \mid n \geq 0\}$       $G = (\{S\}, \{0, 1\}, P, S)$   
 where  $P = \{S \rightarrow 0 \mid 1S\}$
- $\{a^n(b^m \mid c^k) \mid n \geq 0, m, k > n\} = \{a^n b^m \mid m > n \geq 0\} \cup \{a^n c^k \mid k > n \geq 0\}$       $G = (\{S, T, U, V, Y\}, \{a, b, c\}, P, S)$   

$$\begin{aligned} T &\rightarrow aTb \mid U \\ U &\rightarrow Ub \mid b \end{aligned}$$
  
 where  $P = \{$

## Example

- $\{0^n 1^m \mid m \leq n\}$       $G = (\{S\}, \{0, 1\}, P, S)$   
 where  $P = \{S \rightarrow 0S1 \mid 0S \mid \varepsilon\}$
- $\{1^n 0 \mid n \geq 0\}$       $G = (\{S\}, \{0, 1\}, P, S)$   
 where  $P = \{S \rightarrow 0 \mid 1S\}$
- $\{a^n(b^m \mid c^k) \mid n \geq 0, m, k > n\} = \{a^n b^m \mid m > n \geq 0\} \cup \{a^n c^k \mid k > n \geq 0\}$       $G = (\{S, T, U, V, Y\}, \{a, b, c\}, P, S)$   

$$\begin{aligned} T &\rightarrow aTb \mid U \\ U &\rightarrow Ub \mid b \end{aligned}$$
 where  $P = \{$ 

$$\begin{aligned} V &\rightarrow aVc \mid Y \\ Y &\rightarrow Yc \mid c \end{aligned}$$

## Example

- $\{0^n 1^m \mid m \leq n\}$       $G = (\{S\}, \{0, 1\}, P, S)$   
 where  $P = \{S \rightarrow 0S1 \mid 0S \mid \varepsilon\}$
- $\{1^n 0 \mid n \geq 0\}$       $G = (\{S\}, \{0, 1\}, P, S)$   
 where  $P = \{S \rightarrow 0 \mid 1S\}$
- $\{a^n(b^m \mid c^k) \mid n \geq 0, m, k > n\} = \{a^n b^m \mid m > n \geq 0\} \cup \{a^n c^k \mid k > n \geq 0\}$       $G = (\{S, T, U, V, Y\}, \{a, b, c\}, P, S)$   

$$\begin{aligned} T &\rightarrow aTb \mid U \\ U &\rightarrow Ub \mid b \\ \text{where } P = \{ &V \rightarrow aVc \mid Y \} \\ &Y \rightarrow Yc \mid c \\ &S \rightarrow T \mid V \end{aligned}$$

# Table of Contents

- 1 A Quick Recap
- 2 Context-Free Grammars
- 3 Ambiguity**
- 4 Push Down Automaton
- 5 Parser

## Example

CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$

## Example

CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$     three derivations of  $[][]$ :

$$\textcircled{1} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[]]$$

## Example

CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$  three derivations of  $[[[]]$ :

$$\textcircled{1} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[[]]]$$

$$\textcircled{2} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [SS] \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[[]]]$$



## Example

CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$     three derivations of  $[[[]]$ :

$$\textcircled{1} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[[]]]$$

$$\textcircled{2} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [SS] \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[[]]]$$

$$\textcircled{3} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [SS] \xrightarrow[G]{1} [S[S]] \xrightarrow[G]{1} [S[]] \xrightarrow[G]{1} [[[]]]$$

## Example

CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$       three derivations of  $[[[]]]$ :

$$\textcircled{1} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[[]]]$$

$$\textcircled{2} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [SS] \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[[]]]$$

$$\textcircled{3} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [SS] \xrightarrow[G]{1} [S[S]] \xrightarrow[G]{1} [S[]] \xrightarrow[G]{1} [[[]]]$$

## Definition

- in **leftmost** derivation always leftmost nonterminal is replaced

① ②

## Example

CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$     three derivations of  $[][]$ :

$$\textcircled{1} \quad S \xrightarrow{1}_G [S] \xrightarrow{1}_G [[S]] \xrightarrow{1}_G [[]]$$

$$\textcircled{2} \quad S \xrightarrow{1}_G [S] \xrightarrow{1}_G [SS] \xrightarrow{1}_G [S] \xrightarrow{1}_G [[S]] \xrightarrow{1}_G [[]]$$

$$\textcircled{3} \quad S \xrightarrow{1}_G [S] \xrightarrow{1}_G [SS] \xrightarrow{1}_G [S[S]] \xrightarrow{1}_G [S[]] \xrightarrow{1}_G [[]]$$

## Definition

- in leftmost derivation always leftmost nonterminal is replaced
- in **rightmost** derivation always rightmost nonterminal is replaced

① ②

① ③

## Example

CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$       three derivations of  $[[[]]]$ :

$$\textcircled{1} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[[]]]$$

$$\textcircled{2} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [SS] \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[[]]]$$

$$\textcircled{3} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [SS] \xrightarrow[G]{1} [S[S]] \xrightarrow[G]{1} [S[]] \xrightarrow[G]{1} [[[]]]$$

## Definition

- in leftmost derivation always leftmost nonterminal is replaced ① ②
- in rightmost derivation always rightmost nonterminal is replaced ① ③
- **parse tree** is representation of derivation in which replacement order is ignored

## Example

CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$       three derivations of  $[[[]]]$ :

$$\textcircled{1} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[[]]]$$

$$\textcircled{2} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [SS] \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[[]]]$$

$$\textcircled{3} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [SS] \xrightarrow[G]{1} [S[S]] \xrightarrow[G]{1} [S[]] \xrightarrow[G]{1} [[[]]]$$

## Definition

- in leftmost derivation always leftmost nonterminal is replaced
- in rightmost derivation always rightmost nonterminal is replaced
- parse tree is representation of derivation in which replacement order is ignored
- CFG is **ambiguous** if some string has different parse trees

① ②

① ③

## Example

CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$

①  $S \xrightarrow[G]{1} [S]$

parse tree




## Example

CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$

$$\textcircled{1} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]]$$

parse tree




## Example

CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$ 

$$\textcircled{1} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[[ ]]]$$

parse tree







## Example

CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$ 

$$\textcircled{1} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[[ ]]]$$

$$\textcircled{2} \quad S \xrightarrow[G]{1} [S]$$

parse trees





## Example

CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$ 

$$\textcircled{1} \quad S \xrightarrow{G} [S] \xrightarrow{G} [[S]] \xrightarrow{G} [[[ ]]$$

$$\textcircled{2} \quad S \xrightarrow{G} [S] \xrightarrow{G} [SS]$$

parse trees





## Example

CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$

$$\textcircled{1} \quad S \xrightarrow{G} [S] \xrightarrow{G} [[S]] \xrightarrow{G} [[[ ]]$$

$$\textcircled{2} \quad S \xrightarrow{G} [S] \xrightarrow{G} [S] \xrightarrow{G} [S]$$

parse trees





## Example

CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$ 

$$\textcircled{1} \quad S \xrightarrow{G} [S] \xrightarrow{G} [[S]] \xrightarrow{G} [[[ ]]]$$

$$\textcircled{2} \quad S \xrightarrow{G} [S] \xrightarrow{G} [SS] \xrightarrow{G} [\textcolor{red}{S}] \xrightarrow{G} [[S]]$$

parse trees





## Example

CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$ 

$$\textcircled{1} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[]]$$

$$\textcircled{2} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [SS] \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[]]$$

parse trees



## Example




CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$ 

$$\textcircled{1} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[[ ]]$$

$$\textcircled{2} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [SS] \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[[ ]]$$

$$\textcircled{3} \quad S \xrightarrow[G]{1} [S]$$

parse trees



## Example




CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$ 

$$\textcircled{1} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[[ ]]]$$

$$\textcircled{2} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [SS] \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [[S]] \xrightarrow[G]{1} [[[ ]]]$$

$$\textcircled{3} \quad S \xrightarrow[G]{1} [S] \xrightarrow[G]{1} [SS]$$

parse trees



## Example




CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$ 

$$\textcircled{1} \quad S \xrightarrow{G} [S] \xrightarrow{G} [[S]] \xrightarrow{G} [[[ ]]]$$

$$\textcircled{2} \quad S \xrightarrow{G} [S] \xrightarrow{G} [SS] \xrightarrow{G} [S] \xrightarrow{G} [[S]] \xrightarrow{G} [[[ ]]]$$

$$\textcircled{3} \quad S \xrightarrow{G} [S] \xrightarrow{G} [S\textcolor{red}{S}] \xrightarrow{G} [S[S]]$$

parse trees





## Example




CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$

$$\textcircled{1} \quad S \xrightarrow{1_G} [S] \xrightarrow{1_G} [[S]] \xrightarrow{1_G} [[]]$$

$$\textcircled{2} \quad S \xrightarrow{1_G} [S] \xrightarrow{1_G} [SS] \xrightarrow{1_G} [S] \xrightarrow{1_G} [[S]] \xrightarrow{1_G} [[]]$$

$$\textcircled{3} \quad S \xrightarrow{1_G} [S] \xrightarrow{1_G} [SS] \xrightarrow{1_G} [S[S]] \xrightarrow{1_G} [S[]]$$

parse trees



## Example




CFG  $G$ :  $S \rightarrow [S] \mid SS \mid \epsilon$ 

$$\textcircled{1} \quad S \xrightarrow{1_G} [S] \xrightarrow{1_G} [[S]] \xrightarrow{1_G} [[]]$$

$$\textcircled{2} \quad S \xrightarrow{1_G} [S] \xrightarrow{1_G} [SS] \xrightarrow{1_G} [S] \xrightarrow{1_G} [[S]] \xrightarrow{1_G} [[]]$$

$$\textcircled{3} \quad S \xrightarrow{1_G} [S] \xrightarrow{1_G} [SS] \xrightarrow{1_G} [S[S]] \xrightarrow{1_G} [S[]] \xrightarrow{1_G} [[]]$$

parse trees



## Example

- CFG  $G$  :  $S \rightarrow [S] \mid SS \mid \epsilon$
- $G$  is ambiguous

## Example

- CFG  $G$  :  $S \rightarrow [S] \mid SS \mid \epsilon$
- CFG  $G'$ :  $S \rightarrow \epsilon \mid T$   
 $T \rightarrow TU \mid U$   
 $U \rightarrow [] \mid [T]$
- $G$  is ambiguous

## Example

- CFG  $G$  :  $S \rightarrow [S] \mid SS \mid \epsilon$
- CFG  $G'$  :  $S \rightarrow \epsilon \mid T$   
 $T \rightarrow TU \mid U$   
 $U \rightarrow [] \mid [T]$
- $G$  is ambiguous       $G'$  is unambiguous       $L(G) = L(G')$

## Example

- CFG  $G$  :  $S \rightarrow [S] | SS | \epsilon$
- CFG  $G'$  :  $S \rightarrow \epsilon | T$   
 $T \rightarrow TU | U$   
 $U \rightarrow [] | [T]$
- $G$  is ambiguous       $G'$  is unambiguous       $L(G) = L(G')$

$S$   
|  
 $T$   
|  
 $U$   
|  
 $[T]$   
|  
 $[U]$   
|  
 $[[]]$

## Example

- CFG  $G$  :  $S \rightarrow S - S \mid \text{int}$

- $G$  is ambiguous

with  $G$   $7 - 5 - 2$  could be parsed as  $(7 - 5) - 2$  and  $7 - (5 - 2)$

## Example


- CFG  $G$  :  $S \rightarrow S - S \mid \text{int}$
- CFG  $G'$  :  $S \rightarrow S - \text{int} \mid \text{int}$
- $G$  is ambiguous

with  $G$      $7 - 5 - 2$  could be parsed as     $(7 - 5) - 2$  and  $7 - (5 - 2)$




## Example

- CFG  $G$  :  $S \rightarrow S - S \mid \text{int}$
  - CFG  $G'$  :  $S \rightarrow S - \text{int} \mid \text{int}$
  - $G$  is ambiguous       $G'$  is unambiguous       $L(G) = L(G')$
- with  $G$      $7 - 5 - 2$  could be parsed as       $(7 - 5) - 2$  and  $7 - (5 - 2)$
- with  $G'$      $7 - 5 - 2$  could only be parsed as       $(7 - 5) - 2$




## Example

- CFG  $G$  :  $S \rightarrow S - S \mid \text{int}$
- CFG  $G'$  :  $S \rightarrow S - \text{int} \mid \text{int}$
- $G$  is ambiguous       $G'$  is unambiguous       $L(G) = L(G')$ 
  - with  $G$      $7 - 5 - 2$  could be parsed as       $(7 - 5) - 2$  and  $7 - (5 - 2)$
  - with  $G'$      $7 - 5 - 2$  could only be parsed as       $(7 - 5) - 2$
- (if applicable) one way to remove ambiguity is to benefit from **associativity** of binary operators




## Example

- CFG  $G$  :  $S \rightarrow S - S \mid \text{int}$
- CFG  $G'$  :  $S \rightarrow S - \text{int} \mid \text{int}$
- $G$  is ambiguous       $G'$  is unambiguous       $L(G) = L(G')$ 
  - with  $G$      $7 - 5 - 2$  could be parsed as       $(7 - 5) - 2$  and  $7 - (5 - 2)$
  - with  $G'$      $7 - 5 - 2$  could only be parsed as       $(7 - 5) - 2$
- (if applicable) one way to remove ambiguity is to benefit from associativity of binary operators
- $G'$  enforces the “-” operator to be **left associative**



## Example

- CFG  $G$  :  $S \rightarrow S - S \mid \text{int}$
- CFG  $G'$ :  $S \rightarrow S - \text{int} \mid \text{int}$
- $G$  is ambiguous       $G'$  is unambiguous       $L(G) = L(G')$ 
  - with  $G$      $7 - 5 - 2$  could be parsed as       $(7 - 5) - 2$  and  $7 - (5 - 2)$
  - with  $G'$      $7 - 5 - 2$  could only be parsed as       $(7 - 5) - 2$
- (if applicable) one way to remove ambiguity is to benefit from associativity of binary operators
- $G'$  enforces the “-” operator to be left associative
- CFG  $G''$ :  $S \rightarrow \text{int} - S \mid \text{int}$   
turns the “-” operator into a **right associative** one



## Example

- CFG  $G$  :  $S \rightarrow S \times S \mid S + S \mid \text{int}$

- $G$  is ambiguous

with  $G$   $7 + 5 \times 2$  could be parsed as  $7 + (5 \times 2)$  and  $(7 + 5) \times 2$

## Example

- CFG  $G$  :  $S \rightarrow S \times S \mid S + S \mid \text{int}$
- CFG  $G'$  :  $S \rightarrow S + T \mid T$   
 $T \rightarrow T \times U \mid U$   
 $U \rightarrow \text{int} \mid (S)$

- $G$  is ambiguous

with  $G$      $7 + 5 \times 2$  could be parsed as     $7 + (5 \times 2)$  and  $(7 + 5) \times 2$

## Example


- CFG  $G$  :  $S \rightarrow S \times S \mid S + S \mid \text{int}$

- CFG  $G'$  :  $S \rightarrow S + T \mid T$   
 $T \rightarrow T \times U \mid U$   
 $U \rightarrow \text{int} \mid (S)$

- $G$  is ambiguous       $G'$  is unambiguous       $L(G) = L(G')$


with  $G$        $7 + 5 \times 2$  could be parsed as       $7 + (5 \times 2)$  and  $(7 + 5) \times 2$

with  $G'$        $7 + 5 \times 2$  could only be parsed as       $7 + (5 \times 2)$



## Example

- CFG  $G$  :  $S \rightarrow S \times S \mid S + S \mid \text{int}$
- CFG  $G'$  :  $S \rightarrow S + T \mid T$   
 $T \rightarrow T \times U \mid U$   
 $U \rightarrow \text{int} \mid (S)$
- $G$  is ambiguous       $G'$  is unambiguous       $L(G) = L(G')$   
with  $G$      $7 + 5 \times 2$  could be parsed as       $7 + (5 \times 2)$  and  $(7 + 5) \times 2$   
with  $G'$      $7 + 5 \times 2$  could only be parsed as     $7 + (5 \times 2)$
- (if applicable) one way to remove ambiguity is to benefit from precedence of operators






## Parse Trees vs Abstract Syntax Trees

- parse trees (PT) are concrete syntax trees containing all derivation details


## Parse Trees vs Abstract Syntax Trees

- parse trees (PT) are concrete syntax trees containing all derivation details





## Parse Trees vs Abstract Syntax Trees

- parse trees (PT) are concrete syntax trees containing all derivation details
- abstract syntax trees (AST) are reduced PTs eliminating irrelevant information for the evaluation step



## Parse Trees vs Abstract Syntax Trees

- parse trees (PT) are concrete syntax trees containing all derivation details
- abstract syntax trees (AST) are reduced PTs eliminating irrelevant information for the evaluation step



## Remark

there exist context-free sets without unambiguous grammars

## Remark

there exist context-free sets without unambiguous grammars ( **inherently ambiguous** )

## Remark

there exist context-free sets without unambiguous grammars (inherently ambiguous)

## Example

$A = \{a^i b^j c^k \mid i = j \text{ or } j = k\}$  is context-free and inherently ambiguous

## Remark

there exist context-free sets without unambiguous grammars (inherently ambiguous)

## Example

$A = \{a^i b^j c^k \mid i = j \text{ or } j = k\}$  is context-free and inherently ambiguous

$A = \{a^i b^i c^k\} \cup \{a^i b^j c^j\}$



## Remark

there exist context-free sets without unambiguous grammars (inherently ambiguous)

## Example

$A = \{a^i b^j c^k \mid i = j \text{ or } j = k\}$  is context-free and inherently ambiguous

$A = \{a^i b^i c^k\} \cup \{a^i b^j c^j\}$

let  $A = L(G)$  such that  $G$ :

## Remark

there exist context-free sets without unambiguous grammars (inherently ambiguous)

## Example

$A = \{a^i b^j c^k \mid i = j \text{ or } j = k\}$  is context-free and inherently ambiguous

$A = \{a^i b^i c^k\} \cup \{a^i b^j c^j\}$

let  $A = L(G)$  such that  $G$ :

$$\begin{array}{ll} S \rightarrow T \mid W \\ T \rightarrow UV & W \rightarrow XY \\ U \rightarrow aUb \mid \varepsilon & X \rightarrow aX \mid \varepsilon \\ V \rightarrow cV \mid \varepsilon & Y \rightarrow bYc \mid \varepsilon \end{array}$$

## Remark

there exist context-free sets without unambiguous grammars (inherently ambiguous)

## Example

$A = \{a^i b^j c^k \mid i = j \text{ or } j = k\}$  is context-free and inherently ambiguous

$A = \{a^i b^i c^k\} \cup \{a^i b^j c^j\}$

let  $A = L(G)$  such that  $G$ :

$$\begin{array}{ll} S \rightarrow T \mid W & \\ T \rightarrow UV & W \rightarrow XY \\ U \rightarrow aUb \mid \varepsilon & X \rightarrow aX \mid \varepsilon \\ V \rightarrow cV \mid \varepsilon & Y \rightarrow bYc \mid \varepsilon \end{array}$$

the union we used has a non-empty intersection, where letters  $a$ ,  $b$  and  $c$  all are in equal number

## Remark

there exist context-free sets without unambiguous grammars (inherently ambiguous)

## Example

$A = \{a^i b^j c^k \mid i = j \text{ or } j = k\}$  is context-free and inherently ambiguous

$A = \{a^i b^i c^k\} \cup \{a^i b^j c^j\}$

let  $A = L(G)$  such that  $G$ :

$$\begin{array}{ll} S \rightarrow T \mid W \\ T \rightarrow UV & W \rightarrow XY \\ U \rightarrow aUb \mid \varepsilon & X \rightarrow aX \mid \varepsilon \\ V \rightarrow cV \mid \varepsilon & Y \rightarrow bYc \mid \varepsilon \end{array}$$

the union we used has a non-empty intersection, where letters  $a$ ,  $b$  and  $c$  all are in equal number

## Lemma

there is no CFG  $G'$  such that  $L(G')$  is unambiguous with  $L(G') = A$

## Remark

- 1 given an **ambiguous** CFG  $G$ , the language  $L(G)$  **may or may not be ambiguous**

## Remark

- 1 given an **ambiguous** CFG  $G$ , the language  $L(G)$  **may or may not be ambiguous**
  - one can find an **unambiguous** CFG  $G'$  such that  $L(G') = L(G)$

## Remark

- ① given an ambiguous CFG  $G$ , the language  $L(G)$  may or may not be ambiguous
  - one can find an unambiguous CFG  $G'$  such that  $L(G') = L(G)$
- ② there is **no algorithm** to convert ambiguous CFG to unambiguous CFG

## Remark

- 1 given an ambiguous CFG  $G$ , the language  $L(G)$  may or may not be ambiguous
  - one can find an unambiguous CFG  $G'$  such that  $L(G') = L(G)$
- 2 there is no algorithm to convert ambiguous CFG to unambiguous CFG
- 3 unambiguous context free languages can be **parsed** by **deterministic** push down automata



## Table of Contents

- 1 A Quick Recap
- 2 Context-Free Grammars
- 3 Ambiguity
- 4 Push Down Automaton**
- 5 Parser

## Definitions

- **NPDA** is septuple  $M = (Q, \Sigma, \Gamma, \delta, s, \perp, F)$  with

## Definitions

- NPDA is septuple  $M = (Q, \Sigma, \Gamma, \delta, s, \perp, F)$  with
  - 1  $Q$ : finite set of **states**

## Definitions

- NPDA is septuple  $M = (Q, \Sigma, \Gamma, \delta, s, \perp, F)$  with
  - 1  $Q$ : finite set of states
  - 2  $\Sigma$ : input alphabet

## Definitions

- NPDA is septuple  $M = (Q, \Sigma, \Gamma, \delta, s, \perp, F)$  with
  - ①  $Q$ : finite set of states
  - ②  $\Sigma$ : input alphabet
  - ③  $\Gamma$ : **stack alphabet**

## Definitions

- NPDA is septuple  $M = (Q, \Sigma, \Gamma, \delta, s, \perp, F)$  with
  - ①  $Q$ : finite set of states
  - ②  $\Sigma$ : input alphabet
  - ③  $\Gamma$ : stack alphabet
  - ④  $\delta$ : finite subset of  $(Q \times (\Sigma \cup \{\varepsilon\}) \times \Gamma) \times (Q \times \Gamma^*)$

## Definitions

- **NPDA** is septuple  $M = (Q, \Sigma, \Gamma, \delta, s, \perp, F)$  with
  - ①  $Q$ : finite set of states
  - ②  $\Sigma$ : input alphabet
  - ③  $\Gamma$ : stack alphabet
  - ④  $\delta$ : finite subset of  $(Q \times (\Sigma \cup \{\varepsilon\}) \times \Gamma) \times (Q \times \Gamma^*)$
  - ⑤  $s \in Q$ : **start** state

## Definitions

- **NPDA** is septuple  $M = (Q, \Sigma, \Gamma, \delta, s, \perp, F)$  with
  - ①  $Q$ : finite set of states
  - ②  $\Sigma$ : input alphabet
  - ③  $\Gamma$ : stack alphabet
  - ④  $\delta$ : finite subset of  $(Q \times (\Sigma \cup \{\varepsilon\}) \times \Gamma) \times (Q \times \Gamma^*)$
  - ⑤  $s \in Q$ : start state
  - ⑥  $\perp \in \Gamma$ : **initial** stack symbol



## Definitions

- **NPDA** is septuple  $M = (Q, \Sigma, \Gamma, \delta, s, \perp, F)$  with
  - ①  $Q$ : finite set of states
  - ②  $\Sigma$ : input alphabet
  - ③  $\Gamma$ : stack alphabet
  - ④  $\delta$ : finite subset of  $(Q \times (\Sigma \cup \{\varepsilon\}) \times \Gamma) \times (Q \times \Gamma^*)$
  - ⑤  $s \in Q$ : start state
  - ⑥  $\perp \in \Gamma$ : initial stack symbol
  - ⑦  $F \subseteq Q$ : **final** states

## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, []), (1, [])), ((1, \epsilon, \perp), (2, \epsilon))\}$

## Definitions

- NPDA is septuple  $M = (Q, \Sigma, \Gamma, \delta, s, \perp, F)$  with
  - 1  $Q$ : finite set of states
  - 2  $\Sigma$ : input alphabet
  - 3  $\Gamma$ : stack alphabet
  - 4  $\delta$ : finite subset of  $(Q \times (\Sigma \cup \{\varepsilon\}) \times \Gamma) \times (Q \times \Gamma^*)$
  - 5  $s \in Q$ : start state
  - 6  $\perp \in \Gamma$ : initial stack symbol
  - 7  $F \subseteq Q$ : final states
- configuration**: element of  $Q \times \Sigma^* \times \Gamma^*$

## Definitions

- NPDA is septuple  $M = (Q, \Sigma, \Gamma, \delta, s, \perp, F)$  with
  - 1  $Q$ : finite set of states
  - 2  $\Sigma$ : input alphabet
  - 3  $\Gamma$ : stack alphabet
  - 4  $\delta$ : finite subset of  $(Q \times (\Sigma \cup \{\varepsilon\}) \times \Gamma) \times (Q \times \Gamma^*)$
  - 5  $s \in Q$ : start state
  - 6  $\perp \in \Gamma$ : initial stack symbol
  - 7  $F \subseteq Q$ : final states
- configuration**: element of  $Q \times \Sigma^* \times \Gamma^*$  (current state, remaining input, stack content)

## Definitions

- NPDA is septuple  $M = (Q, \Sigma, \Gamma, \delta, s, \perp, F)$  with
  - 1  $Q$ : finite set of states
  - 2  $\Sigma$ : input alphabet
  - 3  $\Gamma$ : stack alphabet
  - 4  $\delta$ : finite subset of  $(Q \times (\Sigma \cup \{\varepsilon\}) \times \Gamma) \times (Q \times \Gamma^*)$
  - 5  $s \in Q$ : start state
  - 6  $\perp \in \Gamma$ : initial stack symbol
  - 7  $F \subseteq Q$ : final states
- configuration: element of  $Q \times \Sigma^* \times \Gamma^*$  (current state, remaining input, stack content)
- start configuration on input  $x$ :  $(s, x, \perp)$

## Definitions

- NPDA is septuple  $M = (Q, \Sigma, \Gamma, \delta, s, \perp, F)$  with
  - 1  $Q$ : finite set of states
  - 2  $\Sigma$ : input alphabet
  - 3  $\Gamma$ : stack alphabet
  - 4  $\delta$ : finite subset of  $(Q \times (\Sigma \cup \{\varepsilon\}) \times \Gamma) \times (Q \times \Gamma^*)$
  - 5  $s \in Q$ : start state
  - 6  $\perp \in \Gamma$ : initial stack symbol
  - 7  $F \subseteq Q$ : final states
- configuration: element of  $Q \times \Sigma^* \times \Gamma^*$  (current state, remaining input, stack content)
- start configuration on input  $x$ :  $(s, x, \perp)$
- next configuration relation** is binary relation  $\xrightarrow[M]{1}$  defined as:  $(p, ay, A\beta) \xrightarrow[M]{1} (q, y, \gamma\beta)$   
for all  $((p, a, A), (q, \gamma)) \in \delta$  with  $a \in \Sigma \cup \{\varepsilon\}$  and  $y \in \Sigma^*, \beta \in \Gamma^*$

## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, []), (1, [\perp)), ((1, \epsilon, \perp), (2, \epsilon))\}$

input:     [ [ ] [ [ ] ] ]

## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, ], (1, [\ ])), ((1, \epsilon, \perp), (2, \epsilon))\}$

input:     [   [ ]   [ [ ] ] ]  
state:     1  
stack:     ⊥



## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((\textcolor{red}{1}, [\textcolor{red}{\perp}), (1, [\perp)), ((1, \textcolor{blue}{]}, [\textcolor{blue}{\perp}), (1, \epsilon)), ((1, [\textcolor{blue}{]}, (1, [\textcolor{blue}{\perp})), ((1, \epsilon, \perp), (2, \epsilon))\}$

input:      $\textcolor{blue}{[} \textcolor{blue}{[} \textcolor{blue}{]} \textcolor{blue}{[} \textcolor{blue}{[} \textcolor{blue}{]} \textcolor{blue}{]} \textcolor{blue}{]}$   
state:      $\textcolor{red}{1}$   
stack:      $\textcolor{red}{\perp}$

## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, []), (1, [])), ((1, \epsilon, \perp), (2, \epsilon))\}$

input:     [ [ ] [ [ ] ] ]  
state:     1 1  
stack:      $\perp$   $\perp$   
           [

## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, [), (1, [\perp)), ((1, ], [), (1, \epsilon)), ((1, \epsilon, \perp), (2, \epsilon))\}$

input:     [ [ ] [ [ ] ] ]  
state:     1 1  
stack:      $\perp$   $\perp$   
           [

## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, ], (1, [\perp)), ((1, ], \perp), (2, \epsilon))\}$

```

input:      [ [ ] [ [ ] ] ]
state:      1 1 1
stack:      ⊥ ⊥ ⊥
            [ [

```

## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, ], (1, [\ ])), ((1, \epsilon, \perp), (2, \epsilon))\}$

input:     [ [ ] [ [ ] ] ]  
state:     1 1 1  
stack:     ⊥ ⊥ ⊥  
           [ [  
           [

## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, [\perp), (1, [\perp)), ((1, \epsilon, \perp), (2, \epsilon))\}$

input:     [ [ ] [ [ ] ] ]  
state:     1 1 1 1  
stack:     ⊥ ⊥ ⊥ ⊥  
           [ [ [  
           [

## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, [), (1, [[)), ((1, ], ]), (1, \epsilon)), ((1, \epsilon, \perp), (2, \epsilon))\}$

input:     [ [ ] [ [ ] ] ]  
state:     1 1 1 1  
stack:     ⊥ ⊥ ⊥ ⊥  
           [ [ [  
           [

## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, [\perp), (1, [\perp)), ((1, ], [\perp), (1, \epsilon)), ((1, \epsilon, \perp), (2, \epsilon))\}$

input:     [ [ ] [ [ ] ] ]  
state:     1 1 1 1 1  
stack:     ⊥ ⊥ ⊥ ⊥ ⊥  
           [ [ [ [





## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, [\perp), (1, [\perp)), ((1, \epsilon, \perp), (2, \epsilon))\}$

input:     [ [ ] [ [ ] ] ]  
state:     1 1 1 1 1 1  
stack:     ⊥ ⊥ ⊥ ⊥ ⊥ ⊥  
           [ [ [ [ [ ]  
                  [ ]

## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, [\perp), (1, [\perp)), ((1, \epsilon, \perp), (2, \epsilon))\}$

input:     [ [ ] [ [ ] ] ]  
state:     1 1 1 1 1 1  
stack:     ⊥ ⊥ ⊥ ⊥ ⊥ ⊥  
           [ [ [ [ [ [ [

## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, [\perp), (1, [\perp)), ((1, \epsilon, \perp), (2, \epsilon))\}$

input:     [ [ ] [ [ ] ] ]  
state:     1 1 1 1 1 1 1  
stack:     ⊥ ⊥ ⊥ ⊥ ⊥ ⊥ ⊥  
           [ [ [ [ [ [ [





## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, [\perp), (1, [\perp)), ((1, \epsilon, \perp), (2, \epsilon))\}$

input:	[	[	]	[	[	]	]	]
state:	1	1	1	1	1	1	1	1
stack:	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$
		[		[		[		[
			[		[		[	
				[		[		[
					[		[	
						[		[
							[	

## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, [\perp), (1, [\perp)), ((1, ], [\perp), (1, \epsilon)), ((1, \epsilon, \perp), (2, \epsilon))\}$

input:	[	[	]	[	[	]	]	]
state:	1	1	1	1	1	1	1	1
stack:	⊥	⊥	⊥	⊥	⊥	⊥	⊥	⊥
		[		[		[		[
			[		[		[	
				[		[		[



## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, [\perp), (1, [\perp)), ((1, \epsilon, \perp), (2, \epsilon))\}$

input:	[	[	]	[	[	]	]	]	$\epsilon$
state:	1	1	1	1	1	1	1	1	2
stack:	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$
		[		[		[		[	
			[		[		[		
				[		[			

## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, [\perp), (1, [\perp)), ((1, ], [\perp), (1, \epsilon)), ((1, \epsilon, \perp), (2, \epsilon))\}$

input:	[	[	]	[	[	]	]	]	$\epsilon$
state:	1	1	1	1	1	1	1	1	2
stack:	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$
		[		[		[		[	
			[		[		[		
				[		[			
					[				

## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by NPDA  $M = (Q, \Sigma, \Gamma, \delta, 1, \perp, F)$  with

- ①  $Q = \{1, 2\}$
- ②  $\Sigma = \{[, ]\}$
- ③  $\Gamma = \{\perp, [\}$
- ④  $F = \{2\}$
- ⑤  $s = 1$
- ⑥  $\delta = \{((1, [, \perp), (1, [\perp)), ((1, ], \perp), (1, \epsilon)), ((1, [, [\perp), (1, [\perp)), ((1, \epsilon, \perp), (2, \epsilon))\}$

input:	[	[	]	[	[	]	]	]	$\epsilon$		[	[	]	]	]
state:	1	1	1	1	1	1	1	1	1	2					
stack:	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$	$\perp$					
			[			[			[						
								[							









## Theorem

CFGs and NPDAs are **equivalent**:

- ①  $A = L(G)$  for some CFG  $G \iff$
- ②  $A = L(M)$  for some NPDA  $M$



## Theorem

CFGs and NPDAs are **equivalent**:

- ①  $A = L(G)$  for some CFG  $G \iff$
- ②  $A = L(M)$  for some NPDA  $M$

## Theorem

CFGs and NPDAs are **equivalent**:

- ①  $A = L(G)$  for some CFG  $G \iff$
- ②  $A = L(M)$  for some NPDA  $M$

## Determinism in PDAs (Informally)

ability to perform **at most one** transition (move)

## Determinism in PDAs (Informally)

ability to perform **at most one** transition (move)

- from the same state

## Determinism in PDAs (Informally)

ability to perform **at most one** transition (move)

- from the same state
- popping the same symbol off the stack

## Determinism in PDAs (Informally)

ability to perform **at most one** transition (move)

- from the same state
- popping the same symbol off the stack
- $\begin{cases} \text{consuming the same input character} \\ \text{consuming an input character and the empty string } \epsilon \end{cases}$

## Determinism in PDAs (Informally)

ability to perform at most one transition (move)

- from the same state
- popping the same symbol off the stack
- $\begin{cases} \text{consuming the same input character} \\ \text{consuming an input character and the empty string } \varepsilon \end{cases}$


## Definition

A **deterministic pushdown automaton (DPDA)** is an octuple  $M = (Q, \Sigma, \Gamma, \delta, \perp, \dashv, s, F)$

- 1  $\dashv$  is a special symbol not in  $\Sigma$ , called the right end-marker
- 2 for any  $p \in Q$ ,  $a \in \Sigma \cup \{\varepsilon\}$ ,  $A \in \Gamma$ , the set  $\delta \subseteq (Q \times (\Sigma \cup \{\dashv\} \cup \{\varepsilon\}) \times \Gamma) \times (Q \times \Gamma^*)$  contains
  - at most one element of the form  $((p, a, A), (q, \beta))$
  - exactly one transition of the form  $((p, a, A), (q, \beta))$  or  $((p, \varepsilon, A), (q, \beta))$

## Example

$A = \{x \in \{[, ]\}^* \mid x \text{ is balanced}\}$  is accepted by DPDA  $M = (\{0, 1\}, \{[, ]\}, \{[, \perp\}, \delta, \perp, \neg, 0, \{1\})$  with



the **final state** acceptance criterion.



## Table of Contents

- 1 A Quick Recap
- 2 Context-Free Grammars
- 3 Ambiguity
- 4 Push Down Automaton
- 5 Parser**

## Parsers (Syntactical Analyzers)

translator tool : list of tokens (lexer generated) → parse trees (or error)

## Parsers (Syntactical Analyzers)

translator tool : list of tokens (lexer generated) → parse trees (or error)

- simulate **deterministic push down automaton** to generate parse trees

## Parsers (Syntactical Analyzers)

translator tool : list of tokens (lexer generated) → parse trees (or error)

- simulate **deterministic push down automaton** to generate parse trees
- parser generators

## Parsers (Syntactical Analyzers)

translator tool : list of tokens (lexer generated) → parse trees (or error)

- simulate **deterministic push down automaton** to generate parse trees
- parser generators
  - Yacc and Bison for C

## Parsers (Syntactical Analyzers)

translator tool : list of tokens (lexer generated) → parse trees (or error)

- simulate **deterministic push down automaton** to generate parse trees
- parser generators
  - Yacc and Bison for C
  - *menhir* for OCaml

## menhir

- generates **parsers** in compatible with OCaml programs
  - input : list of *parsing rules* in the form of *context free grammars* with corresponding *actions*
  - output : a **parser** as a DPDA accepting the language generated by the input grammar
- recognizes patterns specified by the rules, associates the corresponding actions

## menhir (Specifications)

```
%{  
    header  
%}  
  
%token tkn1  
%left  tkn2  
%start <ocaml-type> S  
%%  
  
S:  
| ...      { action }  
| production1 { action };  
T:  
| production2 { action };  
...
```



## menhir (Specifications)

```
%{  
    header  
%}  
  
%token tkn1  
%left  tkn2  
%start <ocaml-type> S  
%%  
  
S:  
  | ...      { action };  
  | production1 { action };  
T:  
  | production2 { action };  
  ...  
  
where  
    header      useful OCaml code – usually just opens
```

## menhir (Specifications)

```
%{  
    header  
%}
```

```
%token tkn1  
%left  tkn2  
%start <ocaml-type> S  
%%
```

```
S:  
  | ...      { action }  
  | production1 { action };  
T:  
  | production2 { action };  
...
```

where

header	useful OCaml code – usually just opens
token	terminal symbols obtained from the lexer, e.g., tkn1

## menhir (Specifications)

```
%{  
    header  
%}
```

```
%token tkn1  
%left tkn2  
%start <ocaml-type> S  
%%
```

```
S:  
  | ...      { action }  
  | production1 { action };  
T:  
  | production2 { action };  
...
```

where

header	useful OCaml code – usually just opens
token	terminal symbols obtained from the lexer, e.g., tkn1
left	defines the tkn1 left associative

## menhir (Specifications)

```
%{  
    header  
%}
```

```
%token tkn1  
%left tkn2  
%start <ocaml-type> S  
%%
```

```
S:  
  | ...      { action }  
  | production1 { action };  
T:  
  | production2 { action };  
...
```

where

header	useful OCaml code – usually just opens
token	terminal symbols obtained from the lexer, e.g., tkn1
left	defines the tkn1 left associative
S, T, etc	CFG non-terminals such that S is the start symbol

## menhir (Specifications)

```
%{  
    header  
%}
```

```
%token tkn1  
%left tkn2  
%start <ocaml-type> S  
%%
```

```
S:  
  | ...      { action }  
  | production1 { action };  
T:  
  | production2 { action };  
...
```

where

header	useful OCaml code – usually just opens
token	terminal symbols obtained from the lexer, e.g., tkn1
left	defines the tkn1 left associative
S, T, etc	CFG non-terminals such that S is the start symbol
production	the CFG production rules

## menhir (Specifications)

```
%{  
    header  
%}
```

```
%token tkn1  
%left tkn2  
%start <ocaml-type> S  
%%
```

```
S:  
  | ...      { action }  
  | production1 { action };  
T:  
  | production2 { action };  
...
```

where

header	useful OCaml code – usually just opens
token	terminal symbols obtained from the lexer, e.g., tkn1
left	defines the tkn1 left associative
S, T, etc	CFG non-terminals such that S is the start symbol
production	the CFG production rules
actions	are OCaml expressions of the same type

## menhir (Specifications)

```
%{  
    header  
%}
```

```
%token tkn1  
%left tkn2  
%start <ocaml-type> S  
%%
```

```
S:  
  | ...      { action }  
  | production1 { action };  
T:  
  | production2 { action };  
...
```

where

header	useful OCaml code – usually just opens
token	terminal symbols obtained from the lexer, e.g., tkn1
left	defines the tkn1 left associative
S, T, etc	CFG non-terminals such that S is the start symbol
production	the CFG production rules
actions	are OCaml expressions of the same type
%%	the obligatory sign separates the header from the production rules

## Example (Balanced Parentheses – Abstract Syntax Tree)

(\* **ast.ml** \*)

open Printf

type bp =

- | Join : (bp\*bp) → bp
- | Single: bp → bp
- | Const : bp
- | Str : string → bp
- | Int : int → bp

let rec bp2String (b: bp): string =

match b with

- | Join(b1, b2) → bp2String b1 ^ "\_" ^ bp2String b2
- | Single b1 → "LPAREN\_" ^ bp2String b1 ^ "\_RPAREN"
- | Const → "LPAREN\_RPAREN"
- | Str s → "IDENT=[\" ^ s ^ "]"
- | Int i → "NUM=[\" ^ (string\_of\_int i) ^ "]"

let printBp (b: bp): unit =

printf "%s\n" (bp2String b)



## Example (menhir: Balanced Parentheses – Header and Tokens)

```
(* parser.mly *)
```

```
%{
```

```
    open Ast
```

```
%}
```

```
%token BLANK LPAREN RPAREN EOL
```

```
%token <string> IDENT
```

```
%token <int> NUM
```

```
%start <bp> start
```

```
%%
```

## Example (menhir: Balanced Parentheses – Production Rules)

```
(* parser.mly *)
```

```
start:
```

```
  | a = T; EOL                { a };
```

```
T:
```

```
  | a = T; b = U              { Join(a,b) }  
  | b = U                     { b };
```

```
U:
```

```
  | LPAREN; RPAREN           { Const }  
  | LPAREN; a = T; RPAREN    { Single a }  
  | s = IDENT                 { Str s }  
  | i = NUM                   { Int i }  
  | BLANK                     { Str "" }
```

## Example (menhir: Balanced Parentheses – Main)

```
(* main.ml *)
open Printf
open Lexing
open Lexer
open Ast
open Parser

let tokenSwitch (t: Lexer.token): Parser.token =
  match t with
  | BLANK   → BLANK
  | LPAREN  → LPAREN
  | RPAREN  → RPAREN
  | EOL     → EOL
  | IDENT s → IDENT s
  | NUM i   → NUM i

let compose (f:  $\alpha \rightarrow \beta$ ) (g:  $\beta \rightarrow \gamma$ ):  $\alpha \rightarrow \gamma$  = fun x → g (f x)
let astOfString (s: string): bp = start (compose tokenize tokenSwitch) (from_string s)
let main: unit = let ast = astOfString "[[][][[[]]]][ekici2023]" in printBp ast;
```

## Remark (in “parser.mly”)

where

start: (Lexing.lexbuf  $\rightarrow$  Parser.token)  $\rightarrow$  bp    function maps an input stream to parser tokens

Thanks! & Questions?