

403 Forbidden

本电子书由CyberArticle制作。点击[这里](#)下载CyberArticle。注册版本不会显示该信息。[删除广告](#)

AP瘦切胖配置方法

目录

AP瘦切胖配置案例	1
1.1 适用产品系列	1
1.1.1 AP瘦切胖配置案例（命令行）	1
1.1.2 AP瘦切胖配置案例（Bootrom）	3

1.1 适用产品系列

本手册适用于如下产品：WAP712C、WAP722E、WAP722S、WAP722、WAP621

1.1.1 AP瘦切胖配置案例（命令行）

操作风险提示：AP瘦切胖有风险，操作不当或者意外断电会导致设备故障，操作需谨慎。WAP722E和、WAP722没有Console口，建议使用Telnet方式登入命令行。命令行升级需在PC上搭建TFTP Server（推荐用户使用3CDaemon搭建TFTP服务器）

将软件版本下载到设备FLASH内，然后通过命令行加载Bootrom版本，再加载主机软件版本，加载时输入的文件名一定要一致，建议复制黏贴，然后升级过程中避免断电重启操作。

具体操作如下：


1. 从新华三的官网下载对应AP型号的胖版本，下载到电脑后，需修改文件名，以WAP621为例子，修改对应的启动文件名wa2600a_fat.bin，需要注意文件名称修改正确。

AP型号和使用版本关系：

AP-mode	版本名称

H3C WAP621	wa2600a_fat.bin
H3C WAP722	wa4300_fat.bin
H3C WAP722E	
H3C WAP722S	wa4300s_fat.bin
H3C WAP712C	
H3C WAP712H	

2. 电脑网卡设置为：192.168.0.1/255.255.255.0，如下例子打开TFTP服务器，把软件版本WA2600a_fat.bin放到电脑桌面上，TFTP服务器目录指向电脑桌面，然后点击确定



3. 创建AP的ip地址，AP设置地址为192.168.0.2 255.255.255.0，和电脑同一个网段，保证电脑和AP网络可达。以下标黑部分为设备自动打印部分，标红加粗的命令是需要手动输入。

<H3C> **system**

[H3C] **interface vlan1**

[H3C-Vlan-interface1] **ip address 192.168.0.2 255.255.255.0**

[H3C-Vlan-interface1] **quit**

4. 通过TFTP上传胖AP：wa2620a_fat.bin，192.168.0.1是电脑的ip，

<H3C> **tftp 192.168.0.1 get wa2600a_fat.bin**

File will be transferred in binary mode.

Downloading file from remote tftp server, please

wait.....

TFTP: 4602950 bytes received in 115 second(s).

File downloaded successfully.

备注：如果提示FLASH空间不足已放下新版本请将老版本删除，删除后请勿重启，否则设备已无系统，只能通过bootrom升级。

<H3C> **delete /unreserved wa2600a_fit.bin**

//如果空间不够，可以删除原有的软件版本释放存储空间

<H3C> **tftp 192.168.0.1 get wa2600a_fit.bin**

5. 加载BOOTROM

<H3C> **bootrom update file wa2600a_fit.btm**（此步忽略）

please wait ...

Bootrom is updated!

6. 加载主机软件

<H3C> **boot-loader file wa2600a_fit.bin main**


<H3C> **reboot**

7. 重启设备完成后就可以使用默认的管理地址192.168.0.50登录AP进行管理了。登录AP的默认用户名是admin，密码是h3capadmin。

1.1.2 AP瘦切胖配置案例（Bootrom）

1. 使用Console口登入到命令行，从官网下载WAP621的软件版本，将压缩包解压，将里面的文件名称修改为wa2600a_fit.bin

2. 电脑网卡设置为：192.168.0.1 255.255.255.0，如下例子打开TFTP服务器，把软件版本WA2600a_fit.bin放到电脑桌面上，TFTP服务器目录指向电脑桌面，然后点击确定



3. 在AP重启的时候按住**Ctrl+B**进入设备的bootrom菜单，以下标黑部分为设备

自动打印部分，标红加粗的命令是需要手动输入。

```

=====<EXTEND-BOOTWARE
MENU>=====
|<1> Boot System
|<2> Enter Serial SubMenu
|<3> Enter Ethernet SubMenu
|<4> File Control
|<5> Restore to Factory Default Configuration
|<6> Skip Current System Configuration
|<7> BootWare Operation Menu
|<8> Clear Super Password
|<9> Storage Device Operation
|<0> Reboot
=====
Ctrl+C: Display Copyright
Ctrl+F: Format File System
Enter your choice(0-9): Ctrl+F
y
Enter your choice(0-9): 3（此处输入）
=====<Enter                                     Ethernet
SubMenu>=====
|Note:the operating device is flash
|<1> Download Application Program To SDRAM And Run
|<2> Update Main Application File
|<3> Update Backup Application File
|<4> Update Secure Application File
|<5> Modify Ethernet Parameter
|<0> Exit To Main Menu
|<Ensure The Parameter Be Modified Before Downloading!>
=====
4. 进入修改以太网参数菜单，使用TFTP网络协议传输wa2600a_fat.bin到AP上
Enter your choice(0-5): 5
=====<ETHERNET PARAMETER SET>=====
|Note:      '.' = Clear field.
|          '.' = Go to previous field.
|          Ctrl+D = Quit.

```

```

=====
Protocol (FTP or TFTP) : TFTP
//忽略输出内容，直接输入TFTP，然后回车
Load File Name      :wa2600a_fat.bin
//忽略输出内容，直接输入wa2600a_fat.bin，然后回车
Target File Name    :wa2600a_fat.bin
//忽略输出内容，直接输入wa2600a_fat.bin，然后回车
Server IP Address   :192.168.0.1
//忽略输出内容，直接输入电脑主机的 IP，比如192.168.0.1，然后回车
Local IP Address    :192.168.0.50
//忽略输出内容，直接输入和电脑主机的ip同一网段，比如192.168.0.50，然后回车
Gateway IP Address  :0.0.0.0
//忽略输出内容，直接回车
备注：注意给电脑手动配置一个与AP同网段的IP地址，保证电脑与AP路由可达

```

```

=====<Enter Ethernet SubMenu>=====
|Note:the operating device is flash
|<1> Download Application Program To SDRAM And
|<2> Update Main Application File
|<3> Update Backup Application File
|<4> Update Secure Application File
|<5> Modify Ethernet Parameter
|<0> Exit To Main Menu
|<Ensure The Parameter Be Modified Before Downloading!>

```

```

=====
Enter your choice(0-5): 2 //此时可以看到TFTP服务器上数据上传的滚动
Loading.....
.....Done!

```

5. 返回主菜单，查看设备上是否真的已经上传了该软件版本

```

=====<Enter Ethernet
SubMenu>=====
|Note:the operating device is flash
|<1> Download Application Program To SDRAM And R
|<2> Update Main Application File
|<3> Update Backup Application Fil
|<4> Update Secure Application File

```

|<5> Modify Ethernet Parameter

||<0> Exit To Main Menu

|<Ensure The Parameter Be Modified Before Downloading!>

|=====

Enter your choice(0-5): 0

=====<EXTEND-BOOTWARE
MENU>=====

<1> Boot System

<2> Enter Serial SubMenu

<3> Enter Ethernet SubMenu

<4> File Control

<5> Restore to Factory Default Configuration

<6> Skip Current System Configuration

<7> BootWare Operation Menu

<8> Clear Super Password

<9> Storage Device Operation

<0>Reboot

=====

Ctrl+C: Display Copyright

Ctrl+F: Format File System

Enter your choice(0-9): 4

=====<File
CONTROL>=====

|Note:the operating device is flash

<1> Display All File(s)

<2> Set Application File type

<3> Delete File

<0> Exit To Main Menu

=====

Enter your choice(0-3): 1

Display all file(s) in flash:

'M' = MAIN 'B' = BACKUP 'S' = SECURE 'N/A' = NOT ASSIGNED

NO.	Size(B)	Time	Type	Name
1	9124864	Aug/08/2008 20:00:00 M		wa2600a_fat.bin

6. 返回主菜单，将设备进行重启

[Note:the operating device is flash

<1> Display All File(s)

<2> Set Application File type

<3> Delete File

<0> Exit To Main Menu

=====

Enter your choice(0-3): 0

=====<EXTEND-BOOTWARE
MENU>=====

<1> Boot System

<2> Enter Serial SubMenu

<3> Enter Ethernet SubMenu

<4> File Control

<5> Restore to Factory Default Configuration

<6> Skip Current System Configuration

<7> BootWare Operation Menu

<8> Clear Super Password

<9> Storage Device Operation

<0>Reboot

=====

Ctrl+C: Display Copyright

Ctrl+F: Format File System

Enter your choice(0-9): 0

System is starting...

7. 重启设备完成后就可以使用默认的管理地址192.168.0.50登录AP进行管理了。登录AP的默认用户名是admin，密码是h3capadmin。