

Inspection Certificate 3.1

Certified according to 3.1/EN10204

Purchaser: GEMUE Gebr. Müller Apparatebau GmbH & Co.KG

Order No. 86411
Invoice No.: 2026-KM-012

Vendor No.

Supplier address: Shanghai Kumai Valve Coll, Ltd
No198-8 Zhanfa Rd, Nanqiao Town, Fengxian District, Shanghai, China

Acceptance representative:

Overview of Certificates

Pos.	Type code	Size	GEMÜ Item-No.	Supplier Code	Q'ty
10	88999181	DN50	R470 50L664A6TLF05 D11	54050011	2
Description	Material	Heat No.			
Body	1.4408 / ASTM A351 CF8M	26C05			
Disc	1.4408 / ASTM A351 CF8M	25D30			
Shaft	1.4542/ 17-4Ph ASTM 564 630	JS2303-076			
Seal Retainer	ASTM A240/A240M	NZ21201AX01			
Packing Gland / washer	ASTM A351 CF8	25D17			
Bottom Screw / Bottom Cap	1.4408 / ASTM A351 CF8M	PF16,PF26			

Chemical Properties

Material : 1.4408/CF8M
acc 0-0005-KZ77rev.065551

Body

GEMÜ Article	Material	Heat No.	C	Si	Mn	P	S	Ni	Cr	Mo	Cu
			Max.	Max.	Max.	Max.	Max.	9-12	18 - 20	2 - 2,5	≤0,50
			0.07	1.5	1.5	0.04	0.03				
88999181	1.4408 / ASTM A351 CF8M	26C05	0.038	0.68	1.05	0.036	0.003	9.38	18.22	2.14	0.14

Mechanical Properties

Material : 1.4408/CF8M
acc 0-0005-KZ77 rev.065551
Mechanical values:
(tested according to EN ISO 6892-1)
(tested according to DIN EN ISO 148)
material is certified according to EN 10213

Body

GEMÜ Article	Heat No.	Yield	Tensile	Elongation	Reduction of Area	Heat Treatment	Impact Test
		(N/mm²)	(N/mm²)	(%)		Temperature °C/ time	(Joule)
		≥210	485-640	≥30		1040°C	min. 60J RT
88999181	26C05	275	593	42		1080°C/2h	163.7

Inspection Certificate 3.1

Certified according to 3.1/EN10204

Purchaser: GEMUE Gebr. Müller Apparatebau GmbH & Co.KG

Order No. 86411
Invoice No.: 2026-KM-012

Vendor No.

Supplier address: Shanghai Kumai Valves Ltd.
Shanghai, Minhang District, Hongmei No4999-118 Road
China

Acceptance representative:

Chemical Properties
Material : 1.4408/CF8M
acc 0-0005-KZ77 rev.065551

Disc

GEMÜ Article	Material	Heat No.	C	Si	Mn	P	S	Ni	Cr	Mo	Cu
			Max.	Max.	Max.	Max.	Max.	9 - 12	18 - 20	2 - 2,5	≤0,50
			0.07	1.5	1.5	0.04	0.03				
88999181	1.4408/ CF8M	25D30	0.037	0.498	1.27	0.035	0.0054	9.45	18.93	2.22	0.149

Mechanical Properties
Material : 1.4408/CF8M
acc 0-0005-KZ77 rev.065551
Mechanical values:
(tested according to EN ISO 6892-1)
(tested according to DIN EN ISO 148)
material is certified according to EN 10213

Disc

GEMÜ Article	Heat No.	Yield	Tensile	Elongation	Reduction of Area	Heat Treatment	Impact Test
		(N/mm²)	(N/mm²)	(%)		Temperature °C/ time	(Joule)
		≥210	485-640	≥30		1040°C	min. 60J RT
88999181	25D30	233	596	58		1080°C/2h	155

Inspection Certificate 3.1

Certified according to 3.1/EN10204

Purchaser: GEMUE Gebr. Müller Apparatebau GmbH & Co.KG

Order No. 86411
Invoice No.: 2026-KM-012

Vendor No.

Supplier address: Shanghai Kumai Valves Ltd.
Shanghai, Minhang District, Hongmei No4999-118 Road
China

Acceptance representative:

Chemical Properties Material : 1.4542/ 17-4Ph ASTM 564 630
acc 0-0005-LB01

Shaft

GEMÜ Article	Material	Heat No.	C	Si	Mn	P	S	Ni	Cr	Mo	Cu
			Max.	Max.	Max.	Max.	Max.	3-5	15-17.5		3-5
			0.07	1	1	0.04	0.03				
88999181	1.4542/ 17-4Ph ASTM 564 630	JS2303-076	0.043	0.44	0.63	0.039	0.001	3.78	15.69		3.15

Material : 1.4542/ 17-4Ph ASTM 564 630
acc 0-0005-LB01

Mechanical Properties

Mechanical values:
(tested according to EN ISO 6892-1)
(tested according to DIN EN ISO 148)
material is certified according to EN 10213

Shaft

GEMÜ Article	Heat No.	Yield	Tensile	Elongation	Reduction of Area	Heat Treatment	Hardness
		(N/mm²)	(N/mm²)	(%)		Temperature °C/ time	(HRC)
		≥725	≥930	≥16		1040°C	≥28
88999181	JS2303-076	1076	1092	21	50	1040°C/2h	30

Inspection Certificate 3.1

Certified according to 3.1/EN10204

Purchaser: GEMUE Gebr. Müller Apparatebau GmbH & Co.KG
Order No.: 86411
Invoice No.: 2026-KM-012

Vendor No.

Supplier address: Shanghai Kumai Valves Ltd.
Shanghai, Minhang District, Hongmei No4999-118 Road
China

Acceptance representative:

Chemical Properties Material : ASTM A240/A240M acc 0-0005-KZ77

Seal Retainer

GEMÜ Article	Material	Heat No.	C	Si	Mn	P	S	Ni	Cr	Mo	Cu
			Max.	Max.	Max.	Max.	Max.	10-14	16-18	2-3	≤0,50
			0.03	0.75	2	0.045	0.03				
88999181	ASTM A240/A240M	N221201AX01	0.017	0.37	1.02	0.037	0.001	10.03	16.46	2.03	

Material : ASTM A240/A240M acc 0-0005-KZ77
rev.065551

Mechanical Properties

Mechanical values:
(tested according to EN ISO 6892-1)
(tested according to DIN EN ISO 148)
material is certified according to EN 10213

Seal Retainer

GEMÜ Article	Heat No.	Yield	Tensile	Elongation	Reduction of Area	Heat Treatment	Hardness
		(N/mm²)	(N/mm²)	(%)		Temperature °C/ time	(HRB)
		≥170	485-640	≥40		1040°C	max.95
88999181	N221201AX01	282	570	56		1040°C	82.4

Inspection Certificate 3.1

Certified according to 3.1/EN10204

Purchaser: GEMUE Gebr. Müller Apparatebau GmbH & Co.KG
Order No.: 86747
Invoice No.: 2026-KM-019

Vendor No.

Supplier address: Shanghai Kumai Valves Ltd.
Shanghai, Minhong District, Hongmei No4999-118 Road
China

Acceptance representative:

Chemical Properties

Material : ASTM A351 CF8
acc 0-0005-??

Packing Gland / washer

GEMÜ Article	Material	Heat No.	C	Si	Mn	P	S	Ni	Cr	Mo	Cu
			Max.	Max.	Max.	Max.	Max.	8-11	18 - 21	≤0,50	≤0,50
			0.08	2	1.5	0.04	0.04				
88999181	ASTM A351 CF8	25D17	0.052	0.46	1.30	0.034	0.0046	8.24	18.93	1.3	

Material : ASTM A351 CF8 acc 0-0005-KZ77
rev.065551

Mechanical Properties

Mechanical values:
(tested according to EN ISO 6892-1)
(tested according to DIN EN ISO 148)
material is certified according to EN 10213

Packing Gland / washer

GEMÜ Article	Heat No.	Yield	Tensile	Elongation	Reduction of Area	Heat Treatment	Impact Test
		(N/mm²)	(N/mm²)	(%)		Temperature °C/ time	(Joule)
		≥205	≥485	≥35		1040°C	min. 60J RT
88999181	25D17	236	564	50		1040°C/2h	

Inspection Certificate 3.1

Certified according to 3.1/EN10204

Purchaser: GEMUE Gebr. Müller Apparatebau GmbH & Co KG

Order No. 86411
Invoice No.: 2026-KM-012

Vendor No.

Supplier address: Shanghai Kumai Valves Ltd.
Shanghai, Minhang District, Hongmei No4999-118 Road
China

Acceptance representative:

Chemical Properties 1.4408 / ASTM A351 CF8M
acc 0-0005-KZ77 rev.065551

Bottem Screw / Bottem Cap

GEMÜ Article	Material	Heat No.	C	Si	Mn	P	S	Ni	Cr	Mo	Cu
			Max.	Max.	Max.	Max.	Max.	9 - 12	18 - 20	2 - 2,5	≤0,50
			0.07	1.5	1.5	0.04	0.03				
88999181	1.4408 / ASTM A351 CF8M	PF26	0.0247	0.91	1.16	0.0316	0.00121	9.2	18.19	2.1768	0.066
88999181	1.4408 / ASTM A351 CF8M	PF16	0.0225	0.626	1.13	0.0277	0.0002	9.03	18.39	2.1697	0.059

Mechanical Properties

Material : 1.4408 / ASTM A351 CF8M
acc 0-0005-KZ77 rev.065551
Mechanical values:
(tested according to EN ISO 6892-1)
(tested according to DIN EN ISO 148)
material is certified according to EN 10213

Bottem Screw / Bottem Cap

		Yield	Tensile	Elongation		Heat Treatment	Impact Test
GEMÜ Heat		(N/mm²)	(N/mm²)	(%)	Reduction of Area	Temperature °C/ time	(Joule)
Article No.		≥210	485-640	≥30		1040°C	min. 60J RT
88999181	PF26	218	517	36		1050°C/1h	95
88999181	PF16	216	514	37		1050°C/1h	96

Inspection Certificate 3.1

Certified according to 3.1/EN10204

Purchaser: GEMUE Gebr. Müller Apparatebau GmbH & Co KG
Order No.: 86411
Invoice No.: 2026-KM-012

Vendor No.

Supplier address: Shanghai Kumai Valves Ltd.
Shanghai, Minhang District, Hongmei No4999-11B Road
China

Acceptance representative:

Test certificate

Item No.	Heat	Heat	Heat	Heat	Heat	Heat	PO Pos.	GEMÜ Article	Description	QTY	Pressure Test (Kg/cm²) DIN EN 12266-1:2012-06			Test Result
	No.	No.	No.	No.	No.	No.					Hydro- static	Water	Gas	
	Body	Disc	Shaft	Seal Retainer	Packing Gland / washer	Bottom Screw / Bottom Cap								
1	26C05	25D30	JS2303-076	N221201AX01	25D17	PF16	10	88999181	R470 50L664A6TLF05 D11	1	60bar	60bar	6bar	Ok
2	26C05	25D30	JS2303-076	N221201AX01	25D17	PF26	10	88999181	R470 50L664A6TLF05 D11	1	60bar	60bar	6bar	Ok

Authorized Signature

We herewith certify that the material described herein has been made in accordance to the above specification and also with the requirement called for above order. All items have been inspected and tested to the satisfaction of the inspector.

Signature:

杨燕