The matchedsplit package

Matched delimiters across manually broken equations

Yu Zhai
me@zhaiyusci.net

Version 0.8.1 — 29 October 2026

Abstract

The matchedsplit package permits a `\left`, `\middle`, `\right` construction to cross manually chosen alignment rows. Each delimiter pair is sized independently from its contents, including nested pairs. The package provides an unnumbered inner alignment and numbered or unnumbered display alignments. Optional package settings replace the `split` and `align` environments of amsmath.

Contents

1 Getting started **2**

2 Environments and package options **3**

3 Delimiter sizing and nested structures **5**

4 Row control, tags and references **6**

5 Rainbow delimiters **7**

6 Compatibility, diagnostics and limitations **8**

7 Version history and distribution information **9**

© 2026 Yu Zhai. Distributed under the LaTeX Project Public License, version 1.3c or later. Maintenance status: maintained. Current maintainer: Yu Zhai, me@zhaiyusci.net.

1 Getting started

1.1 Requirements and installation

The package requires LaTeX 2$_\varepsilon$ dated 2020-10-01 or later and loads amsmath, xcolor and l3keys2e automatically. The command-copy and hook interfaces require this kernel date. Older formats produce an explicit package error. Testing uses the engines supplied with TeX Live 2026, including kernel rollback to 2020-10-01. Rollback retains installed package versions and is not a test of an entire historical TeX distribution.

For a local installation, place `matchedsplit.sty` beside the main source file. For a personal TEXMF installation, place it in `tex/latex/matchedsplit/` below your local TEXMF tree and refresh the filename database if your installation requires it.

```
\usepackage{matchedsplit}
```

No package option is needed to use the new environments. Loading the package without options leaves the native `split`, `align` and `align*` definitions unchanged.

1.2 A complete example

```
\documentclass{article}
\usepackage{matchedsplit}
\begin{document}
\begin{matchedalign}
F &= \left( a+\frac{x}{y} \label{eq:first}\\
  &\quad +\frac{p}{q}\right)\label{eq:second}
\end{matchedalign}
See \eqref{eq:second}.
\end{document}
```

The two rows receive separate numbers, while the parentheses retain the same size:

$$F = \left(a + \frac{x}{y} \right. \tag{1}$$

$$\left. + \frac{p}{q} \right) \tag{2}$$

Compile twice to resolve references, such as (2). The package does not choose line breaks: the author supplies `\\` and alignment markers `&`.

2 Environments and package options

2.1 Environment reference

Environment	Numbering and placement
`matchedaligned`	Inner alignment; explicit top/center/bottom position.
`matchedsplit`	Inner math alignment; numbering belongs to its parent.
`matchedalign`	Display alignment; one number per row by default.
`matchedalign*`	Display alignment; no automatic numbers.
`matchedalignat`	Display alignment; explicit column pairs and spacing.
`matchedalignat*`	Same layout; no automatic numbers.

Use `matchedsplit` inside `equation`, `equation*`, `\[...\]`, or an appropriate outer math alignment. Use `matchedalign` directly in document text, not inside `equation` or `\[...\]`. The special amsmath arrangement of an `align` inside `gather` has also been tested with the replacement.

2.2 One number for the complete formula

```
\begin{equation}\label{eq:whole}
\begin{matchedsplit}
G &= \left(\frac{a}{b}\\
  &\quad +c\right)
\end{matchedsplit}
\end{equation}
```

$$G = \left(\frac{a}{b} \\ \quad +c\right) \tag{3}$$

2.3 Explicit column pairs and spacing (unreleased)

Use `\begin{matchedalignat}[local options]{n}` directly in document text, outside math mode. The mandatory argument counts right/left column pairs, as in native `alignat`. Unlike `align`, no extra space is inserted between pairs: supply `\quad` or other spacing where needed. Native column-count limits apply.

```
\begin{matchedalignat}[rainbow]{2}
F &= \left(a+\frac{x}{y} &\quad&\text{first part}\\
  &+b\right)             &&\text{continuation}
\end{matchedalignat}
```

$$F = \left(a + \frac{x}{y} \quad \text{first part} \tag{4}$$

$$\quad +b\right) \qquad \text{continuation} \tag{5}$$

The starred form `matchedalignat*` suppresses automatic numbering. Both forms retain native tags, labels, `\notag` and `\intertext`. The optional argument accepts the same local color settings as `matchedalign`. The independent `overridealignat` option replaces both native forms and can be combined with `overridealign`.

2.4 Replacing the native environments

Option	Default	Effect
`overridesplit`	Off	Replace `split`.
`overridealign`	Off	Replace `align` and `align*`.
`overridealignat`	Off	Replace `alignat` and `alignat*`.
`rainbow`	Off	Color delimiters by nesting depth.

```
\usepackage[overridesplit,overridealign]{matchedsplit}
```

The options are independent. The replacement `split` uses an `aligned` layout; it does not reproduce every width calculation of native `split`. The replacement `align` delegates numbering and layout to the saved native amsmath implementation.

Configure amsmath before loading this package, for example:

```
\usepackage[tbtags,leqno]{amsmath}
\usepackage[overridesplit]{matchedsplit}
```

With `tbtags`, both `matchedsplit` and replacement `split` align a right-hand tag with the last row, or a left-hand tag with the first row. Otherwise it centers the block vertically for tagging. Applying this policy to the direct `matchedsplit` entry point is an unreleased change.

The package handles delimiter layout. It does not guarantee the semantic correctness of formulas or of the generated mathematical structure in tagged PDFs.

2.5 An embedded alignment with explicit position

The unreleased `matchedaligned` environment uses native `aligned` layout. It takes two optional arguments: first the vertical position `t`, `c`, or `b` (default `c`), then local color options. This position is independent of `tbtags`. Numbering belongs to the outer environment. Native `aligned` is not replaced.

```
\[
\left\{
\begin{matchedaligned}[t][rainbow,colors={blue,red}]
F &= \left(a+\frac{x}{y}\\
  &+b\right)
\end{matchedaligned}
\right.\qquad x>0
\]
```

$$\begin{cases} F = \left(a + \dfrac{x}{y} & x > 0 \\ \quad + b \right) \end{cases}$$

For centered placement with local coloring, use `\begin{matchedaligned}[c][rainbow]`. With no arguments, `\begin{matchedaligned}` uses centered placement and package defaults.

3 Delimiter sizing and nested structures

A pair wholly contained in one alignment cell keeps native left/right layout, including its mathematical spacing next to operators. Spanning pairs retain the original matched-size measurement method on every engine.

A pair is sized from its mathematical contents after removing the outer alignment markers, row breaks and supported numbering commands. The size is *not* the total height of the multirow display. A tall fraction affects every pair that contains it, but not an unrelated pair.

3.1 Nested pairs

```
\begin{matchedalign}
F &= \left( a+\left[\frac{x}{y}+b \\
  &\quad +c\right]+d \\
  &\quad +\frac{p}{q}\right)
\end{matchedalign}
```

$$F = \left(a + \left[\frac{x}{y} + b \right. \tag{6}$$

$$\left. + c \right] + d \tag{7}$$

$$+ \frac{p}{q} \right) \tag{8}$$

The square brackets form the inner pair and are measured separately from the surrounding parentheses.

3.2 Middle and invisible delimiters

`\middle` belongs to the innermost currently open pair. A period is accepted as an invisible delimiter, as in ordinary TEX.

```
\begin{matchedalign*}
S &= \left\{ x\in\mathbb{R} \middle| \frac{x}{2}>0 \\
  &\quad \middle| x<10\right\}
\end{matchedalign*}
```

$$S = \left\{ x \in \mathbb{R} \;\middle|\; \frac{x}{2} > 0 \;\middle|\; x < 10 \right\}$$

Use standard single-token delimiter characters or commands, for example `(`, `\{`, `\langle` and `.`.

3.3 Groups and inner environments

Braced groups retain their braces. Rainbow mode recursively colors explicit delimiter pairs inside groups without changing their mathematical structure. Inner environments, including matrices, retain their own alignment markers and row breaks. A delimiter pair must not cross a group or inner-environment boundary. Native math inside such a structure must already be valid on its own; the outer scanner does not repair it.

4 Row control, tags and references

Supported row endings are `\\`, `\\*`, `\\[3pt]` and `\\*[3pt]`. Their spacing arguments are retained for layout and excluded from delimiter measurements.

In `matchedalign`, use `\label` and `\eqref` as usual. `\notag` or `\nonumber` suppresses a row number. `\tag{A}` supplies a custom tag; `\tag*{B}` omits its usual surrounding parentheses. The counter behavior is that of amsmath, including the effect of custom tags on automatic numbering.

```
\begin{matchedalign}
H &= \left(\frac{a}{b}\tag{A}\label{eq:custom}\\
  &\quad +x\notag\\
  &\quad +y\right)\label{eq:last}
\end{matchedalign}
```

$$H = \left(\frac{a}{b} \right. \tag{A}$$
$$\left. \begin{aligned} &+ x \\ &+ y \end{aligned} \right) \tag{9}$$

The custom tag can be referenced as (A). Labels and tags must be at the top level of the relevant row and use braced arguments. Commands hidden in braced groups are not extracted from measurement content.

4.1 Text between rows

`\intertext` is supported in the display alignments, including while a delimiter pair remains open:

```
\begin{matchedalign}
f &= \left\langle\frac{a}{b}\\
\intertext{The same delimiter pair continues.}
  &\quad +c\right\rangle
\end{matchedalign}
```

$$f = \left\langle \frac{a}{b} \tag{10}$$

The same delimiter pair continues.

$$+ c \right\rangle \tag{11}$$

The text is not measured as part of the mathematics. `\displaybreak[0]` and other native break levels are retained for amsmath. They do not make a boxed `matchedsplit` breakable. Comprehensive multipage pagination tests have not been performed.

5 Rainbow delimiters

The option `niji` aliases `rainbow` at package and environment scope; `niji=false` disables it locally. Color resets stay inside the math atom so superscripts, subscripts and primes retain their attachment.

The optional rainbow mode colors delimiters by nesting depth. Matching left and right delimiters, and any middle delimiters belonging to that pair, use the same color across rows. Ordinary formula contents and numbers retain their surrounding color. This feature is inspired by rainbow-parenthesis highlighting in editors such as Vim's niji.

5.1 Package defaults and local overrides

```
\usepackage[rainbow]{matchedsplit}
% Enable globally, but disable for this display:
\begin{matchedalign}[rainbow=false]
f &= \left(a\\ &+b\right)
\end{matchedalign}
```

Without a package default, opt in for a single environment:

```
\begin{matchedalign*}[rainbow]
f &= \left\{\frac{a}{b}+\left[x+\left(y\middle|z\\
  &\quad +1\right)\right]\right\}
\end{matchedalign*}
```

$$f = \left\{ \frac{a}{b} + \left[x + \left(y \;\middle|\; z \right.\right.\right.$$
$$\left.\left.\left. + 1 \right) \right] \right\}$$

For `matchedaligned`, use the second optional argument for colors. The single optional argument is available on `matchedsplit`, `matchedalign` and `matchedalign*`. With the corresponding replacement options enabled it is also available on `split`, `align` and `align*`. Environment settings override package defaults for that environment only; they do not change later displays. An omitted value in `rainbow` means `rainbow=true`.

5.2 Choosing a palette

```
\usepackage[rainbow,colors={blue,orange,teal}]{matchedsplit}
% A different palette for one display:
\begin{matchedalign}[rainbow,colors={red!70!black,blue}]
f &= \left(a+\left[b\\ &+c\right]\right)
\end{matchedalign}
```

The `colors` key accepts a nonempty, braced comma-separated list of xcolor names or expressions. It does not enable rainbow mode by itself. Undefined colors are diagnosed by xcolor. Configure xcolor before loading this package if additional color-name sets are required.

The default palette is blue, orange, green, purple, red and cyan, using the package's `msblue`, `msorange`, `msgreen`, `mspurple`, `msred` and `mscyan` definitions. Colors cycle when nesting exceeds the palette length. Sibling pairs at the same depth reuse the same color, and every environment starts at depth one. Invisible delimiters still participate in depth counting. Explicit `\left`, `\middle` and `\right` pairs inside braced groups are also colored in their native math style. Native inner environments and pairs hidden in macros remain outside the scanner. Ordinary delimiters are not colored.

6 Compatibility, diagnostics and limitations

6.1 Scope of support

The implementation targets display-style mathematics with explicit, manual row breaks. It is not a general inline-math or script-style formatter. User macros are not expanded to discover hidden delimiters, alignment markers or metadata. Nested `matchedsplit` environments are outside the supported interface.

Measurement executes mathematical contents more than once, especially with nested pairs. Avoid counters, file writes or other side effects in formula contents. For spanning pairs, middle delimiters are relation atoms and left/right delimiters are opening/closing atoms. Pairs contained in one cell retain native left/right layout and spacing.

The package uses internal amsmath bindings. Native `xalignat`, `xxalignat` and `flalign`, including their defined starred variants, retain their native behavior and do not acquire cross-row delimiter support. Their coexistence with the replacement has been tested. No general compatibility claim is made for third-party packages such as mathtools, hyperref or unicode-math, or for publisher-specific document classes. This manual uses hyperref; that is an example configuration, not a complete compatibility test suite.

6.2 Diagnostics

The package reports unmatched `\right` or `\middle`, unclosed `\left`, a missing final delimiter, missing braced arguments for `\label`, `\tag` or `\intertext`, and missing closing brackets in row-spacing arguments. Invalid native mathematics and invalid delimiter tokens may instead produce a TEX or amsmath error.

Since an environment body is collected before processing, an error may be reported at its closing `\end` rather than at the originating row.

6.3 Implementation and validation

A stack tracks open pairs. Each pair is measured in display style with invisible boundaries. Local delimiter constructions with height/depth phantoms allow its ends to occupy different alignment cells. Parser state and box assignments are local to the environment. Repeated token-list copying and measurement can be expensive for long or deeply nested input.

The regression suite checks dimensions against native TEX, label values, option combinations and failure diagnostics on all three engines, including expected-error cases. Selected PDF outputs have also been inspected.

7 Version history and distribution information

0.8.1 (2026-10-29) Use older command-copy primitives, declare the minimum LaTeX kernel date and add clean-archive and kernel-rollback verification.

0.8.0 (2026-10-29) Add package and environment rainbow options, local palette overrides and depth-based delimiter colors.

0.7.1 (2026-10-29) Fix intertext measurement and align inside gather; validate metadata arguments and row-spacing delimiters. Unify the public package name as matchedsplit.

0.7 Add numbered display environments and optional align replacement.

0.6 Add optional split replacement.

0.5 Repair nested-pair measurement and preservation of token groups.

This package is supplied as a directly maintained `.sty` file; no docstrip extraction is required. The documentation source is `matchedsplit.tex`. Copyright © 2026 Yu Zhai. This work may be distributed and/or modified under the LaTeX Project Public License, version 1.3c or (at your option) any later version. Its maintenance status is *maintained*; the current maintainer is Yu Zhai. See `LICENSE` and `MANIFEST.md` for the license notice and scope of the work. Send bug reports with a minimal example, engine version and log to `me@zhaiyusci.net`.