

SDK6 AN: A9 DRAM Tuning (Shmoo Tool)

Draft Version 0.1

October 20, 2014



Confidentiality Notice:

Copyright © 2014 Ambarella Inc.

The contents of this document are proprietary and confidential information of Ambarella Inc.

The material in this document is for information only. Ambarella assumes no responsibility for errors or omissions and reserves the right to change, without notice, product specifications, operating characteristics, packaging, ordering, etc. Ambarella assumes no liability for damage resulting from the use of information contained in this document. All brands, product names and company names are trademarks of their respective owners.

US

3101 Jay Street Ste. 110 Santa Clara, CA 95054, USA Phone: +1.408.734.8888

Fax: +1.408.734.888

Hong Kong

Unit A&B, 18/F, Spectrum Tower 53 Hung To Road Kwun Tong, Kowloon Phone: +85.2.2806.8711

Fax: +85.2.2806.8722

Korea

6 Floor, Hanwon-Bldg. Sunae-Dong, 6-1, Bundang-Gu SeongNam-City, Kyunggi-Do Republic of Korea 463-825 Phone: +031.717.2780

Fax: +031.717.2782

China - Shanghai

9th Floor, Park Center 1088 Fangdian Road, Pudong New District Shanghai 201204, China

Phone: +86.21.6088.0608 Fax: +86.21.6088.0366

Taiwan

Suite C1, No. 1, Li-Hsin Road 1 Science-Based Industrial Park Hsinchu 30078, Taiwan Phone: +886.3.666.8828 Fax: +886.3.666.1282

Japan - Yokohama

Shin-Yokohama Business Center Bldg. 5th Floor 3-2-6 Shin-Yokohama, Kohoku-ku, Yokohama, Kanagawa, 222-0033, Japan Phone: +81.45.548.6150 Fax: +81.45.548.6151

China - Shenzhen

Unit E, 5th Floor No. 2 Finance Base 8 Ke Fa Road Shenzhen, 518057, China Phone: +86.755.3301.0366 Fax: +86.755.3301.0966

I Contents

II	Preface	
1		
	1.1	Overview: Introduction
2	DDR Shm	100
	2.1	: How to Hook Up the Shmoo Tool onto Test Firmware
	2.2	: How to Run the Tool
	2.3	: How to Analyze the Shmoo Results and Find A Good Set of DDR Parameter 3
Appendix 1		Additional Resources
Appendix 2		Important Notice
Appendix 3		Revision History

II Preface

This document provides technical details using a set of consistent typographical conventions to help the user differentiate key concepts at a glance.

Conventions include:

Example	Description
AmbaGuiGen, DirectUSB Save, File > Save Power, Reset, Home	Software names GUI commands and command sequences Computer / Hardware buttons
Flash_IO_control da, status, enable	Register names and register fields. For example, Flash_IO_control is the register for global control of Flash I/O, and bit 17 (da) is used for DMA acknowledgement.
GPIO81, CLK_AU	Hardware external pins
VIL, VIH, VOL, VOH	Hardware pin parameters
INT_O, RXDATA_I	Hardware pin signals
amb_performance_t amb_operating_mode_t amb_set_operating_mode()	API details (e.g., functions, structures, and type definitions)
<pre>/usr/local/bin success = amb_set_operat- ing_mode (amb_base_address, & operating_mode)</pre>	User entries into software dialogues and GUI windows File names and paths Command line scripting and Code

Table II-1. Typographical Conventions for Technical Documents.

Additional Ambarella typographical conventions include:

- Acronyms are given in UPPER CASE using the default font (e.g., AHB, ARM11 and DDRIO).
- Names of Ambarella documents and publicly available standards, specifications, and databooks appear in *italic* type.

Overview

1.1 **Overview: Introduction**

This application note describes the procedure of implementing the tool of DDR parameter Shmoo. The main goal of the DDR Shmoo is to obtain tested, working values for the programmable DDR timing parameters and tap values, which are finally programmed into the A9 controller registers in the code. The Shmoo items include A9 DLL values, driving strength and termination value of pads, if any. To find stable values, recording and playback will be run with each modified parameter to increasing system loading. The operating range of the DRAM may be exceeded in order to determine the boundary between passing and failing parameter values. The failing value will result in system instability or cause the system to hang. The following sections show how to port the tool to the target:

- (Section 2.1): How to Hook Up the Shmoo Tool onto Test Firmware
- (Section 2.2): How to Run the Tool
- Shmo.

 Jl

 The Shmoo Result. (Section 2.3): How to Analyze the Shmoo Results and Find A Good Set of DDR Parameter

2 DDR Shmoo

2.1 : How to Hook Up the Shmoo Tool onto Test Firmware

The Shmoo tool helps to find timing parameters, A9 driving strength, and the termination value of pad operating range of DRAM. Video recording and playback with modified DDR timing parameters are run in the testing target.

The following is the sample code. At DoDdrShmoo(), please fill up the correct configuration: AMBA_DDR_SHMOO_CONFIG_s DdrShmooCtrl.

The configuration includes AmbaShmooTaskStack task priority, stack size, recode time, function pointer of recoding start and stop, playback and file delete function.

The AmbaDdrShmooTask_Start(&DdrShmooCtrl) function is the first step in starting the Shmoo algorithm.

```
DoDdrShmoo() {
  AMBA DDR SHMOO CONFIG s DdrShmooCtr
      .Priority = 80,
      .StackByteSize = sizeof(AmbaShmooTaskStack),
      .pStack = AmbaShmooTaskStack,
      .RecordTime = 10,
                                                              //The duration of video
recording and playback
      .VideoRecordStart = UserDefined VideoRecordStart
                                                              //Function pointer of
      function to start video recording
      .VideoRecordStop = UserDefined VideoRecordStop
                                                              //Function pointer of
      function to stop video recording
      .VideoPlayback = UserDefined VideoPlayback,
                                                              //Function pointer of
      function to start video playback
      .VideoFileDelete = UserDefined VideoFileDelete
                                                              //Function pointer of
      function to delete files
  };
  AmbaDdrShmooTask Start(&DdrShmooCtrl);
}
```

2.2 : How to Run the Tool

The above section shows the related function of the tool. The following steps are the detailed steps for running the Shmoo tool.

- During the Shmoo test, a system hang may occur. When it happens, user has to re-boot in order to perform the next step of the test. To simplify, please added Shmoo API - DoDdrShmoo() to system boot up code. After boot up finishes, the Shmoo tool will auto-run to check next parameters.
- 2. Shmoo API: DoDdrShmoo(&DdrShmooCtrl) start to run Shmoo.
- 3. Please remember to insert an SD card before the test. The Shmoo experiment results are stored in the SD card.

2.3 : How to Analyze the Shmoo Results and Find A Good Set of DDR Parameter

The shmoo result will be saved in drive C (in the SD card). Please open the file and check the PASS results. Find the pass operating ranges of each parameter and use the central value as the final setting.

E.g. Each DLL byte is represented with bit[5] and bit[3:0]. Bit[3:0] which represents the delay value. Bit[5] is the sign bit. Based on the following result, the recommended value is 0x20.

Shmoo result:



1 Additional Resources

Please contact an Ambarella representative for digital copies.



2 Important Notice

All Ambarella design specifications, datasheets, drawings, files, and other documents (together and separately, "materials") are provided on an "as is" basis, and Ambarella makes no warranties, expressed, implied, statutory, or otherwise with respect to the materials, and expressly disclaims all implied warranties of noninfringement, merchantability, and fitness for a particular purpose. The information contained herein is believed to be accurate and reliable. However, Ambarella assumes no responsibility for the consequences of use of such information.

Ambarella Incorporated reserves the right to correct, modify, enhance, improve, and otherwise change its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete.

All products are sold subject to Ambarella's terms and conditions of sale supplied at the time of order acknowledgment. Ambarella warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with its standard warranty. Testing and other quality control techniques are used to the extent Ambarella deems necessary to support this warranty.

Ambarella assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using Ambarella components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

Ambarella does not warrant or represent that any license, either expressed or implied, is granted under any Ambarella patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which Ambarella products or services are used. Information published by Ambarella regarding third-party products or services does not constitute a license from Ambarella to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from Ambarella under the patents or other intellectual property of Ambarella.

Reproduction of information from Ambarella documents is not permissible without prior approval from Ambarella.

Ambarella products are not authorized for use in safety-critical applications (such as life support) where a failure of the product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Customers acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Ambarella products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by Ambarella. Further, Customers must fully indemnify Ambarella and its representatives against any damages arising out of the use of Ambarella products in such safety-critical applications.

Ambarella products are neither designed nor intended for use in automotive and military/aerospace applications or environments. Customers acknowledge and agree that any such use of Ambarella products is solely at the Customer's risk, and they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

Revision History

NOTE: Page numbers for previous drafts may differ from page numbers in the current version.

Version	Date	Comments
0.1	October 20, 2014	Formatted to SDK6
Table 3-1.	Revision History.	

Table 3-1. Revision History.