CentOS 6 [1] Set the static IP addresseto the server. Install CentOS 6 Initial Config [root@dlp ~]# vi /etc/sysconfig/network-NTP Server scripts/ifcfg-eth0 SSH Server **DNS Server** DEVICE=eth0 Storage Server HWADDR=00:50:43:00:3B:AE Virtualization TYPE=Ethernet Cloud Compute UUID=c1539085-73d7-4455-ac82-88f26464458a # change Directory Server ONBOOT=yes WEB Server NM CONTROLLED=yes Database # change FTP Server **BOOTPROTO=none** MAIL Server # add follows Samba Server # this server's IP address Proxy Server IPADDR=10.0.0.30 Load Balancing # subnet mask NETMASK=255.255.255.0 Monitoring # default gateway Desktop Env **GATEWAY=10.0.0.1** Others #1 # DNS server's IP address Others #2 DNS1=10.0.0.10 Other OS IPV6INIT=no USERCTL=no [root@dlp ~]# /etc/rc.d/init.d/network restart Shutting down interface eth0: [ OK ] Shutting down loopback interface: [ OK ] Bringing up loopback interface: [ OK ] Bringing up interface eth0: [ OK ] [root@dlp ~]# chkconfig network on [root@dlp ~]# ifconfig Link encap:Ethernet HWaddr 00:0C:29:D8:7C:06 eth0 inet addr:10.0.0.30 Bcast:10.0.0.255 Mask:255.255.255.0 inet6 addr: fe80::20c:29ff:fed8:7c06/64 Scope:Link UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1 RX packets:885 errors:0 dropped:0 overruns:0 frame:0 TX packets:743 errors:0 dropped:0 overruns:0 carrier:0 collisions:0 txqueuelen:1000 RX bytes:83054 (81.1 KiB) TX bytes:113706 (111.0 KiB) lo Link encap:Local Loopback inet addr:127.0.0.1 Mask:255.0.0.0 inet6 addr: ::1/128 Scope:Host UP LOOPBACK RUNNING MTU:16436 Metric:1 RX packets:0 errors:0 dropped:0 overruns:0 frame:0 TX packets:0 errors:0 dropped:0 overruns:0 carrier:0

collisions:0 txqueuelen:0

RX bytes:0 (0.0 b) TX bytes:0 (0.0 b)

## [2] Disable IPv6 if you don't need it.

```
[root@dlp ~]# ifconfig
eth0
         Link encap:Ethernet HWaddr 00:0C:29:D8:7C:06
         inet addr:10.0.0.30 Bcast:10.0.0.255 Mask:255.255.255.0
         inet6 addr: fe80::20c:29ff:fed8:7c06/64 Scope:Link
         UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
         RX packets:885 errors:0 dropped:0 overruns:0 frame:0
         TX packets:743 errors:0 dropped:0 overruns:0 carrier:0
         collisions:0 txqueuelen:1000
         RX bytes:83054 (81.1 KiB) TX bytes:113706 (111.0 KiB)
         Link encap:Local Loopback
lo
         inet addr:127.0.0.1 Mask:255.0.0.0
         inet6 addr: ::1/128 Scope:Host
         UP LOOPBACK RUNNING MTU:16436 Metric:1
         RX packets:0 errors:0 dropped:0 overruns:0 frame:0
         TX packets:0 errors:0 dropped:0 overruns:0 carrier:0
         collisions:0 txqueuelen:0
         RX bytes:0 (0.0 b) TX bytes:0 (0.0 b)
[root@dlp ~]# vi /etc/sysctl.conf
# add follows to the end
net.ipv6.conf.all.disable_ipv6 = 1
net.ipv6.conf.default.disable_ipv6 = 1
# apply new settings
[root@dlp ~]# sysctl -p
[root@dlp ~]# ifconfig
        Link encap:Ethernet HWaddr 00:0C:29:D8:7C:06
eth0
         inet addr:10.0.0.30 Bcast:10.0.0.255 Mask:255.255.255.0
         UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
         RX packets:885 errors:0 dropped:0 overruns:0 frame:0
         TX packets:743 errors:0 dropped:0 overruns:0 carrier:0
         collisions:0 txqueuelen:1000
         RX bytes:83054 (81.1 KiB) TX bytes:113706 (111.0 KiB)
lo
         Link encap:Local Loopback
         inet addr:127.0.0.1 Mask:255.0.0.0
         UP LOOPBACK RUNNING MTU:16436 Metric:1
         RX packets:0 errors:0 dropped:0 overruns:0 frame:0
         TX packets:0 errors:0 dropped:0 overruns:0 carrier:0
         collisions:0 txqueuelen:0
         RX bytes:0 (0.0 b) TX bytes:0 (0.0 b)
```