Index

Note: Page number followed by *f* indicate figure and *t* indicate tables.

A

Abstract floor plans, 171–172
Access point number reduction, 262–263
Acoustics
  active, 335
  positioning systems. (*see* Airborne acoustic positioning systems (AAPS))
  signal detection and positioning observables, 340–342
  wave propagation in air
    absorption, 337–338
    impedance, 339
    outdoor propagation, 339–340
    propagation speed, 338–339
Active Badge System, 353
Active Bat System, 335–336
Affinity propagation clustering, 138–139
  application of, 146–147
  offline phase, 147
  RP clustering via, 145–147
  two-step algorithm, 148
Airborne acoustic positioning systems (AAPS)
  broadband, 336–337
  compensation algorithms
    Doppler shift, 347–349
    multipath propagation, 346–347
    multiple access interference, 345–346
  positioning strategies, 342–343
    hyperbolic lateration, 344–345
    spherical lateration, 343–344
Alcalá2017 Tutorial dataset, 238
  characteristic of, 236*t*
  mean positioning error, 241, 242*t*
  Radio Map Inherent Difficulty (RMID) value, 243, 243*t*
AmbiLoc dataset, 238
AM radio maps, 74–75
Anchors
  antideflagration ATEX enclosure, 304
  communication module, 303–304
  localization module, 304
  visualization module, 304
Angel of Arrival (AOA), 341, 353
  three-dimensional position, 365–368
Apache, 235
Apple Maps, 101
Architectural floor plans, 171–172
Atmospheric turbulence, 340
Augmented reality systems, 171–172
Auto-regressive model of order one (AR1), 315

B

Basic Service Set IDentifier (BSSID), 157–158
Bluetooth-complaint technologies, 267
Bluetooth low energy (BLE), 156
  communication, 302
  radio maps, 74
  Wi-Fi probability-based positioning and beacon-based positioning
    beacon RSSI weighted centroid, 132
    probability-based results, 130–132
    probability-based setup and algorithm, 129–130
    probability density function, 127–129
  and WLAN, 268

C

Calibration-free indoor positioning system
  CrowdInside, 107
  EZ clients, 106
  iMoon, 108
  Jigsaw, 107

Calibration-free indoor positioning system *(Continued)*
MapGenie, 107
SDM, 105
TIX, 105
UnLoc, 106
Walkie-Markie, 106–107
Calibration issues, in fingerprinting techniques
circle-based fingerprint clustering, 261–262
offline calibration, 261
RSS offsets, effects of, 260–261
test rank based method, 261–262
Cell-ID sytem, 353
Cell Space, 194–196
CIMLoc, 77
CityGML, 190–191
Clustering methods, 252, 253*f*
Compression and clustering methods, 262
Compressive sensing approaches, 257–258
Core module, of IndoorGML, 194–196, 195*f*
Cricket system, 335–336
Crowdsourcing, 138
indoor research
calibration-free, 105–108
equipped sensors implications, 110–111
floor plan layout dimension, 111
map-free *vs.*, 109*t*
maximum likelihood estimator, 103
privacy and security, 112
quality of, 110
simultaneous localization and mapping, 104–105
type of architecture, 111
outdoor map systems, 98–103
Apple Maps, 101
Google Maps, 99
HERE (Nokia Here), 101
MapQuest, 100
Microsoft's Bing Maps, 101
OpenStreetMap (OSM), 99–100
Waze, 100
radio maps building and updating, 76–79

D

Database-size reduction, in fingerprinting techniques, 262–263
Dead-reckoning method, 311
Deployment cycle, passive localization system, 289–290
Device heterogeneity, 162–163
Dijkstra's algorithm, 177–178, 179*f*
Django, 235
Doppler shift, 347–349
Drift reduction methods
height error correction, 329
heuristic drift elimination algorithms, 326
landmark-based algorithms, 328–329
multiinertial sensor fusion algorithms, 327–328
SLAM-based algorithms, 327

E

Electrical calibration process, 360–361
Electrical system modeling, 357–358
Emitters, 367–368
Envelope detection technique, 340, 341*f*
EvAAL-ETRI indoor location competition, 227
EvAAL indoor localization competition
accuracy performance, 213
EvAAL framework
core criteria, 214
extended criteria, 214–215
evaluation, 212–213
long-term goal, 211
setup criteria, 211–212

F

Filtering, radio maps, 84–87
AP selection
offline, 85–86
online, 86–87
density and positioning performance, 84–85
samples, 87
Fingerprint calibrated weighted centroid (FCWC) algorithm
algorithm implementations, 124–125
SPCF and, 125

validation against competing algorithms, 125–127
validation data, 124
FM radio maps, 74–75

G
Geometric calibration system, 361–365, 362*f*
Global navigation satellite system (GNSS) access, 155
Global navigation satellite system integration, with WLAN
categories, 270–271
fusing GNSS pseudoranges with WLAN ranges, 271
fusing GNSS pseudoranges with WLAN RSS
Bayesian filter, 272*f*
cumulative distribution function, 275
estimation stage/online phase, 273–274
extended Kalman filter, 274–275
Gaussian process regression, 272
mean absolute error, 275–276, 275*t*
performance, 274–276
training stage/offline phase, 272–273
Global positioning system (GPS), 97
Google Indoor, 169
Google Maps, 99
GraphSLAM, 77

H
Height error correction, 329
Height/floor estimation, in indoor fingerprinting, 266
HERE (Nokia Here), 101
Heuristic drift elimination algorithms, 326
Hyperbolic lateration, 344–345
algorithm, 336–337

I
Image acquisition, 362–363
Image-based approaches, 254–257
Image compression process, 255–257, 256*f*
Image sensor (IS), 354
Indoor cell-awareness, 190
IndoorLoc platform
actions, 226
AmbiLoc dataset, 238
dashboard section, 229, 233
datasets section, 228, 230*f*
comma-separated values file format, 230
dataset info, 229–230
test set, 230
training set, 230
validation set, 230
deterministic-based approach, 239, 240*f*
homepage, 228, 229*f*
implementation details, 235
magPIE dataset, 238–239
methods, 229, 231–233
objectives, 231
performance, 244
probabilistic-based approach, 239–241, 240*f*
ranking, 229, 231
Wi-Fi-based datasets, 235–238
Indoor maps, 187–188
IndoorTube Map, 172
requirements for
cell-based context awareness, 189–190
indoor accessibility graph, 189
indoor space, 188–189
indoor structure and connectivity, 188–189
integrating multiple data sets, 190–191
"You are here" map, 170
Indoor navigation, radio fingerprinting-based
assumptions, 157–158
challenges, 158–164
motivation, 155–157
Indoor positioning and indoor navigation (IPIN) conference, 209–211
Indoor positioning system (IPS)
angle of arrival, 353
applications, 46–47
calibration and experimental setup
smartphone-based patient monitoring, 47–49
smartwatch-based patient monitoring, 49–50
challenges of fingerprinting
Anyplace (Airplace), 12
classification, 3–4

Indoor positioning system (IPS) *(Continued)*
indoor maps, 14–15
localization mechanisms, 4–6
location, 3
magnetic field fingerprint, 10–11
modular localization system, 13
motivation, 1–2
navigation, 3
position, 3
privacy and security issues, 15
Samsung solution, 11
Wi-Fi fingerprinting, 6–10
developments in, 65
in environment, 365–367, 366*f*
experiences and lessons learned
smartphone-based patient monitoring, 50–51
smartwatch-based patient monitoring, 51–52
first stage, 58
light-emitting diode, 354, 368*f*
measurement quantities, 46
MWMF model, 139–140
optical sensor system
description of, 355–360
electrical system modeling, 357–358
optical system modeling, 358–360
position sensitive device sensor, 356–357
problem/challenge with, 209
requirements, 287
sensor system calibration
electrical calibration, 360–361
geometric calibration, 361–365
at very large scenarios
calibration and experimental setup, 52–58
experiences and lessons learned, 58–64
virtual fingerprinting via, 139
Wi-Fi fingerprinting, 52
heterogeneous mobile applications, 46
for indoor positioning, 52
mapping large environments, 64
measurements, 46
nonobtrusive, 47
offline phase, low-complexity strategy, 139–143
online phase, low-complexity strategy, 145–149
at university campus, 53–57
Indoor radio propagation, RSSI-based positioning algorithms
free space model, 116
indoor propagation, 117
RSSI measurement, 118
IndoorTube Map, 172
Inertial measurement units (IMU), 276
Inertial sensors, 311
and magnetometers, 312–313
Infrared emittingdiode (IRED), 354, 360, 363*f*
mobile agents, 365–367, 366*f*
Interacting multiple model (IMM) algorithm, 278
Interoperability of positioning systems, 249
Intersymbol interference (ISI), 345–346
Inverse distance weighting (IDW) interpolation, 80
ipft R package, 235
IPIN indoor localization competition
error statistics, 218
EvAAL framework, application of, 217–218
fusion strategies, 221–222
Kalman filter, 221–222
objective, 223
particle filter, 222
point error, 216
real-time systems
map matching algorithm, 221
pedestrian dead reckoning, 220–221
raw-data modules, 220–221
selection of, 219–220, 219*t*
user orientation, 221
Wi-Fi scanning, 221
smartphone-based systems, 220
tracks and competitors, 215*t*
IPIN2016 Tutorial dataset, 237
characteristic of, 236*t*
mean positioning error, 241, 242*t*
Radio Map Inherent Difficulty (RMID) value, 243, 243*t*
ranking webpage of, 231, 232*f*

IPS. (*see* Indoor positioning system (IPS))
Iterative method, 365

K
Kaggle, 227
Kalman filter, shoe-mounted positioning systems, 318–319

L
Landmark-based algorithms, 328–329
Levenberg-Marquardt algorithm, 365
Light-emitting diode (LED), 354
Linear Frequency Modulation (LFM), 342
Location-based applications (LBA), 69
Location-based services (LBS)
  applications, 97
  awareness and demand, 155
  for indoor environments, 169
Log-distance path-loss (LDPL) model, 83
Loose coupling algorithms, 327–328
Low-complexity strategy offline and online strategies
  experimental setting and performance indicators, 142–143, 148–149
  offline phase, 141, 147
  online phase, 141–142, 147–148
  RP clustering via affinity propagation, 145–147
  RSS prediction via MWMF model, 139–140

M
Magnetic field
  fingerprint, 10–11
  navigation, 277
MagPIE dataset, 238–239
MapQuest, 100
Map systems
  indoor
    calibration-free, 105–108
    equipped sensors implications, 110–111
    floor plan layout dimension, 111
    map-free *vs.*, 109*t*
    maximum likelihood estimator, 103
    privacy and security, 112
    quality of, 110
    simultaneous localization and mapping, 104–105
    type of architecture, 111
  outdoor, 98–103
    Apple Maps, 101
    Google Maps, 99
    HERE (Nokia Here), 101
    MapQuest, 100
    Microsoft's Bing Maps, 101
    OpenStreetMap (OSM), 99–100
    Waze, 100
  schematic, 170
    challenges, 172
    for mobile GIS applications, 171
    for transport network, 171
  web map systems, 102*t*
Matching pursuit (MP) algorithm, 346–347
Measurement gaps, in fingerprinting techniques, 263–266
MEMS-based inertial sensors, 312
MEMS-based magnetometers, 313
Microsoft indoor localization competition, 213–214
Microsoft's Bing Maps, 101
Multiinertial sensor fusion algorithms, 327–328
Multilateration. (*see* Hyperbolic lateration)
Multimodal positioning, 278
Multiple access interference (MAI), 345–346
Multiple Basic Service Set Identifiers selection, 263
Multiple position sensitive device system, 355
Multislope PL models, 253
Multiwall multifloor (MWMF) indoor propagation model
  empirical nature, 143
  reliability, 142–143
  RSS prediction via, 139–140
  virtual fingerprints, 143

N
Navigation module, of IndoorGML, 196, 196*f*, 197*f*
Nonshoe-mounted positioning systems
  step detection

Navigation module, of IndoorGML *(Continued)*
on horizontal surfaces, 321–322
on stairs, 322–323
step&heading algorithm, 320–321, 321*f*
step length estimation, 324–325
vertical displacement estimation, 325–326

O

Offline phase, low-complexity strategy, 141
experimental setting and performance indicators, 142–143
online phase, 141–142
RSS prediction via MWMF model, 139–140
OGC IndoorGML, 187–188
cell geometry, 191
cell semantics, 192–193
cellular space model, 191
data models of, 188
i-locate portal and JOSM, 203*f*
implementation issues
cell determination and decomposition, 198–199
hierarchical structure, 200, 201*f*
path geometry, 199
space closure, 199–200
thick *vs.* thin door model, 199
vertical connection, 201, 202*f*
wall texture, 201
modular structure, 194*f*
core module, 194–196, 195*f*
navigation module, 196, 196*f*, 197*f*
multilayered space model, 193
topology between cells, 192
use cases, 202–205
user navigation and asset management, 202
Online phase, low-complexity strategy, 147–148
experimental setting and performance indicators, 148–149
offline phase, 147
RP clustering via affinity propagation, 145–147
OpenStreetMap (OSM), 99–100
Optical sensor system
description of, 355–360
electrical system modeling, 357–358
modeling of, 355–360
optical system modeling, 358–360
position sensitive device sensor, 356–357
Order vectors, 292
Orientation estimation, 313
Kalman filter, 314
prediction stage, 314–315
update stage
absolute compass, 317
absolute gravity, 316
absolute magnetic field, 316–317
differential gravity, 316
differential magnetic field, 317
pseudo-measurement, 316
zero angular rate, 317

P

Parallel Interference Cancelation algorithm, 345–346
Passive localization system
data representation, 292
deployment cycle, 289–290
features, 288–289
802.11 fingerprints, 291
lecture room building
accuracy considerations, 295–297
floor plan, 293, 293*f*
occupancy services, 297–298
passive sensing characterization, 294–295
spatial sampling coverage, of monitors, 295, 296*f*
temporal occupancy analysis, 298*f*
time window, 294
training approach, 290–292
user interface of the training application, 291, 291*f*
Path-loss (PL) approaches, 252–253
Pedestrian dead reckoning (PDR), 77, 157
Piloting method, 311
Pinhole model, 358, 358*f*
Point-to-point telemetry, 353
Position sensitive device (PSD) sensor, 356*f*
amplifier circuit, 357*f*

equivalent circuit, 356*f*
indoor positioning system
AoA, three-dimensional position determination, 365–368
optical sensor system, 355–360
sensor system calibration, 360–365
Kalman filter, 355
on mobile agents, 367–368
2D pincushion sensor, 356*f*
uniform illumination, 361*f*
Power/Received Signal Strength (RSS), 340
Probability-based positioning, Wi-Fi and BLE
beacon RSSI weighted centroid, 132
probability-based results, 130–132
probability-based setup and algorithm, 129–130
probability density function, 127–129
PSD sensor. (*see* Position sensitive device (PSD) sensor)
Public repository. (*see* IndoorLoc Platform)

R

Radial basis function (RBF) interpolation, 81–82
Radio fingerprinting-based indoor localization
assumptions, 157–158
challenges, 158–164
motivation, 155–157
Radio-Frequency IDentification (RFID), 156
and WLAN, 268–269
Radio maps
building and updating, 75–79
crowdsourcing, 76–79
construction, 46
definition, 71–72
for different radio technologies, 71–75
Bluetooth low energy radio maps, 74
deterministic radio maps, 73–74
FM and AM radio maps, 74–75
estimation method, 71–72
filtering, 84–87
AP selection, 85–87
density and positioning performance, 84–85
samples, 87
reference points, 71–72
standards
automatic discovery protocols, 89–90
floor maps, 90–91
formats and protocols, 90
fundamental building blocks, indoor positioning and tracking system, 88–89
need for, 89
remote positioning engines, 91–92
standardization initiatives, 92
Wi-Fi density, 79–83
construction using interpolation, 80–83
construction using propagation models, 83
Random walk, 313
Received signal strength (RSS), 137
prediction, 138
Received signal strength-based fingerprinting techniques, 250
challenges and solutions, 258–266, 259*t*
calibration issues, 260–262
database-size reduction, 262–263
height/floor estimation, 266
measurement gaps, 263–266
distance metrics, 252*t*
with full training databases, 250–251
with reduced training databases
clustering methods, 252, 253*f*
image-based approaches, 254–257
path-loss approaches, 252–253
Received signal strength-based seamless positioning
fingerprinting techniques, 250
challenges and solutions, 258–266
distance metrics, 252*t*
with full training databases, 250–251
with reduced training databases, 251–258
one-stage approaches, 250
Received signal strength indicator (RSSI)
fingerprinting, 225
indoor radio propagation
free space model, 116
indoor propagation, 117
RSSI measurement, 118

Received signal strength indicator (RSSI) *(Continued)*
positioning algorithms
access points, 115–116
smartphone-based localization, 115–116
vector similarity measures, 121–123
readings
fingerprint point similarity, 158
logarithmic distance relation, 159
measurements, 157–158
reference point, 157–158
Reference points (RPs), 137
Refinery, tasks in, 301
Refinery worker safety, remote monitoring system for. (*see* Remote monitoring system, for refinery worker safety)
Remote monitoring system, for refinery worker safety
control center, 304–305
alert manager, 305
database, 305
graphical user interface, 305
processing module, 305
remote configuration manager, 305
customized antiexplosive wristband
aim/goal, 303
functionalities, 302–303
data anonymity, 305–306
logistics, 309
person related issues
ergonomics, 308
simplicity, 308
technical and procedure robustness, 308
transparency and privacy, 307–308
wearable devices, 302–303
wireless communication infrastructure, 303–304
RF-based indoor localization algorithms, 228
R Markdown technology, 235
Root mean square (RMS), 360–361

S

Seamless positioning platforms, 249
Sensor system calibration
electrical calibration, 360–361
geometric calibration, 361–365
Shiny, 235
Shoe-mounted inertial positioning systems, 318–320
Signal of opportunity (SoO), 267–268
Simulated annealing optimization technique, 171
Simultaneous localization and mapping (SLAM)
ActionSLAM, 104–105
algorithms, 163–164, 327
FootSLAM, 104–105
indoor map systems' research, 104–105
traditional, 104–105
Smartphone-based patient monitoring, 50–51
Smartwatch-based patient monitoring, 51–52
Sound-based positioning systems, 277
Spherical lateration, 343–344
Stance phase detection, 319
State and Transition, 194–196
Strapdown algorithm, 318, 318*f*

T

Tampere dataset, 237–238
characteristic of, 236*t*
mean positioning error, 241, 242*t*
Radio Map Inherent Difficulty (RMID) value, 243, 243*t*
Ternary vectors, 292
Tight coupling algorithms, 328
Time difference of arrival (TDOA), 341, 353
Time-of-arrival (TOA), 341
Triangular Interpolation and eXtrapolation (TIX)'s localization purpose, 105
Trilateration. (*see* Spherical lateration)
Two-phase localization methods, 258

U

UCI Machine Learning Repository, 227
UFPR CampusMap (UCM) project
classes diagram, 175*f*
database construction
cartographic, 176–177
database conceptual model, 174
database implementation, 174–176

nongeometric and geometric features, 174*t*
indoor routing, 177–179
PgRouting function, 179
PostGIS function, 177–178
results
indoor cartographic representation, 181–182
indoor routes, 183, 183*f*
server-client architecture, 179–180
study area, 172–173
Thormap, 180–181
UJIIndoorLoc dataset, 237
characteristic of, 236*t*
mean positioning error, 241, 242*t*
Radio Map Inherent Difficulty (RMID) value, 243, 243*t*
ranking webpage of, 231, 232*f*
Ultrasonic positioning system, 277
UltraWideBand (UWB), 4
communication, 302
radio, 156
universAAL framework, 210

V

Visible light-based indoor positioning system, 354
Visible light communication (VLC), 354
Visible light positioning (VLP), 277
Vision navigation, 277
Volunteer-based data collection, 47
smartphone-based patient monitoring, 50–51
smartwatch-based patient monitoring, 51–52

W

Waze, 100
Weighted *k*-nearest neighbors (W*k*NN) schemes, 138–139
Wi-Fi fingerprinting indoor positioning systems
heterogeneous mobile applications, 46
for indoor positioning, 52
mapping large environments, 64
measurements, 46
nonobtrusive, 47
offline phase, low-complexity strategy
experimental setting and performance indicators, 142–143
offline phase, 141
online phase, 141–142
RSS prediction via MWMF model, 139–140
online phase, low-complexity strategy
experimental setting and performance indicators, 148–149
offline phase, 147
online phase, 147–148
RP clustering via affinity propagation, 145–147
radio map, 120–121
sources, 156
at university campus, 53–57
Wi-Fi probability-based positioning and BLE
Beacon RSSI weighted centroid, 132
probability-based results, 130–132
probability-based setup and algorithm, 129–130
probability density function, 127–129
Wi-Fi radio maps density construction
using interpolation, 80–83
inverse distance weighting (IDW), 80
IWD, 83
kriging interpolation, 82
radial basis function (RBF), 81–82
RBF, 83
using propagation models, 83
Wi-Fi RSSI-based positioning
centroid method, 118–119
problem, 115
weighted centroid method, 119–120
Wi-Fi tracking, fingerprinting techniques
potentials and limitations of, 25–26
privacy-preserving
deterministic approach, 29–30
deterministic location estimation, 33–37
implementation and setup, 32–33
probabilistic approach, 30–31
probabilistic location estimation, 37–39
user movement, 39–40

Wi-Fi tracking, fingerprinting techniques *(Continued)*
researches on, 22–23
security mechanisms against
MAC address randomization, 27–28
protocol extensions, 27
technical background, 23–24
WLAN networks, integration of, 266–267
and BLE, 268
cloud architectures, 278–279
GNSS positioning, 270–276
inertial measurement units, 276
magnetic field navigation, 277
multimodal positioning, 278
and RFID, 268–269
signal of opportunity (SoO), 267–268
sound-based positioning systems, 277
visible light positioning, 277
vision navigation solutions, 277

Y

"You are here" (YAH) map, 170

Z

Zero velocity update (ZUPT) technique, 220–221