

Carnegie Mellon University

# Database Systems

## Index

## Concurrency Control



15-445/645 FALL 2024 » PROF. ANDY PAVLO

# ADMINISTRIVIA

---

**Homework #3** is due Sunday Sept 6<sup>th</sup> @ 11:59pm

**Project #2** is due Sunday Sept 29<sup>th</sup> @ 11:59pm

→ Recitation next week

**Mid-term Exam** on Wednesday Oct 9<sup>th</sup> @ 2:00pm

→ In-class in this room.

# UPCOMING DATABASE TALKS

---

## DataFusion Comet (DB Seminar)

- Monday Sept 30<sup>th</sup> @ 4:30pm ET
- Zoom



APACHE  
**DATAFUSION COMET™**

## Oracle Talk (DB Group)

- Tuesday Oct 1<sup>st</sup> @ 12:00pm ET
- GHC 8115



## ParadeDB (DB Seminar)

- Monday Oct 7<sup>th</sup> @ 4:30pm ET
- Zoom



# OBSERVATION

---

We (mostly) assumed all the data structures that we have discussed so far are single-threaded.

A modern DBMS needs to allow multiple threads to safely access data structures to take advantage of additional CPU cores and hide disk I/O stalls.



*They Don't Do This!*

**VOLTDB**

**KX**

*Redis*

**H-Store**

# CONCURRENCY CONTROL

---

A concurrency control protocol is the method that the DBMS uses to ensure “correct” results for concurrent operations on a shared object.

A protocol's correctness criteria can vary:

- **Logical Correctness:** Can a thread see the data that it is supposed to see?
- **Physical Correctness:** Is the internal representation of the object sound?

# TODAY'S AGENDA

---

Latches Overview

Hash Table Latching

B+Tree Latching

Leaf Node Scans

**Project #2 Announcement**

# LOCKS VS. LATCHES

---

## Locks (Transactions)

- Protect the database's logical contents from other transactions.
- Held for transaction's duration.
- Need to be able to rollback changes.

## Latches (Workers)

- Protect the critical sections of the DBMS's internal data structure from other workers (e.g., threads).
- Held for operation duration.
- Do not need to be able to rollback changes.

# LOCKS VS. LATCHES

## Lecture #15



### *Locks*

<b>Separate...</b>	Transactions
<b>Protect...</b>	Database Contents
<b>During...</b>	Entire Transactions
<b>Modes...</b>	Shared, Exclusive, Update, Intention
<b>Deadlock</b>	Detection & Resolution
<b>...by...</b>	Waits-for, Timeout, Aborts
<b>Kept in...</b>	Lock Manager

### *Latches*

Workers (threads, processes)
In-Memory Data Structures
Critical Sections
Read, Write
Avoidance
Coding Discipline
Protected Data Structure

Source: [Goetz Graefe](#)



# LATCH MODES

## Read Mode

- Multiple threads can read the same object at the same time.
- A thread can acquire the read latch if another thread has it in read mode.

## Write Mode

- Only one thread can access the object.
- A thread cannot acquire a write latch if another thread has it in any mode.

### *Compatibility Matrix*

	Read	Write
Read	✓	X
Write	X	X

# LATCH IMPLEMENTATION GOALS

---

Small memory footprint. 闕锁需要内联到数据结构中, 因此尽可能占据小的内存空间.

Fast execution path when no contention.

Decentralized management of latches.

Avoid expensive system calls.

# LATCH IN IMPLEMENTATION GOALS

Small memory

Fast execution

Decentralized

Avoid expensive

By: **Linus Torvalds** (torvalds.delete@this.linux-foundation.org), January 3, 2020 6:05 pm

Beastian (no.email.delete@this.aol.com) on January 3, 2020 11:46 am wrote:

> I'm usually on the other side of these primitives when I write code as a consumer of them,  
> but it's very interesting to read about the nuances related to their implementations:

Room: [Moderated Discussions](#)

The whole post seems to be just wrong, and is measuring something completely different than what the author thinks and claims it is measuring.

First off, spinlocks can only be used if you actually know you're not being scheduled while using them. But the blog post author seems to be implementing his own spinlocks in user space with no regard for whether the lock user might be scheduled or not. And the code used for the claimed "lock not held" timing is complete garbage.

It basically reads the time before releasing the lock, and then it reads it after acquiring the lock again, and claims that the time difference is the time when no lock was held. Which is just inane and pointless and completely wrong.

That's pure garbage. What happens is that

(a) since you're spinning, you're using CPU time

(b) at a random time, the scheduler will schedule you out

(c) that random time might be just after you read the "current time", but before you actually released the spinlock.

So now you still hold the lock, but you got scheduled away from the CPU, because you had used up your time slice. The "current time" you read is basically now stale, and has nothing to do with the (future) time when you are *actually* going to release the lock.

Somebody else comes in and wants that "spinlock", and that somebody will now spin for a long while, since nobody is releasing it - it's still held by that other thread entirely that was just scheduled out. At some point, the scheduler says "ok, now you've used your time slice", and schedules the original thread, and *now* the lock is actually released. Then another thread comes in, gets the lock again, and then it looks at the time and says "oh, a long time passed without the lock being held at all".

And notice how the above is the *good* scenario. If you have more threads than CPU's (maybe because of other processes unrelated to your own test load), maybe the next thread that gets scheduled isn't the one that is going to release the lock. No, that one already got its timeslice, so the next thread scheduled might be *another* thread that wants that lock that is still being held by the thread that isn't even running right now!

So the code in question is pure garbage. You can't do spinlocks like that. Or rather, you very much can do them like that, and when you do that you are measuring random latencies and getting nonsensical values, because what you are measuring is "I have a lot of busywork, where all the processes are CPU-bound, and I'm measuring random points of how long the scheduler kept the process in place".

And then you write a blog-post blaming others, not understanding that it's your incorrect code that is garbage, and is giving random garbage values.

# LATCH IN IMPLEMENTATION GOALS

## Small memory

自旋锁是一种锁，当线程尝试获取它时，会在一个循环中简单地等待（“自旋”），反复检查该锁是否可用。

## Fast execution

## Decentralized

避免在用户空间使用自旋锁。

**I repeat: do not use spinlocks in user space, unless you actually know what you're doing. And be aware that the likelihood that you know what you are doing is basically nil.**

By: **Linus Torvalds** (torvalds.delete@this.linux-foundation.org), January 3, 2020 6:05 pm

Beastian (no.email.delete@this.aol.com) on January 3, 2020 11:46 am wrote:

> I'm usually on the other side of these primitives when I write code as a consumer of them,  
> but it's very interesting to read about the nuances related to their implementations:

The whole post seems to be just wrong, and is measuring something completely different than what the author thinks and claims it is measuring.

First off, spinlocks can only be used if you actually know you're not being scheduled while using them. But the blog post author seems to be implementing his own spinlocks in user space with no regard for whether the lock user might be scheduled or not. And the code used for the claimed "lock not held" timing is complete garbage.

It basically reads the time before releasing the lock, and then it reads it after acquiring the lock again, and claims that the time difference is the time when no lock was held. Which is just inane and pointless and completely wrong.

That's pure garbage. What happens is that

(a) since you're spinning, you're using CPU time

(b) at a random time, the scheduler will schedule you out

(c) that random time might be just after you acquire the lock

...of the processes are CPU-bound, and I'm measuring random points of how long the scheduler kept the process in place". And then you write a blog-post blaming others, not understanding that it's your incorrect code that is garbage, and is giving random garbage values.

# LATCH IMPLEMENTATIONS

---

Test-and-Set Spinlock 硬件提供: 自旋锁

Blocking OS Mutex 操作系统提供的阻塞互斥锁

Reader-Writer Locks

Advanced approaches:

- Adaptive Spinlock (Apple ParkingLot)
- Queue-based Spinlock (MCS Locks)
- Optimistic Lock Coupling (The Germans)

# LATCH IN

Test-and-Set Spinlock  
Blocking OS Mutex  
Reader-Writer Lock

Advanced approach  
→ Adaptive Spinlock (C)  
→ Queue-based Spinlock (C)  
→ Optimistic Locking (C)

## Locking in WebKit

May 6, 2016 by Filip Pizlo @filpizlo

Back in August 2015 we replaced all `spinlocks` and `OS-provided mutexes` in WebKit with the new `WTF::Lock` (WTF stands for Web Template Framework). We also replaced all OS-provided condition variables with `WTF::Condition`. These new primitives have some cool properties:

1. `WTF::Lock` and `WTF::Condition` only require one byte of storage each. `WTF::Lock` only needs two bits in that byte. The small size encourages using huge numbers of very fine-grained locks. OS mutexes often require 64 bytes or more. The small size of `WTF::Lock` means that there's rarely an excuse for not having one, or even multiple, fine-grained locks in any object that has things that need to be synchronized.
2. `WTF::Lock` is super fast in the case that matters most: uncontended lock acquisition. Parallel algorithms tend to avoid contention by having many fine-grained locks. This means that a mature parallel algorithm will have many uncontended lock acquisitions – that is, calls to `lock()` when the lock is not held, and calls to `unlock()` when nobody is waiting in line. Similarly, `WTF::Condition` optimizes for the common case of calling `notify` when no threads are waiting.
3. `WTF::Lock` is fast under microcontention. A microcontended lock is one that is contended and the critical section is short. This means that shortly after any failing lock attempt, the lock will become available again since no thread will hold the lock for long. This is the most common kind of contention in parallel code, since it's common to go to great pains to do very little work while holding a lock.
4. `WTF::Lock` doesn't waste CPU cycles when a lock is held for a long time. `WTF::Lock` is *adaptive*: it changes its strategy for how to wait for the lock to become available based on how long it has been trying. If the lock doesn't become available promptly, `WTF::Lock` will suspend the calling thread until the lock becomes available.

# LATCH IN

Test-and-Set Spinlock  
Blocking OS Mutex  
Reader-Writer Lock

避免依赖 OS 提供的 pthread 库实现.

Advanced approach

Compared to OS-provided locks like `pthread_mutex`, `WTF::Lock` is 64 times smaller and up to 180 times faster. Compared to OS-provided condition variables like `pthread_cond`, `WTF::Condition` is 64 times smaller. Using `WTF::Lock` instead of `pthread_mutex` means that WebKit is 10% faster on [JetStream](#), 5% faster on [Speedometer](#), and 5% faster on our page loading test.

## Locking in WebKit

May 6, 2016 by Filip Pizlo @filpizlo

Back in [August 2015](#) we replaced all [spinlocks](#) and [OS-provided mutexes](#) in WebKit with the new [WTF::Lock](#) (WTF stands for Web Template Framework). We also replaced all OS-provided condition variables with [WTF::Condition](#). These new primitives have some cool properties:

1. `WTF::Lock` and `WTF::Condition` only require one byte of storage each. `WTF::Lock` only needs two bits in that byte. The small size encourages using huge numbers of very fine-grained locks. OS mutexes often require 64 bytes or more. The small size of `WTF::Lock` means that there's rarely an excuse for not having one, or even multiple, fine-grained locks in any object that has things that need to be synchronized.
2. `WTF::Lock` is super fast in the case that matters most: uncontended lock acquisition.

Parallel lock acquisition. Parallel lock acquisition is that a mature lock() when y, leads are intended and the lock will be the most common kind of holding a lock.

4. `WTF::Lock` doesn't waste CPU cycles when a lock is held for a long time. `WTF::Lock` is adaptive: it changes its strategy for how to wait for the lock to become available based on how long it has been trying. If the lock doesn't become available promptly, `WTF::Lock` will suspend the calling thread until the lock becomes available.

# LATCH IMPLEMENTATIONS


## Approach #1: Test-and-Set Spin Latch (TAS)

- Very efficient (single instruction to latch/unlatch)
- Non-scalable, not cache friendly, not OS friendly.
- Example: `std::atomic<T>`

[https://en.cppreference.com/w/cpp/atomic/atomic\\_flag.html](https://en.cppreference.com/w/cpp/atomic/atomic_flag.html)

*std::atomic<bool>*

```
std::atomic_flag latch;  
:  
while (latch.test_and_set(...)) {  
    // Retry? Yield? Abort?  
}
```



多插槽 CPU 互联

每个 CPU 有自己的局部 DRAM



# COMPARE-AND-SWAP


硬件提供了 TAS 和 CAS 操作指令.

Atomic instruction that compares contents of a memory location **M** to a given value **V**

→ If values are equal, installs new given value **V'** in **M**

→ Otherwise, operation fails

See C++11 Atomics




# COMPARE-AND-SWAP

Atomic instruction that compares contents of a memory location **M** to a given value **V**

→ If values are equal, installs new given value **V'** in **M**

→ Otherwise, operation fails

See [C++11 Atomics](#)




# COMPARE-AND-SWAP

Atomic instruction that compares contents of a memory location **M** to a given value **V**

→ If values are equal, installs new given value **V'** in **M**

→ Otherwise, operation fails

See C++11 Atomics




# LATCH IMPLEMENTATIONS

操作系统原语: 操作系统阻塞互斥锁.

## Approach #2: Blocking OS Mutex

- Simple to use
- Non-scalable (about 25ns per lock/unlock invocation)
- Example: `std::mutex` → `pthread_mutex_t` → `futex`  
fast user-space locking

```
std::mutex m;  
:  
m.lock();  
// Do something special...  
m.unlock();
```




# LATCH IMPLEMENTATIONS

## Approach #2: Blocking OS Mutex

- Simple to use
- Non-scalable (about 25ns per lock/unlock invocation)
- Example: `std::mutex` → `pthread_mutex_t` → `futex`

```
std::mutex m;  
:  
m.lock();  
// Do something special...  
m.unlock();
```




# LATCH IMPLEMENTATIONS

## Approach #3: Reader-Writer Latches

- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock_t`

→ `pthread_mutex_t`  
→ `pthread_cond_t`




# LATCH IMPLEMENTATIONS

## Approach #3: Reader-Writer Latches

- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock_t`

→ `pthread_mutex_t`  
→ `pthread_cond_t`




# LATCH IMPLEMENTATIONS

## Approach #3: Reader-Writer Latches

- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock_t`


  
`pthread_mutex_t`
  
`pthread_cond_t`






# LATCH IMPLEMENTATIONS

## Approach #3: Reader-Writer Latches

- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock_t`


  
`pthread_mutex_t`
  
`pthread_cond_t`




# LATCH IMPLEMENTATIONS

## Approach #3: Reader-Writer Latches

- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock_t`

 `pthread_mutex_t`  
 `pthread_cond_t`




# LATCH IMPLEMENTATIONS

## Approach #3: Reader-Writer Latches

- Allows for concurrent readers. Must manage read/write queues to avoid starvation.
- Can be implemented on top of spinlocks.
- Example: `std::shared_mutex` → `pthread_rwlock_t`

→ `pthread_mutex_t`  
→ `pthread_cond_t`



# HASH TABLE LATCHING

---

哈希表的优点: 不会发生死锁, 因为所有线程都朝相同的方向执行.

Easy to support concurrent access due to the limited ways threads access the data structure.

- All threads move in the same direction and only access a single page/slot at a time.
- Deadlocks are not possible.

To resize the table, take a global write latch on the entire table (e.g., in the header page).

# HASH TABLE LATCHING

---

Latch 的粒度: 页面锁和槽锁.


## Approach #1: Page/Block Latches

- Each page/block has its own reader-writer latch that protects its entire contents.
- Threads acquire either a read or write latch before they access a page/block.

## Approach #2: Slot Latches 锁的粒度更小.


- Each slot has its own latch.
- Can use a single-mode latch to reduce meta-data and computational overhead.

# HASH TABLE: PAGE/BLOCK LATCHES



# HASH TABLE: PAGE/BLOCK LATCHES


$T_1$ : Find D  
 $hash(D)$



  $T_2$ : Insert E  
写锁阻塞等待.  $hash(E)$


# HASH TABLE: PAGE/BLOCK LATCHES

$T_1$ : Find D  
 $hash(D)$






# HASH TABLE: PAGE/BLOCK LATCHES




# HASH TABLE: PAGE/BLOCK LATCHES

$T_1$ : Find D  
 $hash(D)$




# HASH TABLE: PAGE/BLOCK LATCHES

$T_1$ : Find D  
 $hash(D)$



# HASH TABLE: PAGE/BLOCK LATCHES

$T_1$ : Find D  
 $hash(D)$




$T_2$ : Insert E  
 $hash(E)$

# HASH TABLE: PAGE/BLOCK LATCHES

$T_1$ : Find D  
 $hash(D)$


$T_2$ : Insert E  
 $hash(E)$



# HASH TABLE: PAGE/BLOCK LATCHES


$T_1$ : Find D  
 $hash(D)$

$T_2$ : Insert E  
 $hash(E)$



# HASH TABLE: PAGE/BLOCK LATCHES


$T_1$ : Find D  
 $hash(D)$



$T_2$ : Insert E  
 $hash(E)$

# HASH TABLE: PAGE/BLOCK LATCHES

$T_1$ : Find  $D$   
 $hash(D)$




$T_2$ : Insert  $E$   
 $hash(E)$



# HASH TABLE: SLOT LATCHES


$T_1$ : Find D  
 $hash(D)$  ●



$T_2$ : Insert E  
 $hash(E)$

# HASH TABLE: SLOT LATCHES


$T_1$ : Find D  
 $hash(D)$




$T_2$ : Insert E  
 $hash(E)$

# HASH TABLE: SLOT LATCHES

$T_1$ : Find D  
 $hash(D)$




$T_2$ : Insert E  
 $hash(E)$



# HASH TABLE: SLOT LATCHES

$T_1$ : Find D  
 $hash(D)$




$T_2$ : Insert E  
 $hash(E)$

# HASH TABLE: SLOT LATCHES

$T_1$ : Find D  
 $hash(D)$

$T_2$ : Insert E  
 $hash(E)$




# HASH TABLE: SLOT LATCHES

$T_1$ : Find D

$hash(D)$

It's safe to release the latch on A




$T_2$ : Insert E  
 $hash(E)$

# HASH TABLE: SLOT LATCHES


$T_1$ : Find D  
 $hash(D)$

$T_2$ : Insert E  
 $hash(E)$



# HASH TABLE: SLOT LATCHES

$T_1$ : Find D  
 $hash(D)$




$T_2$ : Insert E  
 $hash(E)$



# HASH TABLE: SLOT LATCHES

$T_1$ : Find D  
 $hash(D)$


$T_2$ : Insert E  
 $hash(E)$



# HASH TABLE: SLOT LATCHES

$T_1$ : Find D  
 $hash(D)$


$T_2$ : Insert E  
 $hash(E)$



# HASH TABLE: SLOT LATCHES

$T_1$ : Find D  
 $hash(D)$


$T_2$ : Insert E  
 $hash(E)$



# HASH TABLE: SLOT LATCHES

$T_1$ : Find  $D$   
 $hash(D)$

$T_2$ : Insert  $E$   
 $hash(E)$



# B+TREE CONCURRENCY CONTROL


---

We want to allow multiple threads to read and update a B+Tree at the same time.


We need to protect against two types of problems:

- Threads trying to modify the contents of a node at the same time.
- One thread traversing the tree while another thread splits/merges nodes.


# B+TREE MULTI-THREADED EXAMPLE



# B+TREE MULTI-THREADED EXAMPLE




# B+TREE MULTI-THREADED EXAMPLE







# B+TREE MULTI-THREADED EXAMPLE




# B+TREE MULTI-THREADED EXAMPLE




# B+TREE MULTI-THREADED EXAMPLE




# B+TREE MULTI-THREADED EXAMPLE




# B+TREE MULTI-THREADED EXAMPLE




# B+TREE MULTI-THREADED EXAMPLE



# B+TREE MULTI-THREADED EXAMPLE



# B+TREE MULTI-THREADED EXAMPLE





# LATCH CRABBING/COUPLING

---

Protocol to allow multiple threads to access/modify B+Tree at the same time. 线程向下移动时如何获取门锁.

- Get latch for parent 1. 先获取父节点上的门锁并保持;
- Get latch for child 2. 获取导航的孩子节点的门锁;
- Release latch for parent if “safe” 3. 如果父节点是安全的, 则释放父节点上的门锁.

A **safe node** is one that will not split or merge when updated.

- Not full (on insertion)
- More than half-full (on deletion)

# LATCH CRABBING/COUPLING

---


**Find:** Start at root and traverse down the tree:

- Acquire **R** latch on child,
- Then unlatch parent.
- Repeat until we reach the leaf node.


**Insert/Delete:** Start at root and go down, obtaining **W** latches as needed. Once child is latched, check if it is safe:

- If child is safe, release all latches on ancestors


# EXAMPLE #1 - FIND 38




# EXAMPLE #1 - FIND 38




# EXAMPLE #1 - FIND 38



# EXAMPLE #1 - FIND 38




# EXAMPLE #1 - FIND 38




# EXAMPLE #1 - FIND 38

$T_1$ : Find 38







# EXAMPLE #2 - DELETE 38




# EXAMPLE #2 - DELETE 38




# EXAMPLE #2 - DELETE 38




# EXAMPLE #2 - DELETE 38




# EXAMPLE #2 - DELETE 38




# EXAMPLE #2 - DELETE 38



# EXAMPLE #2 - DELETE 38




# EXAMPLE #2 - DELETE 38







# EXAMPLE #3 - INSERT 45




# EXAMPLE #3 - INSERT 45




# EXAMPLE #3 - INSERT 45




# EXAMPLE #3 - INSERT 45




# EXAMPLE #3 - INSERT 45




# EXAMPLE #3 - INSERT 45



# EXAMPLE #3 - INSERT 45




# EXAMPLE #3 - INSERT 45







# EXAMPLE #4 - INSERT 25




# EXAMPLE #4 - INSERT 25




# EXAMPLE #4 - INSERT 25




# EXAMPLE #4 - INSERT 25




# EXAMPLE #4 - INSERT 25




# EXAMPLE #4 - INSERT 25



# EXAMPLE #4 - INSERT 25




## EXAMPLE #4 - INSERT 25






# EXAMPLE #4 - INSERT 25



# OBSERVATION

What was the first step that all the update examples did on the B+Tree?



Taking a write latch on the root every time becomes a bottleneck with higher concurrency.

# BETTER LATCHING ALGORITHM

Most modifications to a B+Tree will not require a split or merge.

Instead of assuming there will be a split/merge, optimistically traverse the tree using read latches.

If a worker guesses wrong, repeat traversal with pessimistic algorithm.

Acta Informatica 9, 1–21 (1977)



## Concurrency of Operations on B-Trees

R. Bayer\* and M. Schkolnick  
IBM Research Laboratory, San José, CA 95193, USA

**Summary.** Concurrent operations on *B*-trees pose the problem of insuring that each operation can be carried out without interfering with other operations being performed simultaneously by other users. This problem can become critical if these structures are being used to support access paths, like indexes, to data base systems. In this case, serializing access to one of these indexes can create an unacceptable bottleneck for the entire system. Thus, there is a need for locking protocols that can assure integrity for each access while at the same time providing a maximum possible degree of concurrency. Another feature required from these protocols is that they be deadlock free, since the cost to resolve a deadlock may be high.

Recently, there has been some questioning on whether *B*-tree structures can support concurrent operations. In this paper, we examine the problem of concurrent access to *B*-trees. We present a deadlock free solution which can be tuned to specific requirements. An analysis is presented which allows the selection of parameters so as to satisfy these requirements.

The solution presented here uses simple locking protocols. Thus, we conclude that *B*-trees can be used advantageously in a multi-user environment.

### 1. Introduction

In this paper, we examine the problem of concurrent access to indexes which are maintained as *B*-trees. This type of organization was introduced by Bayer and McCreight [2] and some variants of it appear in Knuth [10] and Wedekind [13]. Performance studies of it were restricted to the single user environment. Recently, these structures have been examined for possible use in a multi-user (concurrent) environment. Some initial studies have been made about the feasibility of their use in this type of situation [1, 6], and [11].

An accessing schema which achieves a high degree of concurrency in using the index will be presented. The schema allows dynamic tuning to adapt its performance to the profile of the current set of users. Another property of the

\* Permanent address: Institut für Informatik der Technischen Universität München, Arcistr. 21, D-8000 München 2, Germany (Fed. Rep.)

# BETTER LATCHING ALGORITHM

---


**Search:** Same as before.

**Insert/Delete:**


- Set latches as if for search, get to leaf, and set **W** latch on leaf.
- If leaf is not safe, release all latches, and restart thread using previous insert/delete protocol with write latches.

This approach optimistically assumes that only leaf node will be modified; if not, **R** latches set on the first pass to leaf are wasteful.


# EXAMPLE #2 - DELETE 38




# EXAMPLE #2 - DELETE 38



# EXAMPLE #2 - DELETE 38




## EXAMPLE #2 - DELETE 38







# EXAMPLE #2 - DELETE 38




# EXAMPLE #2 - DELETE 38




# EXAMPLE #2 - DELETE 38



# EXAMPLE #4 - INSERT 25



# EXAMPLE #4 - INSERT 25



# OBSERVATION


---

The threads in all the examples so far have acquired latches in a "top-down" manner.

- A thread can only acquire a latch from a node that is below its current node.
- If the desired latch is unavailable, the thread must wait until it becomes available.

But what if threads want to move from one leaf node to another leaf node?


# LEAF NODE SCAN EXAMPLE #1



$T_1$ : Find Keys  $< 4$

# LEAF NODE SCAN EXAMPLE #1


$T_1$ : Find Keys < 4






# LEAF NODE SCAN EXAMPLE #1

$T_1$ : Find Keys < 4




# LEAF NODE SCAN EXAMPLE #1

$T_1$ : Find Keys < 4




# LEAF NODE SCAN EXAMPLE #1

$T_1$ : Find Keys < 4




# LEAF NODE SCAN EXAMPLE #2



$T_1$ : Find Keys  $< 4$

$T_2$ : Find Keys  $> 1$


# LEAF NODE SCAN EXAMPLE #2



$T_1$ : Find Keys  $< 4$

$T_2$ : Find Keys  $> 1$

# LEAF NODE SCAN EXAMPLE #2




$T_1$ : Find Keys  $< 4$

$T_2$ : Find Keys  $> 1$

# LEAF NODE SCAN EXAMPLE #2

$T_1$ : Find Keys  $< 4$


$T_2$ : Find Keys  $> 1$



# LEAF NODE SCAN EXAMPLE #2


$T_1$ : Find Keys < 4

$T_2$ : Find Keys > 1







# LEAF NODE SCAN EXAMPLE #2




# LEAF NODE SCAN EXAMPLE #2



# LEAF NODE SCAN EXAMPLE #2




# LEAF NODE SCAN EXAMPLE #3



$T_1$ : Delete 4

$T_2$ : Find Keys > 1

# LEAF NODE SCAN EXAMPLE #3




$T_1$ : Delete 4

$T_2$ : Find Keys > 1


# LEAF NODE SCAN EXAMPLE #3

$T_1$ : Delete 4


$T_2$ : Find Keys > 1



# LEAF NODE SCAN EXAMPLE #3



# LEAF NODE SCAN EXAMPLE #3





# LEAF NODE SCAN EXAMPLE #3

$T_1$ : Delete 4

$T_2$ : Find Keys > 1

$T_2$  Choices?




Wait



Kill Ourselves



Kill Other Thread



# LEAF NODE SCAN EXAMPLE #3

$T_1$ : Delete 4


$T_2$ : Find Keys > 1

$T_2$  Choices?

*Wait*

☠ Kill Ourselves

*Kill Other Thread*



# LEAF NODE SCANS

---

Latches do not support deadlock detection or avoidance. The only way we can deal with this problem is through coding discipline.

The leaf node sibling latch acquisition protocol must support a “no-wait” mode.

The DBMS's data structures must cope with failed latch acquisitions.

→ Usually transparent to end-user / application.

# CONCLUSION

---

Making a data structure thread-safe is notoriously difficult in practice.

We focused on B+Trees, but the same high-level techniques are applicable to other data structures.

# NEXT CLASS

---

We are finally going to discuss how to execute some queries...


# PROJECT #2

---

You will build a thread-safe B+tree backed by your buffer pool manager.

- Page Layout
- Insert/Delete/Find Operations
- Iterator
- Latch Crabbing

We define the API for you. You need to provide the method implementations.



**WARNING:**  
**This is more difficult than Project #1.**  
**Start immediately!**

<https://15445.courses.cs.cmu.edu/fall2024/project2>

# TASKS

---

## Task #1: Page Layouts

- How each node will store its key/values in a page.
- You only need to support unique keys.

## Task #2: Operations

- Support point queries (single key).
- Support inserts with node splitting.
- Support removal of keys with sibling stealing + merging.
- Does not need to be thread-safe.

# TASKS

---

## Task #3: Index Iterator

- Create a STL iterator for range scans on leaf nodes.
- You only need to support ascending scans.

## Task #4: Concurrent Index

- Introduce latch crabbing/coupling protocol to support safe concurrent operations.
- Make sure you have splits / merges working correctly before proceeding with this task.



# DEVELOPMENT HINTS

---

Follow the textbook semantics and algorithms.

Set the page size to be small (e.g., 512B) when you first start so that you can see more splits/merges.

Make sure that you protect the internal B+Tree **root\_page\_id** member.

# EXTRA CREDIT

---

Gradescope Leaderboard runs your code with a specialized in-memory version of BusTub.

The top 20 fastest implementations in the class will receive extra credit for this assignment.

- **#1**: 50% bonus points
- **#2–10**: 25% bonus points
- **#11–20**: 10% bonus points

You must pass all the test cases to qualify!



# PLAGIARISM WARNING

---



The homework and projects must be your own original work. They are **not** group assignments.

You may **not** copy source code from other people or the web.

Plagiarism is **not** tolerated. You will get lit up.  
→ Please ask me if you are unsure.

See [CMU's Policy on Academic Integrity](#) for additional information.